

INTERVAL ABSTRACT DOMAIN

- $I = \{[a, b] \mid a, b \in \mathbb{R} \cup \{-\infty, \infty\}\} \cup \{\perp\}$
 - $D = V \rightarrow I$
 - Also called Box abstract domain.
- $[a_1, b_1] \sqsubseteq [a_2, b_2] \Leftrightarrow a_2 \leq a_1 \wedge b_1 \leq b_2, \forall d \in I. \perp \sqsubseteq d$
 - Is (I, \sqsubseteq) a lattice?
 - Is (I, \sqsubseteq) a complete lattice?
 - Maximal element?
- $[a_1, b_1] \sqcup [a_2, b_2] = ???$

INTERVAL ABSTRACT DOMAIN

- $I = \{[a, b] \mid a, b \in \mathbb{R} \cup \{-\infty, \infty\}\} \cup \{\perp\}$
 - $D = V \rightarrow I$
 - Also called Box abstract domain.
- $[a_1, b_1] \sqsubseteq [a_2, b_2] \Leftrightarrow a_2 \leq a_1 \wedge b_1 \leq b_2, \forall d \in I. \perp \sqsubseteq d$
 - Is (I, \sqsubseteq) a lattice?
 - Is (I, \sqsubseteq) a complete lattice?
 - Maximal element?
- $[a_1, b_1] \sqcup [a_2, b_2] = [\min(a_1, a_2), \max(b_1, b_2)]$

INTERVAL ABSTRACT DOMAIN

- $I = \{[a, b] \mid a, b \in \mathbb{R} \cup \{-\infty, \infty\}\} \cup \{\perp\}$
 - $D = V \rightarrow I$
 - Also called Box abstract domain.
- $[a_1, b_1] \sqsubseteq [a_2, b_2] \Leftrightarrow a_2 \leq a_1 \wedge b_1 \leq b_2, \forall d \in I. \perp \sqsubseteq d$
 - Is (I, \sqsubseteq) a lattice?
 - Is (I, \sqsubseteq) a complete lattice?
 - Maximal element?
- $[a_1, b_1] \sqcup [a_2, b_2] = [\min(a_1, a_2), \max(b_1, b_2)]$
- $(D, \sqsubseteq): \forall d_1, d_2 \in D. d_1 \sqsubseteq d_2 \Leftrightarrow \forall v \in V. d_1(v) \sqsubseteq d_2(v)$

INTERVAL ABSTRACT DOMAIN

ABSTRACTION AND CONCRETIZATION FUNCTION

- $\alpha : \mathbb{P}(\text{State}) \rightarrow D, \gamma : D \rightarrow \mathbb{P}(\text{State})$
- $\alpha(c) = d$
 - $d(v) = [\min\{\sigma(v) \mid \sigma \in c\}, \max\{\sigma(v) \mid \sigma \in c\}]$
- $\gamma(d) = \{\sigma \mid \forall v \in V. d(v) = [a, b] \Rightarrow a \leq \sigma(v) \leq b\}$
- Is $(\mathbb{P}(\text{State}), \subseteq) \overset{\alpha}{\underset{\gamma}{\rightleftarrows}} (D, \sqsubseteq)$ a Galois Connection?
 - Is it an Onto Galois Connection?


INTERVAL ABSTRACT DOMAIN

ABSTRACT TRANSFER FUNCTION

- Consider $c : x := x + y$
 - We can use interval arithmetic for \hat{f}_c
- Assuming $d(x) = [l_x, u_x], d(y) = [l_y, u_y]$
 - $\hat{f}_c(d) = d[x \mapsto [l_x + l_y, u_x + u_y]]$
- Is \hat{f}_c monotonic?
 - Is it distributive?

USING INTERVAL DOMAIN


```
i := 0;  
while(i < n) do  
  i := i + 1;
```



Interval Abstract Domain does not satisfy ACC, hence
Kildall's Algorithm may not terminate

USING INTERVAL DOMAIN

```
i := 0;  
while(i < n) do  
  i := i + 1;
```



Interval Abstract Domain does not satisfy ACC, hence
Kildall's Algorithm may not terminate

WIDENING

- A widening function $\nabla : D \times D \rightarrow D$ on a poset (D, \leq) satisfies the following properties:
 - $\forall x, y \in D. x \sqcup y \leq x \nabla y$
 - For an increasing chain x_0, x_1, \dots , the increasing chain y_0, y_1, \dots where $y_0 = x_0$ and $y_n = y_{n-1} \nabla x_n$ eventually stabilizes.

WIDENING FOR THE INTERVAL DOMAIN

- We can define the widening operator for interval domain as follows:
 - $[a, b] \nabla \perp = [a, b]$
 - $\perp \nabla [a, b] = [a, b]$
 - $[a_1, b_1] \nabla [a_2, b_2] = [(a_2 < a_1)? -\infty : a_1, (b_1 < b_2)? \infty : b_1]$
- Examples
 - $[1, 2] \nabla [0, 2] = ???$

WIDENING FOR THE INTERVAL DOMAIN

- We can define the widening operator for interval domain as follows:
 - $[a, b] \nabla \perp = [a, b]$
 - $\perp \nabla [a, b] = [a, b]$
 - $[a_1, b_1] \nabla [a_2, b_2] = [(a_2 < a_1)? -\infty : a_1, (b_1 < b_2)? \infty : b_1]$
- Examples
 - $[1, 2] \nabla [0, 2] = [-\infty, 2]$

WIDENING FOR THE INTERVAL DOMAIN

- We can define the widening operator for interval domain as follows:
 - $[a, b] \nabla \perp = [a, b]$
 - $\perp \nabla [a, b] = [a, b]$
 - $[a_1, b_1] \nabla [a_2, b_2] = [(a_2 < a_1)? -\infty : a_1, (b_1 < b_2)? \infty : b_1]$
- Examples
 - $[1, 2] \nabla [0, 2] = [-\infty, 2]$
 - $[0, 2] \nabla [1, 2] = ???$

WIDENING FOR THE INTERVAL DOMAIN

- We can define the widening operator for interval domain as follows:
 - $[a, b] \nabla \perp = [a, b]$
 - $\perp \nabla [a, b] = [a, b]$
 - $[a_1, b_1] \nabla [a_2, b_2] = [(a_2 < a_1)? -\infty : a_1, (b_1 < b_2)? \infty : b_1]$
- Examples
 - $[1, 2] \nabla [0, 2] = [-\infty, 2]$
 - $[0, 2] \nabla [1, 2] = [0, 2]$

WIDENING FOR THE INTERVAL DOMAIN

- We can define the widening operator for interval domain as follows:
 - $[a, b] \nabla \perp = [a, b]$
 - $\perp \nabla [a, b] = [a, b]$
 - $[a_1, b_1] \nabla [a_2, b_2] = [(a_2 < a_1)? -\infty : a_1, (b_1 < b_2)? \infty : b_1]$
- Examples
 - $[1, 2] \nabla [0, 2] = [-\infty, 2]$
 - $[0, 2] \nabla [1, 2] = [0, 2]$
 - $[2, 3] \nabla [4, 6] = ???$

WIDENING FOR THE INTERVAL DOMAIN

- We can define the widening operator for interval domain as follows:
 - $[a, b] \nabla \perp = [a, b]$
 - $\perp \nabla [a, b] = [a, b]$
 - $[a_1, b_1] \nabla [a_2, b_2] = [(a_2 < a_1)? -\infty : a_1, (b_1 < b_2)? \infty : b_1]$
- Examples
 - $[1, 2] \nabla [0, 2] = [-\infty, 2]$
 - $[0, 2] \nabla [1, 2] = [0, 2]$
 - $[2, 3] \nabla [4, 6] = [2, \infty]$


KILDALL'S ALGORITHM WITH WIDENING

AbstractForwardPropagate(Γ_c, P)

```
S := {l0};  
 $\hat{\mu}_K(l_0) := \alpha(P)$ ;  
 $\hat{\mu}_K(l) := \perp$ , for  $l \in L \setminus \{l_0\}$ ;  
while S  $\neq \emptyset$  do{  
    l := Choose S;  
    S := S \ {l};  
    foreach (l, c, l')  $\in T$  do{  
        F :=  $\hat{f}_c(\hat{\mu}_K(l))$ ;  
        if  $\neg(F \leq \hat{\mu}_K(l'))$  then{  
             $\hat{\mu}_K(l') := \hat{\mu}_K(l') \nabla F$ ;  
            S := S  $\cup \{l'\}$ ;  
        }  
    }  
}
```


WIDENING EXAMPLE

```
i := 0;  
while(i < n) do  
  i := i + 1;
```



WIDENING EXAMPLE

```
i := 0;  
while(i < n) do  
  i := i + 1;
```

