

ABSTRACT FORWARD PROPAGATE

KILDALL'S ALGORITHM

AbstractForwardPropagate(Γ_c, P)

```
S := {l0};  
 $\hat{\mu}(l_0) := \alpha(P)$ ;  
 $\hat{\mu}(l) := \perp$ , for  $l \in L \setminus \{l_0\}$ ;  
while S  $\neq \emptyset$  do{  
    l := Choose S;  
    S := S \ {l};  
    foreach (l, c, l')  $\in T$  do{  
        F :=  $\hat{sp}(\hat{\mu}(l), c)$ ;  
        if  $\neg(F \leq \hat{\mu}(l'))$  then{  
             $\hat{\mu}(l') := \hat{\mu}(l') \sqcup F$ ;  
            S := S  $\cup \{l'\}$ ;  
        }  
    }  
}
```

- Does this algorithm actually calculate the abstract JOP?
- What are the conditions under which it is guaranteed to terminate?


ABSTRACT FORWARD PROPAGATE

KILDALL'S ALGORITHM


AbstractForwardPropagate(Γ_c, P)

```
S := {l0};  
 $\hat{\mu}_K(l_0) := \alpha(P)$ ;  
 $\hat{\mu}_K(l) := \perp$ , for  $l \in L \setminus \{l_0\}$ ;  
while S  $\neq \emptyset$  do{  
    l := Choose S;  
    S := S \ {l};  
    foreach (l, c, l')  $\in T$  do{  
        F :=  $\hat{f}_c(\hat{\mu}_K(l))$ ;  
        if  $\neg(F \leq \hat{\mu}_K(l'))$  then{  
             $\hat{\mu}_K(l') := \hat{\mu}_K(l') \sqcup F$ ;  
            S := S  $\cup \{l'\}$ ;  
        }  
    }  
}
```



EXAMPLE - KILDALL'S ALGORITHM




EXAMPLE - KILDALL'S ALGORITHM




EXAMPLE - ABSTRACT JOP



EXAMPLE - ABSTRACT JOP



EXAMPLE - KILDALL VS ABSTRACT JOP



$\hat{\mu}_K \neq \hat{\mu}$: This is because Kildall's Algorithm applies join eagerly
 We will prove that $\hat{\mu}_K \geq \hat{\mu}$


PROPERTIES OF KILDALL'S ALGORITHM

1. The values computed using Kildall's algorithm are an over-approximation of the abstract JOP, if the underlying AI framework is monotonic.
2. In general, Kildall's algorithm computes the least solution to a system of equations.
3. If the abstract domain satisfies the ascending chain condition, then Kildall's algorithm is guaranteed to terminate.

DATAFLOW EQUATIONS

- Program $\Gamma_c = (V, L, l_0, l_e, T)$ induces a system of data flow equations:
 - $X_{l_0} = d_0$
 - For all other locations $l \in L \setminus \{l_0\}$, $X_l = \bigsqcup_{(l', c, l) \in T} \hat{f}_c(X_{l'})$
- For collecting semantics, replace d_0 with c_0 , \sqcup with \cup and \hat{f}_c with f_c .

EXAMPLE - DATAFLOW EQUATIONS



$$X_{l_0} = d_0$$

$$X_{l_1} = \hat{f}_{p_1}(X_{l_0}) \sqcup \hat{f}_{p_3}(X_{l_2})$$


$$X_{l_2} = \hat{f}_{p_2}(X_{l_1})$$

DATAFLOW EQUATIONS AS FUNCTION

- Consider the 'vectorised' lattice $(\bar{D}, \bar{\leq})$, where $\bar{D} = D^{|L|}$.
 - $\bar{d} \bar{\leq} \bar{d}' \Leftrightarrow \forall l \in L. \bar{d}(l) \leq \bar{d}'(l)$
 - **Homework:** Prove that if (D, \leq) is a complete lattice, then $(\bar{D}, \bar{\leq})$ is also a complete lattice.
- We can view the data flow equations as a function $\bar{f}: \bar{D} \rightarrow \bar{D}$:
 - $(\bar{f}(\bar{d}))(l_0) = d_0$
 - $(\bar{f}(\bar{d}))(l) = \bigsqcup_{(l', c, l) \in T} \hat{f}_c(\bar{d}(l'))$

DATAFLOW EQUATIONS AS FUNCTION

EXAMPLE



Notice that a
fixpoint of \bar{f} is a
solution to the
dataflow equations


$$\bar{f}(d_{l_0}, d_{l_1}, d_{l_2}) = (d_0, \hat{f}_{p_1}(d_{l_0}) \sqcup \hat{f}_{p_3}(d_{l_2}), \hat{f}_{p_2}(d_{l_1}))$$

DATAFLOW EQUATIONS AS FUNCTION

- If every abstract transfer function $\hat{f}: D \rightarrow D$ is monotonic, then the function $\bar{f}: \bar{D} \rightarrow \bar{D}$ is also monotonic.
 - **Homework:** Prove this.
- We have a monotonic function \bar{f} on a complete lattice \bar{D} . Hence, we can apply Knaster-Tarski fixpoint theorem.
- The least fixpoint $lfp(\bar{f})$ exists, and is in fact the least solution to the dataflow equations.
- We will show that Kildall's algorithm actually computes $lfp(\bar{f})$.
- Note that we can also use the sequence $\perp, \bar{f}(\perp), \bar{f}^2(\perp), \dots$ to compute $lfp(\bar{f})$.
 - This method is also called Kleene Iteration.

LFP INTRODUCES THE LEAST OVER APPROXIMATION: EXAMPLE

```
i := 0;  
while(i < n) do  
  i := i + 1;
```



$(+ -, +, +, +)$ is a solution to the data flow equations,
And $(+ -, + -, + -, + -)$ is also another solution

ABSTRACT JOP $\leq lfp(\bar{f})$ FOR MONOTONIC AI FRAMEWORK

PROOF

- Given AI $(D, \leq, \alpha, \gamma, \hat{F}_D)$, if all functions in \hat{F}_D are monotonic, then Abstract JOP $\leq lfp(\bar{f})$.

Proof: Abstract JOP $\hat{\mu}(l) = \bigsqcup_{\pi \in \Pi_l} \hat{f}_\pi(d_0)$

Let $lfp(\bar{f}) = \bar{d}$. We have to show that $\forall l \in L. \hat{\mu}(l) \leq \bar{d}(l)$.

We will show that for all locations l , all paths $\pi \in \Pi_l$, $\hat{f}_\pi(d_0) \leq \bar{d}(l)$.

This proves the required result. Why?

We will use induction on length of the paths.

Base Case: Paths π of length 0 are empty and end at l_0 . Hence, $\hat{f}_\pi(d_0) = d_0$.

Since $\bar{f}(\bar{d}) = \bar{d}$ and $(\bar{f}(\bar{d}))(l_0) = d_0$, we have $\bar{d}(l_0) = d_0$.


Thus, $\hat{f}_\pi(d_0) \leq \bar{d}(l_0)$

ABSTRACT JOP $\leq lfp(\bar{f})$ FOR MONOTONIC AI FRAMEWORK

PROOF

Inductive Case: Assume that the claim holds for all paths of length n .

Consider a path π of length $n + 1$ ending at location l .



ABSTRACT JOP $\leq lfp(\bar{f})$ FOR MONOTONIC AI FRAMEWORK

PROOF

Inductive Case: Assume that the claim holds for all paths of length n .

Consider a path π of length $n + 1$ ending at location l .

Let π' be the prefix of the path of length n , ending at location l' .


By Inductive Hypothesis, $\hat{f}_{\pi'}(d_0) \leq \bar{d}(l')$.

Since \hat{f}_p is monotonic, $\hat{f}_p(\hat{f}_{\pi'}(d_0)) \leq \hat{f}_p(\bar{d}(l'))$.


Hence, $\hat{f}_{\pi}(d_0) \leq \hat{f}_p(\bar{d}(l'))$.

Now $\bar{f}(\bar{d}) = \bar{d}$. Hence, $\bar{d}(l) = \bigsqcup_{(l',p,l) \in T} \hat{f}_p(\bar{d}(l'))$.

Hence, $\hat{f}_p(\bar{d}(l')) \leq \bar{d}(l)$. Thus, $\hat{f}_{\pi}(d_0) \leq \bar{d}(l)$.



EXAMPLE - LFP VS ABSTRACT JOP



$$\bar{f}(d_{l_0}, d_{l_1}, d_{l_2}) = (d_0, \hat{f}_{p_1}(d_{l_0}) \sqcup \hat{f}_{p_3}(d_{l_2}), \hat{f}_{p_2}(d_{l_1}))$$

DISTRIBUTIVE AND INFINITELY DISTRIBUTIVE FUNCTIONS

- Given two posets (D_1, \leq_1) and (D_2, \leq_2) , function $f: D_1 \rightarrow D_2$ is called distributive if for $x, y \in D_1$ such that $x \sqcup_1 y$ exists, then $f(x) \sqcup_2 f(y)$ also exists, and $f(x \sqcup_1 y) = f(x) \sqcup_2 f(y)$.
- Given two posets (D_1, \leq_1) and (D_2, \leq_2) , function $f: D_1 \rightarrow D_2$ is called infinitely distributive if for all $X \subseteq D_1$ such that $\sqcup_1 X$ exists, then $\sqcup_2 f(X)$ also exists, and $\sqcup_2 f(X) = f(\sqcup_1 X)$.
- **Exercise:** If f is distributive, then f is also monotonic.

ABSTRACT JOP = $lfp(\bar{f})$ FOR INFINITELY DISTRIBUTIVE AI FRAMEWORK

PROOF

- Given AI $(D, \leq, \alpha, \gamma, \hat{F}_D)$, if all functions in \hat{F}_D are infinitely distributive, then Abstract JOP = $lfp(\bar{f})$.

Proof: We will show that Abstract JOP $(\hat{\mu})$ is a fixpoint of \bar{f} . This is sufficient to prove the result. Why?

ABSTRACT JOP = $lfp(\bar{f})$ FOR INFINITELY DISTRIBUTIVE AI FRAMEWORK

PROOF

- Given AI $(D, \leq, \alpha, \gamma, \hat{F}_D)$, if all functions in \hat{F}_D are infinitely distributive, then Abstract JOP = $lfp(\bar{f})$.

Proof: We will show that Abstract JOP $(\hat{\mu})$ is a fixpoint of \bar{f} . This is sufficient to prove the result. Why?

$$\begin{aligned}(\bar{f}(\hat{\mu}))(l) &= \bigsqcup_{(l',p,l) \in T} \hat{f}_p(\hat{\mu}(l')) \\&= \bigsqcup_{(l',p,l) \in T} \hat{f}_p(\bigsqcup_{\pi \in \Pi_{l'}} \hat{f}_\pi(d_0)) \\&= \bigsqcup_{(l',p,l) \in T} \bigsqcup_{\pi \in \Pi_{l'}} \hat{f}_p \circ \hat{f}_\pi(d_0)\end{aligned}$$

ABSTRACT JOP = $lfp(\bar{f})$ FOR INFINITELY DISTRIBUTIVE AI FRAMEWORK

PROOF

$$(\bar{f}(\hat{\mu}))(l) = \bigsqcup_{(l',p,l) \in T} \bigsqcup_{\pi \in \Pi_{l'}} \hat{f}_p \circ \hat{f}_\pi(d_0)$$

And we know that $\hat{\mu}(l) = \bigsqcup_{\pi' \in \Pi_l} \hat{f}_{\pi'}(d_0)$.

Then, due to associativity of \sqcup , $(\bar{f}(\hat{\mu}))(l) = \hat{\mu}(l)$.

Thus, $\hat{\mu}$ is a fixpoint of \bar{f} . We know from previous result that $\hat{\mu} \leq lfp(\bar{f})$. Thus, $\hat{\mu} = lfp(\bar{f})$.

RECALL: SIGN ABSTRACT DOMAIN

- The abstract transfer functions in sign abstract domain are monotonic, but not infinitely distributive.

Consider $p : j := i * k$ and $d_1 = (+ , + - , +)$, $d_2 = (- , + - , -)$.

Then, $\hat{f}_p(d_1 \sqcup d_2) = ???$

RECALL: SIGN ABSTRACT DOMAIN

- The abstract transfer functions in sign abstract domain are monotonic, but not infinitely distributive.

Consider $p : j := i * k$ and $d_1 = (+ , + - , +)$, $d_2 = (- , + - , -)$.

Then, $\hat{f}_p(d_1 \sqcup d_2) = (+ - , + - , + -)$.

RECALL: SIGN ABSTRACT DOMAIN

- The abstract transfer functions in sign abstract domain are monotonic, but not infinitely distributive.

Consider $p : j := i * k$ and $d_1 = (+ , + - , +)$, $d_2 = (- , + - , -)$.

Then, $\hat{f}_p(d_1 \sqcup d_2) = (+ - , + - , + -)$.

$\hat{f}_p(d_1) \sqcup \hat{f}_p(d_2) = ???$

RECALL: SIGN ABSTRACT DOMAIN

- The abstract transfer functions in sign abstract domain are monotonic, but not infinitely distributive.

Consider $p : j := i * k$ and $d_1 = (+, +-, +)$, $d_2 = (-, +-, -)$.

Then, $\hat{f}_p(d_1 \sqcup d_2) = (+-, +-, +-)$.

$$\hat{f}_p(d_1) \sqcup \hat{f}_p(d_2) = (+, +, +) \sqcup (-, +, -) = (+-, +, +-)$$

RECALL: SIGN ABSTRACT DOMAIN

- The abstract transfer functions in sign abstract domain are monotonic, but not infinitely distributive.


Consider $p : j := i * k$ and $d_1 = (+, +-, +)$, $d_2 = (-, +-, -)$.

Then, $\hat{f}_p(d_1 \sqcup d_2) = (+-, +-, +-)$.

$$\hat{f}_p(d_1) \sqcup \hat{f}_p(d_2) = (+, +, +) \sqcup (-, +, -) = (+-, +, +-)$$


- The concrete transfer functions are always infinitely distributive. Hence, the concrete JOP is the least solution of the concrete data-flow equations.

BIG PICTURE



For Monotonic AI Framework

BIG PICTURE



For Infinitely Distributive AI Framework

KILDALL'S ALGORITHM COMPUTES $lfp(\bar{f})$

PROOF

- First, we will show that $\hat{\mu}_K \leq lfp(\bar{f})$

We will show that $\hat{\mu}_K \leq lfp(\bar{f})$ is a loop invariant of the outer while loop.

At the beginning, $\hat{\mu}_K(l_0) = \alpha(P) \leq d_0$.

Hence, $\forall l. \hat{\mu}_K(l) \leq (lfp(\bar{f}))(l)$.

Assuming that the claim holds at the beginning of some iteration, let $\hat{\mu}_K = \bar{d}$, $lfp(\bar{f}) = \bar{g}$. We have $\bar{d} \leq \bar{g}$.

AbstractForwardPropagate(Γ_c, P)

```
S := {l0};  
 $\hat{\mu}_K(l_0) := \alpha(P)$ ;  
 $\hat{\mu}_K(l) := \perp$ , for  $l \in L \setminus \{l_0\}$ ;  
while S  $\neq \emptyset$  do{  
    l := Choose S;  
    S := S \ {l};  
    foreach (l, c, l')  $\in T$  do{  
        F :=  $\hat{f}_c(\hat{\mu}_K(l))$ ;  
        if  $\neg(F \leq \hat{\mu}_K(l'))$  then{  
             $\hat{\mu}_K(l') := \hat{\mu}_K(l') \sqcup F$ ;  
            S := S  $\cup \{l'\}$ ;  
        }  
    }  
}
```


KILDALL'S ALGORITHM COMPUTES $lfp(\bar{f})$

PROOF

```
AbstractForwardPropagate( $\Gamma_c, P$ )  
   $S := \{l_0\};$   
   $\hat{\mu}_K(l_0) := \alpha(P);$   
   $\hat{\mu}_K(l) := \perp, \text{ for } l \in L \setminus \{l_0\};$   
  while  $S \neq \emptyset$  do{  
     $l := \text{Choose } S;$   
     $S := S \setminus \{l\};$   
    foreach  $(l, c, l') \in T$  do{  
       $F := \hat{f}_c(\hat{\mu}_K(l));$   
      if  $\neg(F \leq \hat{\mu}_K(l'))$  then{  
         $\hat{\mu}_K(l') := \hat{\mu}_K(l') \sqcup F;$   
         $S := S \cup \{l'\};$   
      }  
    }  
  }
```


KILDALL'S ALGORITHM COMPUTES $lfp(\bar{f})$

PROOF

For some successor l' of l ,
 $\hat{\mu}_K(l') = d(l') \sqcup \hat{f}_c(d(l))$.

Now, $\bar{d}(l) \leq \bar{g}(l) \Rightarrow \hat{f}_c(\bar{d}(l)) \leq \hat{f}_c(\bar{g}(l))$.

Further, $\bar{g}(l') = \bigsqcup_{(l,c,l') \in T} \hat{f}_c(\bar{g}(l))$

Hence, $\bar{g}(l') \geq \hat{f}_c(\bar{g}(l)) \geq \hat{f}_c(\bar{d}(l))$

We also know that $\bar{g}(l') \geq \bar{d}(l')$.

Thus, $\bar{g}(l') \geq \bar{d}(l') \sqcup \hat{f}_c(\bar{d}(l))$.

Hence, $\bar{g}(l') \geq \hat{\mu}_K(l')$.

AbstractForwardPropagate(Γ_c, P)

$S := \{l_0\};$

$\hat{\mu}_K(l_0) := \alpha(P);$

$\hat{\mu}_K(l) := \perp$, for $l \in L \setminus \{l_0\};$

while $S \neq \emptyset$ do{

$l := \text{Choose } S;$

$S := S \setminus \{l\};$

 foreach $(l, c, l') \in T$ do{

$F := \hat{f}_c(\hat{\mu}_K(l));$

 if $\neg(F \leq \hat{\mu}_K(l'))$ then{

$\hat{\mu}_K(l') := \hat{\mu}_K(l') \sqcup F;$

$S := S \cup \{l'\};$

 }

 }

}