

MODEL CHECKING

- Exhaustive exploration of the state-space of a program.
 - If an error state is not reached, then model checking outputs safe.
 - If an error state is reached, then the path to the error state can be reconstructed, resulting in a **counterexample**.
- Model Checking for sequential programs comes in many variants:
 - Concrete Model Checking
 - Symbolic Model Checking
 - Bounded Model Checking
 - Abstract Model Checking

CONCRETE MODEL CHECKING

```
ConcreteModelChecking( $\Gamma_c, P$ )  
  worklist :=  $\{(l_0, \sigma) \mid \sigma \in P\}$ ;  
  reach :=  $\emptyset$ ;  
  while worklist  $\neq \emptyset$  do{  
    Choose  $(l, \sigma) \in$  worklist;  
    worklist := worklist  $\setminus \{(l, \sigma)\}$ ;  
    if  $((l, \sigma) \notin$  reach) then  
    {  
      reach := reach  $\cup \{(l, \sigma)\}$ ;  
      foreach  $((l, c, l') \in T)$   
        worklist := worklist  $\cup \{(l', \sigma') \mid \sigma' \in sp(\{\sigma\}, c)\}$ ;  
    }  
  }  
  if  $((l_{err}, \_) \in$  reach) then  
    return UNSAFE  
  else  
    return SAFE
```


CONCRETE MODEL CHECKING

WITH COUNTEREXAMPLE GENERATION

```
ConcreteModelChecking( $\Gamma_c, P$ )  
  worklist :=  $\{(l_0, \sigma) \mid \sigma \in P\}$ ; parents :=  $\lambda x. NR$ ;  
  reach :=  $\emptyset$ ;  
  while worklist  $\neq \emptyset$  do{  
    Choose  $(l, \sigma) \in \text{worklist}$ ;  
    worklist := worklist  $\setminus \{(l, \sigma)\}$ ;  
    if  $((l, \sigma) \notin \text{reach})$  then  
    {  
      reach := reach  $\cup \{(l, \sigma)\}$ ;  
      foreach  $((l, c, l') \in T \wedge (l', \sigma') \in sp(\{\sigma\}, c))$  {  
        worklist := worklist  $\cup \{(l', \sigma')\}$ ;  
        parents $((l', \sigma')) := (l, \sigma)$ ;  
      }  
    }  
  }  
  if  $((l_{err}, \_) \in \text{reach})$  then  
    return UNSAFE  
  else  
    return SAFE
```


SYMBOLIC MODEL CHECKING

```
SymbolicModelChecking( $\Gamma_c, P$ )
  worklist :=  $\{(l_0, P)\}$ ;
  reach( $l_0$ ) :=  $P$ ;
  foreach ( $l \in L \setminus \{l_0\}$ ) reach( $l$ ) := false;
  while worklist  $\neq \emptyset$  do{
    Choose  $(l, F) \in$  worklist;
    worklist := worklist  $\setminus \{(l, F)\}$ ;
    if (reach( $l$ )  $\not\Rightarrow F$ ) then
    {
      reach( $l$ ) := reach( $l$ )  $\vee F$ ;
      foreach  $((l, c, l') \in T)$ 
        worklist := worklist  $\cup \{(l', sp(F, c))\}$ ;
    }
  }
  if (reach( $l_{err}$ )  $\neq false$ ) then
    return UNSAFE
  else
    return SAFE
```


BOUNDED MODEL CHECKING

- Concrete/Symbolic model checking for a finite number of steps
 - Unroll loops in the program for a fixed number of iterations, and then do concrete/symbolic model checking on the resultant program.
- Alternatively, we can apply Static Single Assignment (SSA) transformation on the unrolled program, and directly encode the BMC problem in FOL.

ABSTRACT MODEL CHECKING

- All the previous approaches to model checking have severe limitations:
 - Concrete and Symbolic Model Checking may not terminate and are in general computationally expensive.
 - Bounded Model Checking can only be used to find bugs, and not for verification.
- Let's bring back abstraction!
 - Consider a sound Abstract Interpretation framework $(D, \leq, \alpha, \gamma, \hat{F})$.

ABSTRACT MODEL CHECKING

```
AbstractModelChecking( $\Gamma_c, P$ )  
  worklist :=  $\{(l_0, \alpha(P))\}$ ;  
  reach :=  $\emptyset$ ;  
  while worklist  $\neq \emptyset$  do{  
    Choose  $(l, d) \in \text{worklist}$ ;  
    worklist := worklist  $\setminus \{(l, d)\}$ ;  
    if (  $\exists (l, d') \in \text{reach}. d \leq d'$  ) then  
    {  
      reach := reach  $\cup \{(l, d)\}$ ;  
      foreach  $((l, c, l') \in T)$   
        worklist := worklist  $\cup \{(l', d') \mid d' = \hat{f}_c(d)\}$ ;  
    }  
  }  
  if  $((l_{err}, d) \in \text{reach} \wedge d \neq \perp)$  then  
    return UNSAFE  
  else  
    return SAFE
```


ABSTRACT MODEL CHECKING

WITH COUNTEREXAMPLE GENERATION

```
AbstractModelChecking( $\Gamma_c, P$ )
  worklist :=  $\{(l_0, \alpha(P))\}$ ; parents :=  $\lambda x. NR$ ;
  reach :=  $\emptyset$ ;
  while worklist  $\neq \emptyset$  do{
    Choose  $(l, d) \in \text{worklist}$ ;
    worklist := worklist  $\setminus \{(l, d)\}$ ;
    if (  $\exists (l, d') \in \text{reach}. d \leq d'$  ) then
    {
      reach := reach  $\cup \{(l, d)\}$ ;
      foreach  $((l, c, l') \in T)$  {
        worklist := worklist  $\cup \{(l', \hat{f}_c(d))\}$ ;
        parents( $(l', \hat{f}_c(d))$ ) :=  $(l, d)$ ;
      }
    }
  }
  if  $((l_{err}, d) \in \text{reach} \wedge d \neq \perp)$  then
    return UNSAFE
  else
    return SAFE
```


PREDICATE ABSTRACTION

- The predicate abstraction domain is parameterized by a fixed, finite set of predicates P .
 - Each predicate is a formula over the program variables.
 - Example: $P = \{x \leq 1, y = 0, x + y \leq -1\}$
- There are two predicate abstraction domains:
 - Boolean Predicate Abstraction
 - Cartesian Predicate Abstraction

CARTESIAN PREDICATE ABSTRACTION

- The abstract domain is $\mathbb{P}(P) \cup \{ \perp \}$
- The partial order relation \sqsubseteq is defined as follows:
 - $\forall s \in \mathbb{P}(P) . \perp \sqsubseteq s$
 - $\forall s_1, s_2 \in \mathbb{P}(P) . s_1 \sqsubseteq s_2 \Leftrightarrow s_1 \supseteq s_2$
- Top element is \emptyset , bottom element is \perp
- Example: $P = \{x \leq 1, y = 0, x + y \leq -1\}$. Which of the following are true?
 - $\{x \leq 1\} \sqsubseteq \{x \leq 1, x + y \leq -1\}$
 - $\{x + y \leq -1, y = 0\} \sqsubseteq \{y = 0\}$
 - $\{x \leq 1\} \sqsubseteq \emptyset$

CARTESIAN PREDICATE ABSTRACTION

- Abstraction function:

$$\forall c \in \mathbb{P}(\text{State}). c \neq \emptyset \Rightarrow \alpha(c) = \{p \in P \mid \forall \sigma \in c. \sigma \models p\}$$

- $\alpha(\emptyset) = \perp$

- Concretization function: $\forall s \in \mathbb{P}(P). \gamma(s) = \{\sigma \mid \sigma \models \bigwedge_{p \in s} p\}$

- $\gamma(\perp) = \emptyset$

- Examples $P = \{x \leq 1, y = 0, x + y \leq -1\}$

- $\alpha(\{(0,0)\}) = \{x \leq 1, y = 0\}$

- $\alpha(\{(0,0), (-1, -1)\}) = \{x \leq 1, x + y \leq -1\}$

- $\alpha(x \leq 0) = \{x \leq 1\}$