

Linux Commands – Part 1

1. `ip` – from Iproute2, a collection of utilities for controlling TCP/IP networking and traffic control in Linux.
2. `ls` – list directory contents.
3. `df` – display disk space usage.
4. `du` – estimate file space usage.
5. `free` – display memory usage.
6. `scp` – securely Copy Files Using SCP, with examples.
7. `find` – locates files based on some user-specified criteria.
8. `ncdu` – a disk utility for Unix systems.
9. `pstree` – display a tree of processes.
10. `last` – show a listing of last logged-in users.
11. `w` – show a list of currently logged-in user sessions.
12. `grep` – Search a file for a pattern of characters, then display all matching lines.

Linux Commands – Part 2

13. `uptime` – shows system uptime and load average.
14. `top` – shows an overall system view.
15. `vmstat` – shows system memory, processes, interrupts, paging, block I/O, and CPU info.
16. `htop` – interactive process viewer and manager.
17. `dstat` – view processes, memory, paging, I/O, CPU, etc., in real-time. All-in-one for `vmstat`, `iostat`, `netstat`, and `ifstat`.
18. `iftop` – network traffic viewer.
19. `nethogs` – network traffic analyzer.
20. `iotop` – interactive I/O viewer. Get an overview of storage r/w activity.
21. `iostat` – for storage I/O statistics.
22. `netstat` – for network statistics.
23. `ss` – utility to investigate sockets.
24. `atop` – For Linux server performance analysis.
25. `Glances` and `nmon` – `htop` and `top` Alternatives:
26. `ssh` – secure command-line access to remote Linux systems.
27. `sudo` – execute commands with administrative privilege.
28. `cd` – directory navigation.
29. `pwd` – shows your current directory location.
30. `cp` – copying files and folders.
31. `mv` – moving files and folders.
32. `rm` – removing files and folders.
33. `mkdir` – create or make new directories.

Linux Commands – Part 3

- 37. `rsync` – remote file transfers and syncing.
- 38. `tar` – an archiving utility.
- 39. `gzip` – file compression and decompression.
- 40. `bzip2` – similar to `gzip`. It uses a different compression algorithm.
- 41. `zip` – for packaging and compressing (to archive) files.
- 42. `locate` – search files in Linux.
- 43. `ps` – information about the currently running processes.
- 44. Making use of Bash scripts. Example: `./bashscript.sh`
- 45. `cron` – set up scheduled tasks to run.
- 46. `nmcli` – command-line tool for controlling [NetworkManager](#).
- 47. `ping` – send ICMP ECHO_REQUEST to network hosts.
- 48. `traceroute` – check the route packets take to a specified host.
- 49. `mtr` – network diagnostic tool.
- 50. `nslookup` – query Internet name servers (NS) interactively.
- 51. `host` – perform DNS lookups in Linux.
- 52. `dig` – DNS lookup utility.

Linux Commands – Part 4

- 53. `wget` – retrieve files over HTTP, HTTPS, FTP, and FTPS.
- 54. `curl` – transferring data using various network protocols. (supports more protocols than `wget`)
- 55. `dd` – convert and copy files.
- 56. `fdisk` – manipulate the disk partition table.
- 57. `parted` – for creating and manipulating partition tables.
- 58. `blkid` – command-line utility to locate/print block device attributes.
- 59. `mkfs` – build a Linux file system.
- 60. `fsck` – tool for checking the consistency of a file system.
- 61. `whois` – client for the WHOIS directory service.
- 62. `nc` – command-line networking utility. (Also, see [60 Linux Networking commands and scripts.](#))
- 63. `umask` – set file mode creation mask.
- 64. `chmod` – change the access permissions of file system objects.
- 65. `chown` – change file owner and group.
- 66. `chroot` – run command or interactive shell with a special root directory.
- 67. `useradd` – create a new user or update default new user information.
- 68. `userdel` – used to delete a user account and all related files.
- 69. `usermod` – used to modify or change any attributes of an existing user account.

Linux Commands – Part 5

- 70. `vi` – text editor.
- 71. `cat` – display file contents.
- 72. `tac` – output file contents, in reverse.
- 73. `more` – display file contents one screen/page at a time.
- 74. `less` – similar to the more command with additional features.
- 75. `tail` – used to display the tail end of a text file or piped data.
- 76. `dmesg` – prints the message buffer of the kernel ring.
- 77. `journalctl` – query the systemd journal.
- 78. `kill` – terminate a process.
- 79. `killall` – Sends a kill signal to all instances of a process by name.
- 80. `sleep` – suspends program execution for a specified time.
- 81. `wait` – Suspend script execution until all jobs running in the background have been terminated.
- 82. `nohup` – Run Commands in the Background.
- 83. `screen` – hold a session open on a remote server. (also a full-screen window manager)
- 84. `tmux` – a terminal multiplexer.
- 85. `passwd` – change a user's password.
- 86. `chpassword` – allows users to change the password for various user accounts.
- 87. `mount` / `umount` – provides access to an entire file system in one directory.
- 88. `systemctl` – central management tool for controlling the init system.
- 89. `clear` – clears the screen of the terminal.
- 90. `env` -Run a command in a modified environment.

Linux commands – Miscellaneous.

91. `cheat` – allows you to create and view interactive cheat sheets on the command line.
92. `tldr` – Collaborative cheat sheets for console commands.
93. `bt` – C++ version and continuation of `bashtop` and `bpytop`.
94. `nload` – a super simple, command-line network interface monitoring tool.
95. `history` – used to view the previously executed commands.
96. `sar` – collects, reports, and saves system activity information, including CPU, memory, disk, and network usage.
97. `lsof` : List open files and the corresponding processes. This command is invaluable for troubleshooting and understanding what files are used by processes.
98. `awk` : A powerful pattern scanning and processing language. It's used to manipulate data and generate reports.
99. `sed` : A stream editor used to perform basic text transformations on an input stream (a file or input from a pipeline).
100. `watch` : Execute a program periodically, showing output full-screen. It's useful for monitoring commands or scripts that update regularly.