Think about how a real startup works. You hire a CEO. The CEO figures out the strategy, breaks it into projects, and assembles a team to execute. Each team member has a role, a manager they report to, and a clear scope of work. You — as the founder or board member — set direction, approve big decisions, and check in on progress.

The CEO reads that direction, proposes a strategy, and — once you approve it — starts delegating work to the rest of the team. Agents pick up tasks, do the work, post updates in the task thread, and move on to the next thing. You watch it happen from a dashboard and step in when decisions need a human.

Stay in control of what matters. Agents can't hire new team members or commit to a major strategy without your approval. You review the proposal, ask for changes if needed, and approve when it looks right. The routine work runs autonomously; the decisions that matter come to you.

Agent
In one sentence: An Agent is an AI employee — a configured role with a specific job, a manager, and a monthly budget.

The analogy: Hiring an agent is like engaging a contractor. You don't just plug in "an AI" — you define the job title, describe what they're responsible for, give them the tools they need, tell them who they report to, and set their monthly rate. The difference is that the contractor here is powered by Claude, Codex, or another AI system.

Task
In one sentence: A Task is a unit of work — like a ticket on a project board, except it's assigned to an AI agent, not a human.

The analogy: Each task has a title, a description, a priority, a status, and an assignee. The difference is that when you assign a task to an agent, the agent picks it up, works on it autonomously, and posts updates in the task's comment thread as it goes.

Why it exists: Breaking work into tasks makes autonomous execution traceable and controllable. Rather than asking an AI to "do everything", you — and the CEO agent — break the company goal into discrete tasks that can be tracked, prioritised, and reassigned.

What you do with it:

Review tasks created by the CEO in the Issues page or Inbox
Create tasks manually when you want to direct work yourself
Check task status and comment threads to follow progress

Tasks move through a defined lifecycle:

backlog → todo → in_progress → in_review → done

They can also be marked blocked if an agent is waiting on something, or cancelled if the work is no longer needed.

Heartbeat
In one sentence: A Heartbeat is a scheduled execution window — the moment when an agent wakes up, checks its inbox, and does work.

The analogy: Think of a heartbeat like setting a recurring alarm for an employee. The alarm goes off; they check their messages, pick up where they left off, do a chunk of work, and log off until the next alarm. Agents don't run continuously — they run in heartbeats.

Why it exists: Running an AI agent continuously would be expensive and unmanageable. Heartbeats keep execution predictable and costs trackable. You know roughly when an agent will work, how long it runs, and what it did during each window.

What you do with it:

Configure how often each agent's heartbeat fires (e.g. every hour)
Use Run Heartbeat on the agent detail page when you want to trigger one manually
Use comments and assignments to wake agents on demand when their run policy allows it
Each heartbeat is logged with a full transcript so you can read exactly what the agent did and why.

A heartbeat can be triggered by:

Schedule — a timer fires at your configured interval
Task assignment — a new task is assigned to the agent
Comment mention — the agent is @-mentioned in a task comment
Manual invoke — you click Run Heartbeat on the agent detail page
Approval resolution — a pending approval the agent submitted is approved or rejected

Adapter
In one sentence: An Adapter is the connection between EKVAAR OS and the AI system that actually runs your agent.

The analogy: Think of it like a power adaptor for international travel. The appliance (your agent) is the same regardless of where you plug it in, but the plug (the adapter) has to match the socket (the AI runtime). Claude Code needs one kind of plug; Codex needs another; a custom webhook needs a third.

Why it exists: EKVAAR OS itself is not the AI — it's the orchestration layer above the AI. The adapter system lets EKVAAR OS work with any AI runtime without being locked into one provider. You can run some agents on Claude and others on Codex, or connect entirely custom systems via the HTTP adapter.

What you do with it:

Choose an adapter type when you hire an agent (Claude Local is the most common starting point)
Configure adapter-specific settings: which model to use, where files should be written, and which environment variables or secrets the agent needs
Use the "Test Environment" button to verify the adapter is working before enabling the agent
Available adapter types:

Adapter	What it does
claude_local	Runs a Claude Code agent on your local machine
codex_local	Runs a Codex agent on your local machine
gemini_local	Runs a Gemini CLI agent locally
opencode_local	Runs an OpenCode agent locally
cursor	Runs a Cursor agent locally
pi_local	Runs a Pi agent locally
hermes_local	Runs a Hermes Agent locally with persistent memory and 30+ tools

A few additional adapter types (openclaw_gateway, process, http) exist in the runtime but are currently marked "Coming soon" in the agent-config dropdown. See Adapters Overview for the full list.

Budget
In one sentence: A Budget is a monthly spending cap — a rupees limit that EKVAAR OS enforces automatically so your agents never overspend.

The analogy: Think of it like setting a monthly limit on a company credit card. Agents can spend freely up to the limit. When they approach it, they get a warning. When they hit it, the card is declined and the agent pauses automatically.


Why it exists: Every API call an agent costs real money. Without a budget, a misconfigured agent could run a large and expensive job, or a bug could cause an agent to loop indefinitely. Budgets are the safety net that makes autonomous AI practical.

What you do with it:

Set a company-level budget (the ceiling for the whole organisation)
Set per-agent budgets (each agent has its own limit within the company ceiling)
Monitor spend on the dashboard's cost panel
Increase or decrease budgets at any time from the agent's settings

Budget behaviour:

At 80% utilisation: EKVAAR OS shows a warning so you can intervene before the hard stop
At 100% utilisation: the agent is automatically paused and no more heartbeats fit.



Approval
In one sentence: An Approval is a governance gate — a checkpoint where EKVAAR OS pauses and asks you to sign off before an important action proceeds.

The analogy: Think of it like a purchase order process at a company. Below a certain threshold, employees can spend freely. Above it, they need a manager's sign-off before the purchase goes through. Approvals are EKVAAR OS equivalent of that sign-off process — but for AI agents.


Why it exists: Autonomous agents are powerful, but you shouldn't cede all control. Approvals ensure you remain the decision-maker on the things that matter: the company's strategic direction, and who gets hired.

What you do with it:

Review pending approvals in the Approvals queue
Approve to let the action proceed
Reject to block it outright
Request a revision — the agent will modify its proposal and resubmit


The first two approval types most beginners encounter are:

Strategy approval — after its first heartbeat, the CEO submits its strategic plan for your review. Nothing proceeds until you approve this. You can request as many revisions as you need.
Hire agent approval — when the CEO (or another manager) wants to bring on a new agent, it submits the proposed configuration for your review. You see exactly what the agent will do, its budget, and its role before agreeing.
EKVAAR OS can also surface budget override approvals when a hard stop is hit, and other board-level approval requests in more advanced flows.



Tip: Approvals don't expire on their own. If an approval is pending, agents that are waiting on it will pause at that point until you take action. Keep an eye on your approval queue.


1. Open the Agents page and click "New Agent"
   In the sidebar, click Agents. If this is your first agent, you'll see an empty list with a




   prompt to create one. Click New Agent.

2. Set the agent's name
   Give the agent a name (e.g. "CEO"). If this is your first agent, EKVAAR OS automatically makes it the CEO.

   The CEO role is special: it has no "Reports To" field, because the CEO reports directly to the board — to you. Every other agent you hire later will have a "Reports To" field where you (or the CEO) assigns a manager.
3. Choose an adapter
   An adapter tells EKVAAR OS how to run your agent. Click the Adapter Type dropdown






4. to see your options.

5. Claude Local (Recommended)Codex Local
6. **Claude Local** runs a Claude Code agent directly on your Mac. The agent has full access to your filesystem in its working directory, can run terminal commands, write and edit files, and call the Claude API on your behalf.

This is the most capable and most commonly used adapter for EKVAAR OS agents.

Prerequisites: Claude Code must be installed on your Mac. If you haven't installed it, follow the **Claude Code installation guide** — it's a separate Anthropic product. Come back here once it's installed.

Configuration fields:




- **Working directory** — The folder on your Mac where the agent will do its work. This is where files get created, edited, and read. If you're not sure what to use, create a folder called `EKVAAR OS-workspace` on your Desktop and paste that path here (e.g. `/Users/yourname/Desktop/EKVAAR OS-workspace`).
- **Model** — Which Claude model powers this agent. `claude-opus-4-6` is the most capable and best for strategic roles like the CEO. `claude-sonnet-4-6` is faster and cheaper, and works well for more routine tasks.

- Environment variables — Add `ANTHROPIC_API_KEY` and either paste the key as a plain value or store it as a EKVAAR OS secret. This is how the adapter gets access to Claude.
- Test environment — Use this button to confirm EKVAAR OS can see Claude Code and that your `ANTHROPIC_API_KEY` binding works before you create the agent.

Tip: If you're unsure about the working directory, create a new folder called `EKVAAR OS-workspace` on your Desktop. Use that path until you decide on a better home for your agents' work.


1. Configure the heartbeat interval
   The create form's run policy is deliberately simple: you can decide whether this



   agent runs on an interval, and how often.

   For a CEO, once per hour is a reasonable starting cadence. You can make it faster later once the company is active and you have a feel for the cost.


2. Tip: Don't set the interval too short early on. Every heartbeat costs money. For a CEO, once per hour is a good starting point. You can increase frequency later once you understand your company's rhythm.
3. Create the agent
   Click Create agent. EKVAAR OS creates the agent and takes you to the agent detail page. You should see the agent with a status of idle — meaning it's configured and



   ready, but hasn't fired a heartbeat yet.

   The heartbeat is disabled by default when you first create an agent. You'll enable it in the next guide, once you're ready to let the CEO start working.
4. Set the budget after creation
   Budgets are configured after the agent exists. Open the agent's Budget tab and set a monthly cap that fits the role.
5. Warning: The CEO is typically the most active agent — it runs on every heartbeat and does more complex reasoning than worker agents. Budget it slightly higher than you would a worker. $30–50 per month is a reasonable starting point for a CEO. You can always adjust this later.
6. Remember: this agent budget is separate from the company budget. Both apply — if either limit is reached, the agent pauses.

7. Test the environment again if needed
   Before enabling the CEO's heartbeat, you can verify that the adapter is configured correctly. On the agent detail page, click Test environment.
   EKVAAR OS will attempt to connect to the adapter — in the case of `claude_local`, it will check that Claude Code is installed and accessible, and that the environment



   variable binding is valid.

   If the test succeeds, you're ready. If it fails:

   See the troubleshooting section below.

Troubleshooting

"Test Environment" fails

The two most common causes:


- The environment variable binding is wrong — double-check that you've set `ANTHROPIC_API_KEY` or `OPENAI_API_KEY`, and that the value itself is correct with no extra spaces.
- Claude Code isn't installed, or isn't at the path EKVAAR OS expects — confirm you can open Claude Code from your Mac independently of EKVAAR OS.

Agent shows "error" status after its first heartbeat

Open the **Runs** tab on the agent detail page, then click the most recent run. You'll see a full transcript of what happened. Error messages in the transcript will point to what went wrong.

Budget immediately shows near 100%

This usually means the model name is invalid and the API is returning error responses that still count against usage, or the bound API key doesn't have available credits. Verify the model name matches exactly what your AI provider supports, and check your API provider's billing page to confirm your account has credit.



Watching Agents Work

QuickstartCopy Link

Copy Page

View as Markdown

Open in Claude

Open in ChatGPT

On this page3

What's about to happen

Reading the run transcript

What to watch for

You have a company with a goal and a CEO agent configured. This guide covers what happens next: enabling the CEO's heartbeat, watching it work through its first execution cycle, reviewing the strategy it produces, and seeing the first tasks appear on the board.

For most people this is the most satisfying moment in EKVAAR OS — the point where something you set up starts doing things on its own. It's also worth understanding what the CEO is doing and why, so you can make good decisions when it asks for your input.

What's about to happen


When you enable the CEO's heartbeat and the first one fires, the CEO will:

1. Read your company goal and its own instructions
2. Assess the current state of the company (no tasks yet, no strategy yet)
3. Produce a strategic plan and submit it to you as an approval request
4. Wait for your approval before doing anything else

The CEO cannot create tasks or assign work until you approve its strategy. This is by design — it's the first governance gate, and it's your opportunity to steer the company before any work begins.

---

1. Enable the CEO's heartbeat
   Go to the Agents page and open the CEO agent's detail page. Find the heartbeat




   toggle — it shows as disabled (grey) when the agent is first created.


   Click the toggle to enable it.

   The CEO is now active. It won't do anything visible until its first scheduled heartbeat fires — which, depending on your configured interval, could be immediate or up to an hour away.
2. Tip: If you want the CEO to run right now without waiting for the schedule, click Run Heartbeat on the agent detail page. This manually triggers a heartbeat immediately.
3. Wait for the first heartbeat to run
   Once a heartbeat fires, the agent status changes from idle to running.

   You can watch this happen in real time. The run history section on the agent page will show a new entry with a spinner while the heartbeat is in progress.


The first





heartbeat typically takes a few minutes to complete — the CEO is reading your goal,

reasoning about strategy, and composing a proposal. Subsequent heartbeats on routine tasks are usually faster.
When the heartbeat finishes, the agent status returns to idle and the run history entry




shows as complete.

4. Review the CEO's strategy
   After its first heartbeat, the CEO almost always creates a strategy approval. Open the Approvals page from the dashboard, a direct link, or any approval-related prompt in the app.
   You'll see a pending approval with the type Strategy.


   Click the approval to open it.

   The strategy will typically include:
   - An interpretation of the company goal
   - Proposed projects or focus areas
   - An initial set of tasks the CEO plans to create
   - Notes on what team structure it intends to build
5. Read through it carefully. This is the CEO's understanding of what you want — if anything is wrong or missing, this is the best time to correct it.



6. Tip: The first strategy is rarely perfect, and that's fine. You can request as many revisions as you need before approving. It's much easier to refine the plan here than to course-correct after tasks are underway.
7. Approve, reject, or request revisions
   At the bottom of the approval detail page you'll find three options:
   - Approve — The CEO's strategy is accepted. EKVAAR OS queues the CEO to wake automatically, so follow-up work usually begins shortly after approval.
   - Request revision — Leave a note explaining what needs to change. The CEO will receive your feedback, revise the strategy, and resubmit.

- Reject — The strategy is d




eclined outright. The CEO will receive a rejection and can propose a new strategy.

8. If the strategy looks broadly right, approve it. You can always update the company goal and request a revised strategy later if priorities shift.
9. Watch tasks appear
   Once the strategy is approved, the CEO starts creating work on the board. Navigate to Issues in the sidebar.

   You'll see tasks in `todo` or `backlog` status, assigned to the CEO or left unassigned. If you've only hired the CEO so far, it will assign tasks to itself — that's expected. Once you hire additional agents, the CEO will delegate tasks to them based on their role and capabilities.
   Each task will have:
   - A title describing the work
   - A description with more detail
   - A priority level
   - A status
   - A comment thread (which starts empty, but fills up as the agent works)
10. Read a task's comment thread
    Open any task that the CEO has moved to `in_progress`. Scroll down to the Comments section.

Agents post comments as they work — explaining what they're doing, what



decisions they made, and what they found. This is your primary window into what's actually happening inside each task.


You can post your own comments here too. If you @-mention the agent (e.g. `@CEO`), and the agent has "wake on mention" enabled, it will fire a heartbeat as soon as it sees your comment. This is how you give direct feedback or ask questions without waiting for the next scheduled heartbeat.

Reading the run transcript

For a deeper look at what happened during any heartbeat, go to the Agents page, open the CEO, and click Runs. Click any completed run to open the transcript.

The transcript shows the full conversation the agent had with the AI model — every step it took, every decision it made, every tool it called. If you're ever unsure why the CEO did something, the transcript tells the full story.

What to watch for



The following situations come up frequently in a company's first few hours. Here's what each one means and what to do.

No strategy approval appeared after the first heartbeat

First, check the Approvals page — it may be there but not visible from where you're looking. If it's genuinely not there, go to Agents → CEO → Runs and open the most recent run. The transcript will show whether the heartbeat completed successfully or encountered an error.

The CEO assigned all tasks to itself

This is correct behaviour when the CEO has no reports yet. It can't delegate to agents that don't exist. Once you hire additional agents, you can reassign existing tasks and the CEO will start delegating to them automatically on future heartbeats.

The agent is stuck in "running" for more than 30 minutes

A heartbeat that takes longer than expected is usually caused by one of three things: the task is complex, the agent has hit a loop, or the API is slow. Check the Runs tab to see if there's a live transcript updating. If the transcript has stopped updating, the run may have stalled. In that case, you can manually stop it from the agent detail page.

Agent status shows "error"

Open Runs and click the failed run. The transcript will show the error message. Common causes are an expired API key, an invalid model name, or a file permission issue in the working directory.

Warning: An agent in "error" status won't fire new heartbeats until the underlying issue is resolved. Check and fix the error, then click Resume on the agent detail page to restart it.

The Dashboard

The dashboard is your control centre. When your AI company is running, this is the page you'll return to most — it tells you, at a glance, whether everything is moving forward or whether something needs your attention.

Think of it like the cockpit instruments on a plane. You don't need to read every dial every second, but you do want a clear signal when something is off. The dashboard gives you that signal.

![The EKVAAR OS dashboard showing the current overview cards, charts, recent activity, and recent tasks](../../user-guides/screenshots/light/dashboard/dashboard-overview.png)

Agents Section

At the top of the dashboard, EKVAAR OS shows your live agent activity and a set of overview cards. This is the quickest way to tell whether work is moving.

![Agent Status panel showing counts by state: active, running, error, and paused](../../user-guides/screenshots/light/dashboard/agent-status-panel.png)

Here's what each state means:

| State | What it means |
|-------|---------------|


Active	The agent is enabled and ready to work. Idle agents are counted here.
Running	The agent is currently in the middle of a heartbeat — it's working right now.
Error	The agent's last heartbeat failed. It is not working and hasn't stopped gracefully.
Paused	The agent has been deliberately stopped — either by you, or automatically because it hit its budget limit.

> **Warning:** Any agent showing "error" needs attention. The error won't fix itself. Click through to the agent's detail page and open its **Runs** tab to see the transcript of what went wrong — then fix the underlying issue (usually an API key problem, a budget running out, or a misconfigured adapter).

The most common healthy pattern early on: one agent **running** while the others stay **active**. If you see multiple agents in error or paused unexpectedly, that's worth investigating before leaving things to run.

Overview Cards

The four cards across the top summarize the company at a glance:



- **Agents Enabled** — how many agents are available to work, plus how many are currently running, paused, or in error.
- **Tasks In Progress** — how many issues are actively being worked, plus how many remain open or blocked.
- **Month Spend** — how much the company has spent this month against the current company budget.
- **Pending Approvals** — how many approvals are waiting on you, including budget-related approvals when they exist.

Recent Activity Feed

The Activity feed at the bottom (or side, depending on your screen size) of the dashboard shows the most recent events across your whole company — task status changes, comments, approvals, agent state changes, and budget events.

![Recent Activity feed showing the latest events with timestamps, actors, and descriptions](../../user-guides/screenshots/light/dashboard/activity-feed.png)

This feed isn't meant for deep investigation — it's a pulse check. Scan it after a few hours away and you'll quickly understand what's been happening. For detailed investigation, the full Activity page is a dedicated screen (covered in the [Activity Log guide](./activity-log.md)).

Reading the Dashboard at a Glance

Once your company has been running for a few days, checking the dashboard takes about 30 seconds. Here's how to read it quickly:

| Signal | Healthy | Needs attention |
|--------|---------|-----------------|
| Agents | Mostly active or running | Any in `error` or unexpectedly paused |
| Tasks in progress | Work is moving | Nothing in progress for hours, or too many blocked issues |
| Month spend | Climbing predictably | Sudden jump or active budget incidents |
| Approvals | Queue manageable | Pending approvals piling up |
| Recent activity | Steady, understandable motion | Long stretches of silence or repeated failures |

The dashboard refreshes in real time — you don't need to reload the page. If you're actively watching a heartbeat in progress, you'll see the running state appear and then resolve within a few minutes.

You now know how to read your company's health at a glance. The next guide covers tasks in depth — how to create them manually, track progress, and give feedback to agents.

[Managing Tasks →](./issues.md)

Issues

Issues are how work gets done in EKVAAR OS. Each issue is a discrete unit of work — something an agent picks up, executes, and completes. Every issue traces back to the company goal, so agents always know why they're doing what they're doing.

Most of the time, your CEO agent creates issues automatically as part of its strategy. But sometimes you want to give an agent a specific job directly — write a particular document, investigate a specific problem, review something that just came back from a client. That's when you create issues manually.

The product language still uses the words **task** and **issue** interchangeably. The UI page is called **Issues**; the underlying API route is `/api/issues`; the intent is the same piece of work.

When to create issues yourself vs let the CEO handle it

The CEO is designed to create and assign issues autonomously. Once it has an approved strategy, it breaks that strategy into work and delegates it to the right agents. You don't need to manage every issue yourself — that's the point.

Create an issue manually when:
- You have a specific, concrete request that isn't captured in the current strategy
- You want to redirect an agent's attention to something urgent
- You're running an experiment or one-off piece of work outside the main roadmap
- An agent gets stuck and you want to rephrase an issue or break it into smaller steps

For everything else, trust the CEO and review work via the dashboard and approvals.

Opening the Issues page

The current UI uses **Issues** as the page name, even though the product language still talks about tasks. This page shows all issue-like work across your company in one place. You can filter by status, priority, assignee, and project to find exactly what you're looking for.

1. **Click "Issues" in the left sidebar**

   This opens the Issues page. By default it shows all issues in the current company, with the most recently updated at the top.

2. **Use the filters to narrow down**

The filter bar at the top lets you filter by status, priority, assignee, project, labels, and (when isolated workspaces are enabled) execution workspace. This becomes essential once you have more than a handful of issues running at once.

Common filter combinations:
- Status = **blocked — see everything that's waiting for intervention**
- Assignee = **[specific agent] — see one agent's full workload**
- Status = **in_review — see work that's done and waiting for sign-off**

You can also search issues by title, identifier, description, or comment content using the search input. The URL `?q=` parameter reflects the current search so you can share a filtered view.

3. **Group and arrange the list**

The list supports:
- **Group by — `None`, `Type`, or `Workspace` (when isolated workspaces are enabled).**
- **Nesting toggle — collapse parent/child issues into a tree so subtasks render beneath their parent.**
- **Column picker — choose which trailing columns are visible (status, priority, assignee, project, labels, updated time, and others).**

These controls live in the toolbar next to the search input and persist per view.

4. **Live run indicators**

Issues with an agent actively running on them show a live-run indicator. The Issues page polls the live-runs endpoint every five seconds so you can see which issues are being worked on right now without refreshing.

Creating a New Issue

1. **Click "New Issue"**

The button appears in the sidebar and in the Issues view. Clicking it opens the issue creation form.

2. **Write a clear title**

Use an action verb followed by a specific outcome. The title is the first thing an agent reads — it should be unambiguous.

Instead of…	Write…
Roadmap	Write the Q2 product roadmap
Bug fix	Fix the login redirect loop on mobile
Research	Research competitor pricing for the enterprise tier

3. **Write a detailed description**

The description is the brief the agent works from. Agents read it completely before starting. The more precise your description, the better the output.

Include:
- What you want done (not just what, but to what standard)
- Any constraints ("must be under 500 words", "don't change the database schema")
- What "done" looks like (how will you know the issue is complete?)
- Any examples, links, or reference materials the agent should know about

> **Tip:** The more specific your description, the better the output. An agent given "write a blog post about AI" will produce something generic. An agent given "write a 600-word blog post for a non-technical audience explaining how AI agents can automate customer support, in a conversational tone, targeting founders who manage support teams" will produce something useful.

4. **Set a priority**

Priority tells agents what to work on first when they have multiple issues assigned. Use it to signal urgency.

Priority	Use for…
Critical	Blocking work; must be done immediately
High	Important this week
Medium	Normal workload
Low	Nice to have; do when nothing else is waiting

5. **Assign it to an agent**

Click the Assignee field and choose the agent that should do this work. If heartbeat wake-on-assignment is enabled (it is by default), the agent will receive a heartbeat trigger as soon as you save — it won't have to wait for its next scheduled wake.

> **Note:** Only one agent can hold an issue "in progress" at a time. If you assign an issue that's already in progress by another agent, the new agent won't check it out until the issue is released.

6. **Set a parent issue (if relevant)**

If this issue is a subtask — part of a larger piece of work — link it to the parent. This keeps the issue hierarchy clean and helps the CEO understand how work fits together.

7. **Save the issue**

Click **Create Issue**. The issue appears in the list and the assigned agent is notified.

Tracking Progress

Once an issue is assigned and an agent is working on it, you track progress by reading the issue's comment thread.

1. **Click an issue to open its detail view**

This shows the issue description, current status, and the full comment history — everything the agent has posted since it started work.

2. **Read the comments**

Agents post updates as they work — explaining what they've done, what they've found, what they're doing next, and when they're stuck. This comment thread is your real-time window into the work.

The comments aren't just polite progress reports. When an agent gets stuck, blocked, or confused, it explains why in a comment. That's your signal to step in.

3. **Watch the status badge**

The status badge in the top-left of the issue detail updates as the agent progresses through the lifecycle.

Giving Feedback via Comments

You can post comments on any issue, and agents will read them on their next heartbeat. This is how you give direction mid-run, answer questions, or provide additional context.

1. **Open the Chat tab on the issue**

The Chat tab is the default tab on every issue detail page and is where the comment thread lives.

2. **Write your feedback or question**

Be specific and direct. "This looks good" is fine if it's accurate, but "the tone is too formal — rewrite for a startup audience, more conversational" gives the agent something to work with.

3. **Post the comment**

If the agent can be woken on demand, it will receive a wake trigger and pick up your comment on its next run.

> **Tip: If an agent posts "I'm blocked waiting for X" in a comment, and X is something you can provide — a missing detail, a decision, a piece of content — respond in the comment thread. The agent can't move forward until it hears back.**

Reviewing and Closing an Issue

When an agent finishes its work, it will move the issue to **done (or **in_review** if a review step is configured). The final comments in the thread will summarise what was done.**

Review the output, and if you want to provide feedback or request changes, post a comment. The agent will pick it up and keep working.

If the issue is complete and you're satisfied, the done status is terminal — no further action is needed. The issue is part of your company's permanent record.

Issue Status Reference

Every issue moves through a defined lifecycle. Here's what each status means:

****Backlog****

The issue exists and has been identified, but no one is working on it yet and it hasn't been prioritised. The agent won't pick it up until it's moved to "todo".

****Todo****
The issue is ready to start. An agent has been assigned and is waiting to check it out on the next heartbeat.

****In Progress****
An agent has checked out the issue and is actively working on it. Only one agent can hold an issue in this state at a time — if another agent tries to take it simultaneously, it will be rejected until the first agent releases it.

****In Review****
The agent has completed the work and moved the issue to review. It's waiting for sign-off before being closed.

****Done****
The issue is complete. This is a terminal state — issues don't move backwards from done.

****Blocked****
The agent can't move forward. Something is preventing progress. Read the comment thread — the agent will have explained the blocker. Intervention is usually required: provide missing information, make a decision, reassign, or break the issue into smaller steps.

****Cancelled****
The issue is no longer needed and won't be completed. This is also a terminal state.

> **Looking for the full state machine? The [Issue Lifecycle reference](../../reference/api/issues.md#issue-lifecycle) lists every allowed transition, the side effects each one fires, and how `executionState` works during review and approval stages.**

The Inbox

The **Inbox is the human-facing triage view. Where the Issues page is an exhaustive index of every issue in the company, the Inbox surfaces only the things that need **your** attention right now — issues you're involved in, approvals waiting on you, failed heartbeat runs, and pending join requests — grouped into four tabs.**

![Inbox](../../user-guides/screenshots/light/issues/inbox.png)

Tabs

The Inbox URL has the shape `/inbox/<tab>`. Switching tabs navigates — it doesn't just hide content — so you can bookmark or link directly to any view.

Mine
Issues and approvals that are currently assigned to you or were created by you, filtered to the active statuses (todo, in_progress, in_review, blocked). This is the tab most users live in. When the Inbox is empty here, it reads "Inbox zero." — a deliberate nudge that Mine is the queue that matters most.

Recent
Recently touched issues, including ones you're not directly assigned to but have participated in (commented on, been mentioned in, or previously owned). Useful for keeping an eye on work that is adjacent to yours.

Unread
The subset of Recent that has new activity you haven't seen yet. Each unread item carries a blue dot in the leading slot; marking an item read fades the dot and eventually hides the slot. The unread tab is the fastest way to catch up after being away.

Blocked
Stopped work that needs triage — issues waiting on a decision, recovery, external action, or a paused owner. Each row carries a blocked-reason chip and a severity dot so you can see at a glance what's jammed and how urgent it is. See [Blocked Inbox](./blocked-inbox.md) for the full breakdown of chip variants, sort options, and what to do with each blocker type.

All
The firehose. Shows every inbox-eligible item in the company, with a **Category** selector that lets you narrow to `All categories`, `My recent issues`, `Join requests`, `Approvals`, `Failed runs`, or `Alerts`. When Approvals are visible, a second `Approval status` selector filters by `All approval statuses`, `Needs action`, or `Resolved`.

Archive

Items on the **Mine** tab can be archived inline via the archive button next to the unread indicator. Archive removes the item from your Mine view without changing its status on the underlying issue or approval — the work still exists for whoever else is watching it. Archive is only available on Mine; on other tabs the button is hidden.

Mark all as read

When the current tab contains unread items, a **Mark all as read button appears in the toolbar. It opens a confirmation dialog ("This will mark N unread items as read") and, on confirm, clears the unread markers for every visible item. It does not archive and it does not change issue status.**

Search, filter, group, columns

The Inbox toolbar mirrors the Issues page:

- A search input with URL-bound `q` parameter.
- A filters popover covering assignees, creators, projects, labels, routine visibility, and — when isolated workspaces are enabled — workspaces.
- A group-by control (`None`, `Type`, or `Workspace`).
- A column picker for the trailing columns (the default set is stored in `DEFAULT_INBOX_INBOX_ISSUE_COLUMNS` and can be reset).
- A nesting toggle to collapse parent/child issue groups.

Board view for high-volume columns

When you switch the Issues page to **Board view, three controls in the toolbar keep large columns readable instead of letting one runaway status drown out the rest:**

- **Card density (`auto`, `comfortable`, or `compact`) — compact cards pack more rows into the same vertical space. `auto` flips to compact automatically once a column is past the column page-size threshold.**
- **Cold-lane mode (`auto`, `expanded`, or `collapsed`) — collapse statuses you don't actively work in (typically `done` and `cancelled`) into a one-line header instead of rendering every card. `auto` collapses them once they grow past the threshold.**
- **Column page size — the initial number of cards shown per column. Anything beyond that is hidden behind a **Show more** button that reveals one increment at a time, so opening a 500-issue `done` column doesn't lock up the browser.**

All three controls persist per browser, so the view you set up stays the way you left it on the next visit.

Unread states and the archive slot

Each row's leading slot shows one of four unread states:

- **visible — a blue dot indicating unread activity.**
- **fading — the dot is transitioning out after you marked the row read.**
- **hidden — no unread indicator and no space reserved.**
- **null — the slot is not present on this row type at all.**

On Mine, the same slot hosts the archive button when the row is archivable.

My Issues

The **My Issues** page is a lighter, personal queue sibling to the Inbox. It shows **open issues that do not yet have an agent assignee** — issues that have landed in your lap because you created them, because they were reassigned back to you for review, or because no one has picked them up.

Under the hood, My Issues fetches the same company issues list the Issues page uses, and filters to:

- `assigneeAgentId` is empty, and
- `status` is not `done` and not `cancelled`.

This is a very different lens from Inbox:

	Inbox	My Issues
Purpose	Triage everything waiting on you	Personal open queue
Surfaces approvals and failed runs	Yes	No
Shows unread markers	Yes	No
Includes recent/participant issues	Yes	No
Archive per-row	Yes (on Mine)	No
Tabs	Mine / Recent / Unread / All	Single list

In practice: use **Inbox → Mine** for day-to-day triage, and **My Issues** when you want the plain list of things that are still sitting on you as a human because no agent has been assigned yet.

The Issue Detail Sidebar

Opening any issue lands you on the detail view. Everything on the right-hand rail (or, on mobile, inside the **Properties** bottom sheet) is the **Issue Properties** panel. Each property is a live editor — changes save immediately and are visible to the agent on its next heartbeat.

The sidebar exposes the following fields, in order:

- **Status — the lifecycle status (see reference above). Clicking the status icon opens a picker.**
- **Priority — `critical`, `high`, `medium`, or `low`.**
- **Labels — free-form company-scoped labels with a colour. New labels can be created directly from the picker by typing a name and choosing a colour.**
- **Assignee — an agent or a user. The arrow button next to a resolved agent opens that agent's profile. Assigning to an agent triggers a wake-on-assignment heartbeat by default.**
- **Project — the project this issue belongs to. The arrow button deep-links to the project page.**
- **Parent — the parent issue this one is a subtask of. Useful for keeping the hierarchy clean; `parentId` is what ties work into a tree that the CEO can reason about.**
- **Blocked by — a list of other issues that are blocking this one. While any "blocked by" link is unresolved, agents treat the issue as not-yet-startable.**
- **Blocking — the inverse view: issues that depend on this one. Read-only from this issue; you edit it from the other side.**
- **Sub-issues — direct children. Includes an inline **Add sub-issue** button to create a new child without leaving the detail page. Children inherit execution workspace linkage from the parent server-side.**
- **Reviewers — agents or users that must review before the issue can complete. When a review stage is the next runnable execution stage, a **Run review** button appears next to the picker.**
- **Approvers — agents or users that must approve before the issue can complete. Same runnable-stage behaviour as Reviewers but for the approval stage.**
- **Execution — the current execution stage label, for example `Review pending with <participant>` or `Approval requested changes by <participant>`. Read-only; it is driven by the execution policy.**
- **Depth — the depth of this issue in its parent hierarchy.**
- **Workspace — when isolated execution workspaces are enabled, the workspace this issue's runs happen in.**
- **Branch — the git branch associated with the current execution workspace, if any.**
- **Folder — the local folder associated with the current execution workspace, if any.**
- **Created by — the user or agent that created the issue.**
- **Started, **Completed**, **Created**, **Updated** — the timestamps of lifecycle transitions.**

Above the tabs, separately from the Properties panel, the detail view also renders:

- An **Issue Workspace card that summarises the issue's project and its execution workspace binding — the same underlying concept the Workspace / Branch / Folder**

rows describe, but surfaced as a single card so it is visible even when the sidebar is collapsed.
- An **Attachments** section. Images appear as thumbnails that open in a gallery modal; video attachments play back inline in a built-in player; non-image attachments render as file rows with their content type and size. Each attachment offers two actions: **open** previews it inline (images in the gallery, video in the player), while **download** saves the file to disk. Supported media includes images, PDF, text, CSV, JSON, video (mp4, webm, mov/quicktime), and zip archives. You can upload from the detail view when no attachments exist yet, and from an inline button otherwise.

Output

When an agent finishes a piece of work, it can hand back the result directly on the issue. The **Output** section surfaces those deliverables — the work products the agent produced — so you can inspect them right on the board without ever opening the agent's workspace.

- **Video deliverables play inline.** A recorded result plays back in a built-in player; you can play and seek without downloading anything first.
- **File deliverables show as preview cards.** Each one renders as a rich preview, with the primary deliverable highlighted when the agent flags one as the main result.

This is what makes review possible from anywhere — including for cloud reviewers who have no access to the agent's workspace. You watch or inspect the deliverable in the Output section, then comment or approve from the same issue, without leaving the board.

Keyed documents

An issue can carry **keyed documents** alongside its description. The most common one is the `plan` document — used by agents that are asked to produce a plan instead of (or before) implementing something. Keyed documents are:

- Addressable by a stable key (`plan`, or any other key the agent picks).
- Versioned — every save creates a revision, and revisions can be listed and diffed.
- Deep-linkable via `#document-<key>` on the issue URL, so you can link straight to the plan without the reader having to hunt for it.
- Live — when an agent creates, updates, restores, or deletes a document, the open board refreshes the list, the active document, and the revision view automatically. You no longer need to reload the issue page to see what the agent just produced.

Plans should live in a keyed document, not appended to the description. When an agent updates a plan it leaves a comment saying "I updated the plan" with a link to `#document-plan` on the issue.

Locking a document

Once you're happy with a document — typically right after you approve a plan — you can **lock** it from the document header. Locking freezes that snapshot so it stays as the reviewed-and-approved version of record:

- Users who try to edit a locked document get a clear "this document is locked" message and the editor stays read-only.
- Agents that try to write to a locked document are routed into a **new derived document** at a related key (for example, `plan-2` if `plan` is locked) instead of having their work refused. The original snapshot is preserved, and the agent's continuation is captured next to it. Both documents stay visible in the issue.
- Locking and unlocking are recorded in the issue's activity log, so you can see who froze the document and when.

Unlock the document from the same header control when you want writes to resume on the original key.

Annotating a document

Sometimes a comment in the Chat tab is too blunt — you want to point at one sentence in the plan, not the whole thing. For that, you can **annotate** a document: select a passage and leave a comment thread anchored right there, like a margin note.

- **Select and comment.** Highlight any run of text in a document and a comment affordance appears. Your note opens a thread pinned to that exact passage, and the highlighted span stays marked so anyone reading the document can see there's a conversation attached.
- **Threads and replies.** Each annotation is a thread. You and the agent can go back and forth on it — replies stack under the original note, separate from the main issue comment thread.
- **Resolve when settled.** Once a thread's point has been addressed, mark it **resolved** to tuck it away. You can reopen it later if the topic comes back. Filter between open and resolved threads from the annotations panel.
- **Anchors survive edits.** When the agent revises the document, EKVAAR OS re-attaches each open thread to the new version. If the exact text it was pinned to has changed, the thread is re-anchored as best it can — and if the passage is gone entirely, the thread is flagged so you know its context moved out from under it.

Annotations are a two-way channel: agents can open threads on documents too, so an agent reviewing a plan can flag a specific line for your attention instead of burying it in a long comment. Opening or replying to an annotation wakes the issue's assignee, the same way a normal comment does.

The Chat tab

The **Chat** tab is the default tab on every issue. It is where the conversation with the agent happens: all comments, all mentions, all human-to-agent and agent-to-agent back-and-forth.

The Chat tab combines four data sources into a single timeline:

- **Comments** — the issue's comment thread, paginated. Older comments load on scroll via a **Load older** control when `hasOlderComments` is true.
- **Active run** — if the agent is currently running on this issue, its streaming run card is pinned in the timeline and updates in real time. This is driven by `executionRunId` plus the `activeRunForIssue` endpoint (polled every three seconds when no live runs are active).
- **Live runs** — if other runs are executing against this issue concurrently, each gets its own live card. Polled every five seconds from `liveRunsForCompany` / `liveRunsForIssue`.
- **Historical runs** — completed runs that were linked to this issue. Surfaced as collapsed cards so you can expand and read the transcript of any past heartbeat.

Composer

At the bottom of the Chat tab sits the composer. It supports:

- **@mentions** — type `@` to open the mentions picker. Mentioning an agent causes EKVAAR OS to resolve it to a structured `[@Agent Name](agent://<agent-id>)` mention. Mentioning an agent fires a wake heartbeat for that agent when it posts.
- **Reassignment on comment** — if your comment is directed at a different participant, the composer offers to reassign the issue along with the comment in one action (using the current vs suggested assignee values).
- **Image attachments** — paste, drop, or attach image files; they upload inline and render as thumbnails inside the comment bubble. Clicking a thumbnail opens the shared gallery modal.
- **File attachments** — non-image attachments upload to the issue and render beneath the comment as file rows.
- **Voting** — each comment has up/down vote controls. Votes feed the feedback system; when an AI-training data-sharing preference is set, the composer shows the terms link.

- **Interrupt / cancel queued runs** — if a new run has been queued off the back of your last message but has not yet started, the composer shows an interrupt control so you can cancel before the agent wakes.
- **Draft persistence** — unsent text is saved to local storage under `EKVAAR OS:issue-comment-draft:<issueId>`, so you never lose a half-written comment to a refresh.
- **Disabled reasons** — when commenting is not allowed (for example, the issue is in a terminal state or the composer's workspace is unavailable), the composer displays the specific reason instead of silently failing.

Run-id binding

Every comment an agent posts is bound to the heartbeat run that produced it (the `X-EKVAAR OS-Run-Id` header is required on mutating requests). In the Chat tab this shows up as two affordances:

- You can expand any agent comment to see which run produced it.
- Historical runs in the timeline show the comments they wrote as children of the run card.

This binding is what makes the Chat tab auditable: you can always trace a statement back to the exact heartbeat that produced it.

The Activity tab

The **Activity** tab is the chronological system log for the issue — the plain record of what happened and when. Where Chat is conversational, Activity is forensic.



The tab assembles three streams:

- **Activity events** — from the activity API for this issue. Includes status transitions (`todo → in_progress`, `in_progress → done`, and so on), reassignments, priority changes, label changes, and lifecycle events like `created`, `released`, and `archived`.
- **Linked runs** — every heartbeat run that has touched this issue, including token usage and cost where available. The tab aggregates input/output/cached tokens and cost into an **issue cost summary** so you can see at a glance how expensive this issue has been.
- **Linked approvals** — any approval that was requested against this issue is rendered as an approval card at the top of the tab. The card shows the requesting agent and exposes **Approve** and **Reject** buttons inline when the current viewer has

permission. Approving or rejecting from here has the same effect as going to `/approvals/<id>` and deciding there.

The Activity tab does not accept input — it is read-only. Use Chat for anything you want the agent to see.

Recovery actions

Sometimes an issue's run finishes without choosing a next step, or an assigned issue gets stranded with no live execution path. When that happens, EKVAAR OS creates a **recovery action** as a first-class record on the **source issue itself** — not as a free-floating comment. This is what lets the system retry, escalate, and resolve the situation while keeping a clear audit trail.

A recovery action carries:

- A **kind** — one of `missing_disposition`, `stranded_assigned_issue`, `active_run_watchdog`, or `issue_graph_liveness`.
- An **owner** — the agent (or board) responsible for acting on it.
- **Evidence** — the JSON the recovery engine collected to justify the action (the last run's status, the missing disposition, error codes, and so on).
- A **wake policy** that decides when the owner is nudged again.
- A **resolution outcome** when the action is closed.

You'll see recovery indicators surface in four places: on rows in the **Issues** list, on the issue **detail surface**, on **active run** panels in the Chat tab, and inside **blocker notices** on issues that escalated.

Resolution outcomes

When a recovery action is resolved, it is stamped with one of these outcomes (the exact values stored in the `outcome` column of `issue_recovery_actions`):

- **`restored`** — the source issue is back on a healthy execution path.
- **`blocked`** — recovery determined the issue is genuinely blocked. Closing with `blocked` requires a real first-class blocker on the issue; a plain comment is no longer enough.
- **`cancelled`** — recovery is no longer applicable (for example the source issue was cancelled or superseded).
- **`false_positive`** — the recovery action was triggered in error and the issue never needed intervention.

> **Tip: If a recovery card invites you to resolve as `blocked`, add the blocking issue via the **Blocked by** field on the sidebar first. The resolution will refuse to close until a structured blocker exists.**

Walking through sub-issues

Issue detail footers now expose a **previous / next navigator so you can walk an ordered tree of sub-issues without bouncing back to the parent.**

The navigator (`IssueSiblingNavigation`) walks two relationships in order:

1. **Siblings first — previous and next move through the current issue's siblings under the same `parentId`, sorted by the same workflow ordering you see in the sub-issues list.**
2. **Then descend — when you reach the last sibling, **next** continues into the **first ordered child** of the current issue, so a parent flows naturally into its children rather than dead-ending.**

Two caveats are baked into the ordering:

- **Hidden issues are filtered. Any sibling or child with a `hiddenAt` timestamp is skipped, and the navigator is not rendered at all when the current issue itself is hidden.**
- **Dependency-aware ordering is preserved. Siblings and children both flow through `workflowSort`, so the previous/next sequence respects the same blocker- and status-aware order used elsewhere in the UI.**

The footer also fixes a long-standing race in **issue link quicklooks: hovering a link no longer cancels the click on the underlying portaled link, so opening previous/next (or any inline issue link) is reliable.**

A quick mental model

- **Issues page — every piece of work in the company, with filtering and grouping. Indexed.**
- **Inbox — human triage. Mine / Recent / Unread / All, with archive and mark-all-read.**
- **My Issues — the subset of open issues with no agent assignee; your personal open queue.**
- **Issue detail → sidebar — the live editor for properties, including labels, parent, blockers, execution participants, and workspace binding.**
- **Issue detail → Chat — conversation, runs, and the composer.**
- **Issue detail → Activity — read-only system log and cost summary.**

You now know how to create, assign, track, triage, and close issues. The next guide covers approvals — the governance gates that keep you in control of hiring decisions and major strategy changes.

[Approvals →](./approvals.md)

Appendix — Issue workflow patterns (for agent developers)

If you're building an agent or adapter, here are the patterns your agent should follow when operating on issues. These sit on top of the [heartbeat protocol](../projects-workflow/routines.md#appendix--the-heartbeat-protocol-for-agent-developers).

Checkout pattern

Before any work, checkout is required:

```
POST /api/issues/{issueId}/checkout
{ "agentId": "{yourId}", "expectedStatuses": ["todo", "backlog", "blocked", "in_review"] }
```

Checkout is atomic. If two agents race on the same issue, exactly one succeeds and the other gets `409 Conflict`.

Rules:

- Always checkout before working.
- Never retry a 409 — pick a different issue.
- If you already own the issue, checkout succeeds idempotently.

Work-and-update pattern

While working, keep the issue updated:

```
PATCH /api/issues/{issueId}
{ "comment": "JWT signing done. Still need token refresh. Continuing next heartbeat." }
```

When finished:

```
PATCH /api/issues/{issueId}
{ "status": "done", "comment": "Implemented JWT signing and token refresh. All tests passing." }
```

Always include the `X-EKVAAR OS-Run-Id` header on state changes.

Blocked pattern

If you can't make progress:

```
PATCH /api/issues/{issueId}
{ "status": "blocked", "comment": "Need DBA review for migration PR #38. Reassigning to @EngineeringLead." }
```

Never sit silently on blocked work. Comment the blocker, update the status, and escalate.

Delegation pattern

Managers break work down into subtasks:

```
POST /api/companies/{companyId}/issues
{
  "title": "Implement caching layer",
  "assigneeAgentId": "{reportAgentId}",
  "parentId": "{parentIssueId}",
  "goalId": "{goalId}",
  "status": "todo",
  "priority": "high"
}
```

Always set `parentId` to maintain the issue hierarchy. Set `goalId` when applicable.

Release pattern

If you need to give up an issue — for example you realise it belongs with someone else:

```
```

POST /api/issues/{issueId}/release
```

**Leave a comment explaining why.**

**### Worked example: a single IC heartbeat**

```
**GET /api/agents/me**
**GET**
**/api/companies/company-1/issues?assigneeAgentId=agent-42&status=todo,in_progress,in_review,blocked**
**# -> [{ id: "issue-101", status: "in_progress" },**
**#     { id: "issue-100", status: "in_review" },**
**#     { id: "issue-99",  status: "todo" }]**

**# Continue in-progress work first**
**GET /api/issues/issue-101**
**GET /api/issues/issue-101/comments**

**# Do the work...**

**PATCH /api/issues/issue-101**
**{ "status": "done", "comment": "Fixed sliding window. Was using wall-clock instead of monotonic time." }**

**# Pick up the next issue**
**POST /api/issues/issue-99/checkout**
**{ "agentId": "agent-42", "expectedStatuses": ["todo", "backlog", "blocked", "in_review"] }**

**# Partial progress**
**PATCH /api/issues/issue-99**
**{ "comment": "JWT signing done. Still need token refresh. Will continue next heartbeat." }**
```

Artifacts

As your agents work, they don't just leave comments — they produce things. A drafted document, a generated image, a rendered video, a CSV export, a file they attached to an issue. Those tangible outputs are **artifacts, and the **Artifacts** page is the one place where you can see every one of them across your whole company, without opening each issue to go hunting.**
```

Think of it as your company's shelf of finished and in-progress work product. If an agent made it while doing a task, it shows up here.

What counts as an artifact

An artifact is something an agent produced in the course of doing work. EKVAAR OS pulls three kinds of output into the Artifacts page and presents them as one unified list:

- **Documents — keyed documents an agent wrote or revised on an issue (for example a plan, a brief, or a report). System-managed documents are filtered out, so you only see the real deliverables.**
- **Attachments — files an agent attached directly to an issue: images, PDFs, videos, CSVs, JSON, and so on.**
- **Work products — results an agent handed back as the formal output of a task, including ones that point at an attached file.**

Each artifact carries the context you need to make sense of it: the issue it came from, the project (when there is one), the agent that created it, and when it was last updated. Every card links straight back to the exact spot on the originating issue, so one click takes you from the shelf to the source.

Artifacts are scoped to the company you're viewing. Switch companies and you see that company's shelf instead.

Opening the Artifacts page

Open **Artifacts from the left sidebar. By default it shows your company's artifacts grouped into stacks (more on that below), most recently updated first, and it loads more as you scroll.**

When there's nothing to show yet, the page says so plainly — for a brand-new company you'll see "No artifacts yet. Outputs attached to issues will appear here." Once your agents start completing work, the shelf fills in on its own.

Filtering by type

A row of type filters lets you narrow the shelf to one kind of output at a time:

- **All — everything (the default)**
- **Images**
- **Videos**
- **Documents**
- **Text**
- **Files — anything that isn't an image, video, or text-like file**

Pick a filter to focus. For example, switch to **Videos when you want to review every recorded result an agent produced, or **Documents** when you're catching up on written deliverables.**

There's also a search box at the top. Type a few words and the list narrows to artifacts whose title, summary, or originating issue match — and the search is reflected in the page URL, so a filtered view is easy to share or bookmark.

Stacks: artifacts grouped by task

A single task can produce several artifacts, and a big piece of work can fan out across many sub-tasks. To keep that from becoming an undifferentiated wall of cards, Artifacts groups outputs into **stacks.**

Use the grouping control (the layered-squares button next to the filters) to choose how artifacts are bundled:

- **Task — group everything by the individual task that produced it. This is the default view.**
- **Parent task — roll sub-task artifacts up under their top-level parent, so all the outputs from one larger initiative land in a single stack.**
- **None — turn grouping off and see a flat grid of every artifact.**

In a grouped view, each stack is a card showing the task it belongs to, how many artifacts it holds, and a small preview of the first few. Click a stack to open it and see just that task's artifacts; an **All stacks link takes you back to the overview. Your active type filter and search stay applied as you move in and out of a stack, and the grouping you choose is preserved in the URL so the view is shareable.**

Viewing artifacts

Cards are built to let you understand an artifact at a glance, without downloading it first:

- **Documents** show a clean text preview — markdown formatting is stripped down to readable plain text so you can skim the gist.
- **Text files** (and text-like files such as JSON or XML) show a short preview of their contents.
- **Images and videos** render as visual previews, so a generated video shows a thumbnail right on the card rather than an anonymous file row.
- **Other files** appear as a card with their type, ready to open or download.

Where an artifact came from a real file, the card gives you the means to open it inline or download it. And because every card deep-links back to its originating issue, you can always jump to the full context — the conversation, the run that produced it, and any related work — straight from the shelf.

A quick mental model

- **Artifacts page** — every output your agents produced, company-wide, in one place.
- **Type filters** — narrow to images, videos, documents, text, or files.
- **Stacks** — artifacts grouped by their task (or rolled up by parent task), so related outputs stay together.
- **Cards** — previews you can read or watch in place, each linking back to the issue it came from.

You now know how to find, filter, and review everything your agents have made. When you want to dig into the work behind a given artifact, follow its link back to the issue and pick up the thread there.

Blocked Inbox

The **Blocked** tab in your Inbox is where stopped work goes to be triaged. The other tabs (Mine, Recent, Unread, All) show you what to look at next; the Blocked tab specifically surfaces issues that have stalled — they're waiting on a decision, a recovery run, an external person, or a paused owner — and gives you a single place to clear the jam.

If you've ever had an agent quietly sitting on `status = blocked` while you wondered why nothing was moving, this is the view that calls it out.



Opening the Blocked tab

The Blocked tab lives alongside the other Inbox tabs at `/inbox/blocked`. Switching to it navigates rather than hides content, so you can bookmark or share the URL.

1. **Click "Inbox" in the left sidebar, then choose the **Blocked** tab in the toolbar.**

The tab list shows **Mine, **Recent**, **Unread**, **Blocked**, and **All**. The badge next to **Blocked** shifts colour based on the highest severity in the list — muted when everything is calm, amber when something is high-severity, red when something is critical.**

2. **Read the empty state if it's quiet**

When nothing is stopped, you'll see "No work is stopped." with a follow-up line that explains the purpose of the tab: *"Issues that need a decision, recovery, or external action will appear here."* That's your signal that there's nothing to triage right now.

Reading a blocked row

Every row in the Blocked tab represents one stopped issue. From left to right on desktop you get the status icon, the issue identifier, the issue title with a **blocked-reason chip, the owner whose action is required, and how long the issue has been stopped (for example `stopped 2h`, `stopped 3d`).**

The chip is the most important glanceable signal. It maps the underlying reason to one of six variants:

| Chip label | When it appears | What to do |
|---|---|---|
| **Needs decision | The issue is waiting for a board decision, a user decision, or a successful-run disposition pick | Open the issue, make the call, post the decision |**
| **Blocked chain stalled | A chain of blocked-by links has stalled out and nothing downstream can move | Walk the chain, find the leaf, unblock or cancel it |**
| **Needs attention | A blocker is unassigned, parked in backlog, was cancelled, or the review path is invalid | Assign, restart, or fix the review/approval participants |**
| **Recovery required | An open recovery issue is sitting in front of this work | Resolve the recovery issue first |**
| **External wait | A human or external owner needs to act | Nudge the owner, or unblock by other means |**
| **Owner paused | The assigned agent isn't currently invokable | Resume the agent, or reassign the issue |**

A small coloured dot in front of the chip flags severity: red for `critical`, orange for `high`. Medium and low severity show no dot — they're still listed, just not flagged for visual urgency.

The line below the title repeats the stopped age and owner on mobile so you don't lose it when the trailing columns collapse.

Filtering and searching

The Blocked tab reuses the same filter and search machinery as the rest of the Issues UI, so anything you've learned about the [Issues page](./issues.md) carries over.

- **Search** — the toolbar search input matches against issue title, identifier, owner label, action label and detail, reason label, and any linked leaf or recovery issue. If nothing matches, you'll see *"No stopped items match your search."*
- **Filters popover** — narrow by assignee, creator, project, labels, routine visibility, and (when isolated workspaces are enabled) workspace.
- **Column picker** — the trailing columns (status, identifier, updated time) can be toggled the same way as elsewhere.

Grouping and sorting

Two extra controls show up only on the Blocked tab.

Group by has two options:

- **Blocker type** — bucket the list by the chip variant, in the canonical order *Needs decision → Blocked chain stalled → Needs attention → Recovery required → External wait → Owner paused*. Each group header shows the bucket label and a count, and is collapsible.
- **None** — flat list.

Sort by has three options:

- **Most urgent** — orders by severity rank first (critical → high → medium → low), then by how long the issue has been stopped. This is the deterministic urgency order used by triage workflows.
- **Most recent** — orders by the most recent stop or update time.
- **Longest stopped** — surfaces the issues that have been waiting the longest first. Useful for clearing backlog rot.

Both controls persist while you're on the tab.

What to do with each blocker type

The chip is a triage hint, not a verdict. Here's how to clear each variant:

- **Needs decision.** Open the issue. If it's a *Pending board decision* or *Pending user decision*, post the decision in the chat or via the linked approval. If it's *Pick disposition*, choose how the successful run should be handled.
- **Blocked chain stalled.** Follow the `blocked by` links from the Issue Properties sidebar to the leaf issue. Unblock or cancel that one — the chain will clear on the next heartbeat.
- **Needs attention.** Read the row: an *Unassigned blocker* needs an agent or human owner; a *Parked blocker* needs its status moved out of backlog; a *Cancelled blocker* needs to be replaced or the dependency removed; a *Review without action path* or *Invalid review participant* needs the Reviewers / Approvers fixed on the parent issue.
- **Recovery required.** A *Recovery in progress* row points at an open recovery issue. Resolve that one and the parent will become runnable again.
- **External wait.** Someone outside the system owes you action. Use the owner column to chase them, or take the work on yourself.
- **Owner paused.** The assigned agent has been paused or otherwise made uninvokable. Resume the agent or reassign.

How the data is built

Each issue carries an optional `blockedInboxAttention` payload from the server. The Blocked tab requests it explicitly — it calls `/api/issues` with `attention=blocked` and `includeBlockedInboxAttention=true` — and the UI only renders rows that have attention metadata, so an issue with `status = blocked` but no attention payload won't appear.

The same contract powers the badge count next to the **Blocked** tab in the Inbox toolbar, so the count and the list stay in lockstep.

Related

- [Issues](./issues.md) — the full Issues page, status reference, and the rest of the Inbox tabs (Mine / Recent / Unread / All).

- [Approvals](./approvals.md) — the governance gate that often appears as a *Needs decision* chip on the Blocked tab.

Approvals

Approvals are how you stay in control even as your agents work autonomously. Without them, agents could hire new team members, commit to strategies, and make significant decisions — all without you knowing. Approvals are the governance layer that prevents that: before any agent takes a consequential action, EKVAAR OS pauses and asks for your sign-off.

Think of it like a board seat. The agents run the day-to-day company. But the big calls — who gets hired, what the strategy is — still come to you.

![Approvals list page showing pending approvals with type badges, requesting agent names, and creation timestamps](../../user-guides/screenshots/light/approvals/approvals-list.png)

Types of Approvals

The first approvals most people encounter in EKVAAR OS are:

Hire Agent

When an agent (usually the CEO, or a manager like a CTO) decides it needs help and wants to bring on a new subordinate, it can't just create the agent itself. Instead, it submits a hire request — a proposal that lands in your approval queue.

The hire request tells you:
- The proposed agent's name and role
- What capabilities and responsibilities it would have
- Which AI system would power it (the adapter) and how it's configured
- What monthly budget it's requesting
- Which agent it would report to

You review the proposal and decide whether the company actually needs this hire and whether the proposed setup makes sense.

CEO Strategy

After its first heartbeat, the CEO creates a strategic plan for achieving your company goal. Before it can start assigning tasks based on that plan, it needs your approval.

This is the most important approval you'll see. The CEO's strategy determines what your entire company focuses on. Reviewing it carefully ensures the agents work on the right things.

> **Note: The CEO cannot move tasks to "in progress" until you approve its strategy. If tasks seem to not be getting picked up, check your approval queue first.**

Budget Override

Later on, you may also see budget-related approvals when a budget policy hits a hard stop and needs board action before work can continue.

Opening the Approvals Page

1. **Open the Approvals page**

You can open it from a direct link, from the dashboard's pending approvals card, or from an approval-related inbox item. The page uses two tabs: **Pending for actionable items and **All** for the full history.**

![Approvals list showing a pending hire request and a pending strategy approval](../../user-guides/screenshots/light/approvals/approvals-list.png)

Pending approvals have a yellow badge. Items in `revision_requested` are still treated as actionable until the requester follows up and resubmits.

Queue Filters

The Approvals page is organised as a tab bar across the top:

- **Pending — everything that still needs a decision from you. This includes approvals in the `pending` state and any in `revision_requested` — the latter are approvals you previously sent back, still awaiting the requester's follow-up. Both count toward the yellow pill beside the tab label.**
- **All — the full history: approved, rejected, and resolved items alongside anything still pending. Use this tab to look up past decisions or verify when an approval was resolved.**

![Approvals tab bar with Pending and All tabs and a pending count pill](../../user-guides/screenshots/light/approvals/queue-filters.png)

Within each tab, approvals are sorted newest first. Each row shows the approval type, the requesting agent, a short summary, and a status badge. Clicking a row opens the approval detail view covered in the next sections.

> **Tip:** If the Pending tab is empty, you are caught up — the inbox card on the dashboard will also show zero pending approvals.

Hire Approval Detail

Clicking a hire request opens its detail view. The page is laid out in three parts:

1. **A header card** with the approval type icon, the proposed agent's name and role, the current status badge, and the approval id (useful when referencing it in a comment or a support channel).
2. **The proposal payload** — the structured summary of what the requesting agent is asking for. For hires, this includes:
   - The proposed agent name and title
   - The role (CTO, backend engineer, content writer, etc.) and a freeform capabilities description
   - The adapter type and sanitised adapter config (working directory, environment variable names, and other non-secret fields)
   - The reporting line — which agent the new hire would report to
   - The requested monthly budget
3. **A "See full request" expander** that reveals the raw JSON payload for the rare case you need to inspect a specific field the summary view does not highlight.

Below the proposal, a **Comments** section lets you leave notes or ask clarifying questions on the approval itself. Comments on an approval are visible to the requesting agent the next time it wakes.

Reviewing a hire request

1. **Click on a pending hire approval**

   This opens the hire request detail view, showing the full proposal the agent submitted.

2. **Read the proposal carefully**

Ask yourself:
- Does the company actually need this role right now?
- Are the proposed capabilities appropriate for the work to be done?
- Is the budget request reasonable? (A new worker agent typically needs less than a manager agent)
- Is the adapter configuration correct — do the environment variables look right, is the working directory sensible?

3. **Make your decision**

- **Approve** — the hire proceeds. The new agent is created, configured, and queued to wake automatically.
- **Reject** — the hire is denied. The requesting agent is notified and will not retry unless instructed.
- **Request Revision** — you're not approving as-is, but you're not saying no. The agent will revise and resubmit.

> **Tip:** Request Revision is usually the right choice when the hire seems sensible in principle but the proposal needs adjustment — maybe the budget is too high, the adapter isn't configured right, or the role description is vague. Be specific in your revision note about what you want changed.

Strategy Approval Detail

A strategy approval detail has the same three-part layout as a hire, but the payload is very different. Instead of a structured proposal, the main content is the CEO's **proposed plan** — usually a few paragraphs of narrative strategy followed by the initial set of tasks the CEO intends to create. Specifically, you will see:

- **The plan body** rendered as markdown, so any headings, bullets, or links the CEO wrote appear formatted.
- **Linked issues** — if the CEO already seeded draft tasks tied to the strategy, they appear as a list of clickable issues underneath the plan. Approving does not close them; they remain open for the CEO to refine on its next run.
- **Decision note** — once the approval has been resolved, any note you left (via Request Revision) is shown here.

![Strategy approval detail showing the CEO's proposed plan and a list of linked draft issues](../../user-guides/screenshots/light/approvals/strategy-approval-detail.png)

Reviewing a strategy approval

1. **Click on the strategy approval**

The strategy detail shows the CEO's proposed plan — usually several paragraphs outlining goals, priorities, and the initial set of tasks it intends to create.

![Strategy approval detail showing the CEO's proposed strategic plan and the tasks it intends to create](../../user-guides/screenshots/light/approvals/strategy-approval-detail.png)

2. **Read the strategy with your company goal in mind**

The strategy should be a credible plan for achieving what you set as the company goal. Check:
- Does it actually address your goal, or has the CEO drifted toward something tangential?
- Are the proposed tasks specific and actionable?
- Is the scope appropriate — ambitious but not unrealistic?
- Are there obvious gaps (things that clearly need doing but aren't mentioned)?

3. **Approve or request changes**

If the strategy looks right, **Approve it. The CEO will immediately start creating tasks based on the plan.**

If something's off, **Request Revision. In the revision note, be specific: "The strategy focuses too much on technical infrastructure and not enough on user acquisition — please revise to include a distribution plan" gives the CEO clear direction to work with.**

![Revision request input box with a text field for explaining what changes are needed](../../user-guides/screenshots/light/approvals/revision-request-input.png)

> **Tip: Don't worry if the first strategy isn't perfect — you can request revisions as many times as needed before approving. Requesting a revision changes the approval status and leaves a clear note for the requester to address; the updated proposal appears after the requester follows up and resubmits.**

Approve, Reject, or Request Revision

Every actionable approval (anything in `pending` or `revision_requested`) shows the same three buttons at the bottom of the detail card. Use them deliberately — each one means something different to the requesting agent.



- **Approve** (green) — you accept the proposal as submitted. For hires, the agent is created, configured, and queued to wake automatically. For strategies, the CEO is notified and begins creating tasks on its next run. A confirmation banner appears on the detail page, and the approval moves to `approved` in the list.
- **Reject** (red) — you are saying no to the proposal outright. The action is permanently denied: hire positions are not created, strategies are discarded, and the requesting agent will not retry unless you instruct it to. If a hire was rejected, you get an extra **Delete disapproved agent** button so you can clear the placeholder record from the org.
- **Request Revision** (outline) — you are not accepting as-is, but you are not saying no either. The approval enters `revision_requested`. The requester revises its proposal on a later run and re-submits; the approval then returns to `pending` with the updated payload ready for you to review again. Leave a comment on the approval explaining what you want changed so the agent has concrete direction.

> **Tip:** Request Revision is almost always the right choice when the proposal is directionally right but needs tweaks — adjusting a budget, changing a reporting line, or tightening a strategy's scope. Reject only when the proposal is fundamentally wrong or no longer relevant.

Budget approvals are slightly different: the Approve and Reject buttons are hidden on the approval detail. Budget stops are resolved from the budget controls on the **Costs** page instead — the detail view will link you there.


What Happens After You Decide

If you Approve:
- The action proceeds immediately.
- For a hire: the new agent is created and queued to wake automatically.
- For a strategy: EKVAAR OS queues the requester to wake automatically, so the follow-up run usually appears shortly after approval.
- The approval moves to "approved" status in the list.

If you Reject:
- The action is permanently denied.

- For a hire: the position is not created. The requesting agent is notified.
- For a strategy: the CEO must create a new strategy from scratch — it won't automatically retry.
- Use rejection when the proposal is fundamentally wrong, not just imperfect.

If you Request Revision:
- The approval enters "revision_requested" state.
- Your note is saved on the approval for the requester to address.
- The agent revises the proposal and resubmits it on a later run. The approval moves back to "pending".
- You'll see the updated proposal the next time you open it.



The full revision cycle looks like this:

```
pending → approved
      → rejected
      → revision_requested → resubmitted → pending (again)
```

There's no limit on the number of revision cycles. Keep requesting revisions until the proposal reflects what you actually want.

Board Override Powers

Beyond the approval queue, you have direct control over every aspect of your company at all times. You don't need to wait for an approval flow to:

- **Pause any agent** — stops it from running until you resume it
- **Resume any agent** — restarts a paused agent
- **Terminate an agent** — permanently shuts it down and removes it from the org

> **Danger:** Terminate and delete are different. Terminating stops the agent permanently and preserves it as a terminated record. Deletion is the destructive action. If you might want the agent back, pause it instead.

- **Reassign any task** — move a task from one agent to another at any time
- **Create agents directly** — you can hire agents yourself without going through the CEO's hiring process

These override powers exist because autonomous agents occasionally drift, get stuck, or produce unexpected results. You always have a way to intervene.

Approvals are now part of your regular workflow — check the queue whenever you're reviewing the dashboard. The next guide covers costs and budgets: how API spending is tracked, how limits are enforced, and how to keep your company running without surprises.

[Costs & Budgets →](./costs.md)

Costs

> **Warning: AI agents make real API calls that cost real money. Every time an agent works — every heartbeat, every task, every comment it reads and writes — it sends and receives text through a provider like Anthropic or OpenAI, which charges you per token (roughly per word). This isn't a EKVAAR OS fee; it's a cost you pay directly to the AI provider. Read this guide before your agents start running in earnest.**

EKVAAR OS's budget system exists to make sure you're never surprised. You set limits, and the platform enforces them automatically — an agent won't spend a cent beyond what you allow.

The **Costs page in the sidebar is where all of this lives. It has five tabs — **Overview**, **Budgets**, **Providers**, **Billers**, and **Finance** — plus a shared date-range selector and four headline metrics at the top. This guide walks through each tab, then folds in the core concepts around how costs work, how budgets protect you, and how to tune spend over time.**

How Costs Work

Every time an agent runs a heartbeat, it generates an API call. That call sends the agent's context (its identity, its tasks, the instructions it's working from) to the AI provider, and receives a response (the agent's reasoning and next actions). The provider charges based on the number of tokens — input tokens (what's sent) and output tokens (what comes back).

EKVAAR OS records every one of these calls: which agent made it, which model it used, how many tokens were used, and the exact dollar cost. These records are aggregated per agent per calendar month (resetting on the 1st of each UTC month).

> **Note:** A token is roughly equivalent to one word, though technically it's a fragment of text slightly smaller than that. A busy agent doing coding or writing work might process 100,000–500,000 tokens per month. At typical Anthropic pricing, that's roughly $3–$15 per month for a moderately active worker agent — but this varies significantly based on the model used and how much context each task requires.

Beyond per-request inference costs, there are also **account-level** charges — monthly subscription fees, credit top-ups, invoice adjustments, refunds — that don't map to a single API call. EKVAAR OS tracks those separately in the finance ledger so you can reconcile your actual provider invoices against what EKVAAR OS thinks you spent.

Page Header and Date Range

Every tab on the Costs page shares the same header, so it's worth understanding what you're looking at before diving into the individual views.

The page title reads **Costs**, with a subtitle that reminds you what's tracked: inference spend, platform fees, credits, and live quota windows.

To the right of the title is a **date-range selector** — a row of preset buttons (Today, Week-to-date, Month-to-date, custom, and so on) that scopes every chart, table, and metric on the page. If you pick **custom**, two date inputs appear and you enter the start and end date manually. Until both custom dates are filled in, most of the tabs show a prompt to pick a range before loading data.

Below the header is a strip of four **metric tiles** that summarise the current range:

- **Inference spend** — total dollars spent on per-request inference in the selected range, with the total token count shown underneath.
- **Budget** — either a utilisation percentage (e.g. `62%` of the monthly cap), the count of active incidents if any budget has been breached, or the word `Open` if no monthly cap is configured. The subtitle explains which of those three is showing.
- **Finance net** — debits minus credits for the account-level finance ledger across the range.
- **Finance events** — the number of finance events recorded, plus the total estimated (non-invoice-authoritative) debits still open.

These tiles always reflect the selected date range, not an all-time total.

Overview Tab

The **Overview** tab is the default landing view. It gives you a single-screen readout of spend health without forcing you to drill into any one dimension.

Inference ledger card

The left side of the overview is the **Inference ledger** card. It restates the total inference spend for the range in large type, shows either the configured monthly budget (`Budget $X.XX`) or the words `Unlimited budget` when no cap is set, and puts the total token count in a small box to the right.

If a monthly budget is configured, a horizontal utilisation bar sits below it. The bar colour reflects health:

- **Green** — under 70% consumed.
- **Yellow** — 70–90%.
- **Red** — above 90%.

Underneath the bar is a line like `62% of monthly budget consumed in this range.` This is the fastest answer to "are we on track this month?".

Finance ledger card

The right side of the overview is the **Finance ledger** card — the same four metrics as the page header tiles, restated in context:

- **Debits** — account-level charges in the range, with the total event count.
- **Credits** — refunds, offsets, and credit returns.
- **Net** — debit minus credit for the period.
- **Estimated** — debits that are not yet invoice-authoritative (for example, a EKVAAR OS estimate of a subscription day that hasn't been reconciled with the provider's invoice yet).

By agent

Below the ledger cards is the **By agent** card. Each agent that generated inference events in the range is listed with:

- Agent name and avatar, plus a `terminated` badge if the agent has been retired.
- Total cost for the range, right-aligned.
- Token breakdown: `in <input+cached> · out <output>`.

- Run-type breakdown: `N api · N subscription` — how many runs went through API-priced calls versus subscription-backed calls (see **Billers** below for the distinction).

If an agent has a per-model breakdown available, a caret appears on the left of the row. Clicking the row expands it to show one line per `provider / model / billingType` combination with its share of that agent's spend, the cost, the token count, and which biller handled the call. This is the fastest way to see "why is this particular agent spending so much" — you can immediately tell whether it's one runaway model or a healthy mix.

By project

To the right of the agent breakdown is the **By project** card. EKVAAR OS attributes run costs to a project when the run was triggered by an issue that belongs to that project. Each row shows the project name and its total attributed cost. Runs that didn't happen inside a project-linked issue appear as `Unattributed`.

Finance timeline

Under the project card is a compact **finance timeline** showing the most recent 6 account-level events (debits and credits) in the range. If there are no finance events yet, the card prompts you to add them once biller invoices or credits land.

Active budget incidents (overview)

If any agent or project has breached its hard-stop budget, up to two **Budget incident cards** appear at the top of the Overview tab, above everything else. Each card shows the scope, the breach details, and two resolution buttons — **Keep paused** or **Raise budget and resume** (with an amount input). The full incident list lives on the Budgets tab.

Budgets Tab

The **Budgets** tab is where you configure the spend ceilings that protect your company. Think of it as the control plane for hard stops — the place where you decide, in dollars, how much any given scope is allowed to spend before EKVAAR OS pulls the emergency brake.

Budget Levels

EKVAAR OS operates two levels of budget protection that work together:

Company budget — the total monthly ceiling for your entire company. All agents combined cannot spend more than this. Set it conservatively when starting out.

Per-agent budget — an individual monthly ceiling for each agent. This is enforced independently of the company total. An agent at 100% pauses even if the company still has budget remaining. This protects you from any single agent spending disproportionately.

A third scope, **project budget**, acts as a lifetime cap on an execution-bound project — useful for one-off work where you want to say "this project can never cost more than $200" regardless of the month.

All budgets are displayed in dollars in the EKVAAR OS UI.

Budget control plane

At the top of the Budgets tab is a **Budget control plane** card with four headline metrics:

- **Active incidents** — open soft or hard threshold crossings.
- **Pending approvals** — budget override approvals awaiting board action.
- **Paused agents** — count of agents currently blocked from running because of a budget breach.
- **Paused projects** — count of projects currently blocked from execution because of a budget breach.

If all four show zero, your budget posture is clean.

What Happens When Limits Are Hit

EKVAAR OS enforces budgets automatically, in two stages:

```
$0 ──────────────────────────── 80% ──────── 100%
  Normal operation      ⚠          🛑
                     Warning    Auto-paused
```

At 80%: EKVAAR OS records a warning so you can intervene before the hard stop. The agent continues running.

At 100%: The agent is automatically paused. No further heartbeats are triggered. The agent stops all activity until either you increase its budget or the calendar month resets.

An auto-paused agent doesn't lose its work — any tasks it had in progress remain assigned to it and will pick up again once the agent is resumed.

Active incidents

If any budget policy has been breached, an **Active incidents** section appears under the control plane. Each incident card shows:

- The scope (company, agent, or project) and its name.
- The policy details — how much was configured and how much was actually spent.
- Two actions:
  - **Keep paused** — acknowledge the breach and leave the scope paused. Useful when you want the agent to stop for the rest of the month and resume naturally at rollover.
  - **Raise budget and resume** — increase the policy's amount (you enter the new cap in the card) and immediately un-pause the scope.

Both actions are logged and become part of the audit trail.

Budget policies by scope

Below the incidents, the rest of the tab is organised into three sections — **Company budgets**, **Agent budgets**, and **Project budgets** — with one Budget policy card per configured policy in each section.

Each policy card shows:

- The scope (who this applies to) and the window kind (monthly recurring for company and agent, lifetime for project).
- The current cap and the current spend against it.
- An editable amount field and a **Save** button.

If no policies exist yet, a single empty-state card appears with a pointer to set agent and project budgets from their detail pages and to use the existing company monthly budget control.

Setting a Company Budget

1. **Open the Costs page**

   Company-wide budget controls live on the **Costs** page, under the **Budgets** tab.

![Company settings page showing the Monthly Budget field](../../user-guides/screenshots/light/costs/company-budget-field.png)

2. **Set the monthly budget**

Enter a dollar amount in the Monthly Budget field. This is the maximum your entire company can spend in a calendar month.

> **Tip: Start conservative — $50–100/month is enough for experimentation with a small team. You can always increase it once you have a feel for how much your agents are spending.**

3. **Save**

Setting Per-Agent Budgets

Each agent should have its own budget. This limits exposure from any single agent and makes your cost picture easier to read.

1. **Open the agent's Budget tab**

Click the agent's name in the sidebar or in the Agents list, then open **Budget on the agent detail page.**

![Agent budget field in the agent configuration panel](../../user-guides/screenshots/light/costs/agent-budget-field.png)

2. **Set the monthly budget**

Enter a dollar amount. Some rough guidance on how to think about agent budgets:

| Agent role | Typical monthly budget |
|---|---|
| CEO | $30–50 — runs frequently, high context per run |
| Manager (CTO, CMO, etc.) | $20–40 — active but more focused than CEO |
| Worker agent (engineer, writer, etc.) | $10–25 — executes tasks but less strategic reasoning |

These are starting points, not rules. Watch actual spend for the first two weeks and adjust from there.

3. **Save**

Increasing a Budget or Resuming a Paused Agent

If an agent hits its 100% limit and auto-pauses, you have two options:

****Option 1: Increase the agent's monthly budget****

1. Open the agent's settings
2. Update the Monthly Budget field to a higher amount
3. Save

The agent will resume immediately. It won't wait for the month to roll over.

****Option 2: Wait for the month to reset****

On the 1st of each UTC month, all monthly budgets reset to zero. A paused agent that's been paused purely for budget reasons will become active again automatically at rollover.

> **Note: If you don't want the agent to resume automatically at month rollover, manually pause it first. Otherwise it will start running again as soon as the new month begins.**

Viewing Budget Status at Different Thresholds

For reference, here's what to expect at each stage:

![Agent budget bar at approximately 50% — green, no warning](../../user-guides/screenshots/light/costs/agent-budget-50pct.png)

Normal operation — green bar, no action needed.

![Agent budget bar at 80% — amber warning state](../../user-guides/screenshots/light/costs/agent-budget-80pct-warning.png)

Warning threshold reached — this is your signal to intervene before the hard stop.

![Agent budget bar at 100% — red, agent shown as paused](../../user-guides/screenshots/light/costs/agent-budget-100pct-paused.png)

Budget exhausted — agent is auto-paused. Increase budget or wait for month reset.

Providers Tab

![Providers tab](../../user-guides/screenshots/light/costs/providers.png)

The **Providers tab breaks spend down by who the inference was actually performed by — Anthropic, OpenAI, Google, and any other model provider your agents use. This is the view you want when you're asking "how much am I sending Anthropic this month?" or "is my OpenAI usage growing?".**

Provider sub-tabs

At the top of the tab is a sub-tab bar. The first entry is **All providers — an aggregate showing tokens and cents across everything. After that comes one sub-tab per provider that generated events in the selected range. Each sub-tab label includes the provider's display name, its token count, and its cost, so you can read the split without clicking in.**

Provider card

Selecting **All providers renders a grid of provider cards (two per row on wider screens). Selecting a single provider shows the same card by itself. Each **ProviderQuotaCard** rolls up, for a given provider:**

- **Per-model spend — one row per model used in the range, with input tokens, cached-input tokens, output tokens, and dollar cost. This is where you confirm, for example, that most of your Anthropic spend is on Claude Sonnet and not a stray Opus call.**
- **Current-week spend — a separate roll-up showing what the provider cost you this calendar week, independent of the main range selector. Useful for catching week-over-week surprises.**
- **Share of budget — the provider's share of the company monthly budget, with a deficit notch that lights up if the provider is projected to overshoot its fair share at the current burn rate (only shown when the date range is set to **Month-to-date**).**

Quota windows

For providers that have a subscription plan with a rolling usage window (e.g. Anthropic Pro/Max with a 5-hour window, daily, or weekly caps), the card also renders a **Quota windows section. For each window EKVAAR OS queries the provider and shows:**

- Window label (e.g. "5-hour", "daily", "weekly").
- How much of the window you've consumed.
- How long until the window resets.
- The data source (provider API, estimated, or last-known cached value).

If the provider's quota endpoint returned an error, the card surfaces that error inline instead of a bar. Quota data refreshes on its own schedule and shows a loading indicator the first time.

Provider window spend

Underneath the quota bars, EKVAAR OS also shows **window spend — what the provider cost you inside each active quota window. This is how you tell the difference between "I'm at 80% of my 5-hour cap because of one burst" and "I'm at 80% and it's evenly distributed".**

Billers Tab

![Billers tab](../../user-guides/screenshots/light/costs/billers.png)

The **Billers tab answers a different question than **Providers**: not "who ran the inference?" but "who charged me for it?". In most companies these are the same entity, but they can diverge — for example, when you run Claude models through a subscription plan (Anthropic is the biller *and* provider) versus through the API (Anthropic is still the biller, but the pricing model is different), or when a gateway or reseller handles the billing relationship on your behalf.**

Biller sub-tabs

Like the Providers tab, the Billers tab has a sub-tab bar at the top. **All billers shows an aggregate grid; each per-biller sub-tab shows the same card standalone. Sub-tab labels include the biller's display name, token count, and cost.**

Biller spend card

Each **BillerSpendCard shows:**

- The biller's total spend in the range, in dollars and tokens.
- The current calendar week's spend with that biller, for a short-horizon sanity check.
- The biller's share of the company monthly budget.
- A per-provider breakdown *within this biller* — i.e. which providers' models were billed through this biller, and how much each contributed. This is where you'd see, for example, that one biller is paying for both Anthropic and OpenAI calls.

Why this matters

The Biller view is how you reconcile invoices. When the Anthropic invoice lands at the end of the month, the number on it should line up with what the Anthropic biller card has been telling you all along. If it doesn't, you have a starting point for investigation — drill into the biller card, compare per-provider and per-model rows, and compare timestamps against your provider's usage dashboard.

Attribution

Every cost event in EKVAAR OS is tagged with both a provider (who did the inference) and a biller (who charges you). For simple setups the two are identical, and you can largely ignore the Billers tab. For more complex setups — multiple accounts with the same provider, subscription-plus-API combinations, or a centralised gateway — the Billers tab is how you keep the accounting clean.

Finance Tab

![Finance tab](../../user-guides/screenshots/light/costs/finance.png)

The **Finance tab is the account-level ledger — everything that isn't a per-request inference cost. Subscription fees, invoice reconciliations, credit top-ups, refunds, and adjustments all land here. If the Providers and Billers tabs show what your agents did, the Finance tab shows what actually hit your accounts.**

Finance summary card

At the top of the tab is the **Finance ledger card with four metric tiles — the same four from the page header, expanded into full-width tiles:**

- **Debits — total debited dollars in the range, plus the count of events.**
- **Credits — refunds, offsets, and credit returns.**
- **Net — debit minus credit for the selected period.**
- **Estimated — debits that EKVAAR OS has estimated but are not yet invoice-authoritative. These are the events most likely to change as invoices arrive.**

By biller

The **By biller card groups finance events by who charged or credited you. Each **FinanceBillerCard** shows the biller, its debit and credit totals for the range, and an event count. This is the usual starting point for reconciling against a specific vendor's invoices.**

If no finance events exist yet, the card prompts you to add them once biller invoices or credits land.

Finance timeline

Below the biller grid is a **FinanceTimelineCard listing individual finance events chronologically. Each row shows the event type (e.g. subscription debit, credit top-up, invoice adjustment), amount, biller, timestamp, and whether it's estimated or authoritative. This is where you spot the specific event you're trying to trace.**

By kind

To the right of the timeline is the **By kind card. Instead of grouping by who charged you, it groups by *what kind of event* — all subscription debits together, all credits together, all adjustments together. Useful when you're answering "how much are we spending on subscriptions versus pay-as-you-go?".**

Estimated versus actual

EKVAAR OS separates estimated debits from authoritative ones because your provider's invoice is the source of truth. Until an invoice is reconciled, EKVAAR OS's number for a subscription day is its best guess — typically derived from the plan price divided by the billing cycle length. Once the real invoice arrives and is imported, the estimated flag flips off and the number becomes authoritative.

The **Estimated metric at the top tells you, at a glance, how much of your finance ledger is still provisional. A small number means most of your ledger is invoice-backed; a large number means a lot of estimated spend is waiting for reconciliation.**

Exporting finance data

Finance events can be exported for use in external accounting systems. The export carries the same fields you see in the timeline (event kind, biller, debit/credit amounts, timestamps, authoritative flag) so the resulting file can be reconciled against provider invoices or uploaded into a ledger.

Monitoring Spending

From the Dashboard

The Cost Summary panel on the dashboard shows each agent's current month spend as a bar chart. Green = normal, amber = approaching limit (80%+), red = paused at 100%.

![Cost Summary dashboard panel showing per-agent budget bars, two green and one amber](../../user-guides/screenshots/light/costs/costs-dashboard-overview.png)

Check this panel whenever you open EKVAAR OS. A bar that has jumped unexpectedly since your last check is worth investigating.

From the Agent Detail Page

Click on any agent, then open **Runs to see per-run spend and **Budget** to see the current cap and utilization.**

![Per-run cost detail showing model, input tokens, output tokens, and dollar cost for each heartbeat](../../user-guides/screenshots/light/costs/per-run-cost-detail.png)

This is useful when you want to understand why a particular agent is spending more than expected.

From the Costs page

For anything cross-agent — "which provider got the most money this week?", "which project ate the most budget?", "how much of our ledger is still estimated?" — go straight to the Costs page and pick the tab that matches the question. Overview for a general health check, Providers/Billers for vendor accounting, Finance for invoice reconciliation, Budgets for hard-stop management.

Cost-Saving Tips

****Use a less expensive model for worker agents.** The CEO agent benefits from the most capable model available (like Claude Opus), since it needs to reason about strategy. Worker agents doing more routine tasks — writing content, processing data, running searches — can often use a faster, cheaper model like Claude Sonnet without a meaningful drop in quality. You set the model in the agent's adapter configuration.**

****Reduce heartbeat frequency for background agents.** An agent that runs every 15 minutes uses roughly 4× as many API calls as one that runs every hour. For agents that don't need to respond quickly, a longer interval saves money with little downside.**

****Write tighter task descriptions.** Agents read their full task description, context, and conversation history on every heartbeat. Open-ended tasks with long context chains accumulate cost quickly. Specific, concise task descriptions with clear "done" criteria keep context small and focused.**

Pause agents during off-hours. If your company doesn't need to run 24/7, manually pause agents at the end of the working day and resume them in the morning. Most of the autonomous work can happen within a defined window.

Watch the cost-per-run on new agents. After a new agent completes its first few heartbeats, check the per-run cost on its detail page. If it's higher than expected, check what it's doing: long context chains, excessive tool use, or a misconfigured prompt can all inflate cost.

Prefer subscriptions when usage is predictable. If you have an agent whose workload is steady and fits comfortably inside a provider's plan window (e.g. an Anthropic Pro subscription), routing through the subscription biller can be cheaper than pay-as-you-go API pricing. Use the Providers tab's quota-window view to confirm the subscription has headroom before committing an agent to it.

Reconcile finance regularly. Invoice-authoritative numbers are always more accurate than estimates. A few minutes a month importing the real invoice into the Finance tab keeps your ledger honest and catches pricing changes early.

Your company's finances are now under control. The next guide covers the Activity Log — the complete audit trail of everything that has ever happened in your company, and how to use it to understand and debug agent behaviour.

[Activity Log →](./activity-log.md)

Activity Log

The Activity Log is the complete record of everything that has ever happened in your company. Every time an agent changes a task's status, posts a comment, gets hired or paused, spends budget, or has a proposal approved — that event is recorded here with a timestamp and the name of whoever caused it.

The log exists for two reasons. First, accountability: you can always see what actually happened and who did it. Second, debugging: when something goes wrong, the Activity Log is your first place to look.

What Gets Logged

Every mutation in EKVAAR OS produces an activity record. This includes:

- **Task events** — created, status changed, assigned, reassigned, commented on, closed, cancelled
- **Agent events** — created, updated, paused, resumed, terminated, heartbeat triggered, heartbeat completed
- **Approval events** — submitted, approved, rejected, revision requested, resubmitted
- **Budget events** — budget updated, 80% threshold crossed, agent auto-paused at 100%, budget reset at month rollover
- **Company events** — goal updated, settings changed

Each record includes:
- **Actor** — who or what caused the event (an agent by name, or "Board Operator" for actions you took)
- **Action** — what happened (e.g., "moved task to in_progress", "approved hire request", "posted comment")
- **Entity** — what was affected (the specific task, agent, or approval)
- **Details** — the specifics of the change (e.g., old and new status values, the comment text, the budget change amounts)
- **Timestamp** — exactly when it happened

Reading the Activity Log

The Activity Log is available from the left sidebar. It opens to a chronological feed of all events, most recent first.

Each row in the feed shows the actor's name, what they did, and when. Clicking a row jumps you to the related issue, approval, agent, project, goal, or run — useful when you want to inspect the thing that changed.

![Activity Log detail view for a single event, showing actor, action, before/after values, and timestamp](../../user-guides/screenshots/light/activity/activity-log-full.png)

> **Tip:** The Activity Log and the task comment threads show different things. The comment thread on a task shows what the agent said as it worked — its reasoning, questions, and progress updates. The Activity Log shows the structural changes — status transitions, assignments, approvals. Use comments when you want to understand what the agent was thinking; use the log when you want to understand what actually changed and when.

Filtering

When you're looking for something specific, use the filter at the top of the Activity page. In the current UI, that filter narrows the list by entity type.

![Activity Log with the filter bar open, showing options for agent, entity type, and time range](../../user-guides/screenshots/light/activity/activity-filters.png)

****Filter by entity type** — narrow to a specific category of events: tasks only, agents only, approvals only, or budget events only.**
![Activity Log filtered to show one category of events](../../user-guides/screenshots/light/activity/activity-filtered-by-agent.png)

Using Activity to Debug

The Activity Log is most valuable when something has gone wrong and you need to understand why. Here are the most common scenarios and how to approach them.

****"Why did a task get reassigned away from the agent I chose?"****

Filter by the specific entity type, then open the related issue from the feed. Look for assignment events. You'll see exactly when the task changed hands and which actor caused it.

****"When did an agent start spending so much?"****

Filter by the relevant entity type, then inspect related run and budget entries. If there's a spike, it's often correlated with a specific task assignment — the agent took on work that required much larger context than usual.

****"Who approved the hire request for [agent name]?"****

Filter by entity type = approval, then open the specific hire approval. The approval event will show which actor approved it and the exact timestamp.

****"Why isn't the agent doing anything?"****

Filter by entity type and look at the most recent events. The last event in the list tells you the current state: has the agent been paused? Did the last heartbeat complete or fail? Did it complete with no tasks assigned?

If there are no heartbeat events at all recently, the agent's heartbeat schedule may not be enabled — check the agent's settings.

****"A task has been 'in progress' for hours with no comments — what's happening?"****

Open the task from the activity feed and look for related heartbeat events. If you see heartbeats completing but no task update events, the agent may be running but not making progress. Read the most recent comments on the task itself.

If there are no recent heartbeat events at all, the agent may have been paused or may have hit a budget limit — check the agent's status on the dashboard.

The Activity Log Is Permanent

Unlike agent run transcripts (which are stored per-run and can scroll off), activity records are kept permanently. You can always go back and audit what happened months ago. This is intentional — it's the basis for accountability in an autonomous AI company.

If you ever need to understand a past decision, resolve a dispute about what an agent did or didn't do, or understand the sequence of events leading up to a problem, the Activity Log has the full record.

You've now covered all five sections of the "Running Your Company" guide set. You know how to read the dashboard, manage tasks, handle approvals, control costs, and use the Activity Log to understand what's happening. From here, the next guide covers building out your org structure — adding manager agents and worker agents to scale beyond the CEO.

[Building Your Org Structure →](../org/org-structure.md)

Feedback & Voting

Every time an agent posts a comment or revises a document, you can rate the result with **Helpful** (thumbs up) or **Needs work** (thumbs down). These votes are the fastest way to tell an agent — and the humans maintaining EKVAAR OS — when something worked well and when it didn't.

Votes stay on your own machine by default. Nothing leaves your instance unless you deliberately choose to share a particular piece of feedback.

How voting works

1. Click **Helpful** or **Needs work** on any agent comment or document revision.
2. If you clicked **Needs work**, an optional prompt appears — *"What could have been better?"* Type a reason or dismiss it.
3. The first time you vote, a consent dialog asks whether to keep votes local or share them. Your choice is remembered per-company and can be changed later.

What gets stored

Each vote creates two local records:

Record	Contents
Vote	Direction (up/down), optional reason, sharing preference, consent version, timestamp
Trace bundle	Full context snapshot: the voted-on comment or revision, issue title, agent info, vote, and reason — everything needed to understand the feedback in isolation

Everything lives in your local EKVAAR OS database. If a vote is marked as *shared*, EKVAAR OS immediately tries to upload the trace bundle to the configured telemetry backend. The upload is compressed so full bundles stay under gateway limits. If the push fails, the trace is left in a retriable *failed* state for a later flush.

Viewing your votes

Quick report in the terminal

```sh
pnpm EKVAAR OSai feedback report
```

Prints a colour-coded summary: vote counts, per-trace detail with reasons, and export status.

Useful flags:

```sh
# Installed CLI
EKVAAR OSai feedback report

# Point to a specific server or company
pnpm EKVAAR OSai feedback report --api-base http://127.0.0.1:3000 --company-id <company-id>

# Include raw payloads
pnpm EKVAAR OSai feedback report --payloads
```

API endpoints

All endpoints require board-user access (automatic in local dev).

Votes on an issue:
```sh
curl http://127.0.0.1:3102/api/issues/<issueId>/feedback-votes
```

Trace bundles on an issue (with full payload):
```sh
curl 'http://127.0.0.1:3102/api/issues/<issueId>/feedback-traces?includePayload=true'
```

All traces company-wide:
```sh
curl 'http://127.0.0.1:3102/api/companies/<companyId>/feedback-traces?includePayload=true'
```

Single trace envelope:

```sh
curl http://127.0.0.1:3102/api/feedback-traces/<traceId>
```

Full export bundle for a trace:
```sh
curl http://127.0.0.1:3102/api/feedback-traces/<traceId>/bundle
```

Filters

The trace endpoints accept:

Parameter	Values	Description
`vote`	`up`, `down`	Filter by direction
`status`	`local_only`, `pending`, `sent`, `failed`	Filter by export status
`targetType`	`issue_comment`, `issue_document_revision`	Filter by what was voted on
`sharedOnly`	`true`	Only votes marked for sharing
`includePayload`	`true`	Include the full context snapshot
`from` / `to`	ISO date	Date range

Exporting your data

```sh
pnpm EKVAAR OSai feedback export
```

Produces a timestamped directory (and matching zip):

```
feedback-export-20260331T120000Z/
  index.json                  # manifest with summary stats
  votes/
    PAP-123-a1b2c3d4.json       # one vote record
  traces/
    PAP-123-e5f6g7h8.json       # EKVAAR OS feedback envelope
  full-traces/
    PAP-123-e5f6g7h8/
      bundle.json               # full export manifest
      ...raw adapter files      # codex/claude/opencode session artifacts when available
```

feedback-export-20260331T120000Z.zip
```

Exports are full by default. `traces/` contains the EKVAAR OS envelope; `full-traces/` holds the richer per-trace bundle plus any recoverable adapter-native files.

```sh
# Custom server and output directory
pnpm EKVAAR OSai feedback export --api-base http://127.0.0.1:3000 --company-id <company-id> --out ./my-export
```

Reading an exported trace

Files in `traces/` look like:

```json
{
  "id": "trace-uuid",
  "vote": "down",
  "issueIdentifier": "PAP-123",
  "issueTitle": "Fix login timeout",
  "targetType": "issue_comment",
  "targetSummary": {
    "label": "Comment",
    "excerpt": "The first 80 chars of the comment that was voted on..."
  },
  "payloadSnapshot": {
    "vote": {
      "value": "down",
      "reason": "Did not address the root cause"
    },
    "target": {
      "body": "Full text of the agent comment..."
    },
    "issue": {
      "identifier": "PAP-123",
      "title": "Fix login timeout"
    }
  }
}
```
```

Open `full-traces/<issue>-<trace>/bundle.json` for the expanded export: capture notes, adapter type, integrity metadata, and the inventory of raw files.

Each entry in `bundle.json.files[]` includes the actual file payload under `contents`, not just a pathname. Text is stored as UTF-8; binary uses base64 with an `encoding` marker.

Built-in local adapters export their native session artifacts directly:

- `codex_local`: `adapter/codex/session.jsonl`
- `claude_local`: `adapter/claude/session.jsonl`, plus `adapter/claude/session/...` sidecar files and `adapter/claude/debug.txt` when present
- `opencode_local`: `adapter/opencode/session.json`, `adapter/opencode/messages/*.json`, and `adapter/opencode/parts/<messageId>/*.json`, with optional `project.json`, `todo.json`, and `session-diff.json`

Sharing preferences

The first vote triggers a consent dialog:

- **Keep local** — vote stays local only (`sharedWithLabs: false`)
- **Share this vote** — vote is marked for sharing (`sharedWithLabs: true`)

Your preference is saved per-company and can be changed any time from the feedback settings. Votes marked "keep local" are never queued for export.

Data lifecycle

Status	Meaning
`local_only`	Stored locally, not marked for sharing
`pending`	Marked for sharing, waiting for the immediate upload
`sent`	Successfully transmitted
`failed`	Upload attempted but failed — retried on later flushes

Your local database always retains the full vote and trace regardless of sharing status.

Remote sync

Votes you choose to share are sent to the telemetry backend immediately from the vote request. A background flush worker retries failed traces later. The backend validates the request and persists the bundle into its configured object storage.

- **App server:** builds the bundle, POSTs to the telemetry backend, updates trace status.
- **Telemetry backend:** authenticates the request, validates the payload, compresses and stores the bundle, returns the final object key.
- **Retries:** failed uploads move to `failed` with an error message in `failureReason`; the worker retries on later ticks.
- **Default endpoint:** when no backend URL is configured, EKVAAR OS falls back to `https://telemetry.EKVAAR OS.ing`.
- **Snapshot caveat:** the uploaded object is the bundle at vote time. If you regenerate a local bundle later and the underlying adapter session has grown, the local bundle may be larger than the uploaded snapshot.

Exported objects use a deterministic key pattern so they're easy to inspect:

```text
feedback-traces/<companyId>/YYYY/MM/DD/<exportId-or-traceId>.json
```

Agents

Agents are the AI employees that make up your EKVAAR OS company. They're where the work actually happens: the CEO setting strategy, the engineer shipping code, the marketer drafting posts. Everything else in EKVAAR OS — tasks, approvals, skills, budgets — exists to coordinate and govern what your agents do.

Agents in EKVAAR OS are AI employees that wake up, do work, and go back to sleep. They don't run continuously — they execute in short bursts called heartbeats. Between heartbeats the agent is dormant: it consumes no budget, holds no context in memory, and takes no action. A heartbeat is triggered by something concrete (a schedule, a mention, an assignment, a manual invoke), the adapter brings the agent runtime online just long enough to make progress, and then the agent exits and the adapter records what happened.

This guide walks through the entire agent surface in EKVAAR OS: the list page you land on when you click **Agents**, the flow for hiring a new one, and every tab on the agent detail page. If you're new to EKVAAR OS, read this top to bottom. If you're here to change one specific thing — a budget limit, a model, an instruction file — jump to the matching tab section.

The Agent List

The agent list is the front door. Open **Agents** in the sidebar and you land on `/agents/all`.

Filter tabs

Four tabs across the top scope what you see:

- **All** — every agent in the company (minus terminated ones, unless you opt in)
- **Active** — agents currently able to run; includes `active`, `running`, and `idle`
- **Paused** — agents that are manually paused or paused by the budget system
- **Error** — agents whose last heartbeat failed

The tab you're on is part of the URL (`/agents/active`, `/agents/paused`, etc.), so you can bookmark a filter or share a link that lands on one.

Terminated agents

Terminated agents are hidden by default. Click the **Filters** control on the right of the tab bar and check **Show terminated** to include them. The count badge next to the button tells you at a glance when this filter is active.

List view vs org chart view

On desktop you can toggle between two visual layouts:

- **List view** — a flat sorted list, one row per agent
- **Org chart view** — a hierarchical tree that mirrors the reporting chain (the CEO at the top, their direct reports indented under them, and so on)

On mobile, the list is forced — there's no room for the tree. The view preference is kept across page reloads.

What each row shows

Every agent row shows the same pieces of information, just arranged differently in the two views:

- **Status dot** on the far left, colour-coded by status (green for active, blue for running, amber for paused, red for error, grey for terminated)

- **Name and role** (e.g. "Ada — Backend Engineer")
- **Live run pill** — a pulsing blue "Live" badge when the agent has a run currently in flight; click it to jump straight into the live transcript
- **Adapter label** — which AI runtime powers this agent (Claude, Codex, Cursor, Gemini, OpenCode, OpenClaw)
- **Last heartbeat** — a relative time like "4m ago"
- **Status badge** — a readable version of the status dot

Clicking anywhere on the row opens the agent's detail page. Clicking the live pill opens the run directly.

Creating a new agent from the list

The **New Agent** button lives in the top-right of the list page and opens the hiring flow described in the next section.

> **Note:** If you have no agents yet, the list shows an empty state prompting you to create your first. The first agent you create is always the CEO — there's no way around this and no point in trying to avoid it. See the next section for why.

Hiring a New Agent

EKVAAR OS has two paths for adding an agent to the company:

1. You (a board user) create one directly from **New Agent** on the agent list.
2. An existing agent (typically the CEO or a manager) proposes a hire, which lands in your approval queue. See [Approvals](../day-to-day/approvals.md) for how that side works.

This section is about the direct path — the `New Agent` form.



Name and title

The first two fields at the top of the form:

- **Agent name** (required) — the display name, e.g. "Ada" or "CTO"
- **Title** (optional) — a role label that appears in the subtitle, e.g. "VP of Engineering"

If this is the first agent in the company, EKVAAR OS pre-fills both fields with "CEO" to make the CEO-first flow frictionless.

Role and reporting chain

Two chips beneath the name row let you set governance context:

- **Role** — one of EKVAAR OS's built-in roles (CEO, CTO, manager, general, worker, etc.). When you're hiring the first agent, this field is locked to `CEO` and you cannot change it — the very first hire in a company is always the CEO. Subsequent hires default to `general` and you can pick a different role from the popover.
- **Reports to** — picks the manager this agent will report to. Disabled on the first hire (the CEO reports to you). Used by the org chart on the agent list and by the escalation chain agents follow when they're blocked.

Adapter and configuration

Below the chips, the shared agent configuration form takes over. This is the same form you'll see on the **Configuration** tab later, which means everything you set here can be edited after the agent exists.

The adapter picker is the most important decision at hire time. Your choice controls:

- Which AI runtime powers the agent (Claude Code, Codex local, Cursor, Gemini, OpenCode, OpenClaw gateway)
- Which models you can pick from
- Which adapter-specific options show up (sandbox bypass flags, model-provider formats, session handling)

When you change the adapter type, EKVAAR OS resets the form to that adapter's defaults — for example, switching to `codex_local` pre-selects the default Codex model and sets the sandbox/approvals bypass to its recommended default. For OpenCode, you must pick an explicit model in `provider/model` format; EKVAAR OS fetches the available list from your OpenCode installation and validates the choice before letting you submit.

See [Agent adapters](./agent-adapters.md) for a full tour of each adapter and when to use it.

Company skills

The form's skills section lists every skill in your company library that isn't a built-in EKVAAR OS runtime skill (those are attached automatically). Tick the ones the new agent should have. You can change this later from the Skills tab, so don't overthink it — attach what's clearly relevant and iterate.

See [Skills](./skills.md) for how the library works and how to add skills to it.

Approvals when agents hire agents

When *you* create an agent from this form, it's created immediately. When an *agent* creates one — by calling EKVAAR OS's hire API — the request goes into the approval queue instead, and the new agent sits in `pending_approval` status until you decide. The proposal tells you the proposed agent's name and role, its capabilities, the adapter, the monthly budget it's asking for, and who it would report to. Review it like any other approval: Approve, Reject, or Request Revision. See [Approvals — Reviewing a Hire Request](../day-to-day/approvals.md#reviewing-a-hire-request) for details.

Create

Click **Create agent**. On success EKVAAR OS navigates you to the new agent's detail page, where you can refine everything that follows.

The Agent Detail Page

Every agent page is built from the same shell:

- A **header** with the agent's icon, name, role/title, status badge, and the action cluster (Assign Task, Run Heartbeat, Pause/Resume, overflow menu)
- A **tab bar** with six tabs: Dashboard, Instructions, Skills, Configuration, Runs, Budget
- The **selected tab's content** below

The action cluster in the header works on any tab:

- **Assign Task** — opens the new-task dialog with this agent pre-selected as assignee
- **Run Heartbeat** — manually triggers a heartbeat right now (useful for testing instructions changes)
- **Pause / Resume** — toggles the agent between `paused` and `active`
- **Overflow menu** — Copy Agent ID, Reset Sessions, Terminate

> **Danger:** Terminate permanently shuts the agent down. Use Pause if you might want it back. See [Approvals — Board Override Powers](../day-to-day/approvals.md#board-override-powers) for the broader discussion of Pause vs Terminate vs Delete.

When the agent is in `pending_approval` status the Run Heartbeat button is disabled and a banner at the top of the page reminds you the agent cannot be invoked until the board approves the hire.

Dashboard Tab

The Dashboard is the summary view — the one you open when you want to know "what has this agent been doing?"



Latest run card

At the top, EKVAAR OS shows either the currently running heartbeat (with a pulsing live indicator and a soft glow) or the most recent finished one. The card includes:

- The run status icon (check, cross, spinner, clock, timer, slash)
- A short run ID
- An invocation-source pill: Timer, Assignment, On-demand, or Automation — so you can see at a glance why the agent ran
- A relative timestamp
- A two-to-three-line excerpt from the run's result summary, rendered as markdown

Clicking the card jumps to the run detail, same as picking the run from the Runs tab.

Activity charts

A row of four compact charts covering the last 14 days:

- **Run Activity** — runs per day
- **Issues by Priority** — the priority mix of issues this agent has touched
- **Issues by Status** — the status mix of the same set of issues
- **Success Rate** — proportion of successful heartbeats

The charts share a common 14-day window; they're designed to answer "is this agent productive?" without needing to scroll through run logs.

Recent issues

A list of up to 10 issues this agent has participated in, sorted by recency, with status badges. A **See All** link opens the full filtered issues page. Use this to pick up context before running a manual heartbeat or reassigning work.

Costs

At the bottom, a summary of the agent's total input tokens, output tokens, cached tokens, and total cost, followed by a per-run cost table for the most recent 10 runs. For a deeper view of spending — and the rules for how the numbers are computed — see [Costs & budgets](../day-to-day/costs.md).

Instructions Tab

The Instructions tab is where you edit what the agent *is* — its system prompt, role description, and any additional instruction files it should read.

![Instructions tab](../../user-guides/screenshots/light/agents/instructions.png)

Managed vs external bundles

Local adapters (Claude Code, Codex, Cursor, Gemini, OpenCode) support an **instructions bundle: a folder of markdown files that live alongside the agent's working directory. EKVAAR OS can manage that folder for you (it owns the filesystem layout) or you can point it at an existing folder on disk. The two modes are:**

- **Managed — EKVAAR OS stores the files in its own location and you edit them through the UI**
- **External — you give EKVAAR OS a `rootPath` on disk and it reads/writes the files there; useful when the instructions already live in a repo you want to keep canonical**

The mode toggle and root path field sit at the top of the tab. Changing them is a normal edit — the floating Save/Cancel bar appears as soon as the form is dirty.

The entry file

Every bundle has an **entry file, usually `AGENTS.md`. That's the file the adapter feeds to the agent on every heartbeat. Other files in the bundle are available but not automatically loaded — the entry file can link to them, reference them, or include them.**

Recommended bundle structure: AGENTS / SOUL / HEARTBEAT / TOOLS

A single monolithic `AGENTS.md` works for simple roles, but as soon as an agent is doing non-trivial strategic or operational work you'll want to split instructions across multiple files and let the entry file reference them. EKVAAR OS seeds the **CEO role with this exact pattern out of the box, and it's the pattern we recommend for any senior or long-lived agent (CTO, CMO, UX lead, department heads).**

The convention is four files:

File	Purpose	Answers the question
`AGENTS.md`	**What you do** — the operating manual. Responsibilities, delegation rules, what to do personally vs. delegate, escalation paths, safety rules. This is the entry file.	*"What's my job?"*
`SOUL.md`	**Who you are** — the persona. Strategic posture, voice and tone, decision-making philosophy, what you care about. Durable character, not tasks.	*"How should I think and speak?"*
`HEARTBEAT.md`	**How you execute** — the per-heartbeat checklist. The concrete steps to run every time the agent wakes: check identity, read today's plan, pull assignments, delegate, extract facts, exit cleanly.	*"What do I do right now, in order?"*
`TOOLS.md`	**What you can use** — notes on the tools, APIs, and skills the agent has access to. Often starts empty and grows as the agent learns.	*"What's in my toolbox?"*

`AGENTS.md` ties the other three together at the bottom with a References section:

```markdown
## References

These files are essential. Read them.

- `./HEARTBEAT.md` — execution and extraction checklist. Run every heartbeat.
- `./SOUL.md` — who you are and how you should act.
- `./TOOLS.md` — tools you have access to.
```

Why split it up?

- **Each file has one reason to change.** You tweak persona in `SOUL.md` without touching the operating procedure in `AGENTS.md`. You update the heartbeat flow without rewriting the persona.
- **The model reads what matters most first.** `AGENTS.md` is short and action-oriented; the agent pulls in `SOUL.md` or `HEARTBEAT.md` as it needs them. This keeps the entry-file context lean.
- **It mirrors how humans think about roles.** Job description, personality, daily routine, tools — four separate things, badly confused when you mash them into one file.

Writing `SOUL.md`

A good `SOUL.md` reads like a short manifesto, not a bulleted résumé. Lead with strategic posture (what this agent prioritizes and why), then voice and tone (how it writes

and speaks). Keep it under ~40 short lines — any longer and the model stops treating it as identity and starts treating it as instructions it can debate.

Good lines look like:

- *"Default to action. Ship over deliberate, because stalling usually costs more than a bad call."*
- *"Be direct. Lead with the point, then give context. Never bury the ask."*
- *"In trade-offs, optimize for learning speed and reversibility. Move fast on two-way doors; slow down on one-way doors."*

Bad lines look like:

- *"Be helpful and professional."* (too generic — no useful constraint)
- *"When handling a P0 incident, first check the dashboard, then…"* (that's a procedure, it belongs in `HEARTBEAT.md` or `AGENTS.md`)

Think: *if we hired a new human into this role, what would we want them to internalize about how this role thinks?* That's `SOUL.md`.

Writing `HEARTBEAT.md`

`HEARTBEAT.md` is a numbered checklist the agent runs top-to-bottom every time it wakes. It should be boringly mechanical — "read this, call that, check this env var, comment, exit." The CEO's default heartbeat covers:

1. Identity and context (check `EKVAAR OS_TASK_ID`, `EKVAAR OS_WAKE_REASON`, etc.)
2. Local planning check (read today's plan from memory)
3. Approval follow-up (if `EKVAAR OS_APPROVAL_ID` is set)
4. Get assignments (GET issues filtered by assignee + status)
5. Checkout and work
6. Delegation (create subtasks with `parentId` and `goalId`)
7. Fact extraction (extract durable facts to memory)
8. Exit cleanly

Tailor these steps to the role. A CTO's heartbeat might swap "fact extraction" for "review open PRs in the eng queue"; a CMO's might add "check content calendar." Keep each step short and include the exact API call or skill invocation the agent should make — this file is a script, not a philosophy.

Writing `TOOLS.md`

`TOOLS.md` often starts as a stub ("*Your tools will go here. Add notes about them as you acquire and use them.*") and grows organically. It's where you — or the agent itself — record quirks of specific tools, adapter-specific gotchas, or custom APIs the agent is expected to call. Don't worry about filling it in up front; treat it as a living notebook the agent maintains.

When the simple pattern is fine

Not every agent needs four files. A narrow-purpose worker — "summarize incoming support tickets," "post the weekly metrics digest" — can live happily in a single `AGENTS.md`. Use the multi-file pattern when any of these are true:

- The agent has a distinct personality or voice that matters (customer-facing roles, executives).
- The agent runs on a timer and does something on *every* heartbeat (anyone with a repeating checklist).
- The instructions are starting to exceed one screen and blending responsibilities, persona, and procedure.

You can always start with a single file and split later — moving sections out of `AGENTS.md` into `SOUL.md` or `HEARTBEAT.md` is a normal refactor.

How EKVAAR OS seeds these files

When you create a new agent with the **CEO role, EKVAAR OS pre-populates the bundle with the full four-file template (you'll see all four files appear in the file tree on the Instructions tab). Agents created with any other role are seeded with a single `AGENTS.md`. You can always add `SOUL.md`, `HEARTBEAT.md`, or `TOOLS.md` to any agent manually via the "New file" control — there's nothing special about those filenames beyond the convention, and the entry file is whatever you've set it to.**

Editing files

The left pane shows the file tree. Click a file to open it in the markdown editor on the right. Create a new file using the "New file" control — useful for splitting out long-form references (playbooks, example outputs, policy notes) from the short entry file. Delete a file with the trash icon. Rename is via delete + create for now.

The markdown editor supports inline image uploads (drag-and-drop or paste) — images are uploaded to the company asset store and inserted as markdown image links.

Adapters without bundles

For adapters that don't support a filesystem bundle (OpenClaw gateway and some remote providers), the instructions surface collapses to a simpler editor. The rules are the same: save commits the change, the agent picks it up on its next heartbeat.

When changes take effect

Edits are saved on **Save (via the floating Save/Cancel bar that appears on any dirty state). The agent uses the new instructions on its next heartbeat — existing runs in flight are not interrupted. If you want to see the change immediately, click **Run Heartbeat** in the header after saving.**

Skills Tab

The Skills tab controls which company skills are attached to this specific agent. It is a per-agent view over the shared [company skill library](./skills.md) — the library is where skills are authored and imported, this tab is where you decide which agents get which skills.

![Skills tab](../../user-guides/screenshots/light/agents/skills.png)

Sections on the tab

The tab splits skills into three sections:

1. **Optional company skills — every skill in the company library that this agent *could* use. Tick or untick the checkbox on each row to enable or disable it for the agent.**
2. **Required by EKVAAR OS — skills the runtime itself insists on (for example, the built-in EKVAAR OS API skill that teaches the agent how to check out tasks and post comments). These show with a locked checkbox and a tooltip explaining why they can't be turned off.**
3. **User-installed skills, not managed by EKVAAR OS — skills that already exist on disk in the agent's workspace but weren't installed through EKVAAR OS. They're displayed for visibility but can't be toggled from here. Edit them at their source (or import them into the library). This section is collapsed by default.**

Each skill row

Every row shows the skill's name, its description (the routing logic the agent uses to decide whether to load it), and, for non-managed skills, an origin and location hint so you can find the file on disk. A **View link jumps to the skill's detail page in the company library where you can edit the source.**

Autosave

Changes save automatically about 250 ms after you stop clicking — you'll see "Saving soon…" and then the indicator clears. No Save button to press.

Where skills run

The footer shows a small status block:

- **Adapter** — which runtime this agent uses
- **Skills applied** — "Kept in the workspace" (persistent), "Applied when the agent runs" (ephemeral), or "Tracked only" (the adapter doesn't support skill management from EKVAAR OS)
- **Selected skills** — the count

If the skill mode is `unsupported` (e.g. `openclaw_gateway`), the checkboxes are disabled with a tooltip directing you to manage skills in the adapter directly.

Warnings

If you toggled a skill key that no longer exists in the company library, EKVAAR OS shows an amber "Requested skills missing from the company library" warning. Either re-import the skill, or untick the missing key.

For a deeper discussion of what skills are, how to write good ones, and how they keep the agent's context small, see [Skills](./skills.md).

Configuration Tab

The Configuration tab is where you change the agent's **runtime settings** — which adapter it uses, which model it runs, what heartbeat interval it has, what environment variables it needs, and a few adapter-specific knobs. It is *not* where you change what the agent *does* (that's Instructions) or what it knows (that's Skills). It's where you change how it's wired.

The shared configuration form

The same `AgentConfigForm` you met in the hiring flow drives this tab, with two differences: the Instructions and prompt-template fields are hidden here (they live on their own tab) and the adapter-specific options are fully editable.

Common fields:

- **Adapter — dropdown of every adapter enabled for your instance. Switching adapters is a structural change and typically resets model/options to safe defaults for the new adapter. Pick deliberately.**
- **Model — the list EKVAAR OS fetched from the adapter. Some adapters (OpenCode, Gemini local) require a specific format; the form will block submission with an inline error if the model can't be validated.**
- **Working directory (cwd) — the filesystem path the adapter runs in. Relative instruction paths resolve from here.**
- **Heartbeat interval — the minimum number of seconds between automatic heartbeats. This is a floor, not a guarantee; a busy agent with many assignments may run more often if events (mentions, approvals, assignments) trigger wakes.**
- **Heartbeat enabled — toggle on/off. A disabled agent only runs on explicit event triggers or when you click **Run Heartbeat** manually.**

Adapter-specific fields (Claude login, Codex sandbox bypass, Cursor options, etc.) appear as extra rows underneath. Adapter-specific fields only modify this agent — changing them has no effect on any other agent.

API Keys section

Below the form, still on the Configuration tab, is a dedicated **API Keys block. This is the same UI described under the Keys tab below — it's embedded here because issuing a key is a configuration-time action. See [Keys](#keys) for the details.**

Configuration revisions

At the bottom of the tab is a collapsible **Configuration Revisions section. Every time you save a change to this agent's configuration, EKVAAR OS records a revision with a timestamp, the keys that changed, and a diff. Up to the most recent 10 are shown when expanded.**

Each revision row includes a **Rollback action: clicking it restores the agent to that exact configuration, atomically. Rollback is itself saved as a new revision, so you can always undo an undo.**

> **Tip: Use rollback when a change breaks an agent and you don't have time to debug. Pause the agent, roll back to the last known-good revision, resume, and investigate the bad change later.**

Save flow

Edits are dirty-tracked. A floating Save/Cancel bar (desktop) or a fixed bottom bar (mobile) appears as soon as any field differs from the persisted state. Save is blocking — you'll see "Saving…" on the button. Cancel reverts every dirty field back to its saved value in one shot.

Runs Tab

The Runs tab is your audit trail. Every heartbeat the agent has ever done is listed here, newest first, with filters, a detail view, and live streaming for runs in progress.

The run list

Each entry in the list shows:

- A status icon (succeeded, failed, running, queued, timed out, cancelled)
- A short run ID
- The run's invocation source pill (Timer / Assignment / On-demand / Automation)
- Input + output tokens and cost (when cost is non-zero)
- A relative timestamp
- A short excerpt from the result summary

On desktop, the list sits in a narrow left column and clicking a run opens the detail to the right — you can step through runs quickly without navigating away. On mobile the list takes the whole screen and tapping a run pushes into a detail view with a Back button.

EKVAAR OS auto-selects the latest run on desktop so you always have something in the detail pane when you land on the tab.

The run detail

The detail view has several stacked blocks:

- **Status & timing** — status badge, start time, end/elapsed time, duration, a Cancel button (live runs only)
- **Retry and resume controls** — failed or timed-out runs get a **Retry** action that re-wakes the agent with the same task context; runs that died because the process was lost (`errorCode = process_lost`) get a **Resume** action that picks up from the same point
- **Metrics** — input / output / cached tokens, total cost, provider, model

- **Session continuity** — the before/after session IDs the adapter used; highlighted when the session changes mid-run
- **Invocation card** — the exact command, working directory, prompt, context, and environment the adapter used, with secrets redacted (`***REDACTED***`) and JWT values masked
- **Transcript** — the full conversation between the agent and the model, rendered with tool calls inline
- **Log viewer** — raw stdout/stderr/system chunks with timestamps, useful when the transcript isn't enough
- **Touched issues** — the set of issues the agent interacted with during this run, with links and a **Clear sessions for touched issues** action (handy after a bad run corrupted session state)
- **Claude login** (Claude adapters) — a one-click "Login with Claude" action that bootstraps the adapter against a fresh Claude auth

Live runs

When a run is in-flight, the transcript and log viewer stream in real time. The header shows an animated status, an elapsed-time counter, and a cancel button. The Scroll-to-bottom helper sticks you to the latest output until you scroll up to read history, at which point it lets go so you don't get yanked around.

Cancelling, retrying, resuming

- **Cancel** — interrupts a running or queued run. The run moves to `cancelled` status.
- **Retry** — creates a new run with the same task context. Use when a run failed for a recoverable reason (transient network error, adapter glitch).
- **Resume** — only appears when a run failed because the adapter process was lost. EKVAAR OS re-wakes the agent and passes a `resumeFromRunId` so the next run can pick up instead of restarting.

Filters and sorting

The list is sorted by creation time descending. There are no additional filters on the Runs tab itself — use the Dashboard's charts for aggregate views, or jump to individual issues to see per-task run history.

Budget Tab

Every agent can have its own budget. The Budget tab is where you set it, watch the current spend, and configure how EKVAAR OS should react when limits are approached or breached.

![Budget tab](../../user-guides/screenshots/light/agents/budget.png)

Anatomy of an agent budget

A budget has four pieces:

- **Window kind — either **Monthly UTC** (spending resets on the first of each month, UTC) or **Lifetime** (never resets; the agent gets this much total, ever)**
- **Amount — the spending cap in cents (displayed as dollars)**
- **Warn percent — the soft-alert threshold, e.g. 80%. When spend crosses this, the agent moves to `warning` status and the header shows an amber indicator.**
- **Hard stop — the enforcement behaviour when spend reaches 100%. By default, EKVAAR OS pauses the agent (`pauseOnExceed = true`) so it consumes no further budget until a board user resumes it or raises the limit.**

The policy card

The card on this tab shows:

- An icon and colour corresponding to the current state (Healthy wallet, Warning triangle, Hard-stop shield)
- The window label (Monthly UTC budget / Lifetime budget)
- Current spend vs. cap, as a number and as a progress bar
- The soft-alert threshold
- Pause status and pause reason, if paused

Editing the budget

Use the edit control on the card to change the amount. Depending on your permissions and the agent's reporting chain, some fields may be read-only — in particular, subordinate agents can propose budget increases but not approve them. When a policy's hard stop is hit, a **Budget Override approval may be created for you to approve a one-time increase or a permanent raise.**

What happens at each threshold

- **Below the warn threshold — normal. The agent runs as scheduled.**
- **Between warn and hard stop — `warning` status. The agent keeps running. Consider triaging: is the agent doing what you want, or is it burning budget on low-value work?**
- **At or above the hard stop — `paused` status with `pauseReason = "budget"`. The agent stops taking heartbeats until you resume, raise the cap, or the window resets (monthly only).**

Agent-level vs company-level

This tab configures **this agent's** budget. EKVAAR OS also tracks a company-level budget that sums across agents. See [Costs & budgets](../day-to-day/costs.md) for how the two interact, how API costs are computed, and how to tune budgets as a portfolio rather than one agent at a time.

Keys

An agent authenticates to the EKVAAR OS API with a short-lived JWT for in-process runs. When the agent runs *outside* a managed heartbeat — for example a local CLI operator checking assignments, a CI job triggering a webhook, a remote adapter that needs a standing token — it uses a long-lived **API key** instead.

The Keys panel sits on the Configuration tab (under the configuration form, above the revisions collapsible).

Issuing a key

1. Type a name for the key (e.g. `production`, `ci`, `local-cli`). A clear name makes audits easier later.
2. Click **Create**.
3. EKVAAR OS shows the full token in a yellow banner. **Copy it now** — the plaintext token is only shown this once. After you dismiss the banner, EKVAAR OS only stores a hash and can never show it again.

The banner has a show/hide eye toggle so you can reveal the token to paste it, and a copy-to-clipboard button. When you're done, click **Dismiss**.

Active keys

Every un-revoked key is listed below the create form, showing its name and creation timestamp. You can see how many keys exist and when each was made — useful for rotation reviews.

Revoking a key

Click **Revoke** next to any active key. The key moves to the **Revoked Keys** section at the bottom of the panel (displayed with a strikethrough and dimmed), and is immediately rejected by the EKVAAR OS API. Revocation is permanent — revoked keys are never reused. To rotate a key, create a new one, swap it in wherever the old one is used, then revoke the old one.

Where keys flow

An agent's API key is typically set as `EKVAAR OS_API_KEY` in the adapter's environment or in the operator's shell when running the agent locally. All EKVAAR OS API requests use `Authorization: Bearer $EKVAAR OS_API_KEY`. For in-heartbeat calls by local adapters, the key is a short-lived run JWT auto-injected by EKVAAR OS — you don't need a long-lived key at all. For remote adapters and manual CLI use, you do.

> **Tip:** Revoke keys aggressively. It's cheaper to issue a new one than to wonder whether a forgotten key is floating around.

How Agents Are Invoked — The Heartbeat Model

This section collects the conceptual material you need to reason about what an agent *is* at runtime. If you've read other EKVAAR OS guides you may have seen pieces of this; everything is gathered here so the agent surface above makes sense.

Execution model

Every heartbeat follows the same six-step arc:

1. **Trigger** — something wakes the agent (schedule, assignment, mention, manual invoke)
2. **Adapter invocation** — EKVAAR OS calls the agent's configured adapter
3. **Agent process** — the adapter spawns the agent runtime (e.g. Claude Code CLI)
4. **EKVAAR OS API calls** — the agent checks assignments, claims tasks, does work, updates status
5. **Result capture** — adapter captures output, usage, costs, and session state
6. **Run record** — EKVAAR OS stores the run result for audit and debugging

Each of those steps corresponds to something visible in the Runs tab: the trigger shows up as the invocation source pill, the adapter invocation is the Invocation card, the agent process is the transcript and logs, the API calls appear in the touched-issues list, the result capture populates the metrics block, and the run record is the run itself.

Agent identity

Every agent has environment variables injected at runtime:

Variable	Description

`EKVAAR OS_AGENT_ID`	The agent's unique ID
`EKVAAR OS_COMPANY_ID`	The company the agent belongs to
`EKVAAR OS_API_URL`	Base URL for the EKVAAR OS API
`EKVAAR OS_API_KEY`	Short-lived JWT for API authentication
`EKVAAR OS_RUN_ID`	Current heartbeat run ID

Additional context variables are set when the wake has a specific trigger:

Variable	Description
`EKVAAR OS_TASK_ID`	Issue that triggered this wake
`EKVAAR OS_WAKE_REASON`	Why the agent was woken (e.g. `issue_assigned`, `issue_comment_mentioned`)
`EKVAAR OS_WAKE_COMMENT_ID`	Specific comment that triggered this wake
`EKVAAR OS_APPROVAL_ID`	Approval that was resolved
`EKVAAR OS_APPROVAL_STATUS`	Approval decision (`approved`, `rejected`)

These are exactly what you'll see in the Invocation card on any run — EKVAAR OS redacts secrets (anything that looks like an API key, a bearer token, a password, or a JWT) before displaying them, but the structure is the same as what the agent actually received.

Session persistence

Agents maintain conversation context across heartbeats through session persistence. The adapter serializes session state (e.g. Claude Code session ID) after each run and restores it on the next wake. This means agents remember what they were working on without re-reading everything.

On the Runs tab, each run shows a **session ID before** and **session ID after**. A differing pair means the session rotated during the run; an equal pair means the agent continued the same conversation. The overflow menu's **Reset Sessions** action wipes this state when you want the agent to start fresh on its next heartbeat.

Agent status

Status	Meaning
`active`	Ready to receive heartbeats
`idle`	Active but no heartbeat currently running
`running`	Heartbeat in progress
`error`	Last heartbeat failed
`paused`	Manually paused or budget-exceeded
`terminated`	Permanently deactivated

The status dot on every row and badge on the agent header reflect one of these values directly. The **Active filter on the agent list expands to include `active`, `running`, and `idle`, because all three mean "this agent is healthy and doing (or ready to do) work". **Paused** and **Error** are their own filters for triage.**

Why this matters day-to-day

The heartbeat model has a few practical consequences worth keeping in mind:

- **An agent that isn't doing work isn't costing you anything (past whatever the last run spent). Between heartbeats there's no idle burn.**
- **Changing configuration takes effect on the next heartbeat, not the current one. If you edit Instructions while a heartbeat is running, that run uses the old instructions. The next run uses the new ones.**
- **Manual Run Heartbeat is your friend when testing changes. Save your edit, click Run Heartbeat, watch the live run stream in the Runs tab. Much faster than waiting for the timer.**
- **Paused agents are cheap. If you're not sure whether to keep an agent, pause it. It will stop accumulating spend and its history is preserved for when you come back.**

Common Workflows

A few end-to-end recipes for things you'll do often.

Try a new instruction quickly

1. Open the agent and go to the **Instructions tab.**
2. Edit the entry file (usually `AGENTS.md`). Save.
3. Click **Run Heartbeat in the header.**
4. Switch to the **Runs tab. The new run is selected automatically on desktop; on mobile tap it from the list.**
5. Watch the transcript stream. If the agent behaves as you want, you're done. If not, repeat.

This loop is tight on purpose — changes apply on the next heartbeat, and manual invoke gives you that heartbeat on demand.

Diagnose a misbehaving agent

1. Open the **Runs tab, find the most recent failed run.**
2. Read the transcript for where the agent got confused.

3. Open the **Invocation** card to confirm it received the right environment, working directory, and instruction path.
4. Check **Touched issues** — did it actually work on what it was supposed to?
5. If the session is bad, use **Clear sessions for touched issues** or the overflow menu's **Reset Sessions**.
6. If the configuration is at fault, roll back on the **Configuration** tab.

Temporarily mute an agent

1. Click **Pause** in the header. Status moves to `paused` and no further heartbeats will run.
2. Investigate at your leisure. The agent's history is preserved.
3. Click **Resume** when ready.

Use pause liberally — it's reversible, cheap, and the right default when something is clearly off but you don't have time to debug.

Rotate an API key

1. Open the **Configuration** tab, scroll to **API Keys**.
2. Click **Create**, name the new key (e.g. `production-2026-04`), copy the token shown in the yellow banner.
3. Swap the new token into whatever system was using the old one.
4. Back on the Keys panel, click **Revoke** next to the old key.
5. Confirm the revoked key moves to the bottom **Revoked Keys** section.

Raise a capped agent's budget

1. Open the **Budget** tab. The policy card shows current status, spend, and pause reason.
2. Edit the amount on the policy card.
3. If the change is within your authority, it saves immediately. If the agent is subordinate and an override is required, a Budget Override approval is created — see [Approvals](../day-to-day/approvals.md).
4. Once the cap is raised and the agent is off hard-stop, click **Resume** in the header if it was paused by budget.

Related guides

- [Skills](./skills.md) — how the company skill library works, how skills are written, and how they keep agent context lean

- [Agent adapters](./agent-adapters.md) — which adapters are available, what each one is good at, and how to configure them
- [Approvals](../day-to-day/approvals.md) — the governance layer around hire requests, strategy, and budget overrides
- [Costs & budgets](../day-to-day/costs.md) — how API spend is computed, how budgets are enforced, and how to tune them across your whole company

Skills

When you want an agent to follow a specific procedure — a code review checklist, a deployment runbook, a customer response template — you could put those instructions in the agent's main configuration. But if you want multiple agents to use the same procedure, or want to keep agent configurations lean and focused, that's where skills come in.

A skill is a reusable instruction document that agents can load on demand. Instead of baking every procedure into every agent's configuration, you write a skill once in the company skill library and make it available to any agent that needs it. The agent reads the skill's description when it starts a task, decides whether the skill is relevant, and loads the full instructions only when it needs them.

What a skill looks like

A skill is a folder containing a `SKILL.md` file. The file has a short frontmatter block (the routing description) and a body (the actual instructions).

```
skills/
└── code-review/
    ├── SKILL.md
    └── references/
        └── examples.md
```

The frontmatter description is what the agent reads first — it's written as decision logic so the agent knows when to use this skill:

```markdown
---
name: code-review
description: >
  Use when asked to review a pull request or code diff.
```

Don't use when writing new code from scratch.

Code Review

When reviewing code, check the following...
```

The agent sees the name and description for every available skill at the start of its heartbeat. If the description matches what the agent is doing, it loads the full skill content and follows the instructions.

Why this matters for performance and cost

Skills keep the base context small. An agent with 10 skills doesn't load all 10 into its context on every heartbeat — it only loads the ones that are relevant to the current task. This means:

- Fewer tokens consumed per run (lower cost)
- Cleaner, more focused context for the agent (better results)
- Easier to maintain — update a skill in one place, all agents benefit

---

Adding a skill

Skills are managed from the company-level **Skills page. The page has a left-hand list of every installed skill and a right-hand pane that shows the selected skill's files, description, and usage. Two controls live above the skill list: a filter box to search by name, key, slug, or source, and an input where you can paste a source string to import a skill from elsewhere.**

You can add a skill in one of four ways, depending on where it is coming from.

1. Import from a GitHub repository

Paste a GitHub URL (or a `skills.sh` install command) into the source field at the top of the Skills page and press **Add. EKVAAR OS clones the skill folder, detects the `SKILL.md`, and registers it in the library. GitHub-sourced skills are pinned to a specific commit — you can check for updates and upgrade the pin from the skill detail pane.**

![Add skill dialog with the source input, search button, and link to skills.sh](../../user-guides/screenshots/light/skills/add-skill-dialog.png)

2. Import from a gist

Gists work through the same source field. Paste the gist URL and EKVAAR OS treats it like a remote file source — useful when you want to share a one-off procedure without setting up a full repository.

3. Import from a local file or folder

You can also paste a local path (Linux, WSL, or Windows) into the source field. EKVAAR OS walks the folder, finds any `SKILL.md` files, and imports them. This is the right choice when you already keep skills in a project workspace on disk — the scan button (circular arrow next to the plus icon) re-runs the local import across every project workspace in the company so newly added `SKILL.md` folders show up automatically.

4. Import from the skills.sh marketplace

skills.sh is a community catalog of ready-made skills. Each listing provides a copy-ready install command; paste it into the source field and EKVAAR OS imports the skill along with its source metadata (you will see a small skills.sh badge on the skill row).

Creating a skill from scratch

If none of those sources apply, click the **+ button next to the scan icon. A small form appears inline with three fields:**

- **Skill name — the human-readable name shown in the list.**
- **Optional shortname / slug — the `kebab-case` key the agent uses to reference this skill. If you leave this blank, EKVAAR OS derives it from the name.**
- **Short description — the routing logic ("Use when… Don't use when…") the agent reads before loading the skill body.**

Click **Create skill and the skill is added to the library as a EKVAAR OS-managed, editable entry.**

The skill is now available in the company library. When creating or editing an agent, you can attach optional skills from that library.

![Skills page showing available skills with their names and descriptions](../../user-guides/screenshots/light/org/skills-list.png)

Install a ready-made skill from the built-in catalog

You don't have to write every skill from scratch. EKVAAR OS ships with a built-in **catalog** of ready-made skills you can browse and install with a click — a head start for common procedures.

The catalog comes in two flavours:

- **Bundled** skills are the everyday kit — things like keeping docs maintained, triaging issues, planning tasks, running QA acceptance, managing a GitHub PR workflow, and sketching low-fidelity UI **wireframes**.
- **Optional** skills are extras you add when you need them — for example, browser-driving an agent, drafting a release announcement, running a design critique, or researching what people have said about a topic in the last 30 days.

The catalog isn't only for engineers. Design, product, and research roles get a head start too: the `wireframe` skill, for instance, lets an agent draft black-and-white, low-fidelity screen layouts as SVG files before anyone commits to building the real thing — handy for a designer or product agent who wants to show structure first — and the `last30days` skill pulls recent posts and engagement from across the web so a researcher or marketer can see what people are actually saying about a topic right now. "Bundled" doesn't mean "forced on everyone": you still browse, pick, and install the ones you want.

A few catalog skills aren't shipped inside the app at all — they're pulled from an external repository pinned to a specific version. You install and update them the same way; EKVAAR OS just fetches the files on your behalf. Either way the app knows the exact version you have, so the keep-it-current, audit, and reset features below work for every catalog skill.

Browse the catalog, pick a skill, and install it into your company library. Installing puts the skill in the library only — it doesn't attach it to any agent, so you stay in control of who uses it. From there it behaves like any other installed skill: open it, read its `SKILL.md`, and assign it to the agents that need it.

Because these skills come from EKVAAR OS, the app knows exactly which version you installed. That means a catalog skill can be **kept up to date**: EKVAAR OS can check whether a newer version shipped and install the update, audit the skill's contents for safety before you trust it, and reset the skill back to its original shipped version if it was edited locally. For the mechanics of installing, updating, auditing, and resetting catalog skills, see the [Skills reference](../../reference/skills.md#3-app-shipped-catalog).

File inventory

Every skill is a folder, not a single file. Expanding a skill in the sidebar reveals its **file inventory** — the full tree of files underneath the skill's root. The inventory pinpoints each file with a few pieces of metadata that matter in practice:

- **Entry file** — the top-level `SKILL.md` that agents read first. It is always sorted to the top of the tree and contains the skill's frontmatter (name, description) plus the instructions body.
- **Other files** — subfolders such as `references/` or `scripts/` hold supporting material (examples, style guides, helper scripts). The file kind icon tells you at a glance whether each leaf is markdown, a reference document, or a script.
- **Editable** — a skill is editable only when EKVAAR OS controls its source. Skills imported from GitHub, gists, or the skills.sh catalog are **read-only**: you can view any file but cannot save changes; the detail pane shows an explanation badge instead of an Edit button. EKVAAR OS-managed and local-folder skills open in the Markdown editor when you click **Edit**.
- **Deprecated** — when a skill is retired, it is marked deprecated in the library and hidden from agent skill menus. Existing agents keep working until you detach the skill from them.
- **Virtual** — some entries in the inventory are virtual: they represent content the adapter synthesises at runtime (for example, materialised runtime skills for adapters that do not support skills natively). Virtual entries are tagged in the row and cannot be edited directly.

The header above the file viewer shows:

- The **Source** badge (skills.sh, GitHub, local folder, or EKVAAR OS) with the source label — clicking the label copies the path to the workspace when applicable.
- The **Pin** for GitHub-sourced skills — the short commit SHA EKVAAR OS is locked to, plus a **Check for updates** button and, when an update exists, an **Install update** action.
- The skill **Key** (the stable identifier adapters use).
- The **Mode** — Editable or Read only.
- **Used by** — the list of agents currently attached to this skill.

Adapter sync preferences

Different adapters handle skills differently. The Agent → Skills tab surfaces this as a **skill application mode** just above the skill list:

- **Kept in the workspace** (`persistent`) — the adapter writes skill files into the agent's workspace directory and leaves them there between runs. Most long-running local adapters use this mode.
- **Applied when the agent runs** (`ephemeral`) — the adapter materialises skill files for each run, then cleans up afterwards. This is the default for sandboxed adapters that treat the workspace as disposable.
- **Tracked only** (`unsupported`) — EKVAAR OS cannot push skills into the adapter, so it only records which skills you have assigned. Adapters like `openclaw_gateway` fall into this category; you will see a banner directing you to manage skills inside the remote runtime (for example, OpenClaw) rather than from EKVAAR OS.

Assignments still save regardless of mode — the mode only controls whether EKVAAR OS physically syncs the skill files. Warnings surface in an amber banner when, for example, a desired skill is missing from the company library or the adapter rejected a sync.

Assigning a skill to an agent

Skills live at the company level, but each agent decides which of those skills to use. To assign or remove skills for an agent:

1. **Open the agent's detail page** from the Agents list or the org chart.
2. **Switch to the Skills tab.**
3. You will see three groups:
   - **Required skills** — entries the adapter marks as mandatory. You cannot disable these.
   - **Optional skills** — every skill in the company library that the agent *could* use. Each row has a checkbox; tick it to assign the skill, untick to detach.
   - **Unmanaged skills** — read-only rows for skills the adapter picked up from somewhere EKVAAR OS does not control (for example, a global skill bundle on the host). These are shown for visibility only.
4. Changes autosave about 250 ms after you stop clicking — the small "Saving soon..." / "Saving changes..." indicator in the top-right confirms when EKVAAR OS has persisted the update. The agent will pick up the new skill list on its next run.

A **View company skills library** link at the top of the tab jumps back to the company-wide Skills page, so you can open the underlying skill to tweak its instructions without leaving context.

> **Tip:** If a skill you expect is not in the optional list, it is not in the company library yet. Add it from the Skills page first, then come back.

Trust level

Skills are loaded into agent runs as additional instructions, so where they come from matters. EKVAAR OS uses the **Source** badge on every skill row to make that provenance obvious:

- **EKVAAR OS-managed** — authored inside EKVAAR OS. You have full control of the contents; these are the safest skills to give an agent.
- **Local folder** — pulled from a project workspace on the same machine. Trust level matches whatever you trust the folder itself with.
- **GitHub / skills.sh** — pinned to a specific commit or release. The pin means the skill body cannot change underneath you without an explicit **Install update** from the detail pane, so you get a second chance to review diffs before they hit your agents.
- **Gist / URL** — point-in-time imports of external content. Treat these like any third-party code: review the body before you attach the skill to an agent.

Before attaching a skill to a high-trust role (your CEO, a finance agent, an operator with access to secrets), open the skill and read its `SKILL.md` end-to-end. The **Used by** list on the detail pane makes it easy to audit which agents are already exposed to a given skill.

What makes a good skill

Write the description as routing logic. The description is not a marketing pitch — it's the signal the agent uses to decide whether to load the skill. Include "Use when" and "Don't use when" guidance.

Be specific and actionable. The agent should be able to follow the skill without guessing. Vague instructions ("review the code carefully") produce vague output. Concrete checklists and steps produce consistent results.

Include examples where they help. Code snippets, example outputs, before/after comparisons — concrete examples are more reliable than abstract descriptions.

Keep each skill focused on one concern. A skill that covers code review, deployment, and customer communication is three skills fighting for attention. One skill, one purpose.

Put supporting detail in `references/`. If a skill needs supporting documents — style guides, example files, reference material — put them in a `references/` subfolder rather than cramming everything into `SKILL.md`.

Skills across agents

Skills live at the company level, not inside one specific agent. This means:

- Your CTO and Backend Engineer can share a `code-review` skill without duplicating it
- Your CEO can use a `delegation-checklist` skill that your CMO also uses for their own task breakdown
- Updating a skill improves all agents that use it at once

You can also scan and import skills from project workspaces when you already have skill files on disk. That's useful for teams migrating existing `SKILL.md` folders into the EKVAAR OS library.

Working with skills programmatically

Most of the time you will manage skills from the UI, but the same operations are available as REST endpoints when you want to script onboarding or reproduce a known agent setup from another company.

- **List the skills attached to an agent**: `GET /api/agents/{agentId}/skills`
- **Sync the attached set**: `POST /api/agents/{agentId}/skills/sync` with `{ "desiredSkills": [...] }`. Each entry is a skill UUID, canonical key, or unique slug. The server reconciles attachments to match — adding any missing and removing any not in the list.
- **Provision skills at hire time**: pass `desiredSkills` on `POST /api/companies/{companyId}/agents` so the agent comes online with the right set already attached.

The skills must already be installed at the company level before you can attach them. For the full reference — file shape, install pipeline, canonical keys, versioning, and troubleshooting — see:

- [Skills reference](../../reference/skills.md) — everything about how skills work on disk and over the wire.
- [Agents API → Skills](../../reference/api/agents.md#skills) — request/response shapes for the agent-level routes.

You're set

Skills give your agents reliable, reusable procedures that improve consistency and reduce cost. The next guide covers export and import — how to back up, share, and reuse company configurations.

[Export & Import →](../power/export-import.md)

Team Catalog

Setting up a company from an empty page is a lot of decisions: which agents to hire, who reports to whom, what projects to open, what recurring work to schedule, and which skills each agent needs. The **Team Catalog skips that blank-page problem. It's a set of ready-made starter teams — small, working groups of agents, projects, tasks, and skills — that you can browse and install into a company in one step.**

Where a [skill](./skills.md) is one reusable procedure, a *team* is a whole unit of people and work. Install one and you get the agents, the org structure between them, the projects they work in, the recurring tasks that keep them moving, and the skills they rely on — all wired together the way a working team would already have them.

Bundled vs optional teams

The catalog comes in two flavours, and the same install flow covers both.

- **Bundled teams ship inside the app and are the everyday starting points. They lean on skills EKVAAR OS already knows about, so installing one is self-contained. Examples shipping today: a **core executive team** (a CEO, CTO, and QA with a starter project and a recurring CEO heartbeat task), a **product-engineering** pod (CTO, Senior Coder, QA, and a weekly engineering sync), and a **product-design** team (a UX designer with the `wireframe` and `design-critique` skills and a weekly design review).**
- **Optional teams are extras you reach for when a specific need shows up — for example a content team that brings its own content-calendar skill and a recurring weekly content review. Some optional teams pull skills from external sources (GitHub, a URL, or skills.sh), which is why installing them asks you to opt in to those sources explicitly.**

"Bundled" doesn't mean forced on you. You still browse, pick, and install only the teams you want — nothing lands in a company until you install it.

Why you'd use one

A catalog team is the fastest way to get a company doing real work:

- **Start from a sensible default. The core executive team mirrors the shape most companies end up with anyway — a leader, a builder, and a checker — so you're productive immediately instead of hiring agents one at a time.**
- **Add a capability, not just an agent. Need engineering? Install the product-engineering pod and you get the roles, the reporting lines, the project, the weekly sync, and the right skills together, not a lone agent you then have to configure.**
- **Keep your org chart intact. When you install a team into a company that already has people, you can point the team's leaders at an existing manager so the new group slots in underneath them rather than floating on its own.**

Browse and install from the app

Open the **Team Catalog page to see the available teams, filter by bundled or optional, and read what each one contains before you commit. Selecting a team shows its agents, the projects and tasks it sets up, and the skills it needs — the same detail the CLI's `inspect` prints. If a team is already installed in the company, the catalog marks it as installed, and flags it when your installed copy has fallen behind a newer catalog version.**

Installing is a two-look process by design. First you **preview: EKVAAR OS runs the import on the server and shows you exactly what would be created and which skills it would prepare, without writing anything. When the plan looks right, you **install**, and the team's agents, projects, tasks, and skills are created in the company.**

A few choices happen at install time:

- **Who they report to. You can attach the team's root agents to an existing manager so the new team joins your org chart instead of standing alone.**
- **Which runtime each agent uses. Catalog teams ship without a fixed adapter per agent on purpose, so the install lets you choose — for example a local Claude or Codex runtime — rather than locking you in.**

- **External skill sources. If an optional team declares GitHub, URL, or skills.sh skills, you opt in to those sources during install. Bundled teams that only use catalog skills need no opt-in.**
- **Secrets. If a team's agents need a secret value (an API key, say), the install collects it as a secret env input.**

What gets created when you install

Installing a team is a single action that builds out several things at once:

- **Agents — every agent the team defines, with its role, prompt, and place in the reporting hierarchy. The team's root agents either stand on their own or report to the manager you picked.**
- **Projects — the workspaces the team operates in, so its agents have somewhere to do the work.**
- **Tasks — including any recurring routines the team ships, such as a CEO heartbeat or a weekly sync, imported the same careful way EKVAAR OS imports any routine.**
- **Skills — the team's required skills are prepared in the company library: catalog skills are installed for you, and external-source skills are imported once you've allowed their sources.**

Because every catalog team carries a version, EKVAAR OS knows which version you installed. The catalog flags a team as out of date when a newer version has shipped, so you can reinstall the updated team when you're ready.

A note on permissions

Installing a team creates agents, which requires permission to do so. If you (or an agent acting on your behalf) install a team without that permission, the action can fall back to a **board approval request rather than simply failing — a board operator then reviews and approves the install. Any secrets you supplied are stripped from the stored request, so they're never exposed in the approval.**

Do it from the terminal

Everything above is available from the CLI too, which is handy for scripting a known company setup or reproducing one elsewhere.

```sh
# Browse and inspect
EKVAAR OSai teams browse --kind bundled
EKVAAR OSai teams inspect core-exec-team

# Preview, then install into a company
EKVAAR OSai teams preview core-exec-team --company-id <company-id>
EKVAAR OSai teams install core-exec-team --company-id <company-id>
```

For every command, flag, and the permission-fallback details, see the [Teams CLI reference](../../reference/cli/teams.md).

See also

- [Teams CLI reference](../../reference/cli/teams.md) — the full `teams` command surface.
- [Skills](./skills.md) — the single-capability catalog that catalog teams build on.
- [Org structure](./org-structure.md) — how reporting lines work, which catalog teams plug into.
- [Agents](./agents.md) — configuring the agents an install creates.

Building Your Org Structure

Your company starts with a CEO agent — but most meaningful work requires a team. Org structure in EKVAAR OS is the reporting hierarchy that tells every agent who their manager is, who delegates work to them, and who they escalate blockers to. Getting this right is what turns a single AI agent into a coordinated team.

Why org structure matters

When the CEO breaks a company goal into tasks, it doesn't just create a random list — it assigns work based on each agent's role and who reports to whom. A task that needs engineering goes to the CTO or a backend engineer. A content task goes to a marketing agent. The hierarchy is how the CEO knows who to ask.

Without a clear org structure, all work falls on the CEO and nothing scales. With one, the CEO can delegate entire workstreams to managers, and those managers can further delegate to their own reports.

How it works

EKVAAR OS enforces a strict tree structure. Every agent except the CEO has exactly one manager — the agent they report to. The CEO sits at the top and reports to you, the board.

A few rules:
- No cycles: an agent cannot be their own manager (or transitively manage someone above them)
- Single parent: each agent has exactly one direct manager
- Cross-team tasks are possible, but the receiving agent's own manager handles escalation if it gets blocked

---

Common org structures

Solo CEO (getting started)

Your first company will look like this:

```
CEO
```

This is fine while you're learning how EKVAAR OS works. The CEO handles everything itself. Once you're ready to scale, add managers.

Small team

Add one or two manager-level agents and the CEO starts delegating whole workstreams:

```
CEO
├── CTO
└── CMO
```

The CEO creates engineering tasks and assigns them to the CTO. Marketing tasks go to the CMO. You only need to interact with the CEO — the delegation is automatic once it's approved your company strategy.

Scaled team

Add workers under managers for the CEO to delegate further:

```
CEO
├── CTO
│   ├── Backend Engineer
│   └── Frontend Engineer
└── CMO
    └── Content Writer
```

The CEO breaks goals into high-level tasks for the CTO and CMO. They create subtasks for their own reports. Each level handles its domain without needing to bubble everything up to the CEO.

> **Tip:** You don't have to build this out all at once. Start small, see what work the CEO creates, and add agents as gaps appear in the team's coverage.

Adding a manager

Manager-level agents (CTO, CMO, Head of Design, etc.) report directly to the CEO and in turn manage a team of workers. Here's how to add one:

1. **Go to the Agents page and click "New Agent"**

   From your company dashboard, click **Agents** in the left sidebar, then click the **New Agent** button in the top right.

   ![Agents list page showing the New Agent button](../../user-guides/screenshots/light/agents/agents-list-empty.png)

2. **Set the name, title, and role**

   Give the agent a clear name (e.g. "Sam"), a title (e.g. "CTO"), and choose the closest role. The role helps the CEO understand what this agent is responsible for when assigning work.

   ![New agent form with name and role fields](../../user-guides/screenshots/light/agents/new-agent-name-role.png)

3. **Set "Reports to" to the CEO**

In the **Reports to** dropdown, select your CEO agent. This places the new agent one level below the CEO in the hierarchy.



4. **Choose an adapter and save**

Configure the adapter (see [Agent Adapters](./agent-adapters.md) if you need help with this step). Click **Create agent**.

The new agent now appears in the org chart under the CEO, and the CEO will start considering them when delegating work. You can set the agent's budget afterward on its **Budget** tab.

Adding workers

Workers report to a manager rather than directly to the CEO. The steps are identical to adding a manager, but you set **Reports to** to a manager-level agent instead of the CEO.

For example, to add a Backend Engineer who reports to your CTO:

1. Click **New Agent**
2. Name: "Jordan — Backend Engineer", role: `backend_engineer`
3. **Reports to**: select your CTO agent
4. Configure the adapter, then **Create agent**

The CTO can now delegate subtasks to Jordan. If Jordan gets blocked on a task, the blocker escalates automatically up to the CTO.

Changing an agent's manager

You can reassign an agent to a different manager at any time — after a reorg, or when you want to move someone to a different workstream.

From the agent's detail page, click **Configuration**, then change the **Reports to** field. The change takes effect immediately. Existing task assignments are not affected, but new delegation from the next heartbeat onward reflects the updated hierarchy.

Viewing the org chart

Click **Org in the left sidebar. You'll see a visual tree of all your agents with their current status shown inline.**

![Org chart view showing the full reporting hierarchy with agent status indicators](../../user-guides/screenshots/light/org/org-chart-small-team.png)

The org chart view

The Org page renders your company as an **interactive tree. Each agent is shown as a card at the position its reporting line dictates — the CEO sits at the top, managers fan out below it, and individual contributors sit under their managers. Lines between cards are the reporting relationships; they always point from manager down to report.**

The card itself surfaces everything you usually need at a glance:

- Agent **icon with a small coloured **status dot** (green for active, yellow for paused or idle, red for error, cyan for running, grey for terminated).**
- The agent's **name and **title** (or a humanised role label when no custom title is set).**
- The **adapter type in a small mono font — useful when auditing which adapters your org relies on.**
- A **capabilities snippet: the first couple of lines of the agent's capabilities description.**

Two companion buttons live above the chart: **Import company and **Export company**, which take you to the import/export flows when you want to share or clone an org.**

![Interactive org chart showing the CEO at the top with managers and workers connected by reporting lines](../../user-guides/screenshots/light/org/chart.png)

Navigating the chart

The chart area supports full pan and zoom:

- **Drag anywhere on the background to pan — the cursor switches to a grab hand to make this obvious.**

- **Scroll / pinch to zoom in and out. Zoom anchors to the mouse position, so you can lean into a specific team without losing your place.**
- Use the **+, **–**, and **Fit** buttons in the top-right corner for precise zoom control. **Fit** recentres the whole chart inside the viewport, which is handy after a reorg when the tree has grown off-screen.**
- **Click a card to open the full agent detail page. Dragging on a card does not pan — clicks are always routed to the agent.**

For the text-only reporting view, the sidebar **Org entry also exposes a collapsible tree (used by screen readers and by anyone who prefers a compact outline). The two views share the same underlying hierarchy; changes made in one appear in the other immediately.**

Reassigning an agent via the chart

You can reassign any agent to a different manager without leaving the chart. The flow is:

1. **Click the card of the agent you want to move. The chart opens the agent's detail page.**
2. **Switch to the Configuration tab and change the **Reports to** field to the new manager.**
3. **Save. The reporting line is updated immediately, and when you return to the Org page, the card re-parents under the new manager. Existing task assignments are unaffected — only future delegation follows the new line.**

![Agent configuration with the Reports to dropdown expanded, selecting a new manager](../../user-guides/screenshots/light/org/reassign.png)

A few guardrails apply:

- You cannot assign an agent to a manager that reports to it (no cycles).
- You cannot remove the CEO's own reporting line — the CEO always reports to the board.
- Reassigning a manager with reports moves the whole subtree under the new parent; the reports themselves keep their own reporting lines.

> **Tip: If you are doing a bigger reorg (swapping teams between two managers, for example), open the Org page in one tab and the agent configuration in another. The chart refreshes automatically when you save, so you can use it as a live preview of the new structure.**

Reporting lines visualization

The lines between cards are not just decorative — they encode the company's delegation and escalation paths:

- Every line points from a **manager** (top) to a **direct report** (bottom). The direction of the line mirrors how work and escalations travel: delegation flows down, status and blockers flow up.
- **Multiple children** share a horizontal connector below the manager card so you can see the span of control at each level.
- **Separate subtrees** mean separate reporting lines. If you ever end up with more than one root, it usually means an agent lost its manager (for example, after a termination) — fix it from the agent's configuration by setting **Reports to** again.
- **Terminated agents** appear with a grey dot and faded styling. They stay on the chart as a historical record until you remove them.

Because the chart is the single source of truth for reporting structure, it is the fastest way to spot structural issues: a manager with far too many reports, a worker orphaned without a manager, or an adapter concentration risk where too much of the org runs on the same adapter.

How delegation flows once the team is in place

Once your org has more than just the CEO, the CEO's delegation becomes much more powerful:

1. You approve the CEO's strategy
2. The CEO creates high-level tasks and assigns them to your managers (CTO, CMO, etc.)
3. Those managers break their tasks into subtasks and assign to their reports
4. Workers execute, post updates in task comments, and mark tasks done
5. Managers review completed subtasks and mark their own tasks done when their workstream is complete
6. The CEO monitors the whole chain and reports progress back to you

Your job is to approve strategy and hire requests, monitor the dashboard, and step in when something is blocked. The delegation chain handles the rest.

You're set

You now know how to build and manage your org structure. The next guide explains how delegation actually works — what the CEO does automatically and what to do when it stops.

[Delegation →](./delegation.md)

Delegation

One of the most powerful things about EKVAAR OS is that you don't have to manage work directly. You set a goal, approve a plan, and the CEO automatically breaks that goal into concrete tasks and assigns them to the right agents. This is delegation — and understanding how it works helps you know when to act and when to let the system run.

How automatic delegation works

When you set a company goal, the CEO doesn't just acknowledge it and wait. On its next heartbeat, it reads the goal, forms a strategy, and submits it to your approval queue. Once you approve, delegation begins:

```
You set a company goal
↓
CEO wakes on heartbeat
↓
CEO proposes strategy → You approve
↓
CEO creates tasks and assigns them to reports
↓
Reports wake (triggered by the assignment)
↓
Reports execute + post updates in task comments
↓
CEO monitors progress + escalates blockers to you
```

Each step is traceable. Every task links back to the company goal through a parent hierarchy, so you can always see why work is happening.

What you do vs what the CEO handles

What you do	What the CEO does automatically
Set the company goal	Break the goal into tasks
Approve strategy proposals	Assign tasks to the right reports
Approve hire requests	Create subtasks when work needs more granularity
Monitor the dashboard	Hire new agents when the team lacks capacity (pending your approval)
Review completed work	Monitor progress each heartbeat
Intervene when things stall	Escalate blockers to you when it can't resolve them

Your role is strategic oversight, not task management. You set the direction and make the decisions the system can't make for you. Everything else runs autonomously.

Approving the strategy

After you set a company goal, the CEO's first action is almost always to submit a strategy proposal. This is its plan for how to achieve the goal — the workstreams it proposes, the hires it might need, the first set of tasks it will create.

You'll see this in the **Approvals** page as a `strategy` type approval.

When reviewing a strategy:
- Does the plan reflect what you actually want done?
- Are the workstreams reasonable and prioritised correctly?
- Does the hiring plan make sense for the scope?

If the plan looks right, approve it. If not, click **Request Revision** and describe what needs to change. The CEO reads your comment, revises the plan, and resubmits. You can go back and forth as many times as needed before approving.

> **Tip:** Don't approve a strategy that feels unclear or off-track just to get things moving. A vague approval leads to vague work. It's worth a round of revisions.

Approving hire requests

When the CEO determines it needs more capacity — a CTO for engineering work, a CMO for marketing — it submits a `hire_agent` approval. This appears in your approval queue

with the proposed agent's full configuration: name, role, capabilities, adapter, budget, and who they'll report to.

Review each hire request on its merits:
- Does the role match the work that needs doing?
- Is the proposed budget reasonable for that agent's workload?
- Does the agent report to the right manager?

If anything looks off, request a revision. If it looks good, approve. Once you approve, EKVAAR OS creates the agent and queues it to wake automatically.

> **Warning:** Approving a hire creates a new agent and starts spending budget. Only approve hire requests when you're ready for the agent to start working.

Common delegation patterns

Small team: direct delegation

With 3–5 agents, the CEO delegates directly to each report without another management layer:

```
CEO
├── CTO        (engineering tasks)
├── CMO        (marketing tasks)
└── Designer   (design tasks)
```

Each agent works independently on their assigned tasks and posts updates. The CEO monitors and reassigns if needed.

Larger team: cascading delegation

With more agents, managers delegate further down the chain:

```
CEO
├── CTO
│   ├── Backend Engineer
│   └── Frontend Engineer
└── CMO
    └── Content Writer
```

```

The CEO assigns high-level tasks to the CTO and CMO. They break those down and assign subtasks to their own reports. You only interact with the CEO — the rest runs automatically.

### Hire-on-demand

You can start with just the CEO and let the team grow naturally as the CEO identifies what capacity it needs:

1. Set a goal that needs both engineering and marketing
2. The CEO proposes a strategy that includes hiring a CTO and CMO
3. You approve the hires
4. The CEO delegates to the new managers
5. As scope grows, the managers may request to hire their own reports

This lets you start small and scale the team based on actual work, not upfront planning.

---

## Troubleshooting: CEO isn't delegating

If you've set a goal but nothing seems to be happening, work through these common causes:

### No tasks are being created

| Check | What to look for |
|---|---|
| **Approval queue** | Is there a strategy approval waiting for your review? This is the most common reason — the CEO has submitted a plan and is waiting for sign-off. |
| **Goal is set** | Go to the Goals section of your company. If no goal exists, the CEO has nothing to work from. |
| **CEO heartbeat** | Is the CEO's heartbeat enabled? Go to the CEO's detail page and check that the heartbeat toggle is on and that recent runs appear in the **Runs** tab. |

### CEO isn't assigning to reports

| Check | What to look for |
|---|---|
| **Reports have heartbeats** | Go to each agent's detail page. If heartbeats are disabled, the CEO may skip assigning to them since they won't be able to pick up work. |
```

| **Reports are active** | Are any reports paused, terminated, or showing an error state? The CEO won't assign to agents it can't reach. |
| **CEO's budget** | At 80% of its monthly budget, EKVAAR OS warns you. At 100%, it auto-pauses entirely. |

CEO is assigning everything to itself

This is expected behaviour when you have no other active reports. Hire a CTO or CMO and the CEO will start delegating to them once they're set up.

Strategy was approved but nothing happened

After you approve a strategy, EKVAAR OS queues the CEO to wake automatically so follow-up work usually starts shortly after approval. If you want to force it immediately, go to the CEO's detail page and click **Run Heartbeat**.

A specific task is stuck

1. Open the task and read the comment thread — the assigned agent may have posted a blocker or explanation
2. Check if the task status is `blocked` — read the blocker comment to understand what's needed
3. Check the assigned agent's status — it may be paused or over budget
4. If needed: reassign the task to a different agent, or add a comment with specific guidance for the current agent

---

You're set

You understand how delegation works and what to check when it doesn't. The next guide covers agent adapters — the configuration that determines which AI system powers each agent.

[Agent Adapters →](./agent-adapters.md)

Agent Adapters

When you create an agent in EKVAAR OS, one of the first things you configure is its adapter. The adapter is the bridge between EKVAAR OS and the AI system that actually runs your agent — it tells EKVAAR OS how to launch the agent, how to pass it work, and how to receive results back.

Think of it like a power adapter for different countries. The electricity (EKVAAR OS's task system and org chart) is the same everywhere, but the plug you need depends on the socket (the AI runtime you're connecting to). Claude Code needs one configuration, OpenAI Codex needs another, and a custom cloud-based agent needs a third.

Without an adapter, an agent is just a record in a database. With one, it's a working member of your team.

Adapter comparison

Adapter	Best for	Requires
`claude_local`	Most users — runs Claude on your Mac	Claude Code installed, Anthropic API key
`codex_local`	OpenAI users — runs Codex on your Mac	Codex CLI installed, OpenAI API key
`gemini_local`	Gemini users — runs Gemini CLI on your Mac	Gemini CLI installed, Google credentials
`opencode_local`	Multi-provider flexibility, switchable models	OpenCode CLI installed, relevant API keys
`cursor`	Users already working inside Cursor	Cursor installed and configured
`pi_local`	Pi users wanting Pi's built-in tool set	Pi CLI installed, relevant API keys
`hermes_local`	Persistent memory, 30+ tools, 80+ skills	Hermes Agent installed (Python 3.10+)

For most people getting started, **`claude_local`** is the right choice. It runs directly on your Mac using the same Claude that powers Anthropic's Claude.ai, and it only needs Claude Code plus an API key wired through environment variables.



Claude Local (`claude_local`)

The `claude_local` adapter runs your agent using Claude Code — Anthropic's command-line AI tool — directly on your Mac. When EKVAAR OS triggers a heartbeat, it launches Claude Code with the agent's context and task, waits for the run to complete, and reads back what Claude did.

What it means in practice: Your agent thinks like Claude, can read and write files on your computer, browse the web, and run terminal commands — all within the working directory you specify. It's capable of doing real coding work, writing documents, doing research, and more.

Prerequisites

- Claude Code installed on your Mac (claude.ai/code)
- An Anthropic API key (console.anthropic.com)

Configuration fields

Working directory
The folder on your Mac where the agent does its work — reads files, writes outputs, runs commands. If you're using this agent for a software project, point this to your project folder. If you're not sure, create a new folder called `EKVAAR OS-workspace` on your Desktop and use that.

> **Tip:** Give each agent its own working directory if they're doing different kinds of work. Shared directories can lead to agents accidentally overwriting each other's files.

Model
Which Claude model to use. The main choices:
- `claude-opus-4-6` — most capable, best reasoning, highest cost. Good for your CEO or complex strategic agents.
- `claude-sonnet-4-6` — fast, capable, lower cost. Good for worker agents doing routine tasks.

When in doubt, start with Sonnet for workers and Opus for the CEO.

Environment variables
The agent form includes an **Environment variables** section. Add `ANTHROPIC_API_KEY` there, either as a plain value or as a secret reference. If you're not sure what key name to use, `ANTHROPIC_API_KEY` is the standard one.

Timeout (seconds)
How long a single heartbeat run is allowed to take before EKVAAR OS cuts it off. 300 seconds (5 minutes) is a safe default for most tasks. Complex coding tasks may need longer — you can increase it to 600 or more. Setting it too low will cause agents to time out mid-task.

Common errors

"Claude Code not found" — Claude Code isn't installed, or isn't on the system PATH. Install it from claude.ai/code and then use the Test Environment button to verify EKVAAR OS can find it.

"API key invalid" — Check that the environment variable name matches exactly what you've configured, and that the key itself starts with `sk-ant-`. Anthropic keys are case-sensitive.

"Timeout" — The heartbeat ran longer than your timeout setting. Increase the timeout value, or break the task into smaller pieces so each heartbeat can finish faster.

Codex Local (`codex_local`)

The `codex_local` adapter runs your agent using OpenAI's Codex CLI on your Mac. It works the same way as `claude_local` but uses OpenAI models instead of Anthropic.

Prerequisites

- OpenAI Codex CLI installed on your Mac
- An OpenAI API key (platform.openai.com)

Configuration fields

The fields are the same as `claude_local` — mainly model selection and environment variables — but pointing to OpenAI instead of Anthropic.

Model examples for Codex:
- `gpt-5.3-codex` — the default and the normal starting point
- `o4-mini` — fast and cost-effective for routine tasks

OpenCode Local (`opencode_local`)

The `opencode_local` adapter runs your agent using OpenCode — a flexible, open-source AI terminal tool that supports multiple providers. It lets you configure

exactly which model and provider to use via the `adapterConfig.model` field in `provider/model` format.

When to use this: If you want to switch between providers easily, or use a model not available through `claude_local` or `codex_local` directly.

The configuration is similar to the other local adapters, with an additional **Model** field in `provider/model` format (e.g., `anthropic/claude-opus-4-6` or `openai/gpt-5.3-codex`).

Other adapters you may see

Three built-in adapter types are marked **"Coming soon"** in the agent-config dropdown and can't be picked directly from the UI today. They're fully functional in the runtime — you just configure them via the API or an imported company export until the UI picker lands.

- `openclaw_gateway` — remote OpenClaw instances reached over the WebSocket gateway protocol. Today, the normal path is the OpenClaw invite-prompt flow on the Company Settings page. See [OpenClaw Gateway](../../reference/adapters/openclaw-gateway.md).
- `http` — webhook-style invocation into your own service. Aimed at developers building custom agent integrations. See [HTTP](../../reference/adapters/http.md).
- `process` — runs an arbitrary local command or script. See [Process](../../reference/adapters/process.md).

External adapter plugins can also be installed — they appear in the dropdown once loaded.

HTTP Webhook (`http`)

> **Info:** The `http` adapter is currently not selectable from the agent-config dropdown. Configure it via the API or an imported company export for now.

The `http` adapter connects to a web server or cloud function that you control. When a heartbeat fires, EKVAAR OS sends an HTTP request to your endpoint with the agent's context and tasks. Your endpoint processes the work and sends results back.

When to use this: When your agent lives in the cloud, runs on a different machine, or is built on a platform that accepts webhook calls.

Configuration fields

Endpoint URL
The full URL EKVAAR OS will POST to when a heartbeat fires. This must be publicly accessible or reachable from your EKVAAR OS instance.

Authentication
A secret token that EKVAAR OS includes in the request header, so your server can verify the call came from EKVAAR OS and not someone else.

Timeout
How long EKVAAR OS waits for a response before treating the heartbeat as failed.

> **Note:** The HTTP adapter is aimed at developers building custom agent integrations. If you're using a standard AI provider locally, `claude_local` or `codex_local` is the simpler choice.

Shell Process (`process`)

> **Info:** The `process` adapter is currently not selectable from the agent-config dropdown. Configure it via the API or an imported company export for now.

The `process` adapter runs a command on the same machine as EKVAAR OS. When a heartbeat fires, EKVAAR OS executes the command you specify, passing the agent's context as stdin or environment variables.

When to use this: For custom scripts, local automation, or agents built on tools that don't have their own dedicated adapter.

Configuration fields

Command
The executable command and any arguments. The command must be accessible from the machine running EKVAAR OS.

Working directory
Where to run the command.

Environment variables

Additional environment variables to set for the process (e.g., API keys, paths).

Getting API keys

If you haven't set up an API key yet, here's how:

<!-- tabs: Anthropic (Claude), OpenAI -->

<!-- tab: Anthropic (Claude) -->

1. Go to console.anthropic.com and sign in or create an account
2. In the left sidebar, click **API Keys**
3. Click **Create Key**
4. Give it a name you'll recognise (e.g. "EKVAAR OS")
5. Copy the key immediately — it starts with `sk-ant-` and is only shown once

Store it somewhere safe (a password manager works well). You'll use the environment variable name `ANTHROPIC_API_KEY` when configuring the adapter.

> **Warning: Copy the key immediately after creating it. Anthropic shows it only once. If you lose it, you'll need to create a new one and update your adapter configuration.**

<!-- tab: OpenAI -->

1. Go to platform.openai.com and sign in or create an account
2. Click your profile icon in the top right, then click **API keys**
3. Click **Create new secret key**
4. Give it a name (e.g. "EKVAAR OS") and click **Create secret key**
5. Copy the key immediately — it starts with `sk-` and is only shown once

Store it somewhere safe. You'll use the environment variable name `OPENAI_API_KEY` when configuring the adapter.

> **Warning: Copy the key immediately after creating it. OpenAI shows it only once. If you lose it, you'll need to create a new one and update your adapter configuration.**

<!-- /tabs -->

You're set

You now understand what adapters are and how to configure the most common ones. The next guide covers execution workspaces — the isolated code environments that agents work within when doing file-based tasks.

[Execution Workspaces →](../projects-workflow/workspaces.md)

The Adapter Manager

Every agent in EKVAAR OS needs an **adapter** — the shim that lets the control plane talk to a specific AI runtime. Built-in adapters ship with the product (Claude Code, Codex, Gemini, OpenCode, Cursor, Pi, Hermes, HTTP, Process, OpenClaw Gateway), and you can extend the set by installing **external adapters** from npm or a local path.


The **Adapter Manager** is the single place where you see which adapters your instance knows about, toggle their visibility in the agent menus, install and upgrade external packages, and pause external overrides on built-ins.

This guide walks through the page itself. For the per-adapter config fields (working directory, model names, timeouts, environment variables) see [Agent Adapters](./agent-adapters.md). For the technical catalog of every adapter type — wire format, capabilities, model listings — see the [Adapter Reference](../../reference/adapters/overview.md).

> **Alpha:** The external-adapter runtime is in alpha. APIs, on-disk layout, and the list of exposed capabilities can change between versions. For production use, pin adapter package versions.

Opening the Adapter Manager

The Adapter Manager lives under **Settings → Adapters**. The breadcrumb reads _Company_ → _Settings_ → _Adapters_, and the page header shows a CPU icon, the page title, and an **Alpha** badge.



Below the header there's a persistent amber notice reminding you that external adapters are alpha, and that the power icon on each row hides an adapter from the agent menus without removing it.

The two lists

The page is split into two sections:

- **External Adapters** — adapter packages you (or another operator) installed. Each row is removable and can be reloaded or reinstalled in place.
- **Built-in Adapters** — adapters that ship with EKVAAR OS. These cannot be removed, but they can be hidden from the agent dropdown.

When an external adapter declares the same `type` as a built-in (for example, an external `claude_local` package), the server treats it as an **override**. The override row appears in **External Adapters** with a blue _Overrides built-in_ badge, and a synthetic row appears in **Built-in Adapters** with an _Overridden by …_ badge so you can still see which built-in is affected.

What each row shows

Every row shows the same block of metadata:

- The adapter's display label (`Claude Local`, `Codex Local`, your package's `label`, …).
- A **Built-in** or **External** badge.
- For external rows, an icon indicating source: a folder icon for _installed from local path_, a package icon for _installed from npm_.
- A version badge (`v0.3.2`) when the package declares one.
- Any of the override/disabled badges listed below.
- A one-line meta row: `adapter.type · package-name · N models`.

Badges you may see:

Badge	Meaning
`Built-in`	Ships with EKVAAR OS. Cannot be removed.
`External`	Installed by you. Can be removed, reloaded, reinstalled.
`Overrides built-in` (blue)	This external adapter replaces a built-in of the same type.
`Overridden by …` (blue)	This built-in is currently replaced by an external.
`Hidden from menus` (amber)	Adapter is installed and loaded, but the agent-config dropdown will not offer it.
`Override paused` (amber)	External override is loaded but temporarily not taking effect — the built-in is active instead.

Enabling and disabling an adapter

Every row has a power icon in the action column. Its exact behaviour depends on what you clicked:

- **Built-in or plain external adapter.** Clicking the power icon toggles menu visibility. When it's dim/grey, the adapter still exists and still works for any agent already configured to use it — it just doesn't appear in the adapter dropdown when you create or edit an agent. Clicking again shows it in the menu.
- **External adapter that overrides a built-in.** The power icon controls the **override pause** instead of menu visibility. Pausing the override does not uninstall the external package; it simply tells the runtime to fall back to the built-in until you resume.

Hover the icon to see the tooltip for the current state — the wording switches between _Show in agent menus_, _Hide from agent menus_, _Pause external override_, and _Resume external override_ so you always know which action you're about to take.

> **Note:** Hiding a built-in from menus is an operator preference. Existing agents keep working. If you want to truly stop an adapter from running, remove the external package, or — for built-ins — change the affected agents to a different adapter type first.

Installing an external adapter

Click **Install Adapter** in the top right of the page. A dialog opens with a two-button source switch: **npm package** or **Local path**.

From npm

1. Choose **npm package** (the default).
2. Enter the package name — for example, `@my-org/EKVAAR OS-adapter-openrouter`.
3. Optionally enter a version; leave it blank for `latest`.
4. Click **Install**.

EKVAAR OS fetches the package, validates that it exports a `createServerAdapter()` factory, registers the adapter type, and adds a row to **External Adapters**. A toast confirms the install (`Adapter installed — Type "..." registered successfully. (v...)`). On failure the dialog stays open and shows the error.

From a local path

Pick **Local path** when you're developing an adapter or using one you've cloned somewhere on disk:

1. Switch to **Local path** in the dialog.
2. Either paste an absolute path (`/mnt/e/Projects/my-adapter`, `/Users/me/code/my-adapter`, `E:\Projects\my-adapter`) or click the **Choose…** button for platform-specific instructions.
3. Click **Install**.

Linux, WSL, and native Windows paths are all accepted — Windows paths are auto-converted. Local-path installs show a folder icon in the row so you can tell them apart at a glance; they do **not** offer the **Reinstall** action (there's no registry to pull from).

> **Tip:** The adapter package must export a `createServerAdapter()` function that conforms to EKVAAR OS's adapter contract. See [Creating an Adapter](../../reference/adapters/creating-an-adapter.md).

Reload, reinstall, and remove

External adapters have three lifecycle actions, shown as icon buttons on the right of each row.

Reload (circular-arrow icon)
Re-imports the adapter module in place. Use this after changing the code of a local-path adapter — the runtime hot-swaps the module and invalidates any cached config parsers or UI schemas. Existing agents pick up the change on their next run.

Reinstall (download icon, npm installs only)
Pulls the latest version of the package from npm and reloads it. Clicking the icon opens a confirmation dialog that shows the package name, the installed version, and the latest version available on the npm registry:

- **Package** — `@my-org/EKVAAR OS-adapter-x`
- **Current** — `v0.3.2`
- **Latest on npm** — `v0.4.0`

If the installed version already matches the latest, the dialog says "Already on the latest version." You can still reinstall to force a clean re-fetch. Click **Reinstall** to apply. A toast confirms success (`Adapter reinstalled — ... updated from npm. (v...)`).

Remove (trash icon)
Uninstalls the external adapter. A confirmation dialog warns that the adapter will be unregistered, removed from the adapter store, and — for npm installs — cleaned up from

disk. Agents still configured to use that adapter type will start failing on their next run, so reassign them to a different adapter first.

Built-in rows never show the trash icon. They cannot be removed.

Per-adapter configuration

The Adapter Manager itself does **not** hold configuration for a specific adapter. Adapter config lives on each _agent_ that uses the adapter: working directory, model selection, timeouts, environment variables, and whatever extra fields the adapter declares through its UI schema.

To configure a built-in adapter, open the agent you want to change and edit its adapter config on the agent form.

To configure an external adapter, the same pattern applies — the Agent Manager renders the form fields the external adapter's `createServerAdapter()` reports through its UI schema, including any custom widgets the adapter ships.

For field-by-field walkthroughs of the common built-ins, see [Agent Adapters](./agent-adapters.md). For the technical contract that adapters implement (including the UI parser schema), see [Adapter UI Parser](../../reference/adapters/adapter-ui-parser.md).

Health and troubleshooting

Adapters are simpler than plugins — there's no background worker, no scheduled jobs, and no long-running state to go wrong. "Health" for an adapter mostly comes down to: _did the module load, and does it report any models?_

The row meta line (`type · package · N models`) is your first signal:

- **`0 models`** on a model-listing adapter usually means the adapter loaded but couldn't reach its provider (missing API key, offline, auth failure). Check the agent's environment variables and the provider's status page.

- **Row missing after install** — the install failed. Reopen the install dialog; the error toast will have explained why (invalid package, manifest missing, `createServerAdapter()` not exported).
- **Reload or reinstall returns an error toast** — the new code didn't load. The previous version stays active. Fix the error (often a build output issue for local-path installs), then reload again.
- **Agents fail with "adapter not found"** — the adapter was removed or the `type` string on the agent doesn't match an installed adapter. Reinstall the package or change the agent's adapter.
- **Override paused unexpectedly** — someone clicked the power icon on an overriding external row. Click it again to resume the override.

If the list itself fails to load you'll see a _Loading adapters..._ line that never resolves or an error toast. Refresh the page; if it persists, check the server logs for adapter-registry errors.

Where to go next

- [Agent Adapters](./agent-adapters.md) — what each adapter does and which configuration fields it exposes on the agent form.
- [Adapter Reference](../../reference/adapters/overview.md) — technical catalog of every built-in adapter type.
- [Creating an Adapter](../../reference/adapters/creating-an-adapter.md) — how to author and publish an external adapter package.
- [Adapter UI Parser](../../reference/adapters/adapter-ui-parser.md) — the schema contract your adapter uses to render config fields in the agent form.

The Adapter Manager

Every agent in EKVAAR OS needs an **adapter** — the shim that lets the control plane talk to a specific AI runtime. Built-in adapters ship with the product (Claude Code, Codex, Gemini, OpenCode, Cursor, Pi, Hermes, HTTP, Process, OpenClaw Gateway), and you can extend the set by installing **external adapters** from npm or a local path.

The **Adapter Manager** is the single place where you see which adapters your instance knows about, toggle their visibility in the agent menus, install and upgrade external packages, and pause external overrides on built-ins.


This guide walks through the page itself. For the per-adapter config fields (working directory, model names, timeouts, environment variables) see [Agent Adapters](./agent-adapters.md). For the technical catalog of every adapter type — wire

format, capabilities, model listings — see the [Adapter Reference](../../reference/adapters/overview.md).

> **Alpha:** The external-adapter runtime is in alpha. APIs, on-disk layout, and the list of exposed capabilities can change between versions. For production use, pin adapter package versions.

Opening the Adapter Manager

The Adapter Manager lives under **Settings → Adapters**. The breadcrumb reads _Company_ → _Settings_ → _Adapters_, and the page header shows a CPU icon, the page title, and an **Alpha** badge.



Below the header there's a persistent amber notice reminding you that external adapters are alpha, and that the power icon on each row hides an adapter from the agent menus without removing it.

The two lists

The page is split into two sections:

- **External Adapters** — adapter packages you (or another operator) installed. Each row is removable and can be reloaded or reinstalled in place.
- **Built-in Adapters** — adapters that ship with EKVAAR OS. These cannot be removed, but they can be hidden from the agent dropdown.

When an external adapter declares the same `type` as a built-in (for example, an external `claude_local` package), the server treats it as an **override**. The override row appears in **External Adapters** with a blue _Overrides built-in_ badge, and a synthetic row appears in **Built-in Adapters** with an _Overridden by …_ badge so you can still see which built-in is affected.

What each row shows

Every row shows the same block of metadata:

- The adapter's display label (`Claude Local`, `Codex Local`, your package's `label`, …).
- A **Built-in** or **External** badge.

- For external rows, an icon indicating source: a folder icon for _installed from local path_, a package icon for _installed from npm_.
- A version badge (`v0.3.2`) when the package declares one.
- Any of the override/disabled badges listed below.
- A one-line meta row: `adapter.type · package-name · N models`.

Badges you may see:

Badge	Meaning
`Built-in`	Ships with EKVAAR OS. Cannot be removed.
`External`	Installed by you. Can be removed, reloaded, reinstalled.
`Overrides built-in` (blue)	This external adapter replaces a built-in of the same type.
`Overridden by …` (blue)	This built-in is currently replaced by an external.
`Hidden from menus` (amber)	Adapter is installed and loaded, but the agent-config dropdown will not offer it.
`Override paused` (amber)	External override is loaded but temporarily not taking effect — the built-in is active instead.

Enabling and disabling an adapter

Every row has a power icon in the action column. Its exact behaviour depends on what you clicked:

- **Built-in or plain external adapter.** Clicking the power icon toggles menu visibility. When it's dim/grey, the adapter still exists and still works for any agent already configured to use it — it just doesn't appear in the adapter dropdown when you create or edit an agent. Clicking again shows it in the menu.
- **External adapter that overrides a built-in.** The power icon controls the **override pause** instead of menu visibility. Pausing the override does not uninstall the external package; it simply tells the runtime to fall back to the built-in until you resume.

Hover the icon to see the tooltip for the current state — the wording switches between _Show in agent menus_, _Hide from agent menus_, _Pause external override_, and _Resume external override_ so you always know which action you're about to take.

> **Note:** Hiding a built-in from menus is an operator preference. Existing agents keep working. If you want to truly stop an adapter from running, remove the external package, or — for built-ins — change the affected agents to a different adapter type first.

Installing an external adapter

Click **Install Adapter** in the top right of the page. A dialog opens with a two-button source switch: **npm package** or **Local path**.

From npm

1. Choose **npm package** (the default).
2. Enter the package name — for example, `@my-org/EKVAAR OS-adapter-openrouter`.
3. Optionally enter a version; leave it blank for `latest`.
4. Click **Install**.

EKVAAR OS fetches the package, validates that it exports a `createServerAdapter()` factory, registers the adapter type, and adds a row to **External Adapters**. A toast confirms the install (`Adapter installed — Type "..." registered successfully. (v...)`). On failure the dialog stays open and shows the error.

From a local path

Pick **Local path** when you're developing an adapter or using one you've cloned somewhere on disk:

1. Switch to **Local path** in the dialog.
2. Either paste an absolute path (`/mnt/e/Projects/my-adapter`, `/Users/me/code/my-adapter`, `E:\Projects\my-adapter`) or click the **Choose…** button for platform-specific instructions.
3. Click **Install**.

Linux, WSL, and native Windows paths are all accepted — Windows paths are auto-converted. Local-path installs show a folder icon in the row so you can tell them apart at a glance; they do **not** offer the **Reinstall** action (there's no registry to pull from).

> **Tip:** The adapter package must export a `createServerAdapter()` function that conforms to EKVAAR OS's adapter contract. See [Creating an Adapter](../../reference/adapters/creating-an-adapter.md).

Reload, reinstall, and remove

External adapters have three lifecycle actions, shown as icon buttons on the right of each row.

Reload (circular-arrow icon)
Re-imports the adapter module in place. Use this after changing the code of a local-path adapter — the runtime hot-swaps the module and invalidates any cached config parsers or UI schemas. Existing agents pick up the change on their next run.

Reinstall (download icon, npm installs only)
Pulls the latest version of the package from npm and reloads it. Clicking the icon opens a confirmation dialog that shows the package name, the installed version, and the latest version available on the npm registry:

- **Package** — `@my-org/EKVAAR OS-adapter-x`
- **Current** — `v0.3.2`
- **Latest on npm** — `v0.4.0`

If the installed version already matches the latest, the dialog says "Already on the latest version." You can still reinstall to force a clean re-fetch. Click **Reinstall** to apply. A toast confirms success (`Adapter reinstalled — ... updated from npm. (v...)`).

Remove (trash icon)
Uninstalls the external adapter. A confirmation dialog warns that the adapter will be unregistered, removed from the adapter store, and — for npm installs — cleaned up from disk. Agents still configured to use that adapter type will start failing on their next run, so reassign them to a different adapter first.

Built-in rows never show the trash icon. They cannot be removed.

Per-adapter configuration

The Adapter Manager itself does **not** hold configuration for a specific adapter. Adapter config lives on each _agent_ that uses the adapter: working directory, model selection, timeouts, environment variables, and whatever extra fields the adapter declares through its UI schema.

To configure a built-in adapter, open the agent you want to change and edit its adapter config on the agent form.

To configure an external adapter, the same pattern applies — the Agent Manager renders the form fields the external adapter's `createServerAdapter()` reports through its UI schema, including any custom widgets the adapter ships.

For field-by-field walkthroughs of the common built-ins, see [Agent Adapters](./agent-adapters.md). For the technical contract that adapters implement (including the UI parser schema), see [Adapter UI Parser](../../reference/adapters/adapter-ui-parser.md).

Health and troubleshooting

Adapters are simpler than plugins — there's no background worker, no scheduled jobs, and no long-running state to go wrong. "Health" for an adapter mostly comes down to: _did the module load, and does it report any models?_

The row meta line (`type · package · N models`) is your first signal:

- **`0 models`** on a model-listing adapter usually means the adapter loaded but couldn't reach its provider (missing API key, offline, auth failure). Check the agent's environment variables and the provider's status page.
- **Row missing after install** — the install failed. Reopen the install dialog; the error toast will have explained why (invalid package, manifest missing, `createServerAdapter()` not exported).
- **Reload or reinstall returns an error toast** — the new code didn't load. The previous version stays active. Fix the error (often a build output issue for local-path installs), then reload again.
- **Agents fail with "adapter not found"** — the adapter was removed or the `type` string on the agent doesn't match an installed adapter. Reinstall the package or change the agent's adapter.
- **Override paused unexpectedly** — someone clicked the power icon on an overriding external row. Click it again to resume the override.

If the list itself fails to load you'll see a _Loading adapters..._ line that never resolves or an error toast. Refresh the page; if it persists, check the server logs for adapter-registry errors.

Where to go next

- [Agent Adapters](./agent-adapters.md) — what each adapter does and which configuration fields it exposes on the agent form.
- [Adapter Reference](../../reference/adapters/overview.md) — technical catalog of every built-in adapter type.

- [Creating an Adapter](../../reference/adapters/creating-an-adapter.md) — how to author and publish an external adapter package.
- [Adapter UI Parser](../../reference/adapters/adapter-ui-parser.md) — the schema contract your adapter uses to render config fields in the agent form.

Projects

A project is the container EKVAAR OS uses to group related work. If goals answer "why are we doing this?" and issues answer "what exactly needs doing?", projects sit in between: they bind a body of work to a concrete place — a repository, a working directory, a budget envelope, a set of execution workspaces — where agents can actually pick up tasks and make progress.

Every issue in EKVAAR OS lives under a project. Every execution workspace is scoped to a project. Budgets can be pinned to a project. When you tell an agent "work on the marketing site", you are really telling it "work on issues in the Marketing Site project, using the code and configuration the project points at". Projects are how the abstract strategy the CEO writes becomes something concrete an agent can check out and run.

This guide walks through the project list, then the five tabs you see when you open a project: **Overview**, **Issues**, **Workspaces**, **Configuration**, and **Budget**.

Project List

The Projects page lists every active (non-archived) project in the currently selected company, sorted by creation order, with an **Add Project** button in the top right.



Row anatomy

Each row is a single project entry. Reading left to right you see:

- **Color swatch** — a small square in the project's color. The color is chosen when the project is created and can be changed on the project detail page. Use it to visually scan related projects; it has no functional meaning.
- **Project name** — the main title. Clicking anywhere on the row opens the project detail page and defaults to the Issues tab (unless you previously visited the project, in which case EKVAAR OS restores the tab you last used).
- **Description** (subtitle) — the first line of the project description if one has been set. If the project has no description, this area is empty.

- **Target date** — the project's target completion date if set. Shown on the right in muted text. Projects without a target date omit this field.
- **Status badge** — the current project status: `backlog`, `planned`, `in_progress`, `completed`, or `cancelled`. The badge color is consistent with issue status badges used elsewhere in the app.

Archived projects are filtered out of this list. You can still reach them by following a direct link, and you can unarchive them from the project's Configuration tab.

Filters and actions

The list itself does not expose filter controls; it simply shows every active project in the company. If you need to narrow things down, the navigation crumbs at the top of the page and the company switcher in the sidebar are the main tools.

The top-right **Add Project** button opens the New Project dialog, where you can set the name, description, target date, initial status, and color. The Configuration tab is where you come back later to change repository bindings, environment variables, and execution workspace behaviour — the create dialog only covers the minimum a project needs to exist.

If the company has no projects yet, the list is replaced with an empty state prompting you to add the first one.

Keeping projects (and agents) in your sidebar

As a company grows, the **Projects** and **Agents** groups in the left sidebar can get crowded. To keep yours focused, you can **join** or **leave** individual projects and agents — a personal setting that only affects your own navigation.

- Hover a project or agent in the sidebar and use the **Join** / **Leave** control. Leaving hides it from your sidebar; joining brings it back.
- Everything is **joined by default**, so a brand-new project shows up for everyone until they choose to leave it.
- This is purely cosmetic and per-user. Leaving a project doesn't pause it, archive it, or change anything for your teammates — it still runs, and it's still reachable from the Projects and Agents pages. You're just tidying your own view.

Each join or leave is recorded in the company activity log, so the change is auditable even though it only affects one person's sidebar.

Overview Tab

The Overview tab is the light-weight, human-readable summary of a project. It is the right place to land when someone asks "what is this project about?" without diving into issues or configuration.

What you see

- **Description** — an inline-editable markdown block. Click anywhere in the description area to start editing; the value saves when you blur the editor. If there is no description yet, you see a placeholder prompting you to add one. Images can be pasted or dropped and will be uploaded to the project's asset area.
- **Status** — the current project status rendered as a status badge. To change the status you open the Configuration tab; the Overview tab is read-only for this field.
- **Target date** — shown when one has been configured. Like status, the Overview tab only displays this; editing lives in Configuration.

Linked goals and progress

Goals linked to the project are surfaced in the properties panel on the right of the project page (not in the Overview body itself). Linking a project to one or more goals is how the CEO's strategy connects to executable work: a goal describes an outcome, and any project linked to it inherits that outcome as its reason for existing. See the [Goals guide](./goals.md) for how goals are defined and how to link or unlink them.

Progress on a project is implicit: EKVAAR OS does not maintain a single "percent complete" field. Instead, progress is the shape of the Issues tab — how many issues are `todo`, `in_progress`, `in_review`, `done`, or `cancelled`. If you want a rolled-up view, read the Issues tab with the status grouping turned on.

When to use the Overview tab

Use Overview as:

- A landing page for collaborators who are new to the project.
- A place to keep a short, living summary of scope and non-goals.
- The first tab you open when an approval references a project you did not set up.

For everything else — triage, configuration, workspaces, budget — use the other tabs.

Issues Tab

The Issues tab is the project's task board. It is the same issue list you see on the global Issues page, pre-filtered to this project. For most day-to-day work this is the tab you will spend the most time on.

![Issues tab](../../user-guides/screenshots/light/projects/issues.png)

What is shown

The tab renders the shared issues list component, so the columns, grouping, and sorting controls are identical to the global view:

- Issues are grouped by status (`todo`, `in_progress`, `in_review`, `done`, `blocked`, `cancelled`, `backlog`) by default.
- Each row shows the issue identifier, title, assignee, priority, and any live-run indicator when an agent is currently executing against the issue.
- Live run indicators refresh every few seconds while the tab is open, so you can watch a run pick up, advance, and finish without refreshing the page.

Filtering and view state

Your view settings on this tab — grouping, sort order, which statuses are collapsed — are persisted separately from the global issues view under a per-project key. Switching to another project and back restores the same layout. Switching to the global issues list does not disturb the project-scoped view.

There is no separate "filter by project" control here because the list is already scoped to the project. You can still filter by assignee, priority, label, or free-text search within the project.

Creating issues in the project


Issues created from this tab default to the current project, so you do not have to set the project field by hand. If you need to create an issue in a different project, either switch to that project first or use the global issue creation dialog and pick the project explicitly.

Relationship to execution workspaces

Each issue may be tied to an execution workspace — a specific working copy of the project's code — when the issue is picked up by an agent. The Workspaces tab (next section) groups issues by the workspace they are running in, which is often a more useful lens once work is in flight. See [Execution Workspaces](./workspaces.md) for the underlying model.

Workspaces Tab

The Workspaces tab shows the execution workspaces currently attached to the project. It only appears when the company has the **isolated workspaces** experimental setting enabled and the project has at least one non-default workspace with activity. On projects without isolated workspaces, EKVAAR OS redirects you to the Issues tab instead.



What a workspace row represents

Each row on the Workspaces tab is a summary card combining:

- A workspace identity — its name, underlying working directory or git worktree path, and status.
- The issues currently running in that workspace, so you can see what work is tied to it.
- Runtime service controls — Start, Stop, and Restart buttons for any runtime services the workspace exposes (dev servers, watchers, databases). Runtime services are not auto-started; you control them from this card.
- A **Close workspace** action that opens the workspace close dialog. Closing a workspace stops its runtime services and archives it.

Workspaces whose status is `cleanup_failed` are grouped into a separate section labelled **Cleanup attention needed**, rendered in amber. These are workspaces that could not be fully torn down and need a human decision — either retry the close action, or investigate the underlying path manually.

Project primary vs. isolated workspaces

The project's primary working directory is not shown as a separate row here — it is the implicit default every issue runs in when no isolated workspace is provisioned. This tab lists the non-default workspaces only. For the full mental model of primary, isolated, and reused workspaces, see [Execution Workspaces](./workspaces.md).

When agents create workspaces

Agents create isolated workspaces implicitly when they pick up an issue that is configured to run in isolation, or when you explicitly request one. The Workspaces tab is the place to monitor, manage, and close those workspaces over time. If the list grows long, closing the oldest completed ones is safe — once the underlying branch has been merged or discarded, the workspace no longer serves a purpose.

Configuration Tab

The Configuration tab is where the project's editable properties live. Most of these fields auto-save as you edit: you will see a small **Saving / Saved / Failed** indicator next to the field, and there is no explicit save button.

Basic properties

- **Name** — the project name shown in the list and in every breadcrumb. Changing it is safe; links that use the project's slug continue to resolve.
- **Description** — the full description, rendered as markdown. Matches the description on the Overview tab; edit either location and the value stays in sync.
- **Status** — one of `backlog`, `planned`, `in_progress`, `completed`, or `cancelled`. Use this to communicate the overall state of the project to the team and to the CEO; it does not affect whether agents can pick up issues in the project.
- **Goals** — the list of goals the project is linked to. Add or remove goal links here; linked goals appear on the Overview area and in the properties panel. See the [Goals guide](./goals.md) for the goal model.

Repository binding and working directory

Projects can be bound to either a local folder (`cwd`), a remote repository (`repoUrl`), or both:

- **Local folder only** — for projects where the code lives on the machine EKVAAR OS is running on. Agents work directly in this folder (or in isolated worktrees derived from it).
- **Remote repository only** — for projects where EKVAAR OS clones or references a remote repository. Useful when no local checkout exists yet.
- **Both** — the most common setup: a local checkout that also tracks a remote URL. Both references are kept so tooling that needs one or the other has it available.

The **Choose path** action helps you pick a local folder via the native OS file picker.

Environment variables

Each project can define environment variables that are injected into agent runs and execution workspace commands. These are managed through the environment variable editor on this tab:

- Add, rename, and delete variables inline.

- Secret-valued variables are stored via the secrets store and rendered masked.
- Variables set at the project level override nothing at the company level; they simply extend the environment an agent sees when it runs inside this project.

Execution workspace configuration

When isolated workspaces are enabled for the company, the Configuration tab exposes the per-project knobs:

- **Execution workspace enabled** — whether this project participates in isolated workspaces at all. If off, every issue runs in the project primary workspace.
- **Default mode** — the default workspace mode for new issues: isolated (new workspace), reuse existing, or project primary. Individual issues can override.
- **Base ref** — the git ref (branch, tag, or commit) new isolated workspaces branch from.
- **Branch template** — the naming convention EKVAAR OS uses when it creates new branches for isolated workspaces (e.g. a template that includes the issue identifier).
- **Worktree parent directory** — where EKVAAR OS places new git worktrees on disk.
- **Provision command** — an optional command run after a new workspace is created (for example, to install dependencies).
- **Teardown command** — an optional command run before a workspace is closed.

These settings map to the behaviours described in [Execution Workspaces](./workspaces.md). You will usually set them once per project and rarely touch them again.

Archive and unarchive

At the bottom of the Configuration tab is the **Archive** action. Archiving hides the project from the project list and from most pickers, but it does not delete anything: issues, workspaces, and history remain intact. Archived projects can be unarchived from the same control.

When you archive, the page navigates back to the dashboard and shows a confirmation toast. If the archive fails (for example because of a server error), a failure toast appears and the project remains active.

Pause by budget hard stop

If the project is currently paused because its budget policy hit a hard stop, a red **Paused by budget hard stop** pill appears at the top of the project page (not inside this tab specifically, but worth noting here because the resolution path is the Budget tab). Resume the project either by raising the budget or by resolving the budget override approval.

Budget Tab

The Budget tab is where the project-scoped budget policy lives. This is a project-level cap, distinct from:

- **Agent budgets** — per-agent caps, set on each agent's configuration.
- **Company budgets** — the overall cap for the company.

Project budgets are useful when a single project needs a hard spending ceiling independent of the agent doing the work. For a first principles tour of budgeting, see [Costs & Budgets](../day-to-day/costs.md).

Reading the budget card

The Budget tab renders a single policy card for this project's budget:

- **Scope** — always `project` on this tab, targeting the current project's id and name.
- **Metric** — `billed_cents`. EKVAAR OS tracks billable cost in cents and converts to a currency figure for display.
- **Window** — `lifetime`. Project budgets default to a lifetime cap rather than a rolling window; the total spend against the project counts against the amount.
- **Amount** — the configured cap. Editable in the card.
- **Observed amount** — how much has been spent so far against the project.
- **Remaining amount** — amount minus observed.
- **Utilization percent** — the observed share of the cap, with a warn threshold (default 80%) after which the card visually signals that the project is approaching its limit.
- **Hard stop enabled** — when true, exceeding the cap pauses the project automatically. This is the behaviour that triggers the "Paused by budget hard stop" pill described above.
- **Notify enabled** — when true, the company is notified as the project crosses the warn threshold.
- **Paused** — whether the project is currently paused (and why, in **Pause reason**).

Setting or changing the amount

Click the amount field, enter the new cap in dollars (the UI converts to cents), and save. The change invalidates the budget overview, the project detail view, the project list, and the dashboard, so every surface that shows a budget number updates.

If the project has no explicit policy, the card is rendered in a placeholder state with zero amount, zero observed, and `isActive: false`. Saving a non-zero amount creates the policy.

Distinct from agent and company budgets

A project budget does not replace agent budgets or the company budget. All three apply in parallel:

- An agent hitting its own budget stops, regardless of project budget headroom.
- A project hitting its budget pauses the project, regardless of which agent was working in it.
- The company budget is the overall ceiling; if it stops, no agents in any project can spend further.

See [Costs & Budgets](../day-to-day/costs.md) for how these three interact, how to read the company-wide cost overview, and how to resolve a budget override approval when a hard stop is reached.

Resume after a hard stop

When the project is paused by a hard stop, you have two options:

1. **Raise the amount** from the Budget tab. Once the new amount exceeds observed spend, the project can resume on the next run.
2. **Resolve the budget override approval** from the approvals queue. Budget approvals are the formal path an agent uses to ask for more headroom without a human manually raising the cap.

Both flows are described in more detail in the approvals and costs guides.

Where to go next

- Task-level work: [Managing Tasks](../day-to-day/issues.md).
- The goal model that sits above projects: [Goals](./goals.md).
- The execution surface beneath projects: [Execution Workspaces](./workspaces.md).
- Budget mechanics in more depth: [Costs & Budgets](../day-to-day/costs.md).

Goals

A goal in EKVAAR OS is an outcome statement — a description of something the company is trying to achieve. Goals sit above projects and issues in the hierarchy: they

do not contain code, they do not get "worked on" directly, and they do not have an execution workspace. Instead, they act as anchors. Projects link up to goals, and the CEO's strategy typically justifies itself by pointing at which goals it is advancing.

If issues are the "what to do" and projects are the "where to do it", goals are the "why it matters". A company may have just a handful of goals — long-lived, stable, rarely changing — while underneath them the set of projects and issues churns continuously.

This guide covers:

- The goals list and how it is rendered as a tree.
- The goal detail page and its tabs.
- How projects get linked to goals.
- The goal hierarchy: parent and child (sub-)goals.

Goals List

The Goals page lists every goal defined for the selected company. Because goals can have parents and children, the list is rendered as a tree rather than a flat list.

Tree view

The tree is driven by the `parentId` field on each goal:

- **Top-level goals** have no parent. They render at the root of the tree.
- **Sub-goals** have a parent goal and render underneath it, indented.
- Child goals are grouped under their parent and can themselves have children — nesting is not limited to a single level.

Each row in the tree shows the goal's title, a status badge, and a level label (for example `company`, `team`, or whatever levels your company uses). Clicking a row navigates to the goal detail page.

Creating a goal

When the list is non-empty, a **New Goal** button appears at the top of the page. Clicking it opens the new-goal dialog where you set the title, description, level, and optional parent. If you want to create a sub-goal of an existing goal, it is usually easier to open that goal's detail page and use the Sub Goal button from the Sub-Goals tab — it pre-fills the parent.

If the company has no goals yet, the list is replaced with an empty state and a large **Add Goal** button that opens the same dialog.

Filters

The Goals list itself does not expose a filter bar. The tree shows every goal, at every level, for the selected company. Filtering typically happens one level down — you open a goal and inspect its linked projects or its sub-goals. If you need to find a specific goal by title, use your browser's in-page search or the company-wide search once your company has many goals.

Goal Detail

Opening a goal from the tree takes you to its detail page. The layout has three regions: a header with the goal's identity, the main body with editable title and description, and a tab bar with **Sub-Goals** and **Projects** tabs.

Header and body

The header shows:

- **Level** — the goal's level label in muted uppercase (for example `COMPANY` or `TEAM`). Levels are how EKVAAR OS lets you separate high-level company outcomes from narrower team or workstream goals.
- **Status** — a status badge. Goals use the same status vocabulary as projects and issues for visual consistency, so you can tell at a glance whether a goal is active, achieved, or dropped.
- **Properties toggle** — a small slider icon on the right that re-opens the properties panel if you closed it. The properties panel is where you edit level, status, parent, and other metadata without having to leave the page.

The body below the header has:

- An inline-editable **title**. Click it to edit; it saves when you blur.
- An inline-editable **description** that supports multiline markdown. You can paste or drop images into the description — they are uploaded under the goal's asset area. Use the description to write the "success looks like" narrative for the goal: what has changed in the world when this goal is achieved?

Tabs

Underneath the body the page splits into two tabs:

- **Sub-Goals (N)** — the goal's child goals, rendered as the same tree view used on the main Goals page, scoped to this goal's descendants. A **Sub Goal** button opens the new-goal dialog with the parent pre-filled.
- **Projects (N)** — every project that is linked to this goal. Each row is a compact project entity row: color, name, description preview, and a status badge. Clicking a row opens the project detail page. If there are no linked projects, the tab shows a muted "No linked projects." message.

The counts in the tab labels update as you add, remove, or unlink children and projects, so the tab bar doubles as a quick summary of how much sits under this goal.

Progress rollup

EKVAAR OS does not compute a numerical percentage on goals. The goal's status field is the one authoritative signal — set by a human (or by the CEO when the goal is clearly achieved or abandoned). For a qualitative rollup, the Projects tab is the place to look: the shape of the linked projects' statuses (how many are `in_progress` vs `completed` vs `backlog`) tells you how the goal is tracking without forcing the system to invent a synthetic progress number.

If you want more granular signal, drill into individual projects and inspect their Issues tabs.

Linking Issues and Projects to a Goal

Goals do not contain issues directly. Instead, the relationship goes through projects: a project is linked to one or more goals, and every issue inside that project inherits the link implicitly. When the CEO plans work, this is the chain it follows:

```
Goal → Project → Issue → Execution workspace → Agent run
```

Linking a project to a goal

There are two symmetric ways to establish the link:

- **From the project side — open the project's Configuration tab (see [Projects](./projects.md)) and add the goal under the Goals field. The change saves automatically.**
- **From the goal side — open the goal detail page, switch to the Projects tab, and use the project picker in the linking UI. This is useful when you have a new goal and want to attach several existing projects to it in one sitting.**

A project can be linked to multiple goals. This is intentional: a single body of work often advances more than one outcome, and forcing a single-parent relationship would hide that.

Linking individual issues

Because the link travels through projects, there is no separate "assign issue to goal" UI at the issue level. Move the issue between projects to change its goal attribution, or link the issue's project to the goal you want it to roll up to.

If you need an issue to appear under a different goal without moving it to a different project, the right move is usually to link the project to that additional goal rather than special-casing one issue.

Why the indirection matters

Keeping goals at the project layer, not the issue layer, avoids a common failure mode where a goal accumulates hundreds of directly-linked issues and becomes unreadable. Projects are the natural grouping for issues; goals are the natural grouping for projects. The two-step hop is the feature, not the bug.

Goal Hierarchy

Goals can nest via the **parent goal relationship. A goal with no parent is a root goal; a goal with a parent is a sub-goal of that parent.**

When to use sub-goals

Use sub-goals when an outcome is big enough that it needs to be broken into distinct, independently-trackable pieces. A root goal "Ship the public beta" might have sub-goals for "Core product ready", "Pricing and billing live", and "Launch plan executed". Each sub-goal can then have its own linked projects and status, while the root goal stays at the level of the overall narrative.

Do not use sub-goals as a substitute for projects. If the work is concrete enough that you can point at a repository and start running issues, it should be a project, not a sub-goal.

Creating a sub-goal

From the parent goal's detail page, switch to the Sub-Goals tab and click **Sub Goal. The new-goal dialog opens with the parent pre-filled. Fill in the title, description, and level, then save.**

You can also create a sub-goal from the main Goals page by choosing a parent in the dialog; the two entry points produce identical results.

Reparenting and flattening

Moving a goal between parents is done from the goal's properties panel — change the parent field, and the tree re-renders. Flattening a sub-goal to a root goal is the same action, with the parent set to none.

Deep hierarchies are rarely the right answer. Two or three levels is usually enough to capture the structure without making the tree tedious to read.

Status propagation

EKVAAR OS does not auto-compute a parent goal's status from its children. The status field on each goal is independent. This keeps things predictable — a human (or the CEO) stays in charge of declaring when an outcome is achieved — at the cost of having to update parent statuses by hand when the work underneath is clearly done.

Where to go next

- The project layer that sits under goals: [Projects](./projects.md).
- How issues pick up agents: [Managing Tasks](../day-to-day/issues.md).
- How the CEO builds a strategy that references your goals: [Approvals](../day-to-day/approvals.md).

Heartbeats & Routines

When you first hire a few agents, it's tempting to give each one a timer — "wake up every few minutes and see if there's anything to do." It feels proactive. In practice, it's the fastest way to end up with a sidebar full of paused agents, surprise token bills, and a dashboard you have to fight with just to keep things quiet.

EKVAAR OS is designed around a different default: agents stay dormant until real work arrives. This guide explains the two mechanisms that drive an agent — **heartbeats on an interval and **routines** — and when to reach for each one. It also walks through the Routines UI, from the list view down to the detail page where you configure triggers, variables, and run history.**

The two ways an agent starts running

An agent can be woken up in four ways:

| Source | What triggers it |
|---|---|
| **Timer | A heartbeat interval ticks (e.g. every 5 minutes, whether or not there's work) |**
| **Assignment | A task is assigned to the agent, or a new comment arrives on one of its open tasks |**
| **On demand | You click "Wake now" in the UI, or another agent hands it work |**
| **Automation | A routine fires on its schedule and hands the agent an issue to execute |**

The first — timer — is the only one that wakes an agent without anything having actually happened. The other three are event-driven: the agent runs *because there's something to do*, not *in case there's something to do*.

Why timer heartbeats are opt-in

A new agent ships with timer heartbeats **turned off by default. That's deliberate, and it's the setting you should usually keep.**

A timer-on-interval agent wakes every N seconds regardless of whether anything changed. Each wakeup costs tokens, generates a run in the inbox, and gives you one more thing to read. If you have five agents all ticking every five minutes, you'll look away for an hour and come back to sixty runs that mostly said "nothing to do, going back to sleep."

The natural response to that noise is to start pausing agents — which is why people end up on the agents page reaching for a bulk-pause button. But pause is a blunt override: it stops all wakeups, including the event-driven ones you actually want. The better fix is to stop the noise at the source by leaving the heartbeat off in the first place.

> **Rule of thumb:** If you find yourself frequently pausing and resuming an agent, that agent's heartbeat is wrong — not your workflow.

Heartbeat settings on an agent

Open any agent and find the **Run Policy** section. You'll see:

- **Heartbeat on interval** — the master switch. Off by default. Turn it on only when the agent needs to poll something that doesn't have its own event trigger (see "When a timer is the right answer" below).
- **Run heartbeat every _N_ sec** — only visible when the interval is on. If you need a timer at all, prefer minutes or hours, not seconds.

Under **Advanced Run Policy** you'll also find:

- **Wake on demand** — leave this on. It's what lets assignments, comments, and routines reach the agent.
- **Cooldown (sec)** — minimum gap between runs, useful for bursty work.
- **Max concurrent runs** — how many tasks the agent can work in parallel.

The combination you want for most agents: **Heartbeat on interval = off**, **Wake on demand = on**. The agent stays "active" on the dashboard 24/7 but consumes nothing until work actually lands on its desk.

Routines — scheduled work the right way

Routines are where scheduled work belongs. A routine is a reusable job definition with a trigger attached to it. When the trigger fires, the routine creates (or reopens) a task and — if you've assigned it to an agent — the assignment wakes that agent.

Two trigger kinds are supported:

- **Schedule** — a cron expression in your timezone. "Every weekday at 9am", "the first of every month", "every Sunday at midnight". EKVAAR OS computes the next run and fires on that clock.
- **Webhook** — a signed URL you can call from anything outside EKVAAR OS. Useful when another system should kick off the work.

You'll find routines on the **Routines** page in the sidebar.

Creating a routine

1. Open the **Routines** page and click **New Routine**
2. Give it a title and a short description of what the task should do
3. Add a trigger. For scheduled work, pick **Schedule** and enter a cron expression — the default `0 10 * * *` fires every day at 10:00 in your local timezone
4. Assign it to the agent that should handle the work
5. Save and enable it

When the trigger fires, EKVAAR OS creates a task, assigns it to the agent, and that assignment wakes the agent immediately. The run shows up in the inbox with a clear link back to the routine that caused it — so you can always trace "why did this agent run?" back to a specific cause.

Routine policies worth knowing

Two policies control what happens when schedules overlap or the scheduler has been offline:

- **Concurrency policy** — what to do if the routine is still running when the next tick arrives. Options: coalesce into a single queued follow-up, skip the new tick, or always enqueue.
- **Catch-up policy** — what to do about ticks that were missed while the routine or the scheduler was paused. Options: skip the missed windows, or catch up in capped batches.

For most cases the defaults (coalesce if active, skip missed) are what you want: no pile-ups, no surprise flood of work after a restart.

The Routines list

The Routines page is reached from the sidebar and opens on a **Routines** tab plus a **Recent Runs** tab. The header shows the total count of routines and a **Create routine** button.

List columns and badges

Each routine row surfaces:

- **Title** — the routine name. A small grey label appears beside it when the routine is not active: `paused`, `draft` (no default agent assigned), or `archived`.
- **Project** — a coloured square and the project name, or "No project" when the routine has none set.
- **Default agent** — the agent's icon and name, or "No default agent" for drafts.
- **Last run** — a localised timestamp for the most recent execution, followed by its status (for example `succeeded`, `failed`, `running`). Rows that have never fired show "Never".
- **Enabled toggle** — a large switch that flips the routine between `active` and `paused`. The label to the right reads `On`, `Off`, `Draft`, or `Archived`. The toggle is disabled for archived routines.
- **More menu** — a kebab that exposes `Edit`, `Run now`, `Pause`/`Enable`, and `Archive`/`Restore`.

Clicking the row opens the detail page. Actions inside the toggle and dropdown do not navigate — they stay on the list.

Grouping and filtering

Above the list you'll find a **Group** popover with three options:

- **Project** — groups routines by their default project, with "No project" as its own section.
- **Agent** — groups by default assignee, with "Unassigned" for draft routines.
- **None** — the flat default.

Group headers are collapsible and their open/closed state is persisted per company in local storage, along with the chosen grouping, so reloading keeps your view.

The list does not have a separate text search — the count in the header and the collapsible groups are the main way to navigate larger libraries.

Creating a routine from the list

Clicking **Create routine** opens a modal composer. The composer walks you through the minimum a routine needs to exist:

- **Title** — an auto-sizing text area. Press Enter to drop into the description; Tab walks you through assignee, project, and description.
- **For / in** — inline selectors for the default **assignee agent** and default **project**. Both are optional at creation time. Recently-used assignees float to the top of the list.
- **Instructions** — a Markdown editor. Anything you write here becomes the body of every task the routine produces.

- **Advanced delivery settings** — a collapsed section with the concurrency and catch-up policies, each with a plain-English description next to the dropdown.

Draft routines without a default agent are valid — they save and stay paused until you assign one. On save, EKVAAR OS invalidates the list cache and navigates you straight to the new routine's detail page with the triggers tab open, so you can immediately attach a schedule or webhook.

Run now, pause, archive

- **Run now** opens a small dialog where you can fill in runtime variables, override the assignee or project for just this run, and pick an execution workspace if the routine uses one. On submit the run enqueues as a real execution issue.
- **Pause** flips the routine's status to `paused`. A paused routine ignores its triggers but keeps its configuration intact.
- **Archive** removes the routine from the default list without deleting anything. Archived routines can be restored later.

Recent Runs tab

The second tab on the Routines page is a read-only issue list filtered to `originKind = routine_execution`. It uses the same IssuesList component as other issue views, so you get the same columns, live-run indicators, grouping, and inline updates. A background poll refreshes live runs every few seconds so in-flight executions show their progress without a page reload.

The Recent Runs view is the fastest way to answer "did all my morning routines run?" — it is routine-scoped but agent-agnostic, and rows link directly to the execution issue they produced.

The routine detail page

Opening a routine drops you on the detail page. The layout is deliberately narrow — a single editable column — because a routine is really just a task template plus a trigger, and the form is meant to feel like writing a task.

Header

The header packs a lot into one row:

- **Editable title** — click the title to edit inline. Enter jumps to the description; Tab walks through the selectors.
- **Run button** — opens the same "run now" dialog as the list row. This is the manual override for any routine.
- **Automation toggle** — the large switch. On = `active`, off = `paused`. The label to the right reads `Active`, `Paused`, `Draft`, or `Archived` and is colour-coded for state.
- **Draft banner** — if the routine has no default agent yet, a banner explains that it can still run manually but automation stays paused until an agent is assigned.

Below the header is the assignment row — an inline "For [assignee] in [project]" statement that edits the defaults — followed by the Markdown instructions editor. Any change to these fields is tracked as dirty state; a `Save` action appears when there's anything to persist.

Tabs: Triggers, Runs, Activity

The detail page has three tabs, selected via `?tab=` in the URL so you can deep-link:

- **Triggers** — the default. Lists every trigger attached to the routine and provides a composer to add new ones.
- **Runs** — the execution history for this specific routine.
- **Activity** — a structured audit log of edits, enables, pauses, trigger changes, and secret rotations.

Run history and the next-run countdown

The Runs tab lists every execution the routine has produced, newest first. Each run shows its triggered-at timestamp, the trigger that caused it (schedule, webhook, or manual), the resulting issue link, and the final status. When a run is currently live, a `LiveRunWidget` attaches to the row and polls every three seconds so you can watch it progress without reloading.

On the Triggers tab, each scheduled trigger shows a "Next:" line with the resolved local timestamp of its next fire. That value is computed server-side from the cron expression plus the trigger's timezone, so the countdown reflects real scheduler intent rather than browser-local math. Webhook triggers show a `Webhook` label in the same slot, and manual triggers show `API`. Every trigger also surfaces its last result — `succeeded`, `failed`, or a short error — so you can spot a misfiring webhook without leaving the page.

Cron picker

![Cron picker](../../user-guides/screenshots/light/routines/cron-picker.png)

When you add or edit a schedule trigger, EKVAAR OS replaces the raw cron input with a **ScheduleEditor. The editor is a small form with a preset dropdown plus follow-up fields that appear based on what you picked:**

- **Every minute — no extra fields. Emits `* * * * *`.**
- **Every hour — a minute selector. Emits `M * * * *`.**
- **Every day — hour and minute selectors. Emits `M H * * *`.**
- **Weekdays — hour and minute selectors. Emits `M H * * 1-5`.**
- **Weekly — day-of-week, hour, minute. Emits `M H * * D`.**
- **Monthly — day-of-month, hour, minute. Emits `M H D * *`.**
- **Custom (cron) — a raw expression field for anything the presets don't cover.**

Hours are shown in 12-hour format with AM/PM labels in the UI, even though the underlying cron is 24-hour. Minutes snap to five-minute increments in the preset modes (0, 5, 10, ...), matching the resolution of the scheduler. Days of week run Monday–Sunday for readability, but are stored using the standard cron convention (0 = Sunday).

The editor is two-way: if you paste a cron expression into the custom field that matches one of the presets, the form picks it up on the next render and switches back. Expressions it can't classify stay on "Custom" so you never lose an edit.

Below the controls, a one-line human description summarises the current setting ("Every weekday at 9:00 AM" or similar). That same description is what appears on the trigger row in the detail page.

Timezone handling

Every schedule trigger is saved with an explicit **timezone, derived from the browser's `Intl.DateTimeFormat().resolvedOptions().timeZone` at creation time. The scheduler evaluates cron expressions in that timezone, not in UTC. This matters for daylight saving: a routine set to "every weekday at 9am" in Europe/Amsterdam genuinely fires at 9am local time on both sides of a DST switch, rather than shifting by an hour.**

If you need to change the timezone later (for example, you moved), open the trigger and re-save — the editor stamps the current browser timezone onto the updated record. The `Next:` countdown on the detail page is always rendered in your current local time, regardless of which timezone the trigger was originally saved with.

Webhook triggers

Webhook triggers skip the cron editor entirely and show two fields instead:

- **Signing mode** — `bearer`, `hmac_sha256`, `github_hmac`, or `none`. Each has a description below the dropdown explaining how the fire endpoint will authenticate the incoming request.
- **Replay window (seconds)** — how far back in time a signed request's timestamp may be. Hidden for `github_hmac` and `none`, which don't carry a timestamp.

When you create a webhook trigger, EKVAAR OS returns a one-time banner with the webhook URL and secret. **This is the only time the secret is shown** — copy it now. A `Rotate secret` button on the trigger card lets you mint a fresh secret later, which surfaces in the same banner.

Variable templates

Routines can accept **variables**: named inputs that you reference inside the title or instructions using `{{name}}` placeholders. When the routine fires, EKVAAR OS interpolates the values into the resulting task, so one routine can produce many different-looking executions.

Defining variables

Variables are detected automatically. Any `{{name}}` placeholder in the title or instructions becomes a tracked variable, and the **Variables** panel appears below the instructions editor. For each detected variable you can set:

- **Type** — `text`, `textarea`, `number`, `boolean`, or `select`.
- **Label** — a friendly name shown on the run-now dialog.
- **Default value** — the baseline used when nothing else is provided.
- **Options** — a comma-separated list, only for `select`. The options become a dropdown on the run dialog.

Editing a placeholder in the title or body keeps the panel in sync — renaming `{{name}}` to `{{customer}}` renames the variable, and removing the last reference removes it.

Using variables at run time

When a trigger fires, the current default values are substituted in and the task is created. The run-now dialog — reachable from the list kebab menu, the detail header, or an API call — gives you a chance to override any variable for a single run without touching the routine definition. It also lets you override the assignee and project just for that run.

Variables flow through to the execution issue by way of simple Mustache-style interpolation on both the title and description. The original placeholder syntax is preserved in the routine, so if you clear your overrides the routine keeps working with its defaults.

External webhook callers can pass variables in the request body. Each signing mode validates the body on the way in, and the validated payload is then used for interpolation. This is how you wire up "every time GitHub opens a PR, spin up a review task with the PR title in the body" without writing any glue code.

Catch-up behaviour

Two policies control what happens when schedules overlap or the scheduler has been offline:

- **Concurrency policy** — what to do if the routine is still running when the next tick arrives. Options: coalesce into a single queued follow-up, skip the new tick, or always enqueue.
- **Catch-up policy** — what to do about ticks that were missed while the routine or the scheduler was paused. Options: skip the missed windows, or catch up in capped batches.

For most cases the defaults (coalesce if active, skip missed) are what you want: no pile-ups, no surprise flood of work after a restart.

If you restart EKVAAR OS after a long downtime and you had `enqueue_missed_with_cap` set, the scheduler will create up to the configured cap of catch-up runs and then drop the rest. This is intentional: the cap prevents a weekend-long outage from producing hundreds of duplicate tasks on Monday morning.

When a timer IS the right answer

Timer heartbeats aren't wrong — they're just overused. Reach for one when:

- The agent is watching an **external system with no webhook** — an RSS feed, an email inbox without push, a third-party API that only exposes polling. There's no event to wake on, so the tick *is* the event.
- The agent's job is genuinely **"check every N minutes and react"** and you've tried modelling it as a routine and it didn't fit.

Even then, push the interval as high as you can stand. An agent polling once an hour is rarely worse than one polling every minute — and it's sixty times cheaper.

Pause vs. heartbeat off — they are not the same

These two things look similar on the dashboard but behave very differently:

| | Heartbeat off | Paused |
|---|---|---|
| Timer ticks | No | No |
| Wakes on assignment | **Yes | No |**
| Wakes on comment | **Yes | No |**
| Wakes on routine firing | **Yes | No |**
| Wakes on-demand click | **Yes | No |**
| Shows as "active" on dashboard | Yes | No |

****Heartbeat off** is the quiet, productive default — the agent is ready and waiting, it just isn't ticking. **Paused** is a hard stop you use for a specific reason: the agent is misbehaving, you're changing its configuration, or a budget guard tripped it. If you're pausing agents as a routine way to keep the noise down, switch their heartbeats off instead and put them back to active.**

A healthy setup looks like this

For a small AI company running in the background, the steady-state pattern you're aiming for is:

- **Most agents have heartbeats off. They sit at "active" and only run when you assign them work, a teammate hands them a subtask, or a routine fires.**
- **A handful of routines schedule the recurring work: a morning standup summary, a Monday metrics roll-up, a weekly housekeeping pass. Each routine targets one agent.**
- **One or two specialist agents may have heartbeats on — but only because they're polling something external that has no webhook, and only on a long interval.**
- **Pause is reserved for actual problems, not for volume control.**

When that's your layout, the agents page stops being a cockpit you have to constantly wrangle, and starts being what it was meant to be: a quiet status board that only speaks up when something real is happening.

You're set

Heartbeats and routines are how you decide *when* your agents run. Get the defaults right once and most of the "managing agents" pressure disappears. The next guide covers Skills — reusable instruction sets that decide *how* an agent runs once it's woken up.

[Skills →](../org/skills.md)

Appendix — The heartbeat protocol (for agent developers)

When an agent wakes — whether from a timer tick, assignment, comment, routine, or direct wake — it runs the same protocol on every heartbeat. This is the contract between an agent and EKVAAR OS.

If you're writing an agent adapter or a custom agent, implement these nine steps in order.

1. Identity

Fetch your own agent record:

```
GET /api/agents/me
```

Returns your ID, company, role, chain of command, and budget.

2. Approval follow-up

If `EKVAAR OS_APPROVAL_ID` is set in the environment, handle that approval first:

```
GET /api/approvals/{approvalId}
GET /api/approvals/{approvalId}/issues
```

Close the linked issues if the approval resolves them, or comment explaining why they remain open.

3. Get assignments

```
GET
/api/companies/{companyId}/issues?assigneeAgentId={yourId}&status=todo,in_progress
,in_review,blocked
```

Results are sorted by priority. This is your inbox.

4. Pick work

- Work on `in_progress` first, then `in_review` (only if you were woken by a comment on it), then `todo`.
- Skip `blocked` unless you can unblock it.
- If `EKVAAR OS_TASK_ID` is set and assigned to you, prioritise it.
- If woken by a comment mention, read that comment thread first.

5. Checkout

Before any work, checkout the task:

```
POST /api/issues/{issueId}/checkout
Headers: X-EKVAAR OS-Run-Id: {runId}
{ "agentId": "{yourId}", "expectedStatuses": ["todo", "backlog", "blocked", "in_review"] }
```

If you already own the task, checkout succeeds idempotently. If another agent owns it, you get `409 Conflict` — stop and pick a different task. **Never retry a 409.**

6. Understand context

```
GET /api/issues/{issueId}
GET /api/issues/{issueId}/comments
```

Read ancestors to understand why the task exists. If woken by a specific comment, find it and treat it as the immediate trigger.

7. Do the work

Use your tools and capabilities to complete the task.

8. Update status

Always include the run ID header on state changes:

```
PATCH /api/issues/{issueId}
Headers: X-EKVAAR OS-Run-Id: {runId}
{ "status": "done", "comment": "What was done and why." }
```

If blocked:

```
PATCH /api/issues/{issueId}
Headers: X-EKVAAR OS-Run-Id: {runId}
{ "status": "blocked", "comment": "What is blocked, why, and who needs to unblock it." }
```

9. Delegate if needed

Create subtasks for your reports:

```
POST /api/companies/{companyId}/issues
{ "title": "...", "assigneeAgentId": "...", "parentId": "...", "goalId": "..." }
```

Always set `parentId` and `goalId` on subtasks.

Critical rules

- **Always checkout** before working — never PATCH to `in_progress` manually.
- **Never retry a 409** — the task belongs to someone else.
- **Always comment** on in-progress work before exiting the heartbeat.
- **Always set parentId** on subtasks.
- **Never cancel cross-team tasks** — reassign to your manager.
- **Escalate when stuck** — use your chain of command.

Workspaces

When an agent picks up a task that involves working with code or files, it needs a place to do that work — a folder with the right code checked out at the right state, ready for the agent to read, edit, and run. That's what an execution workspace is: a snapshot of a project's working directory, tied to a specific task run.

Execution workspaces exist so that multiple agents can work on the same project simultaneously without stepping on each other. When a project is configured for isolated work, agents can get their own copy — their own branch, folder, and runtime context — so work in one workspace doesn't accidentally break another.

This guide covers what execution workspaces are, how they relate to projects, and how to use the workspace detail screen — its tabs, runtime controls, and logs — to inspect and manage them.

Before you start: turning workspaces on

Workspaces are an **experimental feature, so the **Workspaces** screen is hidden until you opt in.**

1. Go to **Instance settings → Experimental.**
2. Turn on **Enable Isolated Workspaces.**

Once it's on, a **Workspaces item appears in the sidebar, and a **Workspaces** tab appears on any project that has workspace activity. With the setting off, the sidebar item isn't shown and visiting `/workspaces` directly just sends you back to your issues.**

> **Note: This is the single switch that exposes all the workspace UI described in this guide — execution-workspace controls in project configuration, the Workspaces screen, and the per-issue workspace mode picker. If you're not using isolated workspaces, leaving it off keeps that UI out of your way.**

What the Workspaces screen is — and isn't

The most common surprise is opening **Workspaces for the first time and finding it empty, with nothing to click. That's expected, and it's worth understanding why:**

- **You don't create workspaces here. There's no "New workspace" button. Execution workspaces are **provisioned automatically** the first time an agent picks up a task that needs one (see the next section). The Workspaces screen is for *inspecting and managing* what already exists — not for creating anything by hand.**
- **It stays empty until work happens. If no agent has run an isolated task yet, you'll see **"No workspace activity yet."** That's not a bug — there's genuinely nothing to show. Assign a task to an agent, let it run in an isolated workspace, and the workspace will appear here on its own.**
- **A project only shows up once it has something to show. A project's primary workspace surfaces as soon as the project has one set; other (non-primary) project workspaces surface once they have runtime services or config; and isolated execution**

workspaces surface once a task has run against them. A freshly created project with none of that won't list anything yet — and its **Workspaces tab stays hidden until it does.**

So if the screen looks bare, the fix is usually "run a task," not "find the hidden create button" — there isn't one.

How execution workspaces relate to projects

Every execution workspace is linked to a project. The project defines the base configuration — where the code lives, how to run it, what the default setup looks like.

When a task runs, EKVAAR OS resolves which execution workspace to use for that run:

1. **The heartbeat fires and the agent picks up a task**
2. **EKVAAR OS resolves the workspace — creating a new one, reusing an existing one, or sticking with the project default, depending on your settings**
3. **The agent receives the workspace path and works within it**
4. **The workspace persists after the run if you're using an isolated or reusable workspace mode**

Workspace modes

When isolated workspaces are enabled for a project, you can choose how an issue's workspace is handled:

****Isolated (new workspace)****
EKVAAR OS creates a fresh working copy for this task — a new git worktree at a new path, branched from the base. The agent works here without any risk of interfering with other workspaces. When the task is done, you can review and merge the branch, then archive the workspace.

This is the right choice for tasks that make code changes — features, fixes, experiments.

****Reuse existing workspace****
The task shares a workspace with another task or a previous run. Multiple tasks can share one workspace so they can work against the same branch and see the same running services.

This is useful when tasks are closely related and need to coordinate on the same state — for example, multiple issues working against the same feature branch.

****Project primary workspace****
The task runs in the project's primary checkout, not an isolated copy. Use this carefully — changes made here affect the shared working copy directly.

How EKVAAR OS keeps reused workspaces consistent

Reusing a workspace is convenient, but it raises a fair question: what happens when two different agents — with two different intended environments — land in the same workspace? EKVAAR OS closes that gap so a reused workspace never quietly drifts.

- **No silent environment reuse. Each task run has an intended environment, resolved in this order: an environment set explicitly on the issue always wins; otherwise the project's workspace-policy environment applies; otherwise the agent's own default environment; and the instance default is the final fallback. (An agent deliberately pinned to the local default is never promoted off it by a project policy — only an explicit issue-level environment can move it.) When a run reuses a workspace whose environment doesn't match the run's intended one, EKVAAR OS treats that as a conflict to surface rather than silently inheriting whatever the previous occupant left behind.**
- **Dependent issues wait for finalize. When an issue depends on another, its wake no longer fires before the upstream workspace has finished finalizing. The dependent task only starts once the workspace it relies on is in a consistent, settled state — so it never reads a half-written checkout.**
- **Accepting an interaction waits too. Accepting a plan or review (`issue.interaction.accept`) now waits for the workspace to finalize before it proceeds, for the same reason.**

You don't configure any of this — it's part of how isolated and reused workspaces behave. The practical effect is simply that dependent work and reused workspaces see consistent state, every time.

> **Note: Execution workspaces are local working copies. EKVAAR OS does not push them to a remote git host on your behalf — finished work is reviewed and merged through EKVAAR OS, not through a `git push` from inside the workspace.**

Runtime services

Each workspace can have runtime services: background processes that need to be running for the agent's work to make sense — a development server, a database, a build watcher.

Runtime services are manually controlled from the workspace UI. EKVAAR OS does not start or stop them automatically when a heartbeat fires.

To start services for a workspace:
1. Open your project and click on the workspace
2. Click **Start Services (or the specific service you want to start)**
3. The service runs in the background; the status updates in the UI

> **Note: Services you start in one workspace don't affect other workspaces. Each isolated workspace has its own runtime, even if the configuration was inherited from the project's base settings.**

Workspace inheritance

When you create a project, you can define a base runtime configuration for it — how services should be started, what environment variables they need, what commands to run.

Isolated execution workspaces inherit this configuration by default. You can override specific settings on individual workspaces if a particular task needs different settings than the project default.

The inheritance answers the question "how do I run this?" — but the actual running process is always specific to the workspace. Two workspaces with the same inherited configuration will have two separate running processes.

Workspace lifecycle

Execution workspaces are durable — they persist until you explicitly archive or tear them down. This means:

- The agent's branch state, uncommitted changes, and any running services survive across heartbeats
- Multiple heartbeats can pick up the same workspace and continue from where the last one left off
- Shared workspaces accumulate changes across multiple tasks

When you're done with a workspace:
1. Review the agent's work (merge the branch, approve changes, etc.)
2. Click **Archive on the workspace**
3. EKVAAR OS cleans up the workspace according to its mode and project settings

> **Warning: Archiving a workspace that has unmerged changes or uncommitted work means that work is gone. Make sure you've reviewed and merged anything you want to keep before archiving.**

When you'll encounter this

For most board operators, execution workspaces are something that happens in the background. You don't need to configure them for every issue — the defaults work fine for straightforward agents doing straightforward work.

You'll want to pay closer attention when:
- You have multiple agents working on the same codebase and need to avoid conflicts
- An agent needs specific services running to do its work
- You want to review an agent's changes on a branch before they're merged
- A task needs to pick up from where a previous task left off

---

Workspace list

There are two places to see your workspaces, and they show the same data from different angles:

- **The Workspaces sidebar item opens the company-wide view. It's grouped by project, so you see every project that has workspace activity, each with its workspaces underneath. Projects with running services float to the top.**
- **A project's Workspaces tab (open a project, click **Workspaces**) is the same list scoped to that one project. It only appears once that project has workspace activity.**

Either way, you'll see the project's primary workspace and any isolated execution workspaces EKVAAR OS has provisioned. If nothing has been provisioned yet, the company-wide view shows **"No workspace activity yet."**

![The company-wide Workspaces screen, grouped by project: the Website project's isolated execution workspace (with a running service and a linked task) above its primary "main" workspace](../../user-guides/screenshots/light/workspaces/list.png)

Each workspace appears as a card showing:

- Its **kind** — *Execution workspace* or *Project workspace*
- The workspace **name**, with its **branch** and **path**
- Running **services** (for example, `1/1 services`) and a live link when a service exposes a URL
- For an execution workspace, its **status** (active, idle, in review, archived, or cleanup failed) and a **Close workspace** / **Retry close** control
- The **linked tasks** that have run against it, and when it was last updated

If a workspace has runtime config, the card also gives you a **Start services** / **Stop services** button right there. Click the workspace name to open its detail screen, where you can inspect and edit its configuration, control its runtime services, review its operation logs, and see every task that has run against it.

The header of the detail screen shows the workspace name with quick start/stop/restart controls for its services on the right. Below the header, the detail screen is split into tabs:

1. **Tasks** — every task that has run against this workspace (this is the default tab)
2. **Services** — the runtime services and one-shot jobs for this workspace, with start/stop/restart and run controls
3. **Configuration** — workspace settings, workspace context, and concrete location
4. **Runtime logs** — history of runtime and cleanup operations
5. **Routines** — routines that use workspace-specific variables, which you can run against this workspace

Installed plugins can add their own tabs alongside these (for example, a workspace-diff plugin contributes a **Changes** tab). The tabs remember your last selection per workspace, so if you always land on Runtime logs for a specific workspace, EKVAAR OS keeps taking you there.

Services tab

The **Services** tab is the control surface for runtime behaviour: services you want running in the background, and one-shot jobs you want to fire off against this workspace. (The header above the tabs mirrors the service controls as quick start/stop/restart buttons, so you can act on them from any tab.)

Two rules govern what you can do here:

1. **You need a working directory.** Every command EKVAAR OS runs against the workspace needs an absolute path to run in. If the workspace's `cwd` is empty, the action buttons are disabled and a hint reminds you to fix that first. Fill in the **Working directory** field on the Configuration tab, save, and the controls light up again.
2. **Services need runtime config.** Service commands only show up if there's a runtime config somewhere in the chain — either inherited from the project workspace or overridden on this execution workspace. If neither exists, the services list stays empty with a short note; jobs may still run if they're defined and a `cwd` is set.

The tab groups commands into two sections:

- **Services** — long-running processes like `pnpm dev`, a Postgres container, or a build watcher. For each service you'll see start, stop, and restart controls and the service's last observed status.
- **Jobs** — one-shot commands like `pnpm db:migrate` or a test runner. Each job has a single run action.

When EKVAAR OS is busy running an action (for example, starting a service), the controls show a pending state and block duplicate actions. On success you'll see a short confirmation — "Workspace service started.", "Workspace job completed." — and on failure, the error message from the adapter appears in red. Either way, the full history ends up in the Runtime logs tab.

Configuration tab

The Configuration tab is where you inspect and edit everything that makes this workspace concrete — the path on disk, the repo and branch it points at, the provisioning and teardown commands, and any runtime overrides specific to this execution workspace.

Workspace settings

The **Workspace settings** card holds the editable fields for the workspace. Most of these are populated when EKVAAR OS provisions the workspace; you usually only need to touch them when an agent or project has moved, a branch was renamed, or the provisioning scripts changed.

- **Workspace name** — a human label used in lists, breadcrumbs, and notifications.

- **Branch name — the git branch this workspace is checked out on. For isolated worktrees, this is typically something like `PAP-946-workspace`.**
- **Working directory — the absolute path on disk. This is where the agent runs its commands. If this path is empty, EKVAAR OS can't run any local commands for this workspace — it's the single most important field to keep correct.**
- **Provider path / ref — the path or reference used by the workspace provider. For git worktrees this is the worktree path; for other providers it's whatever reference that provider needs.**
- **Repo URL — the remote URL the working directory was cloned from. Used for linking out to GitHub/GitLab in the UI.**
- **Base ref — the ref the workspace branched off from, for example `origin/main`.**
- **Provision command — runs when EKVAAR OS prepares this execution workspace (for example, a script that clones a worktree and installs dependencies).**
- **Teardown command — runs when the execution workspace is archived or cleaned up.**
- **Cleanup command — an optional workspace-specific cleanup step that runs before teardown (for example, killing a stuck `vite` process).**

At the top right of this card you'll find a **Close workspace button. Closing runs the teardown and cleanup commands, and transitions the workspace to `archived` or `cleanup_failed` depending on how those commands exit. If a previous close attempt left the workspace in `cleanup_failed`, the button changes to **Retry close**.**

Below the command fields you'll see a **Runtime config source notice. It tells you at a glance whether this execution workspace is:**

- inheriting the runtime config from its project workspace,
- overriding the project workspace config with its own, or
- has no runtime config at all yet.

If this workspace is overriding the inherited runtime, you can click **Reset to inherit to drop the override and go back to the project workspace default.**

For the rare cases where you need to tweak the raw runtime JSON, expand the **Advanced runtime JSON panel. It contains:**

- A checkbox — **Inherit project workspace runtime config — that toggles override vs. inherit mode.**
- A JSON textarea where you can edit the workspace's `commands` object. Both legacy `services` arrays and the newer `commands` array (supporting both services and jobs) are accepted.

Changes in the Workspace settings card stay local until you click **Save changes**. The **Reset** button reverts the form to whatever EKVAAR OS has currently persisted, so you can back out of a half-edited change without reloading the page.

Workspace context

The **Workspace context** card (labelled "Linked objects" in the UI) shows the other EKVAAR OS entities this execution workspace is connected to:

- **Project** — the project this workspace belongs to.
- **Project workspace** — the project-level workspace this execution workspace was provisioned from. Runtime config inheritance follows this link.
- **Source issue** — the issue that originally triggered this workspace's creation, if any. Clicking it takes you to the issue detail page.
- **Derived from** — if this workspace was created by splitting or branching off another execution workspace, you'll see a link back to the original. This is how EKVAAR OS represents follow-up worktrees that share a code lineage with an earlier one.
- **Workspace ID** — the raw identifier, shown in monospaced text and copyable for API calls or debugging.

Use this card to navigate quickly back to the project, the issue that kicked off the work, or the parent workspace this one derived from.

Concrete location

The **Concrete location** card summarises the physical and git-level facts about the workspace. It doesn't introduce new fields — everything here also appears in Workspace settings — but it's formatted for fast scanning and copying rather than editing.

- **Working dir** — the absolute path, with a copy button so you can paste it into a terminal.
- **Provider ref** — the provider-specific reference or worktree path.
- **Repo URL** — when set to a valid `http(s)` URL, this becomes a clickable link out to the remote.
- **Base ref** — the starting ref the workspace was branched from.
- **Branch** — the active branch name.
- **Opened** — timestamp when EKVAAR OS first opened the workspace.
- **Last used** — the most recent time an agent interacted with it.
- **Cleanup** — if EKVAAR OS has scheduled this workspace for cleanup, the eligible-at time and the reason are shown here. Otherwise this reads `Not scheduled`.

Together, Workspace settings, Workspace context, and Concrete location give you everything you need to answer "what is this workspace, where does it live, and what is it connected to?"

Working with runtime config overrides

Runtime configuration is one of the places where project defaults and workspace-specific needs sometimes pull in different directions. EKVAAR OS resolves this with a two-level inheritance model:

1. The **project workspace** defines a baseline runtime config. This is what gets applied to every execution workspace carved out of that project workspace unless you explicitly override it.
2. The **execution workspace** can either inherit that baseline or override it with its own `workspaceRuntime` object.

The **Runtime config source** notice on the Configuration tab tells you which of these is currently in effect:

- **Execution workspace override** — this workspace has its own runtime config and ignores whatever the project workspace provides. Use this when a specific worktree needs a different port, a different dev command, or extra jobs that don't belong on every workspace.
- **Project workspace default** — this workspace is inheriting the project's runtime config as-is. This is the common case and the one you should aim for — overrides add drift and should be the exception.
- **None** — neither level has runtime config defined, so EKVAAR OS can't start services. Jobs may still run if they're provided, but services won't appear in the Services tab.

If you've added an override and want to go back to inheriting, click **Reset to inherit** — it clears the override and the workspace falls back to the project workspace's config. If the project workspace has no runtime config of its own, that button is disabled; you'd otherwise be resetting the execution workspace to "None".

The **Advanced runtime JSON** panel is hidden behind a disclosure triangle on purpose. Editing the raw JSON is a power-user path; for most teams, configuring services at the project level is enough. When you do need to edit it, the panel accepts both shapes:

- The legacy `{ "services": [...] }` array, kept for backwards compatibility.
- The newer `{ "commands": [...] }` array with `kind: "service"` or `kind: "job"` entries, which is what new workspaces should use.

EKVAAR OS validates the JSON when you hit **Save changes**; if it can't be parsed or isn't a JSON object, you'll get an inline error and the save is aborted.

Runtime logs tab

Switch to the Runtime logs tab to see what EKVAAR OS has actually done with this workspace — which commands ran, when they ran, how they exited, and what they printed.

Under the **Recent operations** heading, each entry represents one workspace operation:

- The **command** that ran (or the **phase**, if this was a lifecycle step rather than a named command).
- The **start time** and, if the operation has finished, the **end time**.
- A short excerpt of **stdout** or, when the command failed, a short excerpt of **stderr**. The stderr excerpt is highlighted in red so you can spot failures at a glance.
- A **status pill** on the right showing whether the operation is running, succeeded, or failed.

This tab covers both kinds of operations:

- **Runtime operations** — service starts, stops, restarts, and one-shot jobs you trigger from the Services tab (or the header quick controls).
- **Cleanup operations** — provision, teardown, and cleanup command runs that happen when EKVAAR OS prepares or closes the workspace.

If nothing has happened yet, you'll see "No workspace operations have been recorded yet." When the operation log fails to load, the error message from the server is shown in red.

Use this tab as your first stop when an agent reports that a service didn't come up, a job failed, or the workspace refused to close. Most of the time, the stderr excerpt is enough to diagnose the problem; the timestamps make it easy to correlate a failed heartbeat run with the exact command that broke.

How operations map to what you did

If you're new to the Runtime logs tab, it helps to know which UI actions produce which operation entries:

- Clicking **Start** on a service in the Services tab creates an operation with the service's command, a `started` phase, and — on a successful start — a running or finished status depending on whether the service stays alive or exits immediately.

- Clicking **Stop** or **Restart** on a service produces a short operation that records how the service was terminated or bounced.
- Clicking **Run** on a job produces a single operation with the job's command; its final status reflects the job's exit code.
- **Close workspace** (from the Configuration tab) runs the cleanup command and then the teardown command in sequence. Each appears as its own operation so you can tell which of the two failed if the close ends in `cleanup_failed`.
- **Provision** operations are emitted automatically when EKVAAR OS first prepares the workspace; you won't trigger these from the UI, but you'll see them here when debugging first-boot problems.

If nothing about a failure is obvious from the excerpt, remember that excerpts are truncated. Reach into the underlying worktree on disk, re-run the command manually from that directory, and compare its output to the excerpt — the mismatch usually points at an environment or permissions difference between the agent's runtime and your shell.

Tasks tab

The Tasks tab shows every issue that has ever run against this execution workspace — not just the source issue that created it, but any follow-ups, retries, and related tasks that inherited the workspace.

The list uses the same components and filters as the main issues view, so you get:

- Issue identifier, title, status, priority, and assignee at a glance.
- The **live-run indicator** — issues whose heartbeat is currently running against this workspace are highlighted so you can see what's active right now.
- Inline actions for updating issue status, reassigning, and opening the issue detail page.
- The view's local state — which columns are visible, how you've sorted — is remembered under the `EKVAAR OS:execution-workspace-issues-view` key, so different execution workspaces can have different preferred layouts.

This tab answers three common questions:

- "What work has this workspace actually been used for?" — scroll the list.
- "Is anything running against this workspace right now?" — look for a live-run highlight.
- "Can I safely archive this workspace?" — if every issue here is `done`, `cancelled`, or otherwise inactive, you're probably safe.

If an issue in the list needs to be reassigned or rescheduled before you can close the workspace, click through, make the change, and come back — the list updates automatically.

Source issue vs. linked issues

Two different relationships show up on the Tasks tab and in the Configuration tab's Workspace context card, and it's worth keeping them straight:

- The **source issue is the single issue that originally caused EKVAAR OS to provision this workspace. It's stored on the workspace itself and appears in the Workspace context card. For isolated worktrees created from a specific task, this will typically be the task that kicked the whole flow off.**
- The **linked issues listed on the Tasks tab are every issue that has ever been attached to this workspace, including the source issue, follow-up child issues that inherited the workspace, and any issue whose `inheritExecutionWorkspaceFromIssueId` pointed back here.**

When you're deciding whether it's safe to archive, look at the full linked list, not just the source issue. An archived workspace takes all its branch state with it, and a follow-up issue that still references it will end up without a valid cwd the next time it runs.

Archiving and cleanup

Closing a workspace is a two-step operation in EKVAAR OS:

1. **Cleanup — the cleanup command (if any) runs first. This is where you stop stray dev servers, free ports, and do anything that would otherwise prevent teardown from succeeding.**
2. **Teardown — the teardown command then dismantles the workspace itself. For git worktrees this typically removes the worktree directory and prunes the branch; for other providers it does whatever that provider considers cleanup.**

If both succeed, the workspace transitions to `archived` and disappears from the default workspace list. If either fails, the workspace transitions to `cleanup_failed` — it's still there, still visible, and the **Close workspace button changes to **Retry close** so you can try again after fixing whatever went wrong. Until a retry succeeds, the workspace keeps whatever state it had before the close was attempted.**

Some practical tips:

- Before closing, check the Runtime logs tab for anything still running. Services that are `running` will be stopped as part of cleanup, but jobs that are genuinely in-flight will also be killed — make sure you're not about to interrupt something important.
- Review the **Tasks tab** for any issue still in `in_progress` that's tied to this workspace. Archive the workspace only after those issues are done, cancelled, or moved to another workspace.
- If an agent had uncommitted changes on the branch, those changes go away at teardown. Either merge the branch first or stash/commit anything you want to keep.

The **Cleanup** row on the Concrete location card tells you whether EKVAAR OS has already scheduled the workspace for automatic cleanup — for example, because it's been idle past a retention window — and what the reason is. If you see a scheduled cleanup you didn't expect, look at the project's workspace lifecycle settings to understand why.

Troubleshooting checklist

When something doesn't behave, run through this checklist before filing a bug:

- **Is the `cwd` set and correct?** Without an absolute working directory, no local command can run. Configuration tab → Workspace settings → Working directory.
- **Is the branch still there?** If someone deleted the branch outside EKVAAR OS, the agent will fail when it tries to check out. Re-create or re-point the branch.
- **Does the runtime config actually apply?** Look at Runtime config source on the Configuration tab. If it says "None", no service commands will be available.
- **Is another workspace holding the port?** Two isolated worktrees on the same machine that both inherit a dev server config will both try to bind. Either override the port on one of them or only start one at a time.
- **Did a previous close fail?** If the workspace is in `cleanup_failed`, you'll keep getting stale state until you either retry the close or manually fix the underlying problem and then retry.
- **Is the agent looking at the right workspace?** When follow-up tasks are created, make sure either `parentId` or `inheritExecutionWorkspaceFromIssueId` is set on the child issue so EKVAAR OS can resolve it back to this workspace.

Most workspace-level issues come down to one of these six questions.

Isolation and git worktrees

EKVAAR OS's default for "isolated" execution workspaces is a **git worktree branched off the project workspace's base ref. If you haven't used git worktrees before, here's what that means in practice:**

- A worktree is a second (or third, or tenth) checkout of the same repository, living at a different path, with its own branch checked out.
- They share the same underlying object database with the primary checkout, so creating a worktree is cheap — no full re-clone, no duplicated history on disk.
- Because each worktree has its own working directory, agents in different worktrees can't accidentally overwrite each other's uncommitted changes.

When EKVAAR OS provisions an isolated workspace:

1. It picks a path under the project workspace's worktree directory.
2. It creates a new branch off the configured base ref (for example, `origin/main`).
3. It checks that branch out into the new worktree path.
4. It runs the provision command so dependencies, env files, and any other per-worktree setup are in place before the agent starts.

From the agent's perspective, all of this is invisible — it just gets a `cwd` that's ready to read, edit, and run. From your perspective as a board operator, the Concrete location card on the Configuration tab shows exactly which path and branch were picked, so you can always drop into that directory yourself to inspect or debug.

When isolation is overkill

Isolation has a cost: each worktree needs its own `node_modules` (or equivalent), its own dev server, its own migrations. For large projects this adds up. You probably don't want isolated workspaces for:

- **Purely read-only tasks — research, summarising, reviewing documentation. Use the project primary workspace or a reused workspace.**
- **Tasks that only touch issue metadata — triaging, estimating, assigning. These don't need a checkout at all.**
- **Coordination between multiple tasks on the same feature — reuse a single workspace and let the tasks accumulate changes together.**

Isolation pays off when agents are genuinely making code changes you'll want to review separately, or when you want to run several experiments in parallel without them tripping over each other.

Observability at a glance

Pulling together the tabs, here's how the detail screen maps to typical questions you'll ask:

- "What is this workspace and where does it live?" → Configuration tab, the Concrete location card.
- "Why does this workspace exist and what's it attached to?" → Configuration tab, the Workspace context card.
- "Who decides how services run here?" → Configuration tab, the Runtime config source notice.
- "What has actually happened in this workspace?" → Runtime logs tab.
- "Who's been running against this workspace?" → Tasks tab.
- "Is anything running right now?" → Services tab (or the header quick controls) for service status plus Tasks tab (live-run indicator).

The breadcrumbs at the top of the screen also tie everything back together: **Projects → {project name} → Workspaces → {workspace name}. From any workspace detail screen, you're always one click from the project and two from the workspace list.**

Common workflows

A few concrete patterns show up often enough to be worth calling out:

****Kicking off a new feature****
1. Create the issue and assign it to the agent who'll do the work.
2. Let EKVAAR OS provision an isolated workspace when the agent checks out the task.
3. When the agent finishes and the branch is ready, review the branch in your usual git workflow.
4. Once merged, come back to the Workspaces tab and archive the workspace.

****Recovering from a failed close****
1. Open the workspace and look at the Runtime logs tab to see which command failed.
2. Fix the underlying problem — a stuck process, a missing permission, a command that assumes the wrong shell.
3. Click **Retry close and confirm the workspace transitions to `archived`.**
4. If retries keep failing, drop into the worktree directory yourself and run the teardown command manually.

****Shipping a migration****
1. Create a job in the workspace's runtime config (for example, `db:migrate`).
2. Open the workspace and click **Run on that job from the Services tab.**
3. Wait for the operation to appear in Runtime logs with a successful status.

4. Link the resulting evidence to the issue — the operation timestamp is enough.

Reusing a workspace across tasks
1. When creating the follow-up issue, set `parentId` if it's a child task, or `inheritExecutionWorkspaceFromIssueId` if it's a sibling that should share the same workspace.
2. EKVAAR OS will wire the new issue up to the existing workspace on checkout.
3. On the Tasks tab of the workspace, you'll see the new issue alongside the original.

These patterns are just defaults — adapt them to how your team actually operates.

You're set

Execution workspaces give agents the isolated, stateful environments they need to do reliable file-based work. The Workspace list shows you everything provisioned for a project; the Configuration tab keeps the path, repo, and runtime config in sync with reality; the Runtime logs tab tells you what actually ran; and the Tasks tab shows you who's been using it.

The next guide covers heartbeats and routines — how you decide *when* an agent runs, and why most agents should stay dormant until real work arrives.

[Heartbeats & Routines →](./routines.md)

Execution Policy

EKVAAR OS's execution policy system keeps tasks honest. Instead of trusting an agent to remember to hand work off for review, the **runtime enforces** review and approval stages automatically — the moment an executor tries to close the issue, the runtime intercepts the transition and routes the work to the right reviewer or approver.

This page covers when to use execution policies, how the three enforcement layers compose, and how to configure policies via the UI and API.


The three layers

Layer	Purpose	Scope
Comment required	Every agent run must post a comment back to the issue	Runtime invariant — always on

| **Review stage** | A reviewer checks quality and can request changes | Per-issue, optional |
| **Approval stage** | A manager or stakeholder gives final sign-off | Per-issue, optional |

An issue can have review only, approval only, both in sequence, or neither (just the comment-required backstop).


Happy path: review → approval



1. Issue is created with an `executionPolicy` specifying a review stage (for example QA) and an approval stage (for example the CTO).
2. Executor works on the issue in `in_progress`.
3. Executor transitions to `done`. The runtime intercepts:
   - Status becomes `in_review`, not `done`.
   - Issue is reassigned to the first reviewer.
   - `executionState` enters `pending` on the review stage.
4. Reviewer approves by transitioning to `done` with a comment.
   - A decision record is created with outcome `approved`.
   - Issue stays `in_review` and is reassigned to the approver.
   - `executionState` advances to the approval stage.
5. Approver approves by transitioning to `done` with a comment.
   - `executionState.status` becomes `completed`.
   - Issue reaches `done` for real.

Changes-requested loop





1. Reviewer transitions to any status other than `done` (typically `in_progress`) with a comment explaining what needs to change.
2. The runtime automatically:
   - Sets status to `in_progress`.
   - Reassigns to the original executor (stored in `returnAssignee`).
   - Sets `executionState.status` to `changes_requested`.
3. Executor makes changes and transitions to `done` again.
4. The runtime routes back to the **same reviewer** — not the beginning of the policy.
5. The loop continues until the reviewer approves.

Policy variants

Review only:

```json
{
  "stages": [
    { "type": "review", "participants": [{ "type": "agent", "agentId": "qa-agent-id" }] }
  ]
}
```

Executor finishes → reviewer approves → done.

Approval only:

```json
{
  "stages": [
    { "type": "approval", "participants": [{ "type": "user", "userId": "manager-user-id" }] }
  ]
}
```

Executor finishes → approver signs off → done.

Multiple reviewers or approvers: each stage supports multiple participants. The runtime picks one to act, excluding the original executor to prevent self-review.

The comment-required backstop

Independent of any review stage, every issue-bound agent run must leave a comment. This is enforced at the runtime level:

1. Run completes — the runtime checks whether the agent posted a comment for this run.
2. **No comment:** `issueCommentStatus` becomes `retry_queued`, and the agent is woken once more with reason `missing_issue_comment`.
3. **Still no comment after retry:** `issueCommentStatus` becomes `retry_exhausted`. No further retries. The failure is recorded.
4. **Comment posted:** `issueCommentStatus` becomes `satisfied` and links to the comment ID.

This prevents silent completions where an agent closes work without leaving a trace.

Run-level tracking fields

Field	Description
`issueCommentStatus`	`satisfied`, `retry_queued`, or `retry_exhausted`
`issueCommentSatisfiedByCommentId`	Comment that fulfilled the requirement
`issueCommentRetryQueuedAt`	Timestamp when the retry wake was scheduled

Data model

Execution policy (issue field: `executionPolicy`)

```ts
interface IssueExecutionPolicy {
  mode: "normal" | "auto";
  commentRequired: boolean;       // always true, enforced by runtime
  stages: IssueExecutionStage[];  // ordered list of review/approval stages
}

interface IssueExecutionStage {
  id: string;                     // auto-generated UUID
```

```
  type: "review" | "approval";
  approvalsNeeded: 1;            // multi-approval not yet supported
  participants: IssueExecutionStageParticipant[];
}

interface IssueExecutionStageParticipant {
  id: string;
  type: "agent" | "user";
  agentId?: string | null;
  userId?: string | null;
}
```

Execution state (issue field: `executionState`)

```ts
interface IssueExecutionState {
  status: "idle" | "pending" | "changes_requested" | "completed";
  currentStageId: string | null;
  currentStageIndex: number | null;
  currentStageType: "review" | "approval" | null;
  currentParticipant: IssueExecutionStagePrincipal | null;
  returnAssignee: IssueExecutionStagePrincipal | null;
  completedStageIds: string[];
  lastDecisionId: string | null;
  lastDecisionOutcome: "approved" | "changes_requested" | null;
}
```

Execution decisions (table: `issue_execution_decisions`)

```ts
interface IssueExecutionDecision {
  id: string;
  companyId: string;
  issueId: string;
  stageId: string;
  stageType: "review" | "approval";
  actorAgentId: string | null;
  actorUserId: string | null;
  outcome: "approved" | "changes_requested";
  body: string;              // required comment explaining the decision
  createdByRunId: string | null;
  createdAt: Date;
```

}
```

Every decision is recorded with actor, outcome, comment, and run ID. The full review history is queryable per issue.

Access control

- Only the **active reviewer or approver (the `currentParticipant` in execution state) can advance or reject the current stage.**
- Non-participants who attempt to transition the issue receive `422 Unprocessable Entity`.
- Both approvals and change requests **require a comment — empty or whitespace-only comments are rejected.**

API usage

Setting a policy at issue creation

```sh
POST /api/companies/{companyId}/issues
{
"title": "Implement feature X",
"assigneeAgentId": "coder-agent-id",
"executionPolicy": {
"mode": "normal",
"commentRequired": true,
"stages": [
{ "type": "review", "participants": [{ "type": "agent", "agentId": "qa-agent-id" }] },
{ "type": "approval", "participants": [{ "type": "user", "userId": "cto-user-id" }] }
]
}
}
```

Stage and participant IDs are auto-generated if omitted. Duplicate participants are deduplicated. Stages with no valid participants are removed. If no valid stages remain, the policy is set to `null`.

Updating a policy on an existing issue

```sh
PATCH /api/issues/{issueId}
{
  "executionPolicy": { ... }
}
```

If the policy is removed (`null`) while a review is in progress, execution state is cleared and the issue is returned to the original executor.

Advancing a stage (approval)

The active reviewer or approver transitions the issue to `done` with a comment:

```sh
PATCH /api/issues/{issueId}
{
  "status": "done",
  "comment": "Reviewed — implementation looks correct, tests pass."
}
```

The runtime decides whether this completes the workflow or advances to the next stage.

Requesting changes

Transition to any non-`done` status with a comment:

```sh
PATCH /api/issues/{issueId}
{
  "status": "in_progress",
  "comment": "Button alignment is off on mobile. Please fix the flex container."
}
```

The runtime reassigns to the original executor automatically.

UI

New issue dialog

When you create an issue, **Reviewer** and **Approver** buttons appear alongside the assignee selector. Each opens a participant picker with:

- *No reviewer* / *No approver* (to clear)
- *Me* (the current user)
- The full list of agents and board users

Selections build the `executionPolicy.stages` array automatically.

Issue properties panel

For existing issues, the properties panel shows editable **Reviewer** and **Approver** fields. Multiple participants can be added per stage. Changes persist to the issue's `executionPolicy` via the API.

Design principles

1. **Runtime-enforced, not prompt-dependent.** Agents don't need to remember to hand off work. The runtime intercepts status transitions and routes accordingly.
2. **Iterative, not terminal.** Review is a loop — request changes, revise, re-review — not a one-shot gate. The system returns to the same stage on re-submission.
3. **Flexible roles.** Participants can be agents or users. Not every organization has "QA" — the reviewer/approver pattern is generic enough for peer review, manager sign-off, or compliance checks.
4. **Auditable.** Every decision is recorded with actor, outcome, comment, and run ID.
5. **Single execution invariant preserved.** Review wakes and comment retries respect the existing constraint that only one agent run can be active per issue at a time.

Export & Import

Once you've built a company — given it a goal, hired agents, configured their adapters, and set up projects — that configuration has real value. Export and import let you capture that configuration as a portable package you can back up, share with others, or reuse as a starting point for a new company.

Exports are human-readable markdown files. Anyone with the package can understand the company's structure without reading a database dump.

What a package contains

An exported company package looks like this:

```
my-company/
├── COMPANY.md          ← Company name, goal, and metadata
├── agents/
│   ├── ceo/AGENT.md    ← Agent identity, role, and instructions
│   └── cto/AGENT.md
├── projects/
│   └── main/PROJECT.md
├── skills/
│   └── review/SKILL.md
└── .EKVAAR OS.yaml     ← Adapter types, environment variable declarations, budgets
```

What's included: Company name, description, and goal. Agent names, roles, reporting structure, and instructions. Project definitions. Skills. Adapter type declarations and the names of environment variables that need values.

What's never included: Secret values — API keys, tokens, passwords. Machine-specific paths. Internal database IDs. These things are environment-specific and wouldn't be valid on another machine anyway.

Exporting a company

You can export and import from the EKVAAR OS UI now. The terminal commands still exist if you prefer them, but they're no longer the only path.

In the UI

Open **Org** and use the **Export company** or **Import company** buttons in the header. You can also reach the same pages from **Company Settings**.

On export, EKVAAR OS shows you the package contents before you download them. On import, it previews what will be created, renamed, or skipped before anything is applied.

In the terminal

To export your company to a folder:

```sh
EKVAAR OSai company export <company-id> --out ./my-export
```

```

Replace `&lt;company-id&gt;` with your company's ID (visible in the URL when you're viewing the company in EKVAAR OS).

By default, this exports the company metadata and agents. To include more:

```sh
# Export everything: company, agents, projects, skills, and tasks
EKVAAR OSai company export <company-id> --out ./full-export \
  --include company,agents,projects,tasks,skills
```

Export options

Option	What it does
`--out <path>`	Where to save the export (required)
`--include <values>`	What to include: `company`, `agents`, `projects`, `issues`, `tasks`, `skills` — comma-separated
`--skills <slugs>`	Export only specific skills by name
`--projects <names>`	Export only specific projects

> **Tip:** Run the export regularly as a backup — especially before making significant changes to your agent configuration or org structure.

Importing a company

You can import from a local folder, a GitHub repository, or a shorthand GitHub reference.

```sh
# From a local folder
EKVAAR OSai company import ./my-export

# From a GitHub repository
EKVAAR OSai company import https://github.com/org/repo

# From a GitHub subfolder
EKVAAR OSai company import org/repo/companies/acme
```

Creating a new company from a package
```

When you import without specifying an existing company, EKVAAR OS creates a fresh one:

```sh
EKVAAR OSai company import ./my-export --target new --new-company-name "My Restored Company"
```

Merging into an existing company

If you want to add agents or projects from a package into a company you already have running:

```sh
EKVAAR OSai company import ./shared-agents \
  --target existing \
  --company-id <your-company-id> \
  --include agents
```

Preview before applying

If you're using the CLI, always preview an import before applying it, especially when merging into an existing company:

```sh
EKVAAR OSai company import ./my-export --target new --dry-run
```

The preview shows you exactly what will be created, renamed, skipped, or replaced — without actually doing anything. Read it carefully before proceeding.

Handling name conflicts

When importing into an existing company, agent or project names may conflict with existing ones. EKVAAR OS offers three strategies:

Strategy	What happens
`rename` (default)	Appends a suffix to avoid conflicts — e.g. `ceo` becomes `ceo-2`
`skip`	Leaves existing entities untouched; skips anything that would conflict
`replace`	Overwrites existing entities. Use with care.

> **Warning:** The `replace` collision strategy overwrites your existing agent configurations. Make sure you have a backup export before using it.

Common use cases

Backing up your company configuration

Run a full export periodically and store it in a safe place — a cloud drive, a private Git repository. If something goes wrong, you can restore from the package.

Starting a new company from a template

Export a well-configured company as a template, then import it with a new name whenever you want to start a similar company. Your agent configurations, skills, and project structure carry over.

Sharing an agent team

If you've built a well-configured team of agents (say, a standard engineering team with CEO, CTO, and engineers), export just the agents and share the package. Others can import it into their own company.

```sh
# Share: export agents only
EKVAAR OSai company export <company-id> --out ./engineering-team --include agents

# Receive: import into a new company
EKVAAR OSai company import org/shared-templates/engineering-team \
  --target new \
  --new-company-name "My Engineering Team"
```

Importing from GitHub

Community-published company templates live in public GitHub repositories. Import directly:

```sh
EKVAAR OSai company import org/company-templates/research-team \
  --target new \
  --dry-run
```

Review the dry-run output, then run without `--dry-run` to apply.

After importing

Imported agents always start with scheduled heartbeats disabled. This is intentional — it gives you a chance to review the imported configuration and set your own budget and heartbeat settings before any agents start spending.

After an import:
1. Open each imported agent and verify the adapter configuration looks right
2. Set per-agent budgets appropriate for your usage
3. Add any API keys or environment variables that the package declared but didn't include values for
4. Enable heartbeats when you're ready for agents to start working

---

You're set

Export and import give you durable, shareable backups of everything you've built. The final guide covers terminal setup — for developers who want to run EKVAAR OS outside the Desktop App.

[Terminal Setup →](./terminal-setup.md)

Terminal Setup

> **Note: This guide is for developers comfortable with a terminal. If you're not a developer, use the [Desktop App installation guide](../getting-started/installation.md) instead — it covers the full setup without any of this.**

EKVAAR OS runs as a Node.js server. The onboarding command handles the full setup in one step.

Prerequisites

- Node.js 20 or later (nodejs.org — download the LTS version)
- pnpm (package manager)

```bash
node --version   # Should print v20.x.x or higher
```

Step 1 — Install pnpm

```bash
npm install -g corepack
corepack enable
corepack prepare pnpm@latest --activate
```

Step 2 — Run the onboarding command

```bash
npx EKVAAR OSai onboard --yes
```

This single command handles everything: downloads EKVAAR OS, creates a configuration directory at `~/.EKVAAR OS/`, initialises the embedded database, and starts the server at `http://localhost:3100`. The `--yes` flag accepts all defaults.

```
✓ Created config at ~/.EKVAAR OS/instances/default/config.json
✓ Initialised database
✓ Server running at http://localhost:3100
→ Opening EKVAAR OS in your browser...
```

Run without `--yes` to go through the interactive setup and choose your deployment mode, database, and storage configuration.

Step 3 — Open EKVAAR OS

EKVAAR OS opens in your browser automatically. If it doesn't, navigate to http://localhost:3100.

To start EKVAAR OS again after restarting your machine:

```bash
npx EKVAAR OSai run
```

Deployment modes

The default mode (`local_trusted`) runs on localhost with no authentication — suitable for single-operator local use. For team access or public hosting:

Mode	Auth	Best for
`local_trusted`	None	Solo, local machine
`authenticated` + `private`	Login required	Private network (Tailscale, VPN, LAN)
`authenticated` + `public`	Login required	Internet-facing cloud deployment

Change the mode:

```bash
npx EKVAAR OSai configure --section server
```

Advanced configuration

For persistent background runs, Docker deployment, external databases, and cloud hosting options, see the [deployment overview](../../reference/deploy/overview.md).

You're set

EKVAAR OS is running. You'll land in onboarding or at the start screen, where the next step is [Create Your First Company](../getting-started/your-first-company.md).

Company Administration

Every EKVAAR OS company has a small cluster of surfaces that control its identity, its membership, and its portability. These pages are where you, as a board user (or a member with the right grants), set the company's name and logo, decide who else can sign in, hand out invite links, review join requests, and move the whole company in and

out of a portable package. The CEO agent never touches most of this — it is deliberately human territory.

This guide walks through each of those surfaces in the order you typically meet them: **General Settings**, **Access & Members**, **Invites**, **Join Requests**, **Export**, and **Import**. If you are looking for how hiring approvals themselves work, see the [Approvals guide](../guides/day-to-day/approvals.md). If you want to understand the reporting tree that sits underneath the membership model, see [Org Structure](../guides/org/org-structure.md).

General Settings

The **Company Settings** page groups the settings that apply to the whole company rather than to any one agent or project. Open it from the sidebar under the company name.

Name and description

The **General** section has two fields:

- **Company name** — the display name shown in the company switcher and across the UI.
- **Description** — an optional one-line description shown on the company profile. Leave it empty if you do not want one.

Changes are not persisted until you click **Save changes**. The save button only appears when one of the fields is dirty, and it is disabled if the name is empty.

Logo and brand color

The **Appearance** section controls the small square tile that represents your company in the sidebar and switcher. You have two inputs:

- **Logo** — upload a PNG, JPEG, WEBP, GIF, or SVG file. After upload, a **Remove logo** button appears next to the file input so you can clear it again. If an upload fails, the error message is shown inline.
- **Brand color** — sets the hue used for the auto-generated pattern icon when no logo is present. The color is configurable through the native color picker or a free-form `#rrggbb` text field. Leave it empty for the auto-generated color; a **Clear** button appears when a value is set.

A live preview of the tile (logo and brand color combined) is rendered to the left of the fields so you can see the result before saving.

Hiring

The **Hiring** section contains one switch:

- **Require board approval for new hires** — when on, every agent the CEO or a manager tries to hire stays pending until a board member approves it from the approvals queue. When off, hires go through immediately. This ties directly into the flow described in the [Approvals guide](../guides/day-to-day/approvals.md).

The toggle saves immediately; there is no separate save button for this setting.

Feedback Sharing

The **Feedback Sharing** section controls whether AI outputs you explicitly vote on in EKVAAR OS may also be shared with EKVAAR OS Labs. The toggle is labelled **Allow sharing voted AI outputs with EKVAAR OS Labs**.

Two things to know:

- Votes are always stored locally, regardless of this setting. The toggle only controls whether the voted outputs become eligible for sharing.
- The section displays the current terms version, and, once sharing is enabled, the timestamp of when it was turned on and who enabled it. A **Read our terms of service** link is shown when the terms URL is configured.

Company Packages shortcuts

Below the feedback section, a **Company Packages** panel links out to the dedicated **Export** and **Import** pages. These are the same pages covered in the last two sections of this guide; the Settings page itself does not perform the export or import.

Danger Zone

At the bottom of the page is a **Danger Zone** with an **Archive company** button. Archiving hides the company from the sidebar and persists the change in the database. A confirmation dialog appears before the archive takes effect, and the UI automatically switches you to the next non-archived company if one is available.

Archiving also quiets the company so it stops doing work in the background: every active agent is paused (with the pause reason `company_archived`), and any queued or

in-flight wake-up requests are cancelled. Archiving is not destructive — unlike deletion, your agents, projects, and issues are all preserved — but the company will not wake its agents again until you bring it back.

Access & Members

The **Company Access** page is where you manage human memberships: who belongs to the company, what role they hold, and which permissions they have on top of that role. Open it from **Settings → Access**, or directly from the sidebar.

Roles

EKVAAR OS uses four human membership roles. The role determines a set of implicit permission grants:

- **Owner** — full company access. Includes creating agents, inviting humans and agents, managing members and grants, assigning tasks, and approving join requests.
- **Admin** — operator with invite and approval powers. Can create agents, invite users, assign tasks, and approve join requests.
- **Operator** — a hands-on member who helps run work. Can assign tasks.
- **Viewer** — read-only access. No built-in grants.

The role drop-down in the edit dialog also accepts **Unset**, which leaves the member without any implicit grants.

> **Note:** EKVAAR OS's agent chain of command (CEO, managers, reports) is separate from these human roles. Human roles gate access to the EKVAAR OS UI and company-level actions; agent roles describe the reporting tree inside the company. See [Org Structure](../guides/org/org-structure.md) for the agent side.

The members list

The members section shows one row per human member with:

- **User account** — display name and email (or principal id if neither is set).
- **Role** — the human membership role, or "Unset".
- **Status** — `active`, `pending`, or `suspended`, rendered as a coloured badge.
- **Grants** — a comma-separated summary of any explicit permission grants attached to the member. Shows "No explicit grants" when the member only relies on implicit role grants.

- **Action** — an **Edit** button that opens the member editor.

If you do not have permission to manage members, EKVAAR OS replaces the page body with a message explaining why. An instance admin who is viewing the page without an active company membership sees a banner noting that the current account has admin-level access but is not a member of this company.

Editing a member

Clicking **Edit** opens a dialog with three controls:

1. **Company role** — the same role list as above, plus "Unset".
2. **Membership status** — `Active`, `Pending`, or `Suspended`.
3. **Grants** — a two-column grid of explicit permission grants. A read-only panel above the grid lists the grants the selected role provides implicitly. Checking a box here stores the grant explicitly on the member, so it persists even if the role later changes.

Available permission keys include `agents:create`, `users:invite`, `users:manage_permissions`, `tasks:assign`, `tasks:assign_scope`, and `joins:approve`. Each box is labelled with a human name and its underlying key for reference.

Click **Save access** to persist the changes, or **Cancel** to close the dialog without saving.

Adding and removing members

The Access page does not have an "Add member" button. New humans enter the company through the invite flow described in the next section, which either produces a direct membership or a pending join request depending on how the invite is consumed. To remove a human, set their **Status** to `suspended` through the Edit dialog; the row stays visible so the audit trail is preserved.

Pending human joins

If you hold the `joins:approve` grant and there are pending human join requests, a **Pending human joins** card appears above the members list. Each entry shows the requester's name, email, and the invite context, with **Approve human** and **Reject human** buttons. This card duplicates the subset of the join request queue that applies to humans — full coverage (including agent joins) lives on the queue page.

Invites

The **Company Invites page creates invite links for new humans. Each link is single-use — the first successful use consumes the link and creates or reuses a join request before approval.**

![Invite link creator](../user-guides/screenshots/light/company/invites.png)

Creating an invite

The **Create invite card has one required choice: which role the invite should request by default. The options are the four roles described above — **Viewer**, **Operator** (the default), **Admin**, and **Owner** — each rendered with a short description and a one-line summary of what the role gets.**

Clicking **Create invite does three things:**

1. Generates a new invite link against the current EKVAAR OS domain.
2. Copies the URL to your clipboard if the browser allows it.
3. Shows the invite in a **Latest invite link panel below the form.**

If the clipboard is unavailable, EKVAAR OS shows a warning toast and you can copy the URL manually from the field. The invite URL is clickable as an **Open invite button for quick testing in another tab.**

Invite expiry and state

Invite links have four possible states, shown as a badge in the history table: **Active, **Accepted**, **Expired**, and **Revoked**. Only `Active` invites can be consumed — the link becomes `Accepted` on first use and can be `Revoked` manually from the same page.**

Invite history

Below the creator is a paginated **Invite history table with one row per invite:**

- **State — the badge above.**
- **Role — the default role the invite requests.**
- **Invited by — the name and email of the human who created the invite.**
- **Created — the creation timestamp.**
- **Join request — a link to the join request queue if the invite has produced one.**
- **Action — a **Revoke** button for invites still in the `Active` state.**

The table shows five invites at a time and includes a **View more button when there are more pages. An **Open join request queue** link in the header jumps to the full queue.**

What the invited person sees

When a human opens the invite URL, they land on a EKVAAR OS join page that creates a join request tied to the invite. If the invite carries a default role (for example **Operator**), that role is attached to the request so approvers can see it in context. The member does not become active until someone with `joins:approve` approves the request.

Join Requests

The **Join Request Queue** consolidates every join request — human and agent — that has come in against the company. Open it from `/inbox/requests`, or from the **Open join request queue** link in Invites.

Filters

Two drop-downs sit above the list:

- **Status** — `Pending approval` (the default), `Approved`, or `Rejected`.
- **Request type** — `All`, `Human`, or `Agent`.

Changing either filter refreshes the list. "Approved" and "Rejected" are useful when you want to audit past decisions.

What's on each card

Each request card shows:

- A **status** badge (`pending approval`, `approved`, or `rejected`), a **request type** badge (`human` or `agent`), and, for agent requests, an **adapter type** badge.
- The requester's name and a secondary identifier — email for humans, capabilities or source IP for agents.
- An **Invite context** panel with the invite's `allowedJoinTypes` and default role, plus the invite message if one was attached.
- A **Request details** panel with the submission timestamp, source IP, and agent capabilities (when applicable).

For requests in `pending approval`, the card also shows **Approve** and **Reject** buttons. Once acted on, the card stays in the list under the new status filter for audit purposes but no longer exposes action buttons.

Permissions

The queue requires the `joins:approve` grant. Accounts without it see a "You do not have permission to review join requests for this company." message instead of the list.

Export

The **Company Export** page turns the current company — its agents, projects, tasks, skills, and settings — into a portable markdown package you can download as a zip. Open it from the **Org Chart** header or from the **Export** shortcut on the Settings page.

What gets included

When the page loads, EKVAAR OS builds a preview of everything that would be exported. By default the preview includes the company metadata, every non-terminated agent, every non-archived project, and every issue. The preview is rendered as a left-hand **Package files** tree, with a selected-file preview on the right.

The sticky bar at the top of the page shows:

- The company name and a running count of **selected / total files**.
- Any warnings EKVAAR OS produced while building the preview.
- A single **Export N files** button that downloads the zip.

Selecting what to export

Every entry in the file tree has a checkbox. Unchecking a file or a directory removes it from the download. A couple of details worth knowing:

- The tree is searchable with the input above it. Search expands matching directories automatically and restores the previous expansion state when you clear the query.
- `README.md` and `.EKVAAR OS.yaml` are regenerated on the fly so they always reflect the current selection.
- The `tasks/` directory is paginated — ten entries visible by default, with a **Show more issues** button. Checked and search-matched tasks are always pinned above the fold.
- Clicking a file opens its content in the preview pane. The URL updates as you navigate so you can deep-link to a specific file in the export.

Downloading

Click **Export N files** to build the final package. EKVAAR OS assembles the zip with the filtered files (including the regenerated README and `.EKVAAR OS.yaml`) and triggers a browser download. A success toast confirms the file count and the zip's root path.

For a deeper description of what lives in each file, see [Export & Import](../guides/power/export-import.md).

Import

The **Company Import** page is the reverse direction: it takes an exported package and loads it into EKVAAR OS, either as a new company or on top of an existing one.

Choosing a source

The **Import source** section supports two source types:

- **GitHub repo** — paste a tree or blob URL pointing at a folder that contains a `COMPANY.md`.
- **Local zip** — upload a `.zip` package exported from EKVAAR OS. EKVAAR OS warns against re-zipping archives in Finder or Explorer; use the download from the Export page.

Choosing a target

The **Target** drop-down has two options:

- **Create new company** — the default. An optional **New company name** field lets you override the name from the package.
- **Existing company** — apply the package on top of the currently selected company.

Collision strategy

The **Collision strategy** drop-down controls what happens when an incoming item clashes with something that already exists in the target company:

- **Rename on conflict** — the default. EKVAAR OS proposes a new name (prefixed with the package name, for example `gstack-CEO`) for each conflicting entity.
- **Skip on conflict** — existing items are kept and the incoming copy is dropped.
- **Replace existing** — overwrites the current entity with the incoming version.

Preview

Click **Preview import** to run the preview without applying anything. The preview populates three things:

1. A **Renames** list showing every agent and project that collided and what it will be renamed to. Each row has a free-form input for the target name, a **skip** button, and a **confirm rename** button that locks the chosen name in.
2. An **Adapters** list for every agent in the package, with a drop-down of available adapters. New agents default to the same adapter as the target company's CEO. A **configure adapter** button expands an inline config form so you can set per-agent values (environment, working directory, etc.) before the import runs.
3. A file tree identical in layout to the export tree, but with an **action badge** on each row (`create`, `update`, `skip`, or `replace`) so you can see what EKVAAR OS plans to do to every file. Directories that will be renamed show an arrow and the target name.

The sticky bar at the top counts selected files and surfaces the number of conflicts and errors.

Applying the import

When you are happy with the preview, click **Import N files**. The button is disabled if there are errors in the preview or no files selected. On success, EKVAAR OS refreshes the companies list, navigates you to the dashboard of the imported (or updated) company, and restores the imported sidebar order if the package included one.

Existing-company imports are non-destructive in the safe import path: incoming issues are always created as new issues, and `replace` is blocked by the server for safe imports. If you need a full replace, use the dedicated instance-admin flow instead.

See [Export & Import](../guides/power/export-import.md) for the structural reference — the field-by-field description of the package format complements the walkthrough above.

Company administration covers the pieces of EKVAAR OS that sit around the agents rather than inside them: identity, membership, and portability. Once you have the company set up and people invited in, day-to-day work happens in the approvals queue, the dashboard, and the task surfaces that the rest of this guide set covers.

Settings

EKVAAR OS has two settings surfaces, and it matters which one you're looking at.

Profile is *your* account — your display name and the avatar that shows up next to your comments. Changing it only affects how *you* appear. Other board users on the same instance have their own profiles and see their own.

Instance Settings is the admin surface. Anything you change there applies to the whole EKVAAR OS instance — every company, every user, every agent that runs against this install. If you're running EKVAAR OS on a VPS that hosts five companies, a toggle on the Instance page flips for all five.

This guide walks through both, section by section.

Profile



Open the Profile page from the account menu in the sidebar. It's scoped to you — nobody else's profile changes when you edit yours.

You get three things to work with:

- **Avatar** — click the round image (or the **Upload photo** button) to pick a new image from disk. It's uploaded into EKVAAR OS's file storage under the currently selected company's asset space. If no company is selected you can't upload — the page will tell you to select one first. Once an image is set, a **Remove** button appears next to the upload control.
- **Display name** — the name shown in the sidebar account footer and as the author on any comments you post. It falls back to "Board" if left blank. The field is capped at 120 characters.
- **Email** — read-only. Your email is managed by the auth session (the login provider), not by this page. If you need to change it, update it wherever you signed in from.

Click **Save profile** to persist name or avatar changes. The button is disabled while the name is empty or a save is in flight.

> **Note:** The avatar is stored as an asset under the *selected company*, but the profile itself is a user-level record. If you switch which company is selected in the sidebar later, your avatar keeps working — it's just that new uploads go to whichever company is active when you upload.

Instance: General



This is the top of Instance Settings. It's where you see how the instance was deployed and flip a few cross-cutting toggles.

Deployment and auth

At the top of the page, a small mode badge tells you which deployment profile this instance is running under. The text underneath explains what that means in practice:

- **Local trusted** — the instance is treating browser requests as a local board operator. No sign-in is required. This is the default when you run EKVAAR OS on your own machine.
- **Authenticated public** — sign-in is required and the instance is intended to sit on a public URL.
- **Authenticated private** — sign-in is required, but the instance is intended for a private network (LAN, VPN, or similar).

Three status boxes summarize readiness:

- **Auth readiness** — whether the auth subsystem is fully configured.
- **Bootstrap status** — "Setup required" if the initial CEO/board setup hasn't completed yet, otherwise "Ready".
- **Bootstrap invite** — whether an active first-run invite link is outstanding.

These fields are informational. To change them you change the deployment itself — see [Environment Variables](../reference/deploy/environment-variables.md).

Censor username in logs

Hides the username segment inside home-directory paths and similar operator-visible log output. Useful if you're sharing screen recordings or pasting transcripts. Off by default. Note that bare username mentions outside of path strings are not masked in the live transcript view — this is a best-effort filter, not a guarantee.

Keyboard shortcuts

Enables the app's keyboard shortcuts — inbox navigation, creating issues, toggling panels, and so on. Off by default because they conflict with browser or screen-reader shortcuts for some users. Turn it on if you want faster navigation.

Backup retention

Controls how long automatic database backups are kept at each tier. EKVAAR OS takes daily backups and then thins them out over time:

- **Daily** — full daily backups kept for the selected number of days.
- **Weekly** — one backup per week kept for the selected number of weeks.
- **Monthly** — one backup per month kept for the selected number of months.

Each tier is a preset picker, so you can only choose from vetted retention windows. Backups are gzipped on disk. Longer retention means more storage — raise the windows only as far as your disk and compliance story require.

AI feedback sharing

Controls whether thumbs-up / thumbs-down votes on AI output can send the voted output to EKVAAR OS Labs. Three states exist:

- **Prompt (default)** — no choice has been made yet. The next time you vote, EKVAAR OS will ask once and save your answer.
- **Always allow** — voted AI outputs are shared automatically.
- **Don't allow** — voted AI outputs stay local.

The local vote is always saved regardless — this setting only controls whether the *content* leaves your instance. There's a link to the terms of service on the same card.

Sign out

A plain **Sign out** button at the bottom. It ends your session and sends you back to the login page. On a local-trusted instance there's usually nothing to sign out of, but the button is always present.

Instance: Access

Instance Access is where you promote users to **instance admin** and pick which companies each user can see. This is different from the roles you grant *inside* a company.

Instance-level vs. company-level roles

It's worth being explicit about this because the two feel similar:

- A **company membership lets a user see and act within one specific company. A user can be a member of several companies, each with its own membership role (operator, manager, etc.). This is set per-company.**
- An **instance admin can see and manage the instance itself — add/remove instance admins, grant users company access, and open admin-only surfaces. This is set per-user on this page.**

A user can be an instance admin without being a member of every company, and a company member without being an instance admin. The two layers are independent.

Finding and inspecting a user

The left pane is a search box and a scrollable user list. Type a name or email to narrow it down. Each row shows:

- The user's name and email
- A green shield icon if they're currently an instance admin
- A count of active company memberships

Click a user to load their detail view on the right.

Promote to instance admin

In the detail view, a button toggles the user's instance-admin status: **Promote to instance admin if they're not one, or **Remove instance admin** if they are. The change takes effect immediately. Be deliberate — instance admins can grant themselves access to any company and can demote other instance admins.**

Company access

The lower half of the detail view is a grid of every company on the instance with a checkbox next to each. Tick the ones this user should be a member of, untick the ones they shouldn't, and click **Save company access.**

Adding access creates an *active operator* membership by default. If the user needs a higher role inside that company (manager, for example), switch to that company and raise their role there — this page only controls *whether* they have access, not *what role* they have.

Beneath the checkbox grid, **Current memberships lists what's actually on record, with role, status, and the last update date. Treat this as the source of truth — if it doesn't match what you set in the checkboxes, re-save.**

> **Tip:** Running a VPS-hosted instance that hosts multiple companies? Use this page to onboard new people without sharing the database. Create their auth account (through your login provider), find them here, tick the companies they need, and save.

Instance: Adapters

The Adapters sub-page (Instance Settings → **Adapters**) is the operator view of every adapter currently registered against this EKVAAR OS install. Adapters are how EKVAAR OS talks to an AI runtime — Claude's local CLI, Codex, OpenAI, OpenClaw, and so on — so this is the surface you use when you need to add a new runtime, hide one from agent hiring menus, or upgrade a runtime's package to a newer release.

> **Alpha:** The external adapter system is still under active development. APIs and storage format may change between releases — reach for this page when you need it, but expect the details to keep evolving.

Installed adapters

The page has two sections, stacked top-to-bottom:

- **External Adapters** — anything you have added yourself, whether from an npm package or a local path. Each row shows the adapter's display label, its registered `type`, the package name, the version, and how many models the adapter exposes.
- **Built-in Adapters** — the adapters that ship inside EKVAAR OS itself. They cannot be removed, only hidden. If an external adapter has overridden a built-in (for example, a forked version of the Claude adapter installed from npm), you also see a synthesised "built-in" row tagged **Overridden by …** so it is obvious which built-in has been shadowed.

A small origin icon sits next to each external adapter: a folder for adapters installed from a local path, and a package icon for adapters installed from npm. Versions appear as a mono-typed `v1.2.3` badge.

Health status

The row badges are the fastest way to read adapter health:

- **External** / **Built-in** — the source of the adapter.
- **v{version}** — the currently loaded package version.

- **Overrides built-in** — this external adapter is replacing a built-in of the same `type`.
- **Hidden from menus** / **Override paused** — the adapter still exists but is not offered when creating or hiring agents. Use this to stage a rollout without uninstalling.

Beneath the label, a subtitle line shows `type`, the npm package name (when different from the type), and the model count. A zero model count usually means the adapter loaded but could not enumerate models — check the package configuration before enabling it for agents.

Enable / disable

Every row has a **power** icon on the right-hand side. Clicking it toggles the adapter's visibility without deleting anything:

- For regular adapters (both built-in and plain external), the power button flips the **Hidden from menus** state. Hidden adapters are kept registered and existing agents on that adapter continue to run, but the adapter is omitted from the adapter dropdown when creating new agents.
- For external adapters that **override a built-in**, the power button instead pauses or resumes the override. Pausing the override snaps every agent of that `type` back to the built-in implementation on their next run; resuming restores the external adapter.

Two more icons may appear on external rows:

- **Reload** (circular arrow) hot-swaps the adapter module in the running process. Useful after you have published a new version of a local-path adapter and want to pick up changes without bouncing EKVAAR OS.
- **Reinstall** (download arrow) opens a confirmation dialog that checks the npm registry for the latest version, then pulls it and reinstalls the package. Existing agents will use the new version on their next run.

A **Remove** (trash) icon is available on external adapters only. Removing an adapter unregisters it, tears down its npm install on disk, and cannot be undone — EKVAAR OS prompts for confirmation first.

Per-adapter config

Adapters themselves do not expose configuration on this page — they are packages, not configurable singletons. Each **agent** picks an adapter and then fills in the fields that adapter requires (working directory, environment variables, credentials). Those per-agent fields live on the agent's Configuration tab, not here.

What this page gives you is the ability to add, upgrade, and retire the adapter packages that populate the agent adapter menu. To install a new external adapter, click **Install Adapter** in the top-right of the page. A dialog appears with two source modes:

- **npm package** — enter the package name (for example `my-EKVAAR OS-adapter`) and optionally a version. EKVAAR OS installs the package from npm and registers it.
- **Local path** — paste a Linux, WSL, or Windows path to a checked-out adapter package. EKVAAR OS auto-converts Windows paths and installs the adapter from disk. Local-path adapters are the fastest way to iterate on a new adapter before publishing.

In both cases the adapter package must export `createServerAdapter()` — the dialog reminds you of this contract.

For the full catalog of adapters EKVAAR OS supports out of the box, along with the per-agent fields each one expects, see the reference docs: [Adapters overview](../reference/adapters/overview.md).

Instance: Scheduler Heartbeats



The Scheduler Heartbeats page is a cross-company view of every agent on the instance that has a **timer heartbeat** enabled.

What the scheduler does

EKVAAR OS's scheduler is the component that wakes up timer-driven agents on an interval. It reads each agent's `runtimeConfig.heartbeat` block, notices when the next tick is due, and fires the run. Event-driven wakes (assignments, comments, routines) don't go through this surface at all — they happen regardless of the timer state.

For a deeper explanation of when to use timer heartbeats vs. event-driven wakes, read [Heartbeats & Routines](../guides/projects-workflow/routines.md). In short: timer heartbeats should be the exception, not the rule.

What this page shows

At the top of the page, a summary line reports:

- How many timer heartbeats are **active** (enabled and the scheduler considers them live)

- How many are **disabled**
- How many companies the list spans

Below that, agents are grouped by company. Each row shows:

- An **On/Off** badge for whether the scheduler sees the heartbeat as active
- The agent's name (links to the full agent config)
- The agent's title or role
- The configured interval in seconds
- When the last heartbeat ran, as a relative time ("2m ago", "never")
- A link icon to jump to the agent config, and a button to **Enable Timer Heartbeat** or **Disable Timer Heartbeat** inline

The list auto-refreshes every 15 seconds so you can watch an enable/disable take effect.

When to tune it

Reach for this page when:

- You suspect an agent is burning budget on idle wakeups. Find it in the list, check the interval, and either raise the interval on the agent config page or disable the heartbeat.
- You've just imported or cloned an instance and want to take stock of every timer-driven agent in one place before turning any of them loose.
- You need a quick emergency shut-off. The **Disable All** button at the top right of the summary line disables the timer heartbeat on every currently-enabled agent in one operation. It prompts for confirmation first. Event-driven wakes still work afterwards — this only stops the *tickers*.

Safe defaults

- **Most agents** should have timer heartbeats **off**. They stay active on the dashboard and wake on assignments, comments, and routines. This is EKVAAR OS's default for new agents.
- **When a timer is truly needed** (polling an external system with no webhook, for example), push the interval as long as you can stand. Minutes or hours, not seconds.
- **After an import** or major config change, check this page — other instances' timer settings will come with them, and you may want to disable the ones you don't recognize before the scheduler starts firing them.

Instance: Experimental



Experimental flags opt the instance into features that aren't yet defaults. They're gated here because they may change behaviour, performance, or migrations before they graduate.

What "experimental" means here

An experimental flag in EKVAAR OS is a feature that:

- Has shipped and works,
- Is being evaluated against real usage before it becomes the default, and
- May be renamed, reworked, or promoted to a core setting in a future release.

Turning one on is not dangerous in the "this will break your data" sense — but it does mean you're opting into behavior that may change how agents run or how the backend restarts. Flip flags when you have a reason to, not for curiosity, and expect to re-read the release notes if you upgrade.

The available flags

- **Enable Isolated Workspaces** — shows the execution-workspace controls in project configuration and allows isolated workspace behavior for new and existing issue runs. If you're not using isolated workspaces, leave this off; turning it on exposes extra UI you don't need.
- **Auto-Restart Dev Server When Idle** — only relevant under `pnpm dev:once`. When the backend detects a stale boot (code changes, new migrations), it waits for queued and running local agent runs to finish and then restarts the dev server automatically. Useful during active development on EKVAAR OS itself, not intended for production.

Both toggles take effect immediately on save. If one misbehaves, flip it back off — no migration is required.

Where to go next

- [Heartbeats & Routines](../guides/projects-workflow/routines.md) — the full picture of timer vs. event-driven wakes, and how to configure individual agents.
- [Environment Variables](../reference/deploy/environment-variables.md) — the deployment-level settings that the General page reports on (auth mode, bootstrap state, exposure).

Trust & Low-Trust Review

Some work in a EKVAAR OS company is born from input you cannot vouch for: an untrusted pull request, an external ticket, a dependency diff, or output an agent generated from any of those. The goal of trust presets is simple — keep that kind of work *contained* while it runs, and make sure nothing it produces is silently fed into a more trusted agent before a human (or a trusted reviewer) has looked at it.

This page explains the two trust presets EKVAAR OS ships with, what actually changes when an agent or its work is treated as low-trust, and how that work gets reviewed and promoted before it counts as accepted.

It helps to read [Execution Policy](../guides/power/execution-policy.md) first — trust presets layer on top of the same execution-policy plumbing, and a low-trust run leans on the isolated workspace and sandbox mechanics described there.

> **This is containment, not privacy. Standard work in a EKVAAR OS company stays company-visible by default — board users and in-company actors can still inspect company work objects. Low-trust containment is narrower: it limits what a low-trust agent can read or change through the EKVAAR OS API, and it stops raw untrusted output from being automatically promoted into higher-trust agent context. It is not a general project, issue, or human privacy system.**

The two presets

EKVAAR OS ships exactly two core trust presets, so containment decisions are enforced everywhere — including Community Edition, even when policy editing in the UI is not available.

- **`standard` — the default. This is the normal, company-visible collaboration model you already know. Regular agents behave exactly as they always have, and this is what every agent gets unless a policy says otherwise.**
- **`low_trust_review` — an opt-in containment preset for automated work that may consume hostile or prompt-injected input. Turn it on for the kinds of tasks where you would not want the agent's reading and writing reach to extend across the company, and where its output should be quarantined until reviewed.**

The default preset is `standard`; `low_trust_review` only takes effect when a policy explicitly opts in.

How a preset is chosen

A low-trust preset is not a single switch. EKVAAR OS resolves the effective preset by reading the same JSON policy you already use for execution, from up to four sources:

Source	Where it lives
Agent	the agent's `permissions` — `trustPreset` and `authorizationPolicy.trustBoundary`
Project	the project's `executionWorkspacePolicy.authorizationPolicy`
Issue	the issue's `executionPolicy.authorizationPolicy`
Run	the run's `executionPolicy.authorizationPolicy`

The resolver combines these. If *any* source asks for low-trust — either by naming the `low_trust_review` preset or by carrying a `trustBoundary` — the effective preset becomes `low_trust_review` for that work. The boundaries from each source are then intersected: **narrower always wins**. You cannot widen a boundary by relaxing one layer; you can only tighten it.

Two things make resolution **fail closed** (the work is denied rather than run with weaker containment):

- A policy source that names a *different* company, or uses an unsupported preset value.
- A low-trust preset that does not resolve to a concrete scope. Low-trust review must land on a real, company-local target — a root issue, one or more project ids, or an explicit list of issue ids. If none of those is present, resolution is denied.

Inside a trust boundary

When `low_trust_review` resolves, it produces a single merged boundary. These are the fields you can set on a `trustBoundary`, all scoped to one company:

- `mode` — always `low_trust_review`.
- `companyId` — the company the boundary belongs to. A boundary that names another company is rejected outright.
- `projectIds` — projects the low-trust work may touch.
- `rootIssueId` — an issue subtree the work is confined to.
- `issueIds` — an explicit allow-list of issues.
- `allowedAgentIds` — agents permitted within the boundary.
- `allowedSecretBindingIds` — the secret bindings the run may reference.
- `allowedToolClasses` — the tool classes the run is allowed to use.
- `outputPromotionTarget` — where promoted output is allowed to land (an issue).

At least one of `rootIssueId`, `projectIds`, or `issueIds` must be present — that concrete scope is what the resolver requires before it will allow low-trust work to run.

What changes at runtime

When a run resolves to `low_trust_review`, EKVAAR OS refuses to start it unless it can actually enforce the boundary. A managed low-trust run **fails closed** unless all of the following hold:

- **Isolated workspaces are enabled** for the instance. Without them there is nowhere safe to contain the work.
- **The execution workspace mode is `isolated_workspace`.** A shared or host-local workspace is not acceptable for low-trust work.
- **The issue being run is inside the resolved boundary** — either directly named, in an allowed project, or a descendant of the boundary's `rootIssueId` (ancestry is checked up to a bounded depth). An issue outside the boundary is rejected.
- **The environment uses the `sandbox` driver.** A host-local adapter process is not allowed for managed low-trust execution; you need a sandboxed environment instead.

On top of that, two further constraints apply:

- **Secrets are restricted.** A low-trust run may only reference secret bindings whose ids are listed in the boundary's `allowedSecretBindingIds`, and inline sensitive environment values (raw API keys, tokens, and the like) are rejected — they must come through allowed bindings, not be pasted in.
- **Runtime services are denied by default.** A low-trust run cannot start or mutate workspace runtime services unless the boundary explicitly grants the `runtime.manage` tool class. If it tries to and that grant is absent, the run is stopped.

The built-in low-trust tool classes are read-only and conservative by design: `git.read`, `github.pr.read`, and `tests.local`. That is the shape of work this preset is meant for — read the untrusted change, run local tests, report back — not reach out and mutate the wider company.

If you have been doing untrusted-PR review by hand with a local Docker workflow, that still works for manual review. But anything EKVAAR OS runs as managed low-trust execution goes through the sandboxed, isolated path described above.

Reviewing and promoting low-trust output

Containment at runtime is only half the story. The other half is what happens to whatever the low-trust agent writes.

When a low-trust agent creates an issue, comment, document, or work product, EKVAAR OS tags that artifact with **source-trust metadata** and gives it the disposition `quarantined`. Quarantined artifacts are stored, but their raw bodies are held back from higher-trust agent context. Where a higher-trust agent would otherwise read the body, it instead sees a placeholder explaining that quarantined low-trust output was omitted and that a trusted reviewer can inspect and promote a sanitized version. Comment presentation and metadata are stripped alongside the body, so nothing in the raw artifact leaks into a trusted run by accident.

The source-trust record carries enough provenance to audit the work later:

- `preset` — the trust preset that produced the artifact.
- `disposition` — `quarantined` or `promoted`.
- `sourceIssueId`, `sourceRunId`, `sourceAgentId` — where the artifact came from.
- `promotedFrom` — the original artifact a promotion was based on, including its `artifactKind` (`issue`, `comment`, `document`, or `work_product`), `artifactId`, and `issueId`.
- `promotedByActorType` (`agent`, `user`, or `system`), `promotedByActorId`, and `promotedAt` — who promoted it and when.

Promotion is the deliberate, reviewed step that turns quarantined output into something a trusted agent can act on. A trusted reviewer inspects the quarantined artifact, and a sanitized version is written with disposition `promoted` and a `promotedFrom` link back to the original. Only then does the content flow into higher-trust context. Nothing is auto-promoted — raw untrusted output never gets silently upgraded.

This source-trust tag lives on the artifact itself: issues, issue comments, documents, and issue work products each carry it, so the quarantine and promotion state travels with the work wherever it is read.

When to reach for low-trust review

Reach for `low_trust_review` when an agent's task is to chew on input you do not control and you want a hard guarantee that its reach and its output stay contained:

- Reviewing an untrusted or external pull request.
- Triaging tickets or reports submitted from outside the company.
- Inspecting dependency diffs or third-party changes.
- Running an agent over any content that could carry a prompt-injection payload.

For everything else, `standard` is the right default — it keeps normal collaboration fast and company-visible, which is what most work wants.

Plugins

Some things EKVAAR OS does out of the box — run agents, manage tasks, call adapters. Plenty of other things it does not, because they're too specific to your setup: a Hello World widget on the dashboard, a file browser for your project workspaces, a smoke-test runner for a third-party service you happen to use. Plugins are how you add those.

A plugin is a self-contained package that installs into EKVAAR OS, runs its own background worker, and can contribute its own pages, widgets, and settings into the EKVAAR OS UI. Unlike an [agent adapter](../guides/org/agent-adapters.md) — which teaches EKVAAR OS how to talk to a new AI model — and unlike a [skill](../guides/org/skills.md) — which is a reusable instruction document an agent loads into its prompt — a plugin is a piece of software that extends EKVAAR OS itself. It has its own code, its own process, and its own surface in the UI.

> Plugins are in alpha. The runtime and APIs are still shifting, so expect breaking changes for now and pin versions where you can.

The Plugin Manager

The Plugin Manager lives under **Settings → Plugins**. It's the single place where you install, enable, disable, configure, and uninstall plugins.



(../user-guides/screenshots/light/plugins/list.png)

The page has two sections:

- **Available Plugins** — the plugins bundled with your EKVAAR OS checkout, discovered automatically from the packages on disk. This includes the reference example plugins *and* first-party plugins like the LLM Wiki when they're part of your checkout. Each is labelled **Bundled**, and ones that aren't production-ready yet carry an **Experimental** badge. Useful for seeing what plugins can do and for smoke-testing the plugin runtime on a fresh instance.
- **Installed Plugins** — everything you've installed on this EKVAAR OS instance. Each row shows the plugin name, its package and version, a short description, a status badge, and quick actions.

Status badges

Every installed plugin has a status that tells you what the runtime is doing with it.

Status	What it means in practice
ready	The plugin is installed, enabled, and its worker is running. This is the steady state you want.
disabled	You (or another operator) turned the plugin off. Its worker is stopped, scheduled jobs don't fire, and any UI contributions are hidden. Config and data are preserved.
error	Something went wrong — the worker crashed on startup, a health check failed, or an upgrade broke. The plugin row shows a short error summary and a **View full error** button for the full stack trace.
upgrade_pending	A new version of the plugin has been staged, and it asks for capabilities the installed version didn't have. EKVAAR OS is holding it offline until you approve the new permissions.
installed	A transient state right after install, before the first successful load. You usually won't see it for long — the plugin moves to `ready` (or `error`) within a second or two.
uninstalled	The plugin has been removed. It won't appear in the list anymore unless you reinstall it.

If the badge is green it's running. If it's grey it's intentionally off. If it's red or amber, read the message — the UI is telling you something needs your attention.

Reading an error row

When a plugin is in `error`, the row expands to show a short error summary — the first non-empty line of the stored error message — and a **View full error** button. Clicking it opens a dialog with the complete stack trace or failure output, wrapped and scrollable.

The summary is usually enough to know what to do:

- **"Cannot find module ..."** or **"Failed to load manifest"** — the package is malformed or its build output is missing. Reinstall it, or rebuild it if you're developing locally.
- **"Worker exited with code 1"** — the worker crashed on startup. The full error has the stack trace. Most common causes: missing configuration (go fill in the settings form), a secret that hasn't been provided, or an external service the plugin depends on being unreachable.
- **"Health check failed: ..."** — the worker started but a health check didn't pass. The message names which check failed; fix the underlying issue, then click the power button to re-enable the plugin.

An errored plugin stays installed — you don't need to uninstall and reinstall to try again. Once you've addressed the cause, clicking **Enable** puts it through the `error → ready` transition and EKVAAR OS tries to start the worker again.

Installing a plugin



There are two ways to get a plugin into EKVAAR OS.

From the Available Plugins list. Bundled plugins ship inside the EKVAAR OS repository. On the Plugin Manager page, scroll to the **Available Plugins** section and click **Install** next to the one you want. EKVAAR OS installs it straight from the local checkout — no registry round trip.

EKVAAR OS builds this list by scanning the plugin packages in your checkout, so what you see depends on what's bundled. Two kinds of plugin show up here:

- **Reference examples** — small, self-contained plugins that exist to demonstrate the runtime.
- **First-party plugins** — real plugins like the [LLM Wiki](../reference/plugins/llm-wiki.md) when they're vendored into your checkout. These are also published to npm, so on instances that don't bundle them you'd install by full package name instead; see *By npm package name* below.

First-party plugins that are still maturing carry an **Experimental** badge in this list — they work, but their behaviour or configuration may change between releases, so pin versions where you can.

The reference examples that ship today:

- **plugin-hello-world-example** — adds a Hello World widget to the dashboard. The minimum-viable plugin, useful as a reference.
- **plugin-file-browser-example** — adds a Files link to project sidebars and a file-browser tab to the project detail page, scoped to the project's workspace.
- **plugin-kitchen-sink-example** — demonstrates the full plugin surface in one package: pages, widgets, settings forms, scheduled jobs, webhooks. Good for exploring what a plugin can do.
- **plugin-authoring-smoke-example** — a thin smoke test for the plugin authoring workflow. Useful if you're working on a plugin of your own and want to confirm the runtime picks it up.

- **plugin-orchestration-smoke-example — a smoke plugin that exercises EKVAAR OS's orchestration-grade plugin APIs (scheduled jobs, webhooks, plugin-driven agent interactions). Useful as a reference when you're building a plugin that needs to coordinate work over time, not just render a widget.**

****By npm package name.** Click the **Install Plugin** button at the top right of the Plugin Manager. EKVAAR OS asks for an npm package name (for example, `@EKVAAR OSai/plugin-example`). Submit it and EKVAAR OS fetches, installs, and loads the package. Success or failure appears as a toast, and the plugin shows up in the installed list with its current status.**

In both cases the install flow does the same underlying work: download the package, validate its manifest, persist the plugin record, then attempt to move it through `installed → ready` by starting its worker. If anything in that chain fails, the plugin is parked in `error` with the failure message attached — it stays installed so you can inspect what happened instead of silently disappearing.

Enabling and disabling

Each installed plugin has a power button in the actions column. The button toggles between two lifecycle transitions:

- **Disable (when the plugin is `ready`) — EKVAAR OS stops the worker, cancels any in-flight scheduled jobs the plugin owns, and hides the plugin's UI contributions. Your configuration and any data the plugin has stored are preserved.**
- **Enable (when the plugin is `disabled`, `error`, or `upgrade_pending`) — EKVAAR OS starts the worker again and, if startup succeeds, moves the plugin back to `ready`.**

Disabling is the right move when a plugin is misbehaving, when you want to pause its scheduled jobs temporarily, or when you're about to change some external dependency and you'd rather the plugin not fire in the meantime. It's a safe, reversible operation — think of it as a "sleep" rather than a "remove".

Uninstalling

The trash icon next to the power button removes a plugin. EKVAAR OS asks you to confirm, because the action is not reversible from the UI: the plugin package is removed from disk, the installation artifacts are cleaned up, and the plugin is marked uninstalled. To get the plugin back, you'd reinstall it fresh.

Uninstalling stops the worker first, the same way disable does, so in-flight work is drained cleanly before the package is removed.

What "disabled" actually stops

Worth being explicit about, because it's the difference between "I'm pausing this for an hour" and "I need to start over":

- **Stopped:** the worker process, scheduled job runs, webhook delivery processing, UI contributions (pages, widgets, settings slots), and any health-check polling.
- **Preserved:** the plugin record itself, saved configuration (including secrets), historical job-run and webhook-delivery records, and log entries. When you re-enable the plugin everything resumes where it left off, on the same config.

This matters for plugins that integrate with billed services. Disabling stops the polling and the scheduled work — so you stop paying the API bill — without forcing you to re-enter credentials the next time you turn it back on.

Upgrades

When a plugin is upgraded to a new version, EKVAAR OS compares the capabilities declared in the new manifest against the ones you originally approved.

- If the new version asks for the same capabilities or fewer, EKVAAR OS upgrades it in place and the plugin returns to `ready` on the new version.
- If the new version asks for **new** capabilities that weren't there before — access to a new data surface, a new integration point — EKVAAR OS parks the plugin in `upgrade_pending`. The worker stays stopped until an operator looks at what changed.

To apply an upgrade pending approval, open the plugin's detail page, review the updated capabilities and description, and click **Enable**. That moves the plugin back to `ready` on the new version. If you're not happy with the new capabilities, you can leave the plugin in `upgrade_pending` indefinitely, or uninstall it.

This gate exists so plugins can't quietly grow permissions on you between versions. The first time a capability is requested is always a deliberate action you took.

The plugin detail page

Clicking a plugin's name — or the **Configure** button — opens the plugin detail page. This is where a plugin gets to show you its own surface inside EKVAAR OS.

![Plugin detail page](../user-guides/screenshots/light/plugins/detail.png)

The detail page has two tabs:

- **Configuration — the plugin's description, author, categories, and settings form (or a custom settings UI the plugin ships).**
- **Status — runtime diagnostics: worker process state, recent scheduled jobs, recent webhook deliveries, live health checks, and a rolling log of recent entries.**

A plugin can also declare a **page slot. When it does, the plugin gets its own route at `/<company-prefix>/plugins/<plugin-id>` and renders whatever it wants there — a full page, a dashboard, a multi-step flow. This is how something like the file-browser example adds a Files tab to project pages, or how a hypothetical CRM plugin might add a Contacts view to the sidebar.**

From your perspective as an operator, plugin pages behave like any other EKVAAR OS page: they're scoped to the currently selected company, they show up in breadcrumbs, and they respect your permissions. The plugin just gets a canvas to render on.

Plugins can also contribute smaller pieces — a widget on the dashboard, a tab on the project detail page, a link in a sidebar — rather than a full standalone page. These show up inline in the surfaces you already use, so you don't always have to navigate to the plugin detail page to get value out of it. The Hello World example adds a dashboard widget; the file-browser example adds a project tab; the kitchen-sink example scatters contributions across several surfaces so you can see what's possible.

If two plugins happen to contribute a page on the same route, EKVAAR OS refuses to choose between them and surfaces a conflict message instead. Uninstall one of the colliding plugins, or use the plugin-id URL directly (`/<prefix>/plugins/<plugin-id>`) to reach a specific one while you sort it out.

Plugin settings

Most plugins have some configuration: an API key, a base URL, a default folder, a list of watched repositories. EKVAAR OS gives plugins two ways to expose that to you.

![Plugin settings](../user-guides/screenshots/light/plugins/settings.png)

****Auto-generated forms.** If the plugin ships a JSON Schema describing its configuration, EKVAAR OS renders a form automatically on the Configuration tab. You fill in the fields, click **Save Configuration**, and EKVAAR OS stores the values securely. For plugins that support it, a **Test Configuration** button appears alongside save — it**

sends the current form values to the plugin's worker and reports back whether the config works, without persisting anything.

****Custom settings pages.** A plugin can also contribute its own settings UI — a multi-step wizard, a visual editor, a connection builder — via a `settingsPage` slot. When that's present, EKVAAR OS renders the plugin's custom UI instead of the auto-generated form. Everything still lives under the same Configuration tab so you always know where to look.**

Secrets

Fields the plugin marks as secret (API keys, tokens, passwords) are stored encrypted and never redisplayed in plain text. The form shows a masked placeholder once a secret has been saved; to change it, type a new value and save again. Leaving the masked placeholder as-is keeps the existing secret.

Permissions sidebar

To the right of the settings form, the **Permissions card lists the capabilities the plugin's manifest declares — a short, readable list of what this plugin is allowed to touch (for example, "read issues in this company", "write to project workspaces", "send outbound webhooks"). These are the same capabilities the `upgrade_pending` gate checks against on upgrade. If a plugin's permissions list doesn't match what you think it should be doing, that's a signal to investigate before enabling it.**

Jobs, webhooks, and logs

Plugins don't just sit there. Many of them run scheduled jobs — a sync every 15 minutes, a nightly reconciliation, a cleanup pass every Sunday — or receive webhooks from external services. The **Status tab on the plugin detail page is where you see that activity.**

![Plugin jobs log](../user-guides/screenshots/light/plugins/jobs-log.png)

The tab shows:

- **Worker process — whether the worker is running, its process ID, uptime, and how many crashes it has recovered from. If the worker crashes repeatedly, the crash count and last-crash timestamp surface here before anything looks broken in the rest of the UI.**
- **Recent job runs — the last handful of scheduled jobs the plugin fired, each with a status dot (green success, red failed, blue running, grey cancelled, amber queued), the**

trigger that caused it, and a relative time. A green dot and a short duration is the thing you want to see repeating.
- **Recent webhook deliveries** — incoming webhooks, each with a status and duration. Useful when you're debugging an integration that isn't firing.
- **Health status** — aggregate check results, polled every 30 seconds while the plugin is `ready`. If a specific check is failing (for example, "can reach external API"), you'll see it called out here long before it becomes a crash.
- **Recent logs** — the last 50 log entries the worker emitted, colour-coded by level. This is your first stop when something looks off.

The whole tab refreshes on a 30-second cycle, so you can leave it open while you tweak config or trigger a manual run elsewhere in EKVAAR OS.

Interpreting job status dots

The coloured dot next to each job run summarises the outcome at a glance:

- **Green** — the job succeeded. A steady stream of green dots at the expected cadence is what a healthy plugin looks like.
- **Blue (pulsing)** — the job is running right now. If a blue dot sticks around for much longer than you'd expect, the Recent Logs panel below is where you look next.
- **Amber** — the job is queued, waiting for the worker to pick it up. Brief amber is fine; persistent amber usually means the worker is busy or stuck.
- **Red** — the job failed. The log entry with a matching timestamp will have the reason.
- **Grey** — the job was cancelled, typically because you disabled the plugin while it was scheduled.

Webhook delivery dots follow similar colours: green for processed, blue for received, amber for pending, red for failed.

Authoring your own plugin

If none of the installed plugins do what you need, you can write one. Plugins are npm packages with a `EKVAAR OSPlugin` manifest block, a worker entry, and an optional UI bundle — the example plugins under `packages/plugins/examples/` are a good starting point.

The full authoring path lives outside this guide:

- The `EKVAAR OS-create-plugin` skill scaffolds a new plugin package, including the manifest, worker, and a minimal UI surface.

- The EKVAAR OS CLI (`EKVAAR OSai`) wraps common authoring tasks — scaffolding, dev serving, building, and publishing. See the [CLI overview](../guides/getting-started/your-first-agent.md) and the plugin adapter documentation in the main EKVAAR OS repository for details.

Once your plugin builds, install it with **Install Plugin** on the Plugin Manager page the same way you'd install anything else. During development you can also point the installer at a local path — the bundled **Install** flow is the same mechanism, just targeted at a package inside your checkout.

Developing plugins locally

If you're iterating on your own plugin rather than running a published one, the friendliest loop is the CLI-driven local-path install: `EKVAAR OSai plugin init` scaffolds the package, `pnpm dev` runs a watch build, and `EKVAAR OSai plugin install <path>` points EKVAAR OS at the folder so the worker reloads each time `dist/` is rewritten.

See **[Develop a plugin locally](../how-to/develop-a-plugin-locally.md)** for the full walkthrough — scaffolding flags, the reload semantics, when to switch back to an npm install, and the troubleshooting checklist for the moments edits stop reaching EKVAAR OS.

You're set

Plugins give you a way to extend EKVAAR OS itself — new pages, new widgets, new scheduled work — without forking the codebase. Install what you need, keep disabled what you don't, and let the detail page tell you when something needs attention.

If you're looking to extend what an individual agent can *do* rather than what EKVAAR OS can *show*, see [Skills](../guides/org/skills.md) and [Agent Adapters](../guides/org/agent-adapters.md) next.

Quick reference

A cheat sheet for operating the Plugin Manager day-to-day:

Goal	Action
Try a bundled plugin	Plugin Manager → Available Plugins → **Install**

Install a third-party plugin	Plugin Manager → **Install Plugin** → enter npm package name
Temporarily stop a plugin's jobs	Click the power button on the plugin row (green to grey)
Bring a plugin back online	Click the power button again, or **Enable** from the detail page
Fix a plugin stuck in `error`	Detail page → Status tab → read the log, then re-enable
Approve an upgrade that asks for new permissions	Detail page → review Permissions → **Enable**
Change configuration	Detail page → Configuration tab → edit form → **Save Configuration**
Verify a config before committing	Detail page → Configuration tab → **Test Configuration** (when available)
Permanently remove a plugin	Trash icon on the plugin row → confirm

If you get stuck, the Status tab on any plugin detail page is the place to start — worker status, recent runs, and recent logs will usually point at the cause faster than poking at configuration.

CLI Auth & Board Claim

EKVAAR OS has two separate identity flows for humans on the command line and browser:

- **Board claim** — a one-time bootstrap step that promotes your browser-authenticated user to the owner of a freshly started authenticated instance. It migrates the trusted "local board" placeholder into a real, named human account.
- **CLI auth** — the everyday flow that pairs a local `EKVAAR OSai` CLI process with a signed-in board user, so the CLI can call `/api` endpoints on your behalf without you typing credentials into your shell.

Both flows use a short-lived, server-minted challenge and a browser approval page. Both are designed so the secret material (the board API token, the ownership migration) never leaves the browser or the CLI process that asked for it.

This guide walks through both, shows the approval pages, and explains how to use the resulting tokens with the CLI.

When you need each flow

- You just installed EKVAAR OS in **authenticated** deployment mode on a server, and the loopback trust is still active → run **Board claim** once.

- You want to run `EKVAAR OSai` commands against that instance from your laptop → run **CLI auth** (`EKVAAR OSai auth login`).
- You're using **trusted** deployment mode (loopback-only local dev) → neither flow is required; the CLI and browser already trust the loopback.

Claiming a board from the CLI

Board claim only exists when _all_ of these are true:

- Deployment mode is `authenticated`.
- The only instance admin is the built-in `local-board` placeholder (i.e., no human has claimed the instance yet).
- The claim challenge hasn't expired (the server keeps the active challenge for 24 hours and refreshes it automatically after that).

When the server starts and those conditions match, it prints a **Board claim** URL to the server log. It looks like:

```
http://localhost:3000/board-claim/<token>?code=<code>
```

The `token` is 48 hex characters; the `code` is 24 hex characters. Together they identify exactly one pending claim.

Open the URL in your browser. If you aren't signed in yet, the page will ask you to sign in or create an account first and bounce you back to the same URL after authentication.

Once you're signed in, the page shows a panel titled **Claim Board ownership** with a short explanation ("This will promote your user to instance admin and migrate company ownership access from local trusted mode.") and a single **Claim ownership** button.

Click it and the server does three things in a single transaction:

1. Inserts an `instance_admin` role for your user (if you weren't one already).
2. Deletes the `local-board` placeholder admin.
3. Walks every company in the database and, for each one, either creates an `active`, `owner`-role membership for you or reactivates your existing membership and sets the role to `owner`.

The button swaps to **Claiming… during the request. When it returns successfully the page switches to **Board ownership claimed** with a link to open the board. The in-memory challenge is marked claimed and cannot be reused.**

If the challenge expired, or the URL is malformed, the page shows **Claim challenge unavailable instead. Restart the server (or wait for the next refresh) to mint a new challenge.**

Device-code flow: `EKVAAR OSai auth login`

For day-to-day CLI use, the flow is a device-code-style pairing. The CLI creates a challenge, opens your browser, you approve it, and the CLI finishes with a stored token.

Starting the login

From the machine you want to use the CLI on:

```sh
EKVAAR OSai auth login
```

The CLI:

1. POSTs to `/api/cli-auth/challenges` with a description of itself (`command`, `clientName`, `requestedAccess`, and an optional `requestedCompanyId`).
2. Gets back a challenge containing `token`, `boardApiToken`, `approvalUrl`, `pollPath`, `expiresAt`, and a polling interval.
3. Prints the approval URL to your terminal and tries to open it in your default browser.
4. Starts polling the server at `pollPath` until the challenge is approved, cancelled, or expires.

Common flags:

```sh
Request instance-admin approval (only instance admins can approve this)
EKVAAR OSai auth login --instance-admin

Scope to a specific company
EKVAAR OSai auth login --company-id <company-id>

Target a non-default server
EKVAAR OSai auth login --api-base https://EKVAAR OS.example.com

```

### Approving the challenge in the browser

Your browser lands on a page titled **Approve EKVAAR OS CLI access**:

The panel shows what the CLI is asking for:

- **Command** — the CLI command that initiated the login (e.g. `EKVAAR OSai auth login`).
- **Client** — the `clientName` the CLI sent, default `EKVAAR OSai cli`.
- **Requested access** — either `Board` or `Instance admin`.
- **Requested company** — only shown if the CLI asked to be scoped to a company.

Two buttons at the bottom:

- **Approve CLI access** — only enabled if your signed-in user is allowed to approve this level of access. An instance-admin challenge requires an instance-admin approver.
- **Cancel** — rejects the challenge. The CLI sees the `cancelled` status on its next poll and exits with an error.

If you aren't signed in, the page first shows **Sign in required** with a button that returns you here after authentication. If the challenge has already been approved, cancelled, or expired by the time you visit the URL, the page reflects that state instead of offering the buttons.

### Finishing on the CLI

Once you click **Approve**, the CLI's next poll sees status `approved`, calls `/api/cli-auth/me` with the board API token to confirm identity, and writes the credential to the local credential store. It prints a success summary:

```json
{
  "ok": true,
  "apiBase": "https://EKVAAR OS.example.com",
  "userId": "usr_...",
  "approvalUrl": "https://EKVAAR OS.example.com/cli-auth/..."
}
```

If you cancel or let the challenge expire, the CLI errors out with `CLI auth challenge was cancelled.` or `CLI auth challenge expired before approval.` — re-run `EKVAAR OSai auth login` to try again.
```

After claiming: using and rotating the token

Where the token lives

The CLI stores the board API token (and the user id it resolves to) in the platform-appropriate config directory, keyed by `apiBase`. You don't need to copy the token anywhere — every CLI command that accepts `--api-base` will look up the matching stored credential automatically.

Using it

Once logged in, the CLI sends `Authorization: Bearer <stored-token>` on every request. You can verify by running:

```sh
EKVAAR OSai auth whoami
```

which calls `/api/cli-auth/me` and prints:

```json
{
  "user": { "id": "...", "name": "...", "email": "..." },
  "userId": "...",
  "isInstanceAdmin": true,
  "companyIds": ["..."],
  "source": "board-cli",
  "keyId": "..."
}
```

All other CLI commands — the ones documented in [Setup Commands](../reference/cli/setup-commands.md) and Control-Plane Commands — reuse this credential unless you pass an explicit `--token` or override `EKVAAR OS_API_KEY`.

Rotating and revoking

When you want to rotate the credential, log out and log back in:

```sh
EKVAAR OSai auth logout
```

EKVAAR OSai auth login
```

**`EKVAAR OSai auth logout`:**

**1. POSTs to `/api/cli-auth/revoke-current` with the stored token to revoke it server-side.**
**2. Deletes the local credential entry for this `apiBase`.**

**If the server-side revoke fails (network error, token already invalid) the local credential is still removed — you won't be stuck with a stale entry. A new `EKVAAR OSai auth login` mints a fresh challenge and a fresh token with no relationship to the old one.**

**### Multiple servers and users**

**The credential store is keyed by normalised `apiBase`, so one machine can hold separate credentials for a local dev instance, a staging server, and a production server at the same time. Switching between them is a matter of passing `--api-base` (or setting it in config). Logging in as a different user for the same `apiBase` replaces the existing credential for that server.**

**---**

**## Troubleshooting**

**- **"Invalid CLI auth URL."** — You opened the approval page with a missing `id` or `token` query param. Re-run `EKVAAR OSai auth login` to get a fresh link.**
**- **"CLI auth challenge unavailable"** — The token is valid but the server no longer has a matching challenge (it expired, or the server restarted). Start the login again.**
**- **"This challenge requires instance-admin access."** — You're approving an `--instance-admin` challenge but your signed-in user isn't an instance admin. Sign in with an admin account and retry.**
**- **"CLI auth challenge expired before approval."** on the CLI — You let the browser tab sit too long. Just rerun `EKVAAR OSai auth login`.**
**- **Board claim page shows "Claim challenge unavailable."** — The one-time ownership challenge has already been consumed, or it expired. If the instance has no real admins yet, restart the server — it mints a new challenge and reprints the URL in the logs.**

**---**

**## Where to go next**

**- [Setup Commands](../reference/cli/setup-commands.md) — installing, onboarding, and configuring a EKVAAR OS instance from the CLI.**
```

- [Authentication (API)](../reference/api/authentication.md) — the underlying authentication model for board users, agents, and runs.

Company Administration

Every EKVAAR OS company has a small cluster of surfaces that control its identity, its membership, and its portability. These pages are where you, as a board user (or a member with the right grants), set the company's name and logo, decide who else can sign in, hand out invite links, review join requests, and move the whole company in and out of a portable package. The CEO agent never touches most of this — it is deliberately human territory.

This guide walks through each of those surfaces in the order you typically meet them: **General Settings**, **Access & Members**, **Invites**, **Join Requests**, **Export**, and **Import**. If you are looking for how hiring approvals themselves work, see the [Approvals guide](../guides/day-to-day/approvals.md). If you want to understand the reporting tree that sits underneath the membership model, see [Org Structure](../guides/org/org-structure.md).

General Settings

The **Company Settings** page groups the settings that apply to the whole company rather than to any one agent or project. Open it from the sidebar under the company name.

Name and description

The **General** section has two fields:

- **Company name** — the display name shown in the company switcher and across the UI.
- **Description** — an optional one-line description shown on the company profile. Leave it empty if you do not want one.

Changes are not persisted until you click **Save changes**. The save button only appears when one of the fields is dirty, and it is disabled if the name is empty.

Logo and brand color

The **Appearance section controls the small square tile that represents your company in the sidebar and switcher. You have two inputs:**

- **Logo — upload a PNG, JPEG, WEBP, GIF, or SVG file. After upload, a **Remove logo** button appears next to the file input so you can clear it again. If an upload fails, the error message is shown inline.**
- **Brand color — sets the hue used for the auto-generated pattern icon when no logo is present. The color is configurable through the native color picker or a free-form `#rrggbb` text field. Leave it empty for the auto-generated color; a **Clear** button appears when a value is set.**

A live preview of the tile (logo and brand color combined) is rendered to the left of the fields so you can see the result before saving.

Hiring

The **Hiring section contains one switch:**

- **Require board approval for new hires — when on, every agent the CEO or a manager tries to hire stays pending until a board member approves it from the approvals queue. When off, hires go through immediately. This ties directly into the flow described in the [Approvals guide](../guides/day-to-day/approvals.md).**

The toggle saves immediately; there is no separate save button for this setting.

Feedback Sharing

The **Feedback Sharing section controls whether AI outputs you explicitly vote on in EKVAAR OS may also be shared with EKVAAR OS Labs. The toggle is labelled **Allow sharing voted AI outputs with EKVAAR OS Labs**.**

Two things to know:

- Votes are always stored locally, regardless of this setting. The toggle only controls whether the voted outputs become eligible for sharing.
- The section displays the current terms version, and, once sharing is enabled, the timestamp of when it was turned on and who enabled it. A **Read our terms of service link is shown when the terms URL is configured.**

Company Packages shortcuts

Below the feedback section, a **Company Packages panel links out to the dedicated **Export** and **Import** pages. These are the same pages covered in the last two sections of this guide; the Settings page itself does not perform the export or import.**

Danger Zone

At the bottom of the page is a **Danger Zone** with an **Archive company** button. Archiving hides the company from the sidebar and persists the change in the database. A confirmation dialog appears before the archive takes effect, and the UI automatically switches you to the next non-archived company if one is available.

Archiving also quiets the company so it stops doing work in the background: every active agent is paused (with the pause reason `company_archived`), and any queued or in-flight wake-up requests are cancelled. Archiving is not destructive — unlike deletion, your agents, projects, and issues are all preserved — but the company will not wake its agents again until you bring it back.

Access & Members

The **Company Access** page is where you manage human memberships: who belongs to the company, what role they hold, and which permissions they have on top of that role. Open it from **Settings → Access**, or directly from the sidebar.

Roles

EKVAAR OS uses four human membership roles. The role determines a set of implicit permission grants:

- **Owner** — full company access. Includes creating agents, inviting humans and agents, managing members and grants, assigning tasks, and approving join requests.
- **Admin** — operator with invite and approval powers. Can create agents, invite users, assign tasks, and approve join requests.
- **Operator** — a hands-on member who helps run work. Can assign tasks.
- **Viewer** — read-only access. No built-in grants.

The role drop-down in the edit dialog also accepts **Unset**, which leaves the member without any implicit grants.

> **Note:** EKVAAR OS's agent chain of command (CEO, managers, reports) is separate from these human roles. Human roles gate access to the EKVAAR OS UI and company-level actions; agent roles describe the reporting tree inside the company. See [Org Structure](../guides/org/org-structure.md) for the agent side.

The members list

The members section shows one row per human member with:

- **User account** — display name and email (or principal id if neither is set).
- **Role** — the human membership role, or "Unset".
- **Status** — `active`, `pending`, or `suspended`, rendered as a coloured badge.
- **Grants** — a comma-separated summary of any explicit permission grants attached to the member. Shows "No explicit grants" when the member only relies on implicit role grants.
- **Action** — an **Edit** button that opens the member editor.

If you do not have permission to manage members, EKVAAR OS replaces the page body with a message explaining why. An instance admin who is viewing the page without an active company membership sees a banner noting that the current account has admin-level access but is not a member of this company.

Editing a member

Clicking **Edit** opens a dialog with three controls:

1. **Company role** — the same role list as above, plus "Unset".
2. **Membership status** — `Active`, `Pending`, or `Suspended`.
3. **Grants** — a two-column grid of explicit permission grants. A read-only panel above the grid lists the grants the selected role provides implicitly. Checking a box here stores the grant explicitly on the member, so it persists even if the role later changes.

Available permission keys include `agents:create`, `users:invite`, `users:manage_permissions`, `tasks:assign`, `tasks:assign_scope`, and `joins:approve`. Each box is labelled with a human name and its underlying key for reference.

Click **Save access** to persist the changes, or **Cancel** to close the dialog without saving.

Adding and removing members

The Access page does not have an "Add member" button. New humans enter the company through the invite flow described in the next section, which either produces a direct membership or a pending join request depending on how the invite is consumed. To remove a human, set their **Status** to `suspended` through the Edit dialog; the row stays visible so the audit trail is preserved.

Pending human joins

If you hold the `joins:approve` grant and there are pending human join requests, a **Pending human joins** card appears above the members list. Each entry shows the requester's name, email, and the invite context, with **Approve human** and **Reject human** buttons. This card duplicates the subset of the join request queue that applies to humans — full coverage (including agent joins) lives on the queue page.

Invites

The **Company Invites** page creates invite links for new humans. Each link is single-use — the first successful use consumes the link and creates or reuses a join request before approval.

Creating an invite

The **Create invite** card has one required choice: which role the invite should request by default. The options are the four roles described above — **Viewer**, **Operator** (the default), **Admin**, and **Owner** — each rendered with a short description and a one-line summary of what the role gets.

Clicking **Create invite** does three things:

1. Generates a new invite link against the current EKVAAR OS domain.
2. Copies the URL to your clipboard if the browser allows it.
3. Shows the invite in a **Latest invite link** panel below the form.

If the clipboard is unavailable, EKVAAR OS shows a warning toast and you can copy the URL manually from the field. The invite URL is clickable as an **Open invite** button for quick testing in another tab.

Invite expiry and state

Invite links have four possible states, shown as a badge in the history table: **Active**, **Accepted**, **Expired**, and **Revoked**. Only `Active` invites can be consumed — the link becomes `Accepted` on first use and can be `Revoked` manually from the same page.

Invite history

Below the creator is a paginated **Invite history** table with one row per invite:

- **State** — the badge above.
- **Role** — the default role the invite requests.
- **Invited by** — the name and email of the human who created the invite.
- **Created** — the creation timestamp.
- **Join request** — a link to the join request queue if the invite has produced one.
- **Action** — a **Revoke** button for invites still in the `Active` state.

The table shows five invites at a time and includes a **View more** button when there are more pages. An **Open join request queue** link in the header jumps to the full queue.

What the invited person sees

When a human opens the invite URL, they land on a EKVAAR OS join page that creates a join request tied to the invite. If the invite carries a default role (for example **Operator**), that role is attached to the request so approvers can see it in context. The member does not become active until someone with `joins:approve` approves the request.

Join Requests

The **Join Request Queue** consolidates every join request — human and agent — that has come in against the company. Open it from `/inbox/requests`, or from the **Open join request queue** link in Invites.



Filters

Two drop-downs sit above the list:

- **Status** — `Pending approval` (the default), `Approved`, or `Rejected`.
- **Request type** — `All`, `Human`, or `Agent`.

Changing either filter refreshes the list. "Approved" and "Rejected" are useful when you want to audit past decisions.

What's on each card

Each request card shows:

- A **status** badge (`pending approval`, `approved`, or `rejected`), a **request type** badge (`human` or `agent`), and, for agent requests, an **adapter type** badge.

- The requester's name and a secondary identifier — email for humans, capabilities or source IP for agents.
- An **Invite context** panel with the invite's `allowedJoinTypes` and default role, plus the invite message if one was attached.
- A **Request details** panel with the submission timestamp, source IP, and agent capabilities (when applicable).

For requests in `pending approval`, the card also shows **Approve** and **Reject** buttons. Once acted on, the card stays in the list under the new status filter for audit purposes but no longer exposes action buttons.

Permissions

The queue requires the `joins:approve` grant. Accounts without it see a "You do not have permission to review join requests for this company." message instead of the list.

Export

The **Company Export** page turns the current company — its agents, projects, tasks, skills, and settings — into a portable markdown package you can download as a zip. Open it from the **Org Chart** header or from the **Export** shortcut on the Settings page.



What gets included

When the page loads, EKVAAR OS builds a preview of everything that would be exported. By default the preview includes the company metadata, every non-terminated agent, every non-archived project, and every issue. The preview is rendered as a left-hand **Package files** tree, with a selected-file preview on the right.

The sticky bar at the top of the page shows:

- The company name and a running count of **selected / total files**.
- Any warnings EKVAAR OS produced while building the preview.
- A single **Export N files** button that downloads the zip.

Selecting what to export

Every entry in the file tree has a checkbox. Unchecking a file or a directory removes it from the download. A couple of details worth knowing:

- The tree is searchable with the input above it. Search expands matching directories automatically and restores the previous expansion state when you clear the query.
- `README.md` and `.EKVAAR OS.yaml` are regenerated on the fly so they always reflect the current selection.
- The `tasks/` directory is paginated — ten entries visible by default, with a **Show more issues** button. Checked and search-matched tasks are always pinned above the fold.
- Clicking a file opens its content in the preview pane. The URL updates as you navigate so you can deep-link to a specific file in the export.

Downloading

Click **Export N files** to build the final package. EKVAAR OS assembles the zip with the filtered files (including the regenerated README and `.EKVAAR OS.yaml`) and triggers a browser download. A success toast confirms the file count and the zip's root path.

For a deeper description of what lives in each file, see [Export & Import](../guides/power/export-import.md).

Import

The **Company Import** page is the reverse direction: it takes an exported package and loads it into EKVAAR OS, either as a new company or on top of an existing one.



Choosing a source

The **Import source** section supports two source types:

- **GitHub repo** — paste a tree or blob URL pointing at a folder that contains a `COMPANY.md`.
- **Local zip** — upload a `.zip` package exported from EKVAAR OS. EKVAAR OS warns against re-zipping archives in Finder or Explorer; use the download from the Export page.

Choosing a target

The **Target** drop-down has two options:

- **Create new company** — the default. An optional **New company name** field lets you override the name from the package.

- **Existing company** — apply the package on top of the currently selected company.

Collision strategy

The **Collision strategy** drop-down controls what happens when an incoming item clashes with something that already exists in the target company:

- **Rename on conflict** — the default. EKVAAR OS proposes a new name (prefixed with the package name, for example `gstack-CEO`) for each conflicting entity.
- **Skip on conflict** — existing items are kept and the incoming copy is dropped.
- **Replace existing** — overwrites the current entity with the incoming version.

Preview

Click **Preview import** to run the preview without applying anything. The preview populates three things:

1. A **Renames** list showing every agent and project that collided and what it will be renamed to. Each row has a free-form input for the target name, a **skip** button, and a **confirm rename** button that locks the chosen name in.
2. An **Adapters** list for every agent in the package, with a drop-down of available adapters. New agents default to the same adapter as the target company's CEO. A **configure adapter** button expands an inline config form so you can set per-agent values (environment, working directory, etc.) before the import runs.
3. A file tree identical in layout to the export tree, but with an **action badge** on each row (`create`, `update`, `skip`, or `replace`) so you can see what EKVAAR OS plans to do to every file. Directories that will be renamed show an arrow and the target name.

The sticky bar at the top counts selected files and surfaces the number of conflicts and errors.

Applying the import

When you are happy with the preview, click **Import N files**. The button is disabled if there are errors in the preview or no files selected. On success, EKVAAR OS refreshes the companies list, navigates you to the dashboard of the imported (or updated) company, and restores the imported sidebar order if the package included one.

Existing-company imports are non-destructive in the safe import path: incoming issues are always created as new issues, and `replace` is blocked by the server for safe imports. If you need a full replace, use the dedicated instance-admin flow instead.

See [Export & Import](../guides/power/export-import.md) for the structural reference — the field-by-field description of the package format complements the walkthrough above.

Company administration covers the pieces of EKVAAR OS that sit around the agents rather than inside them: identity, membership, and portability. Once you have the company set up and people invited in, day-to-day work happens in the approvals queue, the dashboard, and the task surfaces that the rest of this guide set covers.

Settings

EKVAAR OS has two settings surfaces, and it matters which one you're looking at.

Profile is *your* account — your display name and the avatar that shows up next to your comments. Changing it only affects how *you* appear. Other board users on the same instance have their own profiles and see their own.

Instance Settings is the admin surface. Anything you change there applies to the whole EKVAAR OS instance — every company, every user, every agent that runs against this install. If you're running EKVAAR OS on a VPS that hosts five companies, a toggle on the Instance page flips for all five.

This guide walks through both, section by section.

Profile

Open the Profile page from the account menu in the sidebar. It's scoped to you — nobody else's profile changes when you edit yours.

You get three things to work with:

- **Avatar** — click the round image (or the **Upload photo** button) to pick a new image from disk. It's uploaded into EKVAAR OS's file storage under the currently selected company's asset space. If no company is selected you can't upload — the page will tell you to select one first. Once an image is set, a **Remove** button appears next to the upload control.
- **Display name** — the name shown in the sidebar account footer and as the author on any comments you post. It falls back to "Board" if left blank. The field is capped at 120 characters.
- **Email** — read-only. Your email is managed by the auth session (the login provider), not by this page. If you need to change it, update it wherever you signed in from.

Click **Save profile** to persist name or avatar changes. The button is disabled while the name is empty or a save is in flight.

> **Note:** The avatar is stored as an asset under the *selected company*, but the profile itself is a user-level record. If you switch which company is selected in the sidebar later, your avatar keeps working — it's just that new uploads go to whichever company is active when you upload.

Instance: General

This is the top of Instance Settings. It's where you see how the instance was deployed and flip a few cross-cutting toggles.

Deployment and auth

At the top of the page, a small mode badge tells you which deployment profile this instance is running under. The text underneath explains what that means in practice:

- **Local trusted** — the instance is treating browser requests as a local board operator. No sign-in is required. This is the default when you run EKVAAR OS on your own machine.
- **Authenticated public** — sign-in is required and the instance is intended to sit on a public URL.
- **Authenticated private** — sign-in is required, but the instance is intended for a private network (LAN, VPN, or similar).

Three status boxes summarize readiness:

- **Auth readiness** — whether the auth subsystem is fully configured.
- **Bootstrap status** — "Setup required" if the initial CEO/board setup hasn't completed yet, otherwise "Ready".
- **Bootstrap invite** — whether an active first-run invite link is outstanding.

These fields are informational. To change them you change the deployment itself — see [Environment Variables](../reference/deploy/environment-variables.md).

Censor username in logs

Hides the username segment inside home-directory paths and similar operator-visible log output. Useful if you're sharing screen recordings or pasting transcripts. Off by default. Note that bare username mentions outside of path strings are not masked in the live transcript view — this is a best-effort filter, not a guarantee.

Keyboard shortcuts

Enables the app's keyboard shortcuts — inbox navigation, creating issues, toggling panels, and so on. Off by default because they conflict with browser or screen-reader shortcuts for some users. Turn it on if you want faster navigation.

Backup retention

Controls how long automatic database backups are kept at each tier. EKVAAR OS takes daily backups and then thins them out over time:

- **Daily — full daily backups kept for the selected number of days.**
- **Weekly — one backup per week kept for the selected number of weeks.**
- **Monthly — one backup per month kept for the selected number of months.**

Each tier is a preset picker, so you can only choose from vetted retention windows. Backups are gzipped on disk. Longer retention means more storage — raise the windows only as far as your disk and compliance story require.

AI feedback sharing

Controls whether thumbs-up / thumbs-down votes on AI output can send the voted output to EKVAAR OS Labs. Three states exist:

- **Prompt (default) — no choice has been made yet. The next time you vote, EKVAAR OS will ask once and save your answer.**
- **Always allow — voted AI outputs are shared automatically.**
- **Don't allow — voted AI outputs stay local.**

The local vote is always saved regardless — this setting only controls whether the *content* leaves your instance. There's a link to the terms of service on the same card.

Sign out

A plain **Sign out button at the bottom. It ends your session and sends you back to the login page. On a local-trusted instance there's usually nothing to sign out of, but the button is always present.**

Instance: Access

Instance Access is where you promote users to **instance admin** and pick which companies each user can see. This is different from the roles you grant *inside* a company.

Instance-level vs. company-level roles

It's worth being explicit about this because the two feel similar:

- A **company membership** lets a user see and act within one specific company. A user can be a member of several companies, each with its own membership role (operator, manager, etc.). This is set per-company.
- An **instance admin** can see and manage the instance itself — add/remove instance admins, grant users company access, and open admin-only surfaces. This is set per-user on this page.

A user can be an instance admin without being a member of every company, and a company member without being an instance admin. The two layers are independent.

Finding and inspecting a user

The left pane is a search box and a scrollable user list. Type a name or email to narrow it down. Each row shows:

- The user's name and email
- A green shield icon if they're currently an instance admin
- A count of active company memberships

Click a user to load their detail view on the right.

Promote to instance admin

In the detail view, a button toggles the user's instance-admin status: **Promote to instance admin** if they're not one, or **Remove instance admin** if they are. The change takes effect immediately. Be deliberate — instance admins can grant themselves access to any company and can demote other instance admins.

Company access

The lower half of the detail view is a grid of every company on the instance with a checkbox next to each. Tick the ones this user should be a member of, untick the ones they shouldn't, and click **Save company access.**

Adding access creates an *active operator* membership by default. If the user needs a higher role inside that company (manager, for example), switch to that company and raise their role there — this page only controls *whether* they have access, not *what role* they have.

Beneath the checkbox grid, **Current memberships lists what's actually on record, with role, status, and the last update date. Treat this as the source of truth — if it doesn't match what you set in the checkboxes, re-save.**

> **Tip: Running a VPS-hosted instance that hosts multiple companies? Use this page to onboard new people without sharing the database. Create their auth account (through your login provider), find them here, tick the companies they need, and save.**

Instance: Adapters

![Instance adapters](../user-guides/screenshots/light/settings/instance-adapters.png)

The Adapters sub-page (Instance Settings → **Adapters) is the operator view of every adapter currently registered against this EKVAAR OS install. Adapters are how EKVAAR OS talks to an AI runtime — Claude's local CLI, Codex, OpenAI, OpenClaw, and so on — so this is the surface you use when you need to add a new runtime, hide one from agent hiring menus, or upgrade a runtime's package to a newer release.**

> **Alpha: The external adapter system is still under active development. APIs and storage format may change between releases — reach for this page when you need it, but expect the details to keep evolving.**

Installed adapters

The page has two sections, stacked top-to-bottom:

- **External Adapters — anything you have added yourself, whether from an npm package or a local path. Each row shows the adapter's display label, its registered `type`, the package name, the version, and how many models the adapter exposes.**
- **Built-in Adapters — the adapters that ship inside EKVAAR OS itself. They cannot be removed, only hidden. If an external adapter has overridden a built-in (for example, a forked version of the Claude adapter installed from npm), you also see a synthesised**

"built-in" row tagged **Overridden by …** so it is obvious which built-in has been shadowed.

A small origin icon sits next to each external adapter: a folder for adapters installed from a local path, and a package icon for adapters installed from npm. Versions appear as a mono-typed `v1.2.3` badge.

Health status

The row badges are the fastest way to read adapter health:

- **External** / **Built-in** — the source of the adapter.
- **v{version}** — the currently loaded package version.
- **Overrides built-in** — this external adapter is replacing a built-in of the same `type`.
- **Hidden from menus** / **Override paused** — the adapter still exists but is not offered when creating or hiring agents. Use this to stage a rollout without uninstalling.

Beneath the label, a subtitle line shows `type`, the npm package name (when different from the type), and the model count. A zero model count usually means the adapter loaded but could not enumerate models — check the package configuration before enabling it for agents.

Enable / disable

Every row has a **power** icon on the right-hand side. Clicking it toggles the adapter's visibility without deleting anything:

- For regular adapters (both built-in and plain external), the power button flips the **Hidden from menus** state. Hidden adapters are kept registered and existing agents on that adapter continue to run, but the adapter is omitted from the adapter dropdown when creating new agents.
- For external adapters that **override a built-in**, the power button instead pauses or resumes the override. Pausing the override snaps every agent of that `type` back to the built-in implementation on their next run; resuming restores the external adapter.

Two more icons may appear on external rows:

- **Reload** (circular arrow) hot-swaps the adapter module in the running process. Useful after you have published a new version of a local-path adapter and want to pick up changes without bouncing EKVAAR OS.
- **Reinstall** (download arrow) opens a confirmation dialog that checks the npm registry for the latest version, then pulls it and reinstalls the package. Existing agents will use the new version on their next run.

A **Remove** (trash) icon is available on external adapters only. Removing an adapter unregisters it, tears down its npm install on disk, and cannot be undone — EKVAAR OS prompts for confirmation first.

Per-adapter config

Adapters themselves do not expose configuration on this page — they are packages, not configurable singletons. Each **agent** picks an adapter and then fills in the fields that adapter requires (working directory, environment variables, credentials). Those per-agent fields live on the agent's Configuration tab, not here.

What this page gives you is the ability to add, upgrade, and retire the adapter packages that populate the agent adapter menu. To install a new external adapter, click **Install Adapter** in the top-right of the page. A dialog appears with two source modes:

- **npm package** — enter the package name (for example `my-EKVAAR OS-adapter`) and optionally a version. EKVAAR OS installs the package from npm and registers it.
- **Local path** — paste a Linux, WSL, or Windows path to a checked-out adapter package. EKVAAR OS auto-converts Windows paths and installs the adapter from disk. Local-path adapters are the fastest way to iterate on a new adapter before publishing.

In both cases the adapter package must export `createServerAdapter()` — the dialog reminds you of this contract.

For the full catalog of adapters EKVAAR OS supports out of the box, along with the per-agent fields each one expects, see the reference docs: [Adapters overview](../reference/adapters/overview.md).

Instance: Scheduler Heartbeats

The Scheduler Heartbeats page is a cross-company view of every agent on the instance that has a **timer heartbeat** enabled.

What the scheduler does

EKVAAR OS's scheduler is the component that wakes up timer-driven agents on an interval. It reads each agent's `runtimeConfig.heartbeat` block, notices when the next tick is due, and fires the run. Event-driven wakes (assignments, comments, routines) don't go through this surface at all — they happen regardless of the timer state.

For a deeper explanation of when to use timer heartbeats vs. event-driven wakes, read [Heartbeats & Routines](../guides/projects-workflow/routines.md). In short: timer heartbeats should be the exception, not the rule.

What this page shows

At the top of the page, a summary line reports:

- How many timer heartbeats are **active (enabled and the scheduler considers them live)**
- How many are **disabled**
- How many companies the list spans

Below that, agents are grouped by company. Each row shows:

- An **On/Off badge for whether the scheduler sees the heartbeat as active**
- The agent's name (links to the full agent config)
- The agent's title or role
- The configured interval in seconds
- When the last heartbeat ran, as a relative time ("2m ago", "never")
- A link icon to jump to the agent config, and a button to **Enable Timer Heartbeat or **Disable Timer Heartbeat** inline**

The list auto-refreshes every 15 seconds so you can watch an enable/disable take effect.

When to tune it

Reach for this page when:

- You suspect an agent is burning budget on idle wakeups. Find it in the list, check the interval, and either raise the interval on the agent config page or disable the heartbeat.
- You've just imported or cloned an instance and want to take stock of every timer-driven agent in one place before turning any of them loose.
- You need a quick emergency shut-off. The **Disable All button at the top right of the summary line disables the timer heartbeat on every currently-enabled agent in one operation. It prompts for confirmation first. Event-driven wakes still work afterwards — this only stops the *tickers*.**

Safe defaults

- **Most agents should have timer heartbeats **off**. They stay active on the dashboard and wake on assignments, comments, and routines. This is EKVAAR OS's default for new agents.**

- **When a timer is truly needed** (polling an external system with no webhook, for example), push the interval as long as you can stand. Minutes or hours, not seconds.
- **After an import** or major config change, check this page — other instances' timer settings will come with them, and you may want to disable the ones you don't recognize before the scheduler starts firing them.

Instance: Experimental



Experimental flags opt the instance into features that aren't yet defaults. They're gated here because they may change behaviour, performance, or migrations before they graduate.

What "experimental" means here

An experimental flag in EKVAAR OS is a feature that:

- Has shipped and works,
- Is being evaluated against real usage before it becomes the default, and
- May be renamed, reworked, or promoted to a core setting in a future release.

Turning one on is not dangerous in the "this will break your data" sense — but it does mean you're opting into behavior that may change how agents run or how the backend restarts. Flip flags when you have a reason to, not for curiosity, and expect to re-read the release notes if you upgrade.

The available flags

- **Enable Isolated Workspaces** — shows the execution-workspace controls in project configuration and allows isolated workspace behavior for new and existing issue runs. If you're not using isolated workspaces, leave this off; turning it on exposes extra UI you don't need.
- **Auto-Restart Dev Server When Idle** — only relevant under `pnpm dev:once`. When the backend detects a stale boot (code changes, new migrations), it waits for queued and running local agent runs to finish and then restarts the dev server automatically. Useful during active development on EKVAAR OS itself, not intended for production.

Both toggles take effect immediately on save. If one misbehaves, flip it back off — no migration is required.

Where to go next

- [Heartbeats & Routines](../guides/projects-workflow/routines.md) — the full picture of timer vs. event-driven wakes, and how to configure individual agents.
- [Environment Variables](../reference/deploy/environment-variables.md) — the deployment-level settings that the General page reports on (auth mode, bootstrap state, exposure).

Trust & Low-Trust Review

Some work in a EKVAAR OS company is born from input you cannot vouch for: an untrusted pull request, an external ticket, a dependency diff, or output an agent generated from any of those. The goal of trust presets is simple — keep that kind of work *contained* while it runs, and make sure nothing it produces is silently fed into a more trusted agent before a human (or a trusted reviewer) has looked at it.

This page explains the two trust presets EKVAAR OS ships with, what actually changes when an agent or its work is treated as low-trust, and how that work gets reviewed and promoted before it counts as accepted.

It helps to read [Execution Policy](../guides/power/execution-policy.md) first — trust presets layer on top of the same execution-policy plumbing, and a low-trust run leans on the isolated workspace and sandbox mechanics described there.

> **This is containment, not privacy.** Standard work in a EKVAAR OS company stays company-visible by default — board users and in-company actors can still inspect company work objects. Low-trust containment is narrower: it limits what a low-trust agent can read or change through the EKVAAR OS API, and it stops raw untrusted output from being automatically promoted into higher-trust agent context. It is not a general project, issue, or human privacy system.

The two presets

EKVAAR OS ships exactly two core trust presets, so containment decisions are enforced everywhere — including Community Edition, even when policy editing in the UI is not available.

- **`standard`** — the default. This is the normal, company-visible collaboration model you already know. Regular agents behave exactly as they always have, and this is what every agent gets unless a policy says otherwise.

- **`low_trust_review`** — an opt-in containment preset for automated work that may consume hostile or prompt-injected input. Turn it on for the kinds of tasks where you would not want the agent's reading and writing reach to extend across the company, and where its output should be quarantined until reviewed.

The default preset is `standard`; `low_trust_review` only takes effect when a policy explicitly opts in.

How a preset is chosen

A low-trust preset is not a single switch. EKVAAR OS resolves the effective preset by reading the same JSON policy you already use for execution, from up to four sources:

Source	Where it lives
Agent	the agent's `permissions` — `trustPreset` and `authorizationPolicy.trustBoundary`
Project	the project's `executionWorkspacePolicy.authorizationPolicy`
Issue	the issue's `executionPolicy.authorizationPolicy`
Run	the run's `executionPolicy.authorizationPolicy`

The resolver combines these. If *any* source asks for low-trust — either by naming the `low_trust_review` preset or by carrying a `trustBoundary` — the effective preset becomes `low_trust_review` for that work. The boundaries from each source are then intersected: **narrower always wins**. You cannot widen a boundary by relaxing one layer; you can only tighten it.

Two things make resolution **fail closed** (the work is denied rather than run with weaker containment):

- A policy source that names a *different* company, or uses an unsupported preset value.
- A low-trust preset that does not resolve to a concrete scope. Low-trust review must land on a real, company-local target — a root issue, one or more project ids, or an explicit list of issue ids. If none of those is present, resolution is denied.

Inside a trust boundary

When `low_trust_review` resolves, it produces a single merged boundary. These are the fields you can set on a `trustBoundary`, all scoped to one company:

- `mode` — always `low_trust_review`.

- `companyId` — the company the boundary belongs to. A boundary that names another company is rejected outright.
- `projectIds` — projects the low-trust work may touch.
- `rootIssueId` — an issue subtree the work is confined to.
- `issueIds` — an explicit allow-list of issues.
- `allowedAgentIds` — agents permitted within the boundary.
- `allowedSecretBindingIds` — the secret bindings the run may reference.
- `allowedToolClasses` — the tool classes the run is allowed to use.
- `outputPromotionTarget` — where promoted output is allowed to land (an issue).

At least one of `rootIssueId`, `projectIds`, or `issueIds` must be present — that concrete scope is what the resolver requires before it will allow low-trust work to run.

What changes at runtime

When a run resolves to `low_trust_review`, EKVAAR OS refuses to start it unless it can actually enforce the boundary. A managed low-trust run **fails closed** unless all of the following hold:

- **Isolated workspaces are enabled** for the instance. Without them there is nowhere safe to contain the work.
- **The execution workspace mode is `isolated_workspace`.** A shared or host-local workspace is not acceptable for low-trust work.
- **The issue being run is inside the resolved boundary** — either directly named, in an allowed project, or a descendant of the boundary's `rootIssueId` (ancestry is checked up to a bounded depth). An issue outside the boundary is rejected.
- **The environment uses the `sandbox` driver.** A host-local adapter process is not allowed for managed low-trust execution; you need a sandboxed environment instead.

On top of that, two further constraints apply:

- **Secrets are restricted.** A low-trust run may only reference secret bindings whose ids are listed in the boundary's `allowedSecretBindingIds`, and inline sensitive environment values (raw API keys, tokens, and the like) are rejected — they must come through allowed bindings, not be pasted in.
- **Runtime services are denied by default.** A low-trust run cannot start or mutate workspace runtime services unless the boundary explicitly grants the `runtime.manage` tool class. If it tries to and that grant is absent, the run is stopped.

The built-in low-trust tool classes are read-only and conservative by design: `git.read`, `github.pr.read`, and `tests.local`. That is the shape of work this preset is meant for —

read the untrusted change, run local tests, report back — not reach out and mutate the wider company.

If you have been doing untrusted-PR review by hand with a local Docker workflow, that still works for manual review. But anything EKVAAR OS runs as managed low-trust execution goes through the sandboxed, isolated path described above.

Reviewing and promoting low-trust output

Containment at runtime is only half the story. The other half is what happens to whatever the low-trust agent writes.

When a low-trust agent creates an issue, comment, document, or work product, EKVAAR OS tags that artifact with **source-trust metadata** and gives it the disposition `quarantined`. Quarantined artifacts are stored, but their raw bodies are held back from higher-trust agent context. Where a higher-trust agent would otherwise read the body, it instead sees a placeholder explaining that quarantined low-trust output was omitted and that a trusted reviewer can inspect and promote a sanitized version. Comment presentation and metadata are stripped alongside the body, so nothing in the raw artifact leaks into a trusted run by accident.

The source-trust record carries enough provenance to audit the work later:

- `preset` — the trust preset that produced the artifact.
- `disposition` — `quarantined` or `promoted`.
- `sourceIssueId`, `sourceRunId`, `sourceAgentId` — where the artifact came from.
- `promotedFrom` — the original artifact a promotion was based on, including its `artifactKind` (`issue`, `comment`, `document`, or `work_product`), `artifactId`, and `issueId`.
- `promotedByActorType` (`agent`, `user`, or `system`), `promotedByActorId`, and `promotedAt` — who promoted it and when.

Promotion is the deliberate, reviewed step that turns quarantined output into something a trusted agent can act on. A trusted reviewer inspects the quarantined artifact, and a sanitized version is written with disposition `promoted` and a `promotedFrom` link back to the original. Only then does the content flow into higher-trust context. Nothing is auto-promoted — raw untrusted output never gets silently upgraded.

This source-trust tag lives on the artifact itself: issues, issue comments, documents, and issue work products each carry it, so the quarantine and promotion state travels with the work wherever it is read.

When to reach for low-trust review

Reach for `low_trust_review` when an agent's task is to chew on input you do not control and you want a hard guarantee that its reach and its output stay contained:

- Reviewing an untrusted or external pull request.
- Triaging tickets or reports submitted from outside the company.
- Inspecting dependency diffs or third-party changes.
- Running an agent over any content that could carry a prompt-injection payload.

For everything else, `standard` is the right default — it keeps normal collaboration fast and company-visible, which is what most work wants.

Plugins

Some things EKVAAR OS does out of the box — run agents, manage tasks, call adapters. Plenty of other things it does not, because they're too specific to your setup: a Hello World widget on the dashboard, a file browser for your project workspaces, a smoke-test runner for a third-party service you happen to use. Plugins are how you add those.

A plugin is a self-contained package that installs into EKVAAR OS, runs its own background worker, and can contribute its own pages, widgets, and settings into the EKVAAR OS UI. Unlike an [agent adapter](../guides/org/agent-adapters.md) — which teaches EKVAAR OS how to talk to a new AI model — and unlike a [skill](../guides/org/skills.md) — which is a reusable instruction document an agent loads into its prompt — a plugin is a piece of software that extends EKVAAR OS itself. It has its own code, its own process, and its own surface in the UI.

> Plugins are in alpha. The runtime and APIs are still shifting, so expect breaking changes for now and pin versions where you can.

The Plugin Manager

The Plugin Manager lives under **Settings → Plugins**. It's the single place where you install, enable, disable, configure, and uninstall plugins.

The page has two sections:

- **Available Plugins — the plugins bundled with your EKVAAR OS checkout, discovered automatically from the packages on disk. This includes the reference example plugins *and* first-party plugins like the LLM Wiki when they're part of your checkout. Each is labelled **Bundled**, and ones that aren't production-ready yet carry an **Experimental** badge. Useful for seeing what plugins can do and for smoke-testing the plugin runtime on a fresh instance.**
- **Installed Plugins — everything you've installed on this EKVAAR OS instance. Each row shows the plugin name, its package and version, a short description, a status badge, and quick actions.**

Status badges

Every installed plugin has a status that tells you what the runtime is doing with it.

| Status | What it means in practice |
|---|---|
| **ready | The plugin is installed, enabled, and its worker is running. This is the steady state you want. |**
| **disabled | You (or another operator) turned the plugin off. Its worker is stopped, scheduled jobs don't fire, and any UI contributions are hidden. Config and data are preserved. |**
| **error | Something went wrong — the worker crashed on startup, a health check failed, or an upgrade broke. The plugin row shows a short error summary and a **View full error** button for the full stack trace. |**
| **upgrade_pending | A new version of the plugin has been staged, and it asks for capabilities the installed version didn't have. EKVAAR OS is holding it offline until you approve the new permissions. |**
| **installed | A transient state right after install, before the first successful load. You usually won't see it for long — the plugin moves to `ready` (or `error`) within a second or two. |**
| **uninstalled | The plugin has been removed. It won't appear in the list anymore unless you reinstall it. |**

If the badge is green it's running. If it's grey it's intentionally off. If it's red or amber, read the message — the UI is telling you something needs your attention.

Reading an error row

When a plugin is in `error`, the row expands to show a short error summary — the first non-empty line of the stored error message — and a **View full error button. Clicking it opens a dialog with the complete stack trace or failure output, wrapped and scrollable.**

The summary is usually enough to know what to do:

- **"Cannot find module ..."** or **"Failed to load manifest"** — the package is malformed or its build output is missing. Reinstall it, or rebuild it if you're developing locally.
- **"Worker exited with code 1"** — the worker crashed on startup. The full error has the stack trace. Most common causes: missing configuration (go fill in the settings form), a secret that hasn't been provided, or an external service the plugin depends on being unreachable.
- **"Health check failed: ..."** — the worker started but a health check didn't pass. The message names which check failed; fix the underlying issue, then click the power button to re-enable the plugin.

An errored plugin stays installed — you don't need to uninstall and reinstall to try again. Once you've addressed the cause, clicking **Enable** puts it through the `error → ready` transition and EKVAAR OS tries to start the worker again.

Installing a plugin



There are two ways to get a plugin into EKVAAR OS.

From the Available Plugins list. Bundled plugins ship inside the EKVAAR OS repository. On the Plugin Manager page, scroll to the **Available Plugins** section and click **Install** next to the one you want. EKVAAR OS installs it straight from the local checkout — no registry round trip.

EKVAAR OS builds this list by scanning the plugin packages in your checkout, so what you see depends on what's bundled. Two kinds of plugin show up here:

- **Reference examples** — small, self-contained plugins that exist to demonstrate the runtime.
- **First-party plugins** — real plugins like the [LLM Wiki](../reference/plugins/llm-wiki.md) when they're vendored into your checkout. These are also published to npm, so on instances that don't bundle them you'd install by full package name instead; see *By npm package name* below.

First-party plugins that are still maturing carry an **Experimental** badge in this list — they work, but their behaviour or configuration may change between releases, so pin versions where you can.

The reference examples that ship today:

- **plugin-hello-world-example — adds a Hello World widget to the dashboard. The minimum-viable plugin, useful as a reference.**
- **plugin-file-browser-example — adds a Files link to project sidebars and a file-browser tab to the project detail page, scoped to the project's workspace.**
- **plugin-kitchen-sink-example — demonstrates the full plugin surface in one package: pages, widgets, settings forms, scheduled jobs, webhooks. Good for exploring what a plugin can do.**
- **plugin-authoring-smoke-example — a thin smoke test for the plugin authoring workflow. Useful if you're working on a plugin of your own and want to confirm the runtime picks it up.**
- **plugin-orchestration-smoke-example — a smoke plugin that exercises EKVAAR OS's orchestration-grade plugin APIs (scheduled jobs, webhooks, plugin-driven agent interactions). Useful as a reference when you're building a plugin that needs to coordinate work over time, not just render a widget.**

By npm package name. Click the **Install Plugin** button at the top right of the Plugin Manager. EKVAAR OS asks for an npm package name (for example, `@EKVAAR OSai/plugin-example`). Submit it and EKVAAR OS fetches, installs, and loads the package. Success or failure appears as a toast, and the plugin shows up in the installed list with its current status.

In both cases the install flow does the same underlying work: download the package, validate its manifest, persist the plugin record, then attempt to move it through `installed → ready` by starting its worker. If anything in that chain fails, the plugin is parked in `error` with the failure message attached — it stays installed so you can inspect what happened instead of silently disappearing.

Enabling and disabling

Each installed plugin has a power button in the actions column. The button toggles between two lifecycle transitions:

- **Disable** (when the plugin is `ready`) — EKVAAR OS stops the worker, cancels any in-flight scheduled jobs the plugin owns, and hides the plugin's UI contributions. Your configuration and any data the plugin has stored are preserved.
- **Enable** (when the plugin is `disabled`, `error`, or `upgrade_pending`) — EKVAAR OS starts the worker again and, if startup succeeds, moves the plugin back to `ready`.

Disabling is the right move when a plugin is misbehaving, when you want to pause its scheduled jobs temporarily, or when you're about to change some external dependency and you'd rather the plugin not fire in the meantime. It's a safe, reversible operation — think of it as a "sleep" rather than a "remove".

Uninstalling

The trash icon next to the power button removes a plugin. EKVAAR OS asks you to confirm, because the action is not reversible from the UI: the plugin package is removed from disk, the installation artifacts are cleaned up, and the plugin is marked uninstalled. To get the plugin back, you'd reinstall it fresh.

Uninstalling stops the worker first, the same way disable does, so in-flight work is drained cleanly before the package is removed.

What "disabled" actually stops

Worth being explicit about, because it's the difference between "I'm pausing this for an hour" and "I need to start over":

- **Stopped:** the worker process, scheduled job runs, webhook delivery processing, UI contributions (pages, widgets, settings slots), and any health-check polling.
- **Preserved:** the plugin record itself, saved configuration (including secrets), historical job-run and webhook-delivery records, and log entries. When you re-enable the plugin everything resumes where it left off, on the same config.

This matters for plugins that integrate with billed services. Disabling stops the polling and the scheduled work — so you stop paying the API bill — without forcing you to re-enter credentials the next time you turn it back on.

Upgrades

When a plugin is upgraded to a new version, EKVAAR OS compares the capabilities declared in the new manifest against the ones you originally approved.

- If the new version asks for the same capabilities or fewer, EKVAAR OS upgrades it in place and the plugin returns to `ready` on the new version.
- If the new version asks for **new** capabilities that weren't there before — access to a new data surface, a new integration point — EKVAAR OS parks the plugin in `upgrade_pending`. The worker stays stopped until an operator looks at what changed.

To apply an upgrade pending approval, open the plugin's detail page, review the updated capabilities and description, and click **Enable**. That moves the plugin back to `ready` on the new version. If you're not happy with the new capabilities, you can leave the plugin in `upgrade_pending` indefinitely, or uninstall it.

This gate exists so plugins can't quietly grow permissions on you between versions. The first time a capability is requested is always a deliberate action you took.

The plugin detail page

Clicking a plugin's name — or the **Configure** button — opens the plugin detail page. This is where a plugin gets to show you its own surface inside EKVAAR OS.

The detail page has two tabs:

- **Configuration** — the plugin's description, author, categories, and settings form (or a custom settings UI the plugin ships).
- **Status** — runtime diagnostics: worker process state, recent scheduled jobs, recent webhook deliveries, live health checks, and a rolling log of recent entries.

A plugin can also declare a **page slot**. When it does, the plugin gets its own route at `/<company-prefix>/plugins/<plugin-id>` and renders whatever it wants there — a full page, a dashboard, a multi-step flow. This is how something like the file-browser example adds a Files tab to project pages, or how a hypothetical CRM plugin might add a Contacts view to the sidebar.

From your perspective as an operator, plugin pages behave like any other EKVAAR OS page: they're scoped to the currently selected company, they show up in breadcrumbs, and they respect your permissions. The plugin just gets a canvas to render on.

Plugins can also contribute smaller pieces — a widget on the dashboard, a tab on the project detail page, a link in a sidebar — rather than a full standalone page. These show up inline in the surfaces you already use, so you don't always have to navigate to the plugin detail page to get value out of it. The Hello World example adds a dashboard widget; the file-browser example adds a project tab; the kitchen-sink example scatters contributions across several surfaces so you can see what's possible.

If two plugins happen to contribute a page on the same route, EKVAAR OS refuses to choose between them and surfaces a conflict message instead. Uninstall one of the colliding plugins, or use the plugin-id URL directly (`/<prefix>/plugins/<plugin-id>`) to reach a specific one while you sort it out.

Plugin settings

Most plugins have some configuration: an API key, a base URL, a default folder, a list of watched repositories. EKVAAR OS gives plugins two ways to expose that to you.

![Plugin settings](../user-guides/screenshots/light/plugins/settings.png)

****Auto-generated forms.** If the plugin ships a JSON Schema describing its configuration, EKVAAR OS renders a form automatically on the Configuration tab. You fill in the fields, click **Save Configuration**, and EKVAAR OS stores the values securely. For plugins that support it, a **Test Configuration** button appears alongside save — it sends the current form values to the plugin's worker and reports back whether the config works, without persisting anything.**

****Custom settings pages.** A plugin can also contribute its own settings UI — a multi-step wizard, a visual editor, a connection builder — via a `settingsPage` slot. When that's present, EKVAAR OS renders the plugin's custom UI instead of the auto-generated form. Everything still lives under the same Configuration tab so you always know where to look.**

Secrets

Fields the plugin marks as secret (API keys, tokens, passwords) are stored encrypted and never redisplayed in plain text. The form shows a masked placeholder once a secret has been saved; to change it, type a new value and save again. Leaving the masked placeholder as-is keeps the existing secret.

Permissions sidebar

To the right of the settings form, the **Permissions card lists the capabilities the plugin's manifest declares — a short, readable list of what this plugin is allowed to touch (for example, "read issues in this company", "write to project workspaces", "send outbound webhooks"). These are the same capabilities the `upgrade_pending` gate checks against on upgrade. If a plugin's permissions list doesn't match what you think it should be doing, that's a signal to investigate before enabling it.**

Jobs, webhooks, and logs

Plugins don't just sit there. Many of them run scheduled jobs — a sync every 15 minutes, a nightly reconciliation, a cleanup pass every Sunday — or receive webhooks from external services. The **Status tab on the plugin detail page is where you see that activity.**

![Plugin jobs log](../user-guides/screenshots/light/plugins/jobs-log.png)

The tab shows:

- **Worker process — whether the worker is running, its process ID, uptime, and how many crashes it has recovered from. If the worker crashes repeatedly, the crash count and last-crash timestamp surface here before anything looks broken in the rest of the UI.**
- **Recent job runs — the last handful of scheduled jobs the plugin fired, each with a status dot (green success, red failed, blue running, grey cancelled, amber queued), the trigger that caused it, and a relative time. A green dot and a short duration is the thing you want to see repeating.**
- **Recent webhook deliveries — incoming webhooks, each with a status and duration. Useful when you're debugging an integration that isn't firing.**
- **Health status — aggregate check results, polled every 30 seconds while the plugin is `ready`. If a specific check is failing (for example, "can reach external API"), you'll see it called out here long before it becomes a crash.**
- **Recent logs — the last 50 log entries the worker emitted, colour-coded by level. This is your first stop when something looks off.**

The whole tab refreshes on a 30-second cycle, so you can leave it open while you tweak config or trigger a manual run elsewhere in EKVAAR OS.

Interpreting job status dots

The coloured dot next to each job run summarises the outcome at a glance:

- **Green — the job succeeded. A steady stream of green dots at the expected cadence is what a healthy plugin looks like.**
- **Blue (pulsing) — the job is running right now. If a blue dot sticks around for much longer than you'd expect, the Recent Logs panel below is where you look next.**
- **Amber — the job is queued, waiting for the worker to pick it up. Brief amber is fine; persistent amber usually means the worker is busy or stuck.**
- **Red — the job failed. The log entry with a matching timestamp will have the reason.**
- **Grey — the job was cancelled, typically because you disabled the plugin while it was scheduled.**

Webhook delivery dots follow similar colours: green for processed, blue for received, amber for pending, red for failed.

Authoring your own plugin

If none of the installed plugins do what you need, you can write one. Plugins are npm packages with a `EKVAAR OSPlugin` manifest block, a worker entry, and an optional UI bundle — the example plugins under `packages/plugins/examples/` are a good starting point.

The full authoring path lives outside this guide:

- The `EKVAAR OS-create-plugin` skill scaffolds a new plugin package, including the manifest, worker, and a minimal UI surface.
- The EKVAAR OS CLI (`EKVAAR OSai`) wraps common authoring tasks — scaffolding, dev serving, building, and publishing. See the [CLI overview](../guides/getting-started/your-first-agent.md) and the plugin adapter documentation in the main EKVAAR OS repository for details.

Once your plugin builds, install it with **Install Plugin on the Plugin Manager page the same way you'd install anything else. During development you can also point the installer at a local path — the bundled **Install** flow is the same mechanism, just targeted at a package inside your checkout.**

Developing plugins locally

If you're iterating on your own plugin rather than running a published one, the friendliest loop is the CLI-driven local-path install: `EKVAAR OSai plugin init` scaffolds the package, `pnpm dev` runs a watch build, and `EKVAAR OSai plugin install <path>` points EKVAAR OS at the folder so the worker reloads each time `dist/` is rewritten.

See **[Develop a plugin locally](../how-to/develop-a-plugin-locally.md) for the full walkthrough — scaffolding flags, the reload semantics, when to switch back to an npm install, and the troubleshooting checklist for the moments edits stop reaching EKVAAR OS.**

You're set

Plugins give you a way to extend EKVAAR OS itself — new pages, new widgets, new scheduled work — without forking the codebase. Install what you need, keep disabled what you don't, and let the detail page tell you when something needs attention.

If you're looking to extend what an individual agent can *do* rather than what EKVAAR OS can *show*, see [Skills](../guides/org/skills.md) and [Agent Adapters](../guides/org/agent-adapters.md) next.

Quick reference

A cheat sheet for operating the Plugin Manager day-to-day:

Goal	Action
Try a bundled plugin	Plugin Manager → Available Plugins → **Install**
Install a third-party plugin	Plugin Manager → **Install Plugin** → enter npm package name
Temporarily stop a plugin's jobs	Click the power button on the plugin row (green to grey)
Bring a plugin back online	Click the power button again, or **Enable** from the detail page
Fix a plugin stuck in `error`	Detail page → Status tab → read the log, then re-enable
Approve an upgrade that asks for new permissions	Detail page → review Permissions → **Enable**
Change configuration	Detail page → Configuration tab → edit form → **Save Configuration**
Verify a config before committing	Detail page → Configuration tab → **Test Configuration** (when available)
Permanently remove a plugin	Trash icon on the plugin row → confirm

If you get stuck, the Status tab on any plugin detail page is the place to start — worker status, recent runs, and recent logs will usually point at the cause faster than poking at configuration.

CLI Auth & Board Claim

EKVAAR OS has two separate identity flows for humans on the command line and browser:

- **Board claim** — a one-time bootstrap step that promotes your browser-authenticated user to the owner of a freshly started authenticated instance. It migrates the trusted "local board" placeholder into a real, named human account.
- **CLI auth** — the everyday flow that pairs a local `EKVAAR OSai` CLI process with a signed-in board user, so the CLI can call `/api` endpoints on your behalf without you typing credentials into your shell.

Both flows use a short-lived, server-minted challenge and a browser approval page. Both are designed so the secret material (the board API token, the ownership migration) never leaves the browser or the CLI process that asked for it.

This guide walks through both, shows the approval pages, and explains how to use the resulting tokens with the CLI.

When you need each flow

- You just installed EKVAAR OS in **authenticated** deployment mode on a server, and the loopback trust is still active → run **Board claim** once.
- You want to run `EKVAAR OSai` commands against that instance from your laptop → run **CLI auth** (`EKVAAR OSai auth login`).
- You're using **trusted** deployment mode (loopback-only local dev) → neither flow is required; the CLI and browser already trust the loopback.

Claiming a board from the CLI

Board claim only exists when _all_ of these are true:

- Deployment mode is `authenticated`.
- The only instance admin is the built-in `local-board` placeholder (i.e., no human has claimed the instance yet).
- The claim challenge hasn't expired (the server keeps the active challenge for 24 hours and refreshes it automatically after that).

When the server starts and those conditions match, it prints a **Board claim** URL to the server log. It looks like:

```
http://localhost:3000/board-claim/<token>?code=<code>
```

The `token` is 48 hex characters; the `code` is 24 hex characters. Together they identify exactly one pending claim.

Open the URL in your browser. If you aren't signed in yet, the page will ask you to sign in or create an account first and bounce you back to the same URL after authentication.

Once you're signed in, the page shows a panel titled **Claim Board ownership** with a short explanation ("This will promote your user to instance admin and migrate company ownership access from local trusted mode.") and a single **Claim ownership** button.

Click it and the server does three things in a single transaction:

1. Inserts an `instance_admin` role for your user (if you weren't one already).
2. Deletes the `local-board` placeholder admin.
3. Walks every company in the database and, for each one, either creates an `active`, `owner`-role membership for you or reactivates your existing membership and sets the role to `owner`.

The button swaps to **Claiming…** during the request. When it returns successfully the page switches to **Board ownership claimed** with a link to open the board. The in-memory challenge is marked claimed and cannot be reused.

If the challenge expired, or the URL is malformed, the page shows **Claim challenge unavailable** instead. Restart the server (or wait for the next refresh) to mint a new challenge.

Device-code flow: `EKVAAR OSai auth login`

For day-to-day CLI use, the flow is a device-code-style pairing. The CLI creates a challenge, opens your browser, you approve it, and the CLI finishes with a stored token.

Starting the login

From the machine you want to use the CLI on:

```sh
EKVAAR OSai auth login
```

The CLI:

1. POSTs to `/api/cli-auth/challenges` with a description of itself (`command`, `clientName`, `requestedAccess`, and an optional `requestedCompanyId`).
2. Gets back a challenge containing `token`, `boardApiToken`, `approvalUrl`, `pollPath`, `expiresAt`, and a polling interval.
3. Prints the approval URL to your terminal and tries to open it in your default browser.
4. Starts polling the server at `pollPath` until the challenge is approved, cancelled, or expires.

Common flags:

```sh
# Request instance-admin approval (only instance admins can approve this)
```

EKVAAR OSai auth login --instance-admin

Scope to a specific company
EKVAAR OSai auth login --company-id <company-id>

Target a non-default server
EKVAAR OSai auth login --api-base https://EKVAAR OS.example.com
```

### Approving the challenge in the browser

Your browser lands on a page titled **Approve EKVAAR OS CLI access**:

The panel shows what the CLI is asking for:

- **Command** — the CLI command that initiated the login (e.g. `EKVAAR OSai auth login`).
- **Client** — the `clientName` the CLI sent, default `EKVAAR OSai cli`.
- **Requested access** — either `Board` or `Instance admin`.
- **Requested company** — only shown if the CLI asked to be scoped to a company.

Two buttons at the bottom:

- **Approve CLI access** — only enabled if your signed-in user is allowed to approve this level of access. An instance-admin challenge requires an instance-admin approver.
- **Cancel** — rejects the challenge. The CLI sees the `cancelled` status on its next poll and exits with an error.

If you aren't signed in, the page first shows **Sign in required** with a button that returns you here after authentication. If the challenge has already been approved, cancelled, or expired by the time you visit the URL, the page reflects that state instead of offering the buttons.

### Finishing on the CLI

Once you click **Approve**, the CLI's next poll sees status `approved`, calls `/api/cli-auth/me` with the board API token to confirm identity, and writes the credential to the local credential store. It prints a success summary:

```json
{
  "ok": true,
  "apiBase": "https://EKVAAR OS.example.com",
  "userId": "usr_...",

```
  "approvalUrl": "https://EKVAAR OS.example.com/cli-auth/..."
}
```

If you cancel or let the challenge expire, the CLI errors out with `CLI auth challenge was cancelled.` or `CLI auth challenge expired before approval.` — re-run `EKVAAR OSai auth login` to try again.

After claiming: using and rotating the token

Where the token lives

The CLI stores the board API token (and the user id it resolves to) in the platform-appropriate config directory, keyed by `apiBase`. You don't need to copy the token anywhere — every CLI command that accepts `--api-base` will look up the matching stored credential automatically.

Using it

Once logged in, the CLI sends `Authorization: Bearer <stored-token>` on every request. You can verify by running:

```sh
EKVAAR OSai auth whoami
```

which calls `/api/cli-auth/me` and prints:

```json
{
  "user": { "id": "...", "name": "...", "email": "..." },
  "userId": "...",
  "isInstanceAdmin": true,
  "companyIds": ["..."],
  "source": "board-cli",
  "keyId": "..."
}
```

All other CLI commands — the ones documented in [Setup Commands](../reference/cli/setup-commands.md) and Control-Plane Commands — reuse this credential unless you pass an explicit `--token` or override `EKVAAR OS_API_KEY`.

Rotating and revoking

When you want to rotate the credential, log out and log back in:

```sh
EKVAAR OSai auth logout
EKVAAR OSai auth login
```

`EKVAAR OSai auth logout`:

1. POSTs to `/api/cli-auth/revoke-current` with the stored token to revoke it server-side.
2. Deletes the local credential entry for this `apiBase`.

If the server-side revoke fails (network error, token already invalid) the local credential is still removed — you won't be stuck with a stale entry. A new `EKVAAR OSai auth login` mints a fresh challenge and a fresh token with no relationship to the old one.

Multiple servers and users

The credential store is keyed by normalised `apiBase`, so one machine can hold separate credentials for a local dev instance, a staging server, and a production server at the same time. Switching between them is a matter of passing `--api-base` (or setting it in config). Logging in as a different user for the same `apiBase` replaces the existing credential for that server.

Troubleshooting

- **"Invalid CLI auth URL."** — You opened the approval page with a missing `id` or `token` query param. Re-run `EKVAAR OSai auth login` to get a fresh link.
- **"CLI auth challenge unavailable"** — The token is valid but the server no longer has a matching challenge (it expired, or the server restarted). Start the login again.
- **"This challenge requires instance-admin access."** — You're approving an `--instance-admin` challenge but your signed-in user isn't an instance admin. Sign in with an admin account and retry.
- **"CLI auth challenge expired before approval."** on the CLI — You let the browser tab sit too long. Just rerun `EKVAAR OSai auth login`.
- **Board claim page shows "Claim challenge unavailable."** — The one-time ownership challenge has already been consumed, or it expired. If the instance has no real admins yet, restart the server — it mints a new challenge and reprints the URL in the logs.

Where to go next

- [Setup Commands](../reference/cli/setup-commands.md) — installing, onboarding, and configuring a EKVAAR OS instance from the CLI.
- [Authentication (API)](../reference/api/authentication.md) — the underlying authentication model for board users, agents, and runs.

Authentication

EKVAAR OS supports two different identities over the API:

- **Board auth** for humans and operators
- **Agent auth** for agents and heartbeat/runtime code

Every bearer-authenticated request uses the same header shape:

```http
Authorization: Bearer <token>
```

What changes is how EKVAAR OS interprets the token.

How request auth is resolved

EKVAAR OS resolves the request actor in this order:

1. If there is **no** bearer token and the deployment is `local_trusted`, the request starts as a board actor with full local trust.
2. If there is **no** bearer token and the deployment is `authenticated`, EKVAAR OS tries to resolve the current web session and maps it to a board actor when a session user exists.
3. If there **is** a bearer token, EKVAAR OS checks it as a board API key first.
4. If it is not a board key, EKVAAR OS checks agent API keys.
5. If it still does not match, EKVAAR OS tries a local agent JWT.
6. If nothing matches, the request remains unauthenticated.

That means bearer tokens always win over cookies. A request with a valid bearer token is not treated as a session request.

`X-EKVAAR OS-Run-Id` is also read by the server and attached to the resolved actor when present. For agent JWTs, the run ID can also come from the token claims.

Deployment modes

EKVAAR OS only implements two deployment modes in the current codebase:

- `local_trusted`
- `authenticated`

`local_trusted` is the simplest mode. The server starts every request as a board actor with source `local_implicit`. This mode is only valid when `server.exposure` is `private`.

`authenticated` is the login-aware mode. When no bearer token is present, EKVAAR OS can resolve the current web session and treat that user as a board actor. If no session can be resolved, the request stays unauthenticated.

If you expose EKVAAR OS publicly, config validation also requires:

- `auth.baseUrlMode = explicit`
- `auth.publicBaseUrl` to be set

Those checks are enforced by the config schema, so the docs and the running server should agree.

Board authentication

Board auth is for humans operating EKVAAR OS.

There are two board auth paths:

- **Session auth in `authenticated` deployments, where the browser session is resolved automatically**
- **Board API keys for CLI and automation**

Session auth

In `authenticated` deployments, if a request does not send a bearer token, EKVAAR OS tries to resolve a user session. When successful, the request becomes a board actor with:

- the user ID from the session
- the list of company memberships for that user
- instance-admin status when the user has the instance admin role

This is what powers the web UI.

Board API keys

Board API keys are opaque bearer tokens with the prefix `pcp_board_`. They are hashed before storage and matched by hash.

They are created through the CLI auth challenge flow:

- `POST /api/cli-auth/challenges`
- `GET /api/cli-auth/challenges/:id`
- `POST /api/cli-auth/challenges/:id/approve`
- `POST /api/cli-auth/challenges/:id/cancel`
- `GET /api/cli-auth/me`
- `POST /api/cli-auth/revoke-current`

`POST /api/cli-auth/challenges/:id/approve` can mint a board API key as part of the approval flow. `POST /api/cli-auth/revoke-current` only works when the current request is already authenticated with a board API key.

`GET /api/cli-auth/me` is a board-only endpoint. It returns the resolved user, company IDs, instance-admin status, auth source, and key ID when the caller is using a board key.

Agent authentication

Agent auth is for requests that should be scoped to a single agent and a single company.

EKVAAR OS accepts two agent token shapes:

- **Agent API keys** created by `POST /api/agents/:id/keys`
- **Local agent JWTs** created by the runtime secret used in heartbeat and adapter code

Agent API keys

Agent API keys are long-lived bearer tokens. They are created on the agent routes, returned once at creation time, and then stored as hashes.

The server rejects new key creation for agents in these states:

- `pending_approval`
- `terminated`

When an agent API key is used, EKVAAR OS looks up the key by hash, updates `lastUsedAt`, and then verifies that the agent still exists and is not terminated or pending approval.

Local agent JWTs

Local agent JWTs are signed with the configured agent JWT secret. The token must contain:

- agent ID in `sub`
- company ID in `company_id`
- adapter type in `adapter_type`
- run ID in `run_id`
- `iat`
- `exp`

The server accepts the JWT only when:

- the signature is valid
- the token is not expired
- the referenced agent exists
- the agent belongs to the same company as the token claims
- the agent is not `terminated`
- the agent is not `pending_approval`

If the JWT is accepted, the request becomes an agent actor with the token's agent ID, company ID, and run ID.

Agent-only endpoints

`GET /api/agents/me` is the clearest example of agent auth in use. It returns the current agent record only when the caller is authenticated as an agent.

Company scoping

Auth success does not automatically mean broad access.

EKVAAR OS still applies company scoping on top of authentication:

- Agent actors are always limited to their own company.
- Board actors can access the companies they are a member of.
- Instance admins can access instance-wide company data where the route allows it.
- `local_implicit` board actors in `local_trusted` deployments bypass the normal company membership check.

If a request is authenticated but points at the wrong company, the server returns `403` instead of treating it as a missing token.

This is enforced in route guards such as `assertCompanyAccess`, `assertBoard`, and `assertInstanceAdmin`.

Examples

Board auth with a board API key

Use a board API key when you are scripting against the API or calling it from a tool that cannot use the browser session cookie.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -s http://localhost:3100/api/cli-auth/me \
  -H "Authorization: Bearer pcp_board_your_token_here"
```

<!-- tab: JavaScript -->

```js
const res = await fetch("http://localhost:3100/api/cli-auth/me", {
  headers: {
    Authorization: "Bearer pcp_board_your_token_here",
  },
});

const data = await res.json();
console.log(data);
```

<!-- tab: Python -->

```python
import requests

res = requests.get(
   "http://localhost:3100/api/cli-auth/me",
   headers={"Authorization": "Bearer pcp_board_your_token_here"},
)

print(res.json())
```

<!-- /tabs -->

Agent auth with an agent token

Use an agent token when you are acting as an agent or running heartbeat code. The token may be a long-lived agent API key or a short-lived local agent JWT, but the request shape is the same.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -s http://localhost:3100/api/agents/me \
  -H "Authorization: Bearer $EKVAAR OS_API_KEY" \
  -H "X-EKVAAR OS-Run-Id: run_123"
```

<!-- tab: JavaScript -->

```js
const res = await fetch("http://localhost:3100/api/agents/me", {
  headers: {
    Authorization: `Bearer ${process.env.EKVAAR OS_API_KEY}`,
    "X-EKVAAR OS-Run-Id": "run_123",
  },
});

const data = await res.json();
console.log(data);
```

```

<!-- tab: Python -->

```python
import os
import requests

res = requests.get(
  "http://localhost:3100/api/agents/me",
  headers={
    "Authorization": f"Bearer {os.environ['EKVAAR OS_API_KEY']}",
    "X-EKVAAR OS-Run-Id": "run_123",
  },
)

print(res.json())
```

<!-- /tabs -->

Update note

I rewrote this page to reflect the actual auth middleware and route guards, clarify board vs agent auth, document the implemented deployment-mode behavior, and add clearer multi-language examples.

Changed files:

- `docs/api/authentication.md`

Companies

Companies are the top-level tenant boundary in EKVAAR OS. Every agent, project, issue, approval, cost event, and asset belongs to exactly one company, and the API enforces that boundary on every company-scoped route.

Board callers can list and manage companies. Agent callers can read their own company, and CEO agents can update branding for their company. Deleting a company is destructive; archiving is not.

```

Company shape

The company API returns a compact company object with the fields you will use most often:

Field	Meaning
`id`	Stable company id
`name`	Display name
`description`	Optional plain-text description
`status`	`active`, `paused`, or `archived`
`issuePrefix`	Auto-generated issue prefix, based on the company name
`issueCounter`	Next issue number for the company
`budgetMonthlyCents`	Company budget ceiling in cents
`spentMonthlyCents`	Current month spend in cents
`requireBoardApprovalForNewAgents`	Whether hires need board approval
`brandColor`	Optional hex brand color
`logoAssetId`	Stored logo asset id, or `null`
`logoUrl`	Derived content URL for the stored logo, or `null`
`createdAt`	Creation timestamp
`updatedAt`	Last update timestamp

The response also includes feedback-sharing consent fields when they are set. `logoUrl` is derived from `logoAssetId`; you do not set it directly.

List companies

```
GET /api/companies
```

Returns the companies the current board caller can access. In normal use this is your company list, not every company in the instance.

> **Note:** This is a board route. Agent callers do not use it.

Get a company

```
GET /api/companies/{companyId}
```

Returns one company object if the caller has access to that company.

List company artifacts

```
GET /api/companies/{companyId}/artifacts
```

Returns a company-wide projection of the outputs agents produced while working. It flattens three sources — agent-authored issue documents, direct issue attachments, and `artifact` work products — into one card-ready list, so callers do not have to stitch per-issue endpoints together. Company access is checked before the projection runs.

Query parameters

Parameter	Values	Description
`kind`	`image`, `video`, `text`, `document`, `file`, `all`	Filter by media kind. Defaults to `all`.
`projectId`	UUID	Restrict to artifacts from issues in one project.
`q`	string (max 160 chars)	Free-text search over artifact title/summary and originating issue identifier/title.
`groupBy`	`none`, `task`, `parent_task`	Grouping mode. `none` (default) returns a flat artifact list; `task` groups by the originating issue; `parent_task` rolls sub-issue artifacts up under their root issue.
`groupIssueId`	UUID	When grouping, expand a single group (stack) into its own artifacts.
`limit`	integer 1–100	Page size. Defaults to `30`.
`cursor`	string	Opaque pagination cursor from a prior response's `nextCursor`.

Response

The response is an envelope. In the ungrouped case it returns the flat `artifacts` list; when `groupBy` is `task` or `parent_task` it returns `groups` instead (or, when `groupIssueId` is supplied, the expanded group's `artifacts` plus `selectedGroup`). `nextCursor` is `null` when there are no further pages.

```json
{
  "artifacts": [
    {
```

```
      "id": "work_product:...",
      "source": "work_product",
      "mediaKind": "video",
      "title": "Launch teaser render",
      "previewText": null,
      "contentType": "video/mp4",
      "contentPath": "/api/attachments/.../content",
      "openPath": "/api/attachments/.../content",
      "downloadPath": "/api/attachments/.../content?download=1",
      "issue": { "id": "...", "identifier": "PAP-123", "title": "Produce launch teaser" },
      "project": { "id": "...", "name": "Launch" },
      "createdByAgent": { "id": "...", "name": "Video Agent" },
      "updatedAt": "2026-06-01T12:00:00.000Z",
      "href": "/PAP/issues/PAP-123#work-product-..."
    }
  ],
  "nextCursor": null
}
```

Each artifact carries:

Field	Meaning
`id`	Stable artifact id, prefixed by source (`document:`, `attachment:`, or `work_product:`)
`source`	`document`, `attachment`, or `work_product`
`mediaKind`	`image`, `video`, `text`, `document`, `file`, or `empty`
`title`	Display title
`previewText`	Short plain-text preview, or `null`
`contentType`	MIME type of the underlying content, or `null`
`contentPath`	Path to the raw content, or `null`
`openPath`	Path for inline open, or `null`
`downloadPath`	Path for download, or `null`
`issue`	`{ id, identifier, title }` of the originating issue
`project`	`{ id, name }` of the issue's project, or `null`
`createdByAgent`	`{ id, name }` of the producing agent, or `null`
`updatedAt`	Last-updated timestamp
`href`	Deep link to the artifact on its originating issue

A group object (returned under `groups` / `selectedGroup`) carries `id`, `groupBy`, `issue`, `title`, `count`, `mediaKinds`, `previewArtifacts`, `updatedAt`, and `href`.

Create a company

```
POST /api/companies
{
  "name": "Horizon Labs",
  "description": "An autonomous research and marketing company",
  "budgetMonthlyCents": 50000
}
```

Creates a new company and assigns it an automatic issue prefix. If `budgetMonthlyCents` is greater than `0`, EKVAAR OS also creates the matching monthly budget policy in UTC calendar-month mode.

This route is board-facing. In local trusted mode, the implicit board session satisfies that requirement.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -X POST "http://localhost:3100/api/companies" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "Horizon Labs",
    "description": "An autonomous research and marketing company",
    "budgetMonthlyCents": 50000
  }'
```
<!-- tab: JavaScript -->
```js
const res = await fetch("http://localhost:3100/api/companies", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${token}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    name: "Horizon Labs",
    description: "An autonomous research and marketing company",
    budgetMonthlyCents: 50000,
```

```
  }),
});
const company = await res.json();
```
<!-- tab: Python -->
```py
import requests

res = requests.post(
    "http://localhost:3100/api/companies",
    headers={"Authorization": f"Bearer {token}"},
    json={
        "name": "Horizon Labs",
        "description": "An autonomous research and marketing company",
        "budgetMonthlyCents": 50000,
    },
)
company = res.json()
```
<!-- /tabs -->

Update a company

```
PATCH /api/companies/{companyId}
{
  "name": "Horizon Labs",
  "description": "Updated description",
  "budgetMonthlyCents": 75000,
  "status": "active",
  "brandColor": "#2563eb",
  "logoAssetId": "11111111-1111-4111-8111-111111111111"
}
```

Board callers can update the full company record here. CEO agents can also call this route, but only with branding fields. If you only want to change branding, the dedicated `/branding` route below is the clearer option.

Important branding caveat:

- `logoAssetId` must point to an asset that belongs to the same company.

- Replacing or clearing the logo removes the previous logo asset record.
- `logoUrl` is derived by the server after the logo is linked.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -X PATCH "http://localhost:3100/api/companies/company-1" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "Horizon Labs",
    "description": "Updated description",
    "budgetMonthlyCents": 75000,
    "status": "active",
    "brandColor": "#2563eb"
  }'
```
<!-- tab: JavaScript -->
```js
const res = await fetch("http://localhost:3100/api/companies/company-1", {
  method: "PATCH",
  headers: {
    Authorization: `Bearer ${token}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    name: "Horizon Labs",
    description: "Updated description",
    budgetMonthlyCents: 75000,
    status: "active",
    brandColor: "#2563eb",
  }),
});
const company = await res.json();
```
<!-- tab: Python -->
```py
import requests

res = requests.patch(
    "http://localhost:3100/api/companies/company-1",
    headers={"Authorization": f"Bearer {token}"},
    json={
```

```
      "name": "Horizon Labs",
      "description": "Updated description",
      "budgetMonthlyCents": 75000,
      "status": "active",
      "brandColor": "#2563eb",
    },
)
company = res.json()
```
<!-- /tabs -->

Update branding

```
PATCH /api/companies/{companyId}/branding
{
  "name": "Horizon Labs",
  "brandColor": "#2563eb",
  "logoAssetId": "11111111-1111-4111-8111-111111111111"
}
```

Use this when you want a narrower branding-only update. The route accepts:

- `name`
- `description`
- `brandColor`
- `logoAssetId`

Board callers can use it. CEO agents can use it only for their own company.

If you pass a `logoAssetId` that belongs to a different company, the API returns `422`.

Upload a company logo

```
POST /api/companies/{companyId}/logo
Content-Type: multipart/form-data
```

This route uploads the logo image itself and returns an asset record. It does **not attach the logo to the company automatically. After the upload succeeds, send the returned `assetId` to `PATCH /api/companies/{companyId}` or `PATCH /api/companies/{companyId}/branding` as `logoAssetId`.**

Accepted image types:

- `image/png`
- `image/jpeg`
- `image/jpg`
- `image/webp`
- `image/gif`
- `image/svg+xml`

Logo uploads use the normal attachment size limit. SVG files are sanitized before storage. Scripts and external links are stripped, and empty or unsafe SVGs are rejected.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -X POST "http://localhost:3100/api/companies/company-1/logo" \
  -H "Authorization: Bearer <token>" \
  -F "file=@./logo.svg"
```
<!-- tab: JavaScript -->
```js
const formData = new FormData();
formData.append("file", fileInput.files[0]);

const res = await fetch("http://localhost:3100/api/companies/company-1/logo", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${token}`,
  },
  body: formData,
});
const result = await res.json();
```
<!-- tab: Python -->
```py
import requests

with open("logo.svg", "rb") as f:
```

```
    res = requests.post(
        "http://localhost:3100/api/companies/company-1/logo",
        headers={"Authorization": f"Bearer {token}"},
        files={"file": ("logo.svg", f, "image/svg+xml")},
    )

result = res.json()
```
<!-- /tabs -->

The upload response includes `assetId` and `contentPath`. `contentPath` points at `/api/assets/{assetId}/content`.

Company stats

```
GET /api/companies/stats
```

Returns a simple summary keyed by company id:

```json
{
  "company-1": { "agentCount": 5, "issueCount": 42 }
}
```

This route is board-only.

Feedback traces

```
GET /api/companies/{companyId}/feedback-traces
```

Board-only route for reviewing feedback activity across a company. Query filters include:

- `targetType`
- `vote`
- `status`

- `issueId`
- `projectId`
- `from`
- `to`
- `sharedOnly`
- `includePayload`

Use this when you want to inspect the feedback loop, not normal company activity.

Export and import

EKVAAR OS exposes both broad and company-scoped portability routes:

Route	Purpose	Who can call it
`POST /api/companies/{companyId}/export`	Export a company bundle	Any caller with access to the company
`POST /api/companies/{companyId}/exports/preview`	Preview a company export	Board or CEO of that company
`POST /api/companies/{companyId}/exports`	Export a company bundle with the stricter portability flow	Board or CEO of that company
`POST /api/companies/import/preview`	Preview an import into a new or existing company	Board only
`POST /api/companies/{companyId}/imports/preview`	Preview an import into the same company	Board or CEO of that company
`POST /api/companies/{companyId}/imports/apply`	Apply an import into the same company	Board or CEO of that company

The company-scoped `imports/*` routes are intentionally safer:

- they can only target the route company
- they reject the `replace` collision strategy

Use the board-level preview route when you need to inspect an import that would create a brand-new company or target a different company.

Archive or delete

```
POST /api/companies/{companyId}/archive
```

DELETE /api/companies/{companyId}
```

Archiving changes the company status to `archived` and removes it from default listings. It also runs a cascade that pauses every active agent in the company (pause reason `company_archived`) and cancels their queued or in-flight wake-up requests, so an archived company stops doing background work. Deleting removes the company and its related data. Deletion is destructive and should be treated as irreversible.

---

## Practical notes

- Company access is always checked before reading or mutating company data.
- `logoUrl` is derived from the stored logo asset and should be treated as read-only.
- If you are updating branding only, prefer `PATCH /api/companies/{companyId}/branding`.
- If you are uploading a logo, remember the upload and the company update are two separate steps.

# Agents

Manage agents inside a company.

Use this API when you need to create agents, inspect their configuration, manage their lifecycle, rotate API keys, sync skills, inspect the org chart, or manually trigger work.

## Quick Rules

- This API is company-scoped. Every meaningful request is tied to a company.
- Board-authenticated requests can manage agents in the selected company, subject to normal permission checks.
- Agent-authenticated requests can only act inside their own company.
- `GET /api/agents/:id` accepts either a UUID or a company-unique shortname, but shortname lookup only works when the server knows the company context. In practice that means `?companyId=...` or agent auth.
- Terminated agents are hidden from list and org-chart responses, but you can still fetch them directly if you know the ID.
- `GET /api/agents/:id` may return a redacted view for another same-company agent when the caller cannot read agent configuration.

---

## Common Fields
```

The agent payload is a normal JSON object. These are the fields you will see most often:

| Field | Meaning |
|---|---|
| `name` | Human-friendly name. The server also derives a company-unique URL key from it. |
| `role` | Role label such as `ceo`, `engineer`, or `general`. |
| `title` | Optional display title. |
| `reportsTo` | Parent agent in the org tree. Must be in the same company and cannot create a cycle. |
| `adapterType` | Runtime type such as `process`, `http`, `claude_local`, `codex_local`, `gemini_local`, `opencode_local`, `pi_local`, `hermes_local`, `cursor`, or `openclaw_gateway`. External adapters can also be registered. |
| `adapterConfig` | Adapter-specific config. Secret references are allowed inside `env`. |
| `runtimeConfig` | Runtime settings. `heartbeat.enabled` defaults to `false` when you create an agent. |
| `budgetMonthlyCents` | Monthly budget in cents. If this is greater than `0` on create, the server creates a matching budget policy automatically. |
| `status` | Lifecycle state. The shared enum includes `active`, `paused`, `idle`, `running`, `error`, `pending_approval`, and `terminated`. |
| `permissions` | Agent-level permissions, currently `canCreateAgents`. |

List Agents

Lists agents for a company.

`GET /api/companies/{companyId}/agents`

Use this when you want a company-wide roster. The route excludes terminated agents by default.

If the caller cannot read agent configuration, the response is returned in a redacted form instead of failing outright.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
**curl -s **
** "http://localhost:3100/api/companies/{companyId}/agents" **
** -H "Authorization: Bearer <token>"**

```
<!-- tab: JavaScript -->
```js
const res = await fetch(`http://localhost:3100/api/companies/${companyId}/agents`, {
  headers: { Authorization: `Bearer ${token}` },
});

const agents = await res.json();
```
<!-- tab: Python -->
```python
import requests

res = requests.get(
    f"http://localhost:3100/api/companies/{companyId}/agents",
    headers={"Authorization": f"Bearer {token}"},
)
agents = res.json()
```
<!-- /tabs -->

Get Agent

Returns one agent by UUID or company shortname.

`GET /api/agents/{agentId}`

Use this when you want the full agent record plus derived metadata:

- `chainOfCommand`
- `access`

The `access` block explains whether the agent can assign tasks and where that ability came from.

Notes:

- If you pass a shortname instead of a UUID, the server must know the company context. Use `?companyId={companyId}` when needed.
- If an agent asks for another same-company agent and cannot read config, the response is redacted rather than rejected.
```

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -s \
  "http://localhost:3100/api/agents/{agentId}?companyId={companyId}" \
  -H "Authorization: Bearer <token>"
```
<!-- tab: JavaScript -->
```js
const res = await fetch(
  `http://localhost:3100/api/agents/${agentId}?companyId=${companyId}`,
  {
    headers: { Authorization: `Bearer ${token}` },
  },
);

const agent = await res.json();
```
<!-- tab: Python -->
```python
import requests

res = requests.get(
    f"http://localhost:3100/api/agents/{agentId}",
    params={"companyId": companyId},
    headers={"Authorization": f"Bearer {token}"},
)
agent = res.json()
```
<!-- /tabs -->

Get Current Agent

Returns the authenticated agent itself.

`GET /api/agents/me`

Use this from agent-authenticated flows when the agent needs to inspect its own record, chain of command, or access state.

This route is agent-only.

Compact Inbox (`inbox-lite`)

Returns the compact assignment list an agent needs at the start of a heartbeat.

`GET /api/agents/me/inbox-lite`

The response is intentionally narrower than the full issues list endpoint — each item carries just enough data to prioritise work without a second fetch:

- `id`, `identifier`, `title`, `status`, `priority`
- `projectId`, `goalId`, `parentId`
- `updatedAt`
- `activeRun` — the current run on this issue, if one is in flight
- `dependencyReady` — `false` if any blockers are still open
- `unresolvedBlockerCount` and `unresolvedBlockerIssueIds`

Use this route in preference to the full company issues list during heartbeat startup. Fall back to `GET /api/companies/{companyId}/issues?assigneeAgentId=...` only when you need the complete issue object.

This route is agent-only.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -s \
  "http://localhost:3100/api/agents/me/inbox-lite" \
  -H "Authorization: Bearer $EKVAAR OS_API_KEY"
```
<!-- tab: JavaScript -->
```js
const res = await fetch("http://localhost:3100/api/agents/me/inbox-lite", {
  headers: { Authorization: `Bearer ${token}` },
});
const inbox = await res.json();
```
<!-- tab: Python -->
```python
import os, requests
```

```
res = requests.get(
  "http://localhost:3100/api/agents/me/inbox-lite",
  headers={"Authorization": f"Bearer {os.environ['EKVAAR OS_API_KEY']}"},
)
inbox = res.json()
```

<!-- /tabs -->

Create Agent

Creates a new agent in a company.

`POST /api/companies/{companyId}/agents`

Use this when you are hiring or provisioning a new agent. In the current implementation, this route is board-only.

Important behavior:

- The server validates the target company.
- The new agent is created with `status: "idle"`.
- If the company requires board approval for new agents, use the hire flow below instead. That route creates `pending_approval` and records the approval payload.
- Duplicate names are deduplicated on create. If the name already maps to an existing company shortname, the server appends a numeric suffix.
- `runtimeConfig.heartbeat.enabled` defaults to `false` if you omit it.
- `adapterConfig.env` can contain secret references, but those secrets must belong to the same company.
- If `budgetMonthlyCents > 0`, the server creates a matching monthly budget policy automatically.
- Certain adapters apply defaults on create. For example, `codex_local`, `gemini_local`, and `cursor` can fill in a default model, and `openclaw_gateway` can generate a device private key unless device auth is disabled.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -s -X POST \
  "http://localhost:3100/api/companies/{companyId}/agents" \
```

```
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "Engineering Lead",
    "role": "ceo",
    "title": "CEO",
    "reportsTo": null,
    "capabilities": "Plans strategy, delegates work, reviews progress",
    "adapterType": "claude_local",
    "adapterConfig": {
      "model": "claude-sonnet-4-20250514",
      "cwd": "/Users/me/projects/company",
      "env": {
        "ANTHROPIC_API_KEY": {
          "type": "secret_ref",
          "secretId": "secret-id",
          "version": "latest"
        }
      }
    },
    "runtimeConfig": {
      "heartbeat": {
        "enabled": false
      }
    },
    "budgetMonthlyCents": 25000,
    "desiredSkills": ["strategy", "planning"],
    "metadata": {
      "team": "platform"
    }
  }'
```
<!-- tab: JavaScript -->
```js
const res = await fetch(`http://localhost:3100/api/companies/${companyId}/agents`, {
  method: "POST",
  headers: {
    Authorization: `Bearer ${token}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    name: "Engineering Lead",
    role: "ceo",
    title: "CEO",
```

```
    reportsTo: null,
    capabilities: "Plans strategy, delegates work, reviews progress",
    adapterType: "claude_local",
    adapterConfig: {
      model: "claude-sonnet-4-20250514",
      cwd: "/Users/me/projects/company",
      env: {
        ANTHROPIC_API_KEY: {
          type: "secret_ref",
          secretId: "secret-id",
          version: "latest",
        },
      },
    },
    runtimeConfig: {
      heartbeat: { enabled: false },
    },
    budgetMonthlyCents: 25000,
    desiredSkills: ["strategy", "planning"],
    metadata: { team: "platform" },
  }),
});

const agent = await res.json();
```
<!-- tab: Python -->
```python
import requests

res = requests.post(
    f"http://localhost:3100/api/companies/{companyId}/agents",
    headers={
        "Authorization": f"Bearer {token}",
        "Content-Type": "application/json",
    },
    json={
        "name": "Engineering Lead",
        "role": "ceo",
        "title": "CEO",
        "reportsTo": None,
        "capabilities": "Plans strategy, delegates work, reviews progress",
        "adapterType": "claude_local",
        "adapterConfig": {
            "model": "claude-sonnet-4-20250514",
```

```
        "cwd": "/Users/me/projects/company",
        "env": {
          "ANTHROPIC_API_KEY": {
            "type": "secret_ref",
            "secretId": "secret-id",
            "version": "latest",
          }
        },
      },
      "runtimeConfig": {
        "heartbeat": {"enabled": False},
      },
      "budgetMonthlyCents": 25000,
      "desiredSkills": ["strategy", "planning"],
      "metadata": {"team": "platform"},
    },
)
agent = res.json()
```

<!-- /tabs -->

Hire Agent

Creates an agent through the approval-aware hire flow.

`POST /api/companies/{companyId}/agent-hires`

Use this when the company may require board approval for new agents, or when you want to attach source issues to the hire request.

Important behavior:

- The request body accepts the same core agent fields as create.
- You can include `sourceIssueId` or `sourceIssueIds` to link the hire back to one or more issues.
- If the company requires board approval for new agents, this route creates a pending approval record and stores the requested config snapshot.
- The route still runs the same config normalization and adapter validation as the direct create route.

Update Agent

Updates an existing agent.

`PATCH /api/agents/{agentId}`

Use this for normal agent edits such as renaming, changing the role, adjusting the adapter config, changing the manager, or updating runtime settings.

Important behavior:

- `permissions` is not accepted here. Use the permissions route below.
- If you change `adapterConfig` partially, the server normally merges it with the existing config.
- If you set `replaceAdapterConfig: true`, the update behaves more like a replacement.
- If you change an adapter configuration that includes instructions bundle keys, the server preserves bundle-related settings when it can.
- Changing `reportsTo` must stay inside the same company and cannot create a reporting cycle.
- Renaming an agent can fail with `409 Conflict` if the new shortname would collide with another non-terminated agent in the company.
- Terminated agents cannot be resumed through a status patch.
- Pending approval agents cannot be activated directly through a status patch.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -s -X PATCH \
  "http://localhost:3100/api/agents/{agentId}" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "title": "Principal Engineer",
    "capabilities": "Designs systems, reviews architecture, and guides implementation",
    "runtimeConfig": {
      "heartbeat": {
        "enabled": true,
        "intervalSec": 300
      }
    }
  }'
```

```
<!-- tab: JavaScript -->
```js
const res = await fetch(`http://localhost:3100/api/agents/${agentId}`, {
  method: "PATCH",
  headers: {
    Authorization: `Bearer ${token}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    title: "Principal Engineer",
    capabilities: "Designs systems, reviews architecture, and guides implementation",
    runtimeConfig: {
      heartbeat: {
        enabled: true,
        intervalSec: 300,
      },
    },
  }),
});

const agent = await res.json();
```
<!-- tab: Python -->
```python
import requests

res = requests.patch(
    f"http://localhost:3100/api/agents/{agentId}",
    headers={
        "Authorization": f"Bearer {token}",
        "Content-Type": "application/json",
    },
    json={
        "title": "Principal Engineer",
        "capabilities": "Designs systems, reviews architecture, and guides implementation",
        "runtimeConfig": {
            "heartbeat": {
                "enabled": True,
                "intervalSec": 300,
            },
        },
    },
)
```
```

agent = res.json()
```

<!-- /tabs -->

---

## Update Permissions

Updates the agent-level permissions block.

`PATCH /api/agents/{agentId}/permissions`

This is the only supported way to change permissions. The main `PATCH /api/agents/:id` route rejects a `permissions` body.

Current permission fields:

- `canCreateAgents`
- The request body also accepts `canAssignTasks`, which the route applies as a principal permission grant on the agent (`tasks:assign`).
- The agent record itself only stores `canCreateAgents`.

Board sessions can call this route. Agent sessions can only call it when the caller is the company CEO agent.

When you toggle `canAssignTasks`, the server ensures the agent has an active `companyMembership` row and writes (or clears) the `tasks:assign` entry in `principalPermissionGrants`. The CEO role and the legacy `canCreateAgents` flag both keep their implicit assignment authority — `canAssignTasks` only adds an explicit grant on top.

---

## Scoped Permissions and Authorization

Agents and board users share one authorization service. Every mutation that touches an agent or an issue assignment runs through `authorizationService.decide`, which evaluates company membership, explicit permission grants, scope rules, and any protected-agent or protected-project policy attached to the target.

### Permission keys

The `permissionKey` field on a grant is one of:
```

Key	What it allows
`agents:create`	Hire or create new agents in the company. Also satisfies `agent_config:read` and `agent_config:update` checks.
`tasks:assign`	Assign any issue in the company to any active agent or human member.
`tasks:assign_scope`	Assign issues only when the scope matches the grant (see below). Requires a structured scope on the grant.
`tasks:manage_active_checkouts`	Force-release or otherwise manage a checkout owned by another agent.
`environments:manage`	Manage execution workspaces and environments.
`users:invite`	Invite new humans to the company.
`users:manage_permissions`	Edit roles and grants for other members.
`joins:approve`	Approve pending join requests.

The CEO agent role gets `canCreateAgents` by default. Other roles get an empty `permissions` block. Role-default human grants are applied automatically when a user joins — `owner` and `admin` receive almost all keys, `operator` gets `tasks:assign`, and `viewer` gets none.

Grant scope

A grant can either be company-wide (no scope) or scoped to a subset. The scope is a JSON object on the grant and the authorization service understands these keys:

- `projectId` or `projectIds` — restrict the grant to specific projects. The shorthand `project:<id>` inside an `allow` array also works.
- `agentId`, `agentIds`, `assigneeAgentId`, `assigneeAgentIds`, `targetAgentId`, `targetAgentIds` — restrict to specific assignees. Shorthand `agent:<id>` is accepted.
- `managerAgentId`, `subtreeRootAgentId`, and similar keys — restrict to a manager's reporting subtree. Shorthand `subtree:<id>` is accepted.

`tasks:assign_scope` always requires at least one structured constraint. A grant of `tasks:assign` with an empty scope is treated as company-wide.

The `access` block on an agent

`GET /api/agents/{agentId}` includes an `access` object that summarizes the agent's assignment authority:

Field	Meaning
`canAssignTasks`	Whether the agent can currently assign work in the company.

`taskAssignSource`	`ceo_role`, `agent_creator`, `explicit_grant`, `simple_default`, or `none`.
`membership`	The agent's `companyMembership` row, if any.
`grants`	All principal permission grants attached to the agent.

Use this block to render UI without having to replay the authorization rules yourself.

Protected agents, projects, and issues

Agents, projects, and issues can carry an `authorizationPolicy` block (inside `permissions`, `executionWorkspacePolicy`, or `executionPolicy`). The service understands three shapes:

- `agentVisibility.mode: "private"` — the target is hidden from the simple company-wide assignment default. Assigning to it requires an explicit grant.
- `assignmentPolicy.mode: "protected"` — assignment requires an explicit `tasks:assign` or matching `tasks:assign_scope` grant; the simple membership default is rejected.
- `protectedAgent.requiresApproval: true` (or `assignmentPolicy.protectedAgentRequiresApproval: true`) — assignment is blocked entirely until an approval flow is attached, regardless of grants.

When the service can't classify a policy object (unknown top-level keys or unsupported mode strings), it falls back to "unknown" and blocks the assignment with a `deny_policy_restricted` decision. Treat unrecognized policy data as a hard block.

Decision reasons

When an assignment is rejected, the server returns one of these reasons in the error payload. The list is also useful when you're debugging:

Reason	Meaning
`allow_local_board`	The local implicit board is always allowed.
`allow_instance_admin`	Instance admins bypass company-level checks.
`allow_explicit_grant`	A matching `principalPermissionGrants` row covered the action.
`allow_legacy_agent_creator`	The legacy `canCreateAgents` flag covered the action.
`allow_self`	An agent acting on its own assignment or its own config.
`allow_company_agent`	An agent acting on an issue with no agent assignee.
`allow_simple_company_member`	Simple-mode default — any active non-viewer can assign.
`allow_manager_chain`	Manager allowed because the target reports to them.
`deny_unauthenticated`	No actor or no agent id on the request.

`deny_company_boundary`	Cross-company access, or target agent not active in the company.
`deny_missing_membership`	Principal has no active company membership.
`deny_missing_grant`	No grant matched the requested permission key.
`deny_policy_restricted`	A protected agent, project, or issue blocked the action.
`deny_scope`	A grant exists but does not cover the requested project, assignee, or subtree.
`deny_unsupported_action`	No permission mapping exists for the action and actor.

Managing member roles and grants

`PATCH /api/companies/{companyId}/members/{memberId}/role-and-grants`

Use this route to change a human member's role and replace their grant set in one transaction. The caller needs the `users:manage_permissions` permission on the company.

Request body:

Field	Type	Notes
`membershipRole`	`owner`, `admin`, `member`, `viewer` (optional)	When omitted, the existing role is kept. The route refuses to demote the last active owner.
`status`	`active` or `inactive` (optional)	Defaults to the current status.
`grants`	array (optional)	Replaces the member's full grant set. Each entry is `{ permissionKey, scope? }`.

The route deletes the member's existing `principalPermissionGrants` rows before inserting the new ones, so always send the complete set you want — partial updates are not supported. Activity is logged as `company_member.updated`.

Pause, Resume, Terminate, Delete

These routes manage the agent lifecycle.

`POST /api/agents/{agentId}/pause`
`POST /api/agents/{agentId}/resume`
`POST /api/agents/{agentId}/terminate`
`DELETE /api/agents/{agentId}`

Use them like this:

- Pause when the agent should stop taking work temporarily.
- Resume when the agent should become available again.
- Terminate when the agent should never be invoked again, but you want to keep its record.
- Delete when you want a hard delete and cleanup of related runtime state, runs, sessions, wakeups, and key material.

Important edge cases:

- Pausing a terminated agent fails.
- Resuming a terminated agent fails.
- Resuming a pending approval agent fails.
- Terminating an agent revokes all of its API keys.
- Deleting an agent is destructive and removes a lot more than the agent row itself.

API Keys

Agents can have API keys for runtime access.

`GET /api/agents/{agentId}/keys`
`POST /api/agents/{agentId}/keys`
`DELETE /api/agents/{agentId}/keys/{keyId}`

Use keys when an agent or worker needs long-lived authentication that belongs to a specific agent.

Important edge cases:

- A key token is shown only once at create time.
- You cannot create keys for pending approval agents.
- You cannot create keys for terminated agents.
- Revoking a key marks it revoked; it is not hard-deleted.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
**curl -s -X POST **
** "http://localhost:3100/api/agents/{agentId}/keys" **
** -H "Authorization: Bearer <token>" **

```
  -H "Content-Type: application/json" \
  -d '{"name":"deploy-bot"}'
```
<!-- tab: JavaScript -->
```js
const res = await fetch(`http://localhost:3100/api/agents/${agentId}/keys`, {
  method: "POST",
  headers: {
    Authorization: `Bearer ${token}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({ name: "deploy-bot" }),
});

const key = await res.json();
```
<!-- tab: Python -->
```python
import requests

res = requests.post(
    f"http://localhost:3100/api/agents/{agentId}/keys",
    headers={
        "Authorization": f"Bearer {token}",
        "Content-Type": "application/json",
    },
    json={"name": "deploy-bot"},
)
key = res.json()
```
<!-- /tabs -->

Wake an Agent

Queues or coalesces a wakeup with context.

`POST /api/agents/{agentId}/wakeup`

Use this when you want to trigger work manually and include extra context such as an issue ID, reason, comment ID, or a payload object.

The request body supports:

- `source`: `timer`, `assignment`, `on_demand`, or `automation`
- `triggerDetail`: `manual`, `ping`, `callback`, or `system`
- `reason`
- `payload`
- `idempotencyKey`
- `forceFreshSession`

Important behavior:

- The route is company-scoped.
- Agent auth can only invoke the same agent.
- The endpoint returns `202 Accepted`.
- If the server skips the wakeup, it still returns `202` with a skipped payload.
- If an issue already has an active execution run, the wakeup may be deferred or coalesced instead of enqueued.
- If the agent is paused, terminated, or pending approval, the call fails with a conflict.
- Timer wakes can be disabled by heartbeat policy.
- Non-timer wakes can also be disabled by policy.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -s -X POST \
  "http://localhost:3100/api/agents/{agentId}/wakeup" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "source": "assignment",
    "triggerDetail": "manual",
    "reason": "Issue assigned",
    "payload": {
      "issueId": "issue-123",
      "commentId": "comment-456"
    },
    "idempotencyKey": "issue-123-assignment",
    "forceFreshSession": false
  }'
```
<!-- tab: JavaScript -->
```js
```

```
const res = await fetch(`http://localhost:3100/api/agents/${agentId}/wakeup`, {
  method: "POST",
  headers: {
    Authorization: `Bearer ${token}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    source: "assignment",
    triggerDetail: "manual",
    reason: "Issue assigned",
    payload: {
      issueId: "issue-123",
      commentId: "comment-456",
    },
    idempotencyKey: "issue-123-assignment",
    forceFreshSession: false,
  }),
});

const result = await res.json();
```
<!-- tab: Python -->
```python
import requests

res = requests.post(
    f"http://localhost:3100/api/agents/{agentId}/wakeup",
    headers={
        "Authorization": f"Bearer {token}",
        "Content-Type": "application/json",
    },
    json={
        "source": "assignment",
        "triggerDetail": "manual",
        "reason": "Issue assigned",
        "payload": {
            "issueId": "issue-123",
            "commentId": "comment-456",
        },
        "idempotencyKey": "issue-123-assignment",
        "forceFreshSession": False,
    },
)
result = res.json()
```

```
<!-- /tabs -->

### Common skipped responses

The exact skip reason depends on why the wakeup could not be queued. Common examples include:

- `wakeup_skipped`
- `issue_execution_deferred`
- `heartbeat.disabled`
- `heartbeat.wakeOnDemand.disabled`
- `budget.blocked`

---

## Invoke Heartbeat

Triggers a simple on-demand heartbeat.

`POST /api/agents/{agentId}/heartbeat/invoke`

Use this when you want a straightforward manual tick without the richer wakeup payload.

Behavior is similar to wakeup, but the response is simpler:

- `202 Accepted`
- either a run object, or `{ "status": "skipped" }`
- agent auth can only invoke itself

---

## Org Chart

Returns the company org structure.

`GET /api/companies/{companyId}/org`
`GET /api/companies/{companyId}/org.svg`
`GET /api/companies/{companyId}/org.png`

Use the JSON route when you want to build your own visualizations.
Use the SVG or PNG routes when you want the server to render the chart directly.

Notes:
```

- These routes omit terminated agents.
- `style` is optional for the SVG and PNG variants.

Adapter Helpers

These routes help you inspect and validate adapter environments.

`GET /api/companies/{companyId}/adapters/{type}/models`
`GET /api/companies/{companyId}/adapters/{type}/detect-model`
`POST /api/companies/{companyId}/adapters/{type}/test-environment`

Use them when you are choosing a model, auto-detecting a recommended model, or checking whether an adapter config is valid before you create or update an agent.

Important notes:

- The adapter type must be known to the server.
- The test-environment route uses the same company-level access gate as configuration reads.
- The server resolves secrets before running the test.

Skills

These routes inspect and sync the skills attached to an agent.

`GET /api/agents/{agentId}/skills`
`POST /api/agents/{agentId}/skills/sync`

Use them when the agent's adapter supports skill discovery and sync.

Sync request

Send the desired skill set as the request body. The server reconciles attachments to match — adding any skills missing on the agent and removing any that are no longer in the list.

Field	Required	Notes

| `desiredSkills` | yes | Array of references. Each entry is a company-skill UUID, canonical `key`, or unique slug. Mix and match is fine. |

The same field is accepted at hire time on `POST /api/companies/{companyId}/agents` and `POST /api/companies/{companyId}/agent-hires`, so the agent comes online with skills already assigned.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -s -X POST \
  "http://localhost:3100/api/agents/{agentId}/skills/sync" \
  -H "Authorization: Bearer $EKVAAR OS_API_KEY" \
  -H "Content-Type: application/json" \
  -d '{ "desiredSkills": ["EKVAAR OS", "improve-skill"] }'
```
<!-- tab: JavaScript -->
```js
await fetch(`http://localhost:3100/api/agents/${agentId}/skills/sync`, {
  method: "POST",
  headers: {
    Authorization: `Bearer ${token}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({ desiredSkills: ["EKVAAR OS", "improve-skill"] }),
});
```
<!-- tab: Python -->
```python
import os, requests
requests.post(
    f"http://localhost:3100/api/agents/{agent_id}/skills/sync",
    headers={"Authorization": f"Bearer {os.environ['EKVAAR OS_API_KEY']}",
             "Content-Type": "application/json"},
    json={"desiredSkills": ["EKVAAR OS", "improve-skill"]},
)
```
<!-- /tabs -->

Important notes:

- Some adapters do not implement skill sync yet.
- Unsupported adapters still return a useful snapshot with warnings.

- Sync requires update permission on the target agent.
- Skills must already be installed at the company level. The full company-skill lifecycle (file shape, import, scoping, versioning) is documented in the [Skills reference](../skills.md).

Configuration

These routes are for reading and managing agent configuration history.

`GET /api/agents/{agentId}/configuration`
`GET /api/agents/{agentId}/config-revisions`
`GET /api/agents/{agentId}/config-revisions/{revisionId}`
`POST /api/agents/{agentId}/config-revisions/{revisionId}/rollback`
`GET /api/companies/{companyId}/agent-configurations`

Use them when you need to:

- inspect the effective agent configuration
- audit prior config changes
- roll back to a previous revision
- review all company agent configs in one place

Important notes:

- Configuration reads require the same company-level access gate used by the route.
- Revisions redact secret-bearing fields before returning them.
- A rollback can fail if the target revision contains redacted secret values.

Instructions Bundle

These routes are for file-based instructions management:

`PATCH /api/agents/{agentId}/instructions-path`
`GET /api/agents/{agentId}/instructions-bundle`
`PATCH /api/agents/{agentId}/instructions-bundle`
`GET /api/agents/{agentId}/instructions-bundle/file`
`PUT /api/agents/{agentId}/instructions-bundle/file`
`DELETE /api/agents/{agentId}/instructions-bundle/file`

Use them when the agent's prompt instructions are stored as files instead of only inline config.

Notes:

- The target agent or an ancestor manager can manage the instructions path.
- The file-level routes require the caller to be allowed to read or manage the target agent's instructions.
- Relative instructions paths require `adapterConfig.cwd`.

Claude Login

`POST /api/agents/{agentId}/claude-login`

This is board-only and only works for `claude_local` agents.

Common Edge Cases

- Agent shortname lookup without company context returns `422 Unprocessable Entity`.
- A shortname collision returns `409 Conflict`.
- Updating `permissions` through the main update route returns `422`.
- Creating a key for a terminated or pending approval agent returns `409`.
- Pause and resume are not available for terminated agents.
- Wakeup can be skipped even when the request is accepted, especially when policy or execution state blocks it.

Notes

This page was rewritten to match the current agent routes, auth rules, lifecycle behavior, and docs-site markdown conventions.

Changed file:

- `docs/api/agents.md`

Issues

Issues are the core work objects in EKVAAR OS. They can be organized in a hierarchy, linked to blockers and approvals, checked out by agents, annotated with comments, and extended with keyed markdown documents and file attachments.

Use the company-scoped routes for collection operations, and the issue-scoped routes for everything that acts on a single issue. Most issue routes also accept a human-readable identifier like `PAP-39` as well as a UUID.

Overview

Issue APIs are company-aware. In practice that means:

- List and create operations are scoped to `/api/companies/{companyId}/issues`.
- Single-issue routes use `/api/issues/{issueId}`.
- Attachment uploads use `/api/companies/{companyId}/issues/{issueId}/attachments`.
- Attachment downloads use `/api/attachments/{attachmentId}/content`, which supports inline preview, forced download (`?download=1`), and HTTP Range requests.

On issue-scoped routes, `{issueId}` can be either:

- the UUID of the issue, or
- the human identifier, such as `PAP-39`

The server resolves the identifier before handling the request.

Mutating requests can also trigger activity logs, comment wakeups, mention wakeups, and blocker-resolution wakeups. When an issue is checked out by an agent, agent-authenticated updates and comments may require the current `X-EKVAAR OS-Run-Id` header so the server can verify run ownership.

List Issues

```
GET /api/companies/{companyId}/issues
```

Return all issues visible to a company, ordered by priority unless a search query is present.

Query Parameters

Param	Description
`status`	Filter by one status or a comma-separated list, such as `todo,in_progress`
`assigneeAgentId`	Filter by assigned agent
`participantAgentId`	Filter by issues the agent created, was assigned to, or commented on
`assigneeUserId`	Filter by assigned user
`touchedByUserId`	Filter by issues created, assigned, read, or commented on by that user
`inboxArchivedByUserId`	Filter by the user's inbox visibility state
`unreadForUserId`	Filter to issues with comments newer than the user's last touch
`projectId`	Filter by project
`executionWorkspaceId`	Filter by execution workspace
`parentId`	Filter by parent issue
`labelId`	Filter by label
`originKind`	Filter by origin kind, such as `manual` or `routine_execution`
`originId`	Filter by origin identifier
`includeRoutineExecutions`	Include routine execution issues. Default is `false`
`q`	Full-text search across title, identifier, description, and comments
`limit`	Positive integer result cap

Notes:

- `assigneeUserId=me`, `touchedByUserId=me`, `inboxArchivedByUserId=me`, and `unreadForUserId=me` only work with board authentication.
- `limit` must be a positive integer.
- Routine execution issues are excluded by default unless you opt in with `includeRoutineExecutions=true` or filter by `originKind`/`originId`.
- When `q` is present, results are ranked by the best match in title, identifier, description, or comments.

Example

```bash
curl -sS \
  -H "Authorization: Bearer {token}" \
  "https://EKVAAR
OS.example.com/api/companies/{companyId}/issues?status=todo,in_progress&projectId
={projectId}&limit=25"
```

Get Issue

```
GET /api/issues/{issueId}
```

Return the full issue record plus related objects that are useful for rendering the issue detail page.

The response includes the issue itself and these related fields:

- `project`
- `goal`
- `ancestors`
- `blockedBy`
- `blocks`
- `planDocument`
- `documentSummaries`
- `legacyPlanDocument`
- `mentionedProjects`
- `currentExecutionWorkspace`
- `workProducts`

Relationship Notes

- `goal` is resolved in order of precedence: the issue's own goal, the project's goal, then the company's default goal when no project is set.
- `ancestors` contains the parent chain for the issue.
- `blockedBy` and `blocks` come from issue relations of type `blocks`.
- `planDocument` is the keyed issue document with key `plan`, if it exists.
- `legacyPlanDocument` is a read-only fallback extracted from an old `<plan>...</plan>` block in the issue description.

Heartbeat Context

```
GET /api/issues/{issueId}/heartbeat-context
```

This route returns a compact payload for agent wakeup flows. It includes:

- a reduced issue summary
- ancestors
- project and goal summaries

- comment cursor metadata
- an optional `wakeComment`
- attachment summaries

Use this when an agent needs a smaller, execution-friendly context instead of the full issue detail payload.

Create Issue

```
POST /api/companies/{companyId}/issues
```

Create a new issue in a company. This endpoint accepts the full `createIssueSchema`, including the common task fields and the linking fields used by the rest of the issue system.

Notable inputs:

- `title` is required.
- `status` defaults to `backlog`.
- `priority` defaults to `medium`.
- `projectId`, `goalId`, and `parentId` establish the issue's placement.
- `blockedByIssueIds` links blockers.
- `labelIds` attaches labels.
- `executionPolicy`, `executionWorkspaceId`, `executionWorkspacePreference`, and `executionWorkspaceSettings` control execution behavior.
- `assigneeAgentId` and `assigneeUserId` are allowed, but the caller must have task assignment permission.
- `inheritExecutionWorkspaceFromIssueId` copies execution workspace settings from another issue.

If you include `assigneeAgentId` or `assigneeUserId`, the request is checked against task assignment permissions before the issue is created. The check runs through the central authorization service — see [Scoped Permissions and Authorization](./agents.md#scoped-permissions-and-authorization) for the full decision matrix, including the `deny_policy_restricted` reason that protected agents and projects raise.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -sS -X POST \
  -H "Authorization: Bearer {token}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR OS.example.com/api/companies/{companyId}/issues" \
  -d '{
    "title": "Implement caching layer",
    "description": "Add Redis caching for hot queries.",
    "status": "todo",
    "priority": "high",
    "projectId": "{projectId}",
    "goalId": "{goalId}",
    "parentId": "{parentIssueId}"
  }'
```

<!-- tab: JavaScript -->

```js
const response = await fetch(
  `https://EKVAAR OS.example.com/api/companies/${companyId}/issues`,
  {
    method: "POST",
    headers: {
      Authorization: `Bearer ${token}`,
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      title: "Implement caching layer",
      description: "Add Redis caching for hot queries.",
      status: "todo",
      priority: "high",
      projectId,
      goalId,
      parentId: parentIssueId,
    }),
  },
);
```

<!-- tab: Python -->

```python
```

```
import requests

response = requests.post(
    f"https://EKVAAR OS.example.com/api/companies/{company_id}/issues",
    headers={
        "Authorization": f"Bearer {token}",
        "Content-Type": "application/json",
    },
    json={
        "title": "Implement caching layer",
        "description": "Add Redis caching for hot queries.",
        "status": "todo",
        "priority": "high",
        "projectId": project_id,
        "goalId": goal_id,
        "parentId": parent_issue_id,
    },
)
```

<!-- /tabs -->

Update Issue

```
PATCH /api/issues/{issueId}
```

Update an issue and optionally add a comment in the same request.

This endpoint accepts the issue create fields as partial updates, plus:

- `comment`
- `reopen`
- `interrupt`
- `hiddenAt`

Behavior to know:

- If `comment` is present, the server adds a comment as part of the same update flow.
- If `reopen: true` is included with a comment and the issue is closed, the issue is moved back to `todo` unless you explicitly set another status.

- `interrupt` only works when a comment is also being added.
- Only board users can interrupt an active run from issue comments.
- Agent-authenticated updates to a checked-out `in_progress` issue must satisfy checkout ownership checks, including `X-EKVAAR OS-Run-Id`.
- `hiddenAt` hides or unhides the issue from list responses.

Blocking Links

If you update `blockedByIssueIds`, the server replaces the existing `blocks` relations for the issue and validates that:

- all referenced issues belong to the same company,
- the issue does not block itself, and
- the resulting graph does not contain cycles.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -sS -X PATCH \
  -H "Authorization: Bearer {token}" \
  -H "X-EKVAAR OS-Run-Id: {runId}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR OS.example.com/api/issues/{issueId}" \
  -d '{
    "status": "done",
    "comment": "Implemented caching and verified the hit rate.",
    "reopen": false
  }'
```

<!-- tab: JavaScript -->

```js
const response = await fetch(
  `https://EKVAAR OS.example.com/api/issues/${issueId}`,
  {
    method: "PATCH",
    headers: {
      Authorization: `Bearer ${token}`,
      "X-EKVAAR OS-Run-Id": runId,
```

```
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      status: "done",
      comment: "Implemented caching and verified the hit rate.",
      reopen: false,
    }),
  },
);
```

<!-- tab: Python -->

```python
import requests

response = requests.patch(
    f"https://EKVAAR OS.example.com/api/issues/{issue_id}",
    headers={
        "Authorization": f"Bearer {token}",
        "X-EKVAAR OS-Run-Id": run_id,
        "Content-Type": "application/json",
    },
    json={
        "status": "done",
        "comment": "Implemented caching and verified the hit rate.",
        "reopen": False,
    },
)
```

<!-- /tabs -->

Checkout a Task

```
POST /api/issues/{issueId}/checkout
```

Atomically claim an issue for an agent and transition it into `in_progress`.

Request body:

- `agentId` - the agent that will own the issue
- `expectedStatuses` - a non-empty list of statuses that are allowed at checkout time

Rules:

- An agent can only checkout as itself.
- Agent-authenticated checkout requests require `X-EKVAAR OS-Run-Id`.
- The issue must match one of the expected statuses, otherwise the server returns `409 Conflict`.
- If the project is paused, checkout is rejected with `409 Conflict`.
- If the issue's execution workspace is a closed isolated workspace, checkout is rejected with `409 Conflict`.
- If the same agent already owns the task, checkout is idempotent.
- If a previous checkout run crashed and is no longer active, the server can adopt the stale lock when the caller includes the prior checkout status in `expectedStatuses`.

The common reclaim pattern after a crash is to include `in_progress` in `expectedStatuses` and send the new run id in the `X-EKVAAR OS-Run-Id` header.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -sS -X POST \
  -H "Authorization: Bearer {token}" \
  -H "X-EKVAAR OS-Run-Id: {runId}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR OS.example.com/api/issues/{issueId}/checkout" \
  -d '{
    "agentId": "{agentId}",
    "expectedStatuses": ["todo", "backlog", "blocked", "in_review"]
  }'
```

<!-- tab: JavaScript -->

```js
const response = await fetch(
  `https://EKVAAR OS.example.com/api/issues/${issueId}/checkout`,
  {
    method: "POST",
    headers: {
```

```
      Authorization: `Bearer ${token}`,
      "X-EKVAAR OS-Run-Id": runId,
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      agentId,
      expectedStatuses: ["todo", "backlog", "blocked", "in_review"],
    }),
  },
);
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
    f"https://EKVAAR OS.example.com/api/issues/{issue_id}/checkout",
    headers={
        "Authorization": f"Bearer {token}",
        "X-EKVAAR OS-Run-Id": run_id,
        "Content-Type": "application/json",
    },
    json={
        "agentId": agent_id,
        "expectedStatuses": ["todo", "backlog", "blocked", "in_review"],
    },
)
```

<!-- /tabs -->

Reclaiming a stale checkout

If the previous run died while the issue was still `in_progress`, re-checkout can succeed when:

- the old run is finished, failed, cancelled, timed out, or missing,
- the issue is still assigned to the same agent, and
- the new request includes `in_progress` in `expectedStatuses`

That lets a fresh run adopt the stale checkout lock safely.

Release a Task

```
POST /api/issues/{issueId}/release
```

Release a checked-out issue and return it to `todo`.

Release semantics:

- The issue's `status` is set to `todo`.
- `assigneeAgentId` is cleared.
- `checkoutRunId` is cleared.
- `assigneeUserId` is preserved — release only unassigns the agent, not a paired user.
- Board users can release without matching checkout ownership.
- Agent-authenticated releases must come from the assignee's current checkout run.

If you need to give the issue back to the backlog instead of just releasing it, do that as a separate update.

Comments

List Comments

```
GET /api/issues/{issueId}/comments
```

List comments for an issue.

Query parameters:

- `after` or `afterCommentId` - anchor pagination after a specific comment
- `order` - `asc` or `desc`
- `limit` - positive integer, capped at 500

Get Comment

```
GET /api/issues/{issueId}/comments/{commentId}
```

```

Fetch a single comment by id.

### Add Comment

```
POST /api/issues/{issueId}/comments
```

Add a new comment to an issue.

Request body:

- `body` - markdown comment text
- `reopen` - reopen a closed issue back to `todo` before adding the comment
- `interrupt` - cancel the active run for the issue, if one exists

Behavior to know:

- `interrupt` only works for board users.
- `reopen` only has an effect when the issue is `done` or `cancelled`.
- `@mentions` in the comment body trigger wakeups for matching agents.
- Comments are accepted on open and closed issues.

### Comment style

Comments are the primary communication channel between agents. Every status update, finding, question, and handoff happens through comments. Use concise markdown with:

- A short status line.
- Bullets for what changed or what is blocked.
- Links to related entities when available.

```markdown
## Update

Submitted CTO hire request and linked it for board review.

- Approval: [ca6ba09d](/approvals/ca6ba09d-b558-4a53-a552-e7ef87e54a1b)
- Pending agent: [CTO draft](/agents/66b3c071-6cb8-4424-b833-9d9b6318de0b)
- Source issue: [PC-142](/issues/244c0c2c-8416-43b6-84c9-ec183c074cc1)
```
```

@-mentions

Mention another agent by name with `@AgentName` to wake them:

```
POST /api/issues/{issueId}/comments
{ "body": "@EngineeringLead I need a review on this implementation." }
```

The name must match the agent's `name` field exactly (case-insensitive). Mentions also work inside the `comment` field of `PATCH /api/issues/{issueId}`.

Mention rules:

- **Don't overuse mentions** — each mention triggers a budget-consuming heartbeat.
- **Don't use mentions for assignment** — create or assign a task instead.
- **Mention-handoff exception** — if an agent is explicitly @-mentioned with a clear directive to take a task, they may self-assign via checkout.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -sS -X POST \
  -H "Authorization: Bearer {token}" \
  -H "X-EKVAAR OS-Run-Id: {runId}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR OS.example.com/api/issues/{issueId}/comments" \
  -d '{
    "body": "Progress update: cache layer is implemented.",
    "reopen": false
  }'
```

<!-- tab: JavaScript -->

```js
const response = await fetch(
  `https://EKVAAR OS.example.com/api/issues/${issueId}/comments`,
  {
    method: "POST",
```

```
    headers: {
      Authorization: `Bearer ${token}`,
      "X-EKVAAR OS-Run-Id": runId,
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      body: "Progress update: cache layer is implemented.",
      reopen: false,
    }),
  },
);
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
    f"https://EKVAAR OS.example.com/api/issues/{issue_id}/comments",
    headers={
        "Authorization": f"Bearer {token}",
        "X-EKVAAR OS-Run-Id": run_id,
        "Content-Type": "application/json",
    },
    json={
        "body": "Progress update: cache layer is implemented.",
        "reopen": False,
    },
)
```

<!-- /tabs -->

Documents

Issue documents are revisioned markdown artifacts keyed by a stable name such as `plan`, `design`, or `notes`.

Document keys must be lowercase and may contain numbers, `_`, and `-`. The current document format is `markdown`.

The issue detail response also exposes document data directly:

- `planDocument`
- `documentSummaries`
- `legacyPlanDocument`

List Documents

```
GET /api/issues/{issueId}/documents
```

Return all issue documents with their latest body.

Get Document By Key

```
GET /api/issues/{issueId}/documents/{key}
```

Return a single document by key.

Create Or Update Document

```
PUT /api/issues/{issueId}/documents/{key}
```

Create a new document or append a new revision to an existing one.

Request body:

- `title` - optional document title
- `format` - currently only `markdown`
- `body` - markdown content, up to 512 KiB
- `changeSummary` - optional change note for the revision history
- `baseRevisionId` - required when updating an existing document

Concurrency rules:

- Omit `baseRevisionId` when creating a new document.
- Include the current latest `baseRevisionId` when updating.
- A stale `baseRevisionId` returns `409 Conflict` with the current revision id.
- If the key already exists and `baseRevisionId` is omitted, the server rejects the update.

Writing to a locked document

If the target document is locked, the behavior depends on who is writing:

- **User callers** receive `409 Conflict` with `{ "error": "Document is locked", "key": "...", "lockedAt": "..." }`.
- **Agent callers** are routed to a derived document instead. The server creates a new document at a related key (for example `plan-2` if `plan` is taken), applies the write there, and returns the response with a `redirectedFromLockedDocument` field describing the source key and the new key. This keeps the approved snapshot intact while letting the agent continue its work.

Delete also refuses to operate on a locked document and returns `409 Conflict`.

Lock A Document

```
POST /api/issues/{issueId}/documents/{key}/lock
```

Lock an existing document. Subsequent writes from agents are redirected to a new derived document; user writes get a `409 Conflict`. The response includes the updated `lockedAt`, `lockedByAgentId`, and `lockedByUserId` fields.

Locking emits an `issue.document_locked` activity entry.

Unlock A Document

```
POST /api/issues/{issueId}/documents/{key}/unlock
```

Clear the lock. Writes resume normally and an `issue.document_unlocked` activity entry is recorded.

Revision History

```
GET /api/issues/{issueId}/documents/{key}/revisions
```

Return the revision history for a document, newest first.

Restore A Revision

```
POST /api/issues/{issueId}/documents/{key}/revisions/{revisionId}/restore
```

Restore a prior revision by creating a new latest revision from it.

This does not overwrite history. It creates a new revision that becomes the latest body.

Delete Document

```
DELETE /api/issues/{issueId}/documents/{key}
```

Delete a document and all of its revisions.

Delete is board-only in the current implementation.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -sS -X PUT \
  -H "Authorization: Bearer {token}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR OS.example.com/api/issues/{issueId}/documents/plan" \
  -d '{
    "title": "Implementation plan",
    "format": "markdown",
    "body": "# Plan\n\n1. Build the cache layer\n2. Verify the hit rate\n3. Roll out to
production",
    "baseRevisionId": "{latestRevisionId}"
  }'
```

<!-- tab: JavaScript -->

```js
const response = await fetch(
```

```
  `https://EKVAAR OS.example.com/api/issues/${issueId}/documents/plan`,
  {
    method: "PUT",
    headers: {
      Authorization: `Bearer ${token}`,
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      title: "Implementation plan",
      format: "markdown",
      body: "# Plan\n\n1. Build the cache layer\n2. Verify the hit rate\n3. Roll out to
production",
      baseRevisionId: latestRevisionId,
    }),
  },
);
```

<!-- tab: Python -->

```python
import requests

response = requests.put(
    f"https://EKVAAR OS.example.com/api/issues/{issue_id}/documents/plan",
    headers={
        "Authorization": f"Bearer {token}",
        "Content-Type": "application/json",
    },
    json={
        "title": "Implementation plan",
        "format": "markdown",
        "body": "# Plan\n\n1. Build the cache layer\n2. Verify the hit rate\n3. Roll out to
production",
        "baseRevisionId": latest_revision_id,
    },
)
```

<!-- /tabs -->

Document Annotations

Annotations let you attach comment threads to a specific passage of an issue document — the same way you'd leave a margin note on a shared doc. Each thread is anchored to a selected range of text, carries one or more comments, and can be resolved once the conversation is settled. Both users and agents can create and reply to annotation threads.

Annotations live under a single document, addressed by the issue id and the document key.

Anchors and revisions

A thread is pinned to the document text it was created against, using a combination of the quoted text (with surrounding context) and its character positions. Because of this, creating a thread requires you to send the document's current revision — if the document has moved on, the server rejects the request so the anchor can't land in the wrong place.

When a document is later edited, the server re-anchors each open thread against the new revision and records how confidently it could do so. A thread can end up in one of these anchor states:

- `active` — the anchored passage was found cleanly in the new revision.
- `shifted` — the passage moved but was relocated with reasonable confidence.
- `orphaned` — the anchored text no longer exists, so the thread floats free of any passage.

List Threads

```
GET /api/issues/{issueId}/documents/{key}/annotations
```

Return the annotation threads on a document, newest activity first.

Query parameters:

- `status` — `open`, `resolved`, or `all`. Defaults to all.
- `includeComments` — when `true`, each thread embeds its full comment list. Otherwise only the thread records are returned.

The document detail route also folds annotations in directly. `GET /api/issues/{issueId}/documents/{key}` accepts `includeAnnotations` and `includeAnnotationComments` query flags and returns the matching threads on an

`annotations` field. Agent callers receive annotations by default; pass `includeAnnotations=false` to opt out.

Get a Thread

```
GET /api/issues/{issueId}/documents/{key}/annotations/{threadId}
```

Return a single thread with all of its comments. Responds `404` if the thread doesn't belong to that issue document.

Create a Thread

```
POST /api/issues/{issueId}/documents/{key}/annotations
```

Open a new thread anchored to a passage, with its first comment in the same request.

Request body:

Field	Type	Notes
`baseRevisionId`	uuid, required	The document revision the anchor was computed against. Must match the current latest revision.
`baseRevisionNumber`	integer, required	The matching revision number.
`selector`	object, required	The anchor — a `quote` selector (`exact`, plus `prefix`/`suffix` context) and a `position` selector (`normalizedStart`/`normalizedEnd` and `markdownStart`/`markdownEnd`).
`body`	string, required	The first comment's markdown text, 1–20,000 characters.

Concurrency rules:

- A stale `baseRevisionId`/`baseRevisionNumber` returns `409 Conflict` with the current revision so you can re-anchor and retry.
- If the selector can't be matched against the current document text, the server returns `422 Unprocessable Entity`.

A successful create returns the thread with its first comment, records an `issue.document_annotation_thread_created` activity entry, and wakes the issue assignee.

Reply to a Thread

```
POST /api/issues/{issueId}/documents/{key}/annotations/{threadId}/comments
```

Add a comment to an existing thread.

Request body:

- `body` — markdown comment text, 1–20,000 characters.

Adding a comment bumps the thread's activity timestamp, records an `issue.document_annotation_comment_added` entry, and wakes the assignee.

Resolve or Reopen a Thread

```
PATCH /api/issues/{issueId}/documents/{key}/annotations/{threadId}
```

Change a thread's status.

Request body:

- `status` — `resolved` to close the conversation, or `open` to reopen it.

Resolving stamps the thread with who resolved it and when, and logs `issue.document_annotation_thread_resolved`; reopening clears those fields and logs `issue.document_annotation_thread_reopened`. Sending the status the thread already has is a no-op.

Attachments

Attachments are file uploads linked to an issue, and optionally to a specific issue comment.

List Attachments

```
GET /api/issues/{issueId}/attachments
```

Return all attachments for an issue. Each item carries three path fields pointing at the binary content route:

- `contentPath` — `/api/attachments/{attachmentId}/content`. The raw content route.
- `openPath` — same value as `contentPath`. Use it to open or preview the attachment inline.
- `downloadPath` — `/api/attachments/{attachmentId}/content?download=1`. Use it to force a download.

Upload Attachment

```
POST /api/companies/{companyId}/issues/{issueId}/attachments
```

Upload a single file with `multipart/form-data`.

Request fields:

- `file` - the file payload
- `issueCommentId` - optional metadata field that links the attachment to a comment

Upload rules:

- Only one file is accepted.
- Empty files are rejected.
- Files larger than the server limit are rejected.
- `issueCommentId` must belong to the same company and issue.
- The content type must be in the allowed-uploads set.
- The stored response includes `contentPath`, `openPath`, and `downloadPath`.

The default allowed upload types are images, PDF, plain text, JSON, CSV, HTML, `application/zip`, and the video types `video/mp4`, `video/webm`, and `video/quicktime`. Video types are also treated as inline-renderable. Override the allowlist with the `EKVAAR OS_ALLOWED_ATTACHMENT_TYPES` environment variable — a comma-separated list of MIME types or wildcard patterns.

When a file is uploaded with a generic content type (`application/octet-stream`, `binary/octet-stream`, or `application/x-binary`), the server infers a video content type from the filename extension when streaming it back: `.mp4`/`.m4v` → `video/mp4`, `.webm` → `video/webm`, and `.mov`/`.qt`/`.quicktime` → `video/quicktime`.

Download Attachment Content

```
GET /api/attachments/{attachmentId}/content
```

Stream the attachment bytes.

By default the server sets `Content-Disposition` for inline display when the content type is inline-capable (images, PDF, video, and similar), and otherwise serves it as a download. SVG content gets a sandboxed content security policy.

Query parameters:

- `download=1` — force `Content-Disposition: attachment` so the response is always saved as a download instead of rendered inline.

This route supports HTTP Range requests so large media such as video can stream and seek:

- The response sets `Accept-Ranges: bytes`.
- A valid `Range: bytes=...` request returns `206 Partial Content` with a `Content-Range` header.
- An unsatisfiable range returns `416 Range Not Satisfiable` with `Content-Range: bytes */{length}`.

Delete Attachment

```
DELETE /api/attachments/{attachmentId}
```

Delete the attachment record and the stored object.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -sS -X POST \
  -H "Authorization: Bearer {token}" \
  -F "file=@./diagram.png" \
  -F "issueCommentId={commentId}" \
```

```
  "https://EKVAAR
OS.example.com/api/companies/{companyId}/issues/{issueId}/attachments"
```

<!-- tab: JavaScript -->

```js
const formData = new FormData();
formData.append("file", fileInput.files[0]);
formData.append("issueCommentId", commentId);

const response = await fetch(
  `https://EKVAAR
OS.example.com/api/companies/${companyId}/issues/${issueId}/attachments`,
  {
    method: "POST",
    headers: {
      Authorization: `Bearer ${token}`,
    },
    body: formData,
  },
);
```

<!-- tab: Python -->

```python
import requests

with open("diagram.png", "rb") as f:
    response = requests.post(
        f"https://EKVAAR
OS.example.com/api/companies/{company_id}/issues/{issue_id}/attachments",
        headers={
            "Authorization": f"Bearer {token}",
        },
        files={"file": f},
        data={"issueCommentId": comment_id},
    )
```

<!-- /tabs -->

Linked Approvals

Issues can be linked to approval records. These links are separate from task comments and task status.

List Linked Approvals

```
GET /api/issues/{issueId}/approvals
```

Return the approvals currently linked to the issue.

Link An Approval

```
POST /api/issues/{issueId}/approvals
```

Request body:

- `approvalId` - the approval to link

Permissions:

- Board users can always manage approval links when they have company access.
- Agents can manage approval links only if they are CEO or have `canCreateAgents`.

The response returns the updated approval list.

Unlink An Approval

```
DELETE /api/issues/{issueId}/approvals/{approvalId}
```

Remove the approval link from the issue.

The same permissions apply as for linking.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -sS -X POST \
  -H "Authorization: Bearer {token}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR OS.example.com/api/issues/{issueId}/approvals" \
  -d '{
    "approvalId": "{approvalId}"
  }'
```

<!-- tab: JavaScript -->

```js
const response = await fetch(
  `https://EKVAAR OS.example.com/api/issues/${issueId}/approvals`,
  {
    method: "POST",
    headers: {
      Authorization: `Bearer ${token}`,
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      approvalId,
    }),
  },
);
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
    f"https://EKVAAR OS.example.com/api/issues/{issue_id}/approvals",
    headers={
        "Authorization": f"Bearer {token}",
        "Content-Type": "application/json",
    },
    json={
        "approvalId": approval_id,
```

```
  },
)
```

<!-- /tabs -->

Interactions

Interactions are structured prompts an agent attaches to an issue when it needs an authoritative response — a list of suggested next tasks the board should pick from, a set of structured questions, or a confirmation request before acting.

Use them when a free-text comment is not enough because the response shape matters (a yes/no, a choice, or a structured payload), or when the agent should pause and only resume after an explicit decision.

List Interactions

```
GET /api/issues/{issueId}/interactions
```

Returns the interactions on an issue, newest first.

Create Interaction

```
POST /api/issues/{issueId}/interactions
```

Request body fields:

- `kind` — one of `suggest_tasks`, `ask_user_questions`, `request_confirmation`.
- `payload` — interaction-specific structured data (the list of suggested tasks, the questions, or the confirmation summary).
- `idempotencyKey` — optional. Recommended for `request_confirmation` interactions tied to a plan revision (e.g. `confirmation:{issueId}:plan:{revisionId}`) so re-sends do not double-create.
- `continuationPolicy` — `wake_assignee` to resume the assignee after a response is recorded; `wake_requester` to wake the original requester. For `request_confirmation`, the `wake_assignee` policy resumes only after an `accept`.

Permissions:

- Agents can create interactions on issues they are assigned to or have commented on.
- Board users can create interactions on any issue in their company.

Respond, Accept, Reject

```
POST /api/issues/{issueId}/interactions/{interactionId}/accept
POST /api/issues/{issueId}/interactions/{interactionId}/reject
POST /api/issues/{issueId}/interactions/{interactionId}/respond
```

`accept` and `reject` are used for `request_confirmation`. `respond` carries the structured response body for `suggest_tasks` (the chosen subset) or `ask_user_questions` (the answers).

After a terminal action, the interaction is sealed — further responses are rejected.

Choosing the kind

| Kind | When to use |
|---|---|
| `suggest_tasks` | The agent has identified work it could do next and wants the board (or user) to choose which to spin up as subtasks. |
| `ask_user_questions` | The agent needs structured information (multiple choice, short text) it cannot extract from the comment thread. |
| `request_confirmation` | The agent has a proposal — typically a plan revision or a destructive action — and needs explicit acceptance before proceeding. |

For plan-approval flows, the recommended sequence is: update the `plan` document → create a `request_confirmation` interaction with an `idempotencyKey` bound to the latest plan revision → wait for `accept`. The agent only spawns implementation subtasks once the interaction is accepted.

Retry a Scheduled Retry Now

`POST /api/issues/{issueId}/scheduled-retry/retry-now`

Use this when an issue has a live scheduled retry pending and you want the server to fire it immediately instead of waiting for the schedule. The route is board-only and company-scoped to the issue.

The request body is empty. The response always includes `outcome`, `message`, and a `scheduledRetry` summary (or `null` when there was nothing to promote).

Outcome	Meaning
`promoted`	The scheduled retry was moved into the queued run pool and will pick up on the next heartbeat.
`already_promoted`	A queued or running retry already exists for the issue; nothing else to do.
`no_scheduled_retry`	No live scheduled retry exists — the affordance is a no-op.
`gate_suppressed`	The promotion was blocked by a heartbeat gate (e.g. concurrency or budget); the run stays scheduled.

Activity is logged as `issue.scheduled_retry_retry_now` with the outcome attached, so you can find it in the audit trail when an operator clicks "Retry now" from the UI.

Recovery actions

Recovery actions are first-class records attached to a source issue when the system detects that the issue is stuck, stranded, or otherwise off the happy path. They carry an owner, structured evidence, a wake/monitor policy, and a resolution outcome — so the next-step decision lives on the issue itself instead of in scattered comments.

Records live in the `issue_recovery_actions` table (migration `0084`). The issue detail and issue list responses expose the currently active recovery action on each issue as `activeRecoveryAction`, including on `blockedBy` / `blocks` relation summaries.

List recovery actions for an issue

```
GET /api/issues/{issueId}/recovery-actions
```

Returns the active recovery action attached to the issue, if any.

Response:

```json
{
  "active": { "...": "RecoveryAction" } ,
  "actions": [ { "...": "RecoveryAction" } ]
```

}
```

`active` is `null` when no recovery action is currently open. `actions` is an array containing the active action (or empty) — it exists so future revisions can include historical entries without changing the shape.

Resolve the active recovery action

```
POST /api/issues/{issueId}/recovery-actions/resolve
```

Resolve (or cancel) the active recovery action on the source issue and, in the same transaction, transition the source issue to the matching status.

Request body:

| Field | Type | Notes |
|---|---|---|
| `actionId` | uuid, optional | Optional. When set, must match the currently active recovery action on the issue. |
| `outcome` | enum, required | One of `restored`, `false_positive`, `blocked`, `cancelled`. See the outcome table below. |
| `sourceIssueStatus` | enum, required | One of `done`, `in_review`, `blocked`. Must be compatible with `outcome` (see rules). |
| `resolutionNote` | string, optional | Multi-line note explaining the resolution. |

Outcome rules (enforced by the validator):

| Outcome | Allowed `sourceIssueStatus` | Permission | Resulting action `status` |
|---|---|---|---|
| `restored` | `done` or `in_review` | Agent or board | `resolved` |
| `false_positive` | `done` or `in_review` | Board only | `resolved` |
| `blocked` | `blocked` | Agent or board | `resolved` |
| `cancelled` | `done` or `in_review` | Board only | `cancelled` |

Additional constraints:

- `outcome: "blocked"` requires the source issue to have at least one unresolved first-class blocker via `blockedByIssueIds` — otherwise the server returns `422 Unprocessable Entity`.

- If the source issue is currently `in_review` under an execution policy, agent-authenticated resolutions must satisfy the same review-path checks as a normal status change.
- The server writes an `issue.recovery_action_resolved` activity log entry (and an `issue.updated` entry when the source status actually changed).

Response:

```json
{
  "issue": { "...": "Issue", "activeRecoveryAction": null },
  "recoveryAction": { "...": "RecoveryAction" }
}
```

Recovery action shape

The `RecoveryAction` object exposed on responses has the following fields:

Field	Type	Notes
`id`	uuid	
`companyId`	uuid	
`sourceIssueId`	uuid	The issue the recovery action is attached to.
`recoveryIssueId`	uuid | null	Optional companion issue spawned to drive the recovery.
`kind`	enum	See `RecoveryActionKind` below.
`status`	enum	`active`, `escalated`, `resolved`, or `cancelled`.
`ownerType`	enum	`agent`, `user`, `board`, or `system`.
`ownerAgentId`	uuid | null	Owning agent when `ownerType = "agent"`.
`ownerUserId`	string | null	Owning user when `ownerType = "user"`.
`previousOwnerAgentId`	uuid | null	The agent that held the issue before recovery started.
`returnOwnerAgentId`	uuid | null	The agent the issue should return to after recovery.
`cause`	string	Short machine-readable cause tag.
`fingerprint`	string	Stable fingerprint used to dedupe repeated detections.
`evidence`	object	Free-form JSON capturing the detector's evidence.
`nextAction`	string	The next action the owner is expected to take.
`wakePolicy`	object | null	Wake configuration for the owner.
`monitorPolicy`	object | null	Monitor configuration that produced the action.
`attemptCount`	integer	Number of recovery attempts so far.
`maxAttempts`	integer | null	Optional cap on attempts before escalation.
`timeoutAt`	timestamp | null	When the action times out if unresolved.
`lastAttemptAt`	timestamp | null	Timestamp of the most recent attempt.

`outcome`	enum | null	Final outcome — see `RecoveryActionOutcome` below.
`resolutionNote`	string | null	Free-text resolution note.
`resolvedAt`	timestamp | null	When the action was resolved or cancelled.
`createdAt`	timestamp	
`updatedAt`	timestamp	

Only one recovery action can be `active` or `escalated` per source issue at a time (enforced by a partial unique index on `(companyId, sourceIssueId)` where `status in ('active', 'escalated')`).

Enum values

`RecoveryActionKind` — what triggered the recovery action:

- `missing_disposition`
- `stranded_assigned_issue`
- `active_run_watchdog`
- `issue_graph_liveness`

`RecoveryActionStatus`:

- `active`
- `escalated`
- `resolved`
- `cancelled`

`RecoveryActionOwnerType`:

- `agent`
- `user`
- `board`
- `system`

`RecoveryActionOutcome` — set on the resolved record:

- `restored` — the source issue was put back on a healthy path.
- `delegated` — ownership moved elsewhere (set internally; not accepted on `/resolve`).
- `false_positive` — the detector was wrong; no real problem.
- `blocked` — the issue is genuinely blocked by another issue.
- `escalated` — escalated to the board (set internally; not accepted on `/resolve`).
- `cancelled` — the recovery effort is abandoned.


The `/recovery-actions/resolve` endpoint only accepts `restored`, `false_positive`, `blocked`, and `cancelled`. The `delegated` and `escalated` outcomes are produced by other internal flows.

Issue Lifecycle


Status values

Status	Meaning	Terminal?
`backlog`	Parked, unscheduled. Not picked up by inbox queries by default.	No
`todo`	Ready and actionable. Waiting for an agent to check it out.	No
`in_progress`	Checked out by an agent and actively executing. Exclusive — only one agent at a time.	No
`in_review`	Paused pending reviewer, approver, board, or user feedback. The work is paused, not done.	No
`blocked`	Cannot proceed until a named blocker is resolved. Always paired with a blocker explanation or `blockedByIssueIds`.	No
`done`	Work complete.	Yes
`cancelled`	Intentionally abandoned.	Yes

State machine

```


```




```

<details>
<summary>Same diagram in Mermaid (for renderers that support it)</summary>

```mermaid
stateDiagram-v2
   [*] --> backlog
   backlog --> todo: ready
   todo --> in_progress: checkout
   in_progress --> in_review: submit
   in_progress --> done: complete
   in_progress --> blocked: blocker
   in_progress --> todo: release
   in_review --> in_progress: changes requested
   in_review --> done: approve
   blocked --> todo: unblock / release
   todo --> cancelled
   in_progress --> cancelled
   in_review --> cancelled
   blocked --> cancelled
   done --> todo: reopen
   cancelled --> todo: reopen
   done --> [*]
   cancelled --> [*]
```

</details>

Allowed transitions

From	To	Triggered by
```

`backlog`	`todo`	Manual scheduling, ready-for-work signal.
`todo`	`in_progress`	`POST /api/issues/{id}/checkout` (atomic).
`in_progress`	`in_review`	`PATCH` with `status: "in_review"`. Used when the work needs reviewer/approver/board sign-off before being considered done.
`in_progress`	`done`	`PATCH` with `status: "done"`. Sets `completedAt`.
`in_progress`	`blocked`	`PATCH` with `status: "blocked"` and a comment naming the unblock owner and action, or `blockedByIssueIds` populated with concrete blockers.
`in_review`	`in_progress`	Reviewer requested changes (PATCH `status: "in_progress"`). The next execution-policy stage participant becomes the assignee.
`in_review`	`done`	Reviewer/approver advanced the issue (PATCH `status: "done"` from the current stage participant).
`blocked`	`todo`	Blocker resolved (manually, via `release`, or automatically by `issue_blockers_resolved` wake when all `blockedBy` issues reach `done`).
any non-terminal	`cancelled`	`PATCH` with `status: "cancelled"`. Sets `cancelledAt`.
`done` / `cancelled`	`todo`	`PATCH` with `reopen: true`. The only way to bring a terminal issue back.

Automatic side effects

When the server transitions an issue, it also:

Transition	Side effect
`→ in_progress`	Sets `startedAt`. Records the `checkoutRunId` for ownership.
`→ done`	Sets `completedAt`. Wakes any issues whose `blockedByIssueIds` are now fully resolved (`issue_blockers_resolved`). Wakes the parent if all children are now terminal (`issue_children_completed`).
`→ cancelled`	Sets `cancelledAt`. Cancelled issues do **not** count as resolved blockers — replace or remove them explicitly to unblock dependents.
`→ blocked`	Records the unresolved blocker count. Does not auto-resolve when the parent is closed.
`release`	Clears `assigneeAgentId` and `checkoutRunId`, sets status to `todo`. `assigneeUserId` is preserved.
`reopen: true`	If the issue is `done` or `cancelled`, resets to `todo` (or another status if explicitly provided).

Review stages and `executionState`

When an issue moves to `in_review` under an execution policy, the server also populates the `executionState` field with the current review or approval stage. That object captures `currentStageType`, `currentParticipant`, `returnAssignee`, and `lastDecisionOutcome`. Only the current stage participant can advance or reject the stage — other actors get `422`.

For full mechanics see the [Execution Policy guide](../../guides/power/execution-policy.md).

Blockers (`blockedByIssueIds`)

Express "A is blocked by B" as a first-class link, not as free-text:

- Send `blockedByIssueIds` on `POST /api/companies/{companyId}/issues` or `PATCH /api/issues/{issueId}` to declare blockers. The array replaces the current set on each update; send `[]` to clear.
- The server validates that all referenced issues belong to the same company, the issue does not block itself, and the resulting graph has no cycles.
- When every blocker reaches `done`, dependent issues get an `issue_blockers_resolved` wake.

Hidden issues

`hiddenAt` removes an issue from normal list responses without changing its status. Use it to declutter — the issue keeps its history and remains queryable by id. Set or clear `hiddenAt` via `PATCH /api/issues/{issueId}`.

Common mistakes

| Mistake | What goes wrong | Do this instead |
|---|---|---|
| `PATCH status: "in_progress"` to claim a task | Skips checkout, leaves `checkoutRunId` empty, race-prone. | Always claim work via `POST /api/issues/{id}/checkout` with `expectedStatuses` and the `X-EKVAAR OS-Run-Id` header. |
| Retrying a `409 Conflict` from checkout | The issue is owned by another agent or run. Retrying steals or thrashes the lock. | Treat 409 as terminal — pick a different issue. Only re-checkout when adopting a stale lock from a crashed run, with `in_progress` in `expectedStatuses`. |
| Free-text "blocked by PAP-XYZ" comment | Dependent never auto-wakes when the blocker resolves. | Set `blockedByIssueIds` on create or PATCH. The server fires `issue_blockers_resolved` automatically. |
| Cancelling a blocker and expecting auto-unblock | `cancelled` blockers do not count as resolved. Dependents stay blocked. | Replace or remove the cancelled id from `blockedByIssueIds` explicitly. |
| Approving an `in_review` issue you are not the current participant for | Server returns `422`. | Inspect `executionState.currentParticipant` first; only the named participant can advance the stage. |
| Reopening with `PATCH status: "todo"` on a `done` issue | Rejected — terminal status transitions require `reopen`. | Send `PATCH { reopen: true, comment: "…" }`. Use a different status only if you need to override the default `todo`. |

| Forgetting `X-EKVAAR OS-Run-Id` on agent updates | Server rejects the mutation as a checkout-ownership violation. | Always pass the current heartbeat run id on agent-authenticated `PATCH`/`POST` requests against checked-out issues. |
Approvals

Approvals are the board-review layer for decisions that should not happen automatically. In practice, they are used for hires, CEO strategy approval, budget overrides, and other company actions that need a human decision.

Use this API when you want to list approvals, inspect their linked issues, add review comments, or move an approval through its lifecycle.

Approval Types

The API accepts these approval types:

Type	What it means
`hire_agent`	A new agent hire or pending agent activation needs board review.
`approve_ceo_strategy`	The CEO has proposed a strategy and needs approval before executing it.
`budget_override_required`	A budget action needs board intervention.
`request_board_approval`	A general request for board review from an agent or workflow.

List Approvals

```http
GET /api/companies/{companyId}/approvals
```

Query parameters:

Param	Description
`status`	Optional status filter such as `pending`, `revision_requested`, `approved`, or `rejected`.

This endpoint returns company-scoped approvals only. The response payload is redacted before it is returned, so sensitive values inside approval payloads may be hidden.

Get Approval

```http
GET /api/approvals/{approvalId}
```

Returns one approval record, including:

Field	Notes
`type`	The approval type.
`status`	Current lifecycle state.
`payload`	The approval body, with sensitive values redacted when needed.
`requestedByAgentId`	The requesting agent, if one created it.
`requestedByUserId`	The requesting board user, if one created it.
`decisionNote`	The board note attached to the latest decision.
`decidedByUserId`	Who made the latest decision.
`decidedAt`	When the latest decision happened.

If the approval does not exist, or exists outside your company, the API returns `404`.

Create Approval

```http
POST /api/companies/{companyId}/approvals
Content-Type: application/json
```

Body:

Field	Required	Notes
`type`	Yes	One of the approval types above.
`payload`	Yes	Free-form JSON payload for the approval.
`requestedByAgentId`	No	Usually filled in automatically when an agent creates the approval.

| `issueIds` | No | Optional issue links to attach to the approval. Duplicate IDs are ignored. |

The server automatically sets the company, the requestor, and the initial `pending` status. If the caller is an agent and does not provide `requestedByAgentId`, the API uses that agent automatically.

If you pass `issueIds`, the approval is linked to those issues immediately. The linked issues must belong to the same company.

Payload shape per type

The `payload` field is type-specific. The recommended shapes are:

`request_board_approval` — agent asks the board to sign off on a proposed action. Use this when an agent has hit a decision point that requires explicit human approval (a one-off spend, a significant scope change, a hire that needs board sign-off beyond `hire_agent`).

Field	Notes
`title`	One-line headline shown in the board's approval queue.
`summary`	One short paragraph explaining the proposed action and context.
`recommendedAction`	One sentence stating exactly what should happen if approved.
`risks`	Array of strings naming the most material risks. Keep it tight.

When the approval resolves, the requesting agent is woken with `EKVAAR OS_APPROVAL_ID` and `EKVAAR OS_APPROVAL_STATUS` so it can react in its next heartbeat.

```json
{
  "type": "request_board_approval",
  "requestedByAgentId": "{agentId}",
  "issueIds": ["{issueId}"],
  "payload": {
    "title": "Approve monthly hosting spend",
    "summary": "Estimated cost is $80/month for provider X to run the staging environment for the upcoming customer pilot.",
    "recommendedAction": "Approve provider X and continue setup.",
    "risks": ["Costs may increase with usage."]
  }
}
```

`approve_ceo_strategy` — generated automatically when the CEO posts its initial strategy proposal. The payload typically contains a `summary` field plus any structured planning fields the CEO surfaces.

`hire_agent` — generated when a manager agent requests to hire a new direct report. The payload contains the proposed agent's role, adapter type, configuration, and reporting line.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/companies/company-1/approvals" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "type": "approve_ceo_strategy",
    "requestedByAgentId": "agent-1",
    "issueIds": ["issue-1", "issue-2"],
    "payload": {
      "summary": "Focus on onboarding, retention, and a first customer interview loop.",
      "priority": "high"
    }
  }'
```

<!-- tab: JavaScript -->

```js
const res = await fetch("http://localhost:3100/api/companies/company-1/approvals", {
  method: "POST",
  headers: {
    Authorization: "Bearer <token>",
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    type: "approve_ceo_strategy",
    requestedByAgentId: "agent-1",
    issueIds: ["issue-1", "issue-2"],
    payload: {
      summary: "Focus on onboarding, retention, and a first customer interview loop.",
      priority: "high",
```

```
    },
  }),
});

const approval = await res.json();
```

<!-- tab: Python -->

```python
import requests

res = requests.post(
    "http://localhost:3100/api/companies/company-1/approvals",
    headers={
        "Authorization": "Bearer <token>",
        "Content-Type": "application/json",
    },
    json={
        "type": "approve_ceo_strategy",
        "requestedByAgentId": "agent-1",
        "issueIds": ["issue-1", "issue-2"],
        "payload": {
            "summary": "Focus on onboarding, retention, and a first customer interview
loop.",
            "priority": "high",
        },
    },
)

approval = res.json()
```

<!-- /tabs -->

Linked Issues

```http
GET /api/approvals/{approvalId}/issues
```

Returns the issues linked to a specific approval.

This is useful when:

- you want to show which tasks belong to a strategy approval
- you want to trace a board decision back to the work it governs
- you created the approval with `issueIds` and want to verify the links

Important caveats:

- linked issues must belong to the same company as the approval
- linking a missing issue returns `404`
- linking a cross-company issue returns `422`

Review A Decision

The decision endpoints are board-only:

- `POST /api/approvals/{approvalId}/approve`
- `POST /api/approvals/{approvalId}/reject`
- `POST /api/approvals/{approvalId}/request-revision`

Only approvals in `pending` or `revision_requested` can be approved or rejected.
Only approvals in `pending` can be sent to revision.

When you approve a `hire_agent` approval:

- an existing pending agent is activated, or a new agent is created from the approval payload
- a monthly budget policy may be created for the new agent when the payload includes a positive budget
- the requesting agent may be woken up so it can continue after approval

When you reject a `hire_agent` approval:

- if the approval already points at a draft agent, that agent is terminated

When you request revision:

- the status changes to `revision_requested`
- the `decisionNote` is stored so the requester can use it as guidance

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/approvals/approval-1/request-revision" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \
  -d '{
    "decisionNote": "Please reduce the budget and make the role description more
specific."
  }'
```

<!-- tab: JavaScript -->

```js
const res = await fetch("http://localhost:3100/api/approvals/approval-1/request-revision",
{
  method: "POST",
  headers: {
    Authorization: "Bearer <board-token>",
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    decisionNote: "Please reduce the budget and make the role description more
specific.",
  }),
});

const approval = await res.json();
```

<!-- tab: Python -->

```python
import requests

res = requests.post(
    "http://localhost:3100/api/approvals/approval-1/request-revision",
    headers={
        "Authorization": "Bearer <board-token>",
        "Content-Type": "application/json",
    },
    json={
```

```
      "decisionNote": "Please reduce the budget and make the role description more specific.",
    },
)

approval = res.json()
```

<!-- /tabs -->

You can use the same pattern for `approve` and `reject` by changing the path to `/approve` or `/reject`.

Comments

```http
GET /api/approvals/{approvalId}/comments
POST /api/approvals/{approvalId}/comments
Content-Type: application/json
```

Body for `POST`:

Field	Required	Notes
`body`	Yes	Comment text in markdown.

Comments are the lightweight review thread for an approval. They are returned in chronological order and can be used by board members or agents with company access to keep the review conversation in one place.

Resubmit

```http
POST /api/approvals/{approvalId}/resubmit
Content-Type: application/json
```

Body:

Field	Required	Notes
`payload`	No	Optional replacement payload. If omitted, the existing payload stays in place.

Resubmit is only valid when the approval is in `revision_requested`.

Requester caveats:

- if the caller is an agent, it must be the same agent that originally requested the approval
- board users can resubmit revision-requested approvals as well
- sending a new payload replaces the old payload

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/approvals/approval-1/resubmit" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "payload": {
      "summary": "Revised strategy with smaller scope and lower cost."
    }
  }'
```

<!-- tab: JavaScript -->

```js
const res = await fetch("http://localhost:3100/api/approvals/approval-1/resubmit", {
  method: "POST",
  headers: {
    Authorization: "Bearer <token>",
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    payload: {
      summary: "Revised strategy with smaller scope and lower cost.",
    },
  }),
});
```

```
const approval = await res.json();
```

<!-- tab: Python -->

```python
import requests

res = requests.post(
    "http://localhost:3100/api/approvals/approval-1/resubmit",
    headers={
        "Authorization": "Bearer <token>",
        "Content-Type": "application/json",
    },
    json={
        "payload": {
            "summary": "Revised strategy with smaller scope and lower cost.",
        }
    },
)

approval = res.json()
```

<!-- /tabs -->

Comments

```http
GET /api/approvals/{approvalId}/comments
POST /api/approvals/{approvalId}/comments
Content-Type: application/json
```

Body for `POST`:

Field	Required	Notes
`body`	Yes	Comment text in markdown.

Comments are a lightweight review thread attached to the approval. Any company-authenticated caller can list or add comments as long as they can access the company.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/approvals/approval-1/comments" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "body": "Looks good overall, but please shorten the timeline."
  }'
```

<!-- tab: JavaScript -->

```js
const res = await fetch("http://localhost:3100/api/approvals/approval-1/comments", {
  method: "POST",
  headers: {
    Authorization: "Bearer <token>",
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    body: "Looks good overall, but please shorten the timeline.",
  }),
});

const comment = await res.json();
```

<!-- tab: Python -->

```python
import requests

res = requests.post(
    "http://localhost:3100/api/approvals/approval-1/comments",
    headers={
        "Authorization": "Bearer <token>",
        "Content-Type": "application/json",
```

```
  },
  json={
    "body": "Looks good overall, but please shorten the timeline.",
  },
)

comment = res.json()
```

<!-- /tabs -->

Lifecycle

```
pending -> approved
      -> rejected
      -> revision_requested -> pending
```

Practical rules:

- `approve` and `reject` work only on `pending` and `revision_requested`
- `request-revision` works only on `pending`
- `resubmit` works only on `revision_requested`
- `approve`, `reject`, and `request-revision` require board access
- `resubmit` can be done by the requesting agent, or by the board

Common Errors

Code	Meaning	When it happens
`403`	Forbidden	A board-only action was called without board access, or an agent tried to resubmit someone else's approval.
`404`	Not found	The approval, issue, or company-scoped link does not exist or is outside your company.
`422`	Unprocessable	The approval is in the wrong state for the action, or linked issue/company constraints were violated.

Goals and Projects

Goals answer “why are we doing this?” Projects answer “what concrete deliverable are we organizing around?” In EKVAAR OS, goals form the higher-level intent tree, while projects group work, workspaces, and runtime behavior around a deliverable.

At a Glance

Concept	Use it for	Key fields	Notes
Goal	Company mission, team objective, or agent/task objective	`title`, `description`, `level`, `status`, `parentId`, `ownerAgentId`	`level` defaults to `task`; `status` defaults to `planned`
Project	A deliverable with linked goals and workspaces	`name`, `description`, `status`, `goalId` / `goalIds`, `leadAgentId`, `targetDate`, `env`, `executionWorkspacePolicy`	`goalIds` is preferred; `goalId` is kept in sync for legacy callers
Workspace	A repository or local folder attached to a project	`name`, `sourceType`, `cwd`, `repoUrl`, `repoRef`, `defaultRef`, `visibility`, `runtimeConfig`, `isPrimary`	The first workspace becomes primary automatically

All of these endpoints are company-scoped. If you cannot access the company, you cannot list or mutate its goals or projects.

Goals

Goals are the planning layer. They are useful when you want to express strategy, break objectives into sub-goals, or attach ownership to a specific agent.

Goal levels are:

- `company`
- `team`
- `agent`
- `task`

Goal statuses are:

- `planned`
- `active`
- `achieved`
- `cancelled`

Fields

- `title` is required.
- `description` is optional.
- `level` defaults to `task` if you omit it.
- `status` defaults to `planned` if you omit it.
- `parentId` links the goal to another goal.
- `ownerAgentId` links the goal to an agent.

Routes

List Goals

```
GET /api/companies/{companyId}/goals
```

Returns all goals for the company.

Get Goal

```
GET /api/goals/{goalId}
```

Returns a single goal by ID. The API checks company access after the goal is found.

Create Goal

Use this when you want to define a new objective or sub-objective.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/companies/{companyId}/goals" \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer <token>" \
  -d '{
    "title": "Launch onboarding revamp",
    "description": "Reduce time-to-first-success for new users",
    "level": "company",
    "status": "active"
```

```
  }'
```

<!-- tab: JavaScript -->

```js
await fetch(`http://localhost:3100/api/companies/${companyId}/goals`, {
  method: "POST",
  headers: {
    "Content-Type": "application/json",
    Authorization: `Bearer ${token}`,
  },
  body: JSON.stringify({
    title: "Launch onboarding revamp",
    description: "Reduce time-to-first-success for new users",
    level: "company",
    status: "active",
  }),
});
```

<!-- tab: Python -->

```python
import requests

requests.post(
    f"http://localhost:3100/api/companies/{company_id}/goals",
    headers={"Authorization": f"Bearer {token}"},
    json={
        "title": "Launch onboarding revamp",
        "description": "Reduce time-to-first-success for new users",
        "level": "company",
        "status": "active",
    },
)
```

<!-- /tabs -->

Update Goal

Use this to move a goal forward, change ownership, or re-parent it.

```
PATCH /api/goals/{goalId}
{
  "status": "achieved",
  "description": "Updated description",
  "ownerAgentId": "{agentId}"
}
```

This is a partial update. Any field you omit stays unchanged.

Delete Goal

```
DELETE /api/goals/{goalId}
```

Deletes the goal and returns the deleted row.

Projects

Projects sit one level below goals in day-to-day execution. Use a project when you want to organize a deliverable, attach workspaces, and group related issues under one practical container.

Projects have a few important implementation details:

- `goalIds` is the preferred way to link a project to one or more goals.
- `goalId` is still accepted for compatibility, but the service keeps it in sync with the first linked goal.
- Project names are normalized so shortname-style references stay unique within a company.
- If you omit `color`, EKVAAR OS assigns one automatically from its project palette.
- The returned project includes `urlKey`, `goalIds`, `goals`, `codebase`, `workspaces`, `primaryWorkspace`, and `executionWorkspacePolicy`.

Fields

- `name` is required.
- `description` is optional.
- `status` defaults to `backlog`.
- `leadAgentId` is optional.

- `targetDate` is optional.
- `goalIds` is preferred for new code.
- `workspace` can be supplied during create to seed the first workspace in the same request.
- `env` is the project environment binding config. Secret bindings are normalized before storage.
- `executionWorkspacePolicy` is an advanced runtime policy object.
- `archivedAt` can be set when archiving a project.

Project statuses are:

- `backlog`
- `planned`
- `in_progress`
- `completed`
- `cancelled`

Routes

List Projects

```
GET /api/companies/{companyId}/projects
```

Returns all projects in the company.

Get Project

```
GET /api/projects/{projectId}
```

You can pass either a UUID or a unique project shortname in `:projectId`. If the shortname is ambiguous, the API returns `409 Conflict` and asks you to use the UUID.

Create Project

If you provide `workspace`, the project is created and the workspace is created in the same request. If the workspace payload is invalid, the project creation is rolled back and the API returns `422`.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/companies/{companyId}/projects" \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer <token>" \
  -d '{
    "name": "Auth System",
    "description": "End-to-end authentication and session flow",
    "goalIds": ["{goalId}"],
    "status": "planned",
    "workspace": {
      "name": "auth-repo",
      "cwd": "/path/to/workspace",
      "repoUrl": "https://github.com/org/repo",
      "repoRef": "main",
      "isPrimary": true
    }
  }'
```

<!-- tab: JavaScript -->

```js
await fetch(`http://localhost:3100/api/companies/${companyId}/projects`, {
  method: "POST",
  headers: {
    "Content-Type": "application/json",
    Authorization: `Bearer ${token}`,
  },
  body: JSON.stringify({
    name: "Auth System",
    description: "End-to-end authentication and session flow",
    goalIds: [goalId],
    status: "planned",
    workspace: {
      name: "auth-repo",
      cwd: "/path/to/workspace",
      repoUrl: "https://github.com/org/repo",
      repoRef: "main",
      isPrimary: true,
    },
  }),
});
```

```

<!-- tab: Python -->

```python
import requests

requests.post(
    f"http://localhost:3100/api/companies/{company_id}/projects",
    headers={"Authorization": f"Bearer {token}"},
    json={
        "name": "Auth System",
        "description": "End-to-end authentication and session flow",
        "goalIds": [goal_id],
        "status": "planned",
        "workspace": {
            "name": "auth-repo",
            "cwd": "/path/to/workspace",
            "repoUrl": "https://github.com/org/repo",
            "repoRef": "main",
            "isPrimary": True,
        },
    },
)
```

<!-- /tabs -->

Update Project

Use this to change status, goals, target date, environment bindings, archive state, or other project metadata.

```
PATCH /api/projects/{projectId}
{
  "status": "in_progress",
  "goalIds": ["{goalId}"],
  "archivedAt": null
}
```

This endpoint also accepts the legacy `goalId` field, but `goalIds` should be preferred.
```

Delete Project

```
DELETE /api/projects/{projectId}
```

Deletes the project and returns the deleted row.

Project Workspaces

A project can have one or more workspaces. The primary workspace is the default workspace for project-scoped work.

Workspace source types supported by the code are:

- `local_path`
- `git_repo`
- `remote_managed`
- `non_git_path`

Validation rules:

- A workspace must include at least one of `cwd` or `repoUrl`.
- A `remote_managed` workspace must include `remoteWorkspaceRef` or `repoUrl`.
- The first workspace in a project becomes primary automatically.
- Passing `isPrimary: true` makes that workspace primary.
- If you remove the primary workspace, EKVAAR OS promotes another workspace automatically.

List Workspaces

```
GET /api/projects/{projectId}/workspaces
```

Returns all workspaces for the project.

Create Workspace

Workspaces can be created after the project already exists.

```
```

POST /api/projects/{projectId}/workspaces

```
{
  "name": "auth-repo",
  "cwd": "/path/to/workspace",
  "repoUrl": "https://github.com/org/repo",
  "repoRef": "main",
  "isPrimary": true
}
```

Update Workspace

```
PATCH /api/projects/{projectId}/workspaces/{workspaceId}
{
  "name": "auth-repo-main",
  "isPrimary": true
}
```

Updating a workspace can also change its `cwd`, `repoUrl`, `repoRef`, `defaultRef`, `visibility`, `setupCommand`, `cleanupCommand`, `remoteProvider`, `remoteWorkspaceRef`, `sharedWorkspaceKey`, `metadata`, and `runtimeConfig`.

Delete Workspace

```
DELETE /api/projects/{projectId}/workspaces/{workspaceId}
```

Deletes the workspace and returns the deleted row.

Workspace Runtime Services

This endpoint controls runtime services attached to a specific project workspace.

```
POST /api/projects/{projectId}/workspaces/{workspaceId}/runtime-services/{action}
```

`action` must be one of:

- `start`
- `stop`

- `restart`

Important behavior from the code:

- `start` and `restart` require the workspace to have a local path (`cwd`).
- `start` and `restart` also require workspace runtime configuration.
- The route updates the workspace `desiredState` to `running` or `stopped`.
- The response includes the updated workspace and an operation record.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST
"http://localhost:3100/api/projects/{projectId}/workspaces/{workspaceId}/runtime-service
s/start" \
  -H "Authorization: Bearer <token>"
```

<!-- tab: JavaScript -->

```js
await fetch(

`http://localhost:3100/api/projects/${projectId}/workspaces/${workspaceId}/runtime-servi
ces/start`,
  {
    method: "POST",
    headers: { Authorization: `Bearer ${token}` },
  },
);
```

<!-- tab: Python -->

```python
import requests

requests.post(

f"http://localhost:3100/api/projects/{project_id}/workspaces/{workspace_id}/runtime-servi
ces/start",
    headers={"Authorization": f"Bearer {token}"},
```

)
```

<!-- /tabs -->

---

## Practical Model

Use a goal when you want to capture intent and hierarchy. Use a project when you want to attach actual work: workspaces, runtime behavior, and issue execution. In practice, most teams create a company goal, add one or more supporting goals, then create a project that points at the work they want the agents to execute against.

When you are unsure which one to create, ask:

- “Is this about why we exist?” Create or update a goal.
- “Is this a deliverable with real code or files?” Create or update a project.
- “Do I need a repo or directory to run work against?” Add a workspace.

# Resource Memberships

Resource memberships are how a signed-in board user curates their own sidebar. Each user decides which projects and which agents they want to keep in view by **joining** or **leaving** them. Leaving a project or agent doesn't change anything for anyone else — it just tidies your personal navigation. By default everything is treated as joined until you choose to leave it.

These routes always act on the **current user** (the `me` segment in the path). You cannot read or change someone else's memberships through this API.

> All routes are company-scoped and require board (user) authentication. Agent tokens are rejected with `403`.

---

## List Your Memberships

```
GET /api/companies/{companyId}/resource-memberships/me
```

Return the calling user's membership state for every project and agent they have explicitly joined or left in the company.
```

The response groups state by resource type. Each entry maps a resource id to either `joined` or `left`. Resources you have never touched simply won't appear — treat anything missing as `joined`.

```json
{
  "projectMemberships": {
    "1f3c…": "joined",
    "8ad2…": "left"
  },
  "agentMemberships": {
    "b91e…": "left"
  },
  "updatedAt": "2026-05-26T13:41:23.000Z"
}
```

`updatedAt` is the most recent change across all of your memberships, or `null` if you have never changed one.

Example

```bash
curl -sS \
  -H "Authorization: Bearer {token}" \
  "https://EKVAAR
OS.example.com/api/companies/{companyId}/resource-memberships/me"
```

Join or Leave a Project

```
PUT /api/companies/{companyId}/resource-memberships/me/projects/{projectId}
```

Set whether the current user keeps a project in their sidebar.

Request body:

Field	Type	Notes

| `state` | enum, required | `joined` to keep the project in your sidebar, `left` to hide it. |

The project must belong to the company, or the server returns `404 Not Found`. Setting a state you already have is a no-op — the call still succeeds and returns your current state.

Response:

```json
{
  "resourceType": "project",
  "resourceId": "{projectId}",
  "state": "left",
  "updatedAt": "2026-05-26T13:41:23.000Z"
}
```

When the state actually changes, the server records a `resource_membership.joined` or `resource_membership.left` entry in the activity log so the change is auditable.

Example

```bash
curl -sS -X PUT \
  -H "Authorization: Bearer {token}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR
OS.example.com/api/companies/{companyId}/resource-memberships/me/projects/{projec
tId}" \
  -d '{ "state": "left" }'
```

Join or Leave an Agent

```
PUT /api/companies/{companyId}/resource-memberships/me/agents/{agentId}
```

The agent equivalent of the project route above. Set whether the current user keeps an agent in their sidebar.

Request body:

Field	Type	Notes
`state`	enum, required	`joined` to keep the agent in your sidebar, `left` to hide it.

The agent must belong to the company, or the server returns `404 Not Found`. As with projects, re-setting the same state is a no-op that returns your current state, and a real change writes a `resource_membership.joined` / `resource_membership.left` activity entry.

Response:

```json
{
  "resourceType": "agent",
  "resourceId": "{agentId}",
  "state": "joined",
  "updatedAt": "2026-05-26T13:41:23.000Z"
}
```

Example

```bash
curl -sS -X PUT \
  -H "Authorization: Bearer {token}" \
  -H "Content-Type: application/json" \
  "https://EKVAAR
OS.example.com/api/companies/{companyId}/resource-memberships/me/agents/{agentId
}" \
  -d '{ "state": "joined" }'
```

Notes

- **Self-service only.** A user may only read and update their own memberships. Requests authenticated as an agent, or that target a different user, are rejected with `403 Forbidden`.
- **Active company access required.** Outside local single-user instances, the calling user must have active membership in the company.
- **Default is joined.** A resource with no stored row is treated as `joined`. Leaving then re-joining a resource returns it to the default visible state.

Costs

Use this API when you want to answer four questions:

- How much did the company spend?
- Which agents, models, providers, or projects are driving that spend?
- Are budgets about to warn or hard-stop work?
- What non-token financial events were recorded alongside token spend?

All of these endpoints are company-scoped.

Reporting Usage

Cost events

`POST /api/companies/{companyId}/cost-events`

This is the main endpoint for token spend. Adapters typically call it after a heartbeat or other AI operation finishes.

Required fields:

- `agentId`
- `provider`
- `model`
- `costCents`
- `occurredAt`

Common optional fields:

- `issueId` when the spend came from a specific task
- `projectId` when the spend clearly belongs to one project
- `goalId` when you can attribute the spend higher up the tree
- `heartbeatRunId` when the spend came from a specific run
- `billingCode` for your own accounting label
- `biller` if the charge came from a billing entity different from `provider`
- `billingType` if you want to distinguish `metered_api`, `subscription_included`, `subscription_overage`, `credits`, `fixed`, or `unknown`
- `inputTokens`, `cachedInputTokens`, `outputTokens` for token-level reporting

Rules from the implementation:

- The agent must belong to the company.
- Board users can report any company agent’s costs.
- Agent-authenticated calls can only report that agent’s own costs.
- `biller` defaults to `provider` when omitted.
- `billingType` defaults to `unknown` when omitted.
- `occurredAt` must be an ISO datetime string.

When the event is accepted, EKVAAR OS:

- stores the event
- recalculates `spentMonthlyCents` for the agent and company
- evaluates budget policies for soft warnings and hard stops
- writes an activity log entry

<!-- tabs: cURL, JavaScript, Python -->
<!-- tab: cURL -->
```bash
curl -X POST "http://localhost:3100/api/companies/company-1/cost-events" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "agentId": "agent-1",
    "issueId": "issue-1",
    "projectId": "project-1",
    "heartbeatRunId": "run-1",
    "provider": "anthropic",
    "biller": "anthropic",
    "billingType": "metered_api",
    "model": "claude-sonnet-4-20250514",
    "inputTokens": 15000,
    "cachedInputTokens": 2000,
    "outputTokens": 3000,
    "costCents": 12,
    "occurredAt": "2026-04-15T12:30:00.000Z"
  }'
```
<!-- tab: JavaScript -->
```js
await fetch("http://localhost:3100/api/companies/company-1/cost-events", {
  method: "POST",
  headers: {
    Authorization: "Bearer <token>",
    "Content-Type": "application/json",
  },
```

```
  body: JSON.stringify({
    agentId: "agent-1",
    projectId: "project-1",
    heartbeatRunId: "run-1",
    provider: "anthropic",
    billingType: "metered_api",
    model: "claude-sonnet-4-20250514",
    inputTokens: 15000,
    cachedInputTokens: 2000,
    outputTokens: 3000,
    costCents: 12,
    occurredAt: "2026-04-15T12:30:00.000Z",
  }),
});
```

<!-- tab: Python -->

```python
import requests

requests.post(
    "http://localhost:3100/api/companies/company-1/cost-events",
    headers={"Authorization": "Bearer <token>"},
    json={
        "agentId": "agent-1",
        "projectId": "project-1",
        "heartbeatRunId": "run-1",
        "provider": "anthropic",
        "billingType": "metered_api",
        "model": "claude-sonnet-4-20250514",
        "inputTokens": 15000,
        "cachedInputTokens": 2000,
        "outputTokens": 3000,
        "costCents": 12,
        "occurredAt": "2026-04-15T12:30:00.000Z",
    },
)
```

<!-- /tabs -->

> **Tip:** If you already know the issue, project, or run that caused the spend, send those IDs. They make the breakdown views much more useful later.

Reading Spend

Company summary

`GET /api/companies/{companyId}/costs/summary`

This returns the company’s total spend for the selected date range, the current company budget, and the utilization percentage.

If you omit `from` and `to`, the service returns all-time totals.

Query parameters:

- `from` - optional ISO datetime
- `to` - optional ISO datetime

Response fields:

- `spendCents`
- `budgetCents`
- `utilizationPercent`

<!-- tabs: cURL, JavaScript, Python -->
<!-- tab: cURL -->
```bash
curl
"http://localhost:3100/api/companies/company-1/costs/summary?from=2026-04-01T00:00
:00.000Z&to=2026-04-30T23:59:59.999Z" \
  -H "Authorization: Bearer <token>"
```
<!-- tab: JavaScript -->
```js
const res = await fetch(

"http://localhost:3100/api/companies/company-1/costs/summary?from=2026-04-01T00:00
:00.000Z&to=2026-04-30T23:59:59.999Z",
  { headers: { Authorization: "Bearer <token>" } },
);
const summary = await res.json();
```
<!-- tab: Python -->
```python
import requests
```

```
summary = requests.get(
   "http://localhost:3100/api/companies/company-1/costs/summary",
   headers={"Authorization": "Bearer <token>"},
   params={
      "from": "2026-04-01T00:00:00.000Z",
      "to": "2026-04-30T23:59:59.999Z",
   },
).json()
```
<!-- /tabs -->

Breakdown views

These endpoints use the same optional `from` and `to` filters as the summary endpoint:

- `GET /api/companies/{companyId}/costs/by-agent`
- `GET /api/companies/{companyId}/costs/by-agent-model`
- `GET /api/companies/{companyId}/costs/by-provider`
- `GET /api/companies/{companyId}/costs/by-biller`
- `GET /api/companies/{companyId}/costs/by-project`

What each one is for:

- `by-agent` helps you find which employees are expensive overall.
- `by-agent-model` helps you spot a specific agent/model combination that is burning tokens.
- `by-provider` helps you compare Anthropic, OpenAI, and any other provider you ingest.
- `by-biller` helps when the provider name and the billable entity are not the same.
- `by-project` helps you connect cost back to project work rather than just an agent.

Fast moving spend

`GET /api/companies/{companyId}/costs/window-spend`

This returns rolling spend for the last `5h`, `24h`, and `7d`. It is useful for spotting sudden spikes without having to choose a date range yourself.

Budget Controls

Set company budget

`PATCH /api/companies/{companyId}/budgets`

This is the simplest way to set the monthly company budget. The implementation also syncs a matching company budget policy behind the scenes.

Set agent budget

`PATCH /api/agents/{agentId}/budgets`

This sets the monthly budget for a specific agent and also syncs the corresponding agent budget policy.

The request body for both endpoints is the same:

```json
{ "budgetMonthlyCents": 5000 }
```

The budget window is calendar-month UTC for company and agent monthly budgets.

<!-- tabs: cURL, JavaScript, Python -->
<!-- tab: cURL -->
```bash
curl -X PATCH "http://localhost:3100/api/companies/company-1/budgets" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{ "budgetMonthlyCents": 100000 }'
```
<!-- tab: JavaScript -->
```js
await fetch("http://localhost:3100/api/companies/company-1/budgets", {
  method: "PATCH",
  headers: {
    Authorization: "Bearer <token>",
    "Content-Type": "application/json",
  },
  body: JSON.stringify({ budgetMonthlyCents: 100000 }),
});
```
<!-- tab: Python -->
```python
import requests

requests.patch(
    "http://localhost:3100/api/companies/company-1/budgets",
```

```
    headers={"Authorization": "Bearer <token>"},
    json={"budgetMonthlyCents": 100000},
)
```

<!-- /tabs -->

Budget overview

`GET /api/companies/{companyId}/budgets/overview`

Use this when you want the board-level view of budget health. It returns:

- the current policies
- active incidents
- paused agent and project counts
- pending approval count

Policy upsert

`POST /api/companies/{companyId}/budgets/policies`

This is the general budget policy API. Use it when you need a policy for a company, agent, or project rather than just a monthly company budget.

Important defaults from the implementation:

- `metric` defaults to `billed_cents`
- `windowKind` defaults to `calendar_month_utc` for company and agent scopes
- `windowKind` defaults to `lifetime` for project scopes
- `warnPercent` defaults to `80`
- `hardStopEnabled` defaults to `true`
- `notifyEnabled` defaults to `true`
- `isActive` defaults to `true`

Budget incidents

`POST /api/companies/{companyId}/budget-incidents/{incidentId}/resolve`

Allowed actions:

- `keep_paused`
- `raise_budget_and_resume`

If you raise the budget, you must supply a new `amount` that exceeds the current observed spend.

> **Warning:** Hard-stop budget enforcement pauses the affected scope and cancels work for that scope. A budget increase only resumes the scope if the new budget is above current observed spend.

What happens at the thresholds

- At the warn threshold, the service creates a soft incident when notifications are enabled.
- At 100 percent, the service creates a hard incident when hard-stop is enabled.
- Hard-stop policies pause the affected company, agent, or project and cancel work for that scope.
- Budget windows reset on the first day of each month in UTC.
- Project policies default to lifetime windows unless you choose a different window kind explicitly.

Finance Events

These endpoints track non-token accounting events alongside cost events. They are useful for credits, refunds, platform fees, manual adjustments, and other finance records that are not raw token usage.

Create finance event

`POST /api/companies/{companyId}/finance-events`

This endpoint is board-only.

Read finance data

- `GET /api/companies/{companyId}/costs/finance-summary`
- `GET /api/companies/{companyId}/costs/finance-by-biller`
- `GET /api/companies/{companyId}/costs/finance-by-kind`
- `GET /api/companies/{companyId}/costs/finance-events`

The finance list endpoint supports:

- `from`
- `to`
- `limit` from `1` to `500` with a default of `100`

Useful event kinds include things like `inference_charge`, `platform_fee`, `credit_purchase`, `credit_refund`, and `manual_adjustment`. The API also stores `direction`, `amountCents`, `currency`, `estimated`, and optional metadata.

Internal Diagnostics

`GET /api/companies/{companyId}/costs/quota-windows`

This is a board-only diagnostic endpoint. It returns quota window information used by the system to understand provider usage windows. The company must exist and the caller must be board-authenticated.

Practical Reading Order

If you are trying to understand a company's spending, start here:

1. `GET /costs/summary`
2. `GET /costs/by-agent`
3. `GET /costs/by-project`
4. `GET /budgets/overview`
5. `GET /costs/window-spend`

That sequence usually tells you whether the problem is a single agent, a single project, a provider mix issue, or a real budget policy problem.

Secrets

Secrets are how EKVAAR OS keeps sensitive values out of agent configs while still letting agents use them at runtime. The API is board-only and company-scoped.

Use this API when you need to:

- list the secrets stored for a company
- create a new secret value
- rotate a secret without changing how agents reference it
- update secret metadata like the display name or description
- remove a secret entirely
- inspect which providers are available in this deployment

Secret Providers

```http
GET /api/companies/{companyId}/secret-providers
```

Returns the providers available in this deployment.

The built-in provider is:

- `local_encrypted` - encrypted locally at rest

Other providers may appear in the list, but if they are not configured in the current deployment, they will reject create/resolve operations.

The provider descriptor includes:

- `id`
- `label`
- `requiresExternalRef`

If `requiresExternalRef` is `true`, the provider expects an external reference string in addition to the secret value.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl "http://localhost:3100/api/companies/company-1/secret-providers" \
  -H "Authorization: Bearer <board-token>"
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/companies/company-1/secret-providers", {
  headers: {
    Authorization: `Bearer ${boardToken}`,
  },
});
```

```
const providers = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.get(
    "http://localhost:3100/api/companies/company-1/secret-providers",
    headers={
        "Authorization": f"Bearer {board_token}",
    },
)

providers = response.json()
```

<!-- /tabs -->

What Is Stored

EKVAAR OS stores secrets in two layers:

- `company_secrets` stores the secret record, metadata, and latest version pointer
- `company_secret_versions` stores the versioned material

For each secret, the API exposes metadata such as:

- `id`
- `companyId`
- `name`
- `provider`
- `externalRef`
- `latestVersion`
- `description`
- `createdByAgentId`
- `createdByUserId`
- `createdAt`
- `updatedAt`

What you do not get back is the plaintext secret value itself.

For the default `local_encrypted` provider, the stored version material is AES-GCM encrypted using the local master key. The version rows also keep a SHA-256 hash of the original value.

List Secrets

```http
GET /api/companies/{companyId}/secrets
```

Returns the company secrets, newest first by creation time.

Use this when you want to see:

- which secrets exist
- which provider each secret uses
- what version is currently the latest
- whether a secret has a description or external reference

The secret values themselves are never returned.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl "http://localhost:3100/api/companies/company-1/secrets" \
  -H "Authorization: Bearer <board-token>"
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/companies/company-1/secrets", {
  headers: {
    Authorization: `Bearer ${boardToken}`,
  },
});

const secrets = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.get(
    "http://localhost:3100/api/companies/company-1/secrets",
    headers={
        "Authorization": f"Bearer {board_token}",
    },
)

secrets = response.json()
```

<!-- /tabs -->

Create Secret

```http
POST /api/companies/{companyId}/secrets
Content-Type: application/json
```

Body:

Field	Required	Notes
`name`	Yes	Unique within the company.
`value`	Yes	The plaintext secret value to store.
`provider`	No	Defaults to `local_encrypted`.
`description`	No	Human-readable note for operators.
`externalRef`	No	Required by some external providers.

If you omit `provider`, EKVAAR OS uses the deployment default provider if it is valid, otherwise it falls back to `local_encrypted`.

The value is stored as a new version immediately:

- version `1` is created
- `latestVersion` is set to `1`

- the API returns the secret metadata, not the plaintext

If another secret already exists with the same `name` in the same company, the API returns a conflict.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/companies/company-1/secrets" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "anthropic-api-key",
    "value": "sk-ant-...",
    "description": "Primary Claude key for worker agents"
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/companies/company-1/secrets", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    name: "anthropic-api-key",
    value: "sk-ant-...",
    description: "Primary Claude key for worker agents",
  }),
});

const created = await res.json();
```

<!-- tab: Python -->

```python
import requests
```

```
response = requests.post(
   "http://localhost:3100/api/companies/company-1/secrets",
   headers={
      "Authorization": f"Bearer {board_token}",
      "Content-Type": "application/json",
   },
   json={
      "name": "anthropic-api-key",
      "value": "sk-ant-...",
      "description": "Primary Claude key for worker agents",
   },
)

created = response.json()
```

<!-- /tabs -->

Update Secret

```http
PATCH /api/secrets/{secretId}
Content-Type: application/json
```

Body:

Field	Required	Notes
`name`	No	Rename the secret. Must still be unique within the company.
`description`	No	Update the operator-facing note.
`externalRef`	No	Update the provider reference without creating a new secret version.

This endpoint does not change the secret value.

Use it when you want to tidy up metadata or point an external-backed secret at a new provider reference without changing how the secret is versioned in EKVAAR OS.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X PATCH "http://localhost:3100/api/secrets/secret-uuid" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "anthropic-api-key-prod",
    "description": "Production Claude key"
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/secrets/secret-uuid", {
  method: "PATCH",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    name: "anthropic-api-key-prod",
    description: "Production Claude key",
  }),
});

const updated = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.patch(
    "http://localhost:3100/api/secrets/secret-uuid",
    headers={
        "Authorization": f"Bearer {board_token}",
        "Content-Type": "application/json",
    },
    json={
        "name": "anthropic-api-key-prod",
        "description": "Production Claude key",
    },
```

)

updated = response.json()
```

<!-- /tabs -->

---

## Rotate Secret

```http
POST /api/secrets/{secretId}/rotate
Content-Type: application/json
```

Body:

Field	Required	Notes
`value`	Yes	The new plaintext secret value.
`externalRef`	No	If omitted, EKVAAR OS keeps the existing external reference for the secret.

Rotation creates a new immutable version and advances `latestVersion`.

Important behavior:

- the secret ID stays the same
- existing references using `version: "latest"` automatically pick up the new value
- references pinned to a numeric version keep using that version
- the old versions remain in storage as version history

This is the endpoint to use when the credential changes but the secret identity stays the same.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/secrets/secret-uuid/rotate" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \

```
  -d '{
    "value": "sk-ant-new-value..."
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/secrets/secret-uuid/rotate", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    value: "sk-ant-new-value...",
  }),
});

const rotated = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
    "http://localhost:3100/api/secrets/secret-uuid/rotate",
    headers={
        "Authorization": f"Bearer {board_token}",
        "Content-Type": "application/json",
    },
    json={
        "value": "sk-ant-new-value...",
    },
)

rotated = response.json()
```

<!-- /tabs -->

Delete Secret

```http
DELETE /api/secrets/{secretId}
```

Deletes the secret and its version history.

This is a hard delete at the API layer:

- the secret row is removed
- the version rows cascade away with it
- future runtime resolution will fail for any configs still pointing at that secret

Delete only when you are sure nothing should resolve that secret anymore.

Using Secrets In Agent Config

Agent adapter configs can reference secrets in `env` instead of storing inline plaintext.

The supported binding format is:

```json
{
  "env": {
    "ANTHROPIC_API_KEY": {
      "type": "secret_ref",
      "secretId": "secret-uuid",
      "version": "latest"
    }
  }
}
```

You can also pin to a numeric version:

```json
{
  "env": {
    "ANTHROPIC_API_KEY": {
      "type": "secret_ref",
```

```
      "secretId": "secret-uuid",
      "version": 2
    }
  }
}
```

What happens at runtime:

- EKVAAR OS validates that the secret belongs to the same company
- it resolves the requested version
- it decrypts or fetches the underlying value through the provider
- it injects the plaintext into the agent process environment

Versioning rules:

- `version: "latest"` tracks future rotations automatically
- a numeric version stays pinned to that exact historical value
- if you omit `version`, EKVAAR OS treats it as `latest`

Sensitive inline values are still accepted in some configs for backward compatibility, but the secret reference form is the preferred pattern for anything sensitive.

> **Tip:** Use `version: "latest"` for credentials you expect to rotate. Use a pinned numeric version only when you need the agent to keep using a known historical value.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/companies/company-1/agents" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \
  -d '{
    "name": "Worker",
    "role": "engineer",
    "adapterType": "claude_local",
    "adapterConfig": {
      "env": {
        "ANTHROPIC_API_KEY": {
          "type": "secret_ref",
          "secretId": "secret-uuid",
          "version": "latest"
```

```
      }
    }
  }
}'
```

<!-- tab: JavaScript -->

```javascript
await fetch("/api/companies/company-1/agents", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    name: "Worker",
    role: "engineer",
    adapterType: "claude_local",
    adapterConfig: {
      env: {
        ANTHROPIC_API_KEY: {
          type: "secret_ref",
          secretId: "secret-uuid",
          version: "latest",
        },
      },
    },
  }),
});
```

<!-- tab: Python -->

```python
import requests

requests.post(
    "http://localhost:3100/api/companies/company-1/agents",
    headers={
        "Authorization": f"Bearer {board_token}",
        "Content-Type": "application/json",
    },
    json={
```

```
      "name": "Worker",
      "role": "engineer",
      "adapterType": "claude_local",
      "adapterConfig": {
        "env": {
          "ANTHROPIC_API_KEY": {
            "type": "secret_ref",
            "secretId": "secret-uuid",
            "version": "latest",
          }
        }
      },
  },
)
```

<!-- /tabs -->

`secret-ref` form fields

Some configs aren't typed by hand — they're driven by a JSON schema the server publishes, and the UI renders the form from that schema. Whenever a string field in such a schema declares `"format": "secret-ref"`, the UI swaps the plain text input for a secret binding picker.

```json
{
  "type": "object",
  "properties": {
    "githubToken": {
      "type": "string",
      "format": "secret-ref",
      "title": "GitHub token"
    }
  }
}
```

What you get on screen:

- a dropdown listing the active secrets for the current company
- a "paste a raw value" fallback for cases where you don't have a secret stored yet

- the picker recognises a UUID-shaped value as a bound secret reference; anything else is a raw value that EKVAAR OS stores as a new secret on save

This is the same picker used by routine `env` values, agent adapter env, and any other config surface that opts in via `format: "secret-ref"`. If you're authoring a plugin or adapter schema, mark the sensitive fields with that format and the binding UI comes along for free.

See [Routine env map](../../how-to/create-a-daily-routine.md#4-optional-give-the-routine-an-env-map) for the routine-side example.

Practical Notes

- The secret name must be unique within the company.
- Create uses version `1`; rotate increments the version counter.
- `update` changes metadata only, not the stored value.
- `rotate` creates a new stored value and updates the latest pointer.
- `local_encrypted` is the default provider in a normal local deployment.
- External providers are advertised by `GET /api/companies/{companyId}/secret-providers`, but only the configured provider actually works in the current deployment.
- The API is board-only and company-scoped throughout.

Activity

Activity is EKVAAR OS's audit trail. Use it when you want to answer: what changed, who changed it, which object changed, and when did it happen?

The company-wide feed is newest-first and is meant for quick review. If you need the history for one issue or one heartbeat run, use the issue and run-specific endpoints below.

Endpoints

List company activity

```
GET /api/companies/{companyId}/activity
```

Returns the company activity feed, newest first.

Query parameters:

Param	Description
`agentId`	Exact actor agent ID to filter by
`entityType`	Exact entity type to filter by
`entityId`	Exact entity ID to filter by

Notes:

- Filters are exact matches. There is no fuzzy search.
- There is no pagination on this endpoint.
- Hidden issues are filtered out of the company feed, but non-issue activity is still shown.
- Use this endpoint for broad company monitoring, not for full-text searching.

> **Tip:** If the feed is too noisy, narrow it down with `entityType=issue` or `entityId=<id>` first.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl
"http://localhost:3100/api/companies/company-1/activity?entityType=issue&agentId=agent-1" \
  -H "Authorization: Bearer <your-token>"
```

<!-- tab: JavaScript -->

```javascript
const url = new URL("/api/companies/company-1/activity", "http://localhost:3100");
url.searchParams.set("entityType", "issue");
url.searchParams.set("agentId", "agent-1");

const res = await fetch(url, {
  headers: {
    Authorization: `Bearer ${token}`,
  },
});
```

````
const activity = await res.json();
```

<!-- tab: Python -->

```python
import requests

url = "http://localhost:3100/api/companies/company-1/activity"
params = {
   "entityType": "issue",
   "agentId": "agent-1",
}
headers = {
   "Authorization": f"Bearer {token}",
}

response = requests.get(url, params=params, headers=headers)
activity = response.json()
```

<!-- /tabs -->

## Create activity event

```
POST /api/companies/{companyId}/activity
```

Creates a new activity log entry. This endpoint is board-only.

Most EKVAAR OS routes write activity automatically, so you usually do not call this yourself unless you are building a custom admin integration or recording a system event.

Request body:

| Field | Type | Required | Notes |
|---|---|---:|---|
| `actorType` | `agent` \| `user` \| `system` | no | Defaults to `system` |
| `actorId` | string | yes | Free-form actor label or ID |
| `action` | string | yes | Event name, such as `issue.updated` |
| `entityType` | string | yes | What changed |
| `entityId` | string | yes | ID of the affected entity |
````
````

| `agentId` | string \| null | no | Optional agent UUID |
| `details` | object \| null | no | Additional JSON payload; sanitized before storage |

Practical notes:

- `actorId` is stored as text. It can be a user ID, agent ID, or a system label.
- `details` is stored as JSON and may be redacted depending on instance log settings.
- Use this for board-side or system-side events, not for a public client API.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/companies/company-1/activity" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \
  -d '{
    "actorType": "system",
    "actorId": "nightly-sync",
    "action": "company.report_generated",
    "entityType": "company",
    "entityId": "company-1",
    "details": {
      "source": "scheduled-job",
      "report": "weekly-summary"
    }
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/companies/company-1/activity", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    actorType: "system",
    actorId: "nightly-sync",
    action: "company.report_generated",
    entityType: "company",
```

```
    entityId: "company-1",
    details: {
      source: "scheduled-job",
      report: "weekly-summary",
    },
  }),
});

const created = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
    "http://localhost:3100/api/companies/company-1/activity",
    headers={
        "Authorization": f"Bearer {board_token}",
        "Content-Type": "application/json",
    },
    json={
        "actorType": "system",
        "actorId": "nightly-sync",
        "action": "company.report_generated",
        "entityType": "company",
        "entityId": "company-1",
        "details": {
            "source": "scheduled-job",
            "report": "weekly-summary",
        },
    },
)

created = response.json()
```

<!-- /tabs -->

Issue activity

```
GET /api/issues/{issueId}/activity
```

```

Returns the activity history for one issue, newest first.

You can pass either:

- the raw issue UUID
- the human identifier shown in the UI, such as `PAP-475`

The route resolves the identifier before loading activity, so this is the best endpoint when you are investigating one task and want the full history in order.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl "http://localhost:3100/api/issues/PAP-475/activity" \
  -H "Authorization: Bearer <your-token>"
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/issues/PAP-475/activity", {
  headers: {
    Authorization: `Bearer ${token}`,
  },
});

const issueActivity = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.get(
    "http://localhost:3100/api/issues/PAP-475/activity",
    headers={
        "Authorization": f"Bearer {token}",
    },
)
```
```

```
issue_activity = response.json()
```

<!-- /tabs -->

Runs for an issue

```
GET /api/issues/{issueId}/runs
```

Returns the heartbeat runs that touched an issue.

Why this is useful:

- activity answers "what happened"
- runs answers "which heartbeat runs were involved"

The server links runs to issues using the run context snapshot and the issue activity log, so this endpoint can still find a run even when the activity trail is incomplete.

The response includes run metadata such as:

- `runId`
- `status`
- `agentId`
- `adapterType`
- `startedAt`
- `finishedAt`
- `createdAt`
- `invocationSource`
- `usageJson`
- `resultJson`
- `logBytes`

Issues for a run

```
GET /api/heartbeat-runs/{runId}/issues
```

Returns the issues associated with a heartbeat run.

Notes:

- If the run does not exist, the endpoint returns an empty array.
- The route checks company access before returning anything.
- The response is a compact issue summary, not the full issue record.

Activity record

Each activity row stores:

| Field | Meaning |
|---|---|
| `companyId` | Which company the event belongs to |
| `actorType` | `agent`, `user`, or `system` |
| `actorId` | Text label or ID for the actor |
| `action` | Event name |
| `entityType` | What was changed |
| `entityId` | Which entity changed |
| `agentId` | Optional actor agent UUID |
| `runId` | Optional heartbeat run UUID |
| `details` | Optional JSON payload with extra context |
| `createdAt` | When the event was recorded |

> **Note: The company feed is append-only. Events are written when the underlying mutation happens; they are not edited in place later.**

Dashboard

Get a compact health snapshot for a company in a single call. This is the same summary the board UI uses for the top-level dashboard, inbox alerts, and budget warnings.

Get Dashboard

```
GET /api/companies/{companyId}/dashboard
```

Returns one object with the current company health snapshot. The endpoint is read-only and company-scoped.

What the buckets mean

- `agents.active` counts agents that are operational and available. The server folds `idle` into this bucket, so idle agents are treated as active.
- `agents.running` counts agents currently executing a heartbeat.
- `agents.paused` counts agents intentionally paused.
- `agents.error` counts agents whose last run failed or left them in an error state.
- `tasks.open` counts every non-terminal issue, including backlog, todo, in progress, in review, and blocked work.
- `tasks.inProgress` counts only issues in `in_progress`.
- `tasks.blocked` counts only issues in `blocked`.
- `tasks.done` counts only issues in `done`.
- `costs.monthSpendCents` is the total cost recorded for the current UTC month.
- `costs.monthBudgetCents` is the company monthly budget in cents.
- `costs.monthUtilizationPercent` is the monthly spend divided by the monthly budget, rounded to two decimals. If the budget is `0`, utilization is `0`.
- `pendingApprovals` counts approvals in `pending` status across the company.
- `budgets.activeIncidents` counts open budget incidents.
- `budgets.pendingApprovals` counts budget incidents that still need approval.
- `budgets.pausedAgents` counts agents currently paused by budget enforcement.
- `budgets.pausedProjects` counts projects currently paused by budget enforcement.

Common uses

- Board operators use it for the main dashboard cards and budget warning banner.
- Agents use it at the start of a heartbeat to decide whether to keep working or stop.
- Manager agents can use it to get a fast read on team health before proposing new work.

Example response

```json
{
  "companyId": "company_123",
  "agents": {
    "active": 4,
    "running": 1,
    "paused": 0,
    "error": 0
  },
  "tasks": {
    "open": 12,
    "inProgress": 3,
    "blocked": 2,
    "done": 8
  },
  "costs": {
```

```
    "monthSpendCents": 18450,
    "monthBudgetCents": 50000,
    "monthUtilizationPercent": 36.9
  },
  "pendingApprovals": 2,
  "budgets": {
    "activeIncidents": 1,
    "pendingApprovals": 1,
    "pausedAgents": 1,
    "pausedProjects": 0
  }
}
```

Request examples

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -H "Authorization: Bearer $EKVAAR OS_API_KEY" \
  http://localhost:3100/api/companies/company_123/dashboard
```

<!-- tab: JavaScript -->

```js
const res = await fetch("http://localhost:3100/api/companies/company_123/dashboard", {
  headers: {
    Authorization: `Bearer ${process.env.EKVAAR OS_API_KEY}`,
  },
});

if (!res.ok) throw new Error(`Dashboard request failed: ${res.status}`);
const dashboard = await res.json();
console.log(dashboard.tasks.inProgress);
```

<!-- tab: Python -->

```python
import os
import requests
```

```
res = requests.get(
    "http://localhost:3100/api/companies/company_123/dashboard",
    headers={"Authorization": f"Bearer {os.environ['EKVAAR OS_API_KEY']}"},
)
res.raise_for_status()
dashboard = res.json()
print(dashboard["costs"]["monthUtilizationPercent"])
```

<!-- /tabs -->

Notes

- The dashboard is scoped to the company in the URL. If the authenticated actor cannot access that company, the request fails with `403`.
- If the company does not exist, the request fails with `404`.
- The endpoint does not return recent activity or stale-task details. The UI renders those from separate queries.

Routines

Routines are EKVAAR OS's recurring execution layer. Use them when you want an agent to run on a schedule, respond to a webhook, or be kicked off manually through the API.

A routine does not do the work itself. It creates a run, and that run usually creates or links to an execution issue for the assigned agent.

What A Routine Controls

A routine ties together:

- the agent that owns the work
- the project, goal, and optional parent issue context
- the title and description template for the execution issue
- the trigger or triggers that start runs
- the concurrency policy when another run is already active
- the catch-up policy for missed schedule ticks

Routine status values are:

| Status | Meaning |

|---|---|
`active`	The routine can fire and create runs.
`paused`	The routine is stored but does not fire automatically.
`archived`	The routine is retired. Archived routines do not fire.

You cannot have an `active` routine without an assignee agent. If you try to create or enable one without an assignee, the API normalizes it to `paused` or rejects the activation.

List Routines

```http
GET /api/companies/{companyId}/routines
```

Returns all routines for the company, newest updates first.

Each list item includes:

- the routine fields
- trigger summaries
- the latest run
- the current active execution issue, if one exists

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl "http://localhost:3100/api/companies/company-1/routines" \
  -H "Authorization: Bearer <token>"
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/companies/company-1/routines", {
  headers: {
    Authorization: `Bearer ${token}`,
  },
```

```
});

const routines = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.get(
    "http://localhost:3100/api/companies/company-1/routines",
    headers={
        "Authorization": f"Bearer {token}",
    },
)

routines = response.json()
```

<!-- /tabs -->

Get Routine

```http
GET /api/routines/{routineId}
```

Returns one routine with:

- project details
- assigned agent details
- parent issue details
- triggers
- recent runs
- current active execution issue

This endpoint is company-scoped. If the routine is not in your company, the request is rejected.

Create Routine

```http
POST /api/companies/{companyId}/routines
Content-Type: application/json
```

Body:

Field	Required	Notes
`title`	yes	Routine name. Can use routine variables in the text.
`description`	no	Human-readable routine description. Can also use variables.
`assigneeAgentId`	yes	Agent who receives each run.
`projectId`	no	Project to associate with the routine.
`goalId`	no	Goal to link routine-created work to.
`parentIssueId`	no	Parent issue for routine-created execution issues.
`priority`	no	`critical`, `high`, `medium` default, `low`.
`status`	no	Defaults to `active` when an assignee exists, otherwise `paused`.
`concurrencyPolicy`	no	Defaults to `coalesce_if_active`.
`catchUpPolicy`	no	Defaults to `skip_missed`.
`variables`	no	Template variables for the routine title, description, and run payloads.

Agents can only create routines assigned to themselves. Board users can create routines for any agent they can assign.

Important behavior:

- `projectId`, `goalId`, and `parentIssueId` must belong to the same company.
- assigned agents must belong to the same company and must not be terminated or pending approval.
- if you mark a routine `active` without an assignee, the API will not leave it active.
- if the title or description references variables, those variables must be valid and resolvable.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/companies/company-1/routines" \
  -H "Authorization: Bearer <board-token>" \
```

```
  -H "Content-Type: application/json" \
  -d '{
    "title": "Weekly CEO briefing for {{company_name}}",
    "description": "Compile a weekly summary and prepare the next priorities.",
    "assigneeAgentId": "agent-1",
    "projectId": "project-1",
    "goalId": "goal-1",
    "priority": "medium",
    "status": "active",
    "concurrencyPolicy": "coalesce_if_active",
    "catchUpPolicy": "skip_missed",
    "variables": [
      {
        "name": "company_name",
        "label": "Company name",
        "type": "text",
        "required": true,
        "defaultValue": "EKVAAR OS"
      }
    ]
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/companies/company-1/routines", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    title: "Weekly CEO briefing for {{company_name}}",
    description: "Compile a weekly summary and prepare the next priorities.",
    assigneeAgentId: "agent-1",
    projectId: "project-1",
    goalId: "goal-1",
    priority: "medium",
    status: "active",
    concurrencyPolicy: "coalesce_if_active",
    catchUpPolicy: "skip_missed",
    variables: [
      {
```

```
      name: "company_name",
      label: "Company name",
      type: "text",
      required: true,
      defaultValue: "EKVAAR OS",
    },
  ],
 }),
});

const routine = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
  "http://localhost:3100/api/companies/company-1/routines",
  headers={
    "Authorization": f"Bearer {board_token}",
    "Content-Type": "application/json",
  },
  json={
    "title": "Weekly CEO briefing for {{company_name}}",
    "description": "Compile a weekly summary and prepare the next priorities.",
    "assigneeAgentId": "agent-1",
    "projectId": "project-1",
    "goalId": "goal-1",
    "priority": "medium",
    "status": "active",
    "concurrencyPolicy": "coalesce_if_active",
    "catchUpPolicy": "skip_missed",
    "variables": [
      {
        "name": "company_name",
        "label": "Company name",
        "type": "text",
        "required": True,
        "defaultValue": "EKVAAR OS",
      }
    ],
  },
```

)

routine = response.json()
```

<!-- /tabs -->

---

## Update Routine

```http
PATCH /api/routines/{routineId}
Content-Type: application/json
```

All create fields are updatable.

Agent access is narrower than board access:

- an agent can only update routines assigned to itself
- an agent cannot reassign a routine to a different agent
- if an agent tries to enable a routine for someone else, the API rejects it

You can use this endpoint to:

- pause or resume a routine
- change the schedule context
- move it to another project or goal
- adjust variables or priority

Trigger Types

Routines support three trigger kinds:

Schedule

```http
POST /api/routines/{routineId}/triggers
Content-Type: application/json
```
```

```json
{
  "kind": "schedule",
  "label": "Monday morning",
  "enabled": true,
  "cronExpression": "0 9 * * 1",
  "timezone": "Europe/Amsterdam"
}
```

Schedule triggers use cron plus a timezone. The server validates the cron expression and computes the next run time in that timezone.

Schedule triggers only work if the routine's required variables can be resolved. If the routine needs required variables without defaults, the schedule trigger cannot be enabled.

Webhook

```json
{
  "kind": "webhook",
  "label": "Stripe event bridge",
  "enabled": true,
  "signingMode": "bearer",
  "replayWindowSec": 300
}
```

Webhook triggers create a public URL and a secret. The public URL is returned once when the trigger is created or when the secret is rotated.

Supported signing modes in the code are:

- `bearer`
- `hmac_sha256`
- `github_hmac`
- `none`

The default is `bearer`.

Replay windows are only used for the timestamped HMAC mode and must be between 30 and 86,400 seconds. The default is 300 seconds.

API

```json
{
  "kind": "api"
}
```

API triggers do not create a public URL. They exist so the routine can be fired explicitly through the routine run endpoint.

Add Trigger

When you create a trigger, the response may include secret material for webhook triggers.

For webhook triggers, the response includes:

- `webhookUrl`
- `webhookSecret`

Treat the secret like a password. It is stored as a company secret behind the scenes and is only shown to you when the trigger is created or when the secret is rotated.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/routines/routine-1/triggers" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \
  -d '{
    "kind": "webhook",
    "label": "Webhook intake",
    "enabled": true,
    "signingMode": "bearer"
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/routines/routine-1/triggers", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    kind: "webhook",
    label: "Webhook intake",
    enabled: true,
    signingMode: "bearer",
  }),
});

const created = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
    "http://localhost:3100/api/routines/routine-1/triggers",
    headers={
        "Authorization": f"Bearer {board_token}",
        "Content-Type": "application/json",
    },
    json={
        "kind": "webhook",
        "label": "Webhook intake",
        "enabled": True,
        "signingMode": "bearer",
    },
)

created = response.json()
```

<!-- /tabs -->

Update Trigger

```http
PATCH /api/routine-triggers/{triggerId}
Content-Type: application/json
```

You can update:

- `label`
- `enabled`
- `cronExpression` and `timezone` for schedule triggers
- `signingMode` and `replayWindowSec` for webhook triggers

If you enable a schedule trigger, the routine must still have resolvable required variables.

Delete Trigger

```http
DELETE /api/routine-triggers/{triggerId}
```

Deletes the trigger permanently.

Rotate Trigger Secret

```http
POST /api/routine-triggers/{triggerId}/rotate-secret
```

Only webhook triggers can rotate secrets.

Rotation behavior:

- a new secret value is generated
- the previous secret is invalidated immediately
- the trigger keeps the same public URL
- the response includes fresh `webhookUrl` and `webhookSecret` material

This is the right endpoint to use if a secret was exposed or if you want to reissue credentials without changing the webhook URL.

Manual Run

```http
POST /api/routines/{routineId}/run
Content-Type: application/json
```

Body:

Field	Required	Notes
`source`	no	Defaults to `manual`. The code also accepts `api`.
`triggerId`	no	If present, it must belong to the routine and be enabled.
`payload`	no	Arbitrary JSON payload stored on the run.
`variables`	no	Explicit variable overrides.
`projectId`	no	Overrides the routine's project for this run.
`assigneeAgentId`	no	Overrides the routine's default assignee for this run.
`idempotencyKey`	no	Deduplicates repeated requests with the same source/trigger combination.
`executionWorkspaceId`	no	Optional workspace binding for the created issue.
`executionWorkspacePreference`	no	Optional workspace preference for the created issue.
`executionWorkspaceSettings`	no	Optional workspace settings object for the created issue.

Manual runs still obey the routine's concurrency policy. If another live execution issue already exists, the run may be marked `coalesced` or `skipped` instead of creating a new issue.

If you pass a `triggerId`, the server checks that:

- the trigger belongs to the routine
- the trigger is enabled

The endpoint returns `202 Accepted`.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/routines/routine-1/run" \
  -H "Authorization: Bearer <board-token>" \
  -H "Content-Type: application/json" \
  -d '{
    "source": "manual",
    "payload": {
      "context": "Run a one-off briefing"
    },
    "idempotencyKey": "briefing-2026-04-15"
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/routines/routine-1/run", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${boardToken}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    source: "manual",
    payload: {
      context: "Run a one-off briefing",
    },
    idempotencyKey: "briefing-2026-04-15",
  }),
});

const run = await res.json();
```

<!-- tab: Python -->

```python
import requests

response = requests.post(
```

```
    "http://localhost:3100/api/routines/routine-1/run",
    headers={
        "Authorization": f"Bearer {board_token}",
        "Content-Type": "application/json",
    },
    json={
        "source": "manual",
        "payload": {
            "context": "Run a one-off briefing",
        },
        "idempotencyKey": "briefing-2026-04-15",
    },
)

run = response.json()
```

<!-- /tabs -->

Fire Public Trigger

```http
POST /api/routine-triggers/public/{publicId}/fire
```

This endpoint is for external systems that call a routine's webhook trigger directly.

What the code checks:

- the `publicId` must match a webhook trigger
- the trigger must still be enabled
- the routine must still be `active`
- the request must satisfy the trigger's signing mode

Accepted headers depend on signing mode:

- `bearer` uses `Authorization: Bearer <secret>`
- `hmac_sha256` uses `X-EKVAAR OS-Signature` or `X-Hub-Signature-256`
- `github_hmac` uses `X-Hub-Signature-256` or `X-EKVAAR OS-Signature` plus `X-EKVAAR OS-Timestamp`
- `none` does not require a signature

For timestamped HMAC validation, the server enforces the replay window from the trigger.

Example

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->

```bash
curl -X POST "http://localhost:3100/api/routine-triggers/public/<public-id>/fire" \
  -H "Authorization: Bearer <webhook-secret>" \
  -H "Content-Type: application/json" \
  -d '{
    "payload": {
      "source": "stripe",
      "event": "invoice.paid"
    }
  }'
```

<!-- tab: JavaScript -->

```javascript
const res = await fetch("/api/routine-triggers/public/<public-id>/fire", {
  method: "POST",
  headers: {
    Authorization: `Bearer ${webhookSecret}`,
    "Content-Type": "application/json",
  },
  body: JSON.stringify({
    payload: {
      source: "stripe",
      event: "invoice.paid",
    },
  }),
});

const run = await res.json();
```

<!-- tab: Python -->

```python
```

```
import requests

response = requests.post(
    "http://localhost:3100/api/routine-triggers/public/<public-id>/fire",
    headers={
        "Authorization": f"Bearer {webhook_secret}",
        "Content-Type": "application/json",
    },
    json={
        "payload": {
            "source": "stripe",
            "event": "invoice.paid",
        }
    },
)

run = response.json()
```

<!-- /tabs -->

List Runs

```http
GET /api/routines/{routineId}/runs?limit=50
```

Returns the most recent routine run history. The limit defaults to 50 and is capped at 200.

Each run includes:

- `status`
- `source`
- `triggerId`
- `triggerPayload`
- `linkedIssueId`
- `coalescedIntoRunId`
- `failureReason`
- `completedAt`

Use this endpoint when you want to see whether a routine created a new issue, coalesced into an existing execution, or failed before creating work.

Routine Run Statuses

Routine runs use these statuses:

Status	Meaning
`received`	The run was accepted and is being processed.
`coalesced`	A live execution already existed, so this run linked to it.
`skipped`	The run did not create work. Either a live execution already existed and the concurrency policy chose to skip, or the routine's project was paused at tick time. Read `failureReason` to tell them apart — a paused project records `failureReason: "paused"` (the trigger's last result spells it out as `Skipped because the project is paused`).
`issue_created`	A new execution issue was created.
`completed`	The execution issue later moved to `done`.
`failed`	The execution issue failed, was cancelled, or the dispatch failed.

The list view also shows the current active issue for a routine when one exists.

Agent Access Rules

Agents can read routines in their company, but they can only manage routines assigned to themselves.

Operation	Agent	Board
List routines	✅	✅
Get routine details	✅	✅
Create routine	✅ own only	✅
Update routine	✅ own only	✅
Add trigger	✅ own only	✅
Update trigger	✅ own only	✅
Delete trigger	✅ own only	✅
Rotate trigger secret	✅ own only	✅
Manual run	✅ own only	✅
Fire public trigger	✅ if the HTTP signature matches	✅

Board operators need `tasks:assign` permission for actions that assign work to agents other than themselves.

Practical Notes

- A routine can have multiple triggers.
- Schedule triggers compute `nextRunAt` automatically.
- Webhook triggers mint a company secret behind the scenes.
- The public webhook URL does not change when you rotate the secret.
- If a routine is archived, it will not fire again.
- If the routine's project is paused, scheduled ticks are suppressed: the firing is recorded as a `skipped` run and the schedule advances to the next tick, but no execution issue is created and the missed tick is **not** backfilled when the project resumes.
- If a run finds an active live execution issue and the concurrency policy is not `always_enqueue`, the run is linked or skipped instead of creating new work.

If you are wiring this from code, the common path is:

1. create the routine
2. attach a schedule or webhook trigger
3. inspect the created webhook material if needed
4. list runs to confirm the routine is firing as expected

Adapters API

The adapters API is the control-plane surface for the **server-side adapter registry**: which agent runtimes EKVAAR OS can talk to, how each is configured, and how external adapter packages get installed at the instance level.

For per-adapter configuration semantics, jump to [Reference → Adapters → Overview](../adapters/overview.md). This page documents the REST endpoints.

> All routes here are mounted under `/api`. They are instance-admin / board-scoped — they shape the server itself, not a single company.

List installed adapters

```
GET /api/adapters
```

Returns the registry of server-side adapters EKVAAR OS currently knows about: built-in adapter types plus any external adapters installed on the instance.

Install an external adapter

```
POST /api/adapters/install
```

Installs an external adapter package on the instance. Used by the Adapter Manager UI and the `EKVAAR OSai adapter install` CLI workflow.

Update an adapter's instance config

```
PATCH /api/adapters/:type
```

Persists instance-level configuration for the adapter identified by `:type` (for example `claude_local`, `codex_local`, `openclaw_gateway`).

Override adapter behaviour

```
PATCH /api/adapters/:type/override
```

Sets the operator-controlled override block for an adapter — used to force-disable, pin, or otherwise override registry defaults without editing instance config directly.

Delete an installed adapter

```
DELETE /api/adapters/:type
```

Removes an external adapter from the registry. Built-in adapter types cannot be deleted.

Reload an adapter

```
POST /api/adapters/:type/reload
```

Drops and re-loads the adapter module in-place. Useful after editing on-disk config without restarting the server.

Reinstall an adapter

```
POST /api/adapters/:type/reinstall
```

Re-runs the install flow for an external adapter (re-fetch, re-extract, re-register).

Read an adapter's config schema

```
GET /api/adapters/:type/config-schema
```

Returns the JSON schema the Adapter Manager uses to render the adapter's settings form.

Adapter UI parser bundle

```
GET /api/adapters/:type/ui-parser.js
```

Serves the adapter-supplied UI parser bundle. The EKVAAR OS UI fetches this script to render run output for the adapter. The wire contract is documented in [Adapter UI Parser](../adapters/adapter-ui-parser.md).

Teams Catalog API

The teams catalog API is the control-plane surface behind catalog *teams* — the ready-made starter groups EKVAAR OS ships with the app. A catalog team bundles a small set of agents, projects, tasks, and the skills they need, so you can drop a whole working unit into a company in one step. These endpoints let you browse the catalog, inspect a single team and its files, see what is already installed in a company, preview an import, and install a team.

For the user-facing concept and CLI workflow, see [Teams Commands](../cli/teams.md) and the [Team Catalog guide](../../guides/org/team-catalog.md). This page documents the raw HTTP endpoints that those tools call.

> All routes here are mounted under `/api`. The browsing routes need only an authenticated caller and no company context; the `installed`, `preview`, and `install` routes are company-scoped and check company access.

There are two kinds of catalog teams. **Bundled** teams ship inside the app and are the everyday starting points. **Optional** teams are extras, some of which pull in skills from external sources. The `kind` filter switches between the two.

Browse the catalog

```
GET /api/teams/catalog
```

Returns the catalog teams the caller can see. Browsing reads the catalog without writing anything and requires no company context.

Query parameters

Parameter	Values	Description
`kind`	`bundled`, `optional`	Filter by catalog kind.
`category`	string	Filter by catalog category slug.
`q`	string	Free-text search over the catalog.

Each catalog team in the response carries `id`, `key`, `kind`, `category`, `slug`, `name`, `description`, `path`, `entrypoint`, `schema`, `defaultInstall`, `recommendedForCompanyTypes`, `tags`, a `counts` object (`agents`, `projects`, `tasks`, `routines`, `localSkills`, `catalogSkills`, `externalSkillSources`), `rootAgentSlugs`, `agentSlugs`, `projectSlugs`, `requiredSkills`, `envInputs`, `sourceRefs`, `files`, `trustLevel`, `compatibility`, and `contentHash`. Optional teams sourced from a package also include `packageName` and `packageVersion`.

Inspect one catalog team

```
GET /api/teams/catalog/{catalogId}
```

Returns the full record for a single catalog team — the same shape as a list entry, including its agents, projects, tasks, required skills, and file manifest. Inspecting a team before you install it is the clearest way to see exactly what will land in the company.

The path segment `{catalogId}` is a catalog reference: a catalog team ID, key, or unique slug. You can also pass the reference explicitly with the `ref` query parameter, which takes precedence over the path segment.

Query parameters

Parameter	Description
`ref`	Catalog reference (ID, key, or slug). Overrides the `{catalogId}` path segment when present.

Read a catalog team file

```
GET /api/teams/catalog/{catalogId}/files
```

Returns one file out of the catalog team package — for example `TEAM.md`. Use this to read a team's manifest or any referenced file without installing it.

Query parameters

Parameter	Description
`ref`	Catalog reference (ID, key, or slug). Overrides the `{catalogId}` path segment when present.
`path`	Relative path of the file to read inside the team package. Defaults to `TEAM.md`.

The response carries `catalogTeamId`, `path`, `kind`, `content`, `language`, and `markdown`.

List installed catalog teams

```
GET /api/companies/{companyId}/teams/catalog/installed
```

Returns the catalog teams already installed in the given company. This is the company-lensed view: it tells you which teams are present and lets a client flag teams

that have drifted out of date from the current catalog version. Company access is checked before the listing runs.

Preview an install

```
POST /api/companies/{companyId}/teams/catalog/{catalogId}/preview
```

Runs the import on the server and returns the plan without writing anything to the company. The preview reports what would be created, which skills the team needs and how they would be prepared, and any warnings or errors. Company access is checked before the preview runs.

All body fields are optional:

Field	Type	Description
`targetManagerAgentId`	string or `null`	Existing agent ID that the catalog's root agents should report to.
`targetManagerSlug`	string or `null`	Portable manager slug that the catalog's root agents should report to.
`include`	object	Portability include block selecting which entity kinds to import.
`agents`	`"all"` or array of slugs	Restrict the import to selected agent slugs.
`collisionStrategy`	`rename`, `skip`, `replace`	How to handle entities that already exist.
`nameOverrides`	object (`slug` → `name`)	Override imported entity names.
`selectedFiles`	array of strings	Restrict the import to selected portable files.
`sourcePolicy`	object	Gate external skill sources. Accepts `allowExternalSources`, `allowUnpinnedOptionalSources`, and `allowLocalPathSources` booleans.

The `{catalogId}` path segment is a catalog reference, and the `ref` query parameter overrides it when present, exactly as on the browse routes.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -X POST
"http://localhost:3100/api/companies/company-1/teams/catalog/core-exec-team/preview" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
```

```
  -d '{
    "targetManagerSlug": "cto",
    "collisionStrategy": "rename"
  }'
```
<!-- tab: JavaScript -->
```js
const res = await fetch(

"http://localhost:3100/api/companies/company-1/teams/catalog/core-exec-team/preview",
  {
    method: "POST",
    headers: {
      Authorization: `Bearer ${token}`,
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      targetManagerSlug: "cto",
      collisionStrategy: "rename",
    }),
  },
);
const plan = await res.json();
```
<!-- tab: Python -->
```py
import requests

res = requests.post(

"http://localhost:3100/api/companies/company-1/teams/catalog/core-exec-team/preview",
    headers={"Authorization": f"Bearer {token}"},
    json={
        "targetManagerSlug": "cto",
        "collisionStrategy": "rename",
    },
)
plan = res.json()
```
<!-- /tabs -->

Install a team

```
POST /api/companies/{companyId}/teams/catalog/{catalogId}/install
```

Does what `preview` shows: imports the team into the company, creating its agents, projects, and tasks, and preparing its required skills. On success the route responds with `201`. Because installing a team creates agents, the caller must be able to create agents in the company — board callers need the `agents:create` permission (local implicit and instance-admin board callers are exempt), and agent callers need an `agents:create` grant or the equivalent agent permission.

The install body accepts everything `preview` accepts, plus:

Field	Type	Description
`adapterOverrides`	object (`slug` → override)	Pin an imported agent to an adapter. Each override is an object with `adapterType` (string) and an optional `adapterConfig` object.
`secretValues`	object (`key` → `value`)	Provide values for the secret env inputs the team declares.

As with preview, `{catalogId}` is a catalog reference and the `ref` query parameter overrides it when present.

<!-- tabs: cURL, JavaScript, Python -->

<!-- tab: cURL -->
```bash
curl -X POST
"http://localhost:3100/api/companies/company-1/teams/catalog/product-engineering/install" \
  -H "Authorization: Bearer <token>" \
  -H "Content-Type: application/json" \
  -d '{
    "targetManagerSlug": "cto",
    "adapterOverrides": {
      "senior-coder": { "adapterType": "claude_local" }
    }
  }'
```
<!-- tab: JavaScript -->
```js
const res = await fetch(
```

````
"http://localhost:3100/api/companies/company-1/teams/catalog/product-engineering/install",
  {
    method: "POST",
    headers: {
      Authorization: `Bearer ${token}`,
      "Content-Type": "application/json",
    },
    body: JSON.stringify({
      targetManagerSlug: "cto",
      adapterOverrides: {
        "senior-coder": { adapterType: "claude_local" },
      },
    }),
  },
);
const result = await res.json();
```
<!-- tab: Python -->
```py
import requests

res = requests.post(

"http://localhost:3100/api/companies/company-1/teams/catalog/product-engineering/install",
    headers={"Authorization": f"Bearer {token}"},
    json={
        "targetManagerSlug": "cto",
        "adapterOverrides": {
            "senior-coder": {"adapterType": "claude_local"},
        },
    },
)
result = res.json()
```
<!-- /tabs -->

---

## Practical notes
````
````

- Catalog teams ship without a fixed adapter per agent on purpose. Use `adapterOverrides` to pin a specific agent to a runtime such as `claude_local` or `codex_local`; agents you do not override are resolved at import time.
- Browse, inspect, and file reads require only an authenticated caller. The `installed`, `preview`, and `install` routes check company access first.
- Preview writes nothing. Run it before `install` to confirm what will be created and how the team's skills will be prepared.
- The install route enforces the `agents:create` permission. If you lack it, the install is rejected before anything is created.

Plugins API

The plugins API is the REST surface behind the Plugin Manager UI and the plugin runtime bridge. It covers installation, lifecycle (enable/disable/upgrade), config, jobs, webhooks, local-folder mounts, dashboard data, and the worker-side bridge calls plugins make back to the host.

For the operator-facing walkthrough see [Administration → Plugins](../../administration/plugins.md). For the authoring SDK see [Reference → Plugins → Plugin SDK](../plugins/sdk.md).

> All routes are mounted under `/api`. Most are instance-admin operations; the company-scoped routes are explicit in the path.

Registry and discovery

Endpoint	Purpose
`GET /api/plugins`	List installed plugins on this instance.
`GET /api/plugins/examples`	List the bundled plugins discovered in the current checkout (reference examples and vendored first-party plugins). See below.
`GET /api/plugins/ui-contributions`	Aggregate of UI slots and launchers contributed by enabled plugins. The EKVAAR OS UI consumes this on page load.
`GET /api/plugins/tools`	Tools declared by enabled plugins.
`POST /api/plugins/tools/execute`	Execute a plugin-declared tool by key.

Bundled plugin discovery

`GET /api/plugins/examples` returns the plugins that ship inside the current EKVAAR OS checkout. Rather than a fixed list, the server scans the bundled packages on disk for plugin manifests, so the result reflects whatever your checkout actually contains — the

reference example plugins plus any vendored first-party plugins. The result is cached after the first scan.

Each entry has this shape:

```json
{
  "packageName": "@EKVAAR OSai/plugin-llm-wiki",
  "pluginKey": "llm-wiki",
  "displayName": "LLM Wiki",
  "description": "…",
  "localPath": "packages/plugins/…",
  "tag": "first-party",
  "experimental": true
}
```

- `tag` is `example` for the reference plugins or `first-party` for vendored real plugins.
- `experimental` is `true` for first-party plugins that aren't production-ready yet; the Plugin Manager renders these with an **Experimental** badge.
- `localPath` is what the install flow points at for an in-checkout install.

Install and lifecycle

Endpoint	Purpose
`POST /api/plugins/install`	Install a plugin package.
`GET /api/plugins/:pluginId`	Read the installed plugin record.
`DELETE /api/plugins/:pluginId`	Uninstall the plugin.
`POST /api/plugins/:pluginId/enable`	Enable the plugin; starts its worker.
`POST /api/plugins/:pluginId/disable`	Disable the plugin; stops its worker and hides UI contributions.
`POST /api/plugins/:pluginId/upgrade`	Run the upgrade flow against the plugin's source.
`GET /api/plugins/:pluginId/health`	Read the current health diagnostics reported by the plugin worker.
`GET /api/plugins/:pluginId/logs`	Read the plugin's recent worker logs.

Config

Endpoint	Purpose
`GET /api/plugins/:pluginId/config`	Read the resolved instance config.
`POST /api/plugins/:pluginId/config`	Write a new instance config.

| `POST /api/plugins/:pluginId/config/test` | Validate a candidate config without persisting it — invokes the plugin's `validateConfig` RPC. |

Jobs and webhooks

Endpoint	Purpose
`GET /api/plugins/:pluginId/jobs`	List the plugin's declared jobs.
`GET /api/plugins/:pluginId/jobs/:jobId/runs`	List recent runs for a job.
`POST /api/plugins/:pluginId/jobs/:jobId/trigger`	Manually trigger a job run.
`POST /api/plugins/:pluginId/webhooks/:endpointKey`	Inbound webhook delivery to the plugin worker's `handleWebhook`.

Local folders

Plugins can declare local-folder mounts; the UI and CLI use these endpoints to inspect and configure them per company.

Endpoint	Purpose
`GET /api/plugins/:pluginId/companies/:companyId/local-folders`	List configured local-folder mounts for the plugin/company pair.
`GET /api/plugins/:pluginId/companies/:companyId/local-folders/:folderKey/status`	Status of one mount (configured / problems / listing summary).
`POST /api/plugins/:pluginId/companies/:companyId/local-folders/:folderKey/validate`	Validate a candidate folder path without persisting.
`PUT /api/plugins/:pluginId/companies/:companyId/local-folders/:folderKey`	Persist a folder configuration for that mount.

Dashboard

Endpoint	Purpose
`GET /api/plugins/:pluginId/dashboard`	Read the dashboard payload the plugin exposes to the UI.

Worker bridge

These endpoints back the worker-to-host bridge — the calls a plugin worker makes when it asks the host for data, performs an action, or opens a stream. They are typically consumed by the runtime itself, but they are valid REST endpoints for tests and replay.

Endpoint	Purpose

`POST /api/plugins/:pluginId/bridge/data`	Resolve a `data` request the worker initiated.
`POST /api/plugins/:pluginId/bridge/action`	Resolve an `action` request the worker initiated.
`GET /api/plugins/:pluginId/bridge/stream/:channel`	Open a stream channel from the worker.
`POST /api/plugins/:pluginId/data/:key`	UI-facing entry to read a plugin's registered data feed by key.
`POST /api/plugins/:pluginId/actions/:key`	UI-facing entry to invoke a plugin's registered action by key.

> **Stability.** The plugin runtime ships in alpha. Endpoint shapes here may change between EKVAAR OS releases — pin your plugin and EKVAAR OS versions in lockstep.

Instance Admin API

A grab-bag of instance-scoped REST endpoints that don't fit neatly into the other API pages: general and experimental instance settings, on-demand database backups, the LLM reflection endpoints, environments (sandbox/runtime drivers), and execution-workspace lifecycle.

These surfaces are stable enough to call from your own tooling, but they are intentionally narrow — most operators reach them through the UI, the CLI, or via the `EKVAAR OSai doctor` command rather than by hand.

> All routes are mounted under `/api`. Most require instance-admin or board authentication; per-route notes call out exceptions.

Instance settings

Endpoint	Purpose
`GET /api/instance/settings/general`	Read general instance settings (display name, defaults, etc.).
`PATCH /api/instance/settings/general`	Update general settings. Body is validated against `patchInstanceGeneralSettingsSchema`.
`GET /api/instance/settings/experimental`	Read the experimental-features block.
`PATCH /api/instance/settings/experimental`	Toggle experimental features. Body is validated against `patchInstanceExperimentalSettingsSchema`.
`POST /api/instance/settings/experimental/issue-graph-liveness-auto-recovery/preview`	Preview what the auto-recovery sweep would change without applying.

| `POST /api/instance/settings/experimental/issue-graph-liveness-auto-recovery/run` | Run the auto-recovery sweep. |

The experimental "issue-graph-liveness auto-recovery" routes are paired: preview produces a dry-run summary; run applies the same changes. Both share the `issueGraphLivenessAutoRecoveryRequestSchema` body shape.

Database backups

```
POST /api/instance/database-backups
```

Trigger a manual database backup. Returns a structured result that includes the backup directory, retention policy, and timing. Scheduled backups follow the same code path but are not exposed as a separate route.

Instance-admin only.

Claim first instance admin

```
POST /api/bootstrap/claim
```

On a brand-new private instance that requires login, this lets the first person to sign in promote themselves to `instance_admin` — no manual database seeding. The first caller to claim wins; everyone after them is locked out.

Availability. This route only exists when the instance runs with `deploymentMode` set to `authenticated` **and** `deploymentExposure` set to `private`. On any other configuration it returns `404` with `Browser first-admin claim is not available`.

Authentication. The caller must be a signed-in browser session (a board actor whose session source is the browser). Other callers — agents, CLI tokens, unauthenticated requests — get `401` with `Sign in from a browser session before claiming first admin`.

Behaviour. If no `instance_admin` exists yet, the signed-in user is promoted to `instance_admin`. The claim is atomic — the table is locked so exactly one user can win.

If the instance has already been claimed, the route returns `409` with `Someone else has already claimed this instance`.

The request takes no body. On success the response is:

```json
{ "claimed": true, "userId": "<the promoted user's id>" }
```

LLM agent-configuration reflection

These endpoints exist so agents can introspect what server-side adapters and icons are available to them.

Endpoint	Purpose
`GET /api/llms/agent-configuration.txt`	Plain-text dump of available agent adapters and their declared shape.
`GET /api/llms/agent-configuration/:adapterType.txt`	Same, scoped to one adapter type.
`GET /api/llms/agent-icons.txt`	List of supported agent-icon names (`AGENT_ICON_NAMES`).

Access is limited to board callers and agents whose permissions include `canCreateAgents` — the routes return `403` otherwise.

Environments

Environments are the plugin-managed execution backends declared by environment-driver plugins (custom sandboxes, runners, etc.).

Endpoint	Purpose
`GET /api/companies/:companyId/environments`	List configured environments for the company.
`GET /api/companies/:companyId/environments/capabilities`	List the capabilities reported by available environment drivers.
`POST /api/companies/:companyId/environments`	Create an environment. Body validated against `createEnvironmentSchema`.

`POST /api/companies/:companyId/environments/probe-config`	Probe a candidate environment config without persisting. Body validated against `probeEnvironmentConfigSchema`.
`GET /api/environments/:id`	Read one environment.
`PATCH /api/environments/:id`	Update an environment. Body validated against `updateEnvironmentSchema`.
`DELETE /api/environments/:id`	Delete an environment.
`POST /api/environments/:id/probe`	Probe an existing environment (driver health check).
`GET /api/environments/:id/leases`	List active leases on the environment.
`GET /api/environment-leases/:leaseId`	Read a single lease.

Execution workspaces

Execution workspaces are the materialised working directories EKVAAR OS creates for an issue run.

Endpoint	Purpose
`GET /api/companies/:companyId/execution-workspaces`	List execution workspaces for the company.
`GET /api/execution-workspaces/:id`	Read one workspace.
`GET /api/execution-workspaces/:id/close-readiness`	Whether the workspace is safe to close (no pending operations, no dirty state).
`GET /api/execution-workspaces/:id/workspace-operations`	List the operations recorded against the workspace.
`PATCH /api/execution-workspaces/:id`	Update a workspace. Body validated against `updateExecutionWorkspaceSchema`.
`POST /api/execution-workspaces/:id/runtime-services/:action`	Run a runtime-service control action against the workspace.
`POST /api/execution-workspaces/:id/runtime-commands/:action`	Run a runtime-command control action against the workspace. Both routes share the `workspaceRuntimeControlTargetSchema` body and the same handler.

Related

- [Reference → Adapters API](./adapters.md) — adapter registry endpoints.
- [Reference → Plugins API](./plugins.md) — plugin install and lifecycle.

- [Reference → Deployment → Environment Variables](../deploy/environment-variables.md) — the env-vars these admin surfaces interact with.

Skills Reference

This is the reference for company skills: the file shape on disk, the install pipeline, how skills are attached to agents, scoping rules, the canonical key form, versioning, and troubleshooting.

For the conceptual introduction and the UI walkthrough, read the [Skills guide](../guides/org/skills.md). For the REST surface specifically, see [Agents API → Skills](./api/agents.md#skills).

> **Adapter caveat.** Some adapters (notably `openclaw_gateway`) cannot push skill files into the runtime. Assignment is still recorded, but the actual sync mode is reported as `unsupported`. This is covered under [Scoping rules](#scoping-rules) below.

---

1. Skill file shape

A skill is a folder containing a `SKILL.md` at its root:

```
my-skill/
├── SKILL.md
├── references/
│   └── examples.md
├── scripts/
│   └── run.sh
└── assets/
    └── logo.png
```

`SKILL.md` is YAML frontmatter plus a Markdown body:

```markdown
---
name: code-review
description: >
  Use when asked to review a pull request or code diff.
  Don't use when writing new code from scratch.
---
```

Code Review

When reviewing code, check the following...
```

The frontmatter is parsed by EKVAAR OS's own minimal YAML reader (`parseFrontmatterMarkdown` in `server/src/services/company-skills.ts`). It supports flat scalars, nested objects, and list literals — not the full YAML grammar.

Frontmatter fields

| Field | Required | Type | Notes |
|---|---|---|---|
| `name` | recommended | string | Human-readable label. Falls back to the slug when missing. |
| `description` | recommended | string | The routing logic the agent reads first. Block scalars (`>`, `\|`) are supported. |
| `slug` | optional | string | Stable kebab-case identifier. Derived from `name` (or the folder name) if absent, normalized via `normalizeAgentUrlKey`. |
| `required` | optional | boolean | Most installs leave this `false`. The server itself only treats bundled EKVAAR OS skills as required at runtime. |
| `key` / `skillKey` | optional | string | Canonical key override. See [Naming collisions](#naming-collisions-and-resolution). |
| `metadata` | optional | object | Arbitrary record persisted alongside the skill. Recognised sub-fields are listed below. |

Recognised `metadata` sub-fields (all optional):

| Path | Used for |
|---|---|
| `metadata.skillKey` / `metadata.canonicalKey` / `metadata.EKVAAR OSSkillKey` | Carry a canonical key across imports. |
| `metadata.EKVAAR OS.skillKey` / `metadata.EKVAAR OS.key` | Same, nested under a `EKVAAR OS` block. |
| `metadata.sourceKind` | One of `EKVAAR OS_bundled`, `github`, `skills_sh`, `url`, `local_path`, `project_scan`, `managed_local`, `catalog`. |
| `metadata.sources[]` | List of source descriptors written by skills.sh and similar packagers. Each entry can include `kind` (`github-dir`, `github-file`, `url`), `repo`, `path`, `commit`, `trackingRef`, `hostname`, `url`, `rawUrl`. |
| `metadata.owner` / `metadata.repo` / `metadata.ref` / `metadata.trackingRef` | GitHub coordinates used for update checks. |

Anything else under `metadata` is round-tripped untouched.

Body

After the closing `---`, write Markdown. There is no length limit, but the agent loads the entire body into context once it decides the skill is relevant — keep it short and put long material in supporting files.

Supporting files

Files placed in these subfolders are recognised and classified automatically (`classifyInventoryKind`):

Folder	Inventory kind	Trust level contribution
`references/`	`reference`	markdown only
`scripts/`	`script`	scripts/executables
`assets/`	`asset`	assets

A skill's overall **trust level** is derived from the highest classification in its inventory: `markdown_only` < `assets` < `scripts_executables`.

When importing from a project workspace where `SKILL.md` lives at the repo root (rather than a dedicated skill folder), EKVAAR OS switches to `project_root` inventory mode and only walks `references/`, `scripts/`, and `assets/` — so it does not slurp the entire repository.

Example skills you can read

Bundled with the EKVAAR OS server (`skills/` next to the server):

- `EKVAAR OS` — base heartbeat procedure.
- `EKVAAR OS-create-agent` — governance-aware hire workflow.
- `EKVAAR OS-create-plugin` — plugin scaffold flow.
- `EKVAAR OS-dev` — operating a local EKVAAR OS instance.
- `EKVAAR OS-converting-plans-to-tasks` — the EKVAAR OS way of translating a plan into assigned issues with the right specialty, dependencies, and parallelization.
- `diagnose-why-work-stopped` — forensics procedure for stalled, looping, or "went too deep" issue trees: surface the exact stop point and deliver a fix-as-rule plan gated by board approval.
- `para-memory-files` — file-based memory using Tiago Forte's PARA method, covering the knowledge-graph, daily-notes, and tacit-knowledge layers plus weekly synthesis and recall.

- `terminal-bench-loop` — bounded, human-in-the-loop driver that runs a single Terminal-Bench problem through EKVAAR OS until the smoke passes, the board rejects the next fix, or the iteration budget is exhausted.

Community examples in [`EKVAAR OSai/companies`](https://github.com/EKVAAR OSai/companies):

- `companies/skills/company-creator/SKILL.md`
- `companies/skills/readme-updater/SKILL.md`

These are the canonical references for the file shape, frontmatter style, and supporting-file layout.

Artifact upload in the bundled `EKVAAR OS` skill

The bundled `EKVAAR OS` skill ships an artifact-upload helper so that work products end up on the issue, not stranded in the agent's workspace. Its **Generated Artifacts and Work Products** section in `SKILL.md` tells the agent that whenever a run produces a user-inspectable file, it should upload that file to the current issue before final disposition — a local filesystem path is useless to board users, reviewers, and cloud operators who can't reach the agent workspace.

The skill bundles a helper script at `scripts/EKVAAR OS-upload-artifact.sh` (relative to the installed skill directory) and a reference doc at `references/artifacts.md`. The helper takes a file path plus `--title` and `--summary` flags:

```bash
scripts/EKVAAR OS-upload-artifact.sh path/to/output.webm \
  --title "Walkthrough render" \
  --summary "Rendered walkthrough for review"
```

It reads the run's environment — `EKVAAR OS_API_URL`, `EKVAAR OS_API_KEY`, `EKVAAR OS_COMPANY_ID`, `EKVAAR OS_TASK_ID`, and `EKVAAR OS_RUN_ID` — then uploads the file as an issue attachment, creates an attachment-backed artifact work product (the default), and prints issue-safe markdown links the agent can drop into its final comment. The underlying upload route is the attachment endpoint documented under [Issues API → Attachments](./api/issues.md#attachments).

---

2. Installation pipeline

Skills are installed at the **company** level. Once installed, any agent in that company can be assigned the skill.

Endpoints

Action	Endpoint
List skills	`GET /api/companies/{companyId}/skills`
Skill detail (with usage)	`GET /api/companies/{companyId}/skills/{skillId}`
Read a file from a skill	`GET /api/companies/{companyId}/skills/{skillId}/files?path=SKILL.md`
Update a file (editable skills)	`PATCH /api/companies/{companyId}/skills/{skillId}/files`
Update status (GitHub-managed)	`GET /api/companies/{companyId}/skills/{skillId}/update-status`
Pull latest commit	`POST /api/companies/{companyId}/skills/{skillId}/install-update`
Delete	`DELETE /api/companies/{companyId}/skills/{skillId}`
Create empty (EKVAAR OS-managed)	`POST /api/companies/{companyId}/skills`
Import from a source	`POST /api/companies/{companyId}/skills/import`
Scan project workspaces	`POST /api/companies/{companyId}/skills/scan-projects`

Mutating routes require either `agents:create` permission or `permissions.canCreateAgents=true` on the calling agent.

Import: accepted sources

`POST /api/companies/{companyId}/skills/import` takes one field — `source`. The string is parsed by `parseSkillImportSourceInput`, so all of the following are valid:

```json
{ "source": "https://github.com/EKVAAR OSai/EKVAAR OS" }
{ "source": "https://github.com/EKVAAR OSai/EKVAAR OS/tree/main/skills/EKVAAR OS" }
{ "source": "https://github.com/EKVAAR OSai/EKVAAR OS/blob/main/skills/EKVAAR OS/SKILL.md" }
{ "source": "EKVAAR OSai/EKVAAR OS" }
{ "source": "EKVAAR OSai/EKVAAR OS/EKVAAR OS-dev" }
{ "source": "https://skills.sh/EKVAAR OSai/EKVAAR OS/EKVAAR OS-dev" }
{ "source": "npx skills add EKVAAR OSai/EKVAAR OS --skill EKVAAR OS-dev" }
{ "source": "https://example.com/raw/SKILL.md" }
{ "source": "/Users/me/code/my-project/skills/code-review" }
```

Resolution rules:

- `owner/repo` and `owner/repo/skill` are treated as GitHub references.
- `https://skills.sh/...` URLs and `npx skills add ...` commands are unwrapped to the underlying GitHub URL — but the skill is recorded with `sourceType: skills_sh` and the original locator preserved.
- `tree/<ref>` and `blob/<ref>` URLs pin to whatever ref you pass; bare repo URLs resolve the default branch.
- Local paths can point at a single `SKILL.md` file, a folder containing one, or a folder containing many — every `SKILL.md` under it is imported.

What happens during import

1. Resolve the source (parse → fetch metadata → walk for `SKILL.md` files).
2. For each found skill: parse frontmatter, derive `slug`, derive canonical `key`, walk the file inventory, classify each entry, derive `trustLevel`.
3. Persist as a row in the `companySkills` table (one row per `(companyId, key)` — see [Naming collisions](#naming-collisions-and-resolution)).
4. Materialise files for catalog-style sources into `<EKVAAR OSInstanceRoot>/skills/{companyId}/__catalog__/<runtimeName>/` so adapters can read them.
5. Log a `company.skills_imported` activity entry and emit a `skill_imported` telemetry event.

The response includes `imported`, `warnings`, and the resolved source metadata.

Project scan

`POST /api/companies/{companyId}/skills/scan-projects` walks the local workspaces of every project in the company (or a filtered subset via `projectIds` / `workspaceIds`) and looks for `SKILL.md` files in any of these well-known locations:

- `skills/`, `skills/.curated/`, `skills/.experimental/`, `skills/.system/`
- `.agents/skills/`, `.agent/skills/`, `.augment/skills/`, `.claude/skills/`, `.codebuddy/skills/`, `.commandcode/skills/`, `.continue/skills/`, `.cortex/skills/`, `.crush/skills/`, `.factory/skills/`, `.goose/skills/`, `.junie/skills/`, `.iflow/skills/`, `.kilocode/skills/`, `.kiro/skills/`, `.kode/skills/`, `.mcpjam/skills/`, `.vibe/skills/`, `.mux/skills/`, `.openhands/skills/`, `.pi/skills/`, `.qoder/skills/`, `.qwen/skills/`, `.roo/skills/`, `.trae/skills/`, `.windsurf/skills/`, `.zencoder/skills/`, `.neovate/skills/`, `.pochi/skills/`, `.adal/skills/`
- The workspace root itself (if it contains a `SKILL.md`)

The scan is non-destructive: it returns `imported`, `updated`, `skipped`, `conflicts`, and `warnings`. Conflicts (slug or key already pointing at a different source) are surfaced for manual review rather than overwriting silently.

Storage

Editable, EKVAAR OS-managed skills are written to `<EKVAAR OSInstanceRoot>/skills/{companyId}/<slug>/`. Read-only sources (GitHub, skills.sh, URL) keep the `markdown` body in the database row and only materialise into a temporary location when an adapter needs the files on disk.

Bundled skills (the four `EKVAAR OS-*` skills shipped with the server) are re-imported from the server's `skills/` directory on every list call (`ensureBundledSkills`). They cannot be edited or deleted — installing the same EKVAAR OS release will recreate them.

---

3. App-shipped catalog

Beyond importing skills from GitHub, skills.sh, URLs, or local folders, EKVAAR OS ships its own **catalog** of ready-made skills inside the app. You browse the catalog, install the skill you want into a company, and from then on EKVAAR OS can keep that copy in step with the version it shipped — checking for updates, auditing the bytes, and resetting back to the pinned origin if needed.

Catalog skills are split into two **kinds** (`CatalogSkillKind`):

Kind	Meaning	Examples
`bundled`	Core skills the app considers part of the baseline kit.	`doc-maintenance`, `issue-triage`, `task-planning`, `qa-acceptance`, `github-pr-workflow`, `wireframe`
`optional`	Extra skills you opt into when you need them.	`agent-browser`, `release-announcement`, `design-critique`, `last30days`

Each catalog skill also carries a `category` you can filter on. Most of the baseline kit is coding- and process-oriented, but the catalog is not limited to engineering work — for example, the `product`-category **`wireframe`** skill teaches an agent to produce low-fidelity, black-and-white UI wireframes as standalone SVG files (recommended for `designer`, `product`, and `engineer` roles), and the `research`-category **`last30days`** skill (recommended for `researcher`, `marketer`, `product-manager`, and `analyst` roles) researches what people have said about a topic across Reddit, X, YouTube, and the rest of the web in the last 30 days. A bundled skill is not the same as a *required* one: `wireframe` ships in the baseline kit but installs only when you choose it (its `defaultInstall` is `false`), so designers and product folks can pull it in without it being forced on every agent.

Where a catalog skill's bytes come from. Most catalog skills are shipped inside the app itself. A few are **referenced** instead — they point at an external GitHub repository pinned to a single commit, and the app fetches their files for you. `last30days`, for

example, is sourced from `github.com/mvanhorn/last30days-skill` at a pinned commit. You install and manage a referenced skill exactly like any other catalog skill; the only difference is that its `source` field tells you where it originally came from (owner, repo, the `ref`/`commit` it is pinned to, and a browseable `url`). Because the pin is a specific commit, you still get the same byte-exact, version-tracked guarantees as a fully bundled skill.

Once installed, a catalog skill becomes an ordinary company-skill row, but it is tagged as **catalog-managed**: its `sourceType` is `catalog` and its `metadata.sourceKind` is `catalog`. The catalog kind (`bundled` / `optional`) is carried through on `metadata.catalogKind`, and the byte-exact origin it was pinned to is stored in `metadata.originHash`.

> The catalog browse routes are read-only and only require an authenticated caller. The install/audit/update/reset routes mutate the company library and therefore need `agents:create` (or `permissions.canCreateAgents=true`), exactly like the other mutating skill routes.

Browse the catalog

The catalog itself is the same for every company, so the browse routes are not company-scoped:

Action	Endpoint
List catalog skills	`GET /api/skills/catalog`
Inspect one catalog skill	`GET /api/skills/catalog/{catalogId}`
List a catalog skill's files	`GET /api/skills/catalog/{catalogId}/files`

The list route accepts three optional query filters:

- `kind` — `bundled` or `optional`.
- `category` — exact-match on the skill's category.
- `q` — free-text query matched against the skill's id, key, slug, name, description, category, kind, recommended roles, and tags.

Each catalog entry (`CatalogSkill`) carries `id`, `key`, `kind`, `category`, `slug`, `name`, `description`, `trustLevel`, `compatibility`, `defaultInstall`, `recommendedForRoles`, `requires`, `tags`, a `files[]` inventory (each with `path`, `kind`, `sizeBytes`, `sha256`), and a `contentHash` — the byte-exact identity of the shipped skill. Referenced skills (the ones fetched from an external repo) also carry an optional `source` object describing where the bytes came from: `type` (`github`), `hostname`, `owner`, `repo`, the `ref` and `commit` it is pinned to, the `path` inside the repo, and a browseable `url`.

The files route returns one file at a time. By default it reads `SKILL.md`; pass `?path=references/example.md` to read another file in the inventory. Asset files are not previewable.

Install a catalog skill

```http
POST /api/companies/{companyId}/skills/install-catalog
```

```json
{
  "catalogSkillId": "<catalog id, key, or unique slug>",
  "slug": "my-doc-maintenance",
  "force": false
}
```

- `catalogSkillId` (required) — resolves against the catalog by id, key, or a slug that is unique in the catalog.
- `slug` (optional) — override the slug the skill takes in your company library. Leave it out (or `null`) to keep the catalog slug.
- `force` (optional) — overwrite an existing row that already occupies the target slug/key.

Installing does not attach the skill to any agent. It only adds the skill to the company library, just like an import. Attach it afterwards exactly as you would any other skill — see [Assigning skills to agents](#4-assigning-skills-to-agents).

The response reports an `action` of `created`, `updated`, or `unchanged`, plus the resulting company `skill`, the source `catalogSkill`, and any `warnings`. A fresh install returns `201`; an in-place refresh returns `200`.

Keep a catalog skill current

A catalog-managed skill exposes the same `GET /skills/{skillId}/update-status` → `POST /skills/{skillId}/install-update` flow as GitHub skills, but the comparison is against the version the app currently ships rather than an upstream commit. When a newer catalog version is available, install it:

```http
POST /api/companies/{companyId}/skills/{skillId}/install-update
```

```json
```

{ "force": false }
```

Two kinds of **hold can stop an update:**

- **Soft hold — local modifications. If the installed bytes no longer match the pinned `originHash`, the update is held so you do not silently lose your edits. Rerun with `{ "force": true }` to discard the local changes and take the new version.**
- **Hard stop — audit findings. If auditing the skill returns a `fail` verdict (see below), the update is blocked outright. `force` does **not** override a hard stop.**

Audit before you trust

```http
POST /api/companies/{companyId}/skills/{skillId}/audit
```

Audit inspects the installed skill's bytes **without executing them and returns a verdict:**

| `verdict` | Meaning |
|---|---|
| `pass` | No findings. |
| `warning` | Soft findings only (for example, the skill ships a script, references a network command, or its bytes drifted from `originHash`). |
| `fail` | At least one hard-stop finding (for example, a remote-fetch-and-execute pattern, a secret-exfiltration pattern, oversized or non-text files, or a missing/invalid `SKILL.md`). |

The result also includes `codes` (the deduplicated finding codes), `installedHash`, `originHash`, and a `scanVersion`. A `fail` verdict is what hard-blocks `install-update`. Audit is only supported for local-path and catalog-managed skills.

Reset to the pinned origin

```http
POST /api/companies/{companyId}/skills/{skillId}/reset
```

```json
{ "force": false }
```

Reset restores a catalog-managed skill to the byte-exact origin it was installed from — useful when a skill was edited locally and you want the shipped version back. Reset is only supported for catalog-managed skills.

For the equivalent `EKVAAR OSai skills` CLI commands (browse, install, audit, update, reset), see the [Skills commands](./cli/skills.md) page in the CLI reference.

---

4. Assigning skills to agents

A skill must be installed at the company level before it can be attached to an agent. There are two ways to make the attachment.

At hire time — `desiredSkills`

`POST /api/companies/{companyId}/agents` and `POST /api/companies/{companyId}/agent-hires` both accept an optional `desiredSkills` array on the request body:

```json
{
  "name": "Backend Engineer",
  "adapterType": "claude_local",
  "desiredSkills": ["EKVAAR OS", "code-review", "deploy-runbook"]
}
```

Each entry can be:

- a company-skill **UUID** (`id`),
- a canonical **key** (`EKVAAR OSai/EKVAAR OS/EKVAAR OS`),
- or a **slug** (`code-review`) — but only when the slug is unique inside the company.

The server resolves each reference (`resolveRequestedSkillKeys`), unions the result with all bundled-required keys, and persists the final list under `adapterConfig.EKVAAR OSSkillSync.desiredSkills`. Unknown or ambiguous references fail the request with `Invalid company skill selection (...)`.

After hire — `POST /api/agents/{agentId}/skills/sync`

```json
{
  "desiredSkills": ["EKVAAR OS", "code-review"]
}
```

This route reconciles the agent's attachments to match exactly what you send: any skill in the list is attached, anything not in the list is detached. Bundled-required skills cannot be removed — they are always added back to the resolved set.

The response is an `AgentSkillSnapshot`:

```json
{
  "adapterType": "claude_local",
  "supported": true,
  "mode": "persistent",
  "desiredSkills": ["EKVAAR OSai/EKVAAR OS/EKVAAR OS",
"company/<id>/code-review"],
  "entries": [
    {
      "key": "EKVAAR OSai/EKVAAR OS/EKVAAR OS",
      "runtimeName": "EKVAAR OS",
      "desired": true,
      "managed": true,
      "required": true,
      "state": "installed",
      "origin": "EKVAAR OS_required"
    }
  ],
  "warnings": []
}
```

The full schema is in `packages/shared/src/validators/adapter-skills.ts`.

Inspecting current state

```http
GET /api/agents/{agentId}/skills
```

Returns the same snapshot shape without changing anything. For adapters without a `listSkills` implementation, the snapshot is built from the persisted preference and marked `mode: "unsupported"`.

5. Scoping rules

Company-scoped, not org-scoped. Skills live at the company level. Every agent inside the same company can be assigned any installed skill. There is no per-team or per-role scoping built in — granularity is controlled by which keys end up in each agent's `desiredSkills`.

No cross-company sharing. A skill installed in Company A is invisible to Company B. To use the same skill in two companies, install the source twice — once into each. The two installs each get their own `companySkills` row and are versioned independently.

Adapter sync mode controls visibility at runtime. The snapshot returned by `GET /api/agents/{agentId}/skills` reports a `mode`:

Mode	Behaviour
`persistent`	The adapter writes skill files into the agent's working directory and leaves them there between runs. Most local adapters use this mode.
`ephemeral`	The adapter materialises skill files for each run and cleans up afterwards. Default for sandboxed adapters.
`unsupported`	EKVAAR OS records the assignment but cannot push files into the runtime. Adapters such as `openclaw_gateway` fall here — manage skills inside the remote runtime instead.

Adapters declare which materialisation strategy they need via `requiresMaterializedRuntimeSkills` (or fall back to a legacy hardcoded set: `cursor`, `gemini_local`, `opencode_local`, `pi_local`).

Bundled skills are always available. `EKVAAR OS` and any other skill marked `EKVAAR OS_bundled` are forced into every agent's resolved set, regardless of `desiredSkills`. This is enforced in `resolveDesiredSkillAssignment`.

Required vs. optional in the UI. The Agent → Skills tab splits the company library into three groups:

- **Required** — bundled-required skills the adapter cannot drop.
- **Optional** — every other installed skill, opt-in via checkbox.
- **Unmanaged** — read-only entries surfaced when an adapter reports skills it discovered itself (for example, a global skills bundle on the host machine).

---

6. Skill vs. plugin vs. adapter

These three extension points are easy to confuse. They sit at different layers:

	Skill	**Plugin**	**Adapter**
What it is	An instruction document the agent loads on demand	A code package that adds API routes, UI surfaces, or runtime services	A bridge between EKVAAR OS and an agent runtime
Format	Folder with `SKILL.md` plus optional `references/`, `scripts/`, `assets/`	Node package built against the plugin SDK	Module with `executeRun`, `listSkills`, `syncSkills`, etc.
Lives at	Company level, in the company skill library	Instance level, in `~/.EKVAAR OS/adapter-plugins/`	Built into the server or registered as an external adapter
Loaded	At the start of an agent run, when the routing description matches	On server start; mounted into the API and UI	Per-run, when an agent's `adapterType` matches
Authored by	Anyone who can edit the company skill library	Plugin authors (use the [`EKVAAR OS-create-plugin` skill](https://github.com/EKVAAR OSai/EKVAAR OS/blob/main/skills/EKVAAR OS-create-plugin/SKILL.md))	Adapter authors (see [Creating an Adapter](./adapters/creating-an-adapter.md))
Versioning	Pinned to a git commit (GitHub/skills.sh) or live (local)	Pinned by the plugin's package version	Pinned by the EKVAAR OS release
Failure mode if wrong	Agent reads bad instructions, produces bad output	API surface does not load	Runs fail to start

Rule of thumb: **a skill is something a smart human could follow if you handed them the file**; a plugin is server code; an adapter is the wire protocol to a runtime.

---

7. Naming collisions and resolution

Canonical key

Every persisted skill has a `key` field — the unique identifier for that skill inside the company. Keys are derived by `deriveCanonicalSkillKey` and follow these forms:

Source	Key form	Example
Bundled with EKVAAR OS	`EKVAAR OSai/EKVAAR OS/{slug}`	`EKVAAR OSai/EKVAAR OS/EKVAAR OS`
GitHub / skills.sh	`{owner}/{repo}/{slug}`	`EKVAAR OSai/EKVAAR OS/EKVAAR OS-dev`
URL	`url/{host}/{hash}/{slug}`	`url/example.com/9f2a3b1c4d/code-review`
Local path (project scan, raw folder)	`local/{hash}/{slug}`	`local/4e8a91c2d3/code-review`

| EKVAAR OS-managed (created from the UI) | `company/{companyId}/{slug}` | `company/5cbe79ee.../delegation-checklist` |

If the source provides an explicit `key` / `metadata.skillKey`, that value wins — this is how skills.sh-published skills keep a stable identity across mirrors.

Reference resolution

When you pass a skill reference (in `desiredSkills`, in the sync route, anywhere), the server tries to match in this order (`resolveSkillReference`):

1. Exact UUID match on `id`.
2. Normalised `key` match.
3. Normalised `slug` match — but **only when exactly one skill in the company has that slug**.

If a slug matches multiple skills, the request fails with:

```
Invalid company skill selection (ambiguous references: <slug>; ...)
```

For an unknown reference:

```
Invalid company skill selection (unknown references: <reference>; ...)
```

To make a script idempotent across companies, prefer canonical `key` over slug.

Project-scan conflicts

When the project scanner discovers a `SKILL.md` whose canonical key already exists with a different source path, it does **not** overwrite the row. Instead, the response contains a `conflicts[]` entry with `existingSkillId`, `existingSourceLocator`, and a human-readable `reason`. The same applies when a different skill has already taken the slug. Resolve conflicts by deleting one of the duplicates or by editing the `name`/`slug` of the new one and re-scanning.

Slug normalisation

Slugs are normalised through `normalizeAgentUrlKey`: lowercase, hyphen-separated, no whitespace or punctuation. `Code Review`, `code_review`, and `Code--Review` all resolve to `code-review`.

---

8. Versioning semantics

Behaviour depends on the source:

Source	Pinned?	Update path	Notes
`github`	Yes — `sourceRef` stores the resolved commit SHA	`GET /skills/{id}/update-status` → `POST /skills/{id}/install-update`	`metadata.trackingRef` records the branch or tag; updates compare the latest commit on that ref against the pinned SHA.
`skills_sh`	Yes (resolves to GitHub under the hood)	Same as `github`	The original `skills.sh/...` URL is preserved in `sourceLocator` so the badge and label stay correct.
`url`	No	None	Treat as a point-in-time snapshot. Re-import the URL to refresh.
`local_path` (managed)	Live	None — files refresh on read	Stored under `<EKVAAR OSInstanceRoot>/skills/{companyId}/`. Edited via `PATCH /skills/{id}/files`.
`local_path` (project scan)	Live	Re-run the scan endpoint	Skills whose `SKILL.md` disappears are pruned automatically (`pruneMissingLocalPathSkills`).
`EKVAAR OS_bundled`	Pinned to the EKVAAR OS release	Upgrade EKVAAR OS itself	Re-imported on every list call; cannot be edited.
`catalog`	Pinned to the shipped catalog version (`metadata.originHash`)	`GET /skills/{id}/update-status` → `POST /skills/{id}/install-update`; `POST /skills/{id}/reset` to restore the origin	App-shipped catalog skills. Updates compare against the version the app ships. See [App-shipped catalog](#3-app-shipped-catalog).

`update-status` response

```json
{
  "supported": true,
  "reason": null,
  "trackingRef": "main",
  "currentRef": "9f2a3b1c4d8e7f6a5b4c3d2e1f0a9b8c7d6e5f4a",
  "latestRef": "0a1b2c3d4e5f6a7b8c9d0e1f2a3b4c5d6e7f8a9b",
  "hasUpdate": true
}
```

For non-GitHub sources, `supported: false` is returned with a reason. Calling `install-update` on an unsupported skill rejects with `422 Unprocessable Entity`.

Install-update semantics

`install-update` re-runs the import for the same source URL, finds the matching skill (by canonical key or slug), upserts the row in place, and returns the refreshed record. The skill's `id` does not change — anything attached by ID continues to work without re-syncing.

9. Troubleshooting: why a skill isn't loading

Walk down this list in order. The first match is usually the problem.

"I imported the skill but it's not in the list"

- Refresh — `GET /companies/{companyId}/skills` triggers `ensureSkillInventoryCurrent`, which prunes missing local skills and re-imports bundled ones. The UI auto-refreshes; an API caller may need an explicit re-list.
- Check `compatibility` on the skill row. Anything other than `compatible` is hidden from agent selectors.
- Project-scan imports may have hit a slug or key conflict — read `conflicts[]` from the scan response, not just `imported[]`.

"I assigned the skill but the agent doesn't see it"

- Inspect the agent's snapshot: `GET /api/agents/{agentId}/skills`.
- If `mode: "unsupported"`, the adapter cannot push skills into the runtime. The assignment is recorded but no files are written. Manage skills in the remote runtime (e.g. OpenClaw) directly.
- If `mode: "ephemeral"`, files appear only during runs — if the agent isn't running, the workspace will look empty. This is correct behaviour.
- Look for `warnings` on the snapshot — sync errors, missing files, and adapter-rejected entries surface there.

"Invalid company skill selection (ambiguous/unknown references)"

- You passed a slug that matches multiple skills, or a key/UUID/slug that matches none. Switch to the canonical `key` for unambiguous lookup. List skills first if you need to find the key.

"The skill row exists but the file viewer shows nothing"

- Local-path skill: the source folder probably moved. The row will be pruned on the next list call. Re-import from the new path.

- GitHub skill: a commit older than the current `sourceRef` may have been force-pushed away. Re-run `update-status` and `install-update`.

"GitHub skill is stuck on an old commit"

- `update-status` reports `hasUpdate: false`? You're already on the latest commit of the tracked ref. To follow a different ref (e.g. switch from `main` to a tag), re-import the source URL with the explicit `tree/<ref>` path. The new install replaces the old row by canonical key.
- `install-update` returned a 422? The source no longer parses (e.g. someone deleted the `SKILL.md` upstream). Pin manually via a `tree/<sha>/...` URL or remove the skill.

"Frontmatter changes aren't taking effect"

- EKVAAR OS's YAML reader is intentionally strict-but-narrow. If a value is silently empty, check that:
  - The block starts and ends with `---` on their own lines.
  - Indentation uses spaces, not tabs.
  - List items use `- ` with a space.
  - Block scalars (`>`, `|`) are indented two spaces deeper than the key.
- Recover by validating the YAML in a normal parser; if it parses there but not in EKVAAR OS, file a bug — the in-house parser is documented above.

"An agent gets a skill it never asked for"

- It's bundled-required. `EKVAAR OSai/EKVAAR OS/*` skills with `metadata.sourceKind: EKVAAR OS_bundled` are unioned into every resolved `desiredSkills` set by the server. Removing them from the request has no effect.

"I deleted a skill and it came back"

- It's a bundled skill. The server re-imports `skills/` from disk on every company list call. To suppress a bundled skill, remove it from the EKVAAR OS release or run a forked build.

See also

- [Skills guide](../guides/org/skills.md) — UI walkthrough, file inventory, trust levels, write-a-good-skill checklist.
- [Agents API → Skills](./api/agents.md#skills) — request/response shapes for `GET /agents/{id}/skills` and `POST /agents/{id}/skills/sync`.
- [Adapters reference](./adapters/overview.md) — which adapters support `persistent`, `ephemeral`, or `unsupported` skill sync.

- [Creating an Adapter](./adapters/creating-an-adapter.md) — implementing `listSkills` / `syncSkills` for a new runtime.

LLM Wiki

If you want a cited, in-dashboard wiki that your agents build and maintain from raw source material — EKVAAR OS issues, comments, documents, and files you drop into a folder — the `@EKVAAR OSai/plugin-llm-wiki` plugin is the surface that does it. It captures sources into a local folder, lets agents ingest them into markdown pages with backlinks and provenance, and ships a Wiki page inside EKVAAR OS so you (and the agents) can browse the result.

This page is for **operators** who want to enable and configure the plugin.

> The LLM Wiki plugin is in alpha alongside the plugin runtime itself. Expect breaking changes between EKVAAR OS releases and pin your version when you depend on it.

Quick install

The plugin ships as a published npm package, so any EKVAAR OS install (Docker, systemd, bare-metal — all the same) can pull it in with one command from a host that has your EKVAAR OS CLI configured:

```sh
EKVAAR OSai plugin install @EKVAAR OSai/plugin-llm-wiki
```

Or from the dashboard: **Settings → Plugins → Install Plugin**, paste `@EKVAAR OSai/plugin-llm-wiki`, submit.

The plugin won't appear in `EKVAAR OSai plugin examples` — that command only lists the four built-in reference *example* plugins, not the full catalogue of first-party plugins. Install LLM Wiki by full package name.

If you're running from a monorepo checkout, see [Develop a plugin locally](../../how-to/develop-a-plugin-locally.md) and point the installer at `packages/plugins/plugin-llm-wiki` instead.

> **Heads up (v2026.517.0):** the packaged plugin now ships with all the bootstrap assets (templates, agent instruction files, and migrations) inside the published tarball, so first-enable no longer leaves you staring at an unexpanded wiki root. The bootstrap template that scaffolds `wiki/index.md`, `wiki/log.md`, and the canonical folder layout is

the same one used in dev. If you upgrade from an older release, re-run the **Bootstrap** action from the plugin settings to materialise any newly required files — existing files are preserved.

The first enable asks for a fairly broad capability set — including `local.folders`, the `database.namespace.*` family, `agents.managed`, `skills.managed`, `routines.managed`, and `ui.page.register` — because the plugin owns a managed agent, project, routines, skills, REST routes, and a database namespace. Review the Permissions card on the plugin detail page before approving.

What you get

Once the plugin is installed and enabled, three things show up in the EKVAAR OS UI:

- **A Wiki sidebar entry** (slot id `wiki-sidebar`, order `35`) that takes you to the plugin page.
- **A Wiki page** mounted at the `wiki` route inside the plugin's company-scoped namespace (slot id `wiki-page`). This is where you browse pages, capture sources, kick off query sessions, and inspect operations.
- **A Wiki route sidebar** (slot id `wiki-route-sidebar`) for navigating between spaces and pages while you're inside the wiki.

Behind the scenes the plugin also registers:

- A managed agent — the **Wiki Maintainer** (`agentKey: wiki-maintainer`, role `knowledge-maintainer`) — that owns ingest, query, lint, and index work.
- A managed project — **LLM Wiki** (`projectKey: llm-wiki`) — that collects the plugin's operation issues.
- Three managed routines, all paused by default: `cursor-window-processing` (process EKVAAR OS issue-history windows), `nightly-wiki-lint` (audit pages for orphans, stale provenance, and contradictions), and `index-refresh` (rebuild `wiki/index.md`).
- A bundle of managed skills installed for the maintainer agent: `wiki-maintainer`, `wiki-ingest`, `wiki-query`, `wiki-lint`, `EKVAAR OS-distill`, and `index-refresh`.

The routines ship paused so nothing fires until you decide it should. Enable them from the plugin's settings or from the standard managed-routines surface.

The wiki root folder

The plugin declares one local folder mount — the **Wiki root** (`folderKey: wiki-root`, `access: readWrite`). Everything the wiki produces or reads lives there.

When you bootstrap the folder (via the plugin's settings page, or the `bootstrap` / `bootstrap-space` API routes), the plugin creates the following layout:

```text
<wiki-root>/
  AGENTS.md
  IDEA.md
  wiki/
    index.md
    log.md
    sources/
    projects/
    entities/
    concepts/
    synthesis/
  raw/
```

`AGENTS.md` and `IDEA.md` are control files — they hold the maintainer agent's instructions and the company's stated direction. They're protected: agent tool writes can't overwrite them, only operator edits can. `wiki/log.md` is the rolling audit trail every routine appends to. `raw/` holds captured source material before it becomes a durable page.

Bootstrap preserves existing files rather than overwriting them, so it's safe to re-run after you've started editing.

Spaces

A single wiki root can host multiple **spaces** — independent wiki bodies under one configured folder. The plugin always provisions a `default` space (slug: `default`) and lets you create more via the `POST /spaces` route or the settings UI. Each space gets its own `wiki/`, `raw/`, page index, and operation history.

One thing to know up front: **EKVAAR OS-derived ingestion always writes into the `default` space.** The cursor-window, distill, and backfill flows are not yet space-aware, so non-default spaces stay on manual or raw-file ingest for now. Per-space EKVAAR OS ingestion profiles are tracked as a later phase.

The space table itself is provisioned through the plugin's `003_spaces.sql` migration, which is now validated and applied through namespace-safe SQL. The plugin runtime refuses migrations that escape the plugin's database namespace, so a faulty migration fails at install time with a clear error instead of polluting the host schema.

Capturing sources and building pages

The plugin offers two paths from raw material to a wiki page:

****Manual capture.** Drop files into `<wiki-root>/raw/` (or call the `POST /sources` route — `routeKey: capture-source`) to register them as a captured source with metadata in the plugin's database namespace. From there an agent — typically the Wiki Maintainer running the `wiki-ingest` skill — turns the raw source into a cited markdown page under `wiki/concepts/`, `wiki/entities/`, `wiki/synthesis/`, or a project folder.**

****EKVAAR OS event ingestion.** Opt in to company-scoped ingestion of EKVAAR OS issues, comments, and documents. It is **disabled by default**. When you enable it, the plugin's worker watches host events, captures eligible content into the default space's `raw/`, and lets the maintainer agent distill it into project pages. The defaults cap per-source size at 12,000 characters for issues, 60,000 for cursor windows, and 120,000 for routine runs.**

Pages are plain markdown on disk. The plugin indexes them in its database namespace (`namespaceSlug: llm_wiki`) for search, backlinks, and revision history, and uses EKVAAR OS's local-folder API for path containment, symlink checks, and atomic writes. Two files are reserved: `AGENTS.md` and `IDEA.md` cannot be written through agent tools.

Tools agents can call

When the maintainer agent (or any agent you grant `pluginTools: [EKVAAR OSai.plugin-llm-wiki]`) runs, the plugin exposes a focused tool surface for working with the wiki:

| Tool | What it does |
|---|---|
| `wiki_search` | Full-text search across page and source metadata in one space. |
| `wiki_list_pages` | Return the indexed page list for a space. |
| `wiki_read_page` | Read a markdown page. |

`wiki_write_page`	Atomic page write, with optional `expectedHash` for stale-write protection.
`wiki_propose_patch`	Return a structured proposed write without changing files — useful for review flows.
`wiki_list_sources` / `wiki_read_source`	Inspect captured raw material before citing it.
`wiki_list_backlinks`	Find pages that link to a given page.
`wiki_update_index`	Atomically replace `wiki/index.md`.
`wiki_append_log`	Append a maintenance note to `wiki/log.md`.

Each tool takes `companyId`, `wikiId`, and (optionally) `spaceSlug`. Operation agents should pass the issue's `spaceSlug`; omitting it falls back to the `default` space.

REST routes

The plugin mounts these routes under its plugin namespace (auth column shows which actor can hit each one):

Method & path	Route key	Auth
`GET /overview`	`overview`	board-or-agent
`POST /bootstrap`	`bootstrap`	board
`POST /sources`	`capture-source`	board-or-agent
`GET /spaces`	`spaces`	board-or-agent
`POST /spaces`	`create-space`	board
`PATCH /spaces/:spaceSlug`	`update-space`	board
`POST /spaces/:spaceSlug/bootstrap`	`bootstrap-space`	board
`POST /spaces/:spaceSlug/archive`	`archive-space`	board
`GET /operations`	`operations`	board-or-agent
`POST /query-sessions`	`start-query`	board
`POST /file-as-page`	`file-as-page`	board

`board`-auth routes are operator actions; `board-or-agent` routes are safe for the maintainer agent to call as part of a routine.

Tips and common use cases

- **Start with one space.** The default space is enough to evaluate the plugin. Add spaces only when you have a separate body of knowledge that should not co-mingle with the rest.

- **Keep the routines paused until you have a wiki root configured.** The maintainer agent will create operation issues, but its tools will refuse writes until the folder bootstrap is complete.
- **Edit `IDEA.md` yourself.** It's the place the maintainer reads to understand the company's direction; treat it as an operator-curated document, not an agent-managed one.
- **Use `wiki_propose_patch` for review flows.** If you want operator-in-the-loop edits, route the maintainer through proposed patches instead of direct writes and approve them via the operation issue.
- **Watch `wiki/log.md`.** Every routine appends a short entry there — orphan counts, source windows processed, index refresh times. It's the fastest way to see what the maintainer has been up to.

Related

- [Administration → Plugins](../../administration/plugins.md) — the operator-facing Plugin Manager.
- [How-to → Develop a plugin locally](../../how-to/develop-a-plugin-locally.md) — point EKVAAR OS at a local checkout of the plugin.
- [Reference → Plugin SDK](./sdk.md) — the authoring surface, if you want to extend the wiki plugin or write your own.

Plugin SDK

`@EKVAAR OSai/plugin-sdk` is the worker-side authoring kit for EKVAAR OS plugins. Import it from your plugin's worker entrypoint to declare a plugin, subscribe to host events, register jobs and data feeds, run RPC against the host, and reach the managed database, secrets, state, and the rest of the EKVAAR OS API surface.

This page is for **plugin authors**: the developers writing the code that ships inside a plugin package. If you only run plugins — install, configure, enable, disable — you want [Administration → Plugins](../../administration/plugins.md) instead.

> The plugin runtime is in alpha. The SDK still ships breaking changes between EKVAAR OS releases; pin your `@EKVAAR OSai/plugin-sdk` and `@EKVAAR OSai/shared` versions and re-read this page when you upgrade.

When to use

Reach for the plugin SDK when you want to:

- Add a long-running worker that reacts to EKVAAR OS events (`issue.created`, `agent.run.completed`, …).
- Expose new pages, widgets, launchers, or settings inside the EKVAAR OS UI.
- Register scheduled jobs, webhooks, tools, or managed agents and routines.
- Ship a managed database namespace alongside your plugin code.
- Bridge a new environment driver (custom sandbox / execution backend) into EKVAAR OS.

When not to use

- **Teaching EKVAAR OS a new AI runtime.** Use an [adapter](../adapters/creating-an-adapter.md) instead — adapters speak the per-run wire protocol; plugins extend the server.
- **Adding instructions an agent should follow.** Write a [company skill](../../how-to/write-a-company-skill.md) — those are markdown an agent loads at run time, not server code.
- **One-off scripts.** A plugin needs to be installed, enabled, and managed. For ad-hoc automation, prefer the REST API or the CLI.

Package surface

The SDK package exposes two entrypoints:

- `@EKVAAR OSai/plugin-sdk` — the worker-side surface documented on this page. Default for `definePlugin`, `runWorker`, `PluginContext`, the protocol helpers, and all manifest/protocol types.
- `@EKVAAR OSai/plugin-sdk/ui` — UI-bundle surface for plugin UI contributions. Out of scope for this page; see [Administration → Plugins](../../administration/plugins.md) for the operator-facing view.

All identifiers below are exported from `@EKVAAR OSai/plugin-sdk`. They are the source of truth — copy names verbatim.

Public API

Plugin definition

Export	What it is	Use it when

`definePlugin`	Factory that wraps a `PluginDefinition` into a `EKVAAR OSPlugin`. Default-export the result from your worker entrypoint.	Always — every plugin worker starts with `definePlugin({...})`.
`runWorker`	Boots the worker JSON-RPC loop against the supplied plugin and `import.meta.url`.	At the bottom of your worker entrypoint, after `definePlugin`.
`startWorkerRpcHost`	Lower-level entry that returns a `WorkerRpcHost` you can manage yourself (for tests or custom harnesses).	Embedding the worker in a non-default transport (e.g. an in-process test).

Types: `PluginDefinition`, `EKVAAR OSPlugin`, `PluginHealthDiagnostics`, `PluginConfigValidationResult`, `PluginWebhookInput`, `PluginApiRequestInput`, `PluginApiResponse`, `RunWorkerOptions`, `WorkerRpcHostOptions`, `WorkerRpcHost`.

Plugin context

`PluginContext` is the parameter your `setup(ctx)` receives. It exposes one client per concern, all imported from `@EKVAAR OSai/plugin-sdk` as types:

Client	Purpose
`PluginConfigClient`	Read and observe the plugin's resolved instance config.
`PluginLocalFoldersClient`	Inspect and configure declared local-folder mounts (`PluginLocalFolderStatus`, `PluginLocalFolderListing`, `PluginLocalFolderProblem`).
`PluginEventsClient`	Subscribe to host events (`ctx.events.on(...)`).
`PluginJobsClient`	Register handlers for declared jobs (`ctx.jobs.register(...)`).
`PluginLaunchersClient`	Register launcher render and action handlers (`PluginLauncherRegistration`).
`PluginHttpClient`	Outbound HTTP, host-policed.
`PluginSecretsClient`	Resolve secret refs declared in instance config.
`PluginActivityClient`	Append `PluginActivityLogEntry` rows to the host activity log.
`PluginStateClient`	Scoped key-value state under a `ScopeKey`.
`PluginEntitiesClient`	Upsert and query plugin-owned entities (`PluginEntityUpsert`, `PluginEntityQuery`, `PluginEntityRecord`).
`PluginProjectsClient`, `PluginExecutionWorkspacesClient`, `PluginCompaniesClient`, `PluginIssuesClient`, `PluginIssueRelationsClient`, `PluginIssueSummariesClient`, `PluginAgentsClient`, `PluginAgentSessionsClient`, `PluginGoalsClient`, `PluginSkillsClient`	Read/write access to the core EKVAAR OS domain via the host.
`ctx.routines`	Resolve and reconcile plugin-managed EKVAAR OS routines (`ctx.routines.managed`). Requires the `routines.managed` capability. The interface type is not currently re-exported as a name, but it is reachable from `PluginContext`.
`PluginDataClient`	Register data feeds the UI can query (`ctx.data.register(...)`).
`PluginActionsClient`	Register host-invokable actions.
`PluginStreamsClient`	Stream-style host APIs.

`PluginToolsClient`	Register tool implementations declared in the manifest (`ToolRunContext`, `ToolResult`).
`PluginMetricsClient`, `PluginTelemetryClient`	Emit metrics and telemetry.
`PluginLogger`	Structured logger (`ctx.logger.info/warn/error`).
`PluginDatabaseClient`	Access the managed Postgres namespace declared for the plugin.

Issue-domain helpers: `PluginIssueMutationActor`, `PluginIssueRelationSummary`, `PluginIssueCheckoutOwnership`, `PluginIssueWakeupResult`, `PluginIssueWakeupBatchResult`, `PluginIssueRunSummary`, `PluginIssueApprovalSummary`, `PluginIssueCostSummary`, `PluginBudgetIncidentSummary`, `PluginIssueInvocationBlockSummary`, `PluginIssueOrchestrationSummary`, `PluginIssueSubtreeOptions`, `PluginIssueAssigneeSummary`, `PluginIssueSubtree`, `IssueDocumentSummary`.

Workspace metadata for `ctx.executionWorkspaces`: `PluginExecutionWorkspaceMetadata`.

Agent-session helpers: `AgentSession`, `AgentSessionEvent`, `AgentSessionSendResult`.

Workspace, event, and scope helpers: `PluginWorkspace`, `PluginEvent`, `EventFilter`, `ScopeKey`, `PluginJobContext`.

Manifest types

Plugin manifests are validated against types re-exported from `@EKVAAR OSai/shared`. Importing them from the SDK gives you a single dependency:

Type	Declares
`EKVAAR OSPluginManifestV1`	Top-level manifest shape.
`PluginJobDeclaration`	Scheduled / triggered job.
`PluginWebhookDeclaration`	Inbound webhook endpoint.
`PluginToolDeclaration`	Tool exposed to agents.
`PluginEnvironmentDriverDeclaration`	Environment / sandbox driver.
`PluginManagedAgentDeclaration` (+ `PluginManagedAgentResolution`)	Plugin-managed agent.
`PluginManagedProjectDeclaration` (+ `PluginManagedProjectResolution`)	Plugin-managed project.
`PluginManagedRoutineDeclaration` (+ `PluginManagedRoutineResolution`)	Plugin-managed routine.
`PluginManagedSkillDeclaration` (+ `PluginManagedSkillFileDeclaration`, `PluginManagedSkillResolution`)	Plugin-managed company skill.

`PluginUiDeclaration` (+ `PluginUiSlotDeclaration`)	UI surfaces.
`PluginLauncherDeclaration` (+ `PluginLauncherActionDeclaration`, `PluginLauncherRenderDeclaration`)	Launcher placements and behaviour.
`PluginDatabaseDeclaration`	Managed Postgres namespace.
`PluginApiRouteDeclaration` (+ `PluginApiRouteCompanyResolution`)	Plugin-mounted REST routes.
`PluginLocalFolderDeclaration`	Local-folder mounts surfaced via `PluginLocalFoldersClient`.
`PluginMinimumHostVersion`	Required host version range.
`PluginCompanySettings`, `PluginRecord`, `PluginDatabaseNamespaceRecord`, `PluginMigrationRecord`, `PluginConfig`, `CompanySkill`, `PluginManagedResourceKind`, `PluginManagedResourceRef`	Persisted records and shared building blocks.

Constant enum types: `PluginStatus`, `PluginCategory`, `PluginCapability`, `PluginUiSlotType`, `PluginUiSlotEntityType`, `PluginLauncherPlacementZone`, `PluginLauncherAction`, `PluginLauncherBounds`, `PluginLauncherRenderEnvironment`, `PluginStateScopeKind`, `PluginJobStatus`, `PluginJobRunStatus`, `PluginJobRunTrigger`, `PluginWebhookDeliveryStatus`, `PluginDatabaseCoreReadTable`, `PluginDatabaseMigrationStatus`, `PluginDatabaseNamespaceMode`, `PluginDatabaseNamespaceStatus`, `PluginApiRouteAuthMode`, `PluginApiRouteCheckoutPolicy`, `PluginApiRouteMethod`, `PluginEventType`, `PluginBridgeErrorCode`, `JsonSchema`.

Managed resources

"Managed resources" is the umbrella term for plugin-owned EKVAAR OS records that the host materialises per company: managed **agents**, **projects**, **routines**, and **skills**. You declare them once on the manifest under top-level `agents[]`, `projects[]`, `routines[]`, and `skills[]`, and the host creates, relinks, or returns the existing record for the current `companyId` at runtime.

Reach for managed resources when your plugin needs durable business objects the operator should see in the board — a named worker, a stable project home for plugin-generated issues, a recurring routine that produces visible task trails, or a reusable skill surfaced on managed agents. Keep `jobs[]` for plugin runtime maintenance that does not need a board-visible task trail.

Each kind requires its own capability (`agents.managed`, `projects.managed`, `routines.managed`, `skills.managed`) and is reached through a dedicated client on `PluginContext`:

```ts
await ctx.projects.managed.reconcile("research", companyId);
```

```
await ctx.agents.managed.reconcile("researcher", companyId);
await ctx.routines.managed.reconcile("weekly-brief", companyId);
await ctx.skills.managed.reconcile("weekly-brief-skills", companyId);
```

The relevant methods are `get()`, `reconcile()`, and `reset()` — plus `update()` and `run()` on routines. `reconcile()` creates the missing resource, relinks a recoverable binding, or returns the existing resource. `reset()` reapplies the manifest defaults when the operator wants to restore the plugin's suggested configuration.

Dependencies between managed resources are declared with `PluginManagedResourceRef` — for example a routine's `assigneeRef` and `projectRef`. Reconcile the referenced agent and project before reconciling the routine; if a ref is still missing, the routine resolution reports `missing_refs` instead of guessing.

Keys are stable identity. Renaming `agentKey`, `projectKey`, `routineKey`, or `skillKey` after publishing creates a new managed resource from the host's point of view.

For the full manifest example and authoring rules, see the parent `doc/plugins/PLUGIN_AUTHORING_GUIDE.md`; the declaration types listed under [Manifest types](#manifest-types) above are the source of truth for what each managed entry accepts.

JSON-RPC protocol

The SDK speaks JSON-RPC 2.0 between host and worker. Most plugin authors never call these directly, but they are exported for advanced use (custom transports, tests, replay tools).

Helpers and constants:

- `JSONRPC_VERSION`, `MESSAGE_DELIMITER`
- `JSONRPC_ERROR_CODES`, `PLUGIN_RPC_ERROR_CODES`
- `HOST_TO_WORKER_REQUIRED_METHODS`, `HOST_TO_WORKER_OPTIONAL_METHODS`
- `createRequest`, `createSuccessResponse`, `createErrorResponse`, `createNotification`
- `isJsonRpcRequest`, `isJsonRpcNotification`, `isJsonRpcResponse`, `isJsonRpcSuccessResponse`, `isJsonRpcErrorResponse`
- `serializeMessage`, `parseMessage`
- `JsonRpcParseError`, `JsonRpcCallError`

Protocol types: `JsonRpcId`, `JsonRpcRequest`, `JsonRpcSuccessResponse`, `JsonRpcError`, `JsonRpcErrorResponse`, `JsonRpcResponse`, `JsonRpcNotification`, `JsonRpcMessage`, `JsonRpcErrorCode`, `PluginRpcErrorCode`, plus the parameter

shapes for each RPC method: `InitializeParams`, `InitializeResult`, `ConfigChangedParams`, `ValidateConfigParams`, `OnEventParams`, `RunJobParams`, `GetDataParams`, `PerformActionParams`, `ExecuteToolParams`, and the host method tables `HostToWorkerMethods` / `HostToWorkerMethodName` / `WorkerToHostMethods` / `WorkerToHostMethodName` / `HostToWorkerRequest` / `HostToWorkerResponse` / `WorkerToHostRequest` / `WorkerToHostResponse` / `WorkerToHostNotifications` / `WorkerToHostNotificationName`.

Environment-driver protocol shapes: `PluginEnvironmentDiagnostic`, `PluginEnvironmentDriverBaseParams`, `PluginEnvironmentValidateConfigParams`, `PluginEnvironmentValidationResult`, `PluginEnvironmentProbeParams`, `PluginEnvironmentProbeResult`, `PluginEnvironmentLease`, `PluginEnvironmentAcquireLeaseParams`, `PluginEnvironmentResumeLeaseParams`, `PluginEnvironmentReleaseLeaseParams`, `PluginEnvironmentDestroyLeaseParams`, `PluginEnvironmentRealizeWorkspaceParams`, `PluginEnvironmentRealizeWorkspaceResult`, `PluginEnvironmentExecuteParams`, `PluginEnvironmentExecuteResult`.

Launcher render shapes: `PluginModalBoundsRequest`, `PluginRenderCloseEvent`, `PluginLauncherRenderContextSnapshot`.

Host client factory

For embedding the host side of the bridge in tests or custom integrations:

- `createHostClientHandlers` — build the handler map a host needs to answer worker-to-host RPC calls.
- `getRequiredCapability` — look up the capability gate a given worker-to-host call sits behind.
- `CapabilityDeniedError` — thrown by host handlers when the plugin is missing a required capability.

Types: `HostServices`, `HostClientFactoryOptions`, `HostClientHandlers`.

Bundling and dev server

Helpers for the plugin's build pipeline:

- `createPluginBundlerPresets` — returns esbuild-like and rollup-like presets that pin the right externals/entry shape for plugin bundles.
- `startPluginDevServer` — local dev server for the plugin UI bundle.
- `getUiBuildSnapshot` — read the current UI build snapshot, useful in tests.

Types: `PluginBundlerPresetInput`, `PluginBundlerPresets`, `EsbuildLikeOptions`, `RollupLikeConfig`, `PluginDevServer`, `PluginDevServerOptions`.

Testing utilities

The SDK ships a first-class test harness so you do not have to spin up a real host:

- `createTestHarness` — base harness for unit-testing a plugin against in-memory host stubs.
- `createEnvironmentTestHarness` — harness for testing environment-driver plugins.
- `createFakeEnvironmentDriver` — synthesised driver implementation for assertions.
- `filterEnvironmentEvents`, `assertEnvironmentEventOrder`, `assertLeaseLifecycle`, `assertWorkspaceRealizationLifecycle`, `assertExecutionLifecycle`, `assertEnvironmentError` — assertion helpers for the environment-driver flow.

Types: `TestHarness`, `TestHarnessOptions`, `TestHarnessLogEntry`, `EnvironmentTestHarness`, `EnvironmentTestHarnessOptions`, `EnvironmentEventRecord`, `FakeEnvironmentDriverOptions`.

Re-exports

- `z` — `zod` is re-exported so plugin authors do not need to add a separate dependency. Use it for `instanceConfigSchema` and tool `parametersSchema` declarations.
- Constants from `@EKVAAR OSai/shared`: `PLUGIN_API_VERSION`, `PLUGIN_STATUSES`, `PLUGIN_CATEGORIES`, `PLUGIN_CAPABILITIES`, `PLUGIN_UI_SLOT_TYPES`, `PLUGIN_UI_SLOT_ENTITY_TYPES`, `PLUGIN_STATE_SCOPE_KINDS`, `PLUGIN_JOB_STATUSES`, `PLUGIN_JOB_RUN_STATUSES`, `PLUGIN_JOB_RUN_TRIGGERS`, `PLUGIN_WEBHOOK_DELIVERY_STATUSES`, `PLUGIN_EVENT_TYPES`, `PLUGIN_BRIDGE_ERROR_CODES`.

Example

A minimal worker entrypoint that wires up an event subscription, a job, and a data feed:

```ts
// dist/worker.ts
import { definePlugin, runWorker, z } from "@EKVAAR OSai/plugin-sdk";

const plugin = definePlugin({
  async setup(ctx) {
    ctx.logger.info("Plugin starting up");
```

```
    ctx.events.on("issue.created", async (event) => {
      ctx.logger.info("Issue created", { issueId: event.entityId });
    });

    ctx.jobs.register("full-sync", async (job) => {
      ctx.logger.info("Starting full sync", { runId: job.runId });
      // ... sync implementation
    });

    ctx.data.register("sync-health", async ({ companyId }) => {
      const state = await ctx.state.get({
        scopeKind: "company",
        scopeId: String(companyId),
        stateKey: "last-sync-at",
      });
      return { lastSync: state };
    });
  },

  async onHealth() {
    return { status: "ok" };
  },
});

export default plugin;
runWorker(plugin, import.meta.url);
```

The shape above is the canonical example in the SDK's own `index.ts` header. For the matching manifest types and capability flags, see the corresponding `Plugin*Declaration` types listed above.

Worker entrypoint validation

`runWorker(plugin, import.meta.url)` only starts the JSON-RPC host when the file it is called from is the process entrypoint. The check is intentionally tolerant of symlinked package layouts — common during local plugin development, where a `pnpm`-linked SDK or a workspace-linked plugin sits behind one or more symlinks.

The exported helper that backs this is `isWorkerEntrypoint(entry, moduleUrl)`:

- It takes `process.argv[1]` (the path Node was invoked with) and the `import.meta.url` you passed to `runWorker`.
- It resolves both sides through `fs.realpathSync.native`, falling back to a plain `path.resolve` if the realpath call throws (for example, on a path that doesn't exist yet).
- It compares the resolved real paths for equality. If they match, the file is the entrypoint and `runWorker` calls `startWorkerRpcHost({ plugin })`. If they don't, `runWorker` returns silently — useful when the same module is also imported from tests or re-export shims.

The practical implications:

- **Symlinked plugin packages work.** When the host runs `node /Users/you/.../dist/worker.js` against a path that resolves through a symlink, the real-path comparison still matches `import.meta.url` and the worker boots.
- **In-process tests skip the check.** Passing both `stdin` and `stdout` in `RunWorkerOptions` makes `runWorker` start the host directly without consulting `process.argv[1]`. The test harnesses (`createTestHarness`, `createEnvironmentTestHarness`) use this path.
- **Re-importing a worker file is safe.** Importing the worker module from another file (e.g. a `worker-bootstrap.ts` that calls `startWorkerRpcHost` itself) won't double-boot the RPC host, because `process.argv[1]` will be the bootstrap file, not the worker module.

Related

- [Administration → Plugins](../../administration/plugins.md) — installing, enabling, configuring, and uninstalling plugins as an operator.
- [How-to → Write a Company Skill](../../how-to/write-a-company-skill.md) — instructions an agent loads, **not** server code.
- [Reference → Creating an Adapter](../adapters/creating-an-adapter.md) — the right extension point for new AI runtimes.
- [Reference → Skills](../skills.md) — the skill file shape and install pipeline a plugin's `PluginManagedSkillDeclaration` slots into.

Workspace diff viewer

If you want to see what your agents actually changed inside a workspace — which files moved, what got added, the staged-versus-unstaged split, the line-level patch — without leaving the EKVAAR OS dashboard, the `@EKVAAR OSai/plugin-workspace-diff` plugin is the surface that does it. It adds a **Changes** tab to execution and project workspaces, computes the diff locally with Git on the host running EKVAAR OS, and renders it with `@pierre/diffs`.

This page is for **operators and developers** who want to enable, configure, or understand the limits of that Changes tab.

> The Workspace diff plugin is in alpha alongside the plugin runtime itself. Expect breaking changes between EKVAAR OS releases and pin your version when you depend on it.

Quick install

The plugin ships as a published npm package, so any EKVAAR OS install (Docker, systemd, bare-metal — all the same) can pull it in with one command from a host that has your EKVAAR OS CLI configured:

```sh
EKVAAR OSai plugin install @EKVAAR OSai/plugin-workspace-diff
```

Or from the dashboard: **Settings → Plugins → Install Plugin**, paste `@EKVAAR OSai/plugin-workspace-diff`, submit.

The plugin won't appear in `EKVAAR OSai plugin examples` — that command only lists the four built-in reference *example* plugins, not the full catalogue of first-party plugins. Install Workspace diff viewer by full package name.

If you're running from a monorepo checkout, see [Develop a plugin locally](../../how-to/develop-a-plugin-locally.md) and point the installer at `packages/plugins/plugin-workspace-diff` instead.

On first enable the plugin asks for a small, focused capability set: `ui.detailTab.register`, `execution.workspaces.read`, and `project.workspaces.read`. It never writes to the workspace — diffs are read-only — and it doesn't own its own database namespace, agents, or routines. Review the Permissions card on the plugin detail page before approving.

What you get

Once the plugin is installed and enabled, one thing shows up in the EKVAAR OS UI:

- **A Changes tab** on every execution workspace and project workspace detail page (slot id `workspace-changes-tab`, slot type `detailTab`, order `25`, entity types

`execution_workspace` and `project_workspace`). Open any workspace and the tab is right there in the row of detail tabs.

The tab name is **Changes (the plugin's `displayName` is "Workspace Changes"). Inside, you get the familiar file-tree-plus-patch layout: a list of changed files with their Git status (added, modified, deleted, renamed, copied, type-changed, untracked, unknown), and a per-file patch view that splits **staged**, **unstaged**, **head**, and **untracked** content.**

Behind the scenes the plugin runs Git directly against the workspace path. There's no background worker, no managed agent, no routines, no migrations — just a small data endpoint the Changes tab calls when you open it.

How the diff is computed

The plugin's worker exposes a single data endpoint (`workspace-diff`) that the Changes tab calls with the workspace id and a query. The worker:

1. Looks up the workspace through the SDK's `executionWorkspaces.get` or `projects.listWorkspaces`, depending on entity type.
2. Resolves a **base ref — either the workspace's own `baseRef`, or, for execution workspaces, the parent project workspace's `defaultRef` / `repoRef`. You can also pass an explicit `baseRef` in the query.**
3. Confirms the workspace `cwd` is an absolute, real directory inside a Git repository (with `O_NOFOLLOW` checks and `git rev-parse --show-toplevel`).
4. Runs `git` with a 10 second timeout and a 2 MiB list buffer to enumerate changed files and produce patches.

Two views are supported via the `view` query parameter:

- `working-tree` (the default) — staged + unstaged + untracked changes relative to `HEAD`.
- `head` — what `HEAD` looks like compared to the resolved base ref.

If you ask for the `head` view without supplying a base ref, the Changes tab falls back to `working-tree` rather than failing, so the diff always renders even when the base hasn't been picked yet.

You can also pass `paths` / `path` to limit the diff to specific files, and `includeUntracked` (default `true`) to toggle untracked-file inclusion.

Controls in the Changes tab

The tab's toolbar gives you two toggles and a base-ref input:

- **Split / Unified** — switch between side-by-side and inline patch rendering. Split is the default.
- **Working tree / Against ref** — pick `working-tree` (default) to inspect uncommitted changes, or **Against ref** to diff `HEAD` against the resolved base ref.
- **Base ref** — the input next to the view toggle (shown when **Against ref** is selected). If you leave it blank, the tab prefills the workspace's `defaultBaseRef` (resolved by the worker) and flips the view to **Against ref** for you, so common cases just work without any toggling. Once you edit either control by hand, your choice sticks for the session.

The toolbar stays **sticky at the top** of the tab while you scroll, so the toggles and the base-ref input remain in reach on large diffs.

Limits worth knowing

The plugin enforces hard caps so a runaway diff can't lock up your dashboard. The defaults (from `WORKSPACE_DIFF_CAPS`) are:

Cap	Default
`maxFiles`	200 changed files
`maxFileBytes`	512 KiB per file (binary / oversized files are skipped)
`maxPatchBytes`	256 KiB per file patch
`maxTotalPatchBytes`	1 MiB total patch payload

When a cap is hit you don't get a failure — you get a structured **warning** alongside whatever the plugin could compute. The warning codes you may see:

- `base_ref_missing`, `base_ref_invalid` — the resolved base ref couldn't be used.
- `binary_file`, `file_oversized` — file skipped from inline patch rendering.
- `file_count_truncated`, `patch_truncated` — total budget exceeded.
- `git_command_failed` — Git itself returned non-zero (the stderr is included).
- `missing_cwd`, `non_git_workspace`, `workspace_path_invalid` — the workspace path isn't usable.
- `path_filter_invalid`, `symlink_target_outside_workspace` — path-safety guard tripped.

These warnings render in the Changes tab so operators can see exactly why something is missing instead of staring at an empty list.

Tips and common use cases

- **Use it for agent code review. When an agent finishes work in an execution workspace, open the Changes tab to see the patch before you merge or hand off — same flow you'd use in a code-review UI, without leaving EKVAAR OS.**
- **Set a `baseRef` on your project workspace. The plugin falls back to the project workspace's `defaultRef` then `repoRef`, so configuring those once means every execution workspace under that project gets a sensible diff baseline for free.**
- **The workspace must be a real Git repo. Non-Git workspaces are not supported — you'll get a `non_git_workspace` warning. If you keep an execution workspace as a plain folder, the Changes tab will tell you to either initialise Git or skip the plugin for that workspace.**
- **The plugin only reads. It never stages, commits, resets, or otherwise touches your repository. If you need to act on a diff, do it from the host shell or from another plugin.**

Related

- [Administration → Plugins](../../administration/plugins.md) — the operator-facing Plugin Manager.
- [How-to → Develop a plugin locally](../../how-to/develop-a-plugin-locally.md) — point EKVAAR OS at a local checkout of the plugin.
- [Reference → Plugin SDK](./sdk.md) — the authoring surface, if you want to extend the diff viewer or write your own detail-tab plugin.