Q-24.c

```c
#include <stdio.h>
int main()
{
    int n;
    float x,y;
    printf("Enter the value of x:");
    scanf("%f",&x);
    printf("Enter the value of n:");
    scanf("%d",&n);
    if(n==1){
        y = x+1;
    }
    else if(n==2){
        y = 1+x/n;
    }
    else if(n==3){
        y = 1+x*n;
    }
    else if(n>3||n<1){
        y = 1+n*x;
    }
    printf("The value of y is: %f\n",y);
return 0;
}
```

Problems Output Debug Console Terminal Ports

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-24.c -o Q-24 } ; if ($?) { .\Q-24 }
Enter the value of x: 5
Enter the value of n:7
The value of y is: 36.000000
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

C Q-25.c

```c
#include<stdio.h>
int main()
{
    int i,a;
    printf("enter the value");
    scanf("%d",&a);
    i = 1;
    while(i <= 10)
    {
        printf("%d * %d = %d\n",a,i,i*a);
        i++;
    }
    return 0;
}
```

Problems Output Debug Console Terminal Ports

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-25.c -o Q-25 } ; if ($?) { .\Q-25 }
enter the value 4
4 * 1 = 4
4 * 2 = 8
4 * 3 = 12
4 * 4 = 16
4 * 5 = 20
4 * 6 = 24
4 * 7 = 28
4 * 8 = 32
4 * 9 = 36
4 * 10 = 40
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-26.c

```c
#include<stdio.h>
int main()
{
    int a=0, b=0, i, n;

    printf("enter the number of terms:");
    scanf("%d",&n);
    for(i=1;i<=n;i++)
    if(i%2==0)
    {
        a=a+i;
    }
    else
    {
        b=b+i;
    }
    printf("sum of even no.=%d\n",a);
    printf("sum of odd no.=%d\n",b);
}
```

Problems Output Debug Console Terminal Ports Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-26.c -o Q-26 } ; if ($?) { .\Q-26 }
enter the number of terms:4
sum of even no.=6
sum of odd no.=4
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-27.c

```c
#include<stdio.h>
int main()
    {
        int a;
        printf("enter the value:");
        scanf("%d",&a);
        if(2%a!=0||3%a!=0||5%a!=0||7%a!=0)
        {
         printf("the number is not prime");
        }
        else if(a==1)
        {

        printf("the number is nither prime nor composite");
        }
        else
        {
        printf("the number is prime");
        }
        return 0;
    }
```

Problems Output Debug Console Terminal Ports Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>


                                    > cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-27.c -o Q-27 } ; if ($?) { .\Q-27 }
enter the value:4
the number is not prime
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-28.c

```c
#include<stdio.h>
int main()
{
    int n,a,b,c,sum;
    printf("enter three digit number:");
    scanf("%d",&n);
    a = n/100;
    b = (n/10)%10;
    c = n%10;
    sum= a*a*a + b*b*b + c*c*c;
    if(sum==n)
    {
        printf("number is armstrong");
    }
    else
    printf("number is not armstrong");
    return 0;
}
```

Problems Output Debug Console Terminal Ports

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-28.c -o Q-28 } ; if ($?) { .\Q-28 }
enter three digit number:370
number is armstrong
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-29.c

```c
#include<stdio.h>
int main()
{
    int n,original,temp,rev=0;
    printf("enter number :");
    scanf("%d",&n);
    original=n;
    while(n>0)
    {
        temp=n%10;
        rev=rev*10+temp;
        n=n/10;
    }
    if(original==rev)
    printf("number is palindrome");
    else
    printf("number is not palindrome");
}
```

Problems Output Debug Console Terminal Ports Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-29.c -o Q-29 } ; if ($?) { .\Q-29 }
enter number :121
number is palindrome
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-30.c

```c
#include<stdio.h>
int main()
{
    int num=0,a,b;
    printf("Enter a number:");
    scanf("%d",&a);
    while(a!=0)
    {
        b=a%10;
        num=num*10 + b;
        a=a/10;
    }
    printf("reverse of number is:%d",num);
    return 0;
}
```

Problems Output Debug Console Terminal Ports Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>

> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-30.c -o Q-30 } ; if ($?) { .\Q-30 }
Enter a number:432
reverse of number is:234
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-31.c

```c
#include<stdio.h>
int main()
{
    int a,b,num=0;
    printf("Enter a number:");
    scanf("%d",&a);
    while(a!=0)
    {
        b=a%10;
        num+=b;
        a=a/10;
    }
    printf("sum of individual num is:%d",num);
    return 0;
}
```

Ports

Problems Output Debug Console Terminal Ports

Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-31.c -o Q-31 } ; if ($?) { .\Q-31 }
Enter a number:54
sum of individual num is:9
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-32.c | Q-28.c | Q-41.c

Q-32.c > main()

```c
#include<stdio.h>
void main()
{
    int n,i,temp,max1,max2,a[10];
    printf("Enter the number of elements=");
    scanf("%d",&n);
    printf("\nEnter the array elements=\n");
    for(i=0;i<n;i++)
    {
        scanf("%d",&a[i]);
    }
    max1=a[0];
    max2=a[1];
    if(max2>max1)
    {
        temp=max1;
        max1=max2;
        max2=temp;
    }
    for(i=2;i<n;i++)
    {
        if(a[i]>max1)
        {
```

Problems | Output | Debug Console | Terminal | Ports

```
> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-32.c -o Q-32 } ; if ($?) { .\Q-32 }
Enter the number of elements= 5

Enter the array elements=
1
2
3
4
5

First maximum=5
Second maximum=4
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-32.c Q-34.c Q-33.c

Q-33.c > main()

```c
#include<stdio.h>
int main()
{
    int a[10],n,i,max,min;
    printf("enter array no. :");
    scanf("%d",&n);
    printf("enter array elements : \n");
    for(i=0;i<n;i++)
    {
        scanf("%d",&a[i]);
    }
    max=a[0];
    min=a[0];
    for(i=1;i<n;i++)
    {
        if(a[i]>max)
        max=a[i];
        if(a[i]<min)
        min=a[i];
    }
    printf("max no. is : %d\n",max);
    printf("min no. is : %d",min);

```

Problems Output Debug Console Terminal Ports

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-33.c
enter array no. : 5
enter array elements :
2
4
6
4
18
max no. is : 18
min no. is : 2
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-32.c | Q-34.c | Q-33.c

Q-34.c > ...

```c
#include<stdio.h>
int main()
{
    int f,f1,f2,n;
    f1=0;
    f2=1;
    printf("enter the value of n:");
    scanf("%d",&n);
    while(n>0)
    {
        f=f1+f2;
        f1=f2;
        f2=f;
        f++;
        n--;
    }
    printf("The %dth Fibonacci number is: %d", n, f);
    return 0;
}
```

Problems | Output | Debug Console | Terminal | Ports

Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-34.c -o Q-34 } ; if ($?) { .\Q-34 }
enter the value of n: 7
The 0th Fibonacci number is: 22
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-35.c

```c
#include<stdio.h>
int main()
{
    int a,b,num=0;
    printf("Enter a number:");
    scanf("%d",&a);
    while(a>9)
    {
        num = 0;
    while(a>0)
    {
        b=a%10;
        num+=b;
        a=a/10;
    }
    a=num;
    }
    printf("sum of individual num is:%d",num);
    return 0;
}
```

Problems Output Debug Console Terminal Ports Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-35.c -o Q-35 } ; if ($?) { .\Q-35 }
Enter a number: 4567
sum of individual num is:4
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-36.c

```c
#include<stdio.h>
int main()
{
    int n,i;
    printf("enter value of n:");
    scanf("%d",&n);
    printf("even number");
    for(i=1;i<=n;i++)
    printf("%d\n",2*i);
}
```

Q-36.c Q-37.c

Q-36.c > main()

```c
#include<stdio.h>
int main()
{
    int n,i;
    printf("enter value of n:");
    scanf("%d",&n);
    printf("odd number");
    for(i=1;i<=n;i++)
    printf("%d\n",(2*i+1));
}

```

Problems Output Debug Console Terminal Ports Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-36.c -o Q-36 } ; if ($?) { .\Q-36 }
enter value of n: 6
odd number3
5
7
9
11
13
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-38.c > ...

```c
#include<stdio.h>
int main()
{
    int i,j;
    printf("enter value of n:");
    scanf("%d",&j);
    for(i=1;i<=j;i++)
    {
        printf("%d\n",i*i);
    }
}
```

Problems Output Debug Console Terminal Ports

```
> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-38.c -o Q-38 } ; if ($?) { .\Q-38 }
enter value of n: 5
1
4
9
16
25
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-39.c > main()

```c
#include<stdio.h>
int main()
{
    int i,n,fact=1;
    float sum=0;
    printf("enter value of n:");
    scanf("%d",&n);
    for(i=1;i<=n;i++)
    {
        fact=fact*i;
        sum=sum+(float)i/fact;
    }
    printf("sum=%f",sum);
    return 0;
}
```

Problems Output Debug Console Terminal Ports

```
> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-39.c -o Q-39 } ; if ($?) { .\Q-39 }
enter value of n: 5
sum=2.708333
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-36.c | Q-37.c | Q-39.c | Q-40.c | Untitled-2 | Untitled-1

Q-40.c > ...

```c
#include<stdio.h>
int main()
{
    int num,sum=0;
    printf("enter number\n");
    while(1){
        scanf("%d",&num);
        if(num<0)
        {break;}

        sum+=num;

    }
    printf("the sum of number is %d",sum);
}
```

Problems | Output | Debug Console | Terminal | Ports

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-40.c -o Q-40 } ; if ($?) { .\Q-40 }
enter number
6
5
-8
the sum of number is 11
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-36.c | Q-37.c | Q-39.c | Q-41.c | Untitled-2 | Untitled-1

Q-41.c > ...

```c
#include<stdio.h>
int main()
{
    int num,factor;
    printf("enter number");
    scanf("%d", &num);
    factor = 1;
    while(factor <= num)
    {
        if(num % factor == 0)
        {
            printf("%d ", factor);
        }
        factor++;
    }
    return 0;
}
```

Problems | Output | Debug Console | Terminal | Ports | Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-41.c -o Q-41 } ; if ($?) { .\Q-41 }
enter number 24
1 2 3 4 6 8 12 24
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-42.c > ...

```c
#include<stdio.h>
int main()
{
    int n,a;
    printf("enter the value :");
    scanf("%d",&a);
    if(2%a!=0&&3%a!=0&&5%a!=0&&7%a!=0)
       {
        printf("the number is prime");
       }
    else
    {
        printf("composite number");
    }


}
```

Problems Output Debug Console Terminal Ports

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>

                                    > cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-42.c -o Q-42 } ; if ($?) { .\Q-42 }
enter the value : 53
the number is prime
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-36.c | Q-37.c | Q-39.c | Q-43.c | Untitled-2 | Untitled-1

Q-43.c > ...

```c
    scanf("%d",&sales);
    if(sales<=500)
    {
        com=sales*(.05);
        printf("commision is 5 percentange %f",com);

    }
    if(sales>500 && sales<=2000)
    {
        com=sales*(.1)+35;
        printf("commision is 10 per plus 35 %f",com);

    }
    if(sales>2000 && sales<=5000)
    {
        com=sales*(.12)+185;
        printf("commision is 12.5 per plus 185 %f",com);

    }
if(sales>5000)
    {
        com=sales*(.125);
        printf("commision is 12.5 per %f",com);
```

Problems | Output | Debug Console | Terminal | Ports | Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)> cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-43.c -o Q-43 } ; if ($?) { .\Q-43 }
enter the sales 540
commision is 10 per plus 35 89.000000
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```

Q-36.c | Q-37.c | Q-39.c | Q-44.c | Untitled-2 | Untitled-1

Q-44.c > ...

```c
#include<stdio.h>
int main()
{
    int con;
    float rate;
    printf("enter no. of unit ");
    scanf("%d",&con);
    if(con<=200)
    {
        rate=con*(.5);
        printf("charges %2f",rate);

    }
    if(con>210 && con<=400)
    {
        rate=con*(.65)+100;
        printf("charges %2f",rate);

    }
    if(con>401 && con<=600)
    {
        rate=con*(.8)+230;
        printf("charges %2f",rate);
```

Problems | Output | Debug Console | Terminal | Ports | Code

```
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>

                                > cd "c:\Users\Asus\OneDrive\Desktop\lab(1-4)\" ; if ($?) { gcc Q-44.c -o Q-44 } ; if ($?) { .\Q-44 }
enter no. of unit  450
charges 590.000000
PS C:\Users\Asus\OneDrive\Desktop\lab(1-4)>
```