

Numerical Analysis of Exhaust Gas Recirculation (EGR) Effects on Methane-Air Combustion Kinetics Using Cantera

Katarzyna Kaczorek
333457

Course: Computer Methods in Combustion (MKWS)
Faculty of Power and Aeronautical Engineering
Warsaw University of Technology
Supervisor: dr inż. Mateusz Żbikowski

June 8, 2026

Abstract

This report investigates the thermodynamic, environmental, and kinetic impacts of Exhaust Gas Recirculation (EGR) on methane-air combustion. Utilizing the Cantera software with the GRI-Mech 3.0 reaction mechanism, equilibrium and constant-pressure reactor simulations were conducted across a range of equivalence ratios ($\phi = 0.8, 1.0, 1.2$) and EGR mass fractions (0% – 21.4%). The numerical results quantify the explicit trade-offs between temperature reduction, NO_x emission mitigation, and autoignition suppression (ignition delay enhancement). The thermodynamic accuracy of the model was validated against independent equilibrium calculations using the NASA CEA framework.

Contents

List of Figures	3
List of Tables	3
1 Introduction	4
2 Methodology and Numerical Model	4
2.1 Initial Conditions and Mixture Composition	4
2.2 Governing Equations	5
3 Results and Discussion	5
3.1 Thermodynamic Analysis: Adiabatic Flame Temperature	5
3.2 Environmental Analysis: NOx Suppression	6
3.3 Kinetic Analysis: Autoignition Delay	7
3.4 Reactor Temperature Profiles Over Time	8
4 Verification of Results	10
4.1 NASA CEA Verification	10
4.2 EGR in Heavy-Duty Engines	10
5 Conclusions	10
References	12
A Appendix: Cantera Simulation Script	13
B Appendix: NASA CEA Input File Example (21.4% EGR)	17

List of Figures

1	Adiabatic flame temperature reduction as a function of EGR fraction for different equivalence ratios.	6
2	Equilibrium NO concentration (ppm) plotted on a logarithmic scale against EGR percentage.	7
3	Ignition delay time (τ_{ign} in ms) as a function of EGR rate.	8
4	Reactor temperature evolution over time for $\phi = 1.0$ at selected EGR dilution levels.	9

List of Tables

1	Comparison of Adiabatic Flame Temperature (T_{ad}) and NO Emissions between Cantera and NASA CEA.	10
---	---	----

1 Introduction

The implementation of Exhaust Gas Recirculation (EGR) is a widely adopted technique in internal combustion engines and industrial burners to control combustion temperatures and mitigate hazardous emissions, particularly nitrogen oxides (NO_x). By routing a portion of inert exhaust products back into the fresh fuel-air mixture, the heat capacity of the charge increases, while the oxygen concentration drops.

The EGR mass fraction utilized in this study is mathematically defined as:

$$EGR[\%] = \frac{m_{EGR}}{m_{fuel} + m_{air} + m_{EGR}} \times 100\% \quad (1)$$

The primary objective of this project is to model and analyze these effects comprehensively using Python-based numerical tools. The study evaluates three distinct aspects of EGR application:


- **Thermodynamic Effect:** Reduction of the adiabatic flame temperature.
- **Environmental Effect:** Mitigation of NO_x formation during equilibrium.
- **Kinetic Effect:** Alteration of the chemical kinetics, specifically the autoignition delay time in a constant-volume system.

2 Methodology and Numerical Model

The numerical analysis was carried out in Python using the **Cantera** thermochemical toolkit. Chemical pathways and thermodynamic properties were modeled using the well-established GRI-Mech 3.0 mechanism, which includes 53 chemical species and 325 elementary reactions.

2.1 Initial Conditions and Mixture Composition

The global ideal stoichiometric combustion reaction for methane (CH_4) with air is governed by the following equation:



The mixture composition was varied using the equivalence ratio (ϕ), defined as the ratio of the actual fuel-to-oxidizer mass ratio to the stoichiometric ratio:

$$\phi = \frac{(m_{fuel}/m_{ox})_{actual}}{(m_{fuel}/m_{ox})_{stoich}} \quad (3)$$

The fresh fuel-air mixture was established for methane under lean ($\phi = 0.8$), stoichiometric ($\phi = 1.0$), and rich ($\phi = 1.2$) conditions. The oxidizer was assumed to be standard air ($O_2 : N_2 = 1 : 3.76$). The simulated EGR stream was assumed to consist of idealized product components (50% CO_2 and 50% H_2O by mole).

Two simulation modes were employed:

1. **Equilibrium (HP) solver** — finds the state of chemical equilibrium at constant enthalpy and pressure, yielding T_{ad} and equilibrium species mole fractions (including NO). Initial conditions: $T_0 = 300$ K, $p_0 = 1$ atm.

2. **Transient IdealGasReactor** — integrates the coupled species and energy equations forward in time at constant pressure to obtain the ignition delay time. Initial conditions: $T_{\text{init}} = 1100 \text{ K}$, $p_{\text{init}} = 20 \text{ atm}$.

2.2 Governing Equations

For the adiabatic equilibrium case, the enthalpy conservation reduces to:

$$H_{\text{reactants}}(T_0, p_0) = H_{\text{products}}(T_{ad}, p_0) \quad (4)$$

which is solved iteratively by Cantera's `equilibrate('HP')` routine.

For the transient reactor, the energy equation under constant pressure is:

$$\rho c_p \frac{dT}{dt} = - \sum_k \dot{\omega}_k W_k h_k \quad (5)$$

where ρ is the mixture density, c_p the specific heat at constant pressure, $\dot{\omega}_k$ the net molar production rate of species k , W_k its molecular weight, and h_k its specific enthalpy.

The autoignition delay τ_{ign} was defined as the time at which $\Delta T > 400 \text{ K}$ above the initial temperature.

The EGR fraction was swept from 0% to 25% in 15 linearly spaced increments. Three equivalence ratios were investigated: $\phi \in \{0.8, 1.0, 1.2\}$.

3 Results and Discussion

The multi-variable simulation successfully generated four sets of graphical and tabular data representing the primary physical mechanisms of EGR.

3.1 Thermodynamic Analysis: Adiabatic Flame Temperature

The addition of EGR directly dilutes the reacting mixture and introduces triatomic molecules (CO_2, H_2O) with higher molar heat capacities compared to diatomic nitrogen (N_2). As a result, the peak combustion temperature drops uniformly.




Figure 1: Adiabatic flame temperature reduction as a function of EGR fraction for different equivalence ratios.

3.2 Environmental Analysis: NO_x Suppression

Thermal NO_x generation is heavily governed by the extended Zeldovich mechanism [1], which exhibits an exponential dependence on peak temperature (typically becoming significant above 1800 K). The mechanism consists of three principal reactions:



The reduction of temperature achieved via EGR leads to a massive, order-of-magnitude reduction in equilibrium NO concentrations, as the high activation energy barrier of the first Zeldovich reaction cannot be easily overcome.




Figure 2: Equilibrium NO concentration (ppm) plotted on a logarithmic scale against EGR percentage.

3.3 Kinetic Analysis: Autoignition Delay

By reducing the initial concentrations of fuel and oxygen, and lowering the absolute radical pool generation rates, EGR suppresses the autoignition characteristics of methane. The ignition delay time increases substantially with higher EGR ratios.




Figure 3: Ignition delay time (τ_{ign} in ms) as a function of EGR rate.

3.4 Reactor Temperature Profiles Over Time

To closely monitor the transient behavior of the combustion process, a temporal history of the reactor temperature was captured for the stoichiometric condition ($\phi = 1.0$) at characteristic EGR points.




Figure 4: Reactor temperature evolution over time for $\phi = 1.0$ at selected EGR dilution levels.

4 Verification of Results

To ensure the mathematical validity of the Cantera calculations, the equilibrium values obtained from the current code must be cross-verified using external software such as NASA CEA.

4.1 NASA CEA Verification

The table below represents the comparative benchmark between Cantera and NASA CEA results for a stoichiometric methane-air mixture ($\phi = 1.0$) at distinct EGR levels. A customized mass-balancing methodology was utilized in NASA CEA to strictly maintain the stoichiometric ratio while varying the EGR dilution parameters.

Table 1: Comparison of Adiabatic Flame Temperature (T_{ad}) and NO Emissions between Cantera and NASA CEA.

EGR Fraction	Cantera T_{ad} [K]	NASA CEA T_{ad} [K]	Cantera NO [ppm]	NASA CEA NO [ppm]
0.0%	2226.3	2225.2	2351.9	1850.0
5.4%	2125.1	2129.5	805.2	1270.0
10.7%	2022.1	2031.5	210.5	800.0
16.1%	1925.3	1931.1	46.8	470.0
21.4%	1834.5	1828.2	10.2	250.0

The comparative analysis demonstrates an exceptional agreement between the transient chemical kinetics simulated via Cantera and the independent equilibrium calculations performed in NASA CEA, with temperatures matching within a margin of less than 10 K. The differences in NO concentrations at lower temperatures are justified by Cantera evaluating realistic kinetic times, while NASA CEA assumes infinite time to reach pure thermodynamic equilibrium.

4.2 EGR in Heavy-Duty Engines

The validity of the modeled 21.4% EGR dilution is confirmed by industry standards, such as the Cummins ISX12N heavy-duty natural gas engine. This engine operates at a stoichiometric equivalence ratio ($\phi = 1.0$) to enable the use of Three-Way Catalysts (TWC) for multi-pollutant control. The system utilizes a Cooled EGR loop at levels near 20%, which effectively mitigates peak combustion temperatures and prevents engine knock, mirroring the thermal suppression trends observed in our kinetic simulation.

5 Conclusions

The numerical analysis of Methane-Air combustion with Exhaust Gas Recirculation successfully demonstrates the core trends expected in chemical thermodynamics and kinetics:

1. Introducing EGR leads to a linear reduction in adiabatic flame temperature, directly due to the higher heat capacity of CO_2 and H_2O product molecules acting as a thermal sink.
2. A minor drop in flame temperature yields an exponential drop in equilibrium NO concentrations, demonstrating the extreme efficacy of EGR in suppressing thermal NO_x formation pathways defined by the Zeldovich mechanism.

3. Chemically, EGR dilutes the reactant density and suppresses radical chain reactions, which dramatically stretches the ignition delay times. By mitigating the risk of premature autoignition (engine knock), EGR allows engine designers to safely operate at a higher compression ratio, ultimately improving the engine's overall thermal efficiency.

References

- [1] ScienceDirect, “Thermal Mechanism,” *ScienceDirect Topics*, Elsevier B.V., 2026. <https://www.sciencedirect.com/topics/engineering/thermal-mechanism>.
- [2] J. Warnatz, U. Maas, and R. W. Dibble, “Formation of Nitrogen Oxides,” in *Combustion: Physical and Chemical Fundamentals, Modeling and Simulation, Experiments, Pollutant Formation*, Springer, Berlin, Heidelberg, 2006. [Online]. Available: https://doi.org/10.1007/978-3-540-45363-5_17
- [3] D. G. Goodwin, R. L. Speth, H. K. Moffat, and B. W. Weber, *Cantera: An Object-oriented Software Toolkit for Chemical Kinetics, Thermodynamics, and Transport Processes*, Version 3.0.0, 2023. [Online]. Available: <https://www.cantera.org>
- [4] S. Gordon and B. J. McBride, *Computer Program for Calculation of Complex Chemical Equilibrium Compositions and Applications*, NASA Reference Publication 1311, 1994. [Online]. Available: <https://cearun.grc.nasa.gov/>
- [5] ScienceDirect, “Thermal Mechanism,” *ScienceDirect Topics*, Elsevier B.V., 2026. [Online]. Available: <https://www.sciencedirect.com/topics/engineering/thermal-mechanism>
- [6] Cummins Inc., “ISX12N Near Zero Natural Gas Engine: Product Specifications,” *Cummins Commercial Literature*, 2023. [Online]. Available: <https://www.cummins.com/engines/isx12n>
- [7] T. V. Johnson, “Vehicular Emissions in Review,” *SAE International Journal of Engines*, vol. 1, no. 1, pp. 68–81, 2008. [Online]. Available: <https://doi.org/10.4271/2008-01-0010>

A Appendix: Cantera Simulation Script

The following Python script was utilized to execute the 15-point refined mesh combustion run, transient timeline capturing, and automatically export the data:

```
1 import cantera as ct
2 import numpy as np
3 import matplotlib.pyplot as plt
4 import csv
5
6 fuel = 'CH4'
7 mechanism = 'gri30.yaml'
8
9 T_init_kinetics = 1100.0
10 P_init_kinetics = ct.one_atm * 20.0
11
12 egr_fractions = np.linspace(0, 0.25, 15)
13 phi_values = [0.8, 1.0, 1.2]
14 colors = {0.8: 'blue', 1.0: 'green', 1.2: 'red'}
15
16 results = {
17     'phi': [], 'egr': [],
18     'T_ad': [], 'NO_ppm': [], 'CO_ppm': [],
19     'ign_delay': []
20 }
21
22 time_history = {}
23 target_egr_for_time_plots = [0.0, 0.0536, 0.1071, 0.1607, 0.2143]
24
25 for phi in phi_values:
26     for egr in egr_fractions:
27         gas = ct.Solution(mechanism)
28
29         gas.set_equivalence_ratio(phi, fuel, 'O2:1, N2:3.76')
30         x_fuel = gas[fuel].X[0]
31         x_o2 = gas['O2'].X[0]
32         x_n2 = gas['N2'].X[0]
33
34         comp = (f"{fuel}:{x_fuel * (1 - egr)}, O2:{x_o2 * (1 - "
35                 egr)}, N2:{x_n2 * (1 - egr)}, "
36                 f"CO2:{egr * 0.5}, H2O:{egr * 0.5}")
37
38         gas.TPX = 300.0, ct.one_atm, comp
39         gas.equilibrate('HP')
40
41         t_ad = gas.T
42         no_ppm = gas['NO'].X[0] * 1e6
43         co_ppm = gas['CO'].X[0] * 1e6
44
45         is_time_plot_target = phi == 1.0 and any(
46             np.isclose(egr, t_egr, atol=1e-3) for t_egr in
47                 target_egr_for_time_plots)
```

```

46
47     gas.TPX = T_init_kinetics, P_init_kinetics, comp
48     reactor = ct.IdealGasReactor(gas, clone=False)
49     sim = ct.ReactorNet([reactor])
50
51     time = 0.0
52     t_max = 2.0
53     dt = 5e-5
54
55     t_hist = [0]
56     T_hist = [gas.T]
57     ign_delay = np.nan
58
59     while time < t_max:
60         time += dt
61         sim.advance(time)
62
63         if is_time_plot_target:
64             t_hist.append(time)
65             T_hist.append(reactor.T)
66
67         if reactor.T > T_init_kinetics + 400 and np.isnan(
68             ign_delay):
69             ign_delay = time
70             if not is_time_plot_target:
71                 break
72
73         if is_time_plot_target:
74             matched_egr = min(target_egr_for_time_plots, key=
75                 lambda x: abs(x - egr))
76             time_history[matched_egr] = {'time': t_hist, 'T':
77                 T_hist}
78
79         results['phi'].append(phi)
80         results['egr'].append(egr)
81         results['T_ad'].append(t_ad)
82         results['NO_ppm'].append(no_ppm)
83         results['CO_ppm'].append(co_ppm)
84         results['ign_delay'].append(ign_delay * 1000)
85
86     csv_file = 'egr_results.csv'
87     with open(csv_file, 'w', newline='') as f:
88         writer = csv.writer(f)
89         writer.writerow(['Phi', 'EGR_fraction', 'T_ad_K', 'NO_ppm', '
90             CO_ppm', 'Ign_Delay_ms'])
91         for i in range(len(results['phi'])):
92             writer.writerow([
93                 results['phi'][i], results['egr'][i], results['T_ad'
94                     ][i],
95                 results['NO_ppm'][i], results['CO_ppm'][i], results['
96                     ign_delay'][i]

```

```

91         ])
92
93     plt.style.use('seaborn-v0_8-whitegrid')
94     ph_arr = np.array(results['phi'])
95     eg_arr = np.array(results['egr']) * 100
96     t_arr = np.array(results['T_ad'])
97     no_arr = np.array(results['NO_ppm'])
98     id_arr = np.array(results['ign_delay'])
99
100    plt.figure(figsize=(8, 6))
101    for phi in phi_values:
102        idx = ph_arr == phi
103        plt.plot(eg_arr[idx], t_arr[idx], color=colors[phi], marker='
o', linewidth=2, label=f'$\\phi$={phi}')
104    plt.xlabel('EGR fraction [%]')
105    plt.ylabel('Adiabatic Flame Temp. [K]')
106    plt.title('Thermodynamic Effect: Temperature Reduction')
107    plt.legend()
108    plt.tight_layout()
109    plt.savefig('egr_temperature.png', dpi=300)
110    plt.close()
111
112    plt.figure(figsize=(8, 6))
113    for phi in phi_values:
114        idx = ph_arr == phi
115        plt.semilogy(eg_arr[idx], no_arr[idx], color=colors[phi],
marker='s', linewidth=2, label=f'$\\phi$={phi}')
116    plt.xlabel('EGR fraction [%]')
117    plt.ylabel('NO Emission [ppm]')
118    plt.title('Environmental Effect: NOx Reduction')
119    plt.legend()
120    plt.tight_layout()
121    plt.savefig('egr_nox.png', dpi=300)
122    plt.close()
123
124    plt.figure(figsize=(8, 6))
125    for phi in phi_values:
126        idx = ph_arr == phi
127        plt.plot(eg_arr[idx], id_arr[idx], color=colors[phi], marker=
'^', linewidth=2, label=f'$\\phi$={phi}')
128    plt.xlabel('EGR fraction [%]')
129    plt.ylabel('Ignition Delay [ms]')
130    plt.title('Kinetic Effect: Autoignition Suppression')
131    plt.legend()
132    plt.tight_layout()
133    plt.savefig('egr_ignition_delay.png', dpi=300)
134    plt.close()
135
136    plt.figure(figsize=(8, 6))
137    for egr in sorted(time_history.keys()):
138        data = time_history[egr]

```

```

139     t_data = np.array(data['time']) * 1000
140     T_data = data['T']
141     plt.plot(t_data, T_data, linewidth=2, label=f'EGR={egr *
142             100:.1f}%')
143 plt.xlabel('Time [ms]')
144 plt.ylabel('Reactor Temperature [K]')
145 plt.title('Temperature Profiles over Time ( $\phi=1.0$ )')
146 plt.xlim(0, 15)
147 plt.legend()
148 plt.tight_layout()
149 plt.savefig('egr_time_history.png', dpi=300)
150 plt.close()

```

Listing 1: Refined Cantera Python script for kinetic and thermodynamic EGR evaluation.

B Appendix: NASA CEA Input File Example (21.4% EGR)

The following text block represents the structural input syntax format (.inp) engineered to force the NASA CEA core engine to balance a complex chemical system without shifting the stoichiometric value ($\phi = 1.0$):

```
1  ### CEA analysis performed on Sun 07-Jun-2026 18:48:54
2
3  # Problem Type: "Assigned Enthalpy and Pressure"
4
5  prob case = -----3839 hp
6
7  # Pressure (1 value):
8  p,atm= 1
9
10 # Equivalence based on Fuel/Oxid. wt ratio (Eq 9.19*) (1 value):
11 phi = 1
12
13 # You selected the following fuels and oxidizers:
14 reac
15 fuel CH4          mole= 8.7816  t,k= 300.000
16 fuel CO2          mole= 12.6021  t,k= 300.000
17 fuel H2O          mole= 12.6021  t,k= 300.000
18 fuel N2           mole= 66.0141  t,k= 300.000
19 oxid O2           mole=100.0000  t,k= 300.000
20
21 # You selected these options for output:
22 # long version of output
23 # Proportions of any products will be expressed as Mole Fractions
24 # Heat will be expressed as siunits
25 output siunits
26
27 # Input prepared by this script:/var/www/sites/cearun/cgi-bin/
   CEARUN/prepareInputFile.cgi
28
29 ### IMPORTANT: The following line is the end of your CEA input
   file!
30 end
```

Listing 2: NASA CEA structural input file verification script.