

# Dependently Typed Functional Programming with Idris

## Lecture 4: Implementing Idris

Edwin Brady  
University of St Andrews

`ecb10@st-andrews.ac.uk`  
`@edwinbrady`

IDRIS internals:

- The core language, **TT**
- *Elaboration* from high level programs to **TT**
- Compilation challenges

Code is available to browse at

<https://github.com/edwinb/Idris-dev>

High level IDRIIS programs *elaborate* to a core language, TT:

- TT allows *only* data declarations and top level pattern matching definitions
- Limited syntax:
  - Variables, application, binders ( $\lambda$ ,  $\forall$ , `let`, patterns), constants
- All terms *fully explicit*
- Advantage: type checker is small ( $\approx 500$  lines) so less chance of errors
- Challenge: how to build TT programs from IDRIIS programs?

## Vectors, high level IDRIS

```
data Vect : Type -> Nat -> Type where
  Nil      : Vect a 0
  (:::)    : a -> Vect a k -> Vect a (S k)
```

## Vectors, high level IDRIS

```
data Vect : Type -> Nat -> Type where
  Nil      : Vect a 0
  (::)     : a -> Vect a k -> Vect a (S k)
```

## Vectors, TT

```
Nil      : (a : Type) -> Vect a 0
(::)     : (a : Type) -> (k : Nat) ->
           a -> Vect a k -> Vect a (S k)
```

# Elaboration Example

## Vectors, high level IDRIS

```
data Vect : Type -> Nat -> Type where
  Nil      : Vect a 0
  (::)     : a -> Vect a k -> Vect a (S k)
```

## Vectors, TT

```
Nil      : (a : Type) -> Vect a 0
(::)     : (a : Type) -> (k : Nat) ->
           a -> Vect a k -> Vect a (S k)
```

## Example

```
((::) Char (S 0) 'a' ((::) Char 0 'b' (Nil Char))
  -- ['a', 'b']
```

Pairwise addition, high level IDRIS

```
vAdd : Num a => Vect a n -> Vect a n -> Vect a n
vAdd Nil      Nil      = Nil
vAdd (x :: xs) (y :: ys) = x + y :: vAdd xs ys
```

## Step 1: Add implicit arguments

```
vAdd : (a : _) -> (n : _) ->  
      (Num a) -> Vect a n -> Vect a n -> Vect a n  
vAdd _ _ c (Nil _) (Nil _) = Nil _  
vAdd _ _ c ((::) _ _ x xs) ((::) _ _ y ys)  
    = (::) _ _ ((+) _ x y) (vAdd _ _ _ xs ys)
```



## Step 2: Solve implicit arguments

```
vAdd : (a : Type) -> (n : Nat) ->  
      (Num a) -> Vect a n -> Vect a n -> Vect a n  
vAdd a 0 c (Nil a) (Nil a) = Nil a  
vAdd a (S k) c ((::) a k x xs) ((::) a k y ys)  
    = (::) a k ((+) c x y) (vAdd a k c xs ys)
```

## Step 3: Make pattern bindings explicit

```
vAdd : (a : Type) -> (n : Nat) ->
      (Num a) -> Vect a n -> Vect a n -> Vect a n
pat a : Type, c : Num a .
  vAdd a 0 c (Nil a) (Nil a) = Nil a
pat a : Type, k : Nat, c : Num a .
pat x : a, xs : Vect a k, y : a, ys : Vect a k .
  vAdd a (S k) c ((::) a k x xs) ((::) a k y ys)
    = (::) a k ((+) c x y) (vAdd a k c xs ys)
```

IDRIS programs may contain several high level constructs not present in **TT**:

- Implicit arguments, type classes
- **where** clauses, **with** and **case** structures, pattern matching **let**, ...
- Types often left locally *implicit*

We want the high level language to be as *expressive* as possible, while remaining translatable to **TT**.

Consider Coq style theorem proving (with tactics) and Agda style (by pattern matching).

- *Pattern matching* is a convenient abstraction for humans to write programs
- *Tactics* are a convenient abstraction for building programs by refinement
  - i.e. explaining programming to a machine

Consider Coq style theorem proving (with tactics) and Agda style (by pattern matching).

- *Pattern matching* is a convenient abstraction for humans to write programs
- *Tactics* are a convenient abstraction for building programs by refinement
  - i.e. explaining programming to a machine

Idea: High level program structure directs *tactics* to build TT programs by refinement

The proof state is encapsulated in a monad, `Elab`, and contains:

- Current proof term (including *holes*)
  - Holes are incomplete parts of the proof term (i.e. sub-goals)
- Unsolved *unification problems*
- Sub-goal in *focus*
- Global context (definitions)

The proof state is encapsulated in a monad, `Elab`, and contains:

- Current proof term (including *holes*)
  - Holes are incomplete parts of the proof term (i.e. sub-goals)
- Unsolved *unification problems*
- Sub-goal in *focus*
- Global context (definitions)

We distinguish terms which have been typechecked from those which have not:

- `Raw` has not been type checked (and may contain placeholders, `_`)
- `Term` has been type checked (`Type` is a synonym)

Some primitive operations:

- Type checking
  - `check :: Raw -> Elab (Term, Type)`



Some primitive operations:

- Type checking
  - `check :: Raw -> Elab (Term, Type)`
- Normalisation
  - `normalise :: Term -> Elab Term`

Some primitive operations:

- Type checking
  - `check :: Raw -> Elab (Term, Type)`
- Normalisation
  - `normalise :: Term -> Elab Term`
- Unification
  - `unify :: Term -> Term -> Elab ()`

Some primitive operations:

- Type checking
  - `check :: Raw -> Elab (Term, Type)`
- Normalisation
  - `normalise :: Term -> Elab Term`
- Unification
  - `unify :: Term -> Term -> Elab ()`

Querying proof state

- Get the local environment
  - `get_env :: Elab [(Name, Type)]`
- Get the current proof term
  - `get_proofTerm :: Elab Term`

A *tactic* is a function which updates a proof state, for example by:

- Updating the proof term
- Solving a sub-goal
- Changing focus

For example:

- `focus :: Name -> Elab ()`
- `claim :: Name -> Raw -> Elab ()`
- `forall :: Name -> Raw -> Elab ()`
- `exact :: Raw -> Elab ()`
- `apply :: Raw -> [Raw] -> Elab ()`

Tactics can be combined to make more complex tactics

- By sequencing, with `do`-notation
- By combinators:
  - `try :: Elab a -> Elab a -> Elab a`
    - If first tactic fails, use the second
  - `tryAll :: [Elab a] -> Elab a`
    - Try all tactics, *exactly* one must succeed
    - Used to disambiguate overloaded names

Effectively, we can use the `Elab` monad to write proof scripts (c.f. Coq's `Ltac` language)

Given an IDRIS application of a function `f` to arguments `args`:

- Type check `f`
  - Yields types for each argument, `ty_i`

Given an IDRIIS application of a function  $f$  to arguments  $args$ :

- Type check  $f$ 
  - Yields types for each argument,  $ty_i$
- For each  $arg_i : ty_i$ , invent a name  $n_i$  and run the tactic `claim  $n_i$   $ty_i$`

Given an IDRIIS application of a function  $f$  to arguments  $args$ :

- Type check  $f$ 
  - Yields types for each argument,  $ty\_i$
- For each  $arg\_i : ty\_i$ , invent a name  $n\_i$  and run the tactic `claim  $n\_i$   $ty\_i$`
- Apply  $f$  to  $ns$



Given an IDRIIS application of a function  $f$  to arguments  $args$ :

- Type check  $f$ 
  - Yields types for each argument,  $ty\_i$
- For each  $arg\_i : ty\_i$ , invent a name  $n\_i$  and run the tactic `claim  $n\_i$   $ty\_i$`
- Apply  $f$  to  $ns$
- For each *non-placeholder*  $arg$ , `focus` on the corresponding  $n$  and elaborate  $arg$ .

Given an IDRIIS application of a function `f` to arguments `args`:

- Type check `f`
  - Yields types for each argument, `ty_i`
- For each `arg_i : ty_i`, invent a name `n_i` and run the tactic `claim n_i ty_i`
- Apply `f` to `ns`
- For each *non-placeholder* `arg`, `focus` on the corresponding `n` and elaborate `arg`.

(Complication: elaborating an argument may affect the type of another argument!)

## Append

```
(++) : {a : Type} -> {n : Nat} -> {m : Nat} ->  
      Vect a n -> Vect a m -> Vect a (n + m)
```

## Append

```
(++) : {a : Type} -> {n : Nat} -> {m : Nat} ->  
      Vect a n -> Vect a m -> Vect a (n + m)
```

To build an application `append Nil (1 :: 2 :: Nil)`

## Tactic script

```
do claim a Type ; claim n Nat ; claim m Nat
```

## Append

```
(++) : {a : Type} -> {n : Nat} -> {m : Nat} ->  
      Vect a n -> Vect a m -> Vect a (n + m)
```

To build an application `append Nil (1 :: 2 :: Nil)`

## Tactic script

```
do claim a Type ; claim n Nat ; claim m Nat  
   claim xs (Vect a n) ; claim ys (Vect a m)
```

## Append

```
(++) : {a : Type} -> {n : Nat} -> {m : Nat} ->  
      Vect a n -> Vect a m -> Vect a (n + m)
```

To build an application `append Nil (1 :: 2 :: Nil)`

## Tactic script

```
do claim a Type ; claim n Nat ; claim m Nat  
   claim xs (Vect a n) ; claim ys (Vect a m)  
   apply ((++) a n m xs ys)
```

## Append

```
((++)) : {a : Type} -> {n : Nat} -> {m : Nat} ->  
        Vect a n -> Vect a m -> Vect a (n + m)
```

To build an application `append Nil (1 :: 2 :: Nil)`

## Tactic script

```
do claim a Type ; claim n Nat ; claim m Nat  
   claim xs (Vect a n) ; claim ys (Vect a m)  
   apply ((++) a n m xs ys)  
   focus xs; elab Nil
```

## Append

```
((++)) : {a : Type} -> {n : Nat} -> {m : Nat} ->  
        Vect a n -> Vect a m -> Vect a (n + m)
```

To build an application `append Nil (1 :: 2 :: Nil)`

## Tactic script

```
do claim a Type ; claim n Nat ; claim m Nat  
   claim xs (Vect a n) ; claim ys (Vect a m)  
   apply ((++) a n m xs ys)  
   focus xs; elab Nil  
   focus ys; elab (1 :: 2 :: Nil)
```



## Append

```
((++)) : {a : Type} -> {n : Nat} -> {m : Nat} ->  
        Vect a n -> Vect a m -> Vect a (n + m)
```

To build an application `append Nil (1 :: 2 :: Nil)`

## Tactic script

```
do claim a Type ; claim n Nat ; claim m Nat  
   claim xs (Vect a n) ; claim ys (Vect a m)  
   apply ((++) a n m xs ys)  
   focus xs; elab Nil  
   focus ys; elab (1 :: 2 :: Nil)
```

Elaborating each sub-term (and running `apply`) also runs the `unify` operation, which fills in the `_`

Given a binder and its scope, say  $(x : S) \rightarrow T$

- Check that the current goal type is a **Type**
- Create a hole for **S**
  - `claim n_S Type`
- Create a binder with `forall x n_S`
- Elaborate **S** and **T**

For example, to build  $(n : \text{Nat}) \rightarrow \text{Vect Int } n$

Tactic script

```
do claim n_S Type
```

For example, to build  $(n : \text{Nat}) \rightarrow \text{Vect Int } n$

Tactic script

```
do claim n_S Type
  forall n n_S
```

For example, to build  $(n : \text{Nat}) \rightarrow \text{Vect Int } n$

Tactic script

```
do claim n_S Type
  forall n n_S
    focus n_S; elab Nat
```

For example, to build  $(n : \text{Nat}) \rightarrow \text{Vect Int } n$

Tactic script

```
do claim n_S Type
  forall n n_S
  focus n_S; elab Nat
  elab (Vect Int n)
```

## Elaborating terms

```
runElab :: Name -> Type -> Elab a -> Idris a  
build   :: Pattern -> PTerm -> Elab Term
```

## Elaborating terms

```
runElab :: Name -> Type -> Elab a -> Idris a  
build   :: Pattern -> PTerm -> Elab Term
```

- Elaboration is *type-directed*



## Elaborating terms

```
runElab :: Name -> Type -> Elab a -> Idris a  
build   :: Pattern -> PTerm -> Elab Term
```

- Elaboration is *type-directed*
- The `Idris` monad encapsulates system state

## Elaborating terms

```
runElab :: Name -> Type -> Elab a -> Idris a
build   :: Pattern -> PTerm -> Elab Term
```

- Elaboration is *type-directed*
- The `Idris` monad encapsulates system state
- The `Pattern` argument indicates whether this is the left hand side of a definition
  - Free variables on the lhs in IDRIIS become pattern bindings in `TT`
  - `patbind :: Name -> Elab ()` — convert current goal to pattern binding

## Elaborating terms

```
runElab :: Name -> Type -> Elab a -> Idris a
build   :: Pattern -> PTerm -> Elab Term
```

- Elaboration is *type-directed*
- The `Idris` monad encapsulates system state
- The `Pattern` argument indicates whether this is the left hand side of a definition
  - Free variables on the lhs in IDRIIS become pattern bindings in `TT`
  - `patbind :: Name -> Elab ()` — convert current goal to pattern binding
- `PTerm` is the representation of the high-level syntax

## Top level declarations

```
f : S1 -> ... -> Sn -> T
```

```
f x1 ... xn = e
```

## Top level declarations

```
f : S1 -> ... -> Sn -> T
```

```
f x1 ... xn = e
```

- Elaborate the type, and add `f` to the context
- Elaborate the lhs
  - Any out of scope names are assumed to be *pattern* variables
- Elaborate the rhs *in the scope of the pattern variables from the lhs*
- Check that the lhs and rhs have the same type

## Function with where block

```
f : S1 -> ... -> Sn -> T
f x1 ... xn = e
  where
    f_aux = ...
```

## Function with where block

```
f : S1 -> ... -> Sn -> T
f x1 ... xn = e
  where
    f_aux = ...
```

- Elaborate the lhs of `f`
- Lift the auxiliary definitions to top level functions *by adding the pattern variables from the lhs*
- Elaborate the auxiliary definitions
- Elaborate the rhs of `f` as normal

## High level IDRIIS

```
class Show a where
  show : a -> String

instance Show Nat where
  show 0 = "0"
  show (S k) = "s" ++ show k
```



## Elaborated TT

```
data Show : (a : Set) -> Set where
  ShowInstance : (show : a -> String) -> Show a

show : (Show a) -> a -> String
show (ShowInstance show') x = show' x

instanceShowNat : Show Nat
instanceShowNat = ShowInstance show where
  show : Nat -> String
  show 0 = "0"
  show (S k) = "s" ++ show k
```

Type class constraints are a special kind of implicit argument (c.f. Agda's *instance arguments*)

- Ordinary implicit arguments solved by *unification*
- Constraint arguments solved by a tactic
  - `resolveTC :: Elab ()`
  - Looks for a local solution first
  - Then looks for globally defined instances
    - May give rise to further constraints

Recent comment on <http://www.reddit.com/r/programming>:

*"There are also all kinds of issues with the complexity and performance of compiling languages that have dependent types."*

Recent comment on <http://www.reddit.com/r/programming>:

*"There are also all kinds of issues with the complexity and performance of compiling languages that have dependent types."*



(<http://www.xkcd.com/386> — Duty Calls)

- Conventionally seen as separation of *types* and *terms*
  - Erase types before executing a program
  - Perceived complexity with dependent types: what is a type and what is a term?

- Conventionally seen as separation of *types* and *terms*
  - Erase types before executing a program
  - Perceived complexity with dependent types: what is a type and what is a term?
- Really separation of *compile time* and *run time*
  - Erase *compile time only* terms before executing a program
  - Conventionally compile time only = *types*

- Conventionally seen as separation of *types* and *terms*
  - Erase types before executing a program
  - Perceived complexity with dependent types: what is a type and what is a term?
- Really separation of *compile time* and *run time*
  - Erase *compile time only* terms before executing a program
  - Conventionally compile time only = *types*
  - Distinction is harder to make with dependent types
    - but IDRIIS does!

The compiler erases all values which it can prove are unused at run-time, by:

- *Forcing*
  - Erase constructor arguments with value determined by an index



The compiler erases all values which it can prove are unused at run-time, by:

- *Forcing*
  - Erase constructor arguments with value determined by an index
- *Collapsing*
  - Erase data type with only one inhabitant
  - Relies on *totality*
  - Typically erases equality proofs, predicates, ...

The compiler erases all values which it can prove are unused at run-time, by:

- *Forcing*
  - Erase constructor arguments with value determined by an index
- *Collapsing*
  - Erase data type with only one inhabitant
  - Relies on *totality*
  - Typically erases equality proofs, predicates, ...
- *Identifying unused arguments*
  - Erase function and constructor arguments which are never inspected

# Forcing Example

## Vectors, TT

```
Nil    : (a : Type) -> Vect a 0
(::)   : (a : Type) -> (k : Nat) ->
        a -> Vect a k -> Vect a (S k)
```

## vAdd

```
vAdd : (a : Type) -> (n : Nat) ->
      (Num a) -> Vect a n -> Vect a n -> Vect a n
vAdd a 0 c (Nil a) (Nil a) = Nil a
vAdd a (S k) c ((::) a k x xs) ((::) a k y ys)
  = (::) a k ((+) c x y) (vAdd a k c xs ys)
```

## Vectors, TT

```
Nil    : Vect a 0
(::)   :  
      a -> Vect a k -> Vect a (S k)
```

## vAdd

```
vAdd : (a : Type) -> (n : Nat) ->  
      (Num a) -> Vect a n -> Vect a n -> Vect a n  
vAdd a 0 c (Nil ) (Nil ) = Nil  
vAdd a (S k) c ((::) x xs) ((::) y ys)  
    = (::) ((+) c x y) (vAdd a k c xs ys)
```

## Vectors, TT

```
Nil    : Vect a 0
(::)   :  
      a -> Vect a k -> Vect a (S k)
```

## vAdd

```
vAdd : (a : Type) -> (n : Nat) ->  
      (Num a) -> Vect a n -> Vect a n -> Vect a n  
vAdd  c (Nil ) (Nil ) = Nil  
vAdd  c ((::)      x xs) ((::)      y ys)  
= ((::)      ((+) c x y) (vAdd _ _ c xs ys))
```

Less than predicate, high level IDRIS

```
data LE : Nat -> Nat -> Type where  
  lt0 : LE 0 m  
  ltS : LE n m -> LE (S n) (S m)
```

# Collapsing Example

Less than predicate, TT

```
LE  : Nat -> Nat -> Type
lt0 : (m : Nat) -> LE 0 m
ltS : (n : Nat) -> (m : Nat) ->
      LE n m -> LE (S n) (S m)
```

minus

```
minus : (x : Nat) -> (y : Nat) -> LE y x -> Nat
minus x      0      (lt0 x)      = x
minus (S x) (S y) (ltS x y p) = minus x y p
```

# Collapsing Example

Less than predicate, TT

```
LE  : Nat -> Nat -> Type
lt0 :                      LE 0 m
ltS :
      LE n m -> LE (S n) (S m)
```

minus

```
minus : (x : Nat) -> (y : Nat) -> LE y x -> Nat
minus x      0      (lt0 )      = x
minus (S x) (S y) (ltS      p) = minus x y p
```



# Collapsing Example

Less than predicate, TT

```
LE  : Nat -> Nat -> Type
[lt0] :          LE 0 m
[ltS] :
      LE n m -> LE (S n) (S m)
```

minus

```
minus : (x : Nat) -> (y : Nat) -> LE y x -> Nat
minus x 0      (      )      = x
minus (S x) (S y) (      p) = minus x y p
```

# Collapsing Example

Less than predicate, TT

```
LE  : Nat -> Nat -> Type
[lt0] :                LE 0 m
[ltS] :
      -> LE (S n) (S m)
```

minus

```
minus : (x : Nat) -> (y : Nat) -> LE y x -> Nat
minus x      0      -      = x
minus (S x) (S y) -      = minus x y -
```

Some internal (undocumented) features for examining structure:

- REPL command `:di`
  - For “debug info”
- `%logging` directive
  - Displays elaborator progress
  - e.g. `%logging 5` for a high level of logging info
- `--dumpcases <filename>` compiler flag
  - Outputs compiled case trees

Some internal (undocumented) features for examining structure:

- REPL command `:di`
  - For “debug info”
- `%logging` directive
  - Displays elaborator progress
  - e.g. `%logging 5` for a high level of logging info
- `--dumpcases <filename>` compiler flag
  - Outputs compiled case trees

Additional exercise: use these features to examine the internal representations of your answers to earlier exercises

On this course, we have covered:

- Introductory programming with dependent types
  - Invariants, predicates, theorem proving
- Embedded Domain Specific Languages
  - Implementing the  $\lambda$ -calculus
  - Verification of extra-functional properties
- Effect management
  - Programming with side effects, implementing new effects
- Implementing a dependently typed language
  - Elaboration overview
  - Type erasure

Useful features to be added to IDRIS:

- deriving for type classes
- Run-time representation of data
- Decision procedures
  - e.g. Presburger arithmetic solver
- Programming tools
  - Type directed editing
  - Adapt hoople for IDRIS
- See <http://idris-lang.org/help-required>

- <http://idris-lang.org/documentation>
- The mailing list [idris-lang@groups.google.com](mailto:idris-lang@groups.google.com)
- The IRC channel, #idris, on [irc.freenode.net](http://irc.freenode.net)