

ULTRAGARSAS:

```
#define echoPin 11
#define trigPin 12

long duration;
int distance;

void setup() {
  pinMode(trigPin, OUTPUT);
  pinMode(echoPin, INPUT);
  Serial.begin(9600);
  Serial.println("Ultrasonic Sensor HC-SR04 Testas");
  Serial.println("su Arduino UNO R3");
}
void loop() {
  digitalWrite(trigPin, LOW);
  delayMicroseconds(2);
  digitalWrite(trigPin, HIGH);
  delayMicroseconds(10);
  digitalWrite(trigPin, LOW);
  duration = pulseIn(echoPin, HIGH);
  distance = duration * 0.034 / 2;
  Serial.println(distance);
}
```

ULTRAGARSAS; PASISUKA SERVO:

```
#define echoPin 11
#define trigPin 12
#include <Servo.h>
Servo myservo;
long duration;
int distance;

void setup() {

  myservo.attach(9);

  pinMode(trigPin, OUTPUT);
  pinMode(echoPin, INPUT);
  Serial.begin(9600);
  Serial.println("Ultrasonic Sensor HC-SR04 Testas");
  Serial.println("with Arduino UNO R3");
}
void loop() {
  digitalWrite(trigPin, LOW);
```

```

delayMicroseconds(2);
digitalWrite(trigPin, HIGH);
delayMicroseconds(10);
digitalWrite(trigPin, LOW);
duration = pulseIn(echoPin, HIGH);
distance = duration * 0.034 / 2;
Serial.println(distance);

if (distance < 20) {

    myservo.write(180); //clockwise rotation
    delay(1000); //rotation duration in ms
    myservo.write(10); //counterclockwise rotation
    delay(1000); //rotation duration in ms
    myservo.write(90); //clockwise rotation
    delay(100); //rotation duration in ms
}
}

```

VAZIAVIMAS TIESIAI:

```

#include <MotorDriver.h>
MotorDriver m;

void setup() {
}
void loop() {

    m.motor(1,FORWARD,70);
    m.motor(2,FORWARD,80);
}

```

VAZIAVIMAS ATGAL:

```

#include <MotorDriver.h>
MotorDriver m;

void setup() {
}
void loop() {

    m.motor(1,BACKWARD,70);
    m.motor(2,BACKWARD,80);
}

```

SUKIMASIS:

```
#include <MotorDriver.h>
MotorDriver m;

void setup() {
}
void loop() {

    m.motor(1, BACKWARD, 70);
    m.motor(2, BACKWARD, 80);
}
```

VAZIAVIMAS TIESIAI IR SERVO:

```
#include <MotorDriver.h>
MotorDriver m;
#include <Servo.h>
Servo myservo;
const int trigPin = 12;
const int echoPin = 11;
float duration, distance;
void setup() {
    myservo.attach(9);
    pinMode(trigPin, OUTPUT);
    pinMode(echoPin, INPUT);
    Serial.begin(9600);
}
void loop() {
    digitalWrite(trigPin, LOW);
    delayMicroseconds(2);
    digitalWrite(trigPin, HIGH);
    delayMicroseconds(10);
    digitalWrite(trigPin, LOW);

    duration = pulseIn(echoPin, HIGH);
    distance = (duration*.0343)/2;
    Serial.print("Distance: ");
    Serial.println(distance);
    delay(100);
    myservo.write(180); //clockwise rotation
    delay(1000);
    myservo.write(10); //counterclockwise rotation
    delay(1000);
    m.motor(1, FORWARD, 70);
    m.motor(2, FORWARD, 80);
}
```