Husky Hack Sample Data Dictionary - v2

Purpose: support student prototypes for “Stop the Scam Before the Money Moves.”

All people, events, values, outcomes, and identifiers are fictional and synthetic.

Files

HuskyHack_Synthetic_Events_v2.csv - 7,471 events for 118 fictional members, 2026-08-31 to 2026-10-30. Contains only what So observe at the time of each event.

HuskyHack_Member_Key_v2.csv - one row per member: what was really happening, the outcome, and dollars attempted / sent recovered. Use it to check your design, not as a trigger.

How to use

1. Start with an anchor persona: M1001 Linda, M1002 Michael, M1003 Sarah, M1004 James. Filter the events file by synthetic_m rows are already in time order.

2. Follow a single payment with payment_id to see where it could have been paused.

3. Test your trigger on the 20 legitimate look-alikes (Member Key: is_legitimate_lookalike = Yes). If it fires on them, design the lo they experience.

4. Triggers may use only fields marked 'Yes' under Observable at Decision Time. The Member Key is the answer key.

Limits

The data is designed for exploration and prototyping, not for production fraud modeling or statistical benchmarking. 41% of mer scam victims by design; real prevalence is far lower, so false positives matter far more in practice than this file suggests.

Do not infer that a field is currently available in real time at Sound. The Starter Kit's Capability Assumptions section says what tea assume for this challenge.

Teams should explain how false positives, member consent, accessibility, escalation, and recovery are handled.

Color key on the dictionary sheets: green = new in v2; yellow = revised; red = removed or moved.

Synthetic-data governance reference: https://csrc.nist.gov/pubs/sp/800/188/final