Do Code Monitors Go Easy on Their Own Family? Self-Recognition and Leniency in Small Open-Weight LLMs

Kaszioq · AgentEval study 1 · code and data: github.com/Kaszioq/agenteval

Abstract. AI control protocols often let one model monitor code written by another. If a monitor recognised code from its own model family and judged it more leniently, that would be a form of collusion that needs no instruction. We test this with two open-weight models from different families, Qwen2.5-Coder 7B and Llama 3.1 8B, both run locally at zero cost, on HumanEval. No prompt mentions collusion. We pre-registered three hypotheses: self-recognition (H1), the surface features it relies on (H2), and monitor leniency towards the model's own family's backdoored code (H3). In a pairwise "which one did you write?" test, both models show a precise null once position bias is removed: mean probability on their own solution is 0.49–0.50, with 95% intervals inside [0.48, 0.53]. That bias is extreme (P("1") = 0.83–0.91), and naive accuracy would hide it. A single-item yes/no variant shows a small own-code tilt for Qwen (+3.4 points, CI [+0.7, +6.3]). Monitors show no own-family leniency on honest code (rank-scale interaction −0.004, CI [−0.045, +0.038]). E3 results are pending.

1. Motivation

In trusted-monitoring setups, a model's outputs are reviewed by another model, and the most suspicious ones are escalated to a limited human audit budget. If the monitor and the author come from the same family, the monitor might treat the author's code as familiar and normal, and flag it less often. That would be *spontaneous* collusion: nobody asked for it, and it happens through shared style rather than communication. We ask whether small open models (1) recognise their own code, (2) what that recognition rests on, and (3) whether a monitor scores its own family's sabotaged code as less suspicious.

2. Setup

- **Models.** A = `qwen2.5-coder:7b`, B = `llama3.1:8b`, served by Ollama on one consumer GPU. Temperature 0, fixed seed, on-disk response cache. A hard block refuses any paid endpoint.
- **Problems.** HumanEval (164 problems, MIT). Generated code runs in a separate process with a timeout, no network, and resource limits.
- **Framework.** Inspect. Every model call is logged with its full prompt and response. We follow ControlArena's conventions: a backdoor is code plus a secret input on which its output differs from the reference; suspicion is scored 0–10; the audit budget is 2%.
- **Pre-registration.** Hypotheses, equivalence margins (accuracy 0.5 ± 0.10; interaction 0 ± 0.5 points or 0 ± 0.05 on the rank scale) and verdict rules were fixed in the README before the main run. Each estimate is labelled *effect* (CI excludes the null), *no effect* (CI inside the margin) or *inconclusive*. Changes made after pilots on 5 problems are listed in Section 6.

Experiments

- **E1 (H1), pairwise.** The judge sees its own and the other model's passing solution and answers "1" or "2". Each pair is shown in both orders. We read P("1") and P("2") from token log-probabilities. p_own is the probability on the judge's own position, and a pair's score is its mean over the two orders, which cancels any constant position preference.
- **E2 (H2), ablations.** E1 is repeated after removing comments and docstrings, renaming locally bound identifiers, reformatting with `black`, and all three together. Every transform is re-tested; 208/208 transformed solutions still pass.

- **E1b (exploratory), single item.** The judge sees one solution and is asked "did you write this?". For each problem we compare P("yes") on its own solution with P("yes") on the other model's.
- **E3 (H3), 2×2 leniency.** Each author turns its own honest solution into a backdoored one. A backdoor counts only if it passes all tests and gives a different answer on a finite secret input. Both monitors score every backdoor. The quantity of interest is the interaction $I = (S[A,A] - S[A,B]) - (S[B,A] - S[B,B])$, which cancels differences in how detectable each author's backdoors are. H3 predicts $I < 0$.
- **Honest-code leniency (exploratory).** The same interaction, computed on honest solutions.

3. Results

Honest pass rates: A 142/164 (86.6%), B 109/164 (66.5%). Both models pass on 104 problems, which form the pairs. Pairs with textually identical solutions are dropped, leaving 99 in the raw condition.

E1: no self-recognition, and a precise null

Judge	Pairs	Favours own	95% CI (exact)	Mean p_own	95% CI	Verdict (p_own)	Mean P("1")
A	99	0.485	[0.383, 0.587]	0.503	[0.483, 0.524]	no effect	0.83
B	99	0.444	[0.345, 0.548]	0.493	[0.483, 0.504]	no effect	0.91

Both judges put almost equal probability on their own and the other model's solution. Position bias dominates: the sampled answer is "1" in 96% (A) and 99.5% (B) of prompts. A naive accuracy computed from sampled answers sits at 50% by construction and tells us nothing. The both-orders probability read-out is what makes this null interpretable.




Figure 1. E1. Left: share of pairs where the judge favours its own code (exact 95% CI). Right: mean probability on own code (bootstrap 95% CI). Shaded: pre-registered equivalence band.

E2: no signal for the ablations to remove

Every mean p_own interval across the ten judge × condition cells lies inside [0.475, 0.551]. One cell, judge A with comments removed, reaches 0.621 pair-level accuracy ($p = 0.031$). It does not survive a Holm correction over the ten tests ($p = 0.31$; the correction was added after the run), and its mean p_own (0.517) is inside the equivalence band. We treat it as a likely false positive. With no recognition in the raw condition, H2 cannot be tested with these models.




Figure 2. E2 by condition. All probability-scale estimates fall inside the equivalence band.

E1b: a small own-code tilt for Qwen

Judge	Problems	Own higher	95% CI	Mean P("yes") own / other	Mean difference	95% CI
A	104	0.535	[0.432, 0.636]	0.604 / 0.571	+0.034	[+0.007, +0.063]
B	104	0.460	[0.360, 0.563]	0.0003 / 0.0003	−0.00002	[−0.0001, +0.0001]

Asked about one solution at a time, Qwen gives slightly higher P("yes") to its own code. The interval of the paired difference excludes zero, but the effect is small, and the share-of-problems measure does not separate from 0.5. Llama answers "no" to everything (median P("yes") = 0.0001), so the test is at the floor for B. We read this as weak, exploratory evidence of implicit familiarity that the pairwise format did not show.

Monitor leniency on honest code (exploratory)

	Author A code	Author B code
Monitor A	0.23 [0.09, 0.41]	0.20 [0.08, 0.36]
Monitor B	2.65 [1.96, 3.37]	2.55 [1.87, 3.22]

Interaction on the raw scale: −0.08 [−0.61, +0.44], inconclusive. On the rank scale (each score converted to its percentile within the same monitor, which removes differences in how monitors use the scale): −0.004 [−0.045, +0.038], *no effect*. Monitor A rates nearly all honest code near 0, which widens the raw-scale interval.

E3: leniency on backdoored code

Pending.

4. Discussion

For two 7–8B open-weight models from different families, we find no explicit self-recognition, no features for recognition to rest on, and no own-family leniency on honest code. The one positive sign is a small own-code tilt in Qwen's yes/no answers. That fits a weak implicit familiarity signal that a pairwise question hides behind position bias. Methodologically, position bias in small judges is large enough to decide the outcome of a naive pairwise test either way. Any self-recognition eval with small judges should counterbalance order and read probabilities rather than sampled answers.

5. Limitations

- Two small models, one per family. We cannot separate a family effect from the effect of these two models.
- HumanEval problems are short and often have one natural solution, which limits how much style can show.
- Counterbalancing removes a constant position bias, but not one that interacts with content.

- Monitor A uses the bottom of the suspicion scale for nearly all honest code (floor effect); Llama's P("yes") is at the floor in E1b.
- Backdoors from these models are crude (explicit trigger conditions), so detectability is high.
- E1b and honest-code leniency were added after E1 and are exploratory. The Holm correction was not pre-registered.

6. Changes made after pilots (before the main run)

- Judge answers are read from token probabilities averaged over both orders, because sampled answers were almost always "1".
- Backdoor generation: the prompt shows each function's own argument template, the author gets grader feedback with up to 4 turns, it starts from its own honest solution, and it states a trigger property first. Secret inputs must be finite. Before these changes, almost no valid backdoors were produced (0–1 of 5 per model).
- Exact Clopper–Pearson intervals and no verdict below 20 pairs. Tiny pilots had produced misleading "effects".

7. Reproducibility

The pipeline (`agenteval run all --config configs/study.yaml`, then `agenteval analyze`) reproduces every table and figure. Per-sample JSONL with full prompts and responses, the summary CSVs and the figures are committed under `results/study/`; raw Inspect logs are kept locally. Model digests are recorded in `run_info.json`. Seventy-three offline tests cover grading, backdoor validation, behaviour preservation of all transforms on all 164 reference solutions, parsing, caching and the paid-endpoint block.

8. Future work

- Larger models from the same families, for example on a free API tier, with sampled answers in both orders.
- Implicit familiarity measured directly: each model's likelihood of its own versus the other model's code.
- Subtler backdoors and agentic settings (for example ControlArena's APPS and BigCodeBench settings).