


Kathará

kathara lab

Subnetting IPv4

Version	2.0
Author(s)	T. Caiazzi, G. Di Battista
E-mail	contact@kathara.org
Web	http://www.kathara.org/
Description	Exercises on IPv4 subnetting

© Computer Networks Research Group
Roma Tre University




copyright notice


- All the pages/slides in this presentation, including but not limited to, images, photos, animations, videos, sounds, music, and text (hereby referred to as “material”) are protected by copyright.
- This material, with the exception of some multimedia elements licensed by other organizations, is property of the authors and/or organizations appearing in the first slide.
- This material, or its parts, can be reproduced and used for didactical purposes within universities and schools, provided that this happens for non-profit purposes.
- Information contained in this material cannot be used within network design projects or other products of any kind.
- Any other use is prohibited, unless explicitly authorized by the authors on the basis of an explicit agreement.
- The authors assume no responsibility about this material and provide this material “as is”, with no implicit or explicit warranty about the correctness and completeness of its contents, which may be subject to changes.
- This copyright notice must always be redistributed together with the material, or its portions.

© Computer Networks Research Group
Roma Tre University

lab-1-lan: analyze the scenario



© Computer Networks Research Group
Roma Tre University



lab-1-lan: configurations

lab.conf

```
router1[0]="A/00:00:00:00:00:a1"
router1[1]="B/00:00:00:00:00:b1"
router1[image]="kathara/core"
router1[ipv6]="false"


router2[0]="B/00:00:00:00:00:b2"
router2[image]="kathara/core"
router2[ipv6]="false"

pc1[0]="A/00:00:00:00:00:01"
pc1[image]="kathara/core"
pc1[ipv6]="false"
```

lab.conf

```
pc2[0]="A/00:00:00:00:00:01"
pc2[image]="kathara/core"
pc2[ipv6]="false"
```

© Computer Networks Research Group
Roma Tre University



lab-1-lan: configurations

router1.startup

```
ip address add 200.100.50.1/24 dev eth0
ip address add 10.0.0.2/30 dev eth1
ip route add default via 10.0.0.1
```

pc1.startup

```
ip address add 195.11.14.5/24 dev eth0
ip route add default via 195.11.14.1
```

router2.startup


```
ip address add 10.0.0.1/30 dev eth0
```

pc2.startup

```
ip address add 200.1.1.7/24 dev eth0
ip route add default via 200.1.1.1 dev eth0
```

© Computer Networks Research Group
Roma Tre University

lab-1-lan: questions




Inspect the routing table of router 1, how many entries are there?

What is the broadcast address for LAN A?

What is the broadcast address for LAN B?

© Computer Networks Research Group
Roma Tre University

lab-1-lan: inspecting the routing table




router1

```
root@router1:~# ip route
default via 10.0.0.1 dev eth1
10.0.0.0/30 dev eth1 proto kernel scope link src 10.0.0.2
200.100.50.0/24 dev eth0 proto kernel scope link src 200.100.50.1
```

© Computer Networks Research Group
Roma Tre University

lab-1-lan: inspecting the routing table




router1

```
root@router1:/# ip route
default via 10.0.0.1 dev eth1
10.0.0.0/30 dev eth1 proto kernel scope link src 10.0.0.2
200.100.50.0/24 dev eth0 proto kernel scope link src 200.100.50.1
```

© Computer Networks Research Group
Roma Tre University

lab-1-lan: checking the broadcast address




router1

```
root@router1:/# route
Dst             Gateway         Prefsrc         Protocol  Scope   Dev             Table
default         10.0.0.1                                          eth1
10.0.0.0/30                     10.0.0.2        kernel    link    eth1
                                200.100.50.1    kernel    link    eth0
                                10.0.0.2        kernel    host    eth1            local
10.                             10.0.0.2        kernel    link    eth1            local
127.        /8                  127.0.0.1       kernel    host    lo              local
127.0.                          127.0.0.1       kernel    host    lo              local
127.255.    5.255               127.0.0.1       kernel    link    lo              local
200.100.5   .1                  200.100.50.1    kernel    host    eth0            local
200.100.50.255                  200.100.50.1    kernel    link    eth0            local
```

Broadcast address for LAN A

© Computer Networks Research Group
Roma Tre University

lab-1-lan: checking the broadcast addresses




Broadcast address for LAN B

router1

	Gateway	Prefsrc	Protocol	Scope	Dev	Table
ult	10.0.0.1				eth1	
.0.0/30		10.0.0.2	kernel	link	eth1	
100.50.0/24		200.100.50.1	kernel	link	eth0	
.0.2		10.0.0.2	kernel	host	eth1	local
10.0.0.3		10.0.0.2	kernel	link	eth1	local
127.0.0.0/8		127.0.0.1	kernel	host	lo	local
127.0.0.1		127.0.0.1	kernel	host	lo	local
127.255.255.255		127.0.0.1	kernel	link	lo	local
200.100.50.1		200.100.50.1	kernel	host	eth0	local
200.100.50.255		200.100.50.1	kernel	link	eth0	local

© Computer Networks Research Group
Roma Tre University

lab-2-lan: complete the configurations




© Computer Networks Research Group
Roma Tre University

lab-2-lan: complete the configurations

Open the lab folder and complete the configuration by filling in the fields marked with **X**s.

There is only one solution.
Once the configuration is complete, each device should reach the others.




© Computer Networks Research Group
Roma Tre University

lab-2-lan: modify router2 commands

In the provided configuration router2 has **two different entries** (corresponding to the /25 prefixes) in the routing table.

Can we provide the same connectivity adding a single entry in the routing table?

Modify router 2 commands and try to see if it works.




© Computer Networks Research Group
Roma Tre University

lab-4-lan: complete the configurations

The configuration of router2 is not complete.

Complete the configuration by filling in the fields marked with **X**s.

Verify your work by pinging the PCs from router2.



© Computer Networks Research Group
Roma Tre University