

Lab Goal : This lab was designed to teach you more about a linked list and using a linked list in a class as an instance variable / data field.

Lab Description : Use `ListNode` to write some basic `LinkedList` methods.

PART 1 – Open the `ListFunHouseTwo.java` file and complete the methods in this class.

PART 2 – Use the `ListFunHouseTwoRunner` to test your `ListFunHouseTwo` class.

ListNode – stores a value and a reference to the next node

```
public class ListNode implements Linkable
{
    private Comparable listNodeValue;
    private ListNode nextListNode;

    public ListNode(){
        listNodeValue = null;
        nextListNode = null;
    }

    public ListNode(Comparable value, ListNode next){
        listNodeValue=value;
        nextListNode=next;
    }

    public Comparable getValue(){
        return listNodeValue;
    }

    public ListNode getNext(){
        return nextListNode;
    }

    public void setValue(Comparable value){
        listNodeValue = value;
    }

    public void setNext(Linkable next){
        nextListNode = (ListNode)next;
    }
}
```

EXTENSION : Modify `ListNode` by adding in a `ListNode prevListNode` instance variable / data field. Rewrite the program as a double/circular linked list.

Files Needed ::

`ListNode.java`
`Linkable.java`
`ListFunHouseTwo.java`
`ListFunHouseTwoRunner.java`

Sample Data :

See the main of the Runner.

Sample Output :

```
Original list values
over up -a-2-1 2.1 34 at on go

num nodes = 8

List values after calling nodeCount
over up -a-2-1 2.1 34 at on go

List values after calling doubleLast
over up -a-2-1 2.1 34 at on go go

List values after calling doubleFirst
over over up -a-2-1 2.1 34 at on go go

List values after calling removeXthNode(2)
over up 2.1 at go
```

List values after calling `setXthNode(2,one)`

over one 2.1 one go