

Lab Goal : The lab was designed to teach you more about objects and classes.

Lab Description : In this program, you are to create a Roman Numeral class to handle roman numeral operations.

How to convert a Roman Numeral to a standard base ten number :: Locate the first individual roman number in the roman number string. Sum up the numeric value of the individual number. Chop of the individual roman numeral from the string and continue the process if the string has more numbers left.

How to convert a standard base ten number to a Roman Numeral :: Find the first Roman numeral less than the number. Add the roman numeral to a string. Subtract the value of the Roman Numeral from the number. Repeat this until the original number is less than the current Roman Numeral. Move to the next Roman Numeral in the list and repeat the process.

Sample Data :

see the main

Sample Output :

10 is X

100 is C

1000 is M

2500 is MMD

1500 is MD

23 is XXIII

38 is XXXVIII

49 is XLIX

LXXVII is 77

XLIX is 49

XX is 20

XLIX is 49

Roman 1 :: XXI

Roman 2 :: XXV

rOne.equals(rTwo) == false

rOne.compareTo(rTwo) == -4

rTwo.compareTo(rOne) == 4

Files Needed ::

RomanNumeral.java

RomanNumeralRunner.java

```
{1000,900,500,400,100,90,
 50,40,10,9,5,4,1}
```

```
{"M","CM","D","CD","C","XC",
 "L","XL","X","IX","V","IV","I"}
```

algorithm help

basic logic to convert an int to roman

loop through the array of numbers

while orig num >= curr number

add roman to string

subtract curr number from orig