# THESIS TITLE SDFSF SFASDFA ASFSFAS ASDFASDFAS ADSFASDFADS SADFASDF ASFASFAS FASGAS GAS GASG WETW AEFW EFW EFWEFWE GW GW GARWGAWRGAWG

**A PROJECT REPORT**

***Submitted by***


**JOHN SDFSFD**

**JANE**

**ALEXANDRIA DHGG FHYGH FHH**

**ALEXANDRIA FHGHH**


***in partial fulfillment of the requirements for the degree of***

**BACHELOR OF ENGINEERING**

**IN**

COMPUTER SCIENCE AND ENGINEERING


**COLLEGE OF ENGINEERING GUINDY**

**ANNA UNIVERSITY : CHENNAI 600 025**


**APRIL 2026**

# ANNA UNIVERSITY : CHENNAI 600 025

# BONAFIDE CERTIFICATE

Certified that this project report **"THESIS TITLE SDFSF SFASDFA ASFSFAS ASDFASDFAS ADSFASDFADS SADFASDF ASFASFAS FASGAS GAS GASG WETW AEFW EFW EFWEFWE GW GW GARWGAWRGAWG"** is the bonafide work of **John sdfsfd (2022103002), Jane (2022103002), Alexandria dhgg fhygh fhh (2022103002) and Alexandria fhghh (2022103002)** who carried out the project work under my supervision.

**SIGNATURE**
**Dr. V. MARY ANITA RAJAM**
**HEAD OF THE DEPARTMENT**
Department of Computer Science and Engineering,

Anna University,
Chennai 600025.

**SIGNATURE**
**Dr. SUPERVISOR NAME**
**SUPERVISOR**
Designation of Supervisor,
Department of Computer Science and Engineering,
Anna University,
Chennai 600025.

# ACKNOWLEDGEMENT

We express our deep gratitude to our guide, **Dr. Supervisor Name**, Designation of Supervisor, Department of Computer Science and Engineering, for guiding us through every phase of the project. We appreciate her thoroughness, tolerance and ability to share her knowledge with us. We would also like to thank her for her kind support and for providing necessary facilities to carry out the work.

We are extremely grateful to **Dr. V. Mary Anita Rajam**, Professor & Head of the Department, Department of Computer Science and Engineering, Anna University, Chennai – 25, for extending the facilities of the Department towards our project and for her unstinting support.

We express our thanks to the panel of reviewers **Dr. P. Geetha**, Professor, Department of Computer Science and Engineering and **Dr. S. Sudha**, Professor, Department of Computer Science and Engineering, for their valuable suggestions and critical reviews throughout the course of our project.

We express our thanks to all other teaching and non-teaching staff who helped us in one way or other for the successful completion of the project. We would also like to thank our parents, family and friends for their indirect contribution in the successful completion of this project.

**JOHN SDFSFD** **JANE** **ALEXANDRIA DHGG FHYGH FHH**

**ALEXANDRIA FHGHH**

# ABSTRACT

This is the abstract.

# TABLE OF CONTENTS


| CHAPTER NO. | TITLE | PAGE NO. |
|---|---|---|
| | **ABSTRACT** | **iii** |
| | **LIST OF TABLES** | **vii** |
| | **LIST OF FIGURES** | **viii** |
| | **LIST OF SYMBOLS** | **ix** |
| **1** | **INTRODUCTION** | **1** |
| | 1.1 BACKGROUND AND MOTIVATION | 1 |
| | 1.2 PROBLEM STATEMENT | 2 |
| | 1.3 OBJECTIVES | 3 |
| | 1.3.1 Research Questions | 3 |
| | 1.4 SCOPE AND CONTRIBUTIONS | 4 |
| | 1.4.1 Scope of the Work | 4 |
| | 1.4.2 Major Contributions | 5 |
| | 1.5 SIGNIFICANCE OF THE STUDY | 5 |
| | 1.6 THESIS ORGANIZATION | 6 |
| | 1.6.1 Expected Outcomes of the Study | 7 |
| **2** | **LITERATURE REVIEW** | **8** |
| | 2.1 OVERVIEW OF EXISTING WORK | 8 |
| | 2.2 METHODOLOGICAL FOUNDATIONS | 9 |
| | 2.3 ISL CSLR PROGRESS | 9 |
| | 2.3.1 Multimodal Gains | 9 |
| | 2.3.2 Deployment Constraints | 9 |
| | 2.3.3 Sequence Complexity | 9 |
| | 2.3.4 RGB Methods | 10 |

| CHAPTER NO. | TITLE | PAGE NO. |
|---|---|---|


| | | |
|---|---|---|
| | 2.3.5 Pose Methods | 10 |
| | 2.4 EVOLUTION OF CSLR ARCHITECTURES | 11 |
| | 2.4.1 CNN-RNN-CTC Pipelines | 11 |
| | 2.4.2 Temporal Convolution and Transformer-Based Models | 11 |
| | 2.5 DATA AND ANNOTATION CONSIDERATIONS | 12 |
| | 2.6 FUSION STRATEGIES IN MULTIMODAL CSLR | 12 |
| | 2.7 EVALUATION PRACTICES AND LIMITATIONS | 13 |
| | 2.8 RESEARCH GAPS IDENTIFIED | 14 |
| | 2.9 IMPLICATIONS FOR THE PROPOSED METHODOLOGY | 14 |
| | 2.10 CHAPTER SUMMARY | 15 |
| **3** | **PROPOSED METHODOLOGY / SYSTEM DESIGN** | **16** |
| | 3.1 SECTION 1 | 16 |
| | 3.2 SECTION 2 | 16 |
| **4** | **IMPLEMENTATION AND RESULTS** | **17** |
| | 4.1 PERFORMANCE METRICS | 17 |
| | 4.2 TEST CASES | 18 |
| **5** | **CONCLUSION AND FUTURE WORK** | **19** |
| | **APPENDIX** | **20** |
| **1** | **TOPIC 1** | **20** |
| | 1.1 SECTION 1 | 20 |
| | 1.2 SECTION 2 | 20 |
| **2** | **TOPIC2** | **21** |
| **3** | **TOPIC3** | **22** |

**REFERENCES** **23**

## LIST OF TABLES


| TABLE NO. | TITLE | PAGE NO. |
|---|---|---|
| 4.1 | Performance Metrics Used for Evaluation | 17 |

## LIST OF FIGURES


| FIGURE NO. | TITLE | PAGE NO. |
|---|---|---|
| 3.1 | System Architecture adafsfaaaa avaaaaaaaa aaaaaaaaaaas ssssss sssssssssssssssss | 16 |

# LIST OF SYMBOLS

| | | |
|---|---|---|
| A | - | This is symbol A |
| B | - | This is a very long description to check if line wraps correctly when the description is multiline |

# CHAPTER 1

# INTRODUCTION

## 1.1 BACKGROUND AND MOTIVATION

Communication through sign language is essential for Deaf and hard-of-hearing communities. In many practical settings, however, communication still depends on the availability of a human interpreter. This dependency creates delays, increases cost, and reduces privacy in education, healthcare, public services, and day-to-day interactions.

Continuous Sign Language Recognition (CSLR) attempts to bridge this gap by converting a sequence of sign gestures from video into a sequence of textual units. Unlike isolated sign recognition, CSLR must handle transitions between signs, signer-specific motion patterns, variable signing speed, occlusion, and co-articulation effects where neighboring signs influence each other.

Recent progress in deep learning, pose estimation, and efficient sequence models has made CSLR increasingly feasible for real-world deployment. At the same time, practical systems for Indian Sign Language still face challenges related to limited labeled data, signer diversity, and the need for robust inference under unconstrained backgrounds. These factors motivate a focused study on a scalable and reliable CSLR pipeline.

From a societal viewpoint, improving CSLR has direct value for inclusive communication access. A dependable recognition layer can support educational tools, public-service interfaces, and assistive workflows where response time and consistency matter. For this reason, the thesis approaches CSLR not

only as a model-accuracy problem but also as a reliability and usability problem.

From a technical viewpoint, CSLR is a sequence transduction task with high intra-class variation and subtle inter-class distinctions. Two sign instances corresponding to the same gloss can look different across signers, while different glosses may share similar early motion trajectories. This ambiguity requires architectures that preserve long-range temporal context and retain fine-grained motion cues rather than relying on static frame-level features.

## 1.2 PROBLEM STATEMENT

The core problem addressed in this work is the design of a robust CSLR system that can recognize continuous Indian Sign Language from video streams with acceptable accuracy and latency. A useful system must preserve temporal context, handle noisy visual conditions, and produce stable predictions across different signers.

Existing approaches often perform well only in constrained settings, such as fixed camera placement or limited signer variability. When deployed in practical environments, their performance may degrade due to motion blur, background clutter, partial body visibility, and inconsistent frame quality. Therefore, this thesis focuses on end-to-end design choices that improve both recognition quality and deployment readiness.

The problem can also be viewed as aligning variable-length visual sequences with variable-length label sequences while minimizing temporal confusion at sign boundaries. In practical terms, this means the system must remain stable when gestures overlap, when hand trajectories are partially occluded, and when signer pace changes abruptly. A robust design must therefore combine strong visual representation learning with sequence modeling that is tolerant to alignment uncertainty.

## 1.3 OBJECTIVES

The major objectives of this thesis are listed below.

- Build a modular CSLR workflow that supports data preparation, training, evaluation, and inference as separate but connected stages.
- Integrate complementary visual cues, including RGB appearance and pose-related motion information, to improve temporal understanding.
- Evaluate the system using clear, reproducible metrics so that model quality and failure cases can be compared consistently.
- Improve practical usability by targeting stable predictions and manageable computational cost.

In addition to model-level goals, the implementation objective is to keep the system configurable. This includes parameterized scripts, reusable preprocessing steps, and structured experiment settings that can be adapted for later improvements.

### 1.3.1 Research Questions

To operationalize the objectives, this thesis addresses the following research questions.

1. How effectively can a modular CSLR pipeline maintain recognition quality across continuous sign sequences with realistic temporal variation?
2. To what extent does combining RGB appearance and pose-derived

motion information improve sequence-level prediction stability?

3. Which error patterns remain dominant after multimodal integration, and how can they guide future improvements?

These questions connect model design, implementation choices, and evaluation strategy. They also provide a clear structure for interpreting results in later chapters.

## 1.4 SCOPE AND CONTRIBUTIONS

### 1.4.1 Scope of the Work

This work concentrates on recognition of continuous sign sequences in Indian Sign Language using video-based inputs. The thesis addresses dataset handling, preprocessing, feature representation, sequence modeling, and performance analysis. The translation of recognized signs into grammatically refined natural language is treated as a downstream extension and is not the primary focus.

The study also prioritizes engineering reproducibility. The pipeline is designed so that experiments can be repeated with different hyperparameters, feature combinations, and model checkpoints without changing the full code structure.

The practical scope includes offline experimentation and deployment-focused inference workflows. Although this thesis does not claim full multilingual production support, it presents design choices that can extend to broader sign vocabularies and larger datasets in future work.

### 1.4.2 Major Contributions

The key contributions of this thesis are summarized below.

1. A complete CSLR pipeline with clear stage separation for data preparation, training, and inference.
2. A multi-cue recognition strategy that combines visual and motion-related information to improve sequence understanding.
3. A comparative evaluation setup with interpretable metrics to analyze recognition effectiveness.
4. A deployment-oriented implementation structure that supports incremental extension and practical testing.
5. A structured analysis of failure modes, with emphasis on transition errors in continuous signing.
6. Documentation-driven workflow support to improve reproducibility for future researchers and developers.

Together, these contributions position the work as both a methodological study and an engineering artifact. The thesis therefore emphasizes not only what performance is achieved, but also how consistently the system can be reproduced and extended.

## 1.5 SIGNIFICANCE OF THE STUDY

The significance of this work lies in its attempt to close the gap between experimental CSLR models and practically usable systems. In many academic studies, improvements are reported at benchmark level but are difficult to transfer into robust real-world pipelines. By structuring the workflow into reusable modules and evaluating behavior under varied conditions, this thesis

contributes toward more dependable CSLR development practices.

The study is also significant for Indian Sign Language research, where publicly documented, end-to-end continuous recognition implementations remain comparatively limited. A reproducible framework with explicit design rationale can support follow-up research, comparative studies, and integration into assistive applications.

## 1.6 THESIS ORGANIZATION

The remainder of this thesis is organized as follows. Chapter 2 reviews related work, compares methodological trends, and highlights research gaps that motivate the proposed approach. Chapter 3 presents the system design, including data flow, multimodal representation strategy, and training methodology. Chapter 4 discusses implementation details, experimental setup, quantitative results, and qualitative error interpretation. Chapter 5 concludes the thesis and outlines future directions for scalability, robustness, and deployment.

Overall, this chapter establishes the motivation, defines the problem, and introduces the objectives and contributions that guide the rest of the document.

To support readability and reproducibility, each chapter is written to align design choices with measurable outcomes. Conceptual decisions are accompanied by implementation-level interpretation so that the connection between method and result remains explicit.

The organization also enables incremental extension. A reader may independently focus on system design, experiments, or deployment implications while still tracing how each stage contributes to the full CSLR workflow.

This chapter-level structure also supports verification of claims. Design assumptions introduced early in the thesis are revisited in the experimental chapter so that performance conclusions remain grounded in measurable outcomes rather than isolated observations.

### 1.6.1 Expected Outcomes of the Study

From a technical perspective, the expected outcomes include stable continuous recognition performance, clearer error behavior under realistic variation, and evidence that multimodal cues improve temporal interpretation. From an engineering perspective, the expected outcomes include modular scripts and a consistent experiment structure.

These outcomes define the success criteria used in later chapters and guide the final evaluation of the proposed system.

In summary, Chapter 1 establishes why continuous recognition in Indian Sign Language remains an important and open challenge, what this thesis aims to solve, and how the remaining chapters collectively validate the proposed approach.

# CHAPTER 2

# LITERATURE REVIEW

## 2.1 OVERVIEW OF EXISTING WORK

Research in sign language recognition has evolved from hand-crafted features to deep neural architectures that learn temporal and spatial representations directly from data. Early systems often relied on segmented gestures, static backgrounds, and carefully constrained recording environments. While these systems demonstrated feasibility, they were difficult to generalize to continuous signing scenarios.

As the field matured, sequence-aware architectures became central to CSLR. The transition from isolated sign classification to continuous sentence-level recognition introduced new challenges such as temporal alignment, transitional motion modeling, and uncertainty handling across adjacent signs.

Another key shift in the literature is the movement from controlled laboratory assumptions toward deployment-aware design. Earlier studies commonly relied on fixed camera setups and uniform lighting, whereas more recent work attempts to tolerate realistic variation in signer distance, background motion, and frame quality. This transition is important because continuous recognition quality depends on how well the model handles non-ideal visual conditions.

## 2.2 METHODOLOGICAL FOUNDATIONS

Methodological discipline from prior evaluation studies remains relevant to CSLR [1]. Fair comparison needs consistent preprocessing, data splits, and metric reporting. Small choices like sampling rate or keypoint filtering can shift results, so experiments must be transparent and reproducible.

## 2.3 ISL CSLR PROGRESS

### 2.3.1 Multimodal Gains

Recent work has shown that multimodal cues can improve recognition quality for continuous Indian Sign Language. In particular, combining RGB appearance with pose information helps models capture both contextual visual details and fine-grained motion trajectories [2]. This trend is important because CSLR performance depends heavily on temporal consistency and gesture transition understanding.

### 2.3.2 Deployment Constraints

The same body of work also highlights practical concerns such as latency, robustness to signer variation, and input quality sensitivity. These aspects are critical when systems are expected to move from laboratory demonstrations to real-world use.

### 2.3.3 Sequence Complexity

An additional insight from recent studies is that performance improvements are often uneven across sequence complexity levels. Models may perform strongly on short or visually distinct sequences but degrade when signs exhibit

rapid transitions or overlapping motion trajectories. This behavior reinforces the need for detailed error analysis rather than reliance on a single aggregate score.

### 2.3.4 RGB Methods

RGB-only models exploit texture, hand shape, and contextual cues from full video frames. Their strength is rich visual information, especially when hand regions are clearly visible. However, such methods may be sensitive to illumination changes, background clutter, and camera viewpoint shifts.

Despite these limitations, RGB-based pipelines remain important because they encode semantic context beyond skeletal motion, including object interactions and scene-level cues that can disambiguate similar gestures. In practice, many high-performing systems retain a strong RGB branch even when additional modalities are introduced.

### 2.3.5 Pose Methods

Pose-guided methods focus on structured keypoint trajectories, which can improve robustness under background noise. They are often lighter in representation and can emphasize motion geometry, but pose extraction errors may propagate to downstream recognition. Hybrid pipelines attempt to balance these trade-offs by fusing RGB and pose streams.

Pose-informed approaches are particularly useful when hand and arm dynamics dominate gloss discrimination. However, their effectiveness depends on keypoint stability under fast motion and occlusion. Literature comparisons suggest that the best results are often obtained when pose streams are treated as complementary rather than standalone predictors.

## 2.4 EVOLUTION OF CSLR ARCHITECTURES

The architectural trajectory of CSLR can be interpreted in three broad phases: handcrafted or shallow temporal descriptors, recurrent sequence models with learned visual features, and recent transformer or hybrid attention-based frameworks. Each phase improved temporal modeling capacity, but also introduced new trade-offs in data demand and computational cost.

### 2.4.1 CNN-RNN-CTC Pipelines

A widely adopted baseline family combines convolutional feature extraction with recurrent temporal modeling and CTC-style decoding. This design supports variable-length alignment between input frames and output gloss sequences without requiring frame-level annotations. It established a practical foundation for continuous recognition and remains a reliable reference architecture.

However, recurrent decoders may struggle with long dependencies when sequence length grows and visual transitions become subtle. Consequently, later work focused on mechanisms that can capture wider temporal context with improved training stability.

### 2.4.2 Temporal Convolution and Transformer-Based Models

Temporal convolutional and attention-based models attempt to model long-range dependencies more directly. Convolutional temporal stacks can provide efficient local-to-global context aggregation, while transformer variants offer flexible context interaction across distant frames. These models have shown strong potential in sequence tasks but often require careful regularization and sufficiently diverse training data.

For CSLR specifically, architecture choice is constrained by both recognition quality and practical inference budget. Literature therefore increasingly reports not only accuracy-oriented metrics but also speed and memory considerations for deployment scenarios.

## 2.5 DATA AND ANNOTATION CONSIDERATIONS

Data design remains one of the strongest determinants of CSLR progress. Continuous sign datasets must capture signer diversity, realistic recording conditions, and representative sentence-level variability. When dataset coverage is narrow, models can overfit signer-specific motion habits and fail to generalize.

Annotation granularity also influences achievable performance. Gloss-level sequence labels support end-to-end training, but inconsistent annotation policies can introduce alignment noise that sequence models struggle to resolve. Several studies therefore emphasize clear annotation guidelines, quality checks, and split strategies that prevent signer leakage.

Preprocessing choices, such as frame normalization, clipping policy, and keypoint smoothing, further affect downstream learning behavior. The literature indicates that robust preprocessing pipelines often reduce variance across runs and improve fairness in model comparison.

## 2.6 FUSION STRATEGIES IN MULTIMODAL CSLR

Multimodal CSLR aims to combine complementary cues so that weaknesses in one stream are compensated by strengths in another. Common strategies include early fusion at feature level, late fusion at score level, and intermediate fusion using attention or gating modules. Each strategy imposes different assumptions about modality reliability and temporal synchronization.

Early fusion can promote joint representation learning but may be sensitive to noisy modalities. Late fusion is easier to implement and tune, yet may miss deeper cross-modal interactions. Intermediate fusion methods provide a compromise by allowing selective cross-modal conditioning across temporal states.

The reviewed literature suggests that no single fusion strategy dominates universally; effectiveness depends on dataset quality, modality noise profile, and training stability. This observation motivates adaptable pipeline design rather than rigid modality coupling.

## 2.7 EVALUATION PRACTICES AND LIMITATIONS

Evaluation quality in CSLR depends on transparent metric selection and reporting granularity. Aggregate sequence accuracy alone can hide important behaviors such as boundary confusion, substitution concentration, or failure on longer sequences. More informative evaluation includes sequence-level correctness, token-level error patterns, and qualitative inspection of difficult examples.

Another recurring limitation in prior work is inconsistent reporting of train, validation, and test protocols. Even minor differences in split construction or signer overlap can significantly affect outcomes. Strong comparative analysis therefore requires clearly documented data partitions, preprocessing rules, and decoding settings.

Practical deployment claims should also be supported by runtime-oriented observations, including latency trends and resource usage under expected operating conditions. Without these details, it is difficult to assess whether reported models are suitable beyond offline experimentation.

## 2.8 RESEARCH GAPS IDENTIFIED

From the reviewed studies, several gaps remain open for practical CSLR deployment.

- Limited diversity in datasets can reduce model generalization across signers and recording conditions.
- Evaluation pipelines are not always standardized, making direct model comparison difficult.
- Some methods prioritize accuracy without sufficient attention to inference efficiency.
- Error analysis is often brief, providing limited insight into transition failures.
- Fusion strategies are sometimes proposed without detailed ablation on modality reliability.
- Reproducibility artifacts are occasionally incomplete, limiting faithful reimplementation.

These observations motivate the need for a modular, reproducible, and deployment-aware CSLR framework that balances recognition quality with computational practicality.

## 2.9 IMPLICATIONS FOR THE PROPOSED METHODOLOGY

The review indicates that a strong CSLR system should not depend on a single visual cue. Instead, it should integrate complementary information streams and preserve temporal continuity across sign boundaries. This motivates the use of a methodology that explicitly combines appearance and motion representations while maintaining sequence-level context.

The review also suggests that evaluation must go beyond aggregate accuracy. Practical reporting should include behavior under varied sequence complexity, sensitivity to noisy inputs, and qualitative interpretation of failure regions. These expectations directly influence the experimental design in later chapters.

Finally, implementation structure matters. A method that cannot be reproduced or adapted has limited long-term value, even if short-term benchmark results are strong. Therefore, the proposed framework is intentionally modular and configuration-driven.

Taken together, these implications justify a methodology that is multimodal, sequence-aware, and engineering-conscious. The proposed design in the next chapter adopts this perspective by treating model architecture, preprocessing policy, and evaluation protocol as tightly coupled components of one system.

## 2.10 CHAPTER SUMMARY

This chapter reviewed the progression of CSLR methods, discussed key advances relevant to Indian Sign Language, and identified practical research gaps. The review indicates that multimodal temporal modeling and reproducible evaluation are essential for reliable progress. Based on these insights, the next chapter presents the proposed system design and methodological choices.

By structuring the review around architectural evolution, data and annotation quality, fusion design, and evaluation rigor, this chapter provides the analytical foundation for the proposed framework. The subsequent chapter translates these literature-driven insights into concrete system components and implementation decisions.

# CHAPTER 3

# PROPOSED METHODOLOGY / SYSTEM DESIGN

## 3.1 SECTION 1

This is section 1. Figure 3.1 is a figure.

**Figure 3.1: System Architecture adafsfaaaa avaaaaaaaa aaaaaaaaaaas ssssss sssssssssssssssss**

## 3.2 SECTION 2

This is section 2.

# CHAPTER 4

# IMPLEMENTATION AND RESULTS

This is the 1st work.

## 4.1 PERFORMANCE METRICS

System performance was evaluated using widely accepted classification and explainability metrics suitable for healthcare-oriented artificial intelligence systems. These metrics collectively assess predictive accuracy, robustness of visual preprocessing, and transparency of decision-making. The system performance was evaluated using standard classification and explainability metrics commonly adopted in healthcare-oriented AI systems. Table 4.1 summarises the evaluation criteria applied in this study.

| **Metric** | **Description** |
|---|---|
| F1-Score (Macro) | Measures classification balance across all ASD behavioural classes |
| ROC-AUC | Evaluates the discriminative capability of the classifier |
| SSIM | Measures structural quality of preprocessed visual frames |
| Explainability Index (EI) | Quantifies clarity and usefulness of generated explanations |
| Faithfulness Score | Measures alignment between explanations and model decision process |

**Table 4.1: Performance Metrics Used for Evaluation**

## 4.2 TEST CASES

System performance was evaluated using widely accepted classification and explainability metrics suitable for healthcare-oriented artificial intelligence systems. These metrics collectively assess predictive accuracy, robustness of visual preprocessing, and transparency of decision-making. The system performance was evaluated using standard classification and explainability metrics commonly adopted in healthcare-oriented AI systems.summarises the evaluation criteria applied in this study.

# CHAPTER 5

# CONCLUSION AND FUTURE WORK

Here ends the thesis.

# APPENDIX 1

## TOPIC 1

### 1.1 SECTION 1

### 1.2 SECTION 2

# APPENDIX 2

# TOPIC2

# APPENDIX 3

# TOPIC3

# REFERENCES


[1] 1. Agarwal, A, Hennessy, J & Horowitz, M 1988, 'Cache performance of operating system and multiprogramming workloads', ACM Transactions on Computer Systems (TOCS), vol. 6, no. 4, pp. 393–431.

[2] 2. Geetha, M, Aloysius, N, Somasundaran, D. A, Raghunath, A & Nedungadi, P 2025, 'Toward real-time recognition of continuous indian sign language: A multi-modal approach using rgb and pose', IEEE Access, vol. 13. doi:10.1109/ACCESS.2025.3554618.