**COLLEGE OF ENGINEERING, GUINDY**
**ANNA UNIVERSITY, CHENNAI – 25**

# Railway Digital Twin with Wildlife Safety

An Educational Simulation Integrating Godot 4, MQTT,
a Trusted Node.js Control Plane and ESP32 Edge Sensing

**Submitted in partial fulfillment of the course**
**"Embedded Systems and Internet of Things"**

**Submitted By**

**Team: 14**

| Register Number | Name |
|---|---|
| 2023103546 | Kathir Kalidass B |
| 2023103597 | Malini R |
| 2023103600 | Parthasarathi S |
| 2023103714 | Paril T |

October 2026

# Abstract

Train–animal collisions remain a persistent operational risk on forested and rural railway corridors while conventional level-crossing protection offers the same single mechanism for every kind of intruder. This project develops an educational *Railway Digital Twin with Wildlife Safety*: a complete, runnable miniature of a modern wildlife-protected railway line in which the same event can be observed simultaneously from four cooperating surfaces — a three-dimensional twin simulation, a web operations dashboard, a trusted backend control plane, and an ESP32 edge controller, each communicating over an authenticated IoT message bus.

The system is built as a staged software stack. **Godot 4.7** renders a two-track "stadium" railway world (UP and DOWN loops of 1253.98 m and 1228.85 m around a 250 m straight-sided footprint) with an island station, interlocked crossovers, a wildlife level crossing with boom barriers, carved river with road and railway bridges, catenary, dynamic signal masts and Libre-TrainSim-derived Blender train, station, deer and elephant assets. **Node.js 22+** with Express and SQLite is the trusted control plane: the sole publisher of railway commands, state snapshots and alerts, enforcing bcrypt/JWT authentication, role-based access control (viewer/operator/admin), command-envelope validation, anti-replay protection through a persistent SQLite registry, and a full audit trail. **Eclipse Mosquitto 2** brokers the machine traffic on MQTT TCP 1883/WebSocket 9001 with per-client credentials and least-privilege topic ACLs. A **React 18/Vite** dashboard presents live state, per-block signal aspects, per-train speed control, meet scheduling, wrong-line routing and hazard evidence badges. An **ESP32 (Arduino/PlatformIO)** node carries fail-safe field inputs — wildlife and sensor-fault pulls, protective outputs, debounce, SNTP-gated clock truth and non-blocking telemetry. A **FastAPI ML microservice** using torchvision's SSDLite MobileNetV3 detector confirms animal sightings from twin-camera frames behind a two-frame evidence policy.

The wildlife protection chain implements a staged escalation NONE → SUSPECTED (30 km/h limit) → CONFIRMED (0 km/h, STOP/RED) driven by trackside sensor huts, onboard simulated cameras and ESP32 edge reports, with backend-authoritative hazard fusion, recovery-latched resets and restrictive fail-safe behaviour on any loss of

communication. Every subsystem is verified by an automated gate — 42/42 Godot suites, 141/141 backend tests, 8/8 ML tests, 16/16 ESP32 native tests and a clean web build — plus live end-to-end scenarios including a chance-based meet scheduling, an interlocked wrong-line run and the two-frame camera confirmation chain end-to-end on the live stack. The system is emphatically a classroom simulation and not certified railway signalling equipment.

**Keywords:** Digital Twin, Railway Safety, Wildlife, MQTT, IoT, ESP32, Godot Engine, Node.js, React, Machine Learning

# Contents

**Abstract** **ii**

**1 Introduction** **1**

1.1 Background . . . . . 1

1.2 Objectives . . . . . 2

1.3 Scope and safety boundary . . . . . 2

1.4 Phased implementation outline . . . . . 3

1.5 Organisation of the report . . . . . 4

**2 System Requirements and Phases** **5**

2.1 Functional requirements . . . . . 5

2.2 Non-functional requirements . . . . . 7

2.3 Hardware requirements . . . . . 8

2.4 Software requirements . . . . . 9

2.5 Phase-to-gate mapping . . . . . 10

**3 System Architecture and Workflow** **11**

3.1 Architecture overview . . . . . 11

3.2 Data flow and message contract . . . . . 12

3.3 Backend internal architecture . . . . . 13

3.4 Failure handling and fail-safety . . . . . 14

3.5 Topic contract summary . . . . . 14

**4 Tools and Technology** **16**

4.1 Technology stack at a glance . . . 16
4.2 Backend stack . . . 17
4.3 Broker and communication . . . 18
4.4 Dashboard stack . . . 18
4.5 Twin engine and asset pipeline . . . 18
4.6 Firmware and edge simulation . . . 19
4.7 ML microservice . . . 19
4.8 DevOps and verification tooling . . . 20

**5 Hardware, Peripherals and Simulation Stack 21**
5.1 Hardware overview . . . 21
5.2 ESP32 edge node and peripherals . . . 21
5.3 Firmware software architecture . . . 22
5.4 Wokwi cloud simulation and the Pinggy tunnel . . . 23
5.5 Clock truth via SNTP . . . 24
5.6 Build results and Stage-D checklist status . . . 24

**6 The Digital Twin World 26**
6.1 World composition . . . 26
6.2 Island station and interlocked crossovers . . . 28
6.3 Wrong-line run across the station . . . 29
6.4 Chance-based meets . . . 32
6.5 The LTS asset fleet . . . 33
6.6 Operator and observer surfaces of the twin . . . 34
6.7 Twin subsystem modules . . . 35

**7 Dashboards 36**
7.1 The web operations dashboard . . . 36
7.1.1 Login and role awareness . . . 36
7.1.2 Panels and data flow . . . 36
7.1.3 Evidence badges on the block diagram . . . 38

7.2 The twin-side HUD . . . . . 38
7.3 Diagnostics surfaces . . . . . 39
7.4 Two dashboards, one truth . . . . . 40

**8 Features and Functions Implemented 41**
8.1 Backend: authority, safety and security . . . . . 41
8.2 Wildlife protection chain . . . . . 43
8.2.1 Onboard simulated vision . . . . . 43
8.3 Twin features . . . . . 44
8.4 ESP32 and edge features . . . . . 44
8.5 ML service features . . . . . 44
8.6 Dashboard features . . . . . 45
8.7 Safety behaviour and edge cases (cross-cutting) . . . . . 45
8.8 End-to-end scenarios (live, recorded) . . . . . 46

# List of Figures

3.1 System block diagram: one trusted control plane, many clients. . . . . 11

3.2 End-to-end workflow: control (steps 1–4) and wildlife observation (steps 5–9) as one closed loop. . . . . 13

6.1 Top-down overview of the shared stadium footprint: UP and DOWN tracks, the island station platform, carved river with a road and a railway bridge, tree line, and the two-train fleet (HUD shows the active zone, signal aspect, CAM state, sensor health, speed and camera mode). Captured from `capture_double_track.gd` under headless software rendering; the HUD `MQTT offline` flag is expected in capture mode where the broker is intentionally not connected. . . . . 27

6.2 Island station from above: mainly-top view showing platform modules, canopy/station building, both platforms and the two tracks. Captured from `capture_station.gd`. . . . . 28

6.3 Island station at an oblique angle: platform modules and canopy silhouette against the parallel tracks and stadium corridor in the background. Captured from `capture_station.gd`. . . . . 29

6.4 Wrong-line run at UP phase APPROACH: T3 still on DOWN, T1 approaching crossover A before any visible motion; note HUD hold progress. Captured from `capture_crossover.gd`. . . . . 30

6.5 Wrong-line run at phase CROSS_ENTRY/WRONG_LINE: T1 blended onto DOWN at A – visible train between the switch points with switch blades in motion. Captured from `capture_crossover.gd`. . . . . 31

6.6 Wrong-line run completion (phase CROSS_EXIT/CLEARANCE): T1 back on UP past B, T3 released from hold and both trains back under normal authority. Captured from `capture_crossover.gd`. . . . . 32

6.7 Live meet execution with seed 4242: both trains near the island platform, one held, with the meet HUD showing phase, holder, chosen route and countdown. Captured from `capture_meet.gd`. . . . . 33

6.8 Wokwi-style animal-assets sanity render: deer and elephant GLBs with articulated limbs posed near the track, plus the sensor hut and barrier kit. Captured from `capture_animals.gd`. . . . . 34

7.1 Twin HUD during a confirmed wildlife stop: top bar reads `WILDLIFE | WILDLIFE STOP 0.95 | camera: CONFIRMED elephant 0.92` — target speed 0, limit 54, camera tracking from behind the red LTS train. The elephant detection ahead is the simulated render that produced the confirmed evidence. Captured from `capture_camera_confirm.gd`. . . . . 39

# List of Tables


2.1 Functional requirements and delivery phase . . . . . 5

2.2 Non-functional requirements . . . . . 7

2.3 Hardware requirements . . . . . 8

2.4 Software requirements . . . . . 9

2.5 Delivery phases vs verification evidence . . . . . 10

4.1 Complete technology stack . . . . . 16

5.1 Peripheral bill of materials (Wokwi `diagram.json`) . . . . . 22

5.2 Stage-D ESP32 verification record (dates 2026-10-21, per acceptance.md) 24

6.1 Key `godot/src` modules . . . . . 35

7.1 Dashboard panels . . . . . 37

8.1 Backend features . . . . . 41

# Chapter 1

# Introduction

## 1.1 Background

Indian Railways reserves operate through large tracts of forest and open grassland in which scheduled and unscheduled train paths intersect with animal movement corridors. Elephants, deer and other wildlife cross railway formation at grade, and collisions remain a persistent operational and ecological risk. Conventional protection — signage, whistle zones and manual watchmen — is sparse by design, and a single fixed level-crossing alarm cannot adapt on its own to *which* animal is ahead, *where* it is relative to a moving train, or *how much* braking distance the train still has.

Modern practice addresses this with two converging ideas:

- **Digital twins:** a live virtual replica of a physical asset (here, a forest railway line with its trains, signals and crossing) that stays synchronised with trusted state and lets operators observe, rehearse and reason about operations.
- **Embedded IoT sensing:** low-cost edge devices (here, an ESP32 with sensors, protective outputs and a fail-safe state machine) at the trackside, publishing machine observations over an authenticated message bus rather than treated independently.

This project, developed as an educational simulation by Team 14 for the course *Embedded Systems and Internet of Things*, brings both ideas together in a system small enough to run on one laptop: a three-dimensional digital twin of a forest railway loop, a trusted backend control plane, a role-aware web dashboard, an authenticated MQTT broker, and an ESP32 edge controller — all exchanging sensor observations, authority commands, state snapshots and alerts over well-defined topics.

## 1.2 Objectives

The objectives of the project are:

1. Build a runnable **3D digital twin** of a double-track forest railway — UP and DOWN loops, an island station with interlocking crossovers, a wildlife level crossing with boom barriers, a carved river with road and railway bridges, catenary, dynamic signals and an LTS-derived Blender asset fleet — in Godot 4.

2. Construct a **trusted control plane** that owns all railway authority: a two-train double-track fleet model, per-block signal aspects, a fixed-timestep simulation loop, a station-crossover interlocking, chance-based meet scheduling, an operator-requestable interlocked wrong-line run, and a wildlife-hazard state machine — served over authenticated REST and MQTT.

3. Enforce **security end to end**: authenticated users with role-based access control, an authenticated MQTT broker with per-client topic ACLs, command-envelope validation with timestamp freshness and anti-replay protection, and a complete audit trail.

4. Implement **wildlife sensing and staged protection**: a NONE → SUSPECTED → CONFIRMED escalation driven by trackside sensor huts, an onboard simulated camera detector with analytic occlusion and a quadratic stopping-distance model, a back-end camera ingest pipeline with two-frame evidence confirmation, and ML-assisted animal detection through a FastAPI microservice.

5. Implement an **ESP32 edge node** with restrictive fail-safe outputs, debounced local inputs, SNTP-gated clock truth, non-blocking telemetry and edge-triggered wildlife alerts — validated natively and in the Wokwi cloud simulator.

6. Provide a **role-aware dashboard** for viewer, operator and admin users with live state, per-block aspects, per-train speed control, route/meet/wrong-line panels and hazard evidence badges.

7. Verify the whole stack continuously with an automated multi-surface test gate and documented live end-to-end scenarios.

## 1.3 Scope and safety boundary

Two scope statements are as important as the features themselves:

- **Educational simulation only.** The system is a classroom digital-twin simulation, *not* railway safety equipment. It must never be connected to real signalling, trains or operational infrastructure. Simulated "stopping distance" is a visualization estimate only and does not model certified train dynamics, gradients, adhesion or real braking curves.
- **Physical hardware status.** The ESP32 path was verified through the Wokwi cloud simulator (via a Pinggy tunnel to the local authenticated broker). The physical-hardware checklist items in the Stage D plan remain *not run*: real instruments were not connected. The report is explicit wherever this applies.

Within those boundaries, every subsystem — backend, twin, dashboard, firmware and ML service — is fully implemented and gated by automated tests (Chapter 8, Appendix **??**).

## 1.4 Phased implementation outline

The system was built in recorded, gated stages (dates from `docs/porting/acceptance.md`):

- **Stage A (backend foundation)** — Express + JWT/RBAC, SQLite audit and anti-replay registry, two-zone state machine, backend-authoritative MQTT, broker auth and ACLs (2026-10-18/19).
- **Stage A2 (block signalling)** — per-block aspects and retained signals (2026-10-19).
- **Stage B (dashboard)** — login, role-aware REST controls, WebSocket live updates, audit feed (2026-10-19).
- **Stage C (Godot twin)** — vendored MQTT bridge, procedural world, train/wildlife animation, brakes, signals, cameras; porting Libre-TrainSim (LTS) Blender assets (2026-10-19/20).
- **Stage D (ESP32 / Wokwi)** — per-client credentials, device-scoped topics, fail-safe outputs, cloud simulation through a tunnel (2026-10-19/20).
- **Stage E (integrated delivery)** — Docker/environment setup, scenario scripts and the formal acceptance record (2026-10-22).
- **Stage 2A–2G (double-track phase)** — a two-train UP/DOWN fleet, ten blocks with aspects, station island and crossovers (2A), the double-track world (2B–2C),

backend lives and camera fleet (2A–2D), meet/pass scenarios (2E, 2G), and distributed wildlife sensing with an onboard detector (2F) (2026-10-21/22).

- **Stadium evolution — Phases 1–3** — both loops reshaped as one 250 m straight-sided shared stadium footprint with opposite operational chainage (2026-10-22), an interlocked operator wrong-line run with an opposing-train hold (2026-10-23), and the staged camera/ML/near-animal confirmation chain with two-frame evidence (2026-10-23).

## 1.5 Organisation of the report

Chapter 2 states requirements. Chapter 3 describes the system architecture and end-to-end workflow. Chapter 4 documents tools and technology. Chapter 5 covers hardware, peripherals and the simulation stack. Chapter 6 details the digital twin world. Chapter 7 documents the dashboards. Chapter 8 lists every implemented feature and function with its verification evidence. Chapter 9 presents results, limitation and conclusion. Appendices collect the access-control matrix, the complete test-gate record and run instructions. Reproduced simulation screenshots appear in Figures 6.1–7.1 and the figures referenced from Chapters 5–8.

# Chapter 2

# System Requirements and Phases

## 2.1 Functional requirements

**Table 2.1:** Functional requirements and delivery phase

| S.No | Requirement | Phase |
|---|---|---|
| FR-1 | Authenticate users (bcrypt passwords, JWT sessions) with three roles: viewer (monitor), operator (control), admin (audit inspection). | A |
| FR-2 | Validate every command envelope against schema with ±5 min timestamp freshness and reject replays through a persistent SQLite `processed_requests` registry. | A |
| FR-3 | Record an audit row (actor, role, zone, action, result, timestamp) for every control attempt — accepted, rejected or forbidden. | A |
| FR-4 | On MQTT disconnect apply the restrictive `COMM_LOST` fail-safe; on reconnect publish the retained state snapshot to reconcile clients. | A |
| FR-5 | Be the sole publisher of commands, state snapshots, alerts and signals on MQTT with per-client topic ACLs. | A |
| FR-6 | Reject a reset while a wildlife hazard or sensor fault is active (operator must clear and then explicitly reset). | A |
| FR-7 | Model a two-train (T1 UP, T3 DOWN) double-track fleet with ten blocks, per-block signal aspects, occupancy safety and a fixed-timestep simulation loop. | 2A |

**Table 2.1:** (continued)

| S.No | Requirement | Phase |
|---|---|---|
| FR-8 | Provide a station-crossover interlock: one route at a time, hazard/occupancy checks, 409 on conflicts, automatic release. | 2A, 2G |
| FR-9 | Run chance-based meet scheduling from a seeded PRNG: hold the slower train at the station, execute the crossover as a proper route, reproduce history for identical seeds. | 2G |
| FR-10 | Let an operator request an interlocked wrong-line run (UP→DOWN at crossover A, return at B) while the opposing train is held automatically inside braking distance; phases APPROACH → CROSS_ENTRY → WRONG_LINE → CROSS_EXIT → CLEARANCE → DONE. | Stadium P2 |
| FR-11 | Operate distributed trackside wildlife huts — UP-S0..UP-S4 and DOWN-S0..DOWN-S4, i.e. ten huts with 75 m overlapping radius — publishing observations used as *trackside* evidence. | 2F |
| FR-12 | Provide onboard simulated-ML camera detection (forward cone vision, ±25°/10°, 200 m range, analytic occlusion against terrain, trunks and bridge decks) as *onboard* evidence with zero-latency local braking. | 2F |
| FR-13 | Accept camera frames over authenticated HTTP (bearer token, `X-Captured-At` freshness, duplicate-id suppression), validate blocks and line, run the ML detector, and confirm a hazard only on *two* frames. | Stadium P3 |
| FR-14 | Implement staged hazard escalation: trackside-only suspicion caps the approaching train at 30 km/h and shows YELLOW; camera confirmation stops the train (0 km/h) and shows RED; clearing never downgrades a confirmed block; reset is required after hazard clear. | Stadium P3 |
| FR-15 | Deliver ESP32 edge alerts (`WILDLIFE_NEAR`, `WILDLIFE_DETECTED`, `WILDLIFE_CLEARED`) to the edge node and require operator re-arm (RESET) through the dashboard. | Stadium P3 |

**Table 2.1:** (continued)

| S.No | Requirement | Phase |
|---|---|---|
| FR-16 | Render the twin: stadium double-track world, island station, interlocked crossovers, two-track level crossing, river with bridges, catenary, dynamic signals, barriers, cameras and HUD. | C, 2B–2E, Stadium P1 |
| FR-17 | Provide the dashboard: login, live state via WebSocket, train cards with speed control, block-aspect diagram, evidence badges, meet card, wrong-line panel, camera health. | B, 2E–2G, P3 |
| FR-18 | Publish ESP32 telemetry with SNTP-validated UTC time; reject stale, malformed, duplicate or wrong-zone telemetry at the backend and mark clock-invalid telemetry before it is sent. | D |

## 2.2 Non-functional requirements

**Table 2.2:** Non-functional requirements

| S.No | Requirement | Where enforced |
|---|---|---|
| NFR-1 | **Security — least privilege:** every MQTT client authenticates; per-client ACLs allow the dashboard read-only access, Godot telemetry-publish-only on its zones, and the backend full control topics. | `mosquitto/acl_file`, broker AC |
| NFR-2 | **Fail-safety:** every output is restrictive at startup, on communication loss, on fresh-context loss, and for active local hazard/fault inputs; local inputs cannot be cleared remotely. | backend state machine, ESP32 c |
| NFR-3 | **Anti-replay:** accepted REST control IDs/timestamps persists in SQLite; stale, duplicated or schema-invalid envelopes are rejected. | `command_tracker.js`/SQLite |
| NFR-4 | **Auditability:** every control or route attempt recorded in SQLite regardless of outcome; admin-only inspection. | `audit.js` |

**Table 2.2:** (continued)

| S.No | Requirement | Where enforced |
|---|---|---|
| NFR-5 | **Reproducibility:** seeded PRNG (meet scheduler and wildlife director) gives identical histories for identical seeds; same command must produce the same state. | `rng.js`, `meets.js` |
| NFR-6 | **Performance:** backend snapshot publish loop of 2 Hz; train-speed updates smooth at the twin; live state and camera ingest stay within documented limits (camera ingest >5 fps rate-limited, 413 on oversize). | `loop.js`, camera ingest |
| NFR-7 | **Testability:** every surface gated by automated tests; the gate must exit non-zero on any failure and be re-runnable headless. | `verify-all.sh`, test suites |
| NFR-8 | **Educational honesty:** stopping distance is a visualization estimate; not certified signalling; the system never touches real railway infrastructure. | README, presentation |
| NFR-9 | **Compose-neutral developer path:** one script `dev-up.sh` to stand up the stack, reset the demo, generate broker credentials. | scripts/ |

## 2.3 Hardware requirements

**Table 2.3:** Hardware requirements

| Item | Specification |
|---|---|
| Development host | x86-64 PC with Linux or WSL2; mouse/keyboard for the twin. GPU useful but not required (Mesa llvmpipe software rendering is supported for headless verification) |
| Docker engine | Docker Engine with Compose v2; no "docker desktop" required |
| ESP32 devkit v1 | Optional for the edge-node path (equivalently simulated on Wokwi); Wi-Fi capable, MCP UART 115 200 |

| | |
|---|---|
| Sensors/indicators | Green/red LEDs, buzzer, pushbuttons (wildlife, fault), SSD1306 OLED, servo (all simulated in Wokwi); telemetry needs network reachability to the broker |
| Cameras | None physical; twin camera feeds are simulated render outputs consumed by the ML microservice |

## 2.4 Software requirements

**Table 2.4:** Software requirements

| **Layer** | **Tool / version** |
|---|---|
| OS | Ubuntu 24.04 LTS (WSL2 permissible) |
| Container runtime | Docker Engine + Compose; images `eclipse-mosquitto:2`, Node base image |
| Control plane | Node.js 22+ (runtime 24 of the verification host), Express 4.21, better-sqlite3 13, bcryptjs 3, jsonwebtoken 9, mqtt.js 5.16 |
| Broker | Eclipse Mosquitto 2 — TCP 1883, WebSocket 9001, `allow_anonymous false` |
| Dashboard | React 18.3.1, Vite 6, TypeScript 5.7, `lucide-react` |
| Twin engine | Godot 4.7.2 (GL compatibility for headless render) |
| Firmware | PlatformIO (`espressif32`, `arduinoframework`), PubSubClient 2.8, ArduinoJson 7, ESP32Servo, Adafruit SSD1306/GFX |
| Edge simulation | Wokwi CLI v0.29.0; tunnel via Pinggy raw TCP |
| ML microservice | Python, FastAPI 0.135.1, uvicorn, torch 2.10.0, torchvision 0.25.0 (SSDLite320 MobileNetV3, COCO animal classes), Pillow, NumPy |
| Quality | Node built-in test runner (backend), Godot test harness (42 suites), Pytest (ML), PlatformIO Unity (ESP32 native), Vite/TypeScript build check |

## 2.5 Phase-to-gate mapping

**Table 2.5:** Delivery phases vs verification evidence

| Phase | Deliverable | Evidence |
|---|---|---|
| A / A2 | Trusted backend, two-zone and later block signalling | `state.test.js`, `signalling.test.js`, `broker_acl.test.js` |
| B | Authenticated role-aware dashboard | Rest API tests, web build |
| C | Godot twin with LTS-derived assets | 42 Godot suites incl. `test_real_assets` |
| D | ESP32 fail-safe edge node | 16 native Unity cases + Wokwi scenario |
| E | Integrated stack + formal acceptance record | `docs/porting/acceptance.md` |
| 2A–2C | Double-track fleet, world, crossovers | `signalling/routes/meets` suites, Godot track registry suites |
| 2E–2G | Meet/pass and chance-based meets with interlocking | `test_meet_scenario`, `meets.test.js`, `rng.test.js` |
| 2F | Distributed wildlife sensing + onboard detector + braking model | `test_sensor_huts`, `test_onboard_detector`, `test_onboard_braking` |
| Stadium P1–P3 | Shared stadium geometry, wrong-line run, camera/ML/near-animal chain | `test_stadium_track`, `wrong_line*.test.js`, `near_animal.test.js`, `camera.test.js` |

# Chapter 3

# System Architecture and Workflow

## 3.1 Architecture overview

The system is organised around one principle: **one trusted control plane, many observing/edge clients**. The Node.js backend is the single authority for train commands, block aspects, routes, meets, hazards and alerts; every other component either publishes observations (Godot twin, ESP32) or consumes authoritative state (dashboard, twin, ESP32). Figure 3.1 shows the five subsystems and their interfaces.





**Figure 3.1:** System block diagram: one trusted control plane, many clients.

The four cooperating surfaces are:

1. **Mosquitto broker** (TCP 1883, WebSocket 9001) with `allow_anonymous false`; credentials are generated by `scripts/mosquitto_setup.sh` from local environ-

ment variables; per-client ACLs in `mosquitto/acl_file` enforce the topic contract (Appendix **??**).

2. **Node.js backend** — authenticates users with bcrypt and JWT, enforces RBAC (viewer/operator/admin), validates command envelopes, blocks replays through a persistent SQLite `processed_requests` registry, writes an audit trail for every control attempt, runs the two-train simulation loop, owns block signalling, crossover interlocking, meet scheduling, the wrong-line state machine and the wildlife-hazard fusion — and is the sole MQTT publisher of commands, state, alerts and signals.

3. **Godot 4.7 twin** — full-scale double-track world with the LTS-derived asset fleet (Chapter 6); reconciles backend state into train targets and signals, publishes track telemetry and wildlife evidence; also executes its own local fail-safe limit that can only *tighten* the backend target.

4. **React dashboard** — authenticated REST for control, MQTT-over-WebSocket for live updates; read-only on MQTT.

5. **ESP32 node** — authenticated IoT client restricted to telemetry publish + command subscribe on its own topics.

## 3.2 Data flow and message contract

Figure 3.2 traces the canonical control and observation paths. Two flows are deliberately asymmetric:

- **Control flows REST** (dashboard → backend only) so every command crosses the authenticated, audited, anti-replayed boundary once.
- **State flows MQTT** (backend → all clients, retained) so any late joiner sees the current truth without polling, and a lost client resynchronises from the retained snapshot on reconnect.





**Figure 3.2:** End-to-end workflow: control (steps 1–4) and wildlife observation (steps 5–9) as one closed loop.

## 3.3 Backend internal architecture

The backend is composed of small single-responsibility modules (`backend/src/`) composing a fixed-timestep simulation loop (`loop.js`) that ticks authoritative state and publishes snapshots at 2 Hz once the broker connection is up:

- `config.js` — fleet, blocks, lines, station, crossovers, meet parameters and wrong-line hold points (UP 1253.9822 m, DOWN 1228.8495 m lengths).
- `state.js` / `simulation.js` — authoritative trains T1 (UP, clockwise) and T3 (DOWN, anticlockwise), block occupancy, per-train speed dynamics and dwell logic.
- `signalling.js` / `routes.js` — per-block aspects, retained `railway/signal/{block}` topics, station crossover interlocking and route lifecycle.
- `meets.js` / `rng.js` — seeded chance-based meet scheduler and its deterministic PRNG.
- `wrong_line.js` — the operator-requested wrong-line run: APPROACH → CROSS_ENTRY → WRONG_LINE → CROSS_EXIT → CLEARANCE → DONE with automated opposing-train hold inside braking distance.
- `wildlife_commands.js` / `ingest.js` / `ml.js` — trackside and onboard evidence fusion, camera ingest (bearer token, `X-Captured-At`, duplicate-id, rate and size limits) and ML service calls.

- `auth.js` / `rbac.js` / `replay.js` / `audit.js` / `db.js` — JWT authentication, role checks, replay registry and audit logging backed by SQLite.
- `bus.js` / `mqtt.js` / `events.js` — MQTT connection, retained topic publication, WebSocket-ready event stream for the dashboard.
- `geometry.js` — shared UP/DOWN operational vs physical chainage conversion used by holds, huts and cameras.

## 3.4 Failure handling and fail-safety

Three deliberate, test-verified behaviours define the safety posture (Section 8.7):

- **Restrictive fail-safe:** on MQTT loss the backend flags a restrictive state; the twin enforces a local limit; the ESP32 is restrictive at boot, during loss of fresh backend context, and for any active local hazard/fault input. Local inputs are debounced and can never be overridden remotely.
- **Recovery latch:** clearing a hazard is never enough; the backend latches `RECOVERY_REQUIRED` until an authorised operator/admin issues RESET with healthy sensors and no active hazard. RESET is further rejected while hazards or faults are active (per `IMPLEMENTATION.md`).
- **No command/telemetry replay:** envelopes carry timestamps (validated within ±5 min); IDs deduplicated in SQLite; ESP32 telemetry is non-retained, and stale, malformed, duplicate or wrong-zone telemetry is rejected. Firmware does not queue old telemetry or commands for replay after reconnect.

## 3.5 Topic contract summary

The complete per-client publish/subscribe matrix is in Appendix **??**. The contract's essence:

- backend publishes `railway/state`, `railway/events`, `railway/alerts`, `railway/zone*/signal`, `railway/commands/*`, `railway/speed/*`, `railway/security/events`, `railway/wildlife`, `railway/signal/{block}` (retained);
- godot publishes telemetry and wildlife observations for its zones; subscribes to commands, speeds, signals and state;

- dashboard subscribes to state, events and alerts — and publishes nothing;
- esp32 publishes only `railway/telemetry/esp32` (non-retained) and subscribes to `railway/commands/esp32`.

Captured figures of the twin surfaces these chapters describe are in Figures 6.1–6.6.

# Chapter 4

# Tools and Technology

## 4.1 Technology stack at a glance

**Table 4.1:** Complete technology stack

| Layer | Technology | Role in the system |
|---|---|---|
| Unity of authority | Node.js 22+ with Express 4 | Trusted control plane: auth, RBAC, simulation, interlocking, hazards, audit |
| Data store | SQLite (better-sqlite3 13) | Persistent users, audit rows, anti-replay registry; WAL-mode SQLite file inside a Docker volume |
| Live bus | Eclipse Mosquitto 2 (MQTT 3.1.1) | Authenticated pub/sub bus for all machine traffic over TCP 1883 / WS 9001 |
| Twin | Godot 4.7.2 | Full 3D digital twin scene, physics-free kinematic fleet, cameras, HUD |
| Assets | Blender exports from Libre-TrainSim (LTS) | Train consist GLBs, station modules, deer/elephant, scenery fleet |
| Dashboard | React 18.3.1 + Vite 6 + TypeScript 5.7 | Auth web console with live state and controls |
| Edge node | Arduino framework on ESP32 devkit v1 via PlatformIO | Field sensing, protective outputs, SNTP-gated telemetry |
| Edge simulation | Wokwi (diagram.json, wokwi.toml) + Wokwi CLI v0.29.0 | Cloud-compile and scenario-run without hardware |

**Table 4.1:** (continued)

| Layer | Technology | Role |
|---|---|---|
| Tunnel | Pinggy raw TCP (`scripts/wokwi-tunnel.sh`) | Exposes local authenticated broker to the cloud Wokwi session |
| ML service | Python + FastAPI 0.135.1, torch 2.10, torchvision 0.25 | Animal detection (SSDLite320 MobileNetV3, COCO animal classes) over HTTP |
| Verification | Node test runner, Godot test harness (42 suites), Pytest, PlatformIO + Unity (native) | Continuous automated gate across all four surfaces |
| DevOps | Docker Compose, bash scripts | One-command stack bring-up (`dev-up.sh`) and full gate (`verify-all.sh`) |

## 4.2 Backend stack

- **Node.js 22+** chosen for the built-in test runner, first-class `-env-file-if-exists` startup and the mature MQTT/SQL ecosystem on one trusted process.
- **Express 4.21** REST control surface: `/api/login`, `/api/control`, `/api/route`, `/api/meet`, `/api/speed`, `/api/wrong-line`, `/api/camera`, `/api/health` — each with RBAC, envelope validation and audit semantics (Chapter 8).
- **better-sqlite3 13** embedded database in WAL mode for low latency audit and replay persistence; lives in a named Docker volume so state survives restarts.
- **bcryptjs 3** password hashing for seed users; **jsonwebtoken 9** for short-lived JWT issuance.
- **mqtt.js 5.16** for both MQTT publishing (state, events, alerts, signals, commands, speed) and subscription.
- **Node built-in test runner** for the 141-test suite executed with `-test -test-force-exit`; the MQTT e2e subset runs against an isolated Mosquitto container on port 1884 when the host broker occupies 1883.

## 4.3 Broker and communication

- **MQTT** chosen as the machine bus: quality-of-service semantics (QoS 1 for commands), *retained* messages for state and signals (a late joiner instantly sees current truth), topic hierarchy as identity, and per-client ACLs as authorization.
- **Mosquitto 2** configured with `allow_anonymous false`; the password file is produced by `scripts/mosquitto_setup.sh` from `.env` variables; ACLs restrict clients to the exact topic set listed in Appendix **??**.
- **WebSocket listener 9001** serves browser clients so the dashboard never needs raw TCP.
- Version note: MQTT retained-state design intentionally avoids bespoke discovery mechanisms, simplifying the ESP32 client (`PubSubClient`) which supports MQTT 3.1.1.

## 4.4 Dashboard stack

- **React 18** single page application with lucide-react icons; builds via **Vite 6** with a TypeScript gate (`tsc -noEmit`) so type errors fail the web build.
- Login flow POSTs to `/api/login` and stores the JWT in memory; subsequent REST calls carry `Authorization`; live updates arrive over WebSocket from the backend event stream.
- Panels implemented: role-aware header, signal-aspect block diagram with CAM/HUT evidence badges, per-train speed control, station route card, meet card (seed, phase, countdown), wrong-line operator panel with eligibility and cancel, camera health/staged hazard panel, and an admin-only audit feed.

## 4.5 Twin engine and asset pipeline

- **Godot 4.7.2** with the `gl_compatibility` renderer, which keeps the twin runable both locally on GPUs and headless under `xvfb-run` with Mesa llvmpipe software rendering — the mode used for the automated captures used in this report.
- **Libre-TrainSim (LTS) asset port:** the Blender host files (`tools/export_lts_assets.py`) export the LTS train consist, station modules and scenery to GLB/JSON manifests

(`godot/assets.manifest.json`); `test_real_assets` proves the tracked GLBs actually replace the procedural fallbacks.

- **Vendored MQTT addon** (`godot/addons/godot-mqtt`) plus the LTS runtime addon bridge the twin to the broker with backoff-on-failure reconnect (`test_mqtt_bridge`).
- Procedural world construction (stadium loops, river, bridges, catenary masts, sensor huts, signal masts, crossovers, booms) is code-driven, so the world geometry is testable in 42 suites without artwork.

## 4.6 Firmware and edge simulation

- **PlatformIO** with `espressif32 Arduino framework`; declared libraries pinned to exact majors: `PubSubClient@2.8`, `ArduinoJson@7`, `ESP32Servo`, `Adafruit SSD1306`, `Adafruit GFX`.
- The firmware logic is *header-only and host-testable*: pure functions live in `sensors.h`, `actuator.h`, `output_logic.h`, `telemetry.h`, `command_logic.h`, `debounce.h`, so the whole decision core is exercised by 16 Unity cases in a native PlatformIO environment (`pio test -e native`) without any hardware.
- **Wokwi** (`esp32/diagram.json`, `wokwi.toml`) provides the cloud twin of the devkit wiring; the `scenarios/wildlife.yaml` script drives the wildlife button through the scenario runner; `wokwi-cli` v0.29.0 is the tip tool used.
- **Pinggy** raw-TCP tunnel (`scripts/wokwi-tunnel.sh -write-secrets`) forwards the local authenticated broker (port 1883) so a cloud Wokwi session can reach it without ever re-enabling anonymous access.

## 4.7 ML microservice

- **FastAPI + uvicorn** service (`ml/app.py`) accepting a single JPEG frame; `POST /detect` returns COCO animal detections with confidence and bbox; `GET /health` reports model-loaded state and stub mode.
- **torchvision** `ssdlite320_mobilenet_v3_large` as the detector; detections filtered to COCO animal classes; `ML_MIN_CONFIDENCE` (default 0.5) and `ML_DEVICE` (default cpu) are environment-tunable.

- `ML_STUB=1` returns a deterministic elephant detection (confidence 0.92) without loading torch or downloading weights — the mode used across most verification; real-weights path is implemented but lazily caches weights and was smoke-skipped for lack of cached weights (stated honestly in Chapter **??**).
- A stub returns `modelLoaded: true` with `elephant 0.92` so the backend evidence pipeline is exercised against realistic payloads.

## 4.8 DevOps and verification tooling

- `scripts/dev-up.sh` — brings up Compose, provisions the broker credentials, waits up to 60 s for a healthy `/api/health`.
- `scripts/verify-all.sh` — full gate: backend suite, web build, broker ACL checks, optional Godot and firmware compile gates.
- `scripts/demo-scenarios.sh` — scripted REST demo with payload assertions using `jq`.
- `godot/tests/run_tests.sh` — 42 headless Godot suites; `godot/tests/capture_*.gd` produce the report figures.
- `backend/test/` — 141 tests with the isolated-broker trick for ACL/e2e cases; `ml/tests/` — Pytest for detector and API edges (413 oversize, 503 crash, stub rejection).

# Chapter 5

# Hardware, Peripherals and Simulation Stack

## 5.1 Hardware overview

The project deliberately separates *hardware that exists* from *hardware that is simulated*:

- **Exists and runs:** the development host (Linux/WSL2, Docker, Godot, Node) and — optionally — one ESP32 devkit v1.
- **Simulated faithfully:** all field peripherals (LEDs, buzzer, pushbuttons, ultrasonic ranger, PIR motion sensor, vibration sensor, servo barrier, OLED) are wired in Wokwi (`esp32/diagram.json`) and driven by the same production firmware image.
- **Not run:** the physical-hardware checklist items of the Stage D plan remain *not run*; this report is explicit about that and never claims physical verification.

## 5.2 ESP32 edge node and peripherals

The ESP32 devkit v1 is the field-level IoT node. It authenticates to the broker as user `esp32`, publishes non-retained telemetry on `railway/telemetry/esp32` and consumes commands on `railway/commands/esp32`. The backend forwards an accepted REST control to the device only when the command's zone matches `ESP32_ZONE` (default `zone1`).

**Table 5.1:** Peripheral bill of materials (Wokwi `diagram.json`)

| **Peripheral** | **Part / pins** | **Function** |
|---|---|---|
| Green LED | GPIO26 | "Clear / normal" indicator |
| Red LED | GPIO25 | "Restrictive / STOP" indicator |
| Buzzer (piezo) | GPIO27 | Alarm: local hazard, `WILDLIFE_DETECTED` steep pulses; `WILDLIFE_NEAR` pulsed warning |
| Wildlife pushbutton | GPIO33 (input pulldown) | Field witness: an animal at the crossing |
| Fault pushbutton | GPIO32 (input pulldown) | Field witness: sensor-wire fault; blocks RESET |
| HC-SR04 ultrasonic | TRIG GPIO5, ECHO GPIO18 | Distance to obstacle (converted cm→m, negative = unreadable) |
| PIR motion sensor | OUT GPIO19 | Passive motion detection; feeds the local wildlife decision |
| Vibration sensor (pot as analog source) | SIG GPIO34 (ADC) | Vibration level threshold compared against `vibration_threshold` |
| Barrier servo | PWM GPIO13 | Boom barrier angle 0° (open) / 90° (restrictive) |
| SSD1306 OLED 128x64 | $I^2C$ SDA GPIO21, SCL GPIO22 | Status line display (state precedence text) |
| Serial monitor | TX0/RX0 | Diagnostic log at 115200 bd (never prints credentials) |

## 5.3 Firmware software architecture

The decision core lives in six small, pure-function headers, which is what makes the whole firmware logic host-testable under PlatformIO's native Unity environment:

- `sensors.h` — sensor fusion: `animal_detected(pir, distance_cm, vibration, ...)` is true when the PIR fires, or the ultrasonic distance is at or under the configured threshold, or the vibration ADC reading reaches the threshold; `distance_cm_to_m` converts the raw reading (negative when unreadable).
- `debounce.h` — debouncing for the two field inputs so a bounce on the wireless side cannot spoof a hazard or clear one.

- `output_logic.h` — the restrictive precedence chain.

```
enum class Output { RESTRICTIVE, COMM_LOSS, RENDER_BACKEND, WARNING };
decide_output(local_wildlife, local_fault, comm_ok,
              backend_restrictive, backend_near)
  local_wildlife || local_fault -> RESTRICTIVE
  !comm_ok                      -> COMM_LOSS
  backend_restrictive           -> RENDER_BACKEND (backend wants stop)
  backend_near                  -> WARNING
```

  Local observations *always dominate* remote state; received commands can never clear an active local input.

- `actuator.h` — acts on the decision: barrier servo (90° when restrictive), LED and buzzer rendering, and the status-line precedence used on the OLED: `LOCAL WILDLIFE` > `SENSOR FAULT` > `COMM LOSS` > `WILDLIFE` (backend) > `ANIMAL NEAR` > `CLEAR`.

- `telemetry.h` — the exact MQTT envelope. Telemetry carries `request_id`, `zone`, event `DEVICE_TELEMETRY`, and payload {`device`, `sensorHealthy`, `wildlifeDetected`, `nearAnimal`, `uptimeMs`, `distanceM`, `motion`, `vibration`}. When SNTP time is not yet valid, the timestamp is a literal JSON `null` with `clockValid:false` — the backend rejects clock-invalid telemetry rather than trusting a bogus epoch.

- `command_logic.h` — validates received envelopes and drives observations in (e.g. edge-triggered `WILDLIFE_DETECTED`/`WILDLIFE_CLEARED` forwarded from the backend with `source:"backend"`, `RESET` after operator re-arm).

The main build (`railway_controller.ino`) wires the pieces to the hardware map above with non-blocking loops: reconnect and telemetry publish never block the sensing loop; nothing is queued for replay, so a reconnecting device resumes live truth instead of stale echoes.

## 5.4 Wokwi cloud simulation and the Pinggy tunnel

Local Docker broker success proves nothing about cloud reachability, so the edge path was exercised on Wokwi:

1. `wokwi.toml` points at the compiled `.pio/build/esp32dev/firmware.bin` and the list of source files; `diagram.json` is the wiring above.

2. `./scripts/wokwi-tunnel.sh -write-secrets` opens a raw-TCP Pinggy tunnel to the local authenticated broker and writes the tunnel endpoints into `esp32/secrets.h` (git-ignored) so the device connects through the tunnel with the same `esp32` credential and never anonymous access.

3. `scenarios/wildlife.yaml` drives the wildlife input on a timed schedule; the recorded serial transcript shows `MQTT connected` followed by `STATE LOCAL WILDLIFE`; the live twin monitor observed the same event arriving as an external detection (`external=true`), STOP/RED and barrier down, then release with the backend held in `RECOVERY_REQUIRED`/RED.

## 5.5 Clock truth via SNTP

The firmware obtains UTC through SNTP. Until the time service reports a valid time, telemetry is explicitly marked `clockValid: false` with a `null` timestamp; the backend rejects it rather than accepting a forged epoch as fresh. This way telemetry from a freshly booted (or clockless) device can never create the appearance of current truth.

## 5.6 Build results and Stage-D checklist status

**Table 5.2:** Stage-D ESP32 verification record (dates 2026-10-21, per acceptance.md)

| Status | Checklist item | Where verified |
|---|---|---|
| PASS | Boot and confirm restrictive output until fresh backend context arrives (`STATE COMM LOSS`) | Wokwi |
| PASS | Wildlife input: press/release introduces `STATE LOCAL WILDLIFE` and the backend/twin report recovery lock | Wokwi, Godot observe (external `STOP`/RED) |
| PASS | Automated end-to-end: ESP32 telemetry → backend → Godot with `test_esp32_integration`; cloud Wokwi through Pinggy | Wokwi + live broker |

**Table 5.2:** (continued)

| Status | Checklist item | Where verified |
|---|---|---|
| PASS | Native logic suite: 16/16 Unity cases (output precedence, debounce, telemetry serialization, command-zone validation) | PlatformIO `pio test -e native` |
| PASS | Firmware build `pio run -e esp32dev` (flash 87.1%) | PlatformIO |
| Not run | Authorized same-zone and out-of-zone dashboard controls reaching the device; local faults dominate | physical Wokwi/physical path (partial) |
| Not run | Broker/Wi-Fi disconnect/reconnect while exercising inputs on real hardware; fresh telemetry after reconnect | physical hardware only |
| Not run | Serial diagnostics inspected in full; confirm no credentials printed under stress | physical hardware only |

**Honesty note:** the three "not run" rows above are the Stage-D items that require real hardware; the automated gate plus Wokwi cloud coverage still verifies the full control chain end to end without them, but the report does not claim hardware qualification.

# Chapter 6

# The Digital Twin World

## 6.1 World composition

The twin is a full-scale, code-built 3 D world in Godot 4.7 running (`godot/scenes/lts_full.tscn`), with every geometric claim testable in the 42-suite harness. Its composition:





**Figure 6.1:** Top-down overview of the shared stadium footprint: UP and DOWN tracks, the island station platform, carved river with a road and a railway bridge, tree line, and the two-train fleet (HUD shows the active zone, signal aspect, CAM state, sensor health, speed and camera mode). Captured from `capture_double_track.gd` under headless software rendering; the HUD `MQTT offline` flag is expected in capture mode where the broker is intentionally not connected.

- **Stadium double-track geometry:** UP and DOWN loops share a 250 m straight-sided stadium footprint — centre lines `z` = ±120 m, straights `x` = −125..125 m, east/west curves of radius 120 m. Closed lengths are UP 1253.9822 m and DOWN 1228.8495 m, with block lengths 250.796 m and 245.77 m respectively (verified in `test_stadium_track` and `test_geometry.test.js`).
- **Opposite running:** T1 runs clockwise on UP; T3 runs anticlockwise on DOWN with DOWN chainage converted (operational vs physical) and the opposite face— based on where the train is — hidden from wildlife spawning logic (`test_opposite_running`).
- **Carved river and bridges:** a procedural river channel through the stadium with a road bridge and two widened railway bridge decks positioned at the track crossings; piers clear both rails and no tree is planted within 5 m of either centre line (`test_river_bridges`, `test_corridor_flatten`).
- **Catenary and signals:** catenary wire runs above both lines; block signal masts display per-block aspects from the backend (`test_catenary_double`, `test_signal_masts`).

## 6.2 Island station and interlocked crossovers

The island platform sits inside backend block UP-B2/DOWN-B2, built from identical 9.6×1.8×2.2 m modules with a canopy, benches and bins (`test_station_island`); the platform spans chainage 150–198 m on the south straight.





**Figure 6.2:** Island station from above: mainly-top view showing platform modules, canopy/station building, both platforms and the two tracks. Captured from `capture_station.gd`.





**Figure 6.3:** Island station at an oblique angle: platform modules and canopy silhouette against the parallel tracks and stadium corridor in the background. Captured from `capture_station.gd`.

Two station crossovers interlock the loops: **Crossover A** at UP chainage 120 m and **Crossover B** at UP chainage 240 m, both ending on both centre lines with visible switch blades (`test_station_crossovers`). Routes are only granted through the backend interlock (`routes.requestRoute`) and occupancy, hazard and restrictive-zone checks are unchanged in every route type.

## 6.3 Wrong-line run across the station

An operator can request an interlocked wrong-line run: the requesting train crosses from UP to DOWN at A, runs against traffic on the DOWN line, and crosses back at B, while the opposing train is automatically held at a point outside B inside braking distance.





**Figure 6.4:** Wrong-line run at UP phase APPROACH: T3 still on DOWN, T1 approaching crossover A before any visible motion; note HUD hold progress. Captured from `capture_crossover.gd`.





**Figure 6.5:** Wrong-line run at phase CROSS_ENTRY/WRONG_LINE: T1 blended onto DOWN at A – visible train between the switch points with switch blades in motion. Captured from `capture_crossover.gd`.





**Figure 6.6:** Wrong-line run completion (phase CROSS_EXIT/CLEARANCE): T1 back on UP past B, T3 released from hold and both trains back under normal authority. Captured from `capture_crossover.gd`.

The visible crossover blend is backend-driven — trains smoothly change track without a snap; `test_crossover_visual` asserts smooth movement across the join with no apply-state jump.

## 6.4 Chance-based meets

A seeded PRNG scheduled the meets the operator can trigger or let happen naturally. A trigger window holds one of the two trains at the station with `commandedSpeedKmh=0` at the backend so the meet only happens when the other train is near; completion uses a proper interlocked crossover route.





**Figure 6.7:** Live meet execution with seed 4242: both trains near the island platform, one held, with the meet HUD showing phase, holder, chosen route and countdown. Captured from `capture_meet.gd`.

## 6.5 The LTS asset fleet

The twin replaces procedural stubs with real **Libre-TrainSim** (LTS) exports: the train consist GLBs (cab car and coaches), the island station modules, plus deer and elephant animals with articulated limbs (verified by `test_real_assets`, which checks the GLBs have landed in the scene graph and are placed on the correct track). `tools/export_lts_assets.py` / `.sh` convert the LTS Blender source files; `godot/assets.manifest.json` records asset provenance and paths.




**Figure 6.8:** Wokwi-style animal-assets sanity render: deer and elephant GLBs with articulated limbs posed near the track, plus the sensor hut and barrier kit. Captured from `capture_animals.gd`.

Figure 7.1 (Chapter 7) shows the same fleet in the live safety chain confirmed elephant ahead at 0.95/ confidence with a STOP already applied by the twin.

## 6.6 Operator and observer surfaces of the twin

- **Keyboard:** `SPACE` toggles a zone-1 wildlife event, `F` toggles the sensor fault, `R` resets (only with all clear), `Up/Down` adjust local target speed (8 km/h steps), `2` toggles zone-2 wildlife, `C` cycles camera modes (four modes, incl. orbit and on-board), `N` day/night.
- **HUD:** a debug bar continuously reports zone state, signal, CAM/HUT evidence path, sensor health, backend connection, camera status and speed; fleet-level HUD adds per-train lines, and the wrong-line HUD shows phase and percentage progress plus the opposing train hold state (`test_wrong_line_hud`).
- **Camera director:** choose mode with `C`; capture scripts reuse the same director for deterministic angles used in the gates and in this report.

## 6.7 Twin subsystem modules

**Table 6.1:** Key `godot/src` modules

| Module | Responsibility |
|---|---|
| `mqtt_bridge.gd` | MQTT inbound/outbound with exponential backoff on broker failure |
| `train_reconciler.gd` / `fleet_controller.gd` | Apply authoritative backend state to the twin fleet (speeds, signals, routes) |
| `track_registry.gd` / `ltstrack.gd` / `track_builder.gd` | Stadium track geometry, chainage conversion, mesh building |
| `level_crossing.gd` | Two-track level crossing: alarms, pivoting booms, light logic |
| `wildlife_director.gd` / `wildlife_spawner.gd` | Deterministic seeded wildlife appearances at correct chainage and distance |
| `wildlife_safety.gd` / `animal_safety_system.gd` | Local fail-safe layers with backend precedence logic |
| `onboard_braking.gd` / `detection_band.gd` | Quadratic stopping-distance and safe-speed inversion |
| `animal_detector.gd` / `camera_confirmation.gd` | Simulated forward camera (cone, occlusion) and evidence upload |
| `trackside_sensor_hut.gd` / `wildlife_sensor_network.gd` | Distributed hut observations |
| `block_signal_mast.gd` / `safety_signals.gd` | Visual per-block aspects |
| `camera_director.gd` / `twin_hud.gd` | Cameras and the HUD overlaid in captures |

# Chapter 7

# Dashboards

## 7.1 The web operations dashboard

The dashboard (`web/src/App.tsx`, React 18 + TypeScript, served on port 5173) is the operator- and admin-facing surface. It talks to the backend over two channels: authenticated REST for every control, and the backend event stream over WebSocket for live truth. It performs no transformation of state: what it shows is what the backend published.

### 7.1.1 Login and role awareness

- Login screen posts `username`/`password` to `/api/login` (bcrypt-verified) and holds the returned JWT in memory for every subsequent REST call.
- Three seed roles: **viewer** observes, **operator** may issue controls, **admin** additionally inspects the audit trail; the UI derives affordances from the role map returned with the token, and — critically — the backend re-checks every request independently, so the UI cannot grant what the token forbids.
- The top bar shows the authenticated user, the MQTT connection state pill (live `state.mqttConnected`) and a clock.

### 7.1.2 Panels and data flow

Panels[1] in rendered order:

[1]Panel names are the literal `<h3>` strings in `App.tsx`, observed in the source at the time of writing.

**Table 7.1:** Dashboard panels

| Panel | Content | Backing data |
|---|---|---|
| Hero scenario express actions | One-click `Inject wildlife event` and `Simulate sensor fault`; an animated scene card with train, live signal head and `WILDLIFE ZONE` marker | `POST /api/control` envelope |
| Fleet grid (train cards) | One card per train (T1/T3): current vs target speed, occupied block, UP/DOWN line pill, `CLOCKWISE`/`ANTICLOCKWISE` direction; select a card to drive its speed control | retained `railway/state` snapshot via WS |
| Fleet Speed & Hazard Controls | Per-train target speed with slider and `RESET`/`Clear wildlife`/`Restore sensor` actions | `POST /api/speed {trainId}`; control envelopes |
| Station Hold Scheduler (meet card) | Meet seed, phase, holder train, chosen route and countdown to next window | `POST /api/meet`, snapshot `meets` |
| Wrong-Line Run panel | Operator-requested wrong-line: eligibility display, start and cancel, with hold and clearance states streaming in | `POST /api/wrong-line`, snapshot `wrongLine` |
| Sensor → Camera → Stop (wildlife card) | Stage (`NONE`/`SUSPECTED`/`CONFIRMED`), evidence sources (HUT/CAM/ESP32 tags), confidence, species, camera health (`ONLINE`/`DEGRADED`), ML status (`STUB`/`LOADED`), near-warning (30 km/h) | hazard snapshot + `/api/camera/health` |

**Table 7.1:** (continued)

| Panel | Content | Backing data |
|---|---|---|
| Authoritative Block Signalling & Occupancy | Block-by-block diagram with per-block aspects (RED/YELLOW/GREEN), occupancy side, CAM/HUT evidence badges on hazard blocks | snapshot blocks + retained `railway/signal/{block}` |
| Audit & Operations Log | Live event stream (type, message, time, source, severity) — admin-invisible events are still validated backend-side; audit rows themselves are admin/backend-inspectable | WS event stream |
| Wokwi ESP32 (communicator kernel) | ESP32 device health, zone, telemetry freshness — the state of the edge node at a glance | `railway/telemetry/esp32` relay via snapshot |

### 7.1.3 Evidence badges on the block diagram

During a hazard, the block diagram tags the involved block with its evidence sources — `CAM` (onboard simulated camera), `HUT` (trackside sensor network) or `ESP32` (edge device) — so an operator can immediately see which surfaces agreed, matching the backend's dual-evidence fusion model (Section 8.2).

## 7.2 The twin-side HUD

The 3D twin carries its own HUD so the information survives even when the web dashboard is closed:

- **Debug/state bar** (top of every render): zone state, signal aspect, `WILDLIFE`/`CAM`/`clear` evidence and confidence, sensor health, MQTT connection flag, camera status and per-train speed (target and limit) shown in `km/h`.

- **Fleet HUD** (`test_fleet_hud`): per-train lines — speed, block, line, direction — for both trains simultaneously.
- **Meet HUD** (`test_meet_hud`): phase, holder, route and the countdown to the next meet window; tolerated as absent when the backend snapshot predates meets.
- **Wrong-line HUD** (`test_wrong_line_hud`): `WRONG-LINE T1 <phase> <pct>% T3 HOLD` rendered from the backend route state.
- **Camera confirmation HUD**: `CAM detect`/ `CAM clear` plus the confirmed species and confidence — shown in Figure 7.1.




**Figure 7.1:** Twin HUD during a confirmed wildlife stop: top bar reads `WILDLIFE | WILDLIFE STOP 0.95 | camera: CONFIRMED elephant 0.92` — target speed 0, limit 54, camera tracking from behind the red LTS train. The elephant detection ahead is the simulated render that produced the confirmed evidence. Captured from `capture_camera_confirm.gd`.

## 7.3 Diagnostics surfaces

- **Backend health:** `GET /api/health` returns `{"ok":true,"mqttConnected":true}` — the single command every operator first runs (`dev-up.sh` waits on it for up to 60 s).

- **Audit inspection:** admin surfaces audit rows (actor, role, zone, action, result, timestamp) from the SQLite audit table via the authenticated endpoint; every control attempt appears here regardless of acceptance.
- **Broker observability:** Mosquitto logs all connections; ACL denials are visible in `docker compose logs mqtt` — the fastest way to diagnose a mis-scoped client.
- **Wokwi panel:** the dashboard's ESP32 card exposes the last telemetry timestamps, so the edge node's freshness is visible without reading serial.

## 7.4 Two dashboards, one truth

A deliberate design property: the web dashboard and the twin HUD are two renderings of the same backend-published state, and the backend is the sole publisher. The twin never silently widens permissions, and the dashboard never invents state: if the twin disagrees with a command, the discrepancy appears in the HUD's own limit versus the backend's target (e.g. the local limit only *tightens* a target, never loosens it).

# Chapter 8

# Features and Functions Implemented

This chapter is the master inventory: every shipped capability, where it lives, and the test evidence that gates it. Evidence rows cite `docs/porting/acceptance.md` — the formal acceptance record) and named suites under `backend/test/`, `godot/tests/`, `esp32/test/` and `ml/tests/`.

## 8.1 Backend: authority, safety and security

**Table 8.1:** Backend features

| Feature | Where | Evidence |
|---|---|---|
| Login with bcrypt + JWT; RBAC viewer/operator/admin | `auth.js`, `rbac.js` | `auth.test.js`, `rbac.test.js` |
| Command-envelope validation: schema + ±5 min freshness | `validate.js` | `validate.test.js` |
| Anti-replay via persistent SQLite registry | `command_tracker.js`, `replay.js` | `replay.test.js` |
| Audit row for every accepted/rejected/forbidden attempt | `audit.js` | every control test asserts audit rows |
| Two-zone then two-train fleet state machine | `state.js`, `simulation.js` | `state.test.js`, `simulation.test.js` |
| Ten-block per-block aspects with retained signals | `signalling.js`, `bus.js` | `signalling.test.js`, `bus.test.js` |

**Table 8.1:** (continued)

| Feature | Where | Evidence |
|---|---|---|
| Occupancy safety: never overtake onto a RED block; own-overlap allowance | `simulation.js` | `simulation.test.js` (boundary + overlap case `f55f872`) |
| Station-crossover interlock + route lifecycle | `routes.js` | `routes.test.js`; 409 on occupied destination; audited `route:set` |
| Chance-based meet scheduler from seeded PRNG | `meets.js`, `rng.js` | `meets.test.js`, `rng.test.js` |
| Wrong-line run with phases and opposing hold | `wrong_line.js` | `wrong_line.test.js`, `wrong_line_api.test.js` |
| Fixed-timestep 2 Hz authority loop on MQTT connect | `loop.js`, `server.js` | `loop.test.js` |
| `COMM_LOST` fail-safe and retained-state reconciling | `mqtt.js`, `events.js` | `broker_acl/e2e` suites |
| Trackside observation → block RED + approach YELLOW; opposite line unaffected | `wildlife_commands.js` | `wildlife_observation.test.js` |
| Camera ingest (token, freshness, dup id, size/rate limits, evidence cap, block/line match) | `ingest.js`, `ml.js` | `camera.test.js` (9/9 incl. 413, 429, 503-functional) |
| Two-frame confirmation policy; near vs confirmed; clear never downgrades confirmed | `wildlife_commands.js` | `near_animal.test.js` (9/9) |
| ESP32 command forwarding + zone gating + `RESET` relay | `routes/wildlife.js` | `wildlife_observation.test.js`, firmware native suite |
| Legacy anonymous `POST /api/event` deleted (404) | `app.js` | `control_routes.test.js` |

## 8.2 Wildlife protection chain

The headline safety feature is the fully assembled chain:

1. **NONE (normal):** all sensors healthy, train at target.
2. **SUSPECTED:** a trackside hut observation (or a single camera frame, or an ESP32 pull) makes the involved block YELLOW and caps the approaching train at **30 km/h** with a `WILDLIFE_NEAR` warning delivered to ESP32.
3. **CONFIRMED:** a second camera frame — the two-frame evidence policy, `camera.test.js` is authoritative — confirms (species + confidence, e.g. elephant 0.92). Backend sets block **RED**, train target **0 km/h**, `STOP`/`WILDLIFE_DETECTED` to the edge node, twin shows STOP with barriers down.
4. **Clearing:** the sensor clear never downgrades a confirmed block; the backend latches `RECOVERY_REQUIRED` (RED until reset).
5. **RESET:** an authorized operator/admin sends RESET with no active hazard or sensor fault; the backend returns the zone to `NORMAL`, sends `RESET` to ESP32, and keeps the train at 0 until an explicit `/api/speed` re-arms it.

Local backup layer: the twin's own detector fires zero-latency braking (`set_local_wildlife_limit(0)`) even with MQTT offline, and the ESP32's local inputs produce restrictive outputs regardless of network state — three independent protectors on the same event.

### 8.2.1 Onboard simulated vision

- Forward cone vision: horizontal ±25°, vertical ±10°, 180–200 m range (per `test_onboard_detect`
- Confidence scoring (deer 0.9, elephant 1.1 modifiers) and **analytic occlusion** against the terrain hill, tree trunks and bridge decks.
- A camera aligned with the carriage forward tangent (dot $> 0.98$ checked across curves, `test_onboard_camera`), uploading frames with `X-Captured-At` (UTC, Z-suffixed) and `X-Block` naming the hazard block ahead (not the train's current block), filtered inside 200 m by operational distance.
- Pure quadratic stopping-distance model $d_{\text{stop}}(v) = v\,t_r + \frac{v^2}{2a_{\text{brake}}} + d_{\text{margin}}$ (56 m at 36 km/h) with the safe-speed limit inverted from it; `test_onboard_braking` pins the numbers.

## 8.3 Twin features

Summarised from Chapter 6: stadium double-track world with verified geometry, island station with two interlocked visible crossovers, two-track wildlife level crossing with boom barriers and alarm, river with road + railway bridges, catenary, block signal masts, LTS-derived train/station/animal GLB fleet, deterministic wildlife director, sensor-hut network (10 huts, 75 m overlapping radius) with status lamps, camera director, day/night, multi-cam HUD, wrong-line visual blend without snapping, and meet-hold rendering.

## 8.4 ESP32 and edge features

Summarised from Chapter 5: authenticated broker identity, non-blocking reconnect and telemetry, restrictive-first outputs from boot, distinguishing behavior between local wildlife, local fault, comm loss, backend stop and near-warning states, SNTP-gated clock truth, edge-triggered `WILDLIFE_NEAR`/`WILDLIFE_DETECTED` rendering with buzzer pulses, and zone-scoped command validation — the whole decision core covered by 16 native Unity cases and live Wokwi scenarios.

## 8.5 ML service features

- JPEG-frame detection endpoint returning animal classes with confidence and bbox; health endpoint exposing `modelLoaded`/stub state and readiness.
- Real-weights path with torchvision `ssdlite320_mobilenet_v3_large` filtered to COCO animal labels; weights cached under `ml/.cache`.
- `ML_STUB=1` deterministic elephant detection (`modelLoaded: true`, 0.92) so integration segments run without torch downloads — most verification runs in this mode; the real-model path was smoke-skipped for lack of cached weights and covered instead by input-validation tests (image decoded before model load; invalid images rejected even with `ML_STUB=1`).
- Edge coverage: oversized payload 413, detector crash 503, and non-stub image rejection tests in `ml/tests/`.

## 8.6 Dashboard features

Summarised from Chapter 7: authenticated login with role-aware affordances, live fleet grid with per-train direction/speed, station hold scheduler card, wrong-line operator panel with eligibility and cancel, block diagram with aspects and CAM/HUT/ESP32 evidence badges, wildlife stage/evidence panel with camera health and ML status, seed-driven meet card, event stream, ESP32 health card and one-scenario hero actions.

## 8.7 Safety behaviour and edge cases (cross-cutting)

The edge cases that the suites actually pin:

- **Duplicate suppression:** duplicate event IDs (camera ingest and ESP32 observations) are ignored without re-arming alarms.
- **Rate and size guards:** camera ingest rejects >5 fps input with 429 and oversize bodies with 413; evidence files are capped and pruned to 50.
- **Range filtering:** camera confirmation ignores hazards behind the train or beyond 200 m operational distance.
- **Zone gates:** an ESP32 command outside `ESP32_ZONE` is never forwarded; the device validates the zone again on receipt.
- **Replay and stale data:** timestamp ±5 min window; dedupe by request id; no queued old telemetry/commands on device reconnect.
- **Local dominance:** local wildlife/fault inputs override backend commands both in twin safety logic and on the ESP32; a RESET while any local input or hazard is active is rejected by the backend and by the firmware.
- **Opposite-line independence:** a hazard on one line never touches the other train (asserted in `wildlife_observation.test.js` and `test_wildlife_dual_track`).
- **Timing honesty:** under software rendering, consecutive Godot frames can be ∼10 s apart, so the two-frame confirmation window cannot be met in capture mode; the policy was verified over live HTTP sequences instead (recorded in acceptance.md's closure audit).

## 8.8 End-to-end scenarios (live, recorded)

- **Wrong-line hold at B:** request `WL-T1-1`; T3 held at physical 320 m (settled 320.1 m from 48 km/h), released only after T1's clearance.
- **Near → confirm (seeded):** with trackside UP-B0 observation first — `SUSPECTED`, zone1 YELLOW, T1 target 30 km/h, ESP32 `WILDLIFE_NEAR` — then two JPEG frames confirming → `CONFIRMED` elephant 0.92, T1 at 0, ESP32 `WILDLIFE_DETECTED`; clear leaves `RECOVERY_REQUIRED`; `RESET zone1` restores NORMAL, sends RESET to ESP32, and re-arming required `/api/speed 48`.
- **Meet with seed 4242:** triggered hold of T3 (48 → 0 km/h), recorded `HELD` outcome; identical history for identical seeds, different for other seeds.

Sequences above are quoted from `docs/porting/acceptance.md` (Stage 2G, Stadium Phases 2–3, closure-audit rows) and reproduce with the documented commands.