

## **ASSIGNMENT :**

### **Question 1: Create a Procedure to Insert Employee Data**

**Write a PL/SQL procedure named insert\_employee to insert employee data into the**

**EMPLOYEES table:**

□ **Table structure: EMPLOYEES (EMP\_ID NUMBER, EMP\_NAME VARCHAR2(100),**

**DEPARTMENT VARCHAR2(50), SALARY NUMBER) create**

**table employees (**

**emp\_id number constraint employees\_pk primary key,  
emp\_name varchar2(255), dept varchar2(255),  
salary number  
)**

**CREATE PROCEDURE insert\_employees (**

**p\_emp\_id IN NUMBER,  
p\_emp\_name IN VARCHAR2,  
p\_department IN VARCHAR2, p\_salary  
IN NUMBER**

**) AS**

**BEGIN**

**INSERT INTO EMPLOYEES (emp\_id, emp\_name, dept,salary)  
VALUES (p\_emp\_id, p\_emp\_name, p\_department, p\_salary);**

**COMMIT;**

**EXCEPTION**

**WHEN OTHERS THEN**

**ROLLBACK;**

**RAISE\_APPLICATION\_ERROR(-20001, 'An error occurred while inserting  
the employee data: ' || SQLERRM);**

**END insert\_employees;**

**BEGIN**

**insert\_employee(01, 'Hemamalani', 'Development', 28000);  
END;**

**2. Create a Procedure to Update Employee Salary Write a PL/SQL procedure named update\_salary to update an employee's salary based on their current salary:**

- If the current salary is less than 5000, increase it by 10%.
- If the current salary is between 5000 and 10000, increase it by 7.5%.
- If the current salary is more than 10000, increase it by 5%.

```
CREATE PROCEDURE update_salary (  
  p_emp_id IN NUMBER  
) AS  v_current_salary  
EMPLOYEES.SALARY%TYPE;  v_new_salary  
EMPLOYEES.SALARY%TYPE;  
BEGIN  
  
  SELECT SALARY INTO v_current_salary  
  FROM EMPLOYEES  
  WHERE EMP_ID = p_emp_id;  
  
  IF v_current_salary < 5000 THEN  
v_new_salary := v_current_salary * 1.10;  
    ELSIF v_current_salary BETWEEN 5000 AND 10000 THEN  
v_new_salary := v_current_salary * 1.075;  ELSE  
    v_new_salary := v_current_salary * 1.05;  
  END IF;  
  UPDATE EMPLOYEES  
  SET SALARY = v_new_salary  
  WHERE EMP_ID = p_emp_id;
```

```

        COMMIT;
EXCEPTION
    WHEN NO_DATA_FOUND THEN
        RAISE_APPLICATION_ERROR(-02, 'Employee ID not found');
    WHEN OTHERS THEN
        ROLLBACK;
        RAISE_APPLICATION_ERROR(-03, 'An error occurred while updating the
salary: ' || SQLERRM);
END update_salary;
/

```

```

BEGIN
    update_salary(1);
END;
/
select * from employees;

```

### **3. Use a Cursor to Display Employee Names**

**Write a PL/SQL block using a cursor to fetch and display all employee names from the EMPLOYEES table. DECLARE**

```

    CURSOR emp_cursor IS
        SELECT EMP_NAME FROM EMPLOYEES;
v_emp_name EMPLOYEES.EMP_NAME%TYPE;
BEGIN
    OPEN emp_cursor;
    LOOP

```

```

    FETCH emp_cursor INTO v_emp_name;
    EXIT WHEN emp_cursor%NOTFOUND;
    DBMS_OUTPUT.PUT_LINE(v_emp_name);
END LOOP;
CLOSE emp_cursor;
EXCEPTION
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
END;
/

```

#### **4. Create a View for Employees with High Salary**

**Write a SQL statement to create a view named `high_salary_employees` that displays employees earning more than 10000.**

```

CREATE VIEW high_salary_employees AS
SELECT EMP_ID, EMP_NAME, DEPT, SALARY
FROM EMPLOYEES
WHERE SALARY > 10000;
SELECT * FROM high_salary_employees;

```

#### **5. Create a Function to Calculate Bonus**

**Write a PL/SQL function named `calculate_bonus` to calculate the bonus based on an employee's salary:**

- ☐ **Employees earning less than 5000 get a bonus of 10% of their salary.**
- ☐ **Employees earning between 5000 and 10000 get a bonus of 7.5% of their salary.**

□ **Employees earning more than 10000 get a bonus of 5% of their salary.**

```
CREATE FUNCTION calculate_bonus (  
p_salary IN NUMBER ) RETURN  
NUMBER IS    v_bonus NUMBER;  
BEGIN  
  
    IF p_salary < 5000 THEN  
v_bonus := p_salary * 0.10;  
    ELSIF p_salary BETWEEN 5000 AND 10000 THEN  
        v_bonus := p_salary * 0.075;  
ELSE  
        v_bonus := p_salary * 0.05;  
END IF;  
  
    RETURN v_bonus;  
EXCEPTION  
    WHEN OTHERS THEN  
        RETURN NULL;  
END calculate_bonus;  
/  
SELECT calculate_bonus(4500) FROM DUAL;  
  
DECLARE  
    v_salary NUMBER := 7500;  
v_bonus NUMBER; BEGIN
```

```
v_bonus := calculate_bonus(v_salary);  
DBMS_OUTPUT.PUT_LINE('The bonus is: ' || v_bonus);  
END;  
/
```

### **Question 6: Create a Trigger to Log Employee Insertions**


**Write a PL/SQL trigger named log\_employee\_insert to log whenever an employee is inserted into the EMPLOYEES table.**

```
CREATE TABLE EMPLOYEE_LOG (  
    LOG_ID NUMBER GENERATED BY DEFAULT AS IDENTITY PRIMARY  
    KEY,  
    EMP_ID NUMBER,  
    EMP_NAME VARCHAR2(100),  
    DEPARTMENT VARCHAR2(50),  
    SALARY NUMBER,  
    INSERT_DATE DATE  
);  
  
CREATE TRIGGER log_employee_insert  
AFTER INSERT ON EMPLOYEES  
FOR EACH ROW  
BEGIN  
    INSERT INTO EMPLOYEE_LOG (EMP_ID, EMP_NAME, DEPT, SALARY,  
    INSERT_DATE)  
    VALUES (:NEW.EMP_ID, :NEW.EMP_NAME, :NEW.DEPT,  
    :NEW.SALARY, SYSDATE);  
END;
```

/

```
INSERT INTO EMPLOYEES (EMP_ID, EMP_NAME, DEPT, SALARY)
VALUES (07, 'Hari', 'IT', 22000);
```

**Question 7:** Consider the orders and order\_items tables from the sample database.



```
CREATE TABLE ORDERS (
  ORDER_ID NUMBER PRIMARY KEY,
  CUSTOMER_ID NUMBER,
  STATUS VARCHAR2(20),
  SALESMAN_ID NUMBER,
  ORDER_DATE DATE
);
```

```
CREATE TABLE ORDER_ITEMS (
  ORDER_ID NUMBER,
  ITEM_ID NUMBER,
  PRODUCT_ID NUMBER,
  QUANTITY NUMBER,
  UNIT_PRICE NUMBER,
```

```
PRIMARY KEY (ORDER_ID, ITEM_ID),  
FOREIGN KEY (ORDER_ID) REFERENCES ORDERS (ORDER_ID)  
);
```

**A) Create a view that returns the sales revenues by customers. The values of the credit column are 5% of the total sales revenues.**

```
CREATE VIEW sales_revenues_by_customers AS  
SELECT  
    o.CUSTOMER_ID,  
    SUM(oi.QUANTITY * oi.UNIT_PRICE) AS total_sales_revenue,  
    SUM(oi.QUANTITY * oi.UNIT_PRICE) * 0.05 AS credit  
FROM  
    ORDERS o  
    JOIN ORDER_ITEMS oi ON o.ORDER_ID = oi.ORDER_ID  
GROUP BY  
    o.CUSTOMER_ID;  
  
SELECT * FROM sales_revenues_by_customers;
```

**B) Write the PL/SQL query to develop an anonymous block which:**

**1. Reset the credit limits of all customers to zero.**

```
UPDATE Orders SET credit = 0;
```

**2. Fetch customers sorted by sales in descending order and give them new credit limits from a budget of 1 million.**

```
DECLARE
```



```

CURSOR customer_cursor IS
    SELECT CUSTOMER_ID, Total_Sales_Revenue
    FROM Sales_Revenue_By_Customers
    ORDER BY Total_Sales_Revenue DESC;

customer_rec customer_cursor%ROWTYPE;
budget NUMBER := 1000000;
remaining_budget NUMBER := 1000000;
BEGIN
    UPDATE CUSTOMERS
    SET CREDIT_LIMIT = 0;
    OPEN customer_cursor;
    LOOP
        FETCH customer_cursor INTO customer_rec;
        EXIT WHEN customer_cursor%NOTFOUND;
        IF remaining_budget >= customer_rec.Total_Sales_Revenue * 0.05 THEN
            UPDATE CUSTOMERS
            SET CREDIT_LIMIT = customer_rec.Total_Sales_Revenue * 0.05
            WHERE CUSTOMER_ID = customer_rec.CUSTOMER_ID;
            remaining_budget := remaining_budget - (customer_rec.Total_Sales_Revenue *
            0.05);
        ELSE
            UPDATE CUSTOMERS
            SET CREDIT_LIMIT = remaining_budget
            WHERE CUSTOMER_ID = customer_rec.CUSTOMER_ID;
            remaining_budget := 0;
        EXIT;
    END LOOP;
END;

```

```

        END IF;
    END LOOP;
    CLOSE customer_cursor;
END;
/

```

**Question 8: Write a program in PL/SQL to show the uses of implicit cursor without using any attribute.**

**Table: employees**

employee_id	integer
first_name	varchar(25)
last_name	varchar(25)
email	archar(25)
phone_number	varchar(15)
hire_date	date
job_id	varchar(25)
salary	integer
commission_pct	decimal(5,2)
manager_id	integer
department_id	integer

```

CREATE TABLE EMPLOYEES (
    EMPLOYEE_ID INTEGER PRIMARY KEY,
    FIRST_NAME VARCHAR2(25),
    LAST_NAME VARCHAR2(25),
    EMAIL VARCHAR2(25),
    PHONE_NUMBER VARCHAR2(15),
    HIRE_DATE DATE,
    JOB_ID VARCHAR2(25),
    SALARY INTEGER,
    COMMISSION_PCT NUMBER(5,2),

```

```
MANAGER_ID INTEGER,  
DEPARTMENT_ID INTEGER  
);
```

```
DECLARE
```

```
-- Local variables to hold employee details
```

```
  v_employee_id EMPLOYEES.EMPLOYEE_ID%TYPE;  
  v_first_name EMPLOYEES.FIRST_NAME%TYPE;  
  v_last_name EMPLOYEES.LAST_NAME%TYPE;   v_email  
  EMPLOYEES.EMAIL%TYPE;   v_phone_number  
  EMPLOYEES.PHONE_NUMBER%TYPE;   v_hire_date  
  EMPLOYEES.HIRE_DATE%TYPE;   v_job_id  
  EMPLOYEES.JOB_ID%TYPE;   v_salary  
  EMPLOYEES.SALARY%TYPE;   v_commission_pct  
  EMPLOYEES.COMMISSION_PCT%TYPE;   v_manager_id  
  EMPLOYEES.MANAGER_ID%TYPE;   v_department_id  
  EMPLOYEES.DEPARTMENT_ID%TYPE;
```

```
-- Cursor variable to hold the cursor
```

```
CURSOR emp_cursor IS
```

```
  SELECT * FROM EMPLOYEES;
```

```
BEGIN
```

```
-- Open the cursor
```

```
OPEN emp_cursor;
```

```
-- Loop through each row in the cursor
```

LOOP

    FETCH emp\_cursor INTO

    v\_employee\_id,

    v\_first\_name,

    v\_last\_name,        v\_email,

    v\_phone\_number,

    v\_hire\_date,        v\_job\_id,

    v\_salary,

    v\_commission\_pct,

    v\_manager\_id,

    v\_department\_id;

    EXIT WHEN emp\_cursor%NOTFOUND;

    -- Print employee details

    DBMS\_OUTPUT.PUT\_LINE('Employee ID: ' || v\_employee\_id);

    DBMS\_OUTPUT.PUT\_LINE('First Name: ' || v\_first\_name);

    DBMS\_OUTPUT.PUT\_LINE('Last Name: ' || v\_last\_name);

    DBMS\_OUTPUT.PUT\_LINE('Email: ' || v\_email);

    DBMS\_OUTPUT.PUT\_LINE('Phone Number: ' || v\_phone\_number);

    DBMS\_OUTPUT.PUT\_LINE('Hire Date: ' || v\_hire\_date);

    DBMS\_OUTPUT.PUT\_LINE('Job ID: ' || v\_job\_id);

    DBMS\_OUTPUT.PUT\_LINE('Salary: ' || v\_salary);

    DBMS\_OUTPUT.PUT\_LINE('Commission Pct: ' || v\_commission\_pct);

    DBMS\_OUTPUT.PUT\_LINE('Manager ID: ' || v\_manager\_id);

    DBMS\_OUTPUT.PUT\_LINE('Department ID: ' || v\_department\_id);

    DBMS\_OUTPUT.PUT\_LINE('-----');

```
END LOOP;
```

```
-- Close the cursor
```

```
CLOSE emp_cursor;
```

```
EXCEPTION
```

```
WHEN OTHERS THEN
```

```
    DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
```

```
END;
```

```
/
```

**Question 9: Write a program in PL/SQL to create a cursor displays the name and salary of each employee in the EMPLOYEES table whose salary is less than that specified by a passed-in parameter value.**

**Table: employees**

employee_id	integer
first_name	varchar(25)
last_name	varchar(25)
email	archar(25)
phone_number	varchar(15)
hire_date	date
job_id	varchar(25)
salary	integer
commission_pct	decimal(5,2)
manager_id	integer
department_id	integer

```

CREATE TABLE EMPLOYEES (
    EMPLOYEE_ID INTEGER PRIMARY KEY,
    FIRST_NAME VARCHAR2(25),
    LAST_NAME VARCHAR2(25),
    EMAIL VARCHAR2(25),
    PHONE_NUMBER VARCHAR2(15),
    HIRE_DATE DATE,
    JOB_ID VARCHAR2(25),
    SALARY INTEGER,
    COMMISSION_PCT NUMBER(5,2),
    MANAGER_ID INTEGER,
    DEPARTMENT_ID INTEGER
);

```

DECLARE

p\_salary\_limit NUMBER := 50000; -- Replace with desired value or pass as a parameter

CURSOR emp\_cursor IS

SELECT FIRST\_NAME, SALARY

FROM EMPLOYEES

WHERE SALARY < p\_salary\_limit;

emp\_record emp\_cursor%ROWTYPE;

BEGIN

OPEN emp\_cursor;

LOOP

FETCH emp\_cursor INTO emp\_record;

EXIT WHEN emp\_cursor%NOTFOUND;

DBMS\_OUTPUT.PUT\_LINE('First Name: ' || emp\_record.FIRST\_NAME);

DBMS\_OUTPUT.PUT\_LINE('Salary: ' || emp\_record.SALARY);

DBMS\_OUTPUT.PUT\_LINE('-----');

END LOOP;

CLOSE emp\_cursor;

END;

/

**Question 10: Write a code in PL/SQL to create a trigger that checks for duplicate values in a specific column and raises an exception if found.**

```
CREATE TRIGGER check_duplicate_email
BEFORE INSERT OR UPDATE ON EMPLOYEES
FOR EACH ROW DECLARE
    v_count INTEGER;
BEGIN

    SELECT COUNT(*)
    INTO v_count
    FROM EMPLOYEES
    WHERE EMAIL = :NEW.EMAIL
    AND EMPLOYEE_ID <> :NEW.EMPLOYEE_ID;

    IF v_count > 0 THEN
        RAISE_APPLICATION_ERROR(-01, 'Duplicate email address detected: ' ||
:NEW.EMAIL);
    END IF;
END;
/
```

**Question 11: Write a PL/SQL procedure for selecting some records from the database using some parameters as filters.**

**□ Consider that we are fetching details of employees from ib\_employee table where salary is a parameter for filter.**

```
CREATE TABLE IB_EMPLOYEE (
```



```
EMPLOYEE_ID INTEGER PRIMARY KEY,  
FIRST_NAME VARCHAR2(25),  
LAST_NAME VARCHAR2(25),  
EMAIL VARCHAR2(25) UNIQUE,  
PHONE_NUMBER VARCHAR2(15),  
HIRE_DATE DATE,  
JOB_ID VARCHAR2(25),  
SALARY INTEGER,  
COMMISSION_PCT NUMBER(5,2),  
MANAGER_ID INTEGER,  
DEPARTMENT_ID INTEGER  
);
```

```
INSERT INTO IB_EMPLOYEE (EMPLOYEE_ID, FIRST_NAME,  
LAST_NAME, EMAIL, PHONE_NUMBER, HIRE_DATE, JOB_ID, SALARY,  
COMMISSION_PCT, MANAGER_ID, DEPARTMENT_ID)  
VALUES (01, 'Hemamalani', 'Elaiyaraja', 'hema243@gmail.com', '6369176255',  
TO_DATE('2023-07-12', 'YYYY-MM-DD'), 'IT', 23000, 0.10, NULL, 10);
```

```
INSERT INTO IB_EMPLOYEE (EMPLOYEE_ID, FIRST_NAME,  
LAST_NAME, EMAIL, PHONE_NUMBER, HIRE_DATE, JOB_ID, SALARY,  
COMMISSION_PCT, MANAGER_ID, DEPARTMENT_ID)  
VALUES (02, 'Hari', 'Dharan', 'haridharan@gmail.com', '9065079091',  
TO_DATE('2021-03-02', 'YYYY-MM-DD'), 'HR', 60000, 0.05, 1, 20);
```

```
INSERT INTO IB_EMPLOYEE (EMPLOYEE_ID, FIRST_NAME,  
LAST_NAME, EMAIL, PHONE_NUMBER, HIRE_DATE, JOB_ID, SALARY,  
COMMISSION_PCT, MANAGER_ID, DEPARTMENT_ID)
```

```
VALUES (03, 'Bharath', 'Sunder', 'bharathsunder107@gmail.com', '7080164590',  
TO_DATE('2021-11-24', 'YYYY-MM-DD'), 'FINANCE', 50000, 0.07, 1, 30);
```

```
select * from IB_EMPLOYEE;
```

```
CREATE PROCEDURE fetch_employees_by_salary(p_salary IN NUMBER) IS  
BEGIN
```

```
    DBMS_OUTPUT.PUT_LINE('Fetching employees with salary: ' || p_salary);  
    FOR emp_rec IN (  
        SELECT *  
        FROM IB_EMPLOYEE  
        WHERE SALARY = p_salary  
    ) LOOP  
        -- Display employee details  
        DBMS_OUTPUT.PUT_LINE('Employee ID: ' || emp_rec.EMPLOYEE_ID);  
        DBMS_OUTPUT.PUT_LINE('First Name: ' || emp_rec.FIRST_NAME);  
        DBMS_OUTPUT.PUT_LINE('Last Name: ' || emp_rec.LAST_NAME);  
        DBMS_OUTPUT.PUT_LINE('Email: ' || emp_rec.EMAIL);  
        DBMS_OUTPUT.PUT_LINE('Phone Number: ' ||  
emp_rec.PHONE_NUMBER);  
        DBMS_OUTPUT.PUT_LINE('Hire Date: ' || emp_rec.HIRE_DATE);  
        DBMS_OUTPUT.PUT_LINE('Job ID: ' || emp_rec.JOB_ID);  
        DBMS_OUTPUT.PUT_LINE('Salary: ' || emp_rec.SALARY);  
        DBMS_OUTPUT.PUT_LINE('Commission Pct: ' || emp_rec.COMMISSION_PCT);  
        DBMS_OUTPUT.PUT_LINE('Manager ID: ' || emp_rec.MANAGER_ID);  
        DBMS_OUTPUT.PUT_LINE('Department ID: ' ||  
emp_rec.DEPARTMENT_ID);
```

```

        DBMS_OUTPUT.PUT_LINE('-----');
    END LOOP;

    IF SQL%ROWCOUNT = 0 THEN
        DBMS_OUTPUT.PUT_LINE('No employees found with the specified
salary. ');  END IF;
END;

/

BEGIN
    fetch_employees_by_salary(50000);
END;

/

```

**Question 12: Write PL/SQL code block to increment the employee's salary by 1000 whose employee\_id is 102 from the given table below.**

EMPLOYEE E_ID	FIRST_NAME	LAST_NAME	EMAIL _ID	PHONE_NUMBER	JOIN_DATE	JOB_ID	SALARY
100	ABC	DEF	abef	9876543210	2020-06-06	AD_PRES	24000.00
101	GHI	JKL	ghkl	9876543211	2021-02-08	AD_VP	17000.00
102	MNO	PQR	mnqr	9876543212	2016-05-14	AD_VP	17000.00
103	STU	VWX	stwx	9876543213	2019-06-24	IT_PROG	9000.00

```

CREATE TABLE EMPLOYEE (
    EMPLOYEE_ID INTEGER PRIMARY KEY,
    FIRST_NAME VARCHAR2(25),
    LAST_NAME VARCHAR2(25),
    EMAIL VARCHAR2(25),

```

```

    PHONE_NUMBER VARCHAR2(15),
    JOIN_DATE DATE,
    JOB_ID VARCHAR2(25),
    SALARY NUMBER
);

INSERT INTO EMPLOYE (EMPLOYEE_ID, FIRST_NAME, LAST_NAME,
EMAIL, PHONE_NUMBER, JOIN_DATE, JOB_ID, SALARY)
VALUES (100, 'ABC', 'DEF', 'abef', '9876543210', TO_DATE('2020-06-06',
'YYYY-MM-DD'), 'AD_PR', 24000.00);

INSERT INTO EMPLOYE (EMPLOYEE_ID, FIRST_NAME, LAST_NAME,
EMAIL, PHONE_NUMBER, JOIN_DATE, JOB_ID, SALARY)
VALUES (101, 'GHI', 'JKL', 'ghkl', '9876543211', TO_DATE('2021-02-08',
'YYYY-MM-DD'), 'AD_VP', 17000.00);

INSERT INTO EMPLOYE (EMPLOYEE_ID, FIRST_NAME, LAST_NAME,
EMAIL, PHONE_NUMBER, JOIN_DATE, JOB_ID, SALARY)
VALUES (102, 'MNO', 'PQR', 'mnqr', '9876543212', TO_DATE('2016-05-14',
'YYYY-MM-DD'), 'AD_VP', 17000.00);

INSERT INTO EMPLOYE (EMPLOYEE_ID, FIRST_NAME, LAST_NAME,
EMAIL, PHONE_NUMBER, JOIN_DATE, JOB_ID, SALARY)
VALUES (103, 'STU', 'VWX', 'stwx', '9876543213', TO_DATE('2019-06-24',
'YYYY-MM-DD'), 'IT_PROG', 9000.00);

BEGIN
    UPDATE EMPLOYE
    SET SALARY = SALARY + 1000

```

```
WHERE EMPLOYEE_ID = 102;
```

```
COMMIT;
```

```
    DBMS_OUTPUT.PUT_LINE('Salary updated successfully for employee ID  
102.');
```

```
EXCEPTION
```

```
    WHEN OTHERS THEN
```

```
        DBMS_OUTPUT.PUT_LINE('An error occurred: ' || SQLERRM);
```

```
END;
```

```
/
```