Virtual Memory and Memory Management

David Marchant Based on slides by Troels Henriksen

2022-10-04

Inspired by slides by Randal E. Bryant and David R. O'Hallaron.

Simple memory system example

The Linux virtual memory system


Memory mapping

Dynamic allocation

Addressing

- 14-bit virtual addresses.
- 12-bit physical addresses.
- $64 = 2^6$ byte pages.

Virtual addresses



Physical addresses



TLB (4 sets, 4-way set associative)

0

Valid

0

05

06

07

PPN

00

Tag

03

27

33

02

Set

0

01

02

03

	1	03	2D	1	02	10	0	04	0B	0	0A	03	0
	2	02	3D	0	08	0F	0	06	05	0	03	2D	0
	3	07	12	0	03	0D	1	0A	34	1	02	03	0
Page table													
	VPN	PPN	Valid	VPN	PPN	I Valid	MAN F	PPN	Valid	I VPN	PPN	Valid	

0

0

09

0A

0B

Valid

Tag

00

17

09

01

PPN

0A

Valid

0

0D

0E

0F

0

Tag

07

2D

11

0D

PPN

02

0

Valid

PPN

0D

Tag


09

16

28

28

Cache (16 lines, direct mapped, physically addressed)



Contents

ldx	Tag	Valid	Block					
0	19	1	99	11	23	11		
1	15	0	01	02	11	99		
2	18	1	00	02	04	08		
3	36	0	11	23	11	99		
4	32	1	43	6D	8f	09		
5	0D	1	36	72	F0	1D		
6	31	0	72	1D	F0	36		
7	16	1	11	C2	DF	03		

ldx	Tag	Valid	Block					
8	24	1	ЗА	00	51	89		
9	2D	0	89	00	ЗА	51		
Α	2D	1	93	15	DA	3В		
В	08	0	89	51	15	ЗА		
С	12	0	3A	00	15	69		
D	16	1	04	96	34	15		
E	13	1	83	77	1в	D3		
F	14	0	14	20	13	37		

Translating virtual addresses and cache lookups

```
■ Virtual address: 0×03D4
                                 ■ Virtual address: 0×0020
             VPN
                                               VPN
             TLBL
                                               TLBI
            TLBT
                                              TLBT
          TLB Hit?
                                           TLB Hit?
        Page fault?
                                         Page fault?
              PPN
                                               PPN
Physical address:
                                 Physical address:
               CO
                                                CO
                CI
         Cache hit?
                                          Cache hit?
              Byte
                                               Byte
```

Simple memory system example

The Linux virtual memory system

Memory mapping

Dynamic allocation

Structure of a page table

VPN	PPN	Valid	Flags
0			
1			
2			
3			
4			

- Showing a flat page table for simplicity.
- Actually a multi-level page table.


- Page table is accessed by MMU (hardware) so its structure is fixed and kept simple.
- Either a page is *there* or *it's not*.
 - ► No "page is on disk" information.
 - ► No "demand-paging" information.
 - If we access a non-valid page: page fault!
- Page faults are handled by software (kernel code), meaning we have flexibility.
 - Page fault handler can update the page table based on kernel data and policy.
- But what does that actually look like?


VM areas

Linux organises a virtual memory space as a set of areas.


```
struct vm_area_struct {
    unsigned long vm_start;
    unsigned long vm_end;
    pgprot_t vm_page_prot;
    ...
};
```

- Each area describes the properties of a span of virtual memory.
 - May cover any number of pages.
 - Area has uniform protection/access bits (read, write, exe).
- **CPU/MMU has no idea what this is—**purely a software data structyre.
 - Easier to change kernel code than hardware.






 Segmentation fault-page does not exist.



- Segmentation fault-page does not exist.
- Normal page fault
 - Find available physical page in RAM.
 - Fetch page contents from disk.
 - Update page table.



- Segmentation fault-page does not exist.
- Normal page fault
 - Find available physical page in RAM.
 - Fetch page contents from disk.
 - Update page table.
- Segmentation fault permissions are wrong for type of access.

Simple memory system example

The Linux virtual memory system

Memory mapping

Dynamic allocation

Memory mapping

- VM areas are associated with disk objects
 - Known as memory mapping.
 - As a programming abstraction, lets us access a file as it were memory.
 - But also a strong organising principles.
- Area can be backed by (get its initial values from):
 - ▶ Regular file on disk (e.g. a program executable file).
 - ► Initial page contents from from section of file.
 - Anonymous file (i.e. nothing).
 - Initial page contents are zero.
 - Once written to, like any other page.

Memory mapping


- VM areas are associated with disk objects
 - Known as memory mapping.
 - As a programming abstraction, lets us access a file as it were memory.
 - But also a strong organising principles.
- Area can be backed by (get its initial values from):
 - ▶ Regular file on disk (e.g. a program executable file).
 - ► Initial page contents from from section of file.
 - Anonymous file (i.e. nothing).
 - Initial page contents are zero.
 - Once written to, like any other page.

Memory mapping from userspace

- Map len bytes starting at offset offset of the file descriptor fd, preferably at address start.
 - start may be 0 for "I don't care".
 - ▶ prot: PROT_READ, PROT_WRITE, PROT_EXEC, PROT_NONE.
 - ▶ flags: MAP_ANONYMOUS, MAP_PRIVATE, MAP_SHARED, many more...
- Returns a pointer to start of mapped area (may not be start).

```
int munmap(void *addr, size_t length);
```

- Unmaps pages starting at this address.
 - ▶ VM area is cloven in twain if we unmap pages in the middle.



mmap examples

See lecture code.

Simple memory system example

The Linux virtual memory system

Memory mapping

Dynamic allocation

User-space allocators


- mmap() is powerful but inflexible:
 - ► Smallest granularity of allocation is a page.
 - ls a system call, so fairly slow.

User-space allocators

- mmap () is powerful but inflexible:
 - Smallest granularity of allocation is a page.
 - Is a system call, so fairly slow.
- Instead programmers use dynamic memory allocators (e.g. malloc()) to aquire memory at runtime.
 - ▶ Run entirely in user space—not part of the kernel.
 - Acquires memory via mmap() and sbrk().

User-space allocators

- mmap() is powerful but inflexible:
 - Smallest granularity of allocation is a page.
 - ls a system call, so fairly slow.
- Instead programmers use dynamic memory allocators
 (e.g. malloc()) to aquire memory at runtime.
 - Run entirely in user space—not part of the kernel.
 - Acquires memory via mmap() and sbrk().
- Region of virtual memory managed by such an allocator is known as the heap.
 - No relation to the datastructure known as a heap.
 - May have multiple heaps; heap might not be contiguous.
 - When we say the heap, we mean whatever malloc() manages by default.



Dynamic memory allocation

- Allocator maintains heap as collection of blocks of varying size, each of which is either allocated or free.
- Types of allocators:

Explicit allocator: application manually allocates and frees space.

► E.g. malloc() in C.

Implicit allocator: application allocates but freeing is automatic.

- ► E.g. garbage collection in F#, SML, Haskell, Futhark, and Lisp.
- CompSys discusses simple explicit allocators.
 - Implicit allocators may be touched upon in PLD.

Allocator API

```
void *malloc(size_t size);
```

- Returns a pointer to a memory block of at least size bytes.
 - May round up to ensure address is always aligned.
- NULL on failure.

```
void free(void *ptr);
```

- Returns block of memory to heap.
- p must have been returned by malloc() (or one of the variants).

```
void *realloc(void *ptr, size_t size);
void *calloc(size_t nmemb, size_t size);
```

Less crucial, but sometimes useful.

System-level building blocks

malloc() uses the following functions to request memory from the kernel.

 Use MAP_ANONYMOUS to map fresh pages (will be demand-paged when first accessed).


```
void *sbrk(intptr_t increment);
```

- Modifies heap pointer (traditionally called the program break).
- Maps or unmaps new anonymous read-write pages as necessary.
- Similar to growing the stack by decrementing stack pointer.
 - ▶ But with a *system call*: there is no register for the heap pointer.

This memory is then split into blocks and returned to callers of malloc() as needed.


Notation used in the following slides


- We show how the memory managed by malloc is split into blocks.
- We show 4-byte words instead of single bytes.





Free word
Allocated word (will use different colours to indicate different allocated blocks)

p1 = malloc(4*4);









Constraints

Applications

- Can issue arbitrary sequence of malloc() and free() requess.
- free() must be to a malloc() ed block.

Allocators

- Can't control number or size of allocated blocks.
- Blocks must be contiguous in memory.
- Must respond immediately to malloc() requests.
 - i.e. cannot reorder or delay requests.
- Must allocate blocks from free memory.
 - i.e. blocks cannot overlap.
- Can manipulate and modify only free memory.
 - ▶ When a block has been returned from malloc(), that memory belongs to the application.
- Cannot move blocks once malloc() d.
 - ...can someone say why?

Performance Goal I: throughput

- We are given some sequence of malloc and free requests:
 - $ightharpoonup R_0, R_1, \ldots, R_{n-1}.$
- Goal: maximise throughput
- Throughput:
 - Number of completed requests per unit time.
 - ► E.g. suppose 5000 malloc()s and 5000 free()s in 10 seconds.
 - Throughput is 1000 ops/s.

Performance Goal II: peak memory utilisation

- We are given some sequence of malloc and free requests:
 - $ightharpoonup R_0, R_1, \ldots, R_{n-1}$.
- Goal: maximise memory utilisation

Aggregate payload P_k :

- \blacksquare malloc(p) results in a block with a payload of p bytes.
- P_k is the sum of currently allocated payloads after request R_k .

Current heap size H_k :

- Total amount of heap memory requested from the system.
- Grows only when using sbrk() or mmap().

Peak memory utilisation after k requests U_k :


- $U_k = \max_{i < k} \frac{P_i}{H_k}$
- Indicates how much memory we have reserved without using.

Fragmentation

- Poor memory utilisation is caused by
 - ▶ internal fragmentation, and
 - external fragmentation.

Internal fragmentation

Internal fragmentation occurs when the payload is smaller than the block size.




Causes

- Overhead of maintaining heap data structures.
- Padding for alignment purposes.
- Explicit policy decisions, e.g. returning a bigger block than necessary because it's faster.

Depends only on *previous* requests, so easy to measure.

External fragmentation

Occurs when there is enough aggregate heap memory, but no single free block is large enough.



p4 = malloc(6*4); No free block with room for six words.


Depends on future requests, so difficult to measure.

Key implementation questions

- How does free() know the size of the block given just a pointer?
- How do we keep track of free blocks?

Knowing how much to free (standard method)

- Keep the length of a block in the word preceding the block.
 - ▶ This word is often called the *header field* or *header*.
 - We can also use more words to store even more metadata if we wish.
- Requires an extra word for every allocated block.




Keeping track of free blocks

Method 1: Implicit list using length—links all blocks.



• Method 2: Explicit list among the free blocks, using pointers or offsets.



• Method 3: Segregated free list, different free lists for different sizes of blocks.

Conclusions

- mmap () syscall allows processes to map virtual memory.
 - ► Can map files to memory, or make anonymous mapping.
 - Can share memory between processes.
- malloc() is a userspace memory manager.
 - Not a system call itself.
 - ▶ Requests memory from kernel with mmap() and sbrk() and then parcels it out.
 - Internal fragmentation is when allocated blocks have wasted space.
 - External fragmentation is when free space is split into many small blocks.