



Gmail for Work

ook mor rof io al i
om Gmail from Goo l

Start free trial

5) JSP application implicit object

In JSP, application is an implicit object of type *ServletContext*.

The instance of *ServletContext* is created only once by the web container when application or project is deployed on the server.

This object can be used to get initialization parameter from configuration file (web.xml). It can also be used to get, set or remove attribute from the application scope.

This initialization parameter can be used by all jsp pages.

Example of application implicit object:

index.html

```
<form action="welcome">
<input type="text" name="uname">
<input type="submit" value="go"><br/>
</form>
```

web.xml file

```
<web-app>

<servlet>
<servlet-name>sonoojaiswal</servlet-name>
<jsp-file>/welcome.jsp</jsp-file>
</servlet>

<servlet-mapping>
<servlet-name>sonoojaiswal</servlet-name>
<url-pattern>/welcome</url-pattern>
</servlet-mapping>

<context-param>
<param-name>dname</param-name>
<param-value>sun.jdbc.odbc.JdbcOdbcDriver</param-value>
```

Lenovo Vibe K5 NOTE

THE KILLER EXPERIENCE YOU'VE ALWAYS WANTED

STARTING @ ₹11,999/-

BUY NOW

EXCLUSIVELY ON Flipkart

#KILLERNOTE5



```
</context-param>
```

```
</web-app>
```

welcome.jsp

```
<%  
  
out.print("Welcome "+request.getParameter("uname"));  
  
String driver=application.getInitParameter("dname");  
out.print("driver name is="+driver);  
  
%>
```

Output



Other topics in JSP implicit Objects

Example of out implicit Object

Example of request implicit object

Example of Response implicit Object

Example of config implicit object

Example of session implicit object

Example of pageContext implicit object

Example of page implicit object

Example of exception implicit object

[← prev](#)[next →](#)

Share  1