Content Menu

JSP Action Tags

There are many JSP action tags or elements. Each JSP action tag is used to perform some specific tasks.

The action tags are used to control the flow between pages and to use Java Bean. The Jsp action tags are given below.

JSP Action Tags	Description
jsp:forward	forwards the request and response to another resource.
jsp:include	includes another resource.
jsp:useBean	creates or locates bean object.
jsp:setProperty	sets the value of property in bean object.
jsp:getProperty	prints the value of property of the bean.
jsp:plugin	embeds another components such as applet.
jsp:param	sets the parameter value. It is used in forward and include mostly.
jsp:fallback	can be used to print the message if plugin is working. It is used in jsp:plugin.

The jsp:useBean, jsp:setProperty and jsp:getProperty tags are used for bean development. So we will see these tags in bean development.

jsp:forward action tag

The jsp:forward action tag is used to forward the request to another resource it may be jsp, html or another resource.

Syntax of jsp:forward action tag without parameter

```
<jsp:forward page="relativeURL | <%= expression %>" />
```

Syntax of jsp:forward action tag with parameter

```
<jsp:forward page="relativeURL | <%= expression %>">
<jsp:param name="parametername" value="parametervalue | <%=expression%>" />
</jsp:forward>
```

Example of jsp:forward action tag without parameter

In this example, we are simply forwarding the request to the printdate.jsp file.

index.jsp

```
<html>
<body>
<h2>this is index page</h2>
<jsp:forward page="printdate.jsp" />
</body>
</html>
```

printdate.jsp

```
<html>
<body>
<% out.print("Today is:"+java.util.Calendar.getInstance().getTime()); %>
</body>
</html>
```

download this example

Example of jsp:forward action tag with parameter

In this example, we are forwarding the request to the printdate.jsp file with parameter and printdate.jsp file prints the parameter value with date and time.

index.jsp

```
<html>
<body>
<h2>this is index page</h2>
<jsp:forward page="printdate.jsp" >
<jsp:param name="name" value="javatpoint.com" />
</jsp:forward>
</body>
</html>
```

printdate.jsp

```
<html>
<body>

<% out.print("Today is:"+java.util.Calendar.getInstance().getTime()); %>
<%= request.getParameter("name") %>
```

download this example	
< <pre><<pre><<pre><<pre></pre></pre></pre></pre>	next>>