

Cat.6A Patch Panel



Features

- Specified to 500MHz
- Suitable for 10 GBASE-T, 10 Gigabit Ethernet Applications
- Meets or exceeds Cat.6Arequirements when full product system is used
- 50-micron gold plated RJ-45 male-to -male
- PVC, Low Smoke Zero Halogen & Outer Sheath are available
- Multiple Selection of Lengths and Colors
- 24 AWG stranded bare copper conductor for U-UTP; 26 AWG stranded bare copper conductor for F-FTP
- Backward compatible with Cat.5e and Cat.6

Ordering Information

Part No.	Description
IKC-CMS-C6AU-BK-0.5M	Patch cord 0.5m- Cat 6A - UTP - 500MHz - Black
IKC-CMS-C6AU-BK-1M	Patch cord 1m - Cat 6A - UTP - 500MHz - Black
IKC-CMS-C6AU-BK-2M	Patch cord 2m - Cat 6A - UTP - 500MHz - Black
IKC-CMS-C6AU-BK-3M	Patch cord 3m- Cat 6A - UTP - 500MHz - Black
IKC-CMS-C6AU-BK-5M	Patch cord 5m- Cat 6A - UTP - 500MHz - Black
IKC-CMS-C6AU-BK-10M	Patch cord 10m- Cat 6A - UTP - 500MHz - Black

