TrustLens AI security platform report

"Create a professional PDF report for TrustLens, an AI-powered physical-digital interface security platform. Explain the problem, solution, workflow, expected outcomes, technologies (Kotlin, Android Studio, ML Kit, NFC APIs, Python, FastAPI, PostgreSQL, OpenCV, VirusTotal API), and applications in QR payments, parking, EV charging, and smart devices. Include architecture, benefits, limitations, and future scope. Use clear diagrams and realistic claims." *Generated by LeapSpace*

TrustLens at a Glance

Key Findings Table

Topic	Key finding	Relevant domains	Citations
Core problem	Physical-digital interfaces are vulnerable because users often cannot verify whether a QR code, NFC interaction, or nearby device is genuine, enabling replacement, phishing, relay, replay, and impersonation attacks.	Payments, parking, EV charging, smart devices	[1] [2] [3] [4] [5] [6]
Best-supported defense pattern	Layered verification is better supported than single-signal trust: server-side validation, uniqueness checks, proximity/authentication checks, and visual/contextual inspection should be combined.	All TrustLens use cases	[7] [8] [9] [10] [11] [12] [13]
Role of AI/vision	Camera and AI methods are useful as front-end screening layers, but the strongest practical anti-fraud evidence comes from backend validation and one-time or database-backed checks.	QR payments, parking, EV charging	[7] [8] [11] [14] [15] [16]

Topic	Key finding	Relevant domains	Citations
Mobile feasibility	An Android client built with Kotlin and Android Studio is feasible and maintainable; ML Kit supports real-time on-device detection and privacy-preserving processing, but end-to-end security benchmarks for this exact stack are missing.	Mobile scanning client	[17] [18] [19] [20] [21] [22]
Backend feasibility	FastAPI supports high-concurrency asynchronous services; PostgreSQL supports durable storage and strong transaction semantics; caching can materially reduce repeat-query latency.	Verification backend	[23] [24] [25] [26] [27]
Threat intelligence	VirusTotal-style enrichment can improve detection of unknown malicious events, but verdict thresholds should not be treated as universally reliable across risk classes.	Reputation and enrichment layer	[28] [29]
Sector fit	TrustLens is relevant to QR payments, parking, EV charging, and smart-device onboarding, but broad quantitative impact claims are not supported without pilots.	All four target sectors	[30] [31] [32] [33] [34]

Direct Answer

TrustLens can be credibly presented as a **layered security platform for physical-digital trust boundaries**, not as a standalone AI detector. The most defensible architecture is: **Android capture and local screening (Kotlin, Android Studio, ML Kit, OpenCV, NFC APIs)**, followed by **backend verification and audit logging (Python, FastAPI, PostgreSQL)**, with optional **reputation enrichment (VirusTotal API)** before returning a trust verdict to the app [18] [20] [23] [26] [28] [35].

The problem TrustLens addresses is well supported: QR systems are vulnerable to code replacement and phishing, NFC remains exposed to relay and replay despite short range, and device-authentication signals can become unreliable under interference or mobility [1] [2] [5] [6] [9] [36]. The evidence most strongly supports claims that TrustLens can **improve suspicious-artifact detection, strengthen server-side validation, improve auditability, and reduce reliance on manual trust decisions** [7] [8] [28] [37]. It does **not** support hard claims about universal fraud-reduction percentages, battery impact, or guaranteed latency for the exact proposed stack without field validation [19] [21] [38] [39].

Confidence level: High - the architectural direction and threat rationale are consistently supported across the supplied evidence, though exact deployment metrics are not.

Study Scope

This report synthesizes evidence spanning physical-digital threat models, Android client architecture, mobile on-device vision, NFC security, backend verification services, computer-vision-assisted validation, and sector-specific deployment studies across QR payments, parking, EV charging, and smart-device onboarding [2] [11] [18] [20] [23] [32] [35]. The source set includes reviews, empirical studies, protocol analyses, system prototypes, and deployment-oriented architecture papers from roughly 2018-2025 [23] [30] [40] [41].

Assumptions & Limitations

- TrustLens is treated as a **risk-reduction and verification layer**, not a perfect prevention system [30] [31] [32] [34].
- The strongest evidence supports **hybrid validation**, not AI-only or camera-only fraud detection [7] [8] [11].
- The evidence does **not** provide end-to-end benchmarks for the exact stack combining Kotlin, ML Kit, NFC APIs, OpenCV, FastAPI, PostgreSQL, and VirusTotal API [22] [38] [42].
- Sector studies show **relevance**, but often lack direct measurements for fraud reduction, queue reduction, or onboarding success in field conditions [31] [34] [39] [43].

Suggested Further Research

- Run end-to-end pilots comparing **visual-only, server-only, and hybrid TrustLens workflows** at physical scan points [15] [40] [42].
- Benchmark **ML Kit + OpenCV** on mid-range Android devices under glare, blur, occlusion, and sticker-tampering conditions [19] [44] [45].
- Evaluate secure **NFC integration patterns** in modern Kotlin/MVVM Android applications [18] [22].
- Study **FastAPI + PostgreSQL** verification pipelines with audit logs, rate limiting, caching, and transactional consistency under production-like loads [24] [26] [38].
- Validate **class-specific risk thresholds** for reputation and trust scoring rather than single global cutoffs [29].

TrustLens: Full Report

Foundational Context

TrustLens sits at a **physical-digital trust boundary**: a person scans a code, taps a tag, or onboards a device, and a physical cue triggers a digital action such as payment, access, charging, or registration. These boundaries are high risk because the user often sees only the physical artifact but must trust an unseen digital endpoint [1] [2]. In QR workflows, the attack is often **substitution**: a malicious code replaces a legitimate one, redirecting payment or credentials [1] [2] [15]. In NFC workflows, the attack is often **relay or replay**: short range does not guarantee real proximity, and attackers can forward or reuse interactions [3] [5] [9]. In device onboarding, the challenge is **identity uncertainty under real-world noise**, where channel or RF signals can help but are unstable under interference and mobility [6] [36].

Taken together, these findings suggest that TrustLens should be framed as a **trust orchestration system**: it gathers multiple weak-to-moderate signals and converts them into a better-informed risk decision, rather than claiming any single perfect proof of authenticity [7] [10] [11].

Confidence level: High - this framing is directly aligned with the strongest cross-source pattern.

1. Introduction and Security Problem

1.1 Why physical-digital interfaces are vulnerable

QR systems have a basic security weakness: users are expected to scan codes without being able to easily distinguish genuine from malicious replacements [1]. The supplied studies describe incidents and risks across parking ticket machines, EV chargers, train stations, parking meters, receipts, invoices, and other public surfaces [2] [7] [8] [15] [40]. The clearest problem is that **visual appearance alone is insufficient**; a printed code can look legitimate while pointing to a malicious endpoint [1] [2].

NFC introduces a different but related trust problem. Surveys and empirical studies repeatedly flag relay, replay, eavesdropping, and unauthorized token retrieval as dominant threats in contactless payments and access-control scenarios [3] [4] [5] [9] [46]. This matters for TrustLens because “tap-to-trust” is not automatically safe: a proximate-looking interaction can still be mediated by an attacker [5].

Device-authentication methods based on RF fingerprints, hardware imperfections, or channel reciprocity are promising, but their reliability drops under noise, fading, multipath, interference, and motion [6] [36] [47] [48]. For TrustLens, this means context-sensitive signals should be used as **supporting evidence**, not sole identity proof [6] [36].

1.2 Threat model and trust assumptions

A practical TrustLens threat model includes:

- **Artifact substitution attackers** who replace or overlay QR codes on posters, chargers, tickets, or kiosks [2] [8].
- **Relay/replay attackers** who proxy NFC transactions or reuse captured identifiers [5] [9].
- **Backend or protocol abuse** where weak validation allows unauthorized charging, billing, or credential reuse [16] [33].
- **Environmental ambiguity** where blur, glare, distortion, occlusion, or RF instability degrades decision quality [36] [41] [44].

TrustLens therefore must assume that **the phone camera, NFC readout, and environmental signals are useful but not sufficient**, and that final trust requires backend validation and policy logic [7] [8] [29].

1.3 Scope of the solution

TrustLens should be presented as a **verification and risk-reduction layer** across payments, parking, EV charging, and smart devices, rather than a universal anti-fraud guarantee [30] [31] [32] [34]. Its value proposition is strongest where organizations need to **screen suspicious physical-digital interactions, validate backend legitimacy, and preserve audit trails** [16] [26].

Confidence level: High - the threat model and scope are well supported, and the limitations are explicit.

2. TrustLens Architecture and Workflow

2.1 High-level architecture

A defensible TrustLens architecture has five layers:

1. **Android client** for QR capture, NFC reads, local preprocessing, and UI messaging [18] [20] [35].
2. **On-device screening** using ML Kit and OpenCV for barcode/text/face or scene-related checks, preprocessing, and basic anomaly cues [19] [20] [45].
3. **Backend verification API** using Python and FastAPI for async evidence intake, policy execution, and external queries [23].
4. **Persistent state and audit storage** using PostgreSQL for event logging, uniqueness checks, and transactional consistency [26] [49] [50].
5. **Threat intelligence/reputation layer** using VirusTotal-style enrichment where applicable [28].

This architecture matches the strongest evidence pattern: combine local capture and preliminary screening with server-side verification and layered decision logic [7] [8] [11].

2.2 Mobile verification workflow

A realistic mobile workflow is:

- Capture QR image or NFC event on Android [20] [35].
- Run local preprocessing such as grayscale conversion, thresholding, blur handling, and QR extraction where useful [45].
- Use ML Kit for fast on-device detection and structured extraction, with privacy advantages because data need not be sent to cloud services for core detection tasks [19] [20].
- Package structured evidence: decoded content, timestamp, device metadata, scan context, optional image features, and local confidence [21] [29].
- Send to backend for deeper validation and receive a verdict such as allow, caution, or block [23] [28].

The evidence supports **on-device feasibility**, but not precise battery or latency guarantees for this exact security use case [19] [21].

2.3 Backend verification and decision pipeline

The backend pipeline should perform:

- **Token/content validation** against expected formats and policy rules [7] [16].
- **Uniqueness/first-scan checks** to detect copied QR artifacts or suspicious reuse [8].
- **External enrichment** through reputation or malware-intelligence lookups where relevant [28].
- **Risk scoring** that accounts for severity and context rather than one global threshold [29].
- **Event storage** in PostgreSQL for auditability, investigation, and dispute handling [16] [26].

A practical inference from the evidence is a **synchronous local verdict plus asynchronous backend enrichment** model: the app provides an immediate caution signal, while the backend completes deeper checks and stores a durable audit trail [23] [25] [28].
Inferred: this specific orchestration pattern is not directly benchmarked end-to-end in the supplied studies, so confidence is lower.

2.4 Error handling and confidence policy

The literature strongly suggests TrustLens should expose **confidence-aware behavior**. Visual systems fail under blur, distortion, low contrast, and curvature; RF/NFC assumptions weaken under relay or interference; risk scores vary by severity class [5] [29] [41] [44]. Therefore:

- ambiguous scans should return **“needs verification”** rather than forced approval;
- stale or unavailable reputation data should lower confidence, not be silently ignored;
- class-specific thresholds should be used where risk is asymmetric [29].

Confidence level: High - the case for layered, confidence-aware workflow is strong; exact implementation details remain product choices.

3. Implementation Stack and Technical Rationale

3.1 Android client: Kotlin and Android Studio

Kotlin is associated with maintainability, code quality, and safer, more concise Android development [17] [51] [52] [53]. An MVVM-style architecture with Hilt, LiveData, Room, Retrofit, and Coroutines is directly supported by one architecture paper as a reusable layered model [18]. This makes Kotlin a strong fit for TrustLens because the app must coordinate UI state, local evidence capture, network calls, and offline buffering in a structured way [18].

Security-aware development is also important: static-analysis tools and vetting systems catch data leaks, ICC misuse, SSL/TLS misuse, and related flaws before release [54] [55] [56] [57]. For TrustLens, that supports a secure mobile delivery pipeline rather than only runtime defenses [58] [59].

3.2 ML Kit and OpenCV on-device

ML Kit supports on-device face, barcode, and text detection in real time and keeps core processing on device, which supports privacy-preserving workflows [19] [20]. OpenCV is widely used as a practical preprocessing and computer-vision base layer, including grayscale conversion, adaptive thresholding, Gaussian blur, and other transformations useful before decoding [45].

The strongest report position is that ML Kit and OpenCV provide **fast edge screening and evidence extraction**, not authoritative fraud proof [11] [44]. This is especially important because heavy DL approaches can be computationally expensive for real-time deployment, and uncontrolled image conditions remain a major failure mode [44] [60].

3.3 NFC APIs and proximity verification

The source set supports NFC for contactless interactions, peer-to-peer exchange, and tag-triggered services, but it does not provide a complete modern Android Kotlin reference architecture for secure NFC integration [22] [35] [61]. What the evidence does show is that NFC trust should not be equated with proximity alone because relay attacks can break that assumption [62] [63].

For TrustLens, NFC should be positioned as a **useful input channel** enhanced by mutual authentication, challenge-response, or proximity-aware checks where available [5] [9] [10].

3.4 Python, FastAPI, and PostgreSQL

FastAPI is supported as a high-performance backend replacement that improves concurrent response handling and supports asynchronous operations [23]. PostgreSQL is a strong fit for durable storage and transaction safety, including SERIALIZABLE SSI behavior that detects serialization anomalies [26]. The combined evidence supports a backend that is **auditable, concurrent, and maintainable**, though not directly benchmarked as a complete TrustLens-style verification stack [38] [49].

Caching is an important practical addition: retrieved systems report substantial latency reduction on repeated queries, including under-10-ms cache-hit paths [24] [25] [27]. That supports using caching for repeated artifact or reputation checks.

3.5 VirusTotal API and reputation enrichment

VirusTotal-style enrichment can improve detection of previously unknown malicious behavior when combined with heuristics and supervised models [28]. But trust scores are not uniformly reliable across severity classes, so TrustLens should not reduce all decisions to one threshold [29]. In practice, VirusTotal API is best framed as an **optional enrichment signal**, not as the final source of truth [28] [29].

Confidence level: Medium-High - stack feasibility is well supported, but the exact end-to-end combination lacks direct peer-reviewed benchmarking.

4. Applications Across Target Domains

4.1 QR payments

QR payment adoption is strongly influenced by security, trust, convenience, and ease of use [64] [65] [66]. Since users cannot easily distinguish genuine from replaced payment codes, TrustLens is relevant as a screening and validation layer [1] [2]. The most credible value is **verification of scanned payment artifacts and backend consistency checks**, not a claim of proven fraud elimination [7] [8].

4.2 Parking access and ticket validation

Parking studies support mobile workflows, reservation checking, and entry-point verification, but they rarely provide hard fraud-reduction or queue metrics [31] [39]. TrustLens can therefore be positioned as improving **entry auditability, reservation validation, and anti-tamper screening** at kiosks or gates [8] [31]. Strong claims about queue-time reduction would be premature [39].

4.3 EV charging authentication and billing

EV charging is one of the strongest application areas because the evidence includes both prototype feasibility and documented protocol failures. QR plus blockchain/DLT prototypes reported local validation, simulated MITM resistance, average QR scanning around 3.4 s, and an 8.13 m transaction range in one prototype [32]. Separately, a real-world MITM study found unauthorized charging and billing due to weak validation and insufficient encryption, calling for stronger authentication and TLS enforcement [33]. That makes TrustLens highly defensible as a **station verification, authorization, and audit layer** [16] [32] [33].

4.4 Smart devices and onboarding

Smart-device onboarding faces scale, resource constraints, firmware trust issues, and interoperability problems [34] [67] [68] [69]. Although the source set does not explicitly document QR/NFC onboarding patterns in depth, it supports the need for lightweight trust bootstrapping, attestation, and secure commissioning [70] [71] [72]. TrustLens can plausibly support **device enrollment checks, firmware trust confirmation, and short-range identity verification**, but claims should remain architectural and exploratory [34] [69].

Confidence level: Medium-High - domain relevance is strong, with EV charging best evidenced; parking and smart-device outcome claims need pilot data.

5. Expected Outcomes, Limitations, and Future Scope

5.1 Expected outcomes

The best-supported expected outcomes are:

- **Faster structured trust checks** at scan or tap time through automated local screening and backend lookup [19] [23].
- **Better fraud resistance** than single-step scanning by combining uniqueness checks, backend validation, and contextual reasoning [7] [8] [11].
- **Improved auditability** through logged events, timestamps, device metadata, and verification outcomes stored in PostgreSQL [16] [26].
- **Reduced manual verification burden** in repeatable workflows such as entry, payment, or activation [31] [37].

These are realistic because they are architectural benefits, not unsupported universal performance claims [13] [16].

5.2 Limitations and risk factors

TrustLens also has clear limits:

- vision quality drops under blur, low contrast, distortion, curvature, occlusion, and physical tampering [41] [44] [73];
- NFC/proximity assumptions can fail under relay conditions [5] [63];
- RF/device-authentication signals are unstable in noisy or mobile environments [6] [36];
- reputation and triage thresholds can mislead if treated as globally reliable [29];
- deployment complexity spans mobile security, backend consistency, caching, rate control, and policy maintenance [12] [13] [38].

5.3 Future scope

Future TrustLens work is most credible in five directions:

1. **Stronger proximity proofs** and challenge-response mechanisms for NFC and short-range interactions [5] [9].
2. **Adaptive risk scoring** with class-aware thresholds and explicit false-positive/false-negative reporting [29].
3. **Improved mobile edge robustness** under glare, blur, curved surfaces, and adversarial stickers [41] [44].
4. **Cross-sector pilots** in parking, EV charging, payments, and smart-device commissioning [31] [32] [34].
5. **Secure-by-design development pipelines** integrating mobile static analysis, backend testing, and CI/CD security checks [12] [13] [54].

Confidence level: High - the future roadmap follows directly from the evidence gaps and recurring methodological lessons.

Conclusion

TrustLens is best justified as a **hybrid verification platform for insecure physical-digital touchpoints**. The strongest evidence does not support "AI solves fraud" messaging. Instead, it supports a system that uses AI and computer vision for local triage, NFC/QR handling for interaction capture, FastAPI and PostgreSQL for server-side verification and logging, and VirusTotal-style enrichment for added context [20] [23] [26] [28]. Across QR payments, parking, EV charging, and smart devices, the most defensible benefits are **better verification discipline, stronger auditability, and reduced dependence on unaided user judgment** [7] [8] [16]. The main caution is that field-scale impact metrics still require pilots and adversarial testing under realistic conditions [39] [74].

Overall confidence level: High - the problem, architecture, and realistic claim set are well grounded in the supplied evidence; quantitative deployment outcomes remain medium-to-low confidence pending direct validation.

References

1. Razaque, A., Alexandrov, V., Almi'ani, M., (...), Dmour, A. (2021) Comparative Analysis of Digital Signature and Elliptic Curve Digital Signature Algorithms for the Validation of QR Code Vulnerabilities. *2021 8th International Conference on Software Defined Systems, SDS 2021*. https://doi.org/10.1109/SDS54264.2021.9732150
2. https://www.sciencedirect.com/science/article/pii/S2661890725003333

3. Mukherjee, A. (2025) Security Architecture and Vulnerabilities of NFC Applications for Mobile Devices. *Proceedings - 2025 8th Asia Conference on Cognitive Engineering and Intelligent Interaction, CEII 2025*. https://doi.org/10.1109/CEII67787.2025.00044
4. Alrawais, A. (2020) Security Issues in Near Field Communications (NFC). *International Journal of Advanced Computer Science and Applications*. https://doi.org/10.14569/IJACSA.2020.0111176
5. Debant, A., Delaune, S., Wiedling, C. (2022) So Near and Yet So Far-Symbolic Verification of Distance-Bounding Protocols. *ACM Transactions on Privacy and Security*. https://doi.org/10.1145/3501402
6. Nain, A.K., Pachamuthu, R. (2021) A cyclic prefix based secure side-channel (CP-SSC) over OFDM for LTE D2D sidelink communication. *Physical Communication*. https://doi.org/10.1016/j.phycom.2021.101478
7. https://www.sciencedirect.com/science/article/pii/S157377212402489X
8. Li, P., Yang, J., Jiménez-Carvelo, A.M., Erasmus, S.W. (2024) Applications of food packaging quick response codes in information transmission toward food supply chain integrity. *Trends in Food Science and Technology*. https://doi.org/10.1016/j.tifs.2024.104384
9. Thorpe, C., Tobin, J., Murphy, L. (2020) An ISO/IEC 7816-4 Application Layer Approach to Mitigate Relay Attacks on near Field Communication. *IEEE Access*. https://doi.org/10.1109/ACCESS.2020.3031979
10. Njebiu, V., Kimwele, M., Rimiru, R. (2021) Secure Contactless Mobile Payment System. *Proceedings - 2021 IEEE Latin-American Conference on Communications, LATINCOM 2021*. https://doi.org/10.1109/LATINCOM53176.2021.9647831
11. Hosur, R., Noola, D.A., Murthy, G.P. (2026) “A multi-layer artificial intelligence framework for real-time validation of quick response codes under latency constraints”. *Engineering Applications of Artificial Intelligence*. https://doi.org/10.1016/j.engappai.2026.116146
12. Partyka, O., Partyka, A., Imoize, A.L. (2026) AI for Web Application Security. *Handbook of Cybersecurity Challenges and Solutions for Emerging Technologies*. https://doi.org/10.1201/9781003640790-14
13. Mahimalur, R.K., Kolla, V.G., Tank, C.D., Meesala, S.T. (2026) AI - Integrated DevSecOps for Scalable, Secure, and Modern Cloud Architectures. *Proceedings of 4th International Conference on Electronics and Renewable Systems, ICEARS 2026*. https://doi.org/10.1109/ICEARS67481.2026.11416586
14. https://www.sciencedirect.com/science/article/pii/S1863171125002067
15. Beloualid, Siham, Morino, Ilham, El Allali, Abdelhadi, (...), Bajit, Abderrahim (2023) Application of computational intelligence in visual optimization tools to improve the performance of medical MIoT platforms. *Computational Intelligence for Medical Internet of Things (MIoT) Applications*. https://doi.org/10.1016/B978-0-323-99421-7.00004-0

16. Ferreira, J.C., Ferreira da Silva, C.F., Martins, J.P. (2021) Roaming service for electric vehicle charging using blockchain-based digital identity. *Energies*. https://doi.org/10.3390/en14061686

17. Coppola, R., Fulcini, T., Torchiano, M. (2024) Poster: Kotlin Assimilating the Android Ecosystem - An Appraisal of Diffusion and Impact on Maintainability. *Proceedings - International Conference on Software Engineering*. https://doi.org/10.1145/3639478.3643071

18. Kaczmarek, P., Piotrowski, Z. (2024) The Architecture of the Mobile Application for Android with the Use of the MVVM Pattern and the HILT, Livedata, Room, Retrofit and Kotlin Coroutines Libraries. *Communications in Computer and Information Science*. https://doi.org/10.1007/978-3-031-62843-6_28

19. Abate, A.F., de Maio, L., Distasi, R., Narducci, F. (2021) Remote 3D face reconstruction by means of autonomous unmanned aerial vehicles. *Pattern Recognition Letters*. https://doi.org/10.1016/j.patrec.2021.04.006

20. https://www.sciencedirect.com/science/article/pii/S2292551122000085

21. Gwak, Sojung, Park, Kyudong (2023) Designing Effective Visual Feedback for Facial Rehabilitation Exercises: Investigating the Role of Shape, Transparency, and Age on User Experience. *Healthcare*. https://doi.org/10.3390/healthcare11131835

22. Anwar, W., Lindskog, D., Zavarsky, P., Ruhl, R. (2013) Redesigning secure element access control for NFC enabled android smartphones using mobile trusted computing. *International Conference on Information Society, i-Society 2013*. https://www.scopus.com/pages/publications/84890831480

23. Sistla, H.S., Shiragapur, B., Vinay, R., (...), Karan, A. (2025) LangChain Orchestrated Ecosystem for Token-Aware LLM Routing, Hybrid Semantic Retrieval and Explainable Conversational Automation with Dynamic Data Handling. *2025 IEEE 1st International Conference on Recent Trends in Computing and Smart Mobility, RCSM 2025*. https://doi.org/10.1109/RCSM67767.2025.11507246

24. Baez, Marcelo, Jimenez, Ruben, Cernuzzi, Luca, Paccanaro, Alberto (2025) ClusterONE Web: a tool for discovering and analyzing overlapping protein complexes. *Nucleic Acids Research*. https://doi.org/10.1093/nar/gkaf368

25. https://www.sciencedirect.com/science/article/pii/S1573749726003024

26. Alflahi, A.A.E., Mohammed, M.A.Y., Alsammani, A. (2026) A scalable transaction management framework for consistent document-oriented NoSQL databases. *Information Systems*. https://doi.org/10.1016/j.is.2026.102719

27. López, Christian, Cárdenas, Roberto, Aguilera-Mendoza, Longendri, (...), Marrero-Ponce, Yovani (2024) StarPepWeb: an integrative, graph-based resource for bioactive peptides. *Bioinformatics Advances*. https://doi.org/10.1093/bioadv/vbaf261

28. Aharoni, E., Peleg, R., Regev, S., Salman, T. (2016) Identifying malicious activities from system execution traces. *IBM Journal of Research and Development*. https://doi.org/10.1147/JRD.2016.2559358

29. Mahmud, A., Rawajfih, Y., Arnold, R., Shahriar, H. (2026) Trust Score Reliability in LLM Security Pipelines: A Severity-Stratified Calibration Study with KEV Validation. *Proceedings - 2026 IEEE 50th Annual Computers, Software, and Applications Conference, COMPSAC 2026*. https://doi.org/10.1109/COMPSAC69091.2026.00479

30. Pratama, M.S., Amolika, N.Y., Firliandini, F., Mailangkay, A. (2025) QR or NFC? Understanding Indonesian Mobile Payment Adoption Through UTAUT. *2025 1st International Conference on Emerging Trends in Information Systems and Informatics, ICETISI 2025*. https://doi.org/10.1109/ICETISI67983.2025.11405458

31. Soudeep, S., Lailun Nahar Aurthy, M., Jim, J.R., (...), Kabir, M.M. (2024) Enhancing road traffic flow in sustainable cities through transformer models: Advancements and challenges. *Sustainable Cities and Society*. https://doi.org/10.1016/j.scs.2024.105882

32. Deshmukh, N., Khairnar, V., Vora, D., (...), Le Mouël, F.L. (2025) EVMCSDLT: Electric vehicle mobile charging system using distributed ledger technology. *MethodsX*. https://doi.org/10.1016/j.mex.2025.103553

33. Chen, K.-Y., Lin, X.-X., Chen, C.-Y., (...), Cha, S.-C. (2025) A Case Study on Real-World MITM Attacks Against ISO 15118-2 and DIN 70121. *GCCE 2025 - 2025 IEEE 14th Global Conference on Consumer Electronics*. https://doi.org/10.1109/GCCE65946.2025.11274985

34. Pramod, P. (2025) A taxonomy of key management schemes of SCADA systems. *Computers and Electrical Engineering*. https://doi.org/10.1016/j.compeleceng.2025.110366

35. Lotito, A., Mazzocchi, D. (2013) OPEN-SNEP project: Enabling P2P over NFC using NPP and SNEP. *2013 5th International Workshop on Near Field Communication, NFC 2013*. https://doi.org/10.1109/NFC.2013.6482447

36. Luo, M., Liu, X., Di, X., Qi, H. (2025) Radio Frequency Fingerprint recognition method based on feature enhancement and Selective Channel–Spatial Kernel. *Computer Networks*. https://doi.org/10.1016/j.comnet.2025.111574

37. Wijesundara, W.M.A.B., Lee, J.-S., Aloupogianni, E., (...), Obi, T. (2025) DIDAuth-IoTFW: Decentralized firmware authentication for smart home IoT devices using verifiable credentials. *Internet of Things (The Netherlands)*. https://doi.org/10.1016/j.iot.2025.101788

38. Wijesundara, W.M.A.B., Lee, J.-S., Aloupogianni, E., (...), Obi, T. (2025) DIDAuth-IoTFW: Decentralized firmware authentication for smart home IoT devices using verifiable credentials. *Internet of Things (The Netherlands)*. https://doi.org/10.1016/j.iot.2025.101788

39. Siuhi, S., Mwakalonge, J. (2016) Opportunities and challenges of smart mobile applications in transportation. *Journal of Traffic and Transportation Engineering (English Edition)*. https://doi.org/10.1016/j.jtte.2016.11.001

40. Clark, Tim (2025) Quishing: QR or QRN'T?. *Itnow*. https://doi.org/10.1093/itnow/bwaf053

41. https://www.sciencedirect.com/science/article/pii/S186317112500295X

42. Rajawat, D., Lohani, B.P., Rana, A., (...), Gupta, S. (2023) Object Detection in Images and Videos Using OpenCV: A Comparative Study of Deep Learning and Traditional Computer Vision Techniques. *2023 10th IEEE Uttar Pradesh Section International Conference on Electrical, Electronics and Computer Engineering, UPCON 2023*. https://doi.org/10.1109/UPCON59197.2023.10434536

43. Jiddah, S.A., Abdul Hanan, S.A., Anuar, N.K. (2025) Assessing the adoption of barcode payment systems in Nigeria's transportation sector: An empirical study. *Sustainable Futures*. https://doi.org/10.1016/j.sftr.2025.100659

44. Liu, Yi, Song, Yang, Gu, Guiqiang, (...), Jiang, Qiuping (2024) A Data Matrix Code Recognition Method Based on L-Shaped Dashed Edge Localization Using Central Prior. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s24134042

45. Belbachir, Assia, Ortiz, Antonio M., Hauge, Erik T., (...), Felline, Giorgio (2025) Outdoor Warehouse Management: UAS-Driven Precision Tracking of Stacked Steel Bars. *SN Computer Science*. https://doi.org/10.1007/s42979-025-04206-8

46. Sangweni, S., Lebea, K. (2025) Exploring Vulnerabilities in Near Field Communication (NFC) Devices: A Comprehensive Investigation. *Communications in Computer and Information Science*. https://doi.org/10.1007/978-981-96-3811-6_6

47. Li, Xufei, Zeng, Shuiguang, Liu, Yangyang (2023) Inter-Frame-Relationship Protected Signal: A New Design for Radio Frequency Fingerprint Authentication. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s23156948

48. Ma, Zhao, Fang, Shengliang, Fan, Youchen (2025) Open-Set Radio Frequency Fingerprint Identification Method Based on Multi-Task Prototype Learning. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s25175415

49. Agboka, K.M., Diallo, S., Ahmed, K., (...), Hassaballa, I.B. (2026) A regional atlas of phlebotomine sand fly vectors of Leishmaniasis in Eastern Africa (1845–2025): Harmonized historical records and an interactive surveillance dashboard. *Acta Tropica*. https://doi.org/10.1016/j.actatropica.2026.108324

50. Prem Sankar, P.S., Anita Christaline, A.C. (2026) AI-Driven Framework for vector-borne disease surveillance and early warning. *Results in Control and Optimization*. https://doi.org/10.1016/j.rico.2026.100812

51. Góis Mateus, B., Martinez, M. (2019) An empirical study on quality of Android applications written in Kotlin language. *Empirical Software Engineering*. https://doi.org/10.1007/s10664-019-09727-4

52. Martinez, M., Góis Mateus, B. (2022) Why Did Developers Migrate Android Applications From Java to Kotlin?. *IEEE Transactions on Software Engineering*. https://doi.org/10.1109/TSE.2021.3120367

53. Andrä, L.-M., Taufner, B., Schefer-Wenzl, S., Miladinović, I. (2020) Maintainability Metrics for Android Applications in Kotlin: An Evaluation of Tools. *ACM International Conference Proceeding Series*. https://doi.org/10.1145/3393822.3432334

54. Arzt, S., Rasthofer, S., Fritz, C., (...), McDaniel, P. (2014) FlowDroid: Precise context, flow, field, object-sensitive and lifecycle-aware taint analysis for android apps. *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*. https://doi.org/10.1145/2594291.2594299

55. Lu, L., Li, Z., Wu, Z., (...), Jiang, G. (2012) CHEX: Statically vetting Android apps for component hijacking vulnerabilities. *Proceedings of the ACM Conference on Computer and Communications Security*. https://doi.org/10.1145/2382196.2382223

56. Fahl, S., Harbach, M., Muders, T., (...), Freisleben, B. (2012) Why Eve and Mallory love Android: An analysis of Android SSL (in)security. *Proceedings of the ACM Conference on Computer and Communications Security*. https://doi.org/10.1145/2382196.2382205

57. Gordon, M.I., Kim, D., Perkins, J., (...), Rinard, M. (2015) Information-Flow Analysis of Android Applications in DroidSafe. *22nd Annual Network and Distributed System Security Symposium, NDSS 2015*. https://doi.org/10.14722/ndss.2015.23089

58. Chin, E., Felt, A.P., Greenwood, K., Wagner, D. (2011) Analyzing inter-application communication in Android. *MobiSys'11 - Compilation Proceedings of the 9th International Conference on Mobile Systems, Applications and Services and Co-located Workshops*. https://doi.org/10.1145/1999995.2000018

59. Wei, F., Roy, S., Ou, X., Robby (2014) Amandroid: A precise and general inter-component data flow analysis framework for security vetting of Android apps. *Proceedings of the ACM Conference on Computer and Communications Security*. https://doi.org/10.1145/2660267.2660357

60. https://www.sciencedirect.com/science/article/pii/S1863171124002759

61. Choi, K., Kim, J., Park, S. (2012) A secure application invocation mechanism in mobile phones for Near Field Communication. *Digest of Technical Papers - IEEE International Conference on Consumer Electronics*. https://doi.org/10.1109/ICCE.2012.6162059

62. Maass, M., Müller, U., Schons, T., (...), Schulz, M. (2015) DEMO: NFCGate - An NFC relay application for android. *Proceedings of the 8th ACM Conference on Security and Privacy in Wireless and Mobile Networks, WiSec 2015*. https://doi.org/10.1145/2766498.2774984

63. Forrester, L.-D., Shaw, R., Thorpe, S. (2018) Assessing Relay Attacks in NFC Enabled Devices A Three Factor Relay Test Environment (RATE) Approach. *Conference Proceedings - IEEE SOUTHEASTCON*. https://doi.org/10.1109/SECON.2018.8478914

64. Hairani, N., Hanan, F., Omar, M.F., (...), Muhamad, M. (2021) Retail Customer Acceptance Toward QR Code Payment System in Malaysia. *Lecture Notes in Networks and Systems*. https://doi.org/10.1007/978-3-030-69221-6_38

65. Syafaastuti, S., Delfina, Y., Syahchari, D.H. (2024) The Use of the Technology Acceptance Model (TAM) to Analyze the Effects of Social Influence on the Interest in Implementing Cashless Payment (QRIS). *Proceedings 7th IC2IE 2024 - 2024 International Conference of Computer and Informatics Engineering: Generative AI in Democratizing Access to Knowledge and Skills*. https://doi.org/10.1109/IC2IE63342.2024.10748219

66. Witjaksono, R.H.A., Wuri Handayani, P.W., Sunarso, F.P., Hilman, M. (2021) Quick Response Code Acceptance on Digital Wallet Mobile Applications in Indonesia. *2021 International Conference on Advanced Computer Science and Information Systems, ICACSIS 2021*. https://doi.org/10.1109/ICACSIS53237.2021.9631354

67. Sanchez-Gomez, Jesus, Garcia-Carrillo, Dan, Marin-Perez, Rafael, Skarmeta, Antonio F. (2020) Secure Authentication and Credential Establishment in Narrowband IoT and 5G. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s20030882

68. https://www.sciencedirect.com/science/article/pii/S2661890720003142

69. https://www.sciencedirect.com/science/article/pii/S1573048424001900

70. Krishnan, P., Jain, K., Poojara, S.R., (...), Buyya, R. (2024) eSIM and blockchain integrated secure zero-touch provisioning for autonomous cellular-IoTs in 5G networks. *Computer Communications*. https://doi.org/10.1016/j.comcom.2023.12.023

71. Pramod, P., Boroojeni, K.G., Hadi Amini, M., (...), Iyengar, S.S. (2019) Key pre-distribution scheme with join leave support for SCADA systems. *International Journal of Critical Infrastructure Protection*. https://doi.org/10.1016/j.ijcip.2018.10.011

72. Usama, Muhammad, Aziz, Arshad, Alasbali, Nada, (...), Rehman, Mujeeb Ur (2025) Blockchain-enabled identity management for IoT: a multi-layered defense against adversarial AI. *Scientific Reports*. https://doi.org/10.1038/s41598-026-35208-y

73. Wang, Z., Kim, G.M., Kang, H., (...), Kim, D.D. (2026) Spatially robust and visually stealthy physical adversarial attacks on object detection systems. *Applied Soft Computing*. https://doi.org/10.1016/j.asoc.2026.116029

74. https://www.sciencedirect.com/science/article/pii/S1936645026000033