

ASSIGNMENT-1 - Data Wrangling 1

Kaustubh Shrikant Kabra

ERP Number :- 38

TE Comp 1

Importing Packages

```
In [63]: import pandas as pd
import numpy as np
```

Loading Dataset into python dataframe

```
In [64]: df=pd.read_csv('train.csv')
```

```
In [65]: df
```

```
Out[65]:
```

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	I
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833	C85	
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	NaN	
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	
...	
886	887	0	2	Montvila, Rev. Juozas	male	27.0	0	0	211536	13.0000	NaN	

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	I
887	888	1	1	Graham, Miss. Margaret Edith	female	19.0	0	0	112053	30.0000	B42	
888	889	0	3	Johnston, Miss. Catherine Helen "Carrie"	female	NaN	1	2	W./C. 6607	23.4500	NaN	
889	890	1	1	Behr, Mr. Karl Howell	male	26.0	0	0	111369	30.0000	C148	
890	891	0	3	Dooley, Mr. Patrick	male	32.0	0	0	370376	7.7500	NaN	

891 rows × 12 columns



Description of Dataset

PassengerID: ID given to each passenger

Survived: Survival (0=No, 1=Yes)

Pclass: Class of passenger(1=1st, 2=2nd, 3=3rd)

Name: Name of passenger

Sex: Gender of passenger

Age: Age of passenger

SibSp: Number of Siblings/ Spouses Onboard

Parch: Number of Parents/ Children Onboard

Ticket: Ticket Number

Fare: Passenger Fare (Pounds)

Cabin: Cabin Number

Embarked: Port of Embarkation (C = Cherbourg; Q = Queenstown; S = Southampton)

In [66]:

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 12 columns):
#   Column          Non-Null Count  Dtype
---  -
0   PassengerId     891 non-null    int64
1   Survived        891 non-null    int64
2   Pclass          891 non-null    int64
3   Name            891 non-null    object
4   Sex             891 non-null    object
5   Age            714 non-null    float64
6   SibSp           891 non-null    int64
7   Parch           891 non-null    int64
```

```

8 Ticket      891 non-null object
9 Fare        891 non-null float64
10 Cabin      204 non-null object
11 Embarked   889 non-null object
dtypes: float64(2), int64(5), object(5)
memory usage: 83.7+ KB

```

In [67]: `df.describe()`

Out[67]:

	PassengerId	Survived	Pclass	Age	SibSp	Parch	Fare
count	891.000000	891.000000	891.000000	714.000000	891.000000	891.000000	891.000000
mean	446.000000	0.383838	2.308642	29.699118	0.523008	0.381594	32.204208
std	257.353842	0.486592	0.836071	14.526497	1.102743	0.806057	49.693429
min	1.000000	0.000000	1.000000	0.420000	0.000000	0.000000	0.000000
25%	223.500000	0.000000	2.000000	20.125000	0.000000	0.000000	7.910400
50%	446.000000	0.000000	3.000000	28.000000	0.000000	0.000000	14.454200
75%	668.500000	1.000000	3.000000	38.000000	1.000000	0.000000	31.000000
max	891.000000	1.000000	3.000000	80.000000	8.000000	6.000000	512.329200

In [68]: `df.shape`

Out[68]: (891, 12)

In [69]: `df.head()`

Out[69]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...)	female	38.0	1	0	PC 17599	71.2833	C85	S
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	NaN	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	S

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	



In [70]:

df.head(10)

Out[70]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...)	female	38.0	1	0	PC 17599	71.2833	C85	
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	NaN	
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	
5	6	0	3	Moran, Mr. James	male	NaN	0	0	330877	8.4583	NaN	
6	7	0	1	McCarthy, Mr. Timothy J	male	54.0	0	0	17463	51.8625	E46	
7	8	0	3	Palsson, Master. Gosta Leonard	male	2.0	3	1	349909	21.0750	NaN	
8	9	1	3	Johnson, Mrs. Oscar W (Elisabeth Vilhelmina Berg)	female	27.0	0	2	347742	11.1333	NaN	
9	10	1	2	Nasser, Mrs. Nicholas (Adele Achem)	female	14.0	1	0	237736	30.0708	NaN	

Checking NULL Values

In [71]: `df.isnull()`

Out[71]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
0	False	False	False	False	False	False	False	False	False	False	True	False
1	False	False	False	False	False	False	False	False	False	False	False	False
2	False	False	False	False	False	False	False	False	False	False	True	False
3	False	False	False	False	False	False	False	False	False	False	False	False
4	False	False	False	False	False	False	False	False	False	False	True	False
...
886	False	False	False	False	False	False	False	False	False	False	True	False
887	False	False	False	False	False	False	False	False	False	False	False	False
888	False	False	False	False	False	True	False	False	False	False	True	False
889	False	False	False	False	False	False	False	False	False	False	False	False
890	False	False	False	False	False	False	False	False	False	False	True	False

891 rows × 12 columns

In [72]: `df.isnull().sum()`

Out[72]:

```

PassengerId    0
Survived        0
Pclass          0
Name            0
Sex             0
Age            177
SibSp           0
Parch           0
Ticket          0
Fare            0
Cabin          687
Embarked        2
dtype: int64

```

Handling NULL values

Dropping Entire Column

Here, if the percentage of NULL value in a column is more than 70 percent then we are dropping it.

In [75]:

```

drop_col=df.isnull().sum()[df.isnull().sum()>(70/100 * df.shape[0])]
drop_col

```

Out[75]: Cabin 687
dtype: int64

In [76]: *# Drop the columns where NULL values are more than 70 percent*
df.drop(drop_col.index, inplace = True, axis=1)

In [77]: df.head()

Out[77]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833	C
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	S

In [78]: df.isnull().sum()

Out[78]:

PassengerId	0
Survived	0
Pclass	0
Name	0
Sex	0
Age	177
SibSp	0
Parch	0
Ticket	0
Fare	0
Embarked	2

dtype: int64

Replacing with mean

The NULL values in the age column will be filled with the mean age of the passengers

In [79]:

```
mean=np.mean(df['Age'])
mean
```

```
Out[79]: 29.69911764705882
```

```
In [80]: df['Age'].fillna(mean, inplace=True)
```

```
In [81]: df.isnull().sum()
```

```
Out[81]: PassengerId    0
Survived      0
Pclass        0
Name          0
Sex           0
Age           0
SibSp         0
Parch         0
Ticket        0
Fare          0
Embarked      2
dtype: int64
```

Replacing with most frequent value

In the Embarked column, we only have a few missing entries. So it is logical that we fill it with the most frequent value.

```
In [82]: df['Embarked'].describe()
```

```
Out[82]: count      889
unique        3
top           S
freq         644
Name: Embarked, dtype: object
```

```
In [83]: df['Embarked'].fillna(value='S', inplace=True)
```

```
In [84]: df.isnull().sum()
```

```
Out[84]: PassengerId    0
Survived      0
Pclass        0
Name          0
Sex           0
Age           0
SibSp         0
Parch         0
Ticket        0
Fare          0
Embarked      0
dtype: int64
```

So, we can see that we have handled all the NULL values in the dataset

```
In [85]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 11 columns):
#   Column             Non-Null Count  Dtype
---  -
0   PassengerId         891 non-null    int64
1   Survived            891 non-null    int64
2   Pclass              891 non-null    int64
3   Name                891 non-null    object
4   Sex                 891 non-null    object
5   Age                 891 non-null    float64
6   SibSp               891 non-null    int64
7   Parch               891 non-null    int64
8   Ticket              891 non-null    object
9   Fare                891 non-null    float64
10  Embarked            891 non-null    object
dtypes: float64(2), int64(5), object(4)
memory usage: 76.7+ KB
```

In [86]: `df.head()`

Out[86]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833	C
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	S

Turning Categorical variable into quantitative values

Here we will change the categorical values to quantitative values. For example, in the Sex column, if it is male we will replace it with 0 and if it is female we will replace it with 1.

In [87]: `df['Sex'] = df['Sex'].replace(to_replace=['male', 'female'], value=[0,1])`

In [88]:


```
df.head()
```

Out[88]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Embarked
0	1	0	3	Braund, Mr. Owen Harris	0	22.0	1	0	A/5 21171	7.2500	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	1	38.0	1	0	PC 17599	71.2833	C
2	3	1	3	Heikkinen, Miss. Laina	1	26.0	0	0	STON/O2. 3101282	7.9250	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	1	35.0	1	0	113803	53.1000	S
4	5	0	3	Allen, Mr. William Henry	0	35.0	0	0	373450	8.0500	S