

Thank you for taking the Week 1: Assignment 1.

Week 1: Assignment 1

Your last recorded submission was on 2022-02-04, 11:14 IST

Due date: 2022-02-09, 23:59 IST.

1) Which of the arithmetic operators given below cannot be used with 'strings' in Python?

1 point

- ☐ *
- ☒ -
- ☐ +
- ☐ All of the above

2) When the following statement is executed, what type of error is obtained?

1 point

```
var@check1 = 10
```

- ☐ Type Error
- ☒ Syntax Error
- ☐ Value Error
- ☐ None of the above

3) Two variables X and Y were assigned the following values initially. X = 3 and Y = 6. Which of the following statements will help swap the values between these two variables? 1 point

- ☐ Y = X
X = Y
- ☐ X = Y
Y = X
- ☒ X, Y = Y, X

4) From the following set of statements, what will be the value of variable y in the final print statement? 1 point

```
y = 1**2**3**2  
print("Variable y:",y)
```

- ☐ 8
- ☐ 9
- ☒ 1
- ☐ Error
- ☐ 16

5) Consider j = 5 and k = 11. We change the values from j = 7 and k remains constant. 1 point

What is `print(j|k)` before and after modification of value in variable j?

- ☐ 3,15
- ☒ 15,15
- ☐ 11,15
- ☐ 15,7
- ☐ None of the above

6) What would be the output of the following statements?

1 point

```
log_exp = not not True and False or not False
print(log_exp)
```

- ☐ False
- ☒ True
- ☐ Not True
- ☐ None of the above

7) What does `k = 4%7` evaluate to and what is the type of variable `k`?

1 point

- ☒ 4,int
- ☐ 0.0,float
- ☐ 0,int
- ☐ 1,int
- ☐ None of the above

8) `j = 6` and `g = 3.3`. If normal division and floor division was done between `j` and `k`, what would be the type of the resultant variable?

1 point

- ☐ int,int
- ☒ float,float
- ☐ float,int
- ☐ int,float
- ☐ None of the above

9) Consider two answers to a question; `answer1` and `answer2`. What is the output of the following set of statements?

1 point

```
answer1 = True
answer2 = False
print (answer1 * answer2)
```

- ☐ True
- ☐ False
- ☒ 0
- ☐ 1

10) Consider the list of instructions and resulting outputs given below. Pick the set that is incorrect.

1 point

```
1. print("Good", end = "")
   print("Day")
   Output -> GoodDay

2. word1 = "Trial"
   print("Word is %s" %word1)
   Output -> Trial

3. num1 = 23
   print( " Number: %f " %num1 )
   Output -> Number: 23.000000

4. print( "ready\nsteady\ngo")
   Output -> ready
               steady
               go
```

- ☐ 4
- ☒ 2
- ☐ 1,3,4
- ☐ 3,4
- ☐ All are correct

```
In [1]: # When the following statement is executed, what type of error is obtained?
var@check1 = 10

File "C:\Users\asus\AppData\Local\Temp\ipykernel_8188\3869232608.py", line 3
    var@check1 = 10
    ^
SyntaxError: cannot assign to operator

In [2]: # Two variables X and Y were assigned the following values initially.
# X = 3 and Y = 6. Which of the following statements will help swap the values between these two variables?

x = 3
y = 6
x, y = y, x
print(x)
print(y)

6
3

In [3]: # From the following set of statements, what will be the value of variable y in the final print statement?

y = 1**2**3**2
print("Variable y:",y)

Variable y: 1
```

```
In [4]: # Consider j = 5 and k = 11. We change the values from j = 7 and k remains constant.
# What is print(j|k) before and after modification of value in variable j?
```

```
j = 5
k = 11
print(j|k)
j=7
print(j|k)
```

```
15
15
```

```
In [5]: # What would be the output of the following statements?
```

```
log_exp = not not True and False or not False
print(log_exp)
```

```
True
```

```
In [6]: # What does k = 4%7 evaluate to and what is the type of variable k?
```

```
k = 4%7
print(k)
```

```
4
```

```
In [7]: # j = 6 and g = 3.3. If normal division and floor division was done between j and k,
# what would be the type of the resultant variable?
```

```
j = 6
g = 3.3


print(j/g)
print(j//g)
```












```
1.8181818181818183
1.0
```

```
In [8]: # Consider two answers to a question; answer1 and answer2. What is the output of the following set of statements?
```

```
answer1 = True
answer2 = False
print(answer1 * answer2)
```

```
0
```

File Edit View Insert Cell Kernel Widgets Help Trusted Python 3 (ipykernel) 

         Code  

```
1.8181818181818183
1.0
```

In [8]: *# Consider two answers to a question; answer1 and answer2. What is the output of the following set of statements?*

```
answer1 = True
answer2 = False
print(answer1 * answer2)

0
```

In [9]: *# Consider the list of instructions and resulting outputs given below. Pick the set that is incorrect.*

```
print("Good",end="")
print("Day")

word1 = "Trial"
print("Word is %s"%word1)

num1 = 23
print("Number:%f"%num1)

print("ready\nsteady\ngo")

GoodDay
Word is Trial
Number:23.000000
ready
steady
go
```

[Register for Certification exam](#)

Course outline

[How does an NPTEL online course work?](#)[Week 0](#)[Week 1](#)[Week 2](#)[Week 3](#)[Download Videos](#)[Text Transcripts](#)[Books](#)

Thank you for taking the Week 2: Assignment 2.

Week 2: Assignment 2

Your last recorded submission was on 2022-02-09, 17:12 IST

Due date: 2022-02-09, 23:59 IST.

1) Consider a variable job = "chemist". Which of the following expressions will retrieve the last character from the variable value? 1 point

- ☐ job[7]
☒ job[len(job) - 1]
☐ job[5:6]
☒ job[-1]
☐ All of the above statements are true

2) Which of the following expressions should be used to assign the variable get_num to get the final print statement output as value 75 from the below tuple? 1 point

```
nst_tup = ("System", (60, 75, 45), (15, 3, 12))  
get_num =  
print(get_num)
```

- ☐ nst_tup[1][2]
☐ nst_tup[1.2][1]
☒ nst_tup[1][1]
☐ nst_tup[1.2][1]

3) What would be the output for the following set of statements?

1 point

```
new_list = [13, 23, 18, 64, 51]  
new_list[4] = True  
print(new_list)
```

- ☐ [13, 23, 18, 64, 51, "True"]
☒ [13, 23, 18, 64, True]
☐ [13, 23, 18, 64, 51, True]
☐ Index Error

4) What result does the final statement print?

1 point

```
scores = (12, 25, 32, 39, 44)  
f_score, *bw_s, l_score = scores  
print("Output is :", f_score, "and", bw_s, "and", l_score)
```

- ☐ Output is: 12, (25, 32, 39), 44
☐ Output is: 12 and (25, 32, 39) and 44
☐ Output is: 12 and 25 and 39
☐ ValueError: Too many values to unpack
☒ Output is: 12 and [25, 32, 39] and 44

5) When the following set of instructions are executed, how many times does the vowel "e" appear in the result?

1 point

```
word = "occurrence"
for ltr in range(len(word)):
    if ltr % 3 == 0:
        print(word[ltr])
```

- ☐ 1
- ☐ "e" is not printed
- ☒ 2
- ☐ 4
- ☐ None of the above

6) Which of the following options, when executed, will result in a tuple?

1 point

- ☒ t = (2,2)
- ☐ y = ['h',4,'3']
- ☒ r = ('v',)
- ☐ s = ('w')
- ☐ All except b

7) Which statement/ statements will result in an empty datastructure?

1 point

- ☐ dict1 = {}
- ☐ tup1 = ()
- ☐ st1 = set()
- ☐

```
toy = "baseball"
gt_str = toy[2:2]
print("Output:",gt_str)
```

- ☒ All of the above

8) Consider a dictionary city created with the following keys and values.

1 point

```
city = {'Delhi':3, 'Bengaluru':5, 'Chennai':4, 'Kolkata':6, 'Mumbai':7}
```

Through which all possible way / ways can we access the value 5 from the dictionary city?

- ☒ city['Bengaluru']
- ☐ city.get['Bengaluru']
- ☐ city.values()[1]
- ☒ list(city.values())[1]
- ☐ None of the above

9) Count the number of elements in the below list.

1 point

```
list_tens = [["October", 24, ["2021"]]]
```

- ☐ 2
- ☒ 1
- ☐ 3
- ☐ 0
- ☐ None of the above

10) A datastructure is defined as celebrate = set('Nativity Day'). What are the possible outputs if celebrate is printed?

1 point

1. {'v', 'N', 't', 'i', 'y', 'a', 'D'}
2. {'v', 'N', 't', 'i', 'y', 'a', 'D', ' '}
3. {'v', 'N', 't', 'i', 'y', 'a', 'D', ''}
4. {'v', 't', 'i', 'y', 'a', 'D', ' ', 'N'}

- ☐ 1
- ☐ 1 and 3
- ☐ 1,2,3
- ☐ 3 and 4
- ☒ All are correct



In [1]: *# Consider a variable job = "chemist". Which of the following expressions will
retrieve the last character from the variable value?*

```
job = "chemist"
```

In [2]: job[7]

```
-----
IndexError                                Traceback (most recent call last)
~\AppData\Local\Temp\ipykernel_5592\38642040.py in <module>
----> 1 job[7]

IndexError: string index out of range
```

In [3]: job[len(job) - 1]


Out[3]: 't'

In [4]: job[5:6]

Out[4]: 's'

In [5]: job[- 1]

Out[5]: 't'



In [6]: *# Which of the following expressions should be used to assign the variable get_num
to get the final print statement output as value 75 from the below tuple?*

```
nst_tup = ("System", (60, 75, 45), (15, 3, 12))
get_num = nst_tup[1][1]
print(get_num)
```

75

In [7]: *# What would be the output for the following set of statements?*

```
new_list = [13, 23, 18, 64, 51]
new_list[4] = True
print(new_list)
```

[13, 23, 18, 64, True]

In [8]: *# What result does the final statement print?*

```
scores = (12, 25, 32, 39, 44)
f_score, bw_s, l_score = scores
print("Output is :", f_score, "and", bw_s, "and", l_score)
```

Output is : 12 and [25, 32, 39] and 44



In [9]: *# When the following set of instructions are executed, how many times does the vowel "e" appear in the result?*

```
word = "occurrence"
for ltr in range(len(word)):
    if ltr % 3 == 0:
        print(word[ltr])
```

```
o
u
e
e
```

In [10]: *# Which of the following options, when executed, will result in a tuple?*

```
t = (2,2)
y = ['h', '4', '3']
r = ('v',)
s = ('w')
```

In [11]: `type(t)`

Out[11]: tuple

In [12]: `type(y)`

Out[12]: list

In [13]: `type(r)`

Out[13]: tuple

In [14]: `type(s)`

Out[14]: str



In [15]: *# Which statement/ statements will result in an empty datastructure?*

```
dict1 = {}
print(dict1)

tup1 = ()
print(tup1)

st1 = set()
print(st1)

toy = "baseball"
gt_str = toy[2:2]
print("output:",gt_str)

{}
()
set()
output:
```




```
In [16]: # Consider a dictionary city created with the following keys and values.
# Through which all possible way / ways can we access the value 5 from the dictionary city?

city = {'Delhi':3, 'Bengaluru':5, 'Chennai':4, 'Kolkata':6, 'Mumbai':7 }
```

```
In [17]: city['Bengaluru']
```

```
Out[17]: 5
```

```
In [18]: city.get['Bengaluru']
```

```
-----
TypeError                                 Traceback (most recent call last)
~\AppData\Local\Temp\ipykernel_5592\2161206439.py in <module>
----> 1 city.get['Bengaluru']

TypeError: 'builtin_function_or_method' object is not subscriptable
```

```
In [19]: city.values()[1]
```

```
-----
TypeError                                 Traceback (most recent call last)
~\AppData\Local\Temp\ipykernel_5592\1294878199.py in <module>
----> 1 city.values()[1]

TypeError: 'dict_values' object is not subscriptable
```

```
In [20]: list(city.values())[1]
```

```
Out[20]: 5
```



```
TypeError: 'builtin_function_or_method' object is not subscriptable
```

```
In [19]: city.values()[1]
```

```
-----
TypeError                                 Traceback (most recent call last)
~\AppData\Local\Temp\ipykernel_5592\1294878199.py in <module>
----> 1 city.values()[1]

TypeError: 'dict_values' object is not subscriptable
```

```
In [20]: list(city.values())[1]
```

```
Out[20]: 5
```

```
In [21]: # Count the number of elements in the below list.
```

```
list_tens = [['October', 24, ["2021"]]]
len(list_tens)
```

```
Out[21]: 1
```

```
In [ ]:
```


NPTEL

WEEK 3 ASSIGNMENT QUESTIONS

- 1) Data from the file **"brand_data.csv"** has to be loaded into a pandas dataframe. A snippet of the data is shown below:

```
0,1,2,3
brand,type,cost,price
BR1,clnr,12,15
BR2,util,23,34
BR3,lux,189,191
BR4,txtl,150,130
```

What is the right instruction to read the file into a dataframe df_brand with 4 separate columns?

- a) `pd.read_csv("brand_data.csv",index_col=0,header = 1)`
- b) `df_brand = pd.read_csv("brand_data.csv",header = 1)`
- c) `df_brand = pd.read_csv("brand_data.csv",header = None)`
- d) `df_brand = pd.read_table("brand_data.csv",delimiter = ',',header = 1)`

Answers: b) and d)

Option a) chooses the wrong column as index. When set with `index_col = 0`, the dataframe ends with only 3 columns and brand becomes the index.

```
In [5]: df_brand = pd.read_csv("brand_data.csv",index_col=0,header = 1 )
In [6]: df_brand
Out[6]:
```

	type	cost	price
brand			
BR1	clnr	12	15
BR2	util	23	34
BR3	lux	189	191
BR4	txtl	150	130

Option b) returns a dataframe of 4 rows and 4 columns. This is correct.

```
In [7]: df_brand = pd.read_csv("brand_data.csv",header = 1 )
In [8]: df_brand
Out[8]:
```

	brand	type	cost	price
0	BR1	clnr	12	15
1	BR2	util	23	34
2	BR3	lux	189	191
3	BR4	txtl	150	130

Option c) reads the dataframe with the wrong header. The data is read into a dataframe in an illogical manner.

```
In [9]: df_brand = pd.read_csv("brand_data.csv",header = None)
```

```
In [10]: df_brand
```

```
Out[10]:
```

	0	1	2	3
0	0	1	2	3
1	brand	type	cost	price
2	BR1	clnr	12	15
3	BR2	util	23	34
4	BR3	lux	189	191
5	BR4	txtl	150	130

Option d) used read_table which can read csv files using the delimiter = ',' setting. Note that the header is also correctly marked. This is correct.

```
In [14]: df_brand = pd.read_table("brand_data.csv",delimiter = ',',header = 1)
```

```
In [15]: df_brand
```

```
Out[15]:
```

	brand	type	cost	price
0	BR1	clnr	12	15
1	BR2	util	23	34
2	BR3	lux	189	191
3	BR4	txtl	150	130

2) For the same file above "**brand_data.csv**", which parameter in pd.read_csv will help to load dataframe df_brand with the selected columns as shown below?

```
In [17]: df_brand
```

```
Out[17]:
```

	brand	price
0	BR1	15
1	BR2	34
2	BR3	191
3	BR4	130

- a. index_col=['brand','Price']
- b. skiprows=['brand','Price']
- c. usecols=['brand','Price']
- d. None of the above

Answer: c) usecols. Returns a subset of the columns from the original file.

```
In [16]: df_brand = pd.read_csv("brand_data.csv",header = 1,usecols=
['brand','price'] )
```

```
In [17]: df_brand
```

```
Out[17]:
```

	brand	price
0	BR1	15
1	BR2	34
2	BR3	191
3	BR4	130

3) Data from the file “**weather.xlsx**” has to be loaded into a pandas dataframe *df_weather* which when printed is as shown below:

```
In [38]: df_weather
Out[38]:
```

	Direction	Temperature	Windspeed	Humidity
0	East	49	10	78
1	West	54	5	80
2	North	35	8	92
3	South	42	15	70

Of the following set of statements which of them can be used to move the column “Direction” into a separate dataframe

- a. `df_weather[['Direction']]`
- b. `df_weather['Direction']`
- c. `df_weather.loc[:,['Direction']]`
- d. `df_weather.iloc[:,0]`

Answer: a and c.

Option a. ->

```
In [39]: df_dir = df_weather[['Direction']]

In [40]: print(df_dir,type(df_dir))
Direction
0      East
1      West
2     North
3     South <class 'pandas.core.frame.DataFrame'>
```

Option b ->

```
In [41]: sr_dir = df_weather['Direction']

In [42]: print(sr_dir,type(sr_dir))
0      East
1      West
2     North
3     South
Name: Direction, dtype: object <class 'pandas.core.series.Series'>
```

Option c ->

```
In [45]: df_dir = df_weather.loc[:,['Direction']]

In [46]: print(df_dir,type(df_dir))
Direction
0      East
1      West
2     North
3     South <class 'pandas.core.frame.DataFrame'>
```

Option d ->

```
In [43]: sr_dir = df_weather.iloc[:,0]
```

```
In [44]: print(sr_dir,type(sr_dir))
```

```
0    East
1    West
2    North
3    South
```

```
Name: Direction, dtype: object <class 'pandas.core.series.Series'>
```

4) Referring to the same dataframe df_weather in Question (3), which statement/statements will help to print the last row from the dataframe?

- a. `print(df_weather.head(-1))`
- b. `print(df_weather.tail(1))`
- c. `print(df_weather[2:3])`
- d. `print(df_weather.iloc[-1])`

Answer: b and d

Option a. Retrieves all rows except the last row.

```
In [5]: print(df_weather.head(-1))
```

	Direction	Temperature	Windspeed	Humidity
0	East	49	10	78
1	West	54	5	80
2	North	35	8	92

Option b. Correct option.

```
In [10]: print(df_weather.tail(1))
```

	Direction	Temperature	Windspeed	Humidity
3	South	42	15	70

Option c. Retrieves the row with index 2 [second last row].

```
In [11]: print(df_weather[2:3])
```

	Direction	Temperature	Windspeed	Humidity
2	North	35	8	92

Option d. Correct option.

```
In [13]: print(df_weather.iloc[-1])
```

	Direction	Temperature	Windspeed	Humidity
	South	42	15	70

5) In reference to the same dataframe df_weather, we add an additional column 'Hot_day' to determine whether the day is hot or not based on the values in the Temperature column. What will the print statement derive?

```
df_weather['Hot_day'] = np.where(df_weather['Temperature'] > 40, True, False )
print(df_weather['Hot_day'][2])
```

- a. True
- b. SyntaxError
- c. False
- d. None of the above

Answer: c). The third row has a temperature of 35, so it will return False.

```
In [21]: df_weather['Hot_day'] = np.where(df_weather['Temperature'] >
40, True, False )
```

```
In [22]: print(df_weather['Hot_day'][2])
False
```

6) What statement would give the number of columns in a dataframe df?

- a. len(df.columns)
- b. len(df)
- c. df.size
- d. All of the above.

Answer: a) len(df) returns number of rows. df.size returns the number of elements.

7) A file “**Students.csv**” contains the attendance and total scores of three separate students. This data is loaded into a dataframe **df_study** and a pandas crosstab is applied on the same dataframe which results in the following output


Subject	Chemistry	Maths	Physics	All
Person				
Harini	90.00	94.00	83.00	89.00
Rekha	92.00	85.00	95.00	90.67
Sathi	74.00	84.00	81.00	79.67
All	85.33	87.67	86.33	86.44

Which student scored the maximum average score of all three subjects? Which subject has the best average score for all three students?

- a. Harini,Chemistry
- b. Rekha,Physics
- c. Harini,Physics
- d. Rekha,Maths

Answer: d) Rekha, Maths.

8) The following histogram shows the number of books read in a year:




Find the mean and median in the above histogram.

- a) 7,8
- b) 8,9
- c) 8.5,7
- d) 8,8
- e) None of the above

Answer: d) 8 is the central tendency for the above histogram. It is the mean, median and mode.

9) For the following box plot, which among the given options are the median and the outlier?



- a. 15,52
- b. 22, 52
- c. 13.5, 29
- d. 25, 50

Answer: b) Median is between 20 and 25, so 22 is the median. Outlier is between 50 and 55, hence 52 is the outlier.

Q1 -13.5 Q3 – 27.5

10) A dataframe df_logs has the following data.

	A1	B1	C1	D1
0	25.0	NaN	NaN	11.0
1	NaN	22.0	NaN	23.0
2	52.0	12.0	NaN	NaN
3	NaN	33.0	NaN	NaN
4	45.0	NaN	NaN	21.0

All the NaN / Null values in the column C1 can be replaced by zero value by executing which of the following statements?

- a. df_logs['C1'].fillna(0,inplace = True)
- b. df_logs.fillna(0,inplace = True)
- c. df_logs.fillna(0,inplace = False)
- d. df_logs['C1'].fillna(df_logs['B1'],inplace = True)

a. Answer: a) df_logs['C1'].fillna(0,inplace = True)

Option a) Only Column C1 values get replaced by zero value.

```
df_logs['C1'].fillna(0,inplace = True)
df_logs
```

	A1	B1	C1	D1
0	25.0	NaN	0.0	11.0
1	NaN	22.0	0.0	23.0
2	52.0	12.0	0.0	NaN
3	NaN	33.0	0.0	NaN
4	45.0	NaN	0.0	21.0

Option b). All the null values in the dataframe get replaced by zero value. Incorrect.

```
df_logs.fillna(0,inplace = True)
df_logs
```

	A1	B1	C1	D1
0	25.0	0.0	0.0	11.0
1	0.0	22.0	0.0	23.0
2	52.0	12.0	0.0	0.0
3	0.0	33.0	0.0	0.0
4	45.0	0.0	0.0	21.0

Option c). No changes are reflected in the dataframe. Incorrect.

```
df_logs.fillna(0,inplace = False)  
df_logs
```

	A1	B1	C1	D1
0	25.0	NaN	NaN	11.0
1	NaN	22.0	NaN	23.0
2	52.0	12.0	NaN	NaN
3	NaN	33.0	NaN	NaN
4	45.0	NaN	NaN	21.0

Option d). Column C1 null values get replaced by Column B1 values. Incorrect.

```
df_logs['C1'].fillna(df_logs['B1'],inplace = True)  
df_logs
```

	A1	B1	C1	D1
0	25.0	NaN	NaN	11.0
1	NaN	22.0	22.0	23.0
2	52.0	12.0	12.0	NaN
3	NaN	33.0	33.0	NaN
4	45.0	NaN	NaN	21.0

WEEK 4 ASSIGNMENT QUESTIONS

Given Data: Credit Worthiness data containing 1000 observations of income details of individuals comprising 21 attributes along the columns (Cbal, Cdur, Chist, Cpur, Camt, Sbal, Edur, InRate, MSG, Oparties, Rdur, Prop, age, inPlans, Htype, NumCred, JobType, Ndepend, telephone, foreign, creditScore)

Problem statement: By observing the features of the dataset, the problem statement can be defined as a binary classification problem of classifying any individual into an appropriate category of creditScore such as Good or Bad.

- 1) How many unique values are present in the Sbal feature; also, what is the most frequent value within Sbal?
- a) 5, Rs. \geq 10,000
 - b) 4, Rs. $<$ 1000
 - c) 5, Rs. $<$ 1000
 - d) 4, '1000 \leq Rs. $<$ 5,000'

Answers: c)

All features of object type can be analyzed by describe (). MARKUP ON THE PICTURE.

```
data.describe(include = "O").T
```

	count	unique	top	freq
Cbal	1000	4	no checking account	394
Chist	1000	4	all settled till now	618
Cpur	1000	10	electronics	280
Sbal	1000	5	Rs. $<$ 1000	603
Edur	1000	5	1 to 4 years	339

- 2) Find the average age of those customers who have a credit history [Chist] wherein the dues are not paid earlier.

- a. 35.54
- b. 38.44
- c. 33.00
- d. None of the above

Answer: b) 38.44

```
paydue_age = data[data["Chist"] == 'dues not paid earlier']["age"].mean()
print(round(paydue_age,2))
```

38.44

3) A Logistic Regression model is built in which none of the features used are standardized. The train to test proportion is 75:25 and the random state is set to 1. The accuracy of the model is _____.

- a. Less than 50%
- b. Between 50% and 60%
- c. Greater than 70%
- d. None of the above

Answer: c)

```
import os
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import sklearn

from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score, confusion_matrix, classification_report
from sklearn.preprocessing import StandardScaler
```

```
data = pd.read_excel('CreditWorthiness.xlsx', sheet_name = 'Data')
```

```
##Map the deposit to yes as 0 no as 1
data['creditScore'] = data['creditScore'].map({'good':1, 'bad':0})
```

```
X = pd.get_dummies(data.drop(columns = ['creditScore']), drop_first = True)
y = data['creditScore']
```

```
train_x, test_x, train_y, test_y = train_test_split( X, y, test_size=0.25, random_state=1)
```

```
logis_mod = LogisticRegression(max_iter=10000)
logis_mod.fit(train_x,train_y)
prediction_log = logis_mod.predict(test_x)
```

```
confusion_matrix_logr = confusion_matrix(test_y, prediction_log)
tn, fp, fn, tp = confusion_matrix_logr.ravel()
print(confusion_matrix_logr)
print('tp:',tp,'tn:',tn,'fp:',fp,'fn:',fn)
```

```
[[ 28  34]
 [ 29 159]]
tp: 159 tn: 28 fp: 34 fn: 29
```

```
acc_score_logr = accuracy_score(test_y, prediction_log)
print(round(acc_score_logr*100,2))
```

74.8

```
lr_precision = tp/(tp+fp)
lr_recall = tp/(tp+fn)
lr_f1_score = 2/(1/lr_precision + 1/lr_recall)
print("Precision is: ",round(lr_precision*100,2),
      "Recall is: ", round(lr_recall*100,2),
      "F1 Score is: ",round( lr_f1_score *100,2))
```

Precision is: 82.38 Recall is: 84.57 F1 Score is: 83.46

```
print('Misclassified samples: %d' % (test_y != prediction_log).sum())
```

Misclassified samples: 63

4) Import StandardScaler() from the sklearn.preprocessing package to standardize the features. Use the same train-test proportion and the random state should be set to 1. After standardizing the logistic regression model, by what percentage has the misclassified samples changed?

- a. 11.11%
- b. 3.7%
- c. 20%
- d. 39.2%

Answer: a

After Standardizing:

```
col_names = ['age', 'Camt', 'Cdur', 'InRate', 'NumCred', 'Ndepend']
features = train_x[col_names]
scaler = StandardScaler().fit(features.values)

features = scaler.transform(features.values)
train_x.loc[:,col_names]=features

features = test_x[col_names]
features = scaler.transform(features.values)
test_x.loc[:,col_names]=features
```

```

logis_mod = LogisticRegression(max_iter=10000)
logis_mod.fit(train_x,train_y)
prediction_std_log = logis_mod.predict(test_x)

confusion_matrix_slogr = confusion_matrix(test_y, prediction_std_log)
tn, fp, fn, tp = confusion_matrix_slogr.ravel()
print(confusion_matrix_slogr)
print('tp:',tp,'tn:',tn,'fp:',fp,'fn:',fn)

[[ 33  29]
 [ 27 161]]
tp: 161 tn: 33 fp: 29 fn: 27

acc_score_slogr = accuracy_score(test_y, prediction_std_log)
print(round(acc_score_slogr*100,2))

77.6

print('Misclassified samples in Logistic Regression classification: %d' % (test_y != prediction_std_log).sum())

Misclassified samples in Logistic Regression classification: 56

```

Percentage change in misclassified samples : $(56-63 / 63)*100 = 11.11\%$

5) When KNN classification is applied on the same standardized data at the optimal value for k nearest neighbours, the accuracy achieved is _____.

- 64%
- 78%
- 76.4%
- None of the above

Answer: b)

```

Misclassified_sample = []
accuracy_scores_k=[]
# Calculating error for K values between 1 and 25
for i in range(1, 25):
    knn_mod = KNeighborsClassifier(n_neighbors=i,metric='euclidean')
    knn_mod.fit(train_x, train_y)
    predk_i = knn_mod.predict(test_x)
    Misclassified_sample.append((test_y != predk_i).sum())
    acc_score_k = accuracy_score(test_y, predk_i)
    # print("For k =",i,"accuracy score: ",acc_score_k)
    accuracy_scores_k.append(acc_score_k)

print("List of accuracy scores:",accuracy_scores_k)
max_acc = max(accuracy_scores_k)
index_max_acc = accuracy_scores_k.index(max_acc)
print("Maximum accuracy is",round(max_acc*100,2),"at k =",index_max_acc + 1)

List of accuracy scores: [0.66, 0.568, 0.676, 0.652, 0.716, 0.704, 0.74, 0.728, 0.72, 0.724, 0.748, 0.744, 0.76, 0.764, 0.78, 0.768, 0.776, 0.772, 0.776, 0.78, 0.764, 0.772, 0.768, 0.764]
Maximum accuracy is 78.0 at k = 15

```

6) A multiple linear regression model is built on the Global Happiness Index dataset “GHI_Report.csv”. What is the rmse of the baseline model?

- 1.99
- 0.85
- 1.06
- 0.33

Answer: b) 1.06

```
# Set the features and the target
features = list(set(data_ghi.columns)-set(["H_Score"]))
target = list(['H_Score'])

print(features)
print(target)

['Freedom', 'Health', 'Economy', 'Fam']
['H_Score']

X = data_ghi.loc[:,features]
y = data_ghi.loc[:,target]
train_x, test_x, train_y, test_y = train_test_split(X,y,test_size = 0.25, random_state = 1)

# Base Model with test data mean values
base_pred = np.mean(test_y)
print(base_pred)

#repeat the same for all samples in test data
base_pred = np.repeat(base_pred,len(test_y))

# Find Baseline model RMSE
base_rmse = np.sqrt(mean_squared_error(test_y,base_pred))
print("Base RMSE : ",round(base_rmse,2))

H_Score    5.343225
dtype: float64
Base RMSE :  1.06
```

7) From the multiple linear regression model built on the GHI index, we get an R-squared value of ____ on the test data subset.

- a. 55.63
- b. 45.81
- c. 75.59
- d. 81.46

Answer: d)

```
# Find Rsquared value in Test and Train dataset - whether variabi
r2_linr_train = linreg_mod.score(train_x,train_y)
r2_linr_test = linreg_mod.score(test_x,test_y)
print("R2 score of train dataset: ",round(r2_linr_train*100,2))
print("R2 score of test dataset: ",round(r2_linr_test*100,2))
```

```
R2 score of train dataset:  75.59
R2 score of test dataset:  81.46
```

8) Which of the following statement/s about Linear Regression is / are true?

- a) Linear Regression assumes that there exists a linear relationship between the independent variable and dependent variable.
- b) The errors terms are assumed to be independent and normally distributed.
- c) The percentage of variation in the dependent variable as explained by the independent variable/variables is expressed by R-squared value.
- d) Residuals are the product of the predicted value and the actual observed value.

Answer: a,b and c.

Residuals are the difference between the predicted value and the actual observed value.

9) Which of the following statements is inaccurate about Logistic Regression?

- a) Logistic Regression doesn't require a linear relationship between the dependent and independent variables.
- b) The value of the logistic function being a probability will range between 0 and 1.
- c) Cost function of Logistic Regression is also called as the Log Loss function.
- d) The dependent variable can be of both numerical or categorical type just like the independent variables.

Answer: d) Only categorical dependent variable.

10) In a KNN model, by which means do we handle categorical variables?

- a) Standardization
- b) Dummy variables
- c) Correlation
- d) None of the above

Answer: b) Dummy variables can be used to encode the different values contained in a particular categorical independent feature.