
Neural Networks 8. Echo State Networks

Center for Cognitive Science Department of Applied Informatics Faculty of Mathematics, Physics and Informatics Comenius University in Bratislava


Thursday 11th April, 2024

Simple Recurrent Network (last exercise)




$$c(t) = h(t-1)$$
 $h = f_{hid}(W^{in}x' + W^{rec}c')$ $y = f_{out}(W^{out}h')$

Echo State Network



$$c(t) = r(t-1)$$
 $r = f_{res}(W^{in}x + W^{res}c)$ $y = W^{out}r$ hidden layer == "reservoir"

Echo State Network



Echo State Network - training

random Gaussian initialisation

- ▶ **Sparse**: some % of weights are set to 0
- $\max\{|\lambda_i|\} = \rho,$ 0 << ρ < 1

Analytically - pseudo-inverse (for linear output only):

$$W^{out} := DR^+$$

Iteratively - gradient descent:

$$\Delta \mathbf{W}^{out} = \alpha (\mathbf{d} - \mathbf{y}) \mathbf{r}^T$$

Task

- ► C08.1-seq.py and C08.2-seq.py TODO:
 - tune the parameters to make the model work better
- esn.py TODO:
 - initialise weights
 - initialise the reservoir
 - forward pass
 - update weights