
Neural Networks 11. Pytorch – Convolutional Network

Center for Cognitive Science
Department of Applied Informatics
Faculty of Mathematics, Physics and Informatics
Comenius University in Bratislava


Thursday 2nd May, 2024

Convolutional Neural Networks (CNNs)



Convolutional filters

1x1	1 x 0	1x1	0	0
0x0	1x1	1x0	1	0
0 x 1	0x0	1x1	1	1
0	0	1	1	0
0	1	1	0	0




Operation	Filter	Convolved Image
Identity	$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$	
	$\begin{bmatrix} 1 & 0 & -1 \\ 0 & 0 & 0 \\ -1 & 0 & 1 \end{bmatrix}$	
Edge detection	$\begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$	
	$\begin{bmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{bmatrix}$	
Sharpen	$\begin{bmatrix} 0 & -1 & 0 \\ -1 & 5 & -1 \\ 0 & -1 & 0 \end{bmatrix}$	
Box blur (normalized)	$\frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$	
Gaussian blur (approximation)	$\frac{1}{16} \begin{bmatrix} 1 & 2 & 1 \\ 2 & 4 & 2 \\ 1 & 2 & 1 \end{bmatrix}$	

Convolutional pooling


1	1	2	4	may pool with 2x2		
5	6	7	8	max pool with 2x2 window and stride 2	6	8
3	2	1	0		3	4
1	2	3	4			


Convolutional stride



Stride 2 Feature Map

Padding





Stride 1 with Padding

Feature Map

The only formula today:

$$n_{out} = \left[\frac{n_{in} + 2p - k}{s} \right] + 1$$

 n_{in} : number of input features

 n_{out} : number of output features

k: convolution kernel size

p: convolution padding size

s: convolution stride size

Task:

- Implement a convolutional network to classify Fashion MNIST
 - Define at least 2 convolutional layers (each having several filters, activation function and pooling)
 - For regularisation, use dropout (enough to use in the classifier part)
 - Compute by hand the number of neurons needed after last convolutional layer.
- Use learning rate decay to dynamically change the learning rate.
- Find two in the code.