

FIFO Page Replacement Algorithm

Write a C program to implement the FIFO Page Replacement Algorithm. The program should take the number of frames and a reference string (sequence of page requests) as input. For each page in the reference string, determine if it results in a 'Page Hit' or a 'Page Fault'. Display the state of the frames after each request and calculate the total number of page faults and hits.

Input Format

1. The first line of input contains an integer representing the number of pages in the reference string.
2. The second line contains the page reference string as a sequence of integers.
3. The third line contains an integer representing the number of available frames.

Output Format

The total number of Page Faults and Page Hits are displayed

Sample Input 1

Select Language : C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int n, frames, i, j, k, flag;
5
6     printf("Enter number of pages in reference string: \n");
7     scanf("%d", &n);
8
9     int ref[n];
10
11    printf("Enter the reference string: \n");
12    for(i = 0; i < n; i++) {
13        scanf("%d", &ref[i]);
14    }
15
16    printf("Enter number of frames: \n");
17    scanf("%d", &frames);
18
19    int frame[frames];
```

Test Cases 2

Run Sample Cases

Run All Cases

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

[Back to Practice](#)

FIFO Page Replacement Algorithm

Write a C program to implement the FIFO Page Replacement Algorithm. The program should take the number of frames and a reference string (sequence of page requests) as input. For each page in the reference string, determine if it results in a 'Page Hit' or a 'Page Fault'. Display the state of the frames after each request and calculate the total number of page faults and hits.

Input Format

1. The first line of input contains an integer representing the number of pages in the reference string.
2. The second line contains the page reference string as a sequence of integers.
3. The third line contains an integer representing the number of available frames.

Output Format

The total number of Page Faults and Page Hits are displayed

Sample Input 1

Completed

Select Language : C (GCC 9.2.0)

```
21     for(i = 0; i < frames; i++)
22         frame[i] = -1;
23
24     int faults = 0, hits = 0;
25     int pos = 0;
26
27     for(i = 0; i < n; i++) {
28         flag = 0;
29
30         // Check hit
31         for(j = 0; j < frames; j++) {
32             if(frame[j] == ref[i]) {
33                 hits++;
34                 flag = 1;
35                 break;
36             }
37         }
38     }
```

Test Cases 2[Run Sample Cases](#)[Run All Cases](#)

Custom Test Case

[> Custom Test](#)

Sample Test Case

[> Test Case - 1](#)

FIFO Page Replacement Algorithm

Write a C program to implement the FIFO Page Replacement Algorithm. The program should take the number of frames and a reference string (sequence of page requests) as input. For each page in the reference string, determine if it results in a 'Page Hit' or a 'Page Fault'. Display the state of the frames after each request and calculate the total number of page faults and hits.

Input Format

1. The first line of input contains an integer representing the number of pages in the reference string.
2. The second line contains the page reference string as a sequence of integers.
3. The third line contains an integer representing the number of available frames.

Output Format

The total number of Page Faults and Page Hits are displayed

Sample Input 1

Completed

```
36     }
37     }
38
39     // If not found → fault
40     if(flag == 0) {
41         frame[pos] = ref[i];
42         pos = (pos + 1) % frames;
43         faults++;
44     }
45 }
46
47 printf("\nTotal Page Faults: %d\n", faults);
48 printf("Total Page Hits: %d\n", hits);
49
50 return 0;
51 }
```

Test Cases 2

Run Sample Cases

Run All Cases

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

> Test Case - 2