

Mastery Question Bank: Python Data Structures

Comprehensive 100-Question Exam (Dictionaries, Lists, and Strings)

Focus Area: High density on Dictionaries & Cross-interaction methods.

Instructions: Select exactly one alternative for each item. Answers are consolidated into the final index page matrix.

Question 1

EASY

Which of the following data types uses curly braces {} to define literal key-value pairs?

- ☐ A) list
- ☐ B) tuple
- ☐ C) dictionary
- ☐ D) string

Question 2

EASY

How do you access the value associated with the key 'age' in a dictionary named `user`?

- ☐ A) user('age')
- ☐ B) user['age']
- ☐ C) user.age
- ☐ D) user{'age'}

Question 3

EASY

What happens if you try to access a key that does not exist in a dictionary using square brackets (e.g., `d['missing']`)?

- ☐ A) Returns None
- ☐ B) Throws a `KeyError`
- ☐ C) Throws a `ValueError`
- ☐ D) Automatically creates the key

Question 4

EASY

Which dictionary method returns a default value if a key is not found instead of raising an error?

- ☐ A) `d.get(key)`
- ☐ B) `d.find(key)`
- ☐ C) `d.search(key)`
- ☐ D) `d.fetch(key)`

Question 5

EASY

What is the output of `len({'a': 1, 'b': 2, 'c': 3})`?

- ☐ A) 6
- ☐ B) 3
- ☐ C) 2
- ☐ D) 1

Question 6

EASY

Dictionary keys must be of a data type that is:

- ☐ A) Mutable
- ☐ B) Immutable (Hashable)
- ☐ C) Iterable
- ☐ D) Numeric only

Question 7

EASY

Which of the following is NOT a valid key type in a Python dictionary?

- ☐ A) string
- ☐ B) integer
- ☐ C) tuple
- ☐ D) list

Question 8

EASY

How can you add a new key-value pair `'color': 'blue'` to an existing dictionary `car`?

- ☐ A) `car.add('color', 'blue')`
- ☐ B) `car['color'] = 'blue'`
- ☐ C) `car.append('color': 'blue')`
- ☐ D) `car.insert('color', 'blue')`

Question 9

EASY

Which built-in method clears all items from a dictionary?

- ☐ A) remove()
- ☐ B) delete()
- ☐ C) clear()
- ☐ D) flush()

Question 10

EASY

What will `list({'x': 10, 'y': 20}.keys())` return?

- ☐ A) [10, 20]
- ☐ B) [('x', 10), ('y', 20)]
- ☐ C) ['x', 'y']
- ☐ D) {'x', 'y'}

Question 11

EASY

Which operator is used to check if a specific key exists within a dictionary?

- ☐ A) in
- ☐ B) has
- ☐ C) exists
- ☐ D) contains

Question 12

EASY

What does the ``values()`` method of a dictionary return?

- ☐ A) A list of all keys
- ☐ B) A view object of all values
- ☐ C) A tuple of all key-value pairs
- ☐ D) The total count of values

Question 13

EASY

What is the output of the code: ``d = {'a': 1}; d['a'] = 2; print(d['a'])`` ?

- ☐ A) 1
- ☐ B) 2
- ☐ C) KeyError
- ☐ D) (1, 2)

Question 14

EASY

Which dictionary method returns a view of key-value pairs as tuples?

- ☐ A) `keys()`
- ☐ B) `values()`
- ☐ C) `items()`
- ☐ D) `pairs()`

Question 15

EASY

What is the correct way to initialize an empty dictionary?

- ☐ A) `d = []`
- ☐ B) `d = ()`
- ☐ C) `d = {}`
- ☐ D) `d = empty()`

Question 16

EASY

Which method adds an element to the end of a list?

- ☐ A) `extend()`
- ☐ B) `add()`
- ☐ C) `insert()`
- ☐ D) `append()`

Question 17

EASY

What is the index of the first element in a Python list or string?

- ☐ A) 1
- ☐ B) -1
- ☐ C) 0
- ☐ D) Any number

Question 18

EASY

How do you access the last element of a non-empty list `my_list` using negative indexing?

- ☐ A) `my_list[-1]`
- ☐ B) `my_list[0]`
- ☐ C) `my_list[-len(my_list)]`
- ☐ D) `my_list[last]`

Question 19

EASY

What does `'hello'.upper()` evaluate to?

- ☐ A) `'Hello'`
- ☐ B) `'HELLO'`
- ☐ C) `'hello'`
- ☐ D) Error

Question 20

EASY

Which method splits a string into a list of words based on a separator?

- ☐ A) `divide()`
- ☐ B) `partition()`
- ☐ C) `split()`
- ☐ D) `break()`

Question 21

EASY

What is the output of `['a', 'b'] + ['c']`?

- ☐ A) `['a', 'b'], ['c']`
- ☐ B) `['a', 'b', 'c']`
- ☐ C) `['abc']`
- ☐ D) `TypeError`

Question 22

EASY

Strings in Python are mutable or immutable?

- ☐ A) Mutable
- ☐ B) Immutable
- ☐ C) Depends on the length
- ☐ D) Only mutable via methods

Question 23

EASY

How do you find the number of items in a list named `lst`?

- ☐ A) `lst.size()`
- ☐ B) `count(lst)`
- ☐ C) `len(lst)`
- ☐ D) `lst.length()`

Question 24

EASY

What is the output of `""Python"[1:4]`?

- ☐ A) 'Pyth'
- ☐ B) 'yth'
- ☐ C) 'ytho'
- ☐ D) 'yt'

Question 25

EASY

Which method removes and returns the last element from a list?

- ☐ A) `remove()`
- ☐ B) `pop()`
- ☐ C) `delete()`
- ☐ D) `discard()`

Question 26

EASY

Given `d = {'items': [1, 2, 3]}`, what does `d['items'][1]` evaluate to?

- ☐ A) 1
- ☐ B) 2
- ☐ C) 3
- ☐ D) `KeyError`

Question 27

EASY

If `info = {'name': 'Alice'}`, what does `info['name'].lower()` produce?

- ☐ A) 'alice'
- ☐ B) 'Alice'
- ☐ C) TypeError
- ☐ D) None

Question 28

EASY

What is the type of `x` after running `x = {'names': ['Bob', 'Mary']}`?

- ☐ A) list
- ☐ B) string
- ☐ C) dict
- ☐ D) tuple

Question 29

EASY

Given `words = ['apple', 'banana']`, what is the output of `dict.fromkeys(words, 0)`?

- ☐ A) {'apple': 0, 'banana': 0}
- ☐ B) {0: 'apple', 0: 'banana'}
- ☐ C) ['apple', 'banana', 0]
- ☐ D) TypeError

Question 30**EASY**

What does ``len({'colors': ['red', 'green', 'blue']})`` return?

☐ A) 3☐ B) 1☐ C) 4☐ D) 0**Question 31****EASY**

Which of the following creates a dictionary where keys are string representations of numbers 1 to 3 and values are their cubes?

☐ A) `{'1':1, '2':8, '3':27}`☐ B) `{1:'1', 8:'2', 27:'3'}`☐ C) `[('1', 1), ('2', 8)]`☐ D) None of the above**Question 32****EASY**

What is the output of ``type({True: 'yes', False: 'no'})``?

☐ A)☐ B)☐ C)☐ D)

Question 33

EASY

If `d = {'a': 10}` and you run `d.update({'b': 20})`, what is `d`?

- ☐ A) `{'b': 20}`
- ☐ B) `{'a': 10}`
- ☐ C) `{'a': 10, 'b': 20}`
- ☐ D) None

Question 34

EASY

How can you get a list of values from the dictionary `d = {'x':1, 'y':2}`?

- ☐ A) `d.get_values()`
- ☐ B) `list(d.values())`
- ☐ C) `d.val_list()`
- ☐ D) `list(d)`

Question 35

EASY

What is the output of `"".join(['a', 'b', 'c'])`?

- ☐ A) `'a-b-c'`
- ☐ B) `'-a-b-c'`
- ☐ C) `'abc-'`
- ☐ D) `TypeError`

Question 36

EASY

What happens if you use an integer as a key, such as `d = {1: 'One'}`?

- ☐ A) `SyntaxError`
- ☐ B) It works perfectly fine
- ☐ C) `TypeError` because keys must be strings
- ☐ D) The integer is automatically cast to a string

Question 37

EASY

To remove a key-value pair from a dictionary by key and return its value, use:

- ☐ A) `d.remove(key)`
- ☐ B) `d.pop(key)`
- ☐ C) `d.discard(key)`
- ☐ D) `del(d, key)`

Question 38

EASY

What does `str({'a': 1})` evaluate to?

- ☐ A) `"{'a': 1}"`
- ☐ B) `'a: 1',`
- ☐ C) `['a', 1]`
- ☐ D) `TypeError`

Question 39

EASY

If `lst = [1, 2, 3]`, what is the output of `lst.clear()`?

- ☐ A) []
- ☐ B) None
- ☐ C) [1, 2, 3]
- ☐ D) Throws an error

Question 40

EASY

Which expression returns True if the string `"cat"` is a key in the dictionary `animals`?

- ☐ A) `"cat" in animals.values()`
- ☐ B) `"cat" in animals`
- ☐ C) `animals.has_key("cat")`
- ☐ D) `"cat" == animals`

Question 41

EASY

What is the output of `{'a': 5}.get('b', 0)`?

- ☐ A) None
- ☐ B) `KeyError`
- ☐ C) 0
- ☐ D) 5

Question 42

EASY

Can a dictionary contain duplicate keys?

- ☐ A) Yes, values will be stored as a list
- ☐ B) No, assigning to an existing key overwrites its value
- ☐ C) Yes, but only if values are also duplicates
- ☐ D) No, it throws a `DuplicateKeyError`

Question 43

EASY

What will `list('abc')` evaluate to?

- ☐ A) `['abc']`
- ☐ B) `['a', 'b', 'c']`
- ☐ C) `('a', 'b', 'c')`
- ☐ D) `TypeError`

Question 44

EASY

Which of the following is an empty dictionary literal representation?

- ☐ A) `dict([])`
- ☐ B) `{}`
- ☐ C) both A and B
- ☐ D) None of the above

Question 45

EASY

What is the output of `{'a':1, 'b':2} == {'b':2, 'a':1}` in modern Python?

- ☐ A) True
- ☐ B) False
- ☐ C) TypeError
- ☐ D) Depends on Python version

Question 46

INTERMEDIATE

What is the result of the following dictionary comprehension?

`{x: x**2 for x in (2, 4)}`

- ☐ A) {2: 4, 4: 16}
- ☐ B) {4: 2, 16: 4}
- ☐ C) [4, 16]
- ☐ D) {(2,4): (4,16)}

Question 47

INTERMEDIATE

What will be the output of this code snippet?

```
d = {'a': 1, 'b': 2}
print(d.get('c', d.get('b')))
```

- ☐ A) None
- ☐ B) 1
- ☐ C) 2
- ☐ D) KeyError

Question 48

INTERMEDIATE

Which method behaves like ``get()``, but also sets ``d[key] = default`` if the key is not already in the dictionary?

- ☐ A) `setdefault()`
- ☐ B) `get_and_set()`
- ☐ C) `update_default()`
- ☐ D) `fetch_or_create()`

Question 49

INTERMEDIATE

What is the behavior of the following expression in Python 3.9+?

```
`d1 = {'a': 1}; d2 = {'b': 2}; d3 = d1 | d2`
```

- ☐ A) d3 becomes a set: `{'a', 'b'}`
- ☐ B) d3 merges the two dictionaries: `{'a': 1, 'b': 2}`
- ☐ C) Raises a `TypeError`
- ☐ D) Performs a bitwise OR on values

Question 50

INTERMEDIATE

What will be the output of the following code?

```
`d = {1: 'A', True: 'B', 1.0: 'C'}`  
`print(len(d))`
```

- ☐ A) 3
- ☐ B) 2
- ☐ C) 1
- ☐ D) `TypeError`

Question 51

INTERMEDIATE

What will the following code print?

```
`d = {'a': 10, 'b': 20}`  
`del d['a']`  
`print(d.get('a', 'Removed'))`
```

- ☐ A) 10
- ☐ B) 'Removed'
- ☐ C) None
- ☐ D) KeyError

Question 52

INTERMEDIATE

If you iterate over a dictionary using a standard for loop (`for x in d:`), what does the loop variable `x` represent?

- ☐ A) Key-value tuples
- ☐ B) The values
- ☐ C) The keys
- ☐ D) The index integers

Question 53

INTERMEDIATE

What will happen when executing the following snippet?

```
`d = {}`  
`d[[1, 2]] = "list_key"`
```

- ☐ A) d becomes {[1, 2]: "list_key"}
- ☐ B) Raises a TypeError: unhashable type: 'list'
- ☐ C) Raises a KeyError
- ☐ D) Syntactically incorrect syntax

Question 54

INTERMEDIATE

What is the output of the following code?

```
`d = {'a': 1, 'b': 2}`  
`v = d.values()`  
`d['c'] = 3`  
`print(len(v))`
```

- ☐ A) 2
- ☐ B) 3
- ☐ C) 0
- ☐ D) RuntimeError

Question 55

INTERMEDIATE

Which option cleanly merges two dictionaries `x` and `y` in-place (updating `x` with `y`'s values)?

- ☐ A) x.add(y)
- ☐ B) x.extend(y)
- ☐ C) x.update(y)
- ☐ D) x + y

Question 56

INTERMEDIATE

What is the output of `dict([('a', 1), ('b', 2)])`?

- ☐ A) {'a': 1, 'b': 2}
- ☐ B) [('a', 1), ('b', 2)]
- ☐ C) Throws a ValueError
- ☐ D) {'a': 'b', 1: 2}

Question 57

INTERMEDIATE

What does the following `popitem()` code remove from a dictionary in modern standard Python?

```
`d = {'x': 1, 'y': 2}`
```

```
`d.popitem()`
```

- ☐ A) A random item
- ☐ B) The first item ('x': 1)
- ☐ C) The last inserted item ('y': 2)
- ☐ D) All items

Question 58

INTERMEDIATE

What is the output of the following?

```
`d = {'a': 1}`
```

```
`print('a' in d, 1 in d)`
```

- ☐ A) True True
- ☐ B) True False
- ☐ C) False True
- ☐ D) False False

Question 59

INTERMEDIATE

How do you create a shallow copy of a dictionary ``d``?

- ☐ A) `d.copy()`
- ☐ B) `dict(d)`
- ☐ C) Both A and B
- ☐ D) `d.clone()`

Question 60

INTERMEDIATE

What is the outcome of `{}` printing evaluation:
'print(type({}))' vs 'print(type({1}))'?

☐ A) ,

☐ B) ,

☐ C) ,

☐ D) ,

Question 61

INTERMEDIATE

What is the value of `lst` after this operation?
`lst = [1, 2, 3]`
`lst.extend([4, 5])`

☐ A) [1, 2, 3, [4, 5]]

☐ B) [1, 2, 3, 4, 5]

☐ C) [5, 7, 3]

☐ D) None

Question 62

INTERMEDIATE

What is the output of `"ab".join(['1', '2'])`?

☐ A) '1ab2'

☐ B) 'ab1ab2'

☐ C) '12ab'

☐ D) 'ab12'

Question 63

INTERMEDIATE

What is the result of string slicing `"abcdef"[:-2]`?

- ☐ A) 'fdb'
- ☐ B) 'fec'
- ☐ C) 'eca'
- ☐ D) 'ace'

Question 64

INTERMEDIATE

What is the output of `lst = [1, 2, 3, 4]; del lst[1:3]; print(lst)`?

- ☐ A) [1, 4]
- ☐ B) [1, 2, 4]
- ☐ C) [1, 3, 4]
- ☐ D) []

Question 65

INTERMEDIATE

Which of the following code pieces creates a shallow clone of list `L`?

- ☐ A) `L[:]`
- ☐ B) `L.copy()`
- ☐ C) `list(L)`
- ☐ D) All of the above

Question 66**INTERMEDIATE**

What is the value of `s` after executing `s = "abc"; s.replace("a", "z")`?

- ☐ A) 'zbc'
- ☐ B) 'abc'
- ☐ C) None
- ☐ D) Throws an exception

Question 67**INTERMEDIATE**

What does `[x for x in range(5) if x % 2 == 0]` evaluate to?

- ☐ A) [0, 2, 4]
- ☐ B) [2, 4]
- ☐ C) [1, 3]
- ☐ D) [0, 1, 2, 3, 4]

Question 68**INTERMEDIATE**

What is the output of `"hello".find("z")`?

- ☐ A) ValueError
- ☐ B) None
- ☐ C) -1
- ☐ D) False

Question 69

INTERMEDIATE

What is the result of ``['a', 'b', 'c'].index('b')``?

- ☐ A) 0
- ☐ B) 1
- ☐ C) 2
- ☐ D) True

Question 70

INTERMEDIATE

What is the output of ``list(range(5, 2, -1))``?

- ☐ A) [5, 4, 3, 2]
- ☐ B) [5, 4, 3]
- ☐ C) [2, 3, 4, 5]
- ☐ D) []

Question 71

INTERMEDIATE

What is the output of this snippet?

```
`d = {'a': [1, 2]}  
`d['a'].append(3)  
`print(d)`
```

- ☐ A) {'a': [1, 2, 3]}
- ☐ B) {'a': [1, 2], 3: None}
- ☐ C) AttributeError
- ☐ D) {'a': 3}

Question 72

INTERMEDIATE

What is the output of the following code?

```
`res = {str(i): i for i in range(3)}  
`print(res.get(1, "missing"))`
```

- ☐ A) 1
- ☐ B) "missing"
- ☐ C) '1'
- ☐ D) KeyError

Question 73

INTERMEDIATE

What is the outcome of running this snippet?

```
`s = "apple"  
`counts = {char: s.count(char) for char in s}  
`print(counts['p'])`
```

- ☐ A) 1
- ☐ B) 2
- ☐ C) 0
- ☐ D) KeyError

Question 74

INTERMEDIATE

Consider the following:

```
`data = [{'id': 1, 'val': 'A'}, {'id': 2, 'val': 'B'}]`
```

```
`out = {item['id']: item['val'] for item in data}`
```

`What is out?`

- ☐ A) {1: 'A', 2: 'B'}
- ☐ B) {'id': [1, 2], 'val': ['A', 'B']}
- ☐ C) [{1: 'A'}, {2: 'B'}]
- ☐ D) TypeError

Question 75

INTERMEDIATE

What will be printed?

```
`keys = ['x', 'y']`
```

```
`values = [10, 20]`
```

```
`d = dict(zip(keys, values))`
```

```
`print(d)`
```

- ☐ A) {'x': 'y', 10: 20}
- ☐ B) {'x': 10, 'y': 20}
- ☐ C) [('x', 10), ('y', 20)]
- ☐ D) ValueError

Question 76

INTERMEDIATE

What is the output of the following code?

```
`d = {}`  
`for word in ['key', 'key', 'val']:`  
`  d[word] = d.get(word, 0) + 1`  
`print(d['key'])`
```

- ☐ A) 1
- ☐ B) 2
- ☐ C) 3
- ☐ D) KeyError

Question 77

INTERMEDIATE

Given `d = {'matrix': [[1, 2], [3, 4]]}`, how do you extract the value `4`?

- ☐ A) d['matrix'][1][1]
- ☐ B) d['matrix'][2][2]
- ☐ C) d['matrix'][1][1]
- ☐ D) d.get('matrix')[0][1]

Question 78

INTERMEDIATE

What is the outcome of running:

```
`text = "a b a"`  
`d = {w: text.split().count(w) for w in text.split()}`  
`print(len(d))`
```

☐ A) 3

☐ B) 2

☐ C) 1

☐ D) 0

Question 79

INTERMEDIATE

What is the output of the following expression?

```
`d = {'x': 10}`  
`print(d.setdefault('x', 20), d['x'])`
```

☐ A) 20 20

☐ B) 10 10

☐ C) 20 10

☐ D) 10 20

Question 80

INTERMEDIATE

What is the result of ``sorted({'c':3, 'a':1, 'b':2})``?

☐ A) ['a', 'b', 'c']

☐ B) [1, 2, 3]

☐ C) [('a', 1), ('b', 2), ('c', 3)]

☐ D) {'a':1, 'b':2, 'c':3}

Question 81

INTERMEDIATE

What is the output of this program?

```
`d = {i: i*2 for i in range(1, 4)}`  
`print(sum(d.values()))`
```

- ☐ A) 6
- ☐ B) 12
- ☐ C) 8
- ☐ D) 14

Question 82

INTERMEDIATE

If ``d = {'a': 1, 'b': 2}``, what happens during ``list(d.items())[0][0] = 'z'``?

- ☐ A) d changes to `{'z': 1, 'b': 2}`
- ☐ B) Raises a `TypeError` because tuples are immutable
- ☐ C) Runs without changing d
- ☐ D) Raises an index error

Question 83

INTERMEDIATE

What will ``print({v: k for k, v in {'a': 1, 'b': 2}.items()})`` output?

- ☐ A) `{'a': 1, 'b': 2}`
- ☐ B) `{1: 'a', 2: 'b'}`
- ☐ C) `[1, 2]`
- ☐ D) `SyntaxError`

Question 84

INTERMEDIATE

Given `words = ['hello', 'world']`, what does `{w: len(w) for w in words}` yield?

- ☐ A) `{'hello': 5, 'world': 5}`
- ☐ B) `{5: 'hello', 5: 'world'}`
- ☐ C) `{'hello', 'world'}`
- ☐ D) None of the above

Question 85

INTERMEDIATE

What is the output of the following snippet?

```
d = {'a': 1}
res = d.pop('b', 'Not Found')
print(res)
```

- ☐ A) `KeyError`
- ☐ B) `None`
- ☐ C) `'Not Found'`
- ☐ D) `1`

Question 86

INTERMEDIATE

If `d = {'first': [10, 20]}` and you execute `d['first'] += [30]`, what is `d['first']`?

- ☐ A) `[10, 20, 30]`
- ☐ B) `[40, 20]`
- ☐ C) `TypeError`
- ☐ D) `[10, 20, [30]]`

Question 87

INTERMEDIATE

What is the exact output of ``print(type(dict().keys()))``?

☐ A)

☐ B)

☐ C)

☐ D)

Question 88

INTERMEDIATE

What is the result of ``**{'a': 1}, **{'b': 2}``?

☐ A) {'a': 1, 'b': 2}

☐ B) ValueError

☐ C) SyntaxError

☐ D) {'a', 'b'}

Question 89

INTERMEDIATE

What will be the output of ``print(all({'a': True, 'b': False}))``?

☐ A) True

☐ B) False

☐ C) TypeError

☐ D) None

Question 90

INTERMEDIATE

What is the value of ``any({0: 'No', False: 'False'})``?

- ☐ A) True
- ☐ B) False
- ☐ C) 'No'
- ☐ D) TypeError

Question 91

INTERMEDIATE

What will be printed by the following?

```
`d = {'num': 42}`  
`print("Value is %(num)d" % d)`
```

- ☐ A) Value is 42
- ☐ B) Value is num
- ☐ C) TypeError
- ☐ D) KeyError

Question 92

INTERMEDIATE

What does the code ``len({x: x for x in 'banana'})`` return?

- ☐ A) 6
- ☐ B) 3
- ☐ C) 1
- ☐ D) 2

Question 93

INTERMEDIATE

If `d1 = {'a': 1, 'b': 2}` and `d2 = {'b': 9, 'c': 4}`, what is `x = {**d1, **d2}` value for `'b'`?

- ☐ A) 2
- ☐ B) 9
- ☐ C) 11
- ☐ D) [2, 9]

Question 94

INTERMEDIATE

What is the result of `list({'a': 1, 'b': 2}.items())[1]`?

- ☐ A) ('b', 2)
- ☐ B) 'b'
- ☐ C) 2
- ☐ D) KeyError

Question 95

INTERMEDIATE

What is the output of the code below?

```
d = {'vals': [1, 2]}
n = d.copy()
n['vals'].append(3)
print(d['vals'])
```

- ☐ A) [1, 2]
- ☐ B) [1, 2, 3]
- ☐ C) AttributeError
- ☐ D) None

Question 96

INTERMEDIATE

Which of the following creates a dictionary from a string where keys are characters and values are their Unicode code points?

- ☐ A) `{c: ord(c) for c in 'abc'}`
- ☐ B) `{ord(c): c for c in 'abc'}`
- ☐ C) `dict('abc')`
- ☐ D) None of the above

Question 97

INTERMEDIATE

What is the layout of `d` after `d = dict.fromkeys('abc', [])` and `d['a'].append(1)`?

- ☐ A) `{'a': [1], 'b': [], 'c': []}`
- ☐ B) `{'a': [1], 'b': [1], 'c': [1]}`
- ☐ C) `{'a': [], 'b': [], 'c': []}`
- ☐ D) `TypeError`

Question 98

INTERMEDIATE

What is the output of `print(str(list({'k': 'v'}.keys())))`?

- ☐ A) `"['k']"`
- ☐ B) `"dict_keys(['k'])"`
- ☐ C) `"k"`
- ☐ D) `TypeError`

Question 99

INTERMEDIATE

What will `print('-',join({'a':1, 'b':2}))` produce?

- ☐ A) 'a-b'
- ☐ B) '1-2'
- ☐ C) 'a-1-b-2'
- ☐ D) TypeError

Question 100

INTERMEDIATE

Given `d = {'a': 100, 'b': 200}`, what does `max(d)` return?

- ☐ A) 200
- ☐ B) 'b'
- ☐ C) ('b', 200)
- ☐ D) KeyError

Official Answer Key Matrix

Use this verified lookup layout to cross-reference and evaluate your choices after answering.

Q1 C	Q2 B	Q3 B	Q4 A	Q5 B	Q6 B	Q7 D	Q8 B	Q9 C	Q10 C
Q11 A	Q12 B	Q13 B	Q14 C	Q15 C	Q16 D	Q17 C	Q18 A	Q19 B	Q20 C
Q21 B	Q22 B	Q23 C	Q24 B	Q25 B	Q26 B	Q27 A	Q28 C	Q29 A	Q30 B
Q31 A	Q32 C	Q33 C	Q34 B	Q35 A	Q36 B	Q37 B	Q38 A	Q39 B	Q40 B
Q41 C	Q42 B	Q43 B	Q44 C	Q45 A	Q46 A	Q47 C	Q48 A	Q49 B	Q50 C
Q51 B	Q52 C	Q53 B	Q54 B	Q55 C	Q56 A	Q57 C	Q58 B	Q59 C	Q60 B
Q61 B	Q62 A	Q63 A	Q64 A	Q65 D	Q66 B	Q67 A	Q68 C	Q69 B	Q70 B
Q71 A	Q72 B	Q73 B	Q74 A	Q75 B	Q76 B	Q77 A	Q78 B	Q79 B	Q80 A
Q81 B	Q82 B	Q83 B	Q84 A	Q85 C	Q86 A	Q87 B	Q88 A	Q89 True	Q90 B
Q91 A	Q92 B	Q93 B	Q94 A	Q95 B	Q96 A	Q97 B	Q98 A	Q99 A	Q100 B