

231901019

EXP NO:1B

KAVIYA J J

DATE:30.7.24

LINUX COMMANDS

Every computer is connected to some other computer through a network whether internally or externally to exchange some information. This network can be small as some computers connected in your home or office, or can be large or complicated as in large University or the entire Internet.

Maintaining a system's network is a task of System/Network administrator. Their task includes network configuration and troubleshooting.

Here is a list of Networking and Troubleshooting commands:

1.ifconfig: ifconfig is short for interface configurator. This command is utilized in network inspection, initializing the interface, enabling or disabling an IP address, and configuring an interface with an IP address. Also, it is used to show the network and route interface. The basic details shown with ifconfig are:

- MTU
- MAC address
- IP address

Syntax:

Ifconfig

```

root@ip-10-10-38-111:~# ifconfig
docker0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 172.17.0.1 netmask 255.255.0.0 broadcast 172.17.255.255
    inet6 fe80::42:16ff:fec8:24d5 prefixlen 64 scopeid 0x20<link>
    ether 02:42:16:c8:24:d5 txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 35 bytes 4761 (4.7 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

ens5: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 9001
    inet 10.10.38.111 netmask 255.255.0.0 broadcast 10.10.255.255
    inet6 fe80::4a:89ff:fe31:79dd prefixlen 64 scopeid 0x20<link>
    ether 02:4a:89:31:79:dd txqueuelen 1000 (Ethernet)
    RX packets 8907 bytes 715564 (715.5 KB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 6758 bytes 4150018 (4.1 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 15766 bytes 4606708 (4.6 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 15766 bytes 4606708 (4.6 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

veth9ddb7c8: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet6 fe80::540c:a4ff:fe12:a53b prefixlen 64 scopeid 0x20<link>
    ether 56:0c:a4:12:a5:3b txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 57 bytes 7476 (7.4 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

vethf098cf2: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet6 fe80::10a6:daff:fe84:d9f2 prefixlen 64 scopeid 0x20<link>
    ether 12:a6:da:84:d9:f2 txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 58 bytes 7566 (7.5 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

```

2. ip: It is the updated and latest edition of ifconfig command. The command provides the information of every network, such as ifconfig. Also, it can be used to get information about a particular interface. **Syntax:**

1. ip a
2. ip addr

```
File Edit View Search Terminal Help
veth9ddb7c8: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet6 fe80::540c:a4ff:fe12:a53b prefixlen 64 scopeid 0x20<link>
    ether 56:0c:a4:12:a5:3b txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 57 bytes 7476 (7.4 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

vethf098cf2: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet6 fe80::10a6:daff:fe84:d9f2 prefixlen 64 scopeid 0x20<link>
    ether 12:a6:da:84:d9:f2 txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 58 bytes 7566 (7.5 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

root@ip-10-10-38-111:~# ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: ens5: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 9001 qdisc mq state UP group default qlen 1000
    link/ether 02:4a:89:31:79:dd brd ff:ff:ff:ff:ff:ff
    inet 10.10.38.111/16 brd 10.10.255.255 scope global dynamic ens5
        valid_lft 2768sec preferred_lft 2768sec
    inet6 fe80::4a:89ff:fe31:79dd/64 scope link
        valid_lft forever preferred_lft forever
3: docker0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state UP group default
    link/ether 02:42:16:c8:24:d5 brd ff:ff:ff:ff:ff:ff
    inet 172.17.0.1/16 brd 172.17.255.255 scope global docker0
        valid_lft forever preferred_lft forever
    inet6 fe80::42:16ff:fec8:24d5/64 scope link
        valid_lft forever preferred_lft forever
5: vethf098cf2@if4: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue master docker0 state UP group default
    link/ether 12:a6:da:84:d9:f2 brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet6 fe80::10a6:daff:fe84:d9f2/64 scope link
        valid_lft forever preferred_lft forever
7: veth9ddb7c8@if6: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue master docker0 state UP group default
    link/ether 56:0c:a4:12:a5:3b brd ff:ff:ff:ff:ff:ff link-netnsid 1
    inet6 fe80::540c:a4ff:fe12:a53b/64 scope link
        valid_lft forever preferred_lft forever
root@ip-10-10-38-111:~#
```

3.traceroute: The traceroute command is one of the most helpful commands in the networking field. It's used to balance the network. It identifies the delay and decides the pathway to our target. Basically, it aids in the below ways:□ It determines the location of the network latency and informs it.

- It follows the path to the destination.
- It gives the names and recognizes all devices on the path.

Syntax:

traceroute <destination>

```
valid_ttl forever preferred_ttl forever
root@ip-10-10-38-111:~# traceroute www.google.com
traceroute to www.google.com (209.85.202.104), 30 hops max, 60 byte packets
 1 * * *
 2 * * *
 3 * * *
 4 * * *
 5 * * *
 6 * * *
 7 * * *
 8 * * *
 9 * * *
10 * * *
11 * * *
12 * * *
13 * * *
14 * * *
15 * * *
16 * * *
17 * * *
18 * * *
19 * * *
20 * * *
21 * * *
22 * * *
23 * * *
24 * * *
25 * * *
26 * * *
27 * * *
28 * * *
29 * * *
30 * * *
root@ip-10-10-38-111:~#
```

4.

tracpath: The tracpath command is the same as the traceroute command, and it is used to find network delays. Besides, it does not need root privileges. By default, it comes pre-installed in Ubuntu. It traces the path to the destination and recognizes all hops in it. It identifies the point at which the network is weak if our network is not strong enough.

Syntax:

tracpath <destination>


```
root@ip-10-10-38-111: ~
File Edit View Search Terminal Help
root@ip-10-10-38-111:~# tracert www.google.com
1?: [LOCALHOST]          pmtu 1500
 1:  no reply
 2:  no reply
 3:  no reply
 4:  no reply
 5:  no reply
 6:  no reply
 7:  no reply
 8:  no reply
 9:  no reply
10:  no reply
11:  no reply
12:  no reply
13:  no reply
14:  no reply
15:  no reply
```

5.

ping: It is short for Packet Internet Groper. The ping command is one of the widely used commands for network troubleshooting. Basically, it inspects the network connectivity between two different nodes.

Syntax:

ping <destination>



The screenshot shows a terminal window titled "root@ip-10-10-38-111:~" with a menu bar (File, Edit, View, Search, Terminal, Help) and a status bar (Fri 9 Aug, 07:12, AttackBox IP: 10.10.38.111). The terminal displays the usage of the ping command, followed by the execution of "ping 10.10.38.111". The output shows 31 successful pings with varying response times. The statistics at the bottom indicate 31 packets transmitted, 31 received, 0% packet loss, and a total time of 30723ms. The terminal is running on a THM AttackBox. The browser's address bar shows "tryhackme.com/login" and the system clock indicates 11:42 AM on 8/9/2024.

```
Usage: ping -6 [-aAbBdDfhLnOqrRUvV] [-c count] [-i interval] [-I interface]
        [-l preload] [-m mark] [-M pmtudisc_option]
        [-N nodeinfo_option] [-p pattern] [-Q tclass] [-s packetsize]
        [-S sndbuf] [-t ttl] [-T timestamp_option] [-w deadline]
        [-W timeout] destination
root@ip-10-10-38-111:~# ping 10.10.38.
ping: 10.10.38.: Name or service not known
root@ip-10-10-38-111:~# ping 10.10.38.111
PING 10.10.38.111 (10.10.38.111) 56(84) bytes of data.
64 bytes from 10.10.38.111: icmp_seq=1 ttl=64 time=0.042 ms
64 bytes from 10.10.38.111: icmp_seq=2 ttl=64 time=0.037 ms
64 bytes from 10.10.38.111: icmp_seq=3 ttl=64 time=0.027 ms
64 bytes from 10.10.38.111: icmp_seq=4 ttl=64 time=0.029 ms
64 bytes from 10.10.38.111: icmp_seq=5 ttl=64 time=0.023 ms
64 bytes from 10.10.38.111: icmp_seq=6 ttl=64 time=0.044 ms
64 bytes from 10.10.38.111: icmp_seq=7 ttl=64 time=0.025 ms
64 bytes from 10.10.38.111: icmp_seq=8 ttl=64 time=0.027 ms
64 bytes from 10.10.38.111: icmp_seq=9 ttl=64 time=0.032 ms
64 bytes from 10.10.38.111: icmp_seq=10 ttl=64 time=0.025 ms
64 bytes from 10.10.38.111: icmp_seq=11 ttl=64 time=0.035 ms
64 bytes from 10.10.38.111: icmp_seq=12 ttl=64 time=0.029 ms
64 bytes from 10.10.38.111: icmp_seq=13 ttl=64 time=0.041 ms
64 bytes from 10.10.38.111: icmp_seq=14 ttl=64 time=0.044 ms
64 bytes from 10.10.38.111: icmp_seq=15 ttl=64 time=0.039 ms
64 bytes from 10.10.38.111: icmp_seq=16 ttl=64 time=0.030 ms
64 bytes from 10.10.38.111: icmp_seq=17 ttl=64 time=0.040 ms
64 bytes from 10.10.38.111: icmp_seq=18 ttl=64 time=0.027 ms
64 bytes from 10.10.38.111: icmp_seq=19 ttl=64 time=0.042 ms
64 bytes from 10.10.38.111: icmp_seq=20 ttl=64 time=0.042 ms
64 bytes from 10.10.38.111: icmp_seq=21 ttl=64 time=0.027 ms
64 bytes from 10.10.38.111: icmp_seq=22 ttl=64 time=0.025 ms
64 bytes from 10.10.38.111: icmp_seq=23 ttl=64 time=0.037 ms
64 bytes from 10.10.38.111: icmp_seq=24 ttl=64 time=0.042 ms
64 bytes from 10.10.38.111: icmp_seq=25 ttl=64 time=0.181 ms
64 bytes from 10.10.38.111: icmp_seq=26 ttl=64 time=0.028 ms
64 bytes from 10.10.38.111: icmp_seq=27 ttl=64 time=0.043 ms
64 bytes from 10.10.38.111: icmp_seq=28 ttl=64 time=0.025 ms
64 bytes from 10.10.38.111: icmp_seq=29 ttl=64 time=0.032 ms
64 bytes from 10.10.38.111: icmp_seq=30 ttl=64 time=0.031 ms
64 bytes from 10.10.38.111: icmp_seq=31 ttl=64 time=0.047 ms
^C
--- 10.10.38.111 ping statistics ---
31 packets transmitted, 31 received, 0% packet loss, time 30723ms
rtt min/avg/max/mdev = 0.023/0.038/0.181/0.027 ms
root@ip-10-10-38-111:~#
```

6.

netstat: It is short for network statistics. It gives statistical figures of many interfaces, which contain open sockets, connection information, and routing tables.

Syntax:

Netstat

Ss

```
root@ip-10-10-38-111: ~
File Edit View Search Terminal Help
68180 u_str ESTAB 0 * 68181 0 *
63443 u_str ESTAB 0 * 63444 0 *
45154 u_str ESTAB 0 * 44635 0 *
29772 u_str ESTAB 0 * 29378 0 *
62417 u_str ESTAB 0 * 62416 0 *
24854 u_str ESTAB 0 * 26289 0 *
62776 u_str ESTAB 0 * 63530 0 *
29679 u_str ESTAB 0 * 30095 0 *
29656 u_str ESTAB 0 * 30068 0 *
19962 u_str ESTAB 0 * 18852 0 *
27917 u_str ESTAB 64 * 27916 0 *
26859 u_str ESTAB 0 * 25446 0 *
28978 u_str ESTAB 0 * 28369 0 *
28317 u_str ESTAB 0 * 28906 0 *
63890 u_str ESTAB 0 * 63006 0 *
32451 * 33491
```

8.

nslookup: The nslookup command is an older edition of the dig command. Also, it is utilized for DNS related problems.

The screenshot shows a Kali Linux desktop environment. At the top, there is a purple taskbar with icons for Applications, Places, System, and a terminal icon. Below this is a window titled "root@ip-10-10-38-111: ~". The window contains a terminal window with a menu bar (File, Edit, View, Search, Terminal, Help) and a list of network connections. The connections are listed in a table-like format with columns for protocol, state, local address, remote address, and local port. The connections are as follows:

Protocol	State	Local Address	Remote Address	Local Port
tcp	SYN-SENT	0	1	10.10.38.111:
44124			34.117.188.166:https	
tcp	SYN-SENT	0	1	10.10.38.111:
59546			34.120.208.123:https	
tcp	ESTAB	0	0	127.0.0.1:
5901			127.0.0.1:54532	
tcp	SYN-SENT	0	1	10.10.38.111:
56484			34.107.221.82:http	
tcp	ESTAB	0	0	10.10.38.111:
http			10.100.2.28:52654	
tcp	ESTAB	0	0	127.0.0.1:
54532			127.0.0.1:5901	

Below the table, the terminal shows the command `nslookup` being executed. The output of the command is as follows:

```
root@ip-10-10-38-111:~# nslookup
> www.google.com
Server:      127.0.0.53
Address:     127.0.0.53#53

Non-authoritative answer:
Name:   www.google.com
Address: 209.85.202.104
Name:   www.google.com
Address: 209.85.202.103
Name:   www.google.com
Address: 209.85.202.106
Name:   www.google.com
Address: 209.85.202.99
Name:   www.google.com
Address: 209.85.202.147
Name:   www.google.com
Address: 209.85.202.105
Name:   www.google.com
Address: 2a00:1450:400b:c00::68
Name:   www.google.com
Address: 2a00:1450:400b:c00::6a
Name:   www.google.com
Address: 2a00:1450:400b:c00::63
Name:   www.google.com
Address: 2a00:1450:400b:c00::67
>
```

The terminal window is titled "THM AttackBox" and shows a timer of "33min 11s". The desktop environment includes a taskbar at the bottom with icons for Google, Firefox, and other applications. The system tray at the bottom right shows the date and time as "11:46 AM 8/9/2024".


Syntax:

`nslookup <domainname>`

9.

dig: dig is short for Domain Information Groper. The dig command is an improvised edition of the nslookup command. It is utilized in DNS lookup to reserve the DNS name server. Also, it is used to balance DNS related problems. Mainly, it is used to authorize DNS mappings, host addresses, MX records, and every other DNS record for the best DNS topography understanding. **Syntax:**

dig <domainname>



```
x | +
Fri 9 Aug, 07:17 AttackBox IP: 10.10.38.111
root@ip-10-10-38-111: ~
File Edit View Search Terminal Help
Address: 209.85.202.104
Name: www.google.com
Address: 209.85.202.103
Name: www.google.com
Address: 209.85.202.106
Name: www.google.com
Address: 209.85.202.99
Name: www.google.com
Address: 209.85.202.147
Name: www.google.com
Address: 209.85.202.105
Name: www.google.com
Address: 2a00:1450:400b:c00::68
Name: www.google.com
Address: 2a00:1450:400b:c00::6a
Name: www.google.com
Address: 2a00:1450:400b:c00::63
Name: www.google.com
Address: 2a00:1450:400b:c00::67
^Croot@ip-10-10-38-111:~# dig www.google.com
; <<>> DiG 9.11.3-1ubuntu1.18-Ubuntu <<>> www.google.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 41715
;; flags: qr rd ra; QUERY: 1, ANSWER: 6, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:;; udp: 65494
;; QUESTION SECTION:
;www.google.com.                IN      A

;; ANSWER SECTION:
www.google.com.                180     IN      A      209.85.202.105
www.google.com.                180     IN      A      209.85.202.147
www.google.com.                180     IN      A      209.85.202.99
www.google.com.                180     IN      A      209.85.202.106
www.google.com.                180     IN      A      209.85.202.103
www.google.com.                180     IN      A      209.85.202.104

;; Query time: 0 msec
;; SERVER: 127.0.0.53#53(127.0.0.53)
;; WHEN: Fri Aug 09 07:17:37 BST 2024
;; MSG SIZE rcvd: 139

root@ip-10-10-38-111:~#
```

route: The route command shows and employs the routing table available for our system. Basically, a router is used to detect a better way to transfer the packets around a destination.

Syntax:

Route 11.

host: The host command shows the IP address for a hostname and the domain name for an IP address. Also, it is used to get DNS lookup for DNS related issues.

Syntax:

host -t <resourceName>

12.

arp: The arp command is short for Address Resolution Protocol. This command is used to see and include content in the ARP table of the kernel.

Syntax:

1. Arp

13. **iwconfig:** It is a simple command which is used to see and set the system's hostname.

Syntax: Hostname

14. **curl and wget:** These commands are used to download files from CLI from the internet. curl must be specified with the "O" option to get the file, while wget is directly used. **curl Syntax:**

1. curl -O <fileLink>

15. **wget**

Syntax:

1. wget <fileLink>

16. **mtr:** The mtr command is a mix of the traceroute and ping commands. It regularly shows information related to the packets transferred using the ping time of all hops. Also, it is used to see network problems.

Syntax:

1. mtr <path>

17. **whois:** The whois command fetches every website related information. We can get every information of a website, such as an owner and the registration information.

Syntax:

1. mtr <websiteName>

18. **ifplugstatus**: The ifplugstatus command checks whether a cable is currently plugged into a network interface. It is not available in Ubuntu directly. We can install it with the help of the below command:

1. sudo apt-get install ifplugd **Syntax:**

1. Ifplugstatus **iftop**: The iftop command is utilized in traffic monitoring. **tcpdump**: The tcpdump command is widely used in network analysis with other commands of the Linux network. It analyses the traffic passing from the network interface and shows it. When balancing the network, this type of packet access will be crucial.

Syntax:

1. \$ tcpdump -i <network_device>

RESULT :

Basic linux commands are executed successfully.