

EXPT NO : 3 A python program to implement Logistic Model DATE:

AIM: 06/09/24

To write a python program to implement a Logistic Model.

PROCEDURE:

Implementing Logistic method using the iris dataset involve the following steps:

Step 1: Import Necessary Libraries

First, import the libraries that are essential for data manipulation, visualization, and model building.

```
# Step 1: Import Necessary Libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score, confusion_matrix,
classification_report
```

Step 2: Load the Iris Dataset

The iris dataset can be loaded.

```
# Step 2: Load the Dataset
# For this example, we'll use a built-in dataset from sklearn. You can
replace it with your dataset.
from sklearn.datasets import load_iris

# Load the iris dataset

data = load_iris()

X = data.data
```

231501075

```
                                # For binary classification (
y = (data.target == 0).astype(int)  classifying
Iris-setosa)
```

Step 3: Data Preprocessing

Ensure the data is clean and ready for modeling. Since the Iris dataset is clean, minimal preprocessing is needed.

```
# Step 3: Prepare the Data


# Split the dataset into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42)
```

Step 4 : Train a Model

```
# Step 4: Create and Train the Model

model = LogisticRegression()
model.fit(X_train, y_train)
```

OUTPUT :



Step 5 : Make Predictions

Use the model to make predictions based on the independent variable.

```
# Step 5: Make Predictions

y_pred = model.predict(X_test)
```

Step 6 : Evaluate the Model

Evaluate the model performance.

```
# Step 6: Evaluate the Model

accuracy = accuracy_score(y_test, y_pred)
conf_matrix = confusion_matrix(y_test, y_pred)
class_report = classification_report(y_test, y_pred)

# Print evaluation metrics
print(f"Accuracy: {accuracy}")
```

```

print("Confusion Matrix:")
print( conf_matrix )
print("Classification Report:")
print( class_report )

```

OUTPUT :

```

⇒ Accuracy: 1.0
Confusion Matrix:
[[20  0]
 [ 0 10]]
Classification Report:

```

	precision	recall	f1-score	support
0	1.00	1.00	1.00	20
1	1.00	1.00	1.00	10
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

Step 7 :Visualize the Results

Plot the original data points and the fitted regression line.

```


# Step 7: Visualize Results ( Optional )

x_values = np.linspace(-10, 10, 100)
sigmoid_values = 1 / (1 + np.exp(-x_values))

# Plot the sigmoid function
plt.figure(figsize=(10, 5))
plt.plot(x_values, sigmoid_values, label='Sigmoid Function', color='blue')
plt.title('Sigmoid Function')
plt.xlabel('x')
plt.ylabel('σ(x)')
plt.grid()
plt.axhline(0.5, color='red', linestyle='--') # Line at y=0.5
plt.axvline(0, color='gray', linestyle='--') # Line at x=0
plt.legend()
plt.show()

```

OUTPUT :



RESULT:

This step-by-step process will help us to implement Logistic models using the Iris dataset and analyze their performance.