Ex.P: 8
24/1/26

Develop a Customized ping Command to test the Server connectivity

Aim:-

To develop a customized ping command to test the server connectivity.

why is Ping used?

ping is a network diagnostic command used to check a server or host is reachable over a network. It helps verify connectivity between two devices.

what does ping measure?

* Reachability - Check whether destination server can be contacted
* Latency (Response Time) - Measures the time taken for packets to travel the server & back (in milliseconds)
* Packet Loss - Shows whether any packets were lost during transmission

Uses:-

* Verify that a server is online
* Test network connectivity before troubleshooting application
* Measure network response time

* Detect packet loss caused by unstable connection

* perform basic network health checks.

Commands :-

1. Basic ping command

ping www.google.com

output :-

Displays the IP address of the server, the number of packets sent, received, lost and average round trip time.

2. ping Localhost (To check internal network stack)

ping localhost

output :-

Replies from 127.0.0.1 confirm that the TCP/IP stack on the local system is working properly.

3. Ping using Ip address

Ping 8.8.8.8

output :-

Display connectivity and delay time (in millisecond) between your system and Google DNS server

5. Ping with Specific Number of Echo Requests

ping www.google.com -n 5

output:

Sends exactly 5 echo requests and display the result with average time and packet loss summary.

6. ping with packet size specification

ping www.google.com -l 1000

output:

Sends a ping request with a packet size of 1000 bytes, showing transmission performance.

Result:-

The Ping commands were successfully executed in windows Command Prompt. The network connectivity, latency and packet transmission status between the local computer and various servers were verified.