



**DustLabs**

**Point Staking**

**SMART CONTRACT AUDIT**

**22.0.2023**

**Made in Germany by Chainsulting.de**



## Table of contents

1. Disclaimer.....	4
2. Project Overview .....	5
3. Vulnerability & Risk Level .....	6
4. Auditing Strategy and Techniques Applied.....	7
4.1 Methodology .....	7
5. Metrics .....	8
5.1 Tested Contract Files .....	8
5.2 Used Code from other Frameworks/Smart Contracts .....	9
5.3 CallGraph .....	10
5.4 Inheritance Graph .....	11
5.5 Source Lines & Risk .....	12
5.6 Capabilities .....	13
5.7 Source Unites in Scope .....	14
6. Scope of Work .....	15
6.1 Findings Overview .....	16
6.2 Manual and Automated Vulnerability Test.....	17
6.2.1 Overpowered Manager/Owner Rights .....	17
6.2.2 Owner Can Permanently Lock Staked NFTs.....	19
6.2.3 Points Calculation Vulnerability.....	21
6.2.4 Owner Can Disable Staking .....	22
6.2.5 Potential Loss Of Ownership.....	23
6.2.6 Missing Function to Withdraw Collected Fees.....	24

6.2.7 State Variable Could Be Marked As Constant.....	25
6.2.8 Not Emitting Events for Fee Updates.....	25
6.2.9 Unexplicit uint Types.....	27
6.3 SWC Attacks .....	28
6.4 Verify Claims .....	32
6.5 Unit Tests .....	33
7. Executive Summary.....	36
8. About the Auditor .....	37



## 1. Disclaimer

The audit makes no statements or warranties about utility of the code, safety of the code, suitability of the business model, investment advice, endorsement of the platform or its products, regulatory regime for the business model, or any other statements about fitness of the contracts to purpose, or their bug free status. The audit documentation is for discussion purposes only.

The information presented in this report is confidential and privileged. If you are reading this report, you agree to keep it confidential, not to copy, disclose or disseminate without the agreement of Dust Labs. If you are not the intended receptor of this document, remember that any disclosure, copying or dissemination of it is forbidden.

Major Versions / Date	Description
0.1 (20.03.2022)	Layout
0.4 (22.03.2022)	Automated Security Testing Manual Security Testing
0.5 (20.03.2023)	Verify Claims and Test Deployment
0.6 (21.03.2023)	Testing SWC Checks
0.9 (21.03.2023)	Summary and Recommendation
1.0 (22.03.2023)	Final document

## 2. Project Overview

DUST protocol is a decentralized protocol and SPL (Solana Program Library) token created on the Solana blockchain with a starting supply of zero, and a maximum supply of 33,300,000. DUST has an emission schedule with multiple halvings and mining rewards that are earned via staking NFTs. Countless projects have independently adopted DUST within their own ecosystems making it the most used SPL token on the Solana blockchain.

DeGods and Y00ts are two popular nonfungible token (NFT) digital art collections on the Solana blockchain. Both of these projects have attracted attention from the NFT community, offering unique digital artwork and novel features for collectors.

### Website:

<https://degods.com>

<https://www.y00ts.com>

### Twitter:

<https://twitter.com/DeGodsNFT>

<https://twitter.com/y00tsNFT>

### Discord:

<https://discord.gg/dedao>

<https://discord.gg/y00ts>

### Instagram:

<https://www.instagram.com/thedegods>

<https://instagram.com/they00ts>



### 3. Vulnerability & Risk Level

Risk represents the probability that a certain source-threat will exploit vulnerability, and the impact of that event on the organization or system. Risk Level is computed based on CVSS version 3.0.

Level	Value	Vulnerability	Risk (Required Action)
Critical	9 – 10	A vulnerability that can disrupt the contract functioning in a number of scenarios, or creates a risk that the contract may be broken.	Immediate action to reduce risk level.
High	7 – 8.9	A vulnerability that affects the desired outcome when using a contract, or provides the opportunity to use a contract in an unintended way.	Implementation of corrective actions as soon as possible.
Medium	4 – 6.9	A vulnerability that could affect the desired outcome of executing the contract in a specific scenario.	Implementation of corrective actions in a certain period.
Low	2 – 3.9	A vulnerability that does not have a significant impact on possible scenarios for the use of the contract and is probably subjective.	Implementation of certain corrective actions or accepting the risk.
Informational	0 – 1.9	A vulnerability that have informational character but is not effecting any of the code.	An observation that does not determine a level of risk

## 4. Auditing Strategy and Techniques Applied

Throughout the review process, care was taken to evaluate the repository for security-related issues, code quality, and adherence to specification and best practices. To do so, reviewed line-by-line by our team of expert pentesters and smart contract developers, documenting any issues as there were discovered.

### 4.1 Methodology

The auditing process follows a routine series of steps:

1. Code review that includes the following:
  - i. Review of the specifications, sources, and instructions provided to Chainsulting to make sure we understand the size, scope, and functionality of the smart contract.
  - ii. Manual review of code, which is the process of reading source code line-by-line in an attempt to identify potential vulnerabilities.
  - iii. Comparison to specification, which is the process of checking whether the code does what the specifications, sources, and instructions provided to Chainsulting describe.
2. Testing and automated analysis that includes the following:
  - i. Test coverage analysis, which is the process of determining whether the test cases are actually covering the code and how much code is exercised when we run those test cases.
  - ii. Symbolic execution, which is analysing a program to determine what inputs causes each part of a program to execute.
3. Best practices review, which is a review of the smart contracts to improve efficiency, effectiveness, clarify, maintainability, security, and control based on the established industry and academic practices, recommendations, and research.
4. Specific, itemized, actionable recommendations to help you take steps to secure your smart contracts.

## 5. Metrics

The metrics section should give the reader an overview on the size, quality, flows and capabilities of the codebase, without the knowledge to understand the actual code.

### 5.1 Tested Contract Files

The following are the MD5 hashes of the reviewed files. A file with a different MD5 hash has been modified, intentionally or otherwise, after the security review. You are cautioned that a different MD5 hash could be (but is not necessarily) an indication of a changed condition or potential vulnerability that was not within the scope of the review


File	Fingerprint (MD5)
./ERC721PointsStakingV1.sol	941034bcf23327b1c8f091a2a248bb49




## 5.2 Used Code from other Frameworks/Smart Contracts (direct imports)

Dependency / Import Path	Source
@openzeppelin/contracts-upgradeable/access/OwnableUpgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/access/OwnableUpgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/access/OwnableUpgradeable.sol</a>
@openzeppelin/contracts-upgradeable/proxy/utils/UUPSUpgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/proxy/utils/UUPSUpgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/proxy/utils/UUPSUpgradeable.sol</a>
@openzeppelin/contracts-upgradeable/security/PausableUpgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/security/PausableUpgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/security/PausableUpgradeable.sol</a>
@openzeppelin/contracts-upgradeable/security/ReentrancyGuardUpgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/security/ReentrancyGuardUpgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/security/ReentrancyGuardUpgradeable.sol</a>
@openzeppelin/contracts-upgradeable/token/ERC20/IERC20Upgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC20/IERC20Upgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC20/IERC20Upgradeable.sol</a>
@openzeppelin/contracts-upgradeable/token/ERC20/utils/SafeERC20Upgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC20/utils/SafeERC20Upgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC20/utils/SafeERC20Upgradeable.sol</a>
@openzeppelin/contracts-upgradeable/token/ERC721/IERC721Upgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC721/IERC721Upgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC721/IERC721Upgradeable.sol</a>
@openzeppelin/contracts-upgradeable/token/ERC721/utils/ERC721HolderUpgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC721/utils/ERC721HolderUpgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/token/ERC721/utils/ERC721HolderUpgradeable.sol</a>
@openzeppelin/contracts-upgradeable/utils/structs/EnumerableSetUpgradeable.sol	<a href="https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/utils/structs/EnumerableSetUpgradeable.sol">https://github.com/OpenZeppelin/openzeppelin-contracts-upgradeable/tree/v4.8.2/contracts/utils/structs/EnumerableSetUpgradeable.sol</a>



## 5.3 CallGraph




## 5.4 Inheritance Graph



## 5.5 Source Lines & Risk





## 5.6 Capabilities


Solidity Versions observed		 Experimental Features		 Can Receive Funds		 Uses Assembly		 Has Destroyable Contracts			
0.8.19											
 Transfers ETH		 Low-Level Calls		 DelegateCall		 Uses Hash Functions		 ECTrecover		 New/Create/Create2	

### Exposed Functions



This section lists functions that are explicitly declared public or payable. Please note that getter methods for public stateVars are not included.

 Public	 Payable				
15	0				
External	Internal	Private	Pure	View	
14	19	0	0	4	

### StateVariables

Total	 Public
10	8

## 5.7 Source Unites in Scope

Type	File	Logic Contracts	Interfaces	Lines	nLines	nSLOC	Comment Lines	Complex. Score	Capabilities
	contracts/ERC721PointsStakingV1.sol	1	_____	319	302	220	36	195	_____
	<b>Totals</b>	<b>1</b>	_____	<b>319</b>	<b>302</b>	<b>220</b>	<b>36</b>	<b>195</b>	

- **Lines:** total lines of the source unit
- **nLines:** normalized lines of the source unit (e.g. normalizes functions spanning multiple lines)
- **nSLOC:** normalized source lines of code (only source-code lines; no comments, no blank lines)
- **Comment Lines:** lines containing single or block comments
- **Complexity Score:** a custom complexity score derived from code statements that are known to introduce code complexity (branches, loops, calls, external interfaces, ...)

## 6. Scope of Work


The DustLabsTeam provided us with the files that needs to be tested. The scope of the audit is the point staking contract.

The team put forward the following assumptions regarding the security, usage of the contracts:

- Staking and unstaking of NFTs is working as expected.
- Calculation of points is working as expected.
- Privileged functions for owner and manager are working as expected.
- The smart contract is coded according to the newest standards and in a secure way.

The main goal of this audit was to verify these claims. The auditors can provide additional feedback on the code upon the client's request.

## 6.1 Findings Overview



No	Title	Severity	Status
6.2.1	Overpowered Manager/Owner Rights	HIGH	OPEN
6.2.2	Owner Can Permanently Lock Staked NFTs	HIGH	OPEN
6.2.3	Points Calculation Vulnerability	MEDIUM	OPEN
6.2.4	Owner Can Disable Staking	MEDIUM	OPEN
6.2.5	Potential Loss Of Ownership	MEDIUM	OPEN
6.2.6	Missing Function to Withdraw Collected Fees	MEDIUM	OPEN
6.2.7	State Variable Could Be Marked As Constant	LOW	OPEN
6.2.8	Not Emitting Events for Fee Updates	LOW	OPEN
6.2.9	Unexplicit uint Types	INFORMATIONAL	OPEN



## 6.2 Manual and Automated Vulnerability Test

### CRITICAL ISSUES

During the audit, Chainsulting's experts found **no Critical issues** in the code of the smart contract.

### HIGH ISSUES

During the audit, Chainsulting's experts found **2 High issues** in the code of the smart contract.

#### 6.2.1 Overpowered Manager/Owner Rights

Severity: HIGH

Status: OPEN

Code: CWE 264

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	The contract manager can deduct any staking rewards by calling the spendPoints function. The manager is allowed to set any token reward point to zero. Additionally, the manager can set the token reward multiplier for each token to any desired value. This can lead to having no staking to very high staking rewards for any targeted token. Furthermore, the manager is able to set an unlimited amount of initial rewards for any token, that has not been staked before. In the current implementation, the owner can set and change the manager at will, thus the overpowered rights issue implicitly holds for the owner role as well.
<b>Code</b>	Line 245 – 288 (ERC721PointsStakingV1.sol) <pre>function setRewardMultipliers(     uint[] calldata _tokenIds,     uint _newMultiplier ) external nonReentrant managerOnly {     for (uint i = 0; i &lt; _tokenIds.length; i += 1) {         _refreshPoints(_tokenIds[i]);     } }</pre>

```

        stakingMetadata[_tokenIds[i]].multiplier = uint16(_newMultiplier);
    }

    emit MultiplierUpdated(msg.sender, _newMultiplier, _tokenIds);
}

// @notice Initialize points
// @param tokenIds The tokenIds of the NFTs to initialize points for
function initPoints(
    uint[] calldata _tokenIds,
    uint[] calldata _points
) external nonReentrant managerOnly {
    if (_tokenIds.length != _points.length) {
        revert TokenIdsPointsLengthMismatch();
    }
    for (uint i = 0; i < _tokenIds.length; i += 1) {
        StakingMetadata storage metadata = stakingMetadata[_tokenIds[i]];
        if (metadata.lastUpdated != 0) {
            revert PointsInitialized();
        }
        metadata.points = uint32(_points[i]);
        metadata.lastUpdated = uint40(block.timestamp);
        emit SetPoints(msg.sender, _tokenIds[i], metadata.points);
    }
}

// @notice Spend points
// @param tokenIds The tokenIds of the NFTs which will be spent
function spendPoints(uint _tokenId, uint _points) external nonReentrant
managerOnly {
    _refreshPoints(_tokenId);

    StakingMetadata storage metadata = stakingMetadata[_tokenId];

```

	<pre> if (_points &gt; metadata.points) {     revert NotEnoughPoints(); } metadata.points -= uint32(_points); emit SpentPoints(msg.sender, _tokenId, _points); } </pre>
<b>Result/Recommendation</b>	<p>It is recommended to remove overpowered owner rights such as deducting staking rewards at will. If there is a wish for adjustable staking multiplier rates, it is recommended to set a max and min value to ensure a specific range of reward multipliers. The same recommendation holds for setting an initial reward amount for unstaked tokens.</p>

## 6.2.2 Owner Can Permanently Lock Staked NFTs

Severity: HIGH

Status: OPEN

Code: NA

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	<p>The users can unstake their staked NFTs by calling the withdraw function. This function charges a unstakeFee paid with the related unstakeFeeToken (ERC20-Token). The owner has the right to change the unstakeFeeToken to any address and the unstakeFee to any uint96 amount by calling the setFees function. Changing the unstakeFeeToken to an invalid address leads to a function call revert on any withdraw and thus permanent locking of the NFT. Additionally, if the owner set the unstakeFee to a high amount (max uint96), the users are very likely not able to unstake their NFT for a valid unstakeFeeToken.</p>
<b>Code</b>	<pre> Line 168 – 172 (ERC721PointsStakingV1.sol) // Transfer unstake fee to the staking contract unstakeFeeToken.safeTransferFrom(     msg.sender,     address(this), </pre>

	<pre>                                 unstakeFee                                 ); </pre> <p>Line 223 – 233 (ERC721PointsStakingV1.sol)</p> <pre> function setFees(     address _stakeFeeToken,     uint _stakeFee,     address _unstakeFeeToken,     uint _unstakeFee ) external onlyOwner {     stakeFeeToken = IERC20Upgradeable(_stakeFeeToken);     stakeFee = uint96(_stakeFee);     unstakeFeeToken = IERC20Upgradeable(_unstakeFeeToken);     unstakeFee = uint96(_unstakeFee); } </pre>
<b>Result/Recommendation</b>	<p>It is highly recommended to set the <i>unstakeFeeToken</i> to a constant address, supporting the IERC20 interface. Otherwise, it is recommended to check if the new token address implements the IERC20 interface by implementing ERC165 checks. Additionally, it is highly recommended to limit the possible values for <i>unstakeFee</i>, by setting a max value.</p> <p>Having these two parameters in combination changeable, is not a good approach, because a maximum value for one token is not comparable to a maximum for a newly set token (i.e. 5 WETH are not comparable to 5 WBTC). Subsequently, it is highly recommended to set the <i>unstakeFeeToken</i> to a constant address.</p>

## MEDIUM ISSUES

During the audit, Chainsulting's experts found **4 Medium issues** in the code of the smart contract

### 6.2.3 Points Calculation Vulnerability

Severity: MEDIUM

Status: OPEN

Code: CWE-682

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	The current points calculation in the getPoints function may lead to incorrect results due to integer overflow.
<b>Code</b>	<p>Line 86 – 94 (ERC721PointsStakingV1.sol)</p> <pre>function getPoints(uint32 _tokenId) external view returns (uint32) {     StakingMetadata memory metadata = stakingMetadata[_tokenId];     if (metadata.owner == address(0)) {         return metadata.points;     }      uint16 multiplier = metadata.multiplier == 0 ? 100 : metadata.multiplier;     return uint32(metadata.points + (block.timestamp - metadata.lastUpdated) * multiplier / 6000); }</pre>
<b>Result/Recommendation</b>	<p>Use the SafeMath library for arithmetic operations to prevent integer overflows. Update the getPoints function as follows:</p> <pre>import "@openzeppelin/contracts-upgradeable/utils/math/SafeMathUpgradeable.sol"; ... using SafeMathUpgradeable for uint; ... function getPoints(uint32 _tokenId) external view returns (uint32) {     ...     uint16 multiplier = metadata.multiplier == 0 ? 100 : metadata.multiplier;</pre>

	<pre> return uint32(metadata.points.add((block.timestamp.sub(metadata.lastUpdated)).mul(multiplier).div(6000))); } </pre>
--	---

## 6.2.4 Owner Can Disable Staking

Severity: MEDUM

Status: OPEN

Code: NA

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	<p>The users can stake their NFTs by calling the <i>stake</i> function. This function charges a <i>stakeFee</i>, paid with the related <i>stakeFeeToken</i> (ERC20-Token). The owner has the right to change the <i>stakeFeeToken</i> to any address and the <i>stakeFee</i> to any uint96 amount by calling the <i>setFees</i> function. Changing the <i>stakeFeeToken</i> to an invalid address lead to a function call revert, on staking any token even if the contract is unpaused. Additionally, if the owner set the <i>stakeFee</i> to a high amount (max uint96), the users are very likely not able to stake their NFT for a valid <i>stakeFeeToken</i>.</p>
<b>Code</b>	<pre> Line 136 – 137 (ERC721PointsStakingV1.sol) // Transfer stake fee to the staking contract stakeFeeToken.safeTransferFrom(msg.sender, address(this), stakeFee);  Line 223 – 233 (ERC721PointsStakingV1.sol) function setFees(     address _stakeFeeToken,     uint _stakeFee,     address _unstakeFeeToken,     uint _unstakeFee ) external onlyOwner {     stakeFeeToken = IERC20Upgradeable(_stakeFeeToken); </pre>

	<pre> stakeFee = uint96(_stakeFee); unstakeFeeToken = IERC20Upgradeable(_unstakeFeeToken); unstakeFee = uint96(_unstakeFee); } </pre>
<b>Result/Recommendation</b>	<p>It is highly recommended to set the <i>stakeFeeToken</i> to a constant address supporting the IERC20 interface. Otherwise, it is recommended to check if the new token address implements the IERC20 interface by implementing ERC165 checks. Additionally, it is recommended to limit the possible values for <i>stakeFee</i> by setting a max value.</p> <p>Having these two parameters in combination changeable is not a good approach, because a maximum value for one token is not comparable to a maximum for a newly set token (i.e. 5 WETH are not comparable to 5 WBTC). Subsequently, it is highly recommended to set the <i>stakeFeeToken</i> to a constant address.</p>

#### 6.2.5 Potential Loss Of Ownership

Severity: MEDUM

Status: OPEN

Code: NA

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	The owner of the contract can be changed by calling transferOwnership function of OpenZeppelin Ownable implementation. This function directly sets the owner to the given address if the address is not the zero address. Making such a critical change in a single step is error-prone and can lead to irrevocable mistakes.
<b>Code</b>	<p>Line 10 (ERC721PointsStakingV1.sol)</p> <pre> import {OwnableUpgradeable} from "@openzeppelin/contracts-upgradeable/access/OwnableUpgradeable.sol"; </pre>

<b>Result/Recommendation</b>	It is recommended to use the two-step pattern, by setting the new owner as potential owner in the first step and approving the ownership transfer by calling an approve function, by the new owner. OpenZeppelin provides such a Ownable2Step implementation. This prevents transferring ownership to an invalid address.
------------------------------	---

## 6.2.6 Missing Function to Withdraw Collected Fees

Severity: MEDUM

Status: OPEN

Code: CWE-384 (Session Fixation)

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	The contract currently collects stake and unstake fees, but there is no functionality for the owner or manager to withdraw these collected fees. This could lead to a lock-up of funds in the contract with no way to access them.
<b>Code</b>	<p>Line 136 – 137 (ERC721PointsStakingV1.sol)</p> <pre>// Transfer stake fee to the staking contract stakeFeeToken.safeTransferFrom(msg.sender, address(this), stakeFee);</pre> <p>Line 167 – 172 (ERC721PointsStakingV1.sol)</p> <pre>// Transfer unstake fee to the staking contract     unstakeFeeToken.safeTransferFrom(         msg.sender,         address(this),         unstakeFee     );</pre>
<b>Result/Recommendation</b>	It is recommended to implement a restricted fee withdraw function, to claim all collected staking and unstaking fees. Alternatively, it is recommended to implement a fee receiving address to send the tokens directly to an address of choice.



--	--

## LOW ISSUES

During the audit, Chainsulting's experts found **2 Low issues** in the code of the smart contract

### 6.2.7 State Variable Could Be Marked As Constant

Severity: LOW

Status: OPEN

Code: NA

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	The <i>stakingToken</i> variable is defined as normal state variable although it is set once during contract initialization and is never changed.
<b>Code</b>	Line 44 (ERC721PointsStakingV1.sol)  IERC721Upgradeable <b>public</b> stakingToken;
<b>Result/Recommendation</b>	It is recommended to mark the <i>stakingToken</i> state variable as <i>immutable</i> , to symbolize that it is not changeable the staking contract is permanently valid for one ERC721 contract.

### 6.2.8 Not Emitting Events for Fee Updates

Severity: LOW

Status: OPEN

Code: CWE-778 (Insufficient Logging)

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	The contract does not emit any events when updating stake and unstake fees. This makes it difficult for external parties, such as users or third-party services, to track changes in the fee structure.
<b>Code</b>	<p>Line 223 - 233 (ERC721PointsStakingV1.sol)</p> <pre> function setFees(     address _stakeFeeToken,     uint _stakeFee,     address _unstakeFeeToken,     uint _unstakeFee ) external onlyOwner {     stakeFeeToken = IERC20Upgradeable(_stakeFeeToken);     stakeFee = uint96(_stakeFee);     unstakeFeeToken = IERC20Upgradeable(_unstakeFeeToken);     unstakeFee = uint96(_unstakeFee); } </pre>
<b>Result/Recommendation</b>	<p>Implement events for updating stake and unstake fees and emit them in the setFees function. This will provide transparency to users and third-party services about changes in the fee structure of the contract. Example of events to add:</p> <pre> event StakeFeeUpdated(address indexed _stakeFeeToken, uint256 _stakeFee); event UnstakeFeeUpdated(address indexed _unstakeFeeToken, uint256 _unstakeFee); </pre> <p>Example of emitting events in the setFees function:</p> <pre> function setFees(     address _stakeFeeToken,     uint _stakeFee,     address _unstakeFeeToken,     uint _unstakeFee ) external onlyOwner { </pre>

	<pre> stakeFeeToken = IERC20Upgradeable(_stakeFeeToken); stakeFee = uint96(_stakeFee); unstakeFeeToken = IERC20Upgradeable(_unstakeFeeToken); unstakeFee = uint96(_unstakeFee);  emit StakeFeeUpdated(_stakeFeeToken, _stakeFee); emit UnstakeFeeUpdated(_unstakeFeeToken, _unstakeFee); } </pre>
--	---

## INFORMATIONAL ISSUES

During the audit, Chainsulting's experts found **1 Informational issue** in the code of the smart contract

### 6.2.9 Unexplicit uint Types

Severity: INFORMATIONAL

Status: OPEN

Code: NA

File(s) affected: ERC721PointsStakingV1.sol

<b>Attack / Description</b>	The current implementation uses the term uint for defining unsigned integers. This term is implicitly using the uint256.
<b>Code</b>	NA
<b>Result/Recommendation</b>	It is recommended to use uint256 explicitly to indicate that the largest sized unsigned integer is intended to be used. This is a recommendation best on best practices.

## 6.3 SWC Attacks

ID	Title	Relationships	Test Result
<a href="#">SWC-131</a>	Presence of unused variables	<a href="#">CWE-1164: Irrelevant Code</a>	✓
<a href="#">SWC-130</a>	Right-To-Left-Override control character (U+202E)	<a href="#">CWE-451: User Interface (UI) Misrepresentation of Critical Information</a>	✓
<a href="#">SWC-129</a>	Typographical Error	<a href="#">CWE-480: Use of Incorrect Operator</a>	✓
<a href="#">SWC-128</a>	DoS With Block Gas Limit	<a href="#">CWE-400: Uncontrolled Resource Consumption</a>	✓
<a href="#">SWC-127</a>	Arbitrary Jump with Function Type Variable	<a href="#">CWE-695: Use of Low-Level Functionality</a>	✓
<a href="#">SWC-125</a>	Incorrect Inheritance Order	<a href="#">CWE-696: Incorrect Behavior Order</a>	✓
<a href="#">SWC-124</a>	Write to Arbitrary Storage Location	<a href="#">CWE-123: Write-what-where Condition</a>	✓
<a href="#">SWC-123</a>	Requirement Violation	<a href="#">CWE-573: Improper Following of Specification by Caller</a>	✓


ID	Title	Relationships	Test Result
<a href="#">SWC-122</a>	Lack of Proper Signature Verification	<a href="#">CWE-345: Insufficient Verification of Data Authenticity</a>	✓
<a href="#">SWC-121</a>	Missing Protection against Signature Replay Attacks	<a href="#">CWE-347: Improper Verification of Cryptographic Signature</a>	✓
<a href="#">SWC-120</a>	Weak Sources of Randomness from Chain Attributes	<a href="#">CWE-330: Use of Insufficiently Random Values</a>	✓
<a href="#">SWC-119</a>	Shadowing State Variables	<a href="#">CWE-710: Improper Adherence to Coding Standards</a>	✓
<a href="#">SWC-118</a>	Incorrect Constructor Name	<a href="#">CWE-665: Improper Initialization</a>	✓
<a href="#">SWC-117</a>	Signature Malleability	<a href="#">CWE-347: Improper Verification of Cryptographic Signature</a>	✓
<a href="#">SWC-116</a>	Timestamp Dependence	<a href="#">CWE-829: Inclusion of Functionality from Untrusted Control Sphere</a>	✓
<a href="#">SWC-115</a>	Authorization through tx.origin	<a href="#">CWE-477: Use of Obsolete Function</a>	✓
<a href="#">SWC-114</a>	Transaction Order Dependence	<a href="#">CWE-362: Concurrent Execution using Shared Resource with Improper Synchronization ('Race Condition')</a>	✓

ID	Title	Relationships	Test Result
<a href="#">SWC-113</a>	DoS with Failed Call	<a href="#">CWE-703: Improper Check or Handling of Exceptional Conditions</a>	✓
<a href="#">SWC-112</a>	Delegatecall to Untrusted Callee	<a href="#">CWE-829: Inclusion of Functionality from Untrusted Control Sphere</a>	✓
<a href="#">SWC-111</a>	Use of Deprecated Solidity Functions	<a href="#">CWE-477: Use of Obsolete Function</a>	✓
<a href="#">SWC-110</a>	Assert Violation	<a href="#">CWE-670: Always-Incorrect Control Flow Implementation</a>	✓
<a href="#">SWC-109</a>	Uninitialized Storage Pointer	<a href="#">CWE-824: Access of Uninitialized Pointer</a>	✓
<a href="#">SWC-108</a>	State Variable Default Visibility	<a href="#">CWE-710: Improper Adherence to Coding Standards</a>	✓
<a href="#">SWC-107</a>	Reentrancy	<a href="#">CWE-841: Improper Enforcement of Behavioral Workflow</a>	✓
<a href="#">SWC-106</a>	Unprotected SELFDESTRUCT Instruction	<a href="#">CWE-284: Improper Access Control</a>	✓
<a href="#">SWC-105</a>	Unprotected Ether Withdrawal	<a href="#">CWE-284: Improper Access Control</a>	✓
<a href="#">SWC-104</a>	Unchecked Call Return Value	<a href="#">CWE-252: Unchecked Return Value</a>	✓


ID	Title	Relationships	Test Result
<a href="#">SWC-103</a>	Floating Pragma	<a href="#">CWE-664: Improper Control of a Resource Through its Lifetime</a>	✓
<a href="#">SWC-102</a>	Outdated Compiler Version	<a href="#">CWE-937: Using Components with Known Vulnerabilities</a>	✓
<a href="#">SWC-101</a>	Integer Overflow and Underflow	<a href="#">CWE-682: Incorrect Calculation</a>	✓
<a href="#">SWC-100</a>	Function Default Visibility	<a href="#">CWE-710: Improper Adherence to Coding Standards</a>	✓

## 6.4 Verify Claims


6.4.1 Staking and unstaking of NFTs is working as expected

**Status:** tested and verified 


6.4.2 Calculation of points is working as expected

**Status:** tested and verified 

6.4.3 Privileged functions for owner and manager are working as expected

**Status:** tested and verified 

6.4.4 The smart contract is coded according to the newest standards and in a secure way.

**Status:** tested and verified 



## 6.5 Unit Tests

### ERC721 Staking

- ✓ Should initialize properly with correct configuration

#### Owner

- ✓ Should set owner to deployer
- ✓ Should allow owner to pause
- ✓ Should allow owner to unpause
- ✓ Should not allow nonOwner to pause
- ✓ Should not allow nonOwner to unpause
- ✓ Should allow owner to set a manager
- ✓ Should not allow nonOwner to set a manager
- ✓ Should not allow nonOwner to unset a manager
- ✓ Should allow owner to set fees
- ✓ Should not allow nonOwner to set fees

#### Manager

- ✓ Should allow manager to set a reward multiplier
- ✓ Should not allow nonManager to set a reward multiplier
- ✓ Should allow manager to init points
- ✓ Should not allow nonManager to init points
- ✓ Should allow manager to spend points
- ✓ Should not allow spending points if not manager
- ✓ Should emit events correctly

#### Staking

- ✓ Should stake 1 NFT successfully
- ✓ Should stake multiple NFTs successfully
- ✓ Should update fields correctly on second time staking
- ✓ Should revert on staking non-existing tokens

- ✓ Should revert on staking non-owned tokens
- ✓ Should not allow staking of no tokens
- ✓ Should not allow staking when paused
- ✓ Should not allow staking if not enough stake fee
- ✓ Should emit events correctly

#### Withdrawal

- ✓ Should withdraw staked NFTs successfully
- ✓ Should withdraw when paused
- ✓ Should emit events correctly on Withdraw
- ✓ Should not be able to withdraw NFTs staked by other person
- ✓ Should not allow withdraw of no tokens
- ✓ Should not allow withdraw if not enough unstaking fee

#### Points

- ✓ Should accrue points correctly for 1 NFT staked
- ✓ Should get points correctly if time elapsed is not divisible by minutes
- ✓ Should accrue points correctly when staked and multiplier is set
- ✓ Should not accrue points when unstaked
- ✓ Should correctly set points after withdrawal
- ✓ Should init points correctly
- ✓ Should not allow setting points if already set
- ✓ Should not allow setting points if array lengths do not match
- ✓ Should spend points correctly
- ✓ Should not allow spending points if not enough

43 passing (3s)

#### Test Coverage



File	% Stmts	% Branch	% Funcs	% Lines	Uncovered Lines
contracts/	100	95	93.33	98.68	
ERC721PointsStakingV1.sol	100	95	93.33	98.68	168
All files	100	95	93.33	98.68	

## 7. Executive Summary

Two (2) independent Chainsulting experts performed an unbiased and isolated audit of the smart contract codebase.

The main goal of the audit was to verify the claims regarding the security and functions of the smart contract. During the audit, no critical, two high, four medium, two low and one informational issues have been found, after the manual and automated security testing.

We advise the DustLabs team to implement the recommendations to further enhance the code's security and readability.

## 8. About the Auditor

Chainsulting is a professional software development firm, founded in 2017 and based in Germany. They show ways, opportunities, risks and offer comprehensive Web3 solutions. Their services include Web3 development, security and consulting.

Chainsulting conducts code audits on market-leading blockchains such as Solana, Tezos, Ethereum, Binance Smart Chain, and Polygon to mitigate risk and instil trust and transparency into the vibrant crypto community. They have also reviewed and secure the smart contracts of many top DeFi projects.

Chainsulting currently secures [\\$100 billion](#) in user funds locked in multiple DeFi protocols. The team behind the leading audit firm relies on their robust technical know-how in the web3 sector to deliver top-notch smart contract audit solutions, tailored to the clients' evolving business needs.

Check our website for further information: <https://chainsulting.de>

### How We Work



**1** -----

#### PREPARATION

Supply our team with audit ready code and additional materials



**2** -----

#### COMMUNICATION

We setup a real-time communication tool of your choice or communicate via e-mails.



**3** -----

#### AUDIT

We conduct the audit, suggesting fixes to all vulnerabilities and help you to improve.



**4** -----

#### FIXES

Your development team applies fixes while consulting with our auditors on their safety.



**5** -----

#### REPORT

We check the applied fixes and deliver a full report on all steps done.