


Arithmetic for Computers

Binary Representation

Unsigned :

- The binary number



represents the quantity $0 \times 2^{31} + 1 \times 2^{30} + \dots + 1 \times 2^0$

- A 32-bit word can represent 2^{32} numbers between 0 and $2^{32} - 1$ Numbers are always positive

Binary Representation

2's Complement:

32 bits can only represent 2^{32} numbers – if we wish to also represent negative numbers, we can represent 2^{31} positive numbers (incl zero) and 2^{31} negative numbers

0000 0000 0000 0000 0000 0000 0000 0000_{two} = 0_{ten}

0000 0000 0000 0000 0000 0000 0000 0001_{two} = 1_{ten}

...

0111 1111 1111 1111 1111 1111 1111 1111_{two} = $2^{31}-1$

1000 0000 0000 0000 0000 0000 0000 0000_{two} = -2^{31}

1000 0000 0000 0000 0000 0000 0000 0001_{two} = $-(2^{31} - 1)$

1000 0000 0000 0000 0000 0000 0000 0010_{two} = $-(2^{31} - 2)$

...

1111 1111 1111 1111 1111 1111 1111 1110_{two} = -2

1111 1111 1111 1111 1111 1111 1111 1111_{two} = -1

Each number represents the quantity

$$-2^{31} x_{31} + x_{30} 2^{30} + x_{29} 2^{29} + \dots + x_1 2^1 + x_0 2^0$$

Why is this representation favorable?

Consider the sum of 1 and -2 ... we get -1

Consider the sum of 2 and -1 ... we get +1

This format can directly undergo addition without any conversions!

Binary Representation

2's Complement:

0000 0000 0000 0000 0000 0000 0000 0000_{two} = 0_{ten}

0000 0000 0000 0000 0000 0000 0000 0001_{two} = 1_{ten}

...

0111 1111 1111 1111 1111 1111 1111 1111_{two} = $2^{31}-1$

1000 0000 0000 0000 0000 0000 0000 0000_{two} = -2^{31}

1000 0000 0000 0000 0000 0000 0000 0001_{two} = $-(2^{31} - 1)$

1000 0000 0000 0000 0000 0000 0000 0010_{two} = $-(2^{31} - 2)$

...

1111 1111 1111 1111 1111 1111 1111 1110_{two} = -2

1111 1111 1111 1111 1111 1111 1111 1111_{two} = -1

Note that the sum of a number x and its inverted representation x' always equals a string of 1s (-1)

$$x + x' = -1$$

$$x' + 1 = -x$$

$$-x = x' + 1$$


... hence, can compute the negative of a number by inverting all bits and adding 1

Similarly, the sum of x and $-x$ gives us all zeroes, with a carry of 1


In reality, $x + (-x) = 2^n$... hence the name 2's complement

ALU Design


1bit ALU:



Q. How to design 32-bit ALU from 1-bit ALU?




Q. How to do subtraction?




Tailoring the 32-bit ALU to MIPS

slt rd, rs, rt -- if $(rs < rt)$ $rd = 1$; else $rd = 0$

Idea: $(a-b) < 0 \rightarrow a < b$




ALU 0 – ALU 30



ALU 31

Problem: Overflow e.g., $rs = (1001)_2 = -7$ and $rt = (0110)_2 = 6$

How to modify the 1-bit ALU to handle slt correctly?




Unsigned Multiplication (Sequential)

```

1 1 0 1 Multiplicand (13)
1 0 1 1 Multiplier (11)
-----
1 1 0 1
1 1 0 1
0 0 0 0
1 1 0 1
-----
1 0 0 0 1 1 1 1 Product (143)


```



Unsigned Multiplication

Unsigned multiplication:

Initialization			
C	M	Q	
0	1 1 0 1	1 0 1 1	
	A		
	0 0 0 0		
0	1 1 0 1	1 0 1 1	q ₀ = 1 → Add
0	0 1 1 0	1 1 0 1	Shift right
1	0 0 1 1	1 1 0 1	q ₀ = 1 → Add
0	1 0 0 1	1 1 1 0	Shift right
0	1 0 0 1	1 1 1 0	q ₀ = 0 → No Add
0	0 1 0 0	1 1 1 1	Shift right
1	0 0 0 1	1 1 1 1	q ₀ = 1 → Add
0	1 0 0 0	1 1 1 1	Shift right



```

1 1 0 1 Multiplicand (13)
1 0 1 1 Multiplier (11)
-----
1 1 0 1
1 1 0 1
0 0 0 0
1 1 0 1
-----
1 0 0 0 1 1 1 1 Product (143)

```

Signed Multiplication

- Recall grade school trick
 - When multiplying by 9:
 - Multiply by 10 (shift digits left)
 - Subtract once
 - E.g., $12345 \times 9 = 12345 \times (10 - 1)$
 $= 123450 - 12345$
- Booth's algorithm applies same principle
 - Except no '9' in binary, just '1' and '0'
- Search for a run of '1' bits in the multiplier
 - E.g. '0110' has a run of 2 '1' bits in the middle
 - Multiplying by '0110' (6 in decimal) is equivalent to multiplying by 8 and subtracting twice, since $6 \times m = (8 - 2) \times m = 8m - 2m$

Booth's encoding:

Current bit	Bit to right	Explanation	Example	Operation
1	0	Begins run of '1'	0000111 <u>1</u> 00	Subtract
1	1	Middle of run of '1'	000011 <u>1</u> 100	Nothing
0	1	End of a run of '1'	000 <u>0</u> 111100	Add
0	0	Middle of a run of '0'	0000111100	Nothing

Booth's Algorithm

Example: $2 \times -3 = -6$, or $0010 \times 1101 = 1111\ 1010$

M			
0010			
0000	Q	Q ₁	Initialization
A	1101	0	
1110	1101	0	Q ₀ Q ₁ = 10 → Subtract
1111	0110	1	Arithmetic right shift
0001	0110	1	Q ₀ Q ₁ = 01 → Add
0000	1011	0	Arithmetic right shift
1110	1011	0	Q ₀ Q ₁ = 10 → Subtract
1111	0101	1	Arithmetic right shift

Current bit	Bit to right	Operation
1	0	Subtract
1	1	Nothing
0	1	Add
0	0	Nothing

1111	0101	1	$Q_0Q_1 = 11 \rightarrow$ Nothing
1111	1010	1	Arithmetic right shift

Why Booth's Algorithm Works?

Assume a be the multiplier and b be the multiplicand

Booth's algorithm can be written as

$$(a_{-1} - a_0) \times b \times 2^0$$

$$+ (a_0 - a_1) \times b \times 2^1$$

$$+ (a_1 - a_2) \times b \times 2^2$$

... ..

$$+ (a_{29} - a_{30}) \times b \times 2^{30}$$

$$+ (a_{30} - a_{31}) \times b \times 2^{31}$$

Note: $-a_i \times 2^i + a_i \times 2^{i+1} = a_i \times 2^i$ and $a_{-1} = 0$

a_i	a_{i-1}	Operation
1	0	Subtract
1	1	Nothing
0	1	Add
0	0	Nothing

$a_{i-1} - a_i = 0$ Nothing
 $a_{i-1} - a_i = 1$ Add
 $a_{i-1} - a_i = -1$ Subtract

Factoring out b from each term: $b \times ((a_{31} \times -2^{31}) + (a_{30} \times 2^{30}) + \dots + (a_1 \times 2^1) + (a_0 \times 2^0))$

2's complement of a

Unsigned Division

```

1101 100010010 Dividend
Divisor 1101
      10000
      1101
      ---
       1110
       1101
       ---
        1 Remainder
  
```

Restoring division:

Do the following n times

1. Shift A and Q left one bit

2. $A \leftarrow A - M$


3. If the sign of A is 1 i.e., $a_n = 1$

$q_0 \leftarrow 0$

$A \leftarrow A + M$ //Restore

else

$q_0 \leftarrow 1$




After division n -bit quotient is in Q and the remainder is in A

Unsigned Division (Restoring)

Example: Divisor: 11 Dividend: 1000

A	Q	M	
00000	1000	00011	Initialization
00001	000?		Shift left AQ
11101	000?		Subtract $A \leftarrow A - M$
00001	0000		$q_0 \leftarrow 0, A \leftarrow A + M$
00010	000?		Shift left AQ
11111	000?		Subtract $A \leftarrow A - M$
00010	0000		$q_0 \leftarrow 0, A \leftarrow A + M$
00100	000?		Shift left AQ
00001	000?		Subtract $A \leftarrow A - M$
00001	0001		$q_0 \leftarrow 1$
00010	001?		Shift left AQ
11111	001?		Subtract $A \leftarrow A - M$
00010	0010		$q_0 \leftarrow 0, A \leftarrow A + M$
Remainder	Quotient		



Do the following n times

1. Shift A and Q left one bit
2. $A \leftarrow A - M$
3. If the sign of A is 1 i.e., $a_n = 1$
 $q_0 \leftarrow 0$
 $A \leftarrow A + M$ //Restore
 else
 $q_0 \leftarrow 1$

Unsigned Division (Non-restoring)

In restoring division after subtraction what we do?

If A is positive – Shift left AQ and subtract M

➤ $2A - M$

If A is negative – First we restore A by adding M , then we shift left AQ and subtract M

➤ $2(A + M) - M = 2A + M$

Summary: Restore operation is eliminated


In each step, we need to shift and then Add/Subtract

Non-restoring division

Step 1: Do the following n times

1. If the sign of A is 0, Shift left AQ by one bit, and subtract M from A
 otherwise, Shift left AQ by one bit and add M from A
2. Now, if the sign of A is 0, set q_0 to 1; otherwise set q_0 to 0

Step 2 [Sign correction of reminder]: If the sign of A is 1, add M to A



Restoring Division


Do the following n times

1. Shift A and Q left one bit
2. $A \leftarrow A - M$
3. If the sign of A is 1 i.e., $a_n = 1$
 $q_0 \leftarrow 0$
 $A \leftarrow A + M$ //Restore
 else
 $q_0 \leftarrow 1$

Unsigned Division (Non-restoring)

Example: Divisor: 11 Dividend: 1000

A	Q	M	
00000	1000	00011	Initialization
00001	000?		Shift left AQ
11110	000?		Subtract $A \leftarrow A - M$
11110	0000		$q_0 \leftarrow 0$ (A is -ve)
11100	000?		Shift left AQ
11111	000?		Add $A \leftarrow A + M$
11111	0000		$q_0 \leftarrow 0$ (A is -ve)
11110	000?		Shift left AQ
00001	000?		Add $A \leftarrow A + M$
00001	0001		$q_0 \leftarrow 1$ (A is +ve)
00010	001?		Shift left AQ
11111	001?		Subtract $A \leftarrow A - M$
11111	0010		$q_0 \leftarrow 0$ (A is -ve)
Remainder(?) Quotient			



Non-restoring division

Step 1: Do the following n times

1. If the sign of A is 0, Shift left AQ by one bit, and subtract M from A
otherwise, Shift left AQ by one bit and add M from A
2. Now, if the sign of A is 0, set q_0 to 1; otherwise set q_0 to 0

Step 2 [Sign correction of remainder]:

If the sign of A is 1, add M to A

After sign correction, remainder is 00010

Signed Division

Simplest solution: Use unsigned division and negate the quotient if signs of divisor and dividend disagree.

Q. What should be the sign of remainder?

Note: The equation $Dividend = Quotient \times Divisor + Remainder$ must always hold

Example: $-7 \div 2$: $Quotient = -3$,

$$Remainder = Dividend - Quotient \times Divisor = -7 - (-3 \times 2) = -1$$

Note: -4 as quotient also satisfies the formula i.e., $Remainder = -7 - (-4 \times 2) = 1$. However, the absolute value of the quotient would change depending on the sign of the divisor and the dividend. Here, $-(x \div y) \neq (-x) \div y$, which is problematic!

Example: $7 \div -2$: $Quotient = -3$,

$$Remainder = Dividend - Quotient \times Divisor = 7 - (-3 \times -2) = 1$$

Example: $-7 \div -2$: $Quotient = 3$,

$$Remainder = Dividend - Quotient \times Divisor = -7 - (3 \times -2) = -1$$


Rule: Negate the quotient if the sign of divisor and dividend are opposite.

Sign of non-zero remainder matches the dividend.

MIPS Multiplication and Division

Multiplication:

- Two 32-bit registers for product
 - HI: most-significant 32 bits
 - LO: least-significant 32-bits
- Instructions
 - mult rs, rt / multu rs, rt
 - 64-bit product in HI/LO
 - mfhi rd / mflo rd
 - Move from HI/LO to rd
 - Can test HI value to see if product overflows 32 bits



Division:

- Use HI/LO registers for result
 - HI: 32-bit remainder
 - LO: 32-bit quotient
- Instructions
 - div rs, rt / divu rs, rt
 - No overflow or divide-by-0 checking
 - If divisor is 0, result is unpredictable
 - Software must perform checks if required
 - Use mfhi, mflo to access result

Floating Point Numbers

Normalized scientific notation: single non-zero digit to the left of the decimal (binary) point
 – example: 3.5×10^9

Floating-point standard:

- Defined by IEEE Std 754-1985
- Developed in response to divergence of representations
 - Portability issues for scientific code
- Now almost universally adopted
- Two representations
 - Single precision (32-bit)
 - Double precision (64-bit)

IEEE Floating Point Format

single: 8 bits
double: 11 bits

single: 23 bits
double: 52 bits

S	Exponent	Fraction
---	----------	----------

$$x = (-1)^S \times (1 + \text{Fraction}) \times 2^{(\text{Exponent} - \text{Bias})}$$

- S: sign bit (0 $\Rightarrow$ non-negative, 1 $\Rightarrow$ negative)
- **Normalize significand:** $1.0 \leq |\text{significand}| < 2.0$
 - Always has a leading pre-binary-point 1 bit, so no need to represent it explicitly (hidden bit)
 - Significand is Fraction with the "1." restored
- **Exponent:** excess representation: actual exponent + Bias
 - Ensures exponent is unsigned
 - Single: Bias = 127; Double: Bias = 1203

Q. Why excess-127 representation for exponent is used?

Note: More exponent bits $\rightarrow$ wider range of numbers
More fraction bits $\rightarrow$ higher precision

Example

- Represent 0.75
 - $0.75 = 1.1_2 \times 2^{-1}$
 - S = 0
 - Fraction = $1000...00_2$
 - Exponent = $-1 + \text{Bias}$
 - Single: $-1 + 127 = 126 = 01111110_2$
- Single: $001111101000...00$

Q. Represent 0.5

Q. How to represent 0 ?

A. Exponent $00...0$, Fraction: $00...0$

$\pm$ Infinity: Exponent = $111...1$, Fraction = $000...0$

NAN: Exponent = $111...1$, Fraction $\neq 000...0$

Indicates illegal or undefined result e.g., $0.0/0.0$

- What number is represented by the single-precision float

$11000000101000...00$

- S = 1
- Fraction = $01000...00_2$
- Exponent = $10000001_2 = 129$
- $x = (-1)^1 \times (1 + 01_2) \times 2^{(129 - 127)}$
 $= (-1) \times 1.25 \times 2^2$
 $= -5.0$

Single precision		Object represented
Exponent	Fraction	
0	0	0
0	Nonzero	$\pm$ denormalized number
1-254	Anything	$\pm$ floating-point number
255	0	$\pm$ infinity
255	Nonzero	NaN (Not a Number)

Floating Point Numbers

Single Precision Range:

- Exponents 00000000 and 11111111 reserved

Smallest value

Exponent: 00000001

$\Rightarrow$ actual exponent = $1 - 127 = -126$

Fraction: 000...00 $\Rightarrow$ significand = 1.0

$\pm 1.0 \times 2^{-126} \approx \pm 1.2 \times 10^{-38}$

Largest value

exponent: 11111110

$\Rightarrow$ actual exponent = $254 - 127 = +127$

Fraction: 111...11 $\Rightarrow$ significand ≈ 2.0

$\pm 2.0 \times 2^{+127} \approx \pm 3.4 \times 10^{+38}$

Double Precision Range:

- Exponents 0000...00 and 1111...11 reserved

Smallest value

- Exponent: 00000000001

$\Rightarrow$ actual exponent = $1 - 1023 = -1022$

- Fraction: 000...00 $\Rightarrow$ significand = 1.0

$\pm 1.0 \times 2^{-1022} \approx \pm 2.2 \times 10^{-308}$

Largest value


- Exponent: 1111111110

$\Rightarrow$ actual exponent = $2046 - 1023 = +1023$

- Fraction: 111...11 $\Rightarrow$ significand ≈ 2.0

$\pm 2.0 \times 2^{+1023} \approx \pm 1.8 \times 10^{+308}$

Summary



Same rules as above, but the sign bit is 1
Same magnitudes as above, but negative numbers

Floating Point Addition

- Consider a 4-digit binary example ($0.5 + -0.4375$)
 - $1.000_2 \times 2^{-1} + -1.110_2 \times 2^{-2}$

1. Align binary points

Shift number with smaller exponent

$$1.000_2 \times 2^{-1} + -0.111_2 \times 2^{-1}$$

2. Add significands

$$1.000_2 \times 2^{-1} + -0.111_2 \times 2^{-1} = 0.001_2 \times 2^{-1}$$

3. Normalize result & check for over/underflow


$$1.000_2 \times 2^{-4}, \text{ with no over/underflow}$$

4. Round and renormalize if necessary

$$1.000_2 \times 2^{-4} \text{ (no change)} = 0.0625$$

Assumptions of associativity may fail

		$(x+y)+z$	$x+(y+z)$
x	-1.50E+38		-1.50E+38
y	1.50E+38	0.00E+00	
z	1.0	1.0	1.50E+38
		1.00E+00	0.00E+00



Floating Point Multiplication

- Consider a 4-digit binary example
 - $1.000_2 \times 2^{-1} \times -1.110_2 \times 2^{-2}$ (0.5×-0.4375)
- 1. Add exponents
 - Unbiased: $-1 + -2 = -3$
 - Biased: $(-1 + 127) + (-2 + 127) = -3 + 254 - 127 = -3 + 127$
- 2. Multiply significands
 - $1.000_2 \times 1.110_2 = 1.1102 \Rightarrow 1.110_2 \times 2^{-3}$
- 3. Normalize result & check for over/underflow
 - $1.110_2 \times 2^{-3}$ (no change) with no over/underflow
- 4. Round and renormalize if necessary
 - $1.110_2 \times 2^{-3}$ (no change)
- 5. Determine sign: $+ve \times -ve \Rightarrow -ve$
 - $-1.110_2 \times 2^{-3} = -0.21875$

