


CS23336-Introduction to Python Programming

Started on	Sunday, 10 November 2024, 7:17 PM
State	Finished
Completed on	Sunday, 10 November 2024, 8:17 PM
Time taken	59 mins 42 secs
Marks	10.00/10.00
Grade	100.00 out of 100.00

Question 1

Correct
Mark 1.00 out of 1.00
Flag question

Question text

An list contains N numbers and you want to determine whether two of the numbers sum to a given number K. For example, if the input is 8, 4, 1, 6 and K is 10, the answer is yes (4 and 6). A number may be used twice.

Input Format

The first line contains a single integer n , the length of list
The second line contains n space-separated integers, list[i].
The third line contains integer k.

Output Format

Print Yes or No.

Sample Input

7
0 1 2 4 6 5 3
1

Sample Output

Yes

For example:

Input	Result
5 8 9 12 15 3 11	Yes
6 2 9 21 32 43 43 1 4	No

Answer:(penalty regime: 0 %)

```
1- def fun(n,arr,k):
2-     seen=set()
3-     for num in arr:
4-         if (k-num)in seen:
5-             return "Yes"
6-         seen.add(num)
7-     return "No"
8- n=int(input())
9- arr=list(map(int,input().split()))
10- k=int(input())
11- print(fun(n,arr,k))
```

Feedback


Input	Expected Got	
5 8 9 12 15 3 11	Yes	Yes
6 2 9 21 32 43 43 1 4	No	No
6 13 42 31 4 8 9 17	Yes	Yes

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 2

Correct
Mark 1.00 out of 1.00

 Flag question

Question text

Given an array `nums` containing `n` distinct numbers in the range `[0, n]`, return *the only number in the range that is missing from the array*.

Example 1:

Input: `nums = [3,0,1]`
Output: `2`
Explanation: `n = 3` since there are 3 numbers, so all numbers are in the range `[0,3]`. 2 is the missing number in the range since it does not appear in `nums`.

Example 2:

Input: `nums = [0,1]`
Output: `2`
Explanation: `n = 2` since there are 2 numbers, so all numbers are in the range `[0,2]`. 2 is the missing number in the range since it does not appear in `nums`.

Example 3:

Input: `nums = [9,6,4,2,3,5,7,0,1]`
Output: `8`
Explanation: `n = 9` since there are 9 numbers, so all numbers are in the range `[0,9]`. 8 is the missing number in the range since it does not appear in `nums`.

For example:

Test	Result
<code>print(missingNumber([3,0,1]))</code>	<code>2</code>
<code>print(missingNumber([0,1]))</code>	<code>2</code>

Answer:(penalty regime: 0 %)

Reset answer

```
1 def missingNumber(nums):
2     n=len(nums)
3     s=n*(n+1)//2
4     s1=sum(nums)
5     return s-s1
```

Feedback

Test	Expected Got	
<code>print(missingNumber([3,0,1]))</code>	2	2


```
print(missingNumber([0,1]))      2      2

print(missingNumber([9,6,4,2,3,5,7,0,1])) 8      8
```

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 3

Correct
Mark 1.00 out of 1.00
 Flag question

Question text

Balanced strings are those that have an equal quantity of 'L' and 'R' characters.

Given a balanced string s, split it in the maximum amount of balanced strings.

Return the maximum amount of split balanced strings.

Example 1:

Input:

RLRRLRLRL

Output:

4

Explanation: s can be split into "RL", "RRL", "RL", "RL", each substring contains same number of 'L' and 'R'.

Example 2:

Input:

RLLLLRRRLR

Output:

3

Explanation: s can be split into "RL", "LLLR", "LR", each substring contains same number of 'L' and 'R'.

Example 3:

Input:

LLLLRRRR

Output:

1

Explanation: s can be split into "LLLLRRRR".

Constraints:

1 <= s.length <= 1000

s[i] is either 'L' or 'R'.

s is a balanced string.


For example:

Test	Result
print(BalancedStrings('RLRRLRLRL'))	4
print(BalancedStrings('RLLLLRRRLR'))	3

Answer:(penalty regime: 0 %)

Reset answer

```
1 def BalancedStrings(s):
2     b=0
3     c=0
4     for char in s:
5         if char=='L':
6             b+=1
7         else:
8             b-=1
9         if b==0:
10             c+=1
11     return c
```




Feedback

Test	Expected Got
print(BalancedStrings('RLRRLRLRL')) 4	4
print(BalancedStrings('RLLLLRRRLR')) 3	3

Passed all tests!
Correct
Marks for this submission: 1.00/1.00.

Question 4

Correct
Mark 1.00 out of 1.00
 Flag question

Question text

Given an array of integers `nums` which is sorted in ascending order, and an integer `target`, write a function to search `target` in `nums`. If `target` exists, then return its index. Otherwise, return `-1`.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: `nums = [-1,0,3,5,9,12]`, `target = 9`
Output: `4`
Explanation: 9 exists in `nums` and its index is 4

Example 2:

Input: `nums = [-1,0,3,5,9,12]`, `target = 2`
Output: `-1`
Explanation: 2 does not exist in `nums` so return `-1`

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^4 < \text{nums}[i], \text{target} < 10^4$
- All the integers in `nums` are **unique**.
- `nums` is sorted in ascending order.

For example:

Test	Result
print(search([-1,0,3,5,9,12],9)) 4	

Answer:(penalty regime: 0 %)

Reset answer

```
1 def search(nums,target):
2     l,r=0,len(nums)-1
3     while l<=r:
4         m=l+(r-l)//2
5         if nums[m]==target:
6             return m
7         elif nums[m]<target:
8             l=m+1
9         else:
10            r=m-1
11     return -1
```


Feedback

Test	Expected Got
print(search([-1,0,3,5,9,12],9)) 4	4
print(search([-1,0,3,5,9,12],2)) -1	-1

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 5

Correct
Mark 1.00 out of 1.00
 Flag question

Question text

Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

Constraints

1<= string length <= 200

Sample Input 1

experience
enc

Sample Output 1

xpri
Answer:(penalty regime: 0 %)

```
1 def remove(s1,s2):
2     res=''.join([char for char in s1 if char not in s2])
3     return res
4 s1=input()
5 s2=input()
6 print(remove(s1,s2))
```


Feedback

Input	Expected Got
experience enc	xpri xpri

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 6

Correct
Mark 1.00 out of 1.00
 Flag question

Question text

Write a Python program for binary search.

For example:

Input	Result
1,2,3,5,8 6	False
3,5,9,45,42 42	True

Answer:(penalty regime: 0 %)

```
1 def search(arr,t):
2     arr.sort()
3     l,r=0,len(arr)-1
4     while l<=r:
5         m=(l+r)//2
6         if arr[m]==t:
7             return True
8         elif arr[m]<t:
9             l=m+1
10        else:
11            r=m-1
12    return False
13 arr=list(map(int,input().split(',')))
14 t=int(input())
15 print(search(arr,t))
```


Feedback

Input	Expected	Got
1,2,3,5,8 6	False	False
3,5,9,45,42 42	True	True
52,45,89,43,11 11	True	True

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Question 7

Correct
Mark 1.00 out of 1.00
 Flag question

Question text

Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

Input Format:

The first line contains S1.
The second line contains S2.
The third line contains N.

Output Format:

The first line contains the N characters present in S1 which are also present in S2.

Boundary Conditions:

2 <= N <= 10
2 <= Length of S1, S2 <= 1000

Example Input/Output 1:

Input:

abcbde
cdefghbb
3

Output:

bcd

Note:

b occurs twice in common but must be printed only once.

Answer:(penalty regime: 0 %)

```
1 def fun(s1,s2,n):  
2     res=[]  
3     seen=set()  
4     for char in s1:  
5         if char in s2 and char not in seen:  
6             res.append(char)  
7             seen.add(char)  
8         if len(res)==n:  
9             break  
10    return ''.join(res)  
11 s1=input()  
12 s2=input()  
13 n=int(input())  
14 print(fun(s1,s2,n))
```

Feedback

Input Expected Got

abcbde	
cdefghbb bcd	bcd
3	

Passed all tests!


Correct

Marks for this submission: 1.00/1.00.

Question 8

Correct

Mark 1.00 out of 1.00

 Flag question

Question text

You are given an $m \times n$ integer matrix `matrix` with the following two properties:

- Each row is sorted in non-decreasing order.
- The first integer of each row is greater than the last integer of the previous row.

Given an integer `target`, return `True` *if target is in matrix* or `False` *otherwise*.

You must write a solution in $O(\log(m * n))$ time complexity.

Example 1:



Input: `matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]]`, `target = 3`
Output: `True`

Example 2:



Input: `matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]]`, `target = 13`
Output: `False`

For example:

Test	Result
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))</code>	False
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))</code>	True

Answer:(penalty regime: 0 %)

Reset answer


```
1- def searchMatrix(m,t):
2-     if not m or not m[0]:
3-         return False
4-     r,c=len(m),len(m[0])
5-     l,r=0,r*c-1
6-     while l<=r:
7-         mid=(l+r)//2
8-         midl=m[mid//c][mid%c]
9-         if midl==t:
10-             return True
11-         elif midl<t:
12-             l=mid+1
13-         else:
14-             r=mid-1
15-     return False
16-
```

Feedback

Test	Expected	Got
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))</code>	False	False
<code>print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))</code>	True	True

Passed all tests!
Correct
Marks for this submission: 1.00/1.00.

Question 9

Correct
Mark 1.00 out of 1.00
 Flag question

Question text

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element a[i] is a peak element if

A[i-1] <= A[i] >=a[i+1] for middle elements. [0<i<n-1]

A[i-1] <= A[i] for last element [i=n-1]

A[i]>=A[i+1] for first element [i=0]

Input Format

The first line contains a single integer n , the length of A .
The second line contains n space-separated integers,A[i].

Output Format

Print peak numbers separated by space.

Sample Input

5
8 9 10 2 6

Sample Output

10 6

For example:

Input Result

12 3 6 8 12 8

Answer:(penalty regime: 0 %)


```
1 def find(n,arr):
2     peaks=[]
3     for i in range(n):
4         if i==0:
5             if n==1 or arr[i]>=arr[i+1]:
6                 peaks.append(arr[i])
7         elif i==n-1:
8             if arr[i]>=arr[i-1]:
9                 peaks.append(arr[i])
10        else:
11            if arr[i]>=arr[i-1] and arr[i]>=arr[i+1]:
12                peaks.append(arr[i])
13    return peaks
14 n=int(input())
15 arr=list(map(int,input().split()))
16 peaks=find(n,arr)
17 print(" ".join(map(str,peaks)))
```

Feedback

Input	Expected	Got
7 15 7 10 8 9 4 6	15 10 9 6	15 10 9 6
4 12 3 6 8	12 8	12 8

Passed all tests!
Correct
Marks for this submission: 1.00/1.00.

Question 10

Correct
Mark 1.00 out of 1.00
 Flag question

Question text

String should contain only the words are not palindrome.

Sample Input 1

Malayalam is my mother tongue

Sample Output 1

is my mother tongue

Answer:(penalty regime: 0 %)

```
1 def ispalindrome(word):
2     i=0
3     j=len(word)-1
4     while i<j:
5         if word[i]!=word[j]:
6             return False
7         i+=1
8         j-=1
9     return True
10 words=input().lower().split(" ")
11 for word in words:
12     if not ispalindrome(word):
13         print(word,end=" ")
```

Feedback

Input	Expected	Got
Malayalam is my mother tongue	is my mother tongue	is my mother tongue

Passed all tests!

Correct
Marks for this submission: 1.00/1.00.

Finish review

[Skip Quiz navigation](#)

Quiz navigation

[Question 1 This page](#) [Question 2 This page](#) [Question 3 This page](#) [Question 4 This page](#) [Question 5 This page](#) [Question 6 This page](#) [Question 7 This page](#) [Question 8 This page](#) [Question 9 This page](#) [Question 10 This page](#)

[Show one page at a time](#) Finish review