








GE23131-Programming Using C-2024

Navigation

- **∨** Dashboard
- **?** Site home
- > Site pages
- ✓ My courses
 - **∨** GE23131-PUC-2024

- > Participants
- Competencies
- **Grades**
- > General
- > Skill Test-01-MCQ & Coding
- > Lecture Notes
- > Week-01-Overview of C, Constants, Variables and Da...
- > Assessment-01-Overview of C, Constants, Variables ...
- > Week-02-Operators and Expressions, Managing Input ...
- > Assessment-02-Operators and Expressions, Managing




This quiz has been configured so that students may only attempt it using the Safe Exam Browser.

Time limit: 1 hour 30 mins

Grading method: Highest grade

Your attempts



Attempt 1		
Status	Finished	
Started	Sunday, 12 January 2025, 11:48 PM	
Completed	Monday, 13 January 2025, 1:18 AM	
Duration	1 hour 30 mins	
Review		

The Safe Exam Browser keys could not be validated. Check that you're using Safe Exam Browser with the correct configuration file.

Launch Safe Exam Browser

Download configuration




































GE23131-Programming Using C-2024





Correct Flag question

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- the sum of the first three elements, 1+2+3=6. The value of the last element is 6.
- Using zero based indexing, arr[3]=4 is the pivot between the two subarrays.
- The index of the pivot is 3.

Function Description

Complete the function balancedSum in the editor below.

























It is guaranteed that a solution always exists.

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n, the size of the array arr.

Each of the next n lines contains an integer, arr[i], where $0 \le i < n$.

Sample Case 0

Sample Input 0

STDIN Function Parameters

$$4 \rightarrow arr[] size n = 4$$

$$1 \rightarrow arr = [1, 2, 3, 3]$$

3

3

Sample Output 0






























△ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=163196&cmid=406

REC-CIS

Explanation 0

- The sum of the first two elements, 1+2=3. The value of the last element is 3.
- Using zero based indexing, arr[2]=3 is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1

Sample Input 1

STDIN Function Parameters

$$3 \rightarrow arr[] size n = 3$$

$$\rightarrow$$
 arr = [1, 2, 1]

Sample Output 1

Explanation 1





















```
Answer: (penalty regime: 0 %)
```


Reset answer

```
* Complete the 'balancedSum' function below.
     * The function is expected to return an INTEGER.
     * The function accepts INTEGER_ARRAY arr as parameter.
    int balancedSum(int arr count, int* arr)
 9 ,
     int left sum=0;
10
     for(int i=0;i<arr_count;i++){</pre>
11 v
         left_sum+=arr[i];
12
         for(int j=arr_count;j>arr_count/2;j--){
13 1
             if(left_sum==arr[j]) return arr_count-(i+1);
14
15
16
17
     return -1;
18
19
```

	Test	Expected	Got	
~	<pre>int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr))</pre>	2	2	~

Passed all tests! <



























Each of the next n lines contains an integer numbers[i] where $0 \le i < n$.

Sample Case 0

Sample Input 0

Function STDIN

$$5 \rightarrow numbers[] size n = 5$$

1
$$\rightarrow$$
 numbers = [1, 2, 3, 4, 5]

2

3

5

Sample Output 0

15

Explanation 0

$$1 + 2 + 3 + 4 + 5 = 15$$
.

Sample Case 1

Sample Input 1



















⚠ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=163196&cmid=406

REC-CIS

```
The function accepts INTEGER_ARRAY numbers as parameter.
     */
6
    int arraySum(int numbers_count, int *numbers)
        int sum=0;
10
        for(int i=0;i<numbers_count;i++){</pre>
11
            sum+=numbers[i];
12
13
14
        return sum;
15
16
```

	Test	Expected	Got	
~	<pre>int arr[] = {1,2,3,4,5}; printf("%d", arraySum(5, arr))</pre>	15	15	~

Passed all tests! <

Question 3

Correct

Flag question

Given an array of n integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example n = 5 arr = [1, 3, 3, 2, 4] If the list is rearranged as arr' = [1, 2, 3, 3, 4], the absolute differences are |1-2|=1, |2-3|=1, |3-3|=0, |3-4|=1. The sum of those differences is 1+1+0+1=3. Function Description Complete the function minDiff in the editor below. minDiff has the following parameter: arr: an integer array Returns: int: the sum of the absolute differences of adiacent elements Constraints 2 < n <105 0 < arr[i] < 109. where 0 < i < n Input Format For Custom Testing The first line of input contains an



















⚠ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=163196&cmid=406

REC-CIS

Explanation n = 2 arr = [3, 2] There is no need to rearrange because there are only two elements. The final answer is |3 - 2| = 1.

Answer: (penalty regime: 0 %)

Reset answer

```
* Complete the 'minDiff' function below.
     * The function is expected to return an INTEGER.
     * The function accepts INTEGER ARRAY arr as parameter.
 6
     int minDiff(int arr count, int* arr)
 9 ,
        int sum=0;
10
        for(int i=0;i<arr_count;i++){</pre>
11 1
12 1
             for(int j=i+1; j<arr count; j++){</pre>
                 if(arr[i]>arr[j]){
13 1
                     int temp=arr[i];
14
                     arr[i]=arr[j];
15
                     arr[j]=temp;
16
17
18
19
        for(int i=0;i<arr count-1;i++){</pre>
20
             if(arr[i]<arr[i+1]) sum+=(arr[i+1]-arr[i]);</pre>
21
             else sum+=(arr[i]-arr[i+1]);
22
23
24
        return sum;
25
26
```

Test

Expected Got























⚠ Not secure rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=163196&cmid=406

REC-CIS

```
int minDiff(int arr_count, int* arr)
 9 ,
10
        int sum=0;
        for(int i=0;i<arr_count;i++){</pre>
11 v
            for(int j=i+1; j<arr_count; j++){</pre>
12 1
                 if(arr[i]>arr[j]){
13 🔻
                     int temp=arr[i];
14
                     arr[i]=arr[j];
15
                     arr[j]=temp;
16
17
18
19
        for(int i=0;i<arr_count-1;i++){</pre>
20
            if(arr[i]<arr[i+1]) sum+=(arr[i+1]-arr[i]);
21
            else sum+=(arr[i]-arr[i+1]);
22
23
24
        return sum;
25
26
```

	Test	Expected	Got	
~	<pre>int arr[] = {5, 1, 3, 7, 3}; printf("%d", minDiff(5, arr))</pre>	6	6	~

Passed all tests! <

Finish review



















