

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Tuesday, 26 November 2024, 12:30 PM
Duration	27 days 5 hours

Question 1

Correct

Marked out of 3.00

Flag question

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int x,y;
5     scanf("%d %d",&x,&y);
6     if(x%10==y%10)
7     {
8         printf("true");
9     }
10    else{
11        printf("false");
12    }
13    return 0;
14 }
```

Input	Expected	Got
-------	----------	-----

✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 [Flag question](#)

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, ***n***, perform the following conditional actions:

- If ***n*** is odd, print **Weird**
- If ***n*** is even and in the inclusive range of **2** to **5**, print ***Not Weird***
- If ***n*** is even and in the inclusive range of **6** to **20**, print ***Weird***
- If ***n*** is even and greater than **20**, print ***Not Weird***

Complete the stub code provided in your editor to print whether or not ***n*** is weird.

Input Format

A single line containing a positive integer, ***n***.

Constraints

- $1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print **Weird**.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n;
4     scanf("%d",&n);
5     if(n%2==0){
6         if(n>20&&n%4==0)
```

```

6      if (n%2==0)
7      {
8          printf("Not Weird");
9      }
10     else if (n>=6&& n<=20)
11     {
12         printf("Weird");
13     }
14     else{
15         printf("Not Weird");
16     }
17
18 }
19 else
20 {
21     printf("Weird");
22 }
23 return 0;
24 }

```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of
7.00

Flag question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main()
3  {
4      int a,b,c;
5      scanf("%d %d %d",&a,&b,&c);
6      if((a*a==b*b+c*c) || (b*b==c*c+a*a) || (c*c==a*a+b*b))
7      {
8          printf("yes");
9      }

```

```

10     else
11     {
12         printf("no");
13     }
14     return 0;
15 }

```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review