15 · Landing page

The public home page for visitors who are not signed in.

New to the syntax? Read **00 · How to read this code** first; this guide explains what is specific to this feature.

What this feature does

The landing page introduces HealthNexus with a hero section, feature and community showcases, a community-insights chart, a privacy banner, a final call to action and a footer. Signed-in users never see it: they are sent to their own home.

All the text lives in `content/landing.ts`, separate from the layout, so wording can change without touching components. The chart section is only loaded when the visitor scrolls near it, to keep the first load fast.

Files involved

Only the files this feature uses.

```
frontend/src/
├── pages/LandingPage.tsx                  puts the sections together
├── content/landing.ts                     every piece of landing-page text and the icons
├── components/landing/                    one folder per section, each with .tsx + .module.css
│   ├── Hero/  FeatureShowcase/  CommunityShowcase/  CommunityInsights/
│   ├── PrivacyBanner/  FinalCta/  Footer/  LandingNavbar/  PhoneMockup/  Eyebrow/
│   └── index.ts                           re-exports every section
├── components/ui/LazySection/LazySection.tsx   load a section only when it is near the screen
└── components/RedirectIfAuthenticated.tsx      sends signed-in users away from public pages
```

Code walkthrough

Every excerpt below is copied straight from the file, with its real line numbers, when this guide was generated.

1. `frontend/src/pages/LandingPage.tsx` · LandingPage

```tsx
28  export function LandingPage() {
29    return (
30      <>
31        <LandingNavbar />
32        <main>
33          <Hero />
34          <FeatureShowcase />
35          <CommunityShowcase />
36          <LazySection placeholder={<ChartSectionFallback />}>
37            <Suspense fallback={<ChartSectionFallback />}>
38              <CommunityInsights />
39            </Suspense>
40          </LazySection>
41          <PrivacyBanner />
42          <FinalCta />
43        </main>
44        <Footer />
45      </>
46    );
47  }
```

What the code means

- `<>...</>` is a **fragment**: groups elements without adding an extra box to the page.
- The sections are plain components in order. `<main>` marks the main content for screen readers.
- `<LazySection placeholder=...>` delays the chart section; `<Suspense fallback=...>` shows the placeholder while its code downloads.

2. `frontend/src/pages/LandingPage.tsx` · ChartSectionFallback

```
20  function ChartSectionFallback() {
21    return (
22      <div id={insights.id} className={styles.chartFallback} role="status">
23        <span className="visually-hidden">{chartFallbackLabel}</span>
24      </div>
25    );
26  }
```

What the code means

- A fixed-height placeholder so the page does not jump when the chart arrives. It keeps the section's `id`, so links to `#insights` still work.
- `styles.chartFallback` comes from a **CSS module** (`LandingPage.module.css`): class names are local to this file.

3. `frontend/src/components/ui/LazySection/LazySection.tsx` · LazySection

```
16  export function LazySection({ children, placeholder, rootMargin = "600px 0px" }: LazySectionProps) {
17    const ref = useRef<HTMLDivElement>(null);
18    const [near, setNear] = useState(false);
19
20    useEffect(() => {
21      const node = ref.current;
22      if (!node || near) return;
23      if (typeof IntersectionObserver === "undefined") {
24        setNear(true);
25        return;
26      }
27      const observer = new IntersectionObserver(
28        ([entry]) => {
29          if (entry?.isIntersecting) {
30            setNear(true);
31            observer.disconnect();
32          }
33        },
34        { rootMargin },
35      );
36      observer.observe(node);
37      return () => observer.disconnect();
38    }, [near, rootMargin]);
39
40    return near ? <>{children}</> : <div ref={ref}>{placeholder}</div>;
41  }
```

What the code means

- `IntersectionObserver` is a browser feature that reports when an element comes near the visible area; `rootMargin: "600px 0px"` starts 600 px early.
- Once near, `setNear(true)` re-draws the component; `observer.disconnect()` in the clean-up stops watching.
- Old browsers without `IntersectionObserver` simply load the section straight away.
- The last line chooses what to draw: the real section once near, otherwise the placeholder inside a `<div ref={ref}>` that the observer watches.

4. `frontend/src/content/landing.ts` · content/landing.ts (shape of a heading)

```
25  export interface Heading {
26    lead: string;
27    emphasis: string;
28    tail: string;
29  }
```

What the code means

- Headings are stored in three parts so the middle word can be styled differently (italic serif) without HTML inside the text.

Syntax used in this feature

Code	What it means
`<>...</>`	A fragment: several elements without a wrapper.
`<Suspense fallback={x}>`	Show x while lazy-loaded code downloads.
`import styles from "./X.module.css"`	A CSS module: class names local to the component.
`new IntersectionObserver(cb, opts)`	Get told when an element scrolls near the screen.