

Homework 3

Question 3.a

```
SELECT name
FROM inode
WHERE type = "FILE"
      AND mtime = (
        SELECT max(mtime)
        FROM inode
        WHERE type = "FILE"
      );
```

```
mysql> SELECT name
-> FROM inode
-> WHERE type = "FILE"
->      AND mtime = (
->          SELECT max(mtime)
->          FROM inode
->          WHERE type = "FILE"
->      );
+-----+
| name          |
+-----+
| yarn-site.xml |
+-----+
1 row in set (0.00 sec)
```

Question 3.b

```
SELECT name
FROM inode
WHERE permission LIKE "%6%";
```

```
mysql> SELECT name
-> FROM inode
-> WHERE permission LIKE "%6%";
+-----+
| name          |
+-----+
| a.txt          |
| b.txt          |
| capacity-scheduler.xml |
| core-site.xml  |
| hadoop-policy.xml |
| hdfs-site.xml  |
| httpfs-site.xml |
| kms-acls.xml   |
| kms-site.xml   |
| mapred-site.xml |
| yarn-site.xml  |
| capacity-scheduler.xml |
| core-site.xml  |
| hadoop-policy.xml |
| hdfs-site.xml  |
| httpfs-site.xml |
| kms-acls.xml   |
| kms-site.xml   |
| mapred-site.xml |
| yarn-site.xml  |
| capacity-scheduler.xml |
| core-site.xml  |
| hadoop-policy.xml |
| hdfs-site.xml  |
| httpfs-site.xml |
| kms-acls.xml   |
| kms-site.xml   |
| mapred-site.xml |
| yarn-site.xml  |
+-----+
29 rows in set (0.00 sec)
```

Question 3.c

```
SELECT i.id,
       i.name,
       b.numBytes
from inode as i,
     blocks as b
where type = "FILE"
     and i.id = b.inumber;
```

```
mysql> SELECT i.id,
->      i.name,
->      b.numBytes
-> from inode as i,
->      blocks as b
-> where type = "FILE"
->      and i.id = b.inumber;
```

id	name	numBytes
16389	a.txt	19
16390	b.txt	19
16392	capacity-scheduler.xml	8260
16393	core-site.xml	874
16394	hadoop-policy.xml	11392
16395	hdfs-site.xml	853
16396	httpfs-site.xml	620
16397	kms-acls.xml	3518
16398	kms-site.xml	682
16399	mapred-site.xml	758
16400	yarn-site.xml	690
16403	capacity-scheduler.xml	8260
16404	core-site.xml	874
16405	hadoop-policy.xml	11392
16406	hdfs-site.xml	853
16407	httpfs-site.xml	620
16408	kms-acls.xml	3518
16409	kms-site.xml	682
16410	mapred-site.xml	758
16411	yarn-site.xml	690
16414	capacity-scheduler.xml	8260
16415	core-site.xml	874
16416	hadoop-policy.xml	11392
16417	hdfs-site.xml	853
16418	httpfs-site.xml	620
16419	kms-acls.xml	3518
16420	kms-site.xml	682
16421	mapred-site.xml	758
16422	yarn-site.xml	690

```
29 rows in set (0.00 sec)
```

Question 3.d

```
SELECT i.id,
       i.name,
       count(d.child) as num_obj
from inode as i
JOIN directory d ON i.id = d.parent
GROUP BY i.id,
       i.name;
```

```
mysql> SELECT i.id,
->      i.name,
->      count(d.child) as num_obj
-> from inode as i
->      JOIN directory d ON i.id = d.parent
-> GROUP BY i.id,
->      i.name;
```

id	name	num_obj
16385		1
16386	user	1
16387	ec2-user	5
16388	input1	1
16391	input	9
16401	inf551	1
16402	input	9
16412	inf351	1
16413	input	9

```
9 rows in set (0.00 sec)
```

Question 3.e

```

SELECT i.name
FROM inode as i
JOIN (
  SELECT parent,
    count(child) as num_files
  from (
    SELECT d.parent,
      d.child
    FROM directory as d
    JOIN inode i on i.id = d.child
    WHERE type = "FILE"
  ) as t
  GROUP BY parent
  HAVING num_files > 2
) as x ON i.id = x.parent;

```

```

mysql> SELECT i.name
-> FROM inode as i
-> JOIN (
->   SELECT parent,
->     count(child) as num_files
->   from (
->     SELECT d.parent,
->       d.child
->     FROM directory as d
->     JOIN inode i on i.id = d.child
->     WHERE type = "FILE"
->   ) as t
->   GROUP BY parent
->   HAVING num_files > 2
-> ) as x ON i.id = x.parent;
+-----+
| name |
+-----+
| input |
| input |
| input |
+-----+
3 rows in set (0.00 sec)

```