

KUET_NlogN Team Notebook

Kazi Rifat Al Muin, Siyam Khan,
Hassan Mohammad Naquibul Hoque

Contents

1 Data Structure	1
1.1 DSU [23 lines] - 72e19576	1
1.2 Dsu With Rollback [90 lines] - b7e8efda	1
1.3 MO with Update [43 lines] - a0826346	2
1.4 MO [28 lines] - ec9fc177	2
1.5 Segment Tree Lazy [73 lines] - 1b64fde6	2
1.6 Segment Tree [41 lines] - 17c5e235	3
1.7 Trie Bit [61 lines] - 25d39ae1	3
2 Dynamic Programming	3
2.1 Digit Dp [19 lines] - f18e4b74	3
2.2 Divide and Conquer DP [26 lines] - 6000baee	3
2.3 Dynamic Convex Hull Trick [66 lines] - 86f3d1cf	3
2.4 Knapsack DP [12 lines] - ef62fd72	4
2.5 Knuth Optimization [32 lines] - 5f2f74dc	4
2.6 LIS O(nlogn) with full path [17 lines] - bcb566b7	4
2.7 SOS DP [18 lines] - e5398562	4
2.8 Sibling DP [26 lines] - 95945016	4
3 Flow	4
3.1 Blossom [59 lines] - a41c2f2c	4
3.2 Flow [21 lines] - ae00b72c	5
3.3 HopcroftKarp [66 lines] - 779699b6	5
3.4 kuhn [34 lines] - 8b05d01e	5
4 Game Theory	6
4.1 Inclusion Exclusion with Nim [33 lines] - 1a428d17	6
4.2 Points to be noted [14 lines] - 69c18f5f	6
5 Geometry	6
5.1 Basic Geometry [113 lines] - 00878049	6
5.2 Geometry [536 lines] - 349abbca	7
5.3 Rotation Matrix [39 lines] - d41f8b6c	10
6 Graph	10
6.1 Articulation Bridge [24 lines] - ce2d2a56	10
6.2 Articulation Point [25 lines] - ce1ae03f	11
6.3 Basic [137 lines] - 5a88e77e	11
6.4 Centroid Decomposition [39 lines] - f24b6f45	11
6.5 DSU on Tree [56 lines] - b5007715	12
6.6 Heavy Light Decomposition [73 lines] - 74d2c2ea	12
6.7 K'th Shortest path [40 lines] - 1294302c	12
6.8 LCA [121 lines] - 3f335059	13
6.9 Multisource BFS [75 lines] - d8742599	13
6.10 SCC [31 lines] - 9982799c	14
6.11 Tree [48 lines] - 8fa963f9	14
7 Math	14
7.1 Basic [132 lines] - 7c2ca56e	14
7.2 CRT [52 lines] - ff3bd658	15

7.3 Coprime Subsequence Mobius [31 lines] - dc967df5	15
7.4 Extended GCD [19 lines] - 45160ec3	15
7.5 FFT [85 lines] - 5ed04be4	16
7.6 GaussElimination [39 lines] - 1203a4bb	16
7.7 GaussMod2 [44 lines] - 1d49c381	16
7.8 Karatsuba Idea [5 lines] - 6686aa78	17
7.9 Linear Diophantine [19 lines] - ebfad56a	17
7.10 Matrix [100 lines] - 60a4fb89	17
7.11 Miller-Rabin-Pollard-Rho [46 lines] - d12e2f09	17
7.12 NTT [96 lines] - b8108f51	18
7.13 No of Digits in n! in base B [7 lines] - 21d4aeb2	18
7.14 SOD Upto N [42 lines] - 10b7fcd5	18
7.15 Sieve Phi Mobius [26 lines] - 966c3571	18
7.16 nCr [46 lines] - 79b48d4a	19
8 Misc	19
8.1 BigSum [35 lines] - 2a3cf6fd	19
8.2 Bit Hacks [51 lines] - 15b43442	19
8.3 Bitset C++ [33 lines] - 62a433dd	19
8.4 Custom Hash [19 lines] - 496c4203	20
8.5 Important [94 lines] - a982d219	20
8.6 N-Queen [15 lines] - c51ac310	20
8.7 Template [33 lines] - 52af6a79	20
8.8 debug scripts [49 lines] - 72496740	21
8.9 pbds inversions [21 lines] - 9cb3c2cf	21
8.10 sublime-build [12 lines] - ea28f58d	21
9 String	21
9.1 Double Hasing [50 lines] - f434a7a8	21
9.2 KMP [33 lines] - c11dbb44	22
9.3 Manacher [41 lines] - c534b74d	22
9.4 Palindromic Tree [30 lines] - b398a8f0	22
9.5 Prefix Function Automaton [21 lines] - 5a2cc30b	22
9.6 Suffix Array [78 lines] - 582667ab	22
9.7 Trie [28 lines] - 6b8f900b	23
9.8 Z-Algorithm [11 lines] - 3923b6ef	23
10 Random	23
10.1 Combinatorics	23
10.1.1 Catalan Number	23
10.1.2 Stirling Number of the First Kind	23
10.1.3 Stirling Numbers of the Second Kind	24
10.1.4 Bell Number	24
10.1.5 Lucas Theorem	24
10.1.6 Derangement	24
10.1.7 Burnside Lemma	24
10.1.8 Eulerian Number	24
10.2 Number Theory	24
10.2.1 Mobius Function and Inversion	24
10.2.2 GCD and LCM	24
10.2.3 Gauss Circle Theorem	24
10.2.4 Pick's Theorem	24
10.2.5 Formula Cheatsheet	25
10.2.6 3D Geometry	25

1 Data Structure

1.1 DSU [23 lines] - 72e19576

```
vector<ll> par, sum, diff, sz;
ll find(ll a) {
    if(par[a] == a) return a;
    ll root = find(par[a]); // recursion should be called first to update diff & par
    diff[a] += diff[par[a]]; // adds all parent offset
    return par[a] = root;
}
void merge(ll a, ll b){
    ll ra = find(a);
    ll rb = find(b);
    if(ra != rb){
        if(sz[ra] <= sz[rb]){
            par[ra] = rb;
            sz[rb] += sz[ra];
            diff[ra] = sum[ra] - sum[rb];
        }
        else{
            par[rb] = ra;
            sz[ra] += sz[rb];
            diff[rb] = sum[rb] - sum[ra];
        }
    }
}
```

1.2 Dsu With Rollback [90 lines] - b7e8efda

```
struct dsu_save {
    int v, rnk, u, rnku;
    dsu_save() {}
    dsu_save(int _v, int _rnk, int _u, int _rnku) : v(_v), rnk(_rnk), u(_u), rnku(_rnku) {}
};
struct dsu_with_rollback {
    vector<int> p, rnk;
    int comps;
    stack<dsu_save> op;
    dsu_with_rollback() {}
    dsu_with_rollback(int n) {
        p.resize(n);
        rnk.resize(n);
        for (int i = 0; i < n; i++) {
            p[i] = i;
            rnk[i] = 0;
        }
        comps = n;
    }
    int find_set(int v) { return (v == p[v]) ? v : find_set(p[v]); }
    bool unite(int v, int u) {
        v = find_set(v);
        u = find_set(u);
        if (v == u) return false;
        comps--;
        if (rnk[v] > rnk[u]) swap(v, u);
        op.push(dsu_save(v, rnk[v], u, rnk[u]));
        p[v] = u;
        if (rnk[u] == rnk[v]) rnk[u]++;
        return true;
    }
    void rollback() {
        if (op.empty()) return;
        dsu_save x = op.top();
```

```

op.pop();
comps++;
p[x.v] = x.v;
rnk[x.v] = x.rnk;
p[x.u] = x.u;
rnk[x.u] = x.rnk;
}
};
struct query {
    int v, u;
    bool united;
    query(int _v, int _u) : v(_v), u(_u) {}
};
struct QueryTree {
    vector<vector<query>> t;
    dsu_with_rollback dsu;
    int T;
    QueryTree() {}
    QueryTree(int _T, int n) : T(_T) {
        dsu = dsu_with_rollback(n);
        t.resize(4 * T + 4);
    }
    void add_to_tree(int v, int l, int r, int ul, int ur,
        query& q) {
        if (ul > ur) return;
        if (l == ul && r == ur) {
            t[v].push_back(q);
            return;
        }
        int mid = (l + r) / 2;
        add_to_tree(2 * v, l, mid, ul, min(ur, mid), q);
        add_to_tree(2 * v + 1, mid + 1, r, max(ul, mid +
            1), ur, q);
    }
    void add_query(query q, int l, int r) {
        add_to_tree(1, 0, T - 1, l, r, q);
    }
    void dfs(int v, int l, int r, vector<int>& ans) {
        for (query& q : t[v]) {
            q.united = dsu.unite(q.v, q.u);
        }
        if (l == r)
            ans[l] = dsu.comps;
        else {
            int mid = (l + r) / 2;
            dfs(2 * v, l, mid, ans);
            dfs(2 * v + 1, mid + 1, r, ans);
        }
        for (query q : t[v]) {
            if (q.united) dsu.rollback();
        }
    }
    vector<int> solve() {
        vector<int> ans(T);
        dfs(1, 0, T - 1, ans);
        return ans;
    }
};
// need to add queries first and then call solve() to
// get the answer for each query.

```

1.3 MO with Update [43 lines] - a0826346

```

//1 indexed
//Complexity:  $O(S \times Q + Q \times \frac{N^2}{S^2})$ 
// $S = (2 * n^2)^{(1/3)}$ 

```

```

const int block_size = 2720; // 4310 for 2e5
const int mx = 1e5 + 5;
struct Query {
    int L, R, T, id;
    Query() {}
    Query(int _L, int _R, int _T, int _id) : L(_L),
        R(_R), T(_T), id(_id) {}
    bool operator<(const Query &x) const {
        if (L / block_size == x.L / block_size) {
            if (R / block_size == x.R / block_size) return T <
                x.T;
            return R / block_size < x.R / block_size;
        }
        return L / block_size < x.L / block_size;
    }
} Q[mx];
struct Update {
    int pos;
    int old, cur;
    Update() {}
    Update(int _p, int _o, int _c) : pos(_p), old(_o),
        cur(_c) {}
} U[mx];
int ans[mx];
inline void add(int id) {}
inline void remove(int id) {}
inline void update(int id, int L, int R) {}
inline void undo(int id, int L, int R) {}
inline int get() {}
void MO(int nq, int nu) {
    sort(Q + 1, Q + nq + 1);
    int L = 1, R = 0, T = nu;
    for (int i = 1; i <= nq; i++) {
        Query q = Q[i];
        while (T < q.T) update(++T, L, R);
        while (T > q.T) undo(T--, L, R);
        while (L > q.L) add(--L);
        while (R < q.R) add(++R);
        while (L < q.L) remove(L++);
        while (R > q.R) remove(R--);
        ans[q.id] = get();
    }
}

```

1.4 MO [28 lines] - ec9fc177

```

const int N = 2e5 + 5;
const int Q = 2e5 + 5;
const int SZ = sqrt(N) + 1;
struct qry {
    int l, r, id, blk;
    bool operator<(const qry& p) const {
        return blk == p.blk ? r < p.r : blk < p.blk;
    }
};
qry query[Q];
ll ans[Q];
void add(int id) {}
void remove(int id) {}
ll get() {}
int n, q;
void MO() {
    sort(query, query + q);
    int cur_l = 0, cur_r = -1;
    for (int i = 0; i < q; i++) {
        qry q = query[i];
    }
}

```

```

while (cur_l > q.l) add(--cur_l);
while (cur_r < q.r) add(++cur_r);
while (cur_l < q.l) remove(cur_l++);
while (cur_r > q.r) remove(cur_r--);
ans[q.id] = get();
}
}
/* 0 indexed. */

```

1.5 Segment Tree Lazy [73 lines] - 1b64fde6

```

/*edit:data,combine,build check datatype*/
template<typename T>
struct SegmentTree {
    #define lc (C << 1)
    #define rc (C << 1 | 1)
    #define M ((L+R)>>1)
    struct data {
        T sum;
        data() : sum(0) {}
    };
    vector<data> st;
    vector<bool> isLazy;
    vector<T> lazy;
    int N;
    SegmentTree(int _N) : N(_N) {
        st.resize(4 * N);
        isLazy.resize(4 * N);
        lazy.resize(4 * N);
    }
    void combine(data& cur, data& l, data& r) {
        cur.sum = l.sum + r.sum;
    }
    void push(int C, int L, int R) {
        if (!isLazy[C]) return;
        if (L != R) {
            isLazy[lc] = 1;
            isLazy[rc] = 1;
            lazy[lc] += lazy[C];
            lazy[rc] += lazy[C];
        }
        st[C].sum = (R - L + 1) * lazy[C];
        lazy[C] = 0;
        isLazy[C] = false;
    }
    void build(int C, int L, int R) {
        if (L == R) {
            st[C].sum = 0;
            return;
        }
        build(lc, L, M);
        build(rc, M + 1, R);
        combine(st[C], st[lc], st[rc]);
    }
    data Query(int i, int j, int C, int L, int R) {
        push(C, L, R);
        if (j < L || i > R || L > R) return data(); //
            default val 0/INF
        if (i <= L && R <= j) return st[C];
        data ret;
        data d1 = Query(i, j, lc, L, M);
        data d2 = Query(i, j, rc, M + 1, R);
        combine(ret, d1, d2);
        return ret;
    }
}

```

```

}
void Update(int i, int j, T val, int C, int L, int R)
{
    push(C, L, R);
    if (j < L || i > R || L > R) return;
    if (i <= L && R <= j) {
        isLazy[C] = 1;
        lazy[C] = val;
        push(C, L, R);
        return;
    }
    Update(i, j, val, lc, L, M);
    Update(i, j, val, rc, M + 1, R);
    combine(st[C], st[lc], st[rc]);
}
void Update(int i, int j, T val) {
    Update(i, j, val, 1, 1, N);
}
T Query(int i, int j) {
    return Query(i, j, 1, 1, N).sum;
}
};

```

1.6 Segment Tree [41 lines] - 17c5e235

```

struct node{
    ll sum, maxi, mini;
    node() { sum = 0; maxi = -1e17; mini = 1e17; }
};
node tree[N*4];
node merge(node a, node b){
    node ans;
    ans.sum = a.sum + b.sum;
    ans.mini = min(a.mini, b.mini);
    ans.maxi = max(a.maxi, b.maxi);
    return ans;
}
void build(int id, int l, int r){ // (1, 0, n-1)
    if(l == r){
        tree[id] = node();
        return;
    }
    ll mid = (l+r)/2;
    build(2*id, l, mid);
    build(2*id + 1, mid+1, r);
    tree[id] = merge(tree[2*id], tree[2*id + 1]);
}
void update(int id, int l, int r, int pos, ll val){
    if(pos < l || pos > r) return;
    if(l == r){
        tree[id].sum = val;
        tree[id].mini = val;
        tree[id].maxi = val;
        return;
    }
    ll mid = (l+r)/2;
    update(2*id, l, mid, pos, val);
    update(2*id + 1, mid+1, r, pos, val);
    tree[id] = merge(tree[2*id], tree[2*id + 1]);
}
node query(int id, int l, int r, int lq, int rq){
    if(lq > r || rq < l) return node();
    if(l >= lq && r <= rq) return tree[id];
    ll mid = (l+r)/2;
    return merge(query(2*id, l, mid, lq, rq), query(2*id
+ 1, mid+1, r, lq, rq));
}

```

```

}
1.7 Trie Bit [61 lines] - 25d39ae1
struct Trie {
    struct node {
        int next[2];
        int cnt, fin;
        node() : cnt(0), fin(0) {
            for (int i = 0; i < 2; i++) next[i] = -1;
        }
    };
    vector<node>data;
    Trie() {
        data.push_back(node());
    }
    void key_add(int val) {
        int cur = 0;
        for (int i = 30; i >= 0; i--) {
            int id = (val >> i) & 1;
            if (data[cur].next[id] == -1) {
                data[cur].next[id] = data.size();
                data.push_back(node());
            }
            cur = data[cur].next[id];
            data[cur].cnt++;
        }
        data[cur].fin++;
    }
    int key_search(int val) {
        int cur = 0;
        for (int i = 30; ~i; i--) {
            int id = (val >> i) & 1;
            if (data[cur].next[id] == -1) return 0;
            cur = data[cur].next[id];
        }
        return data[cur].fin;
    }
    void key_delete(int val) {
        int cur = 0;
        for (int i = 30; ~i; i--) {
            int id = (val >> i) & 1;
            cur = data[cur].next[id];
            data[cur].cnt--;
        }
        data[cur].fin--;
    }
    bool key_remove(int val) {
        if (key_search(val)) return key_delete(val), 1;
        return 0;
    }
    int maxXor(int x) {
        int cur = 0;
        int ans = 0;
        for (int i = 30; ~i; i--) {
            int b = (x >> i) & 1;
            if (data[cur].next[!b] + 1 &&
                data[data[cur].next[!b]].cnt > 0) {
                ans += (1LL << i);
                cur = data[cur].next[!b];
            }
            else cur = data[cur].next[b];
        }
        return ans;
    }
};

```

2 Dynamic Programming

2.1 Digit Dp [19 lines] - f18e4b74

```

ll dp[20][20][2]; // How many zeros
ll digitDP(const string &num, ll pos = 0, ll cnt = 0,
    bool tight = 1, bool isStart = 1){
    if(pos == num.size()) return isStart ? 1 : cnt;
    else if(dp[pos][cnt][tight] != -1) return
        dp[pos][cnt][tight];
    ll ans = 0, lim = tight ? num[pos] - '0' : 9;
    for(int digit = 0; digit <= lim; digit++){
        ans += digitDP(num, pos + 1, cnt + (!isStart &&
            digit == 0), tight && digit == lim, isStart
            && digit == 0);
    }
    return isStart ? ans : dp[pos][cnt][tight] = ans;
}
void solve() {
    ll l, r;
    cin >> l >> r;
    memset(dp, -1, sizeof(dp));
    ll ans1 = digitDP(to_string(r));
    memset(dp, -1, sizeof(dp));
    ll ans2 = digitDP(to_string(l - 1));
    cout << ans1 - ans2 << "\n";
}

```

2.2 Divide and Conquer DP [26 lines] - 6000baee

```

ll G,L;///total group,cell size
ll dp[8001][801],cum[8001];
ll C[8001];///value of each cell
inline ll cost(ll l,ll r){
    return(cum[r]-cum[l-1])*(r-l+1);
}
void fn(ll g,ll st,ll ed,ll r1,ll r2){
    if(st>ed)return;
    ll mid=(st+ed)/2,pos=-1;
    dp[mid][g]=inf;
    for(int i=r1;i<=r2;i++){
        ll tcost=cost(i,mid)+dp[i-1][g-1];
        if(tcost<dp[mid][g]){
            dp[mid][g]=tcost,pos=i;
        }
    }
    fn(g,st,mid-1,r1,pos);
    fn(g,mid+1,ed,pos,r2);
}
int main(){
    for(int i=1;i<=L;i++)
        cum[i]=cum[i-1]+C[i];
    for(int i=1;i<=L;i++)
        dp[i][1]=cost(1,i);
    for(int i=2;i<=G;i++)fn(i,1,L,1,L);
}

```

2.3 Dynamic Convex Hull Trick [66 lines] - 86f3d1cf

```

const int N = 3e5 + 9;
const int mod = 1e9 + 7;

//add lines with -m and -b and return -ans to
//make this code work for minimums.(not -x)
const ll inf = -(1LL << 62);
struct line {

```

```

11 m, b;
mutable function<const line*> succ;
bool operator < (const line& rhs) const {
    if (rhs.b != inf) return m < rhs.m;
    const line* s = succ();
    if (!s) return 0;
    ll x = rhs.m;
    return b - s->b < (s->m - m) * x;
}
};
struct CHT : public multiset<line> {
    bool bad(iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;
            return y -> m == z -> m && y -> b <= z -> b;
        }
        auto x = prev(y);
        if (z == end()) return y -> m == x -> m && y -> b
            <= x -> b;
        return 1.0 * (x -> b - y -> b) * (z -> m - y -> m)
            >= 1.0 * (y -> b - z -> b) * (y -> m - x -> m);
    }
    void add(ll m, ll b) {
        auto y = insert({ m, b });
        y->succ = [ = ] { return next(y) == end() ? 0 :
            &*next(y); };
        if (bad(y)) {
            erase(y);
            return;
        }
        while (next(y) != end() && bad(next(y)))
            erase(next(y));
        while (y != begin() && bad(prev(y))) erase(prev(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound((line) {
            x, inf
        });
        return l.m * x + l.b;
    }
};
CHT* cht;
ll a[N], b[N];
int32_t main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);

    int n;
    cin >> n;
    for(int i = 0; i < n; i++) cin >> a[i];
    for(int i = 0; i < n; i++) cin >> b[i];
    cht = new CHT();
    cht -> add(-b[0], 0);
    ll ans = 0;
    for(int i = 1; i < n; i++) {
        ans = -cht -> query(a[i]);
        cht -> add(-b[i], -ans);
    }
    cout << ans << nl;
    return 0;
}

```

2.4 Knapsack DP [12 lines] - ef62fd72

```

// unbounded knapsack: ascending
for(auto x : v){
    for(int i = x; i <= N; i++){
        dp[i] = (dp[i] + dp[i-x]) % mod;
    }
}
// bounded knapsack: descending
for(auto x : v){
    for(int i = N; i >= x; i--){
        dp[i] = (dp[i] + dp[i-x]) % mod;
    }
}

```

2.5 Knuth Optimization [32 lines] - 5f2f74dc

*/*It is applicable where recurrence is in the form :*
 $dp[i][j] = \min_{k < j} \{ dp[i][k] + dp[k][j] \} + C[i][j]$
condition for applicability is:
 $A[i, j-1] \leq A[i, j] \leq A[i+1, j]$
Where,
 $A[i][j]$ - the smallest k that gives optimal answer, like-
 $dp[i][j] = dp[i-1][k] + C[k][j]$
 $C[i][j]$ - given cost function
also applicable if: $C[i][j]$ satisfies the following 2 conditions:
 $C[a][c] + C[b][d] \leq C[a][d] + C[b][c], a \leq b \leq c \leq d$
 $C[b][c] \leq C[a][d], a \leq b \leq c \leq d$
*reduces time complexity from $O(n^3)$ to $O(n^2)$ */*
for(int s=0; s<=k; s++) //s-length(size) of substring
 for(int l=0; l+s<=k; l++){ //l-left point
 int r=l+s; //r-right point
 if(s<2){
 res[l][r]=0; //DP base-nothing to break
 mid[l][r]=l; //mid is equal to left border*/
 continue;
 }
 int mleft=mid[l][r-1]; //Knuth's trick: getting
 bounds on m*/
 int mright=mid[l+1][r];
 res[l][r]=inf;
 for(int m=mleft; m<=mright; m++){ //iterating for m in
 the bounds only*/
 int64 tres=res[l][m]+res[m][r]+(x[r]-x[l]);
 if(res[l][r]>tres){ //relax current solution
 res[l][r]=tres;
 mid[l][r]=m;
 }
 }
 }
 int64 answer=res[0][k];

2.6 LIS O(nlogn) with full path [17 lines] - bcb566b7

```

int num[MX], mem[MX], prev[MX], array[MX], res[MX], maxlen;
void LIS(int SZ, int num[]) {
    CLR(mem), CLR(prev), CLR(array), CLR(res);
    int i, k;
    maxlen=1;
    array[0]=-inf;
    RFOR(i, 1, SZ+1) array[i]=inf;
    prev[0]=-1, mem[0]=num[0];
    FOR(i, SZ){
        k=lower_bound(array, array+maxlen+1, num[i])-array;
        if(k==1) array[k]=num[i], mem[k]=i, prev[i]=-1;
        else array[k]=num[i], mem[k]=i, prev[i]=mem[k-1];
        if(k>maxlen) maxlen=k;
    }
}

```

```

}
k=0;
for(i=mem[maxlen]; i!=-1; i=prev[i]) res[k++]=num[i];
}

```

2.7 SOS DP [18 lines] - e5398562

```

//iterative version
for(int mask = 0; mask < (1<<N); ++mask){
    dp[mask][0] = A[mask]; //handle base case separately
    (leaf states)
    for(int i = 0; i < N; ++i){
        if(mask & (1<<i))
            dp[mask][i] = dp[mask][i-1] +
                dp[mask^(1<<i)][i-1];
        else
            dp[mask][i] = dp[mask][i-1];
    }
    F[mask] = dp[mask][N-1];
}
//memory optimized, super easy to code.
for(int i = 0; i < (1<<N); ++i)
    F[i] = A[i];
for(int i = 0; i < N; ++i) for(int mask = 0; mask <
    (1<<N); ++mask){
    if(mask & (1<<i))
        F[mask] += F[mask^(1<<i)];
}

```

2.8 Sibling DP [26 lines] - 95945016

```

/*dividing tree into min group such that each group
cost not exceed k*/
ll n, k, dp[mx][mx];
vector<pair<ll, ll>> adj[mx]; //must be rooted tree
ll sibling_dp(ll par, ll idx, ll remk){
    if(remk<0) return inf;
    if(adj[par].size()<idx+1) return 0;
    ll u=adj[par][idx].first;
    if(dp[u][remk]!=-1)
        return dp[u][remk];
    ll ret=inf, under=0, sibling=0;
    if(par!=0){ //creating new group
        under=1+dfs(u, 0, k);
        sibling=dfs(par, idx+1, remk);
        ret=min(ret, under+sibling);
    }
    //divide the current group
    ll temp=remk-adj[par][idx].second;
    for(ll chk=temp; chk>=0; chk--){
        ll siblingk=temp-chk;
        under=0, sibling=0;
        under=dfs(u, 0, chk);
        sibling=dfs(par, idx+1, siblingk);
        ret=min(ret, under+sibling);
    }
    return dp[u][remk]=ret;
}

```

3 Flow

3.1 Blossom [59 lines] - a41c2f2c

```

// Finds Maximum matching in General Graph
// Complexity O(NM)
// mate[i] = j means i is paired with j
// Usage: `auto mate = Blossom(graph);` where `graph` is
vector<vector<int>>.

```



```
// source: https://codeforces.com/blog/entry_
/92339?#comment-810242
vector<int> Blossom(vector<vector<int>>& graph) {
    //mate contains matched edge.
    int n = graph.size(), timer = -1;
    vector<int> mate(n, -1), label(n), parent(n),
        orig(n), aux(n, -1), q;
    auto lca = [&](int x, int y) {
        for (timer++; ; swap(x, y)) {
            if (x == -1) continue;
            if (aux[x] == timer) return x;
            aux[x] = timer;
            x = (mate[x] == -1 ? -1 : orig[parent[mate[x]]]);
        }
    };
    auto blossom = [&](int v, int w, int a) {
        while (orig[v] != a) {
            parent[v] = w; w = mate[v];
            if (label[w] == 1) label[w] = 0, q.push_back(w);
            orig[v] = orig[w] = a; v = parent[w];
        }
    };
    auto augment = [&](int v) {
        while (v != -1) {
            int pv = parent[v], nv = mate[pv];
            mate[v] = pv; mate[pv] = v; v = nv;
        }
    };
    auto bfs = [&](int root) {
        fill(label.begin(), label.end(), -1);
        iota(orig.begin(), orig.end(), 0);
        q.clear();
        label[root] = 0; q.push_back(root);
        for (int i = 0; i < (int)q.size(); ++i) {
            int v = q[i];
            for (auto x : graph[v]) {
                if (label[x] == -1) {
                    label[x] = 1; parent[x] = v;
                    if (mate[x] == -1)
                        return augment(x), 1;
                    label[mate[x]] = 0; q.push_back(mate[x]);
                }
                else if (label[x] == 0 && orig[v] != orig[x]) {
                    int a = lca(orig[v], orig[x]);
                    blossom(x, v, a); blossom(v, x, a);
                }
            }
        }
        return 0;
    };
    // Time halves if you start with (any) maximal
    // matching.
    for (int i = 0; i < n; i++)
        if (mate[i] == -1)
            bfs(i);
    return mate;
}
```

3.2 Flow [21 lines] - ae00b72c

Covering Problems:

- Maximum Independent Set (Bipartite): $V - \text{MaxMatching}$
- Minimum Vertex Cover (Bipartite): $= \text{MaxMatching}$
- Minimum Edge Cover (General): $V - \text{MaxMatching}$ (no isolated vertices)

- Min Path Cover (vertex-disjoint, DAG): $V - \text{MaxMatching}$ (reduce to bipartite)
 - Min Path Cover (general): contract cycles $\rightarrow$ DAG reduction
- Matching | problem & when:
- Find maximum set of edges with no shared endpoints (bipartite case).
 - Use for assignment, scheduling, pairing; K nig gives min vertex cover from matching.

Templates (how to use):

- Kuhn: set ``n,k,g``; ``mt.assign(k,-1);`
for `(v=0..n-1){used.assign(n,false); try_kuhn(v);}`
 $\rightarrow$ result: ``mt[r]=l`` or `-1`; complexity $O(n*m)$.
- Hopcroft{Karp: ``HK hk(L); hk.addEdge(u,v); int M = hk.max_match();``
 $\rightarrow$ use ``matchL`/`matchR``; complexity $O(E*\sqrt{V})$.
- Blossom (``code/Flow/Blossom.cpp``): ``auto mate = Blossom(graph);`` for general graphs.
- Flow reduction: connect ``s->L(1)``, ``L->R(1)``, ``R->t(1)``; run max-flow; unit flows on ``L->R`` are matches.

Tips:

- Prefer Hopcroft{Karp for bipartite; Blossom for non-bipartite.
- Seed Kuhn with a greedy matching to speed it; use K nig to recover min vertex cover.
- Keep adjacency 0-based for Kuhn/Blossom; this repo's HK is 1-based.

3.3 HopcroftKarp [66 lines] - 779699b6

```
/* Finds Maximum Matching In a bipartite graph
.Complexity  $O(E\sqrt{V})$ 
.1-indexed
.No default constructor
.add single edge for (u, v)
Usage: `HK hk(L); hk.addEdge(u,v); int M =
hk.max_match();` */
```

```
struct HK {
    static const int inf = 1e9;
    int n;
    vector<int> matchL, matchR, dist;
    //matchL contains value of matched node for L part.
    vector<vector<int>> adj;
    HK(int n) : n(n), matchL(n + 1),
        matchR(n + 1), dist(n + 1), adj(n + 1) {}

    void addEdge(int u, int v) {
        adj[u].push_back(v);
    }
    bool bfs() {
        queue<int> q;
        for (int u = 1; u <= n; u++) {
            if (!matchL[u]) {
                dist[u] = 0;
                q.push(u);
            }
            else dist[u] = inf;
        }
        dist[0] = inf; //unmatched node matches with 0.
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (auto v : adj[u]) {
```

```
                if (dist[matchR[v]] == inf) {
                    dist[matchR[v]] = dist[u] + 1;
                    q.push(matchR[v]);
                }
            }
        }
        return dist[0] != inf;
    }
    bool dfs(int u) {
        if (!u) return true;
        for (auto v : adj[u]) {
            if (dist[matchR[v]] == dist[u] + 1
                && dfs(matchR[v])) {
                matchL[u] = v;
                matchR[v] = u;
                return true;
            }
        }
        dist[u] = inf;
        return false;
    }
    int max_match() {
        int matching = 0;
        while (bfs()) {
            for (int u = 1; u <= n; u++) {
                if (!matchL[u])
                    if (dfs(u))
                        matching++;
            }
        }
        return matching;
    }
};
```

3.4 kuhn [34 lines] - 8b05d01e

```
// Problem: find a maximum matching in a bipartite graph
// (no two chosen edges share a vertex).
// Where to use: assignment problems, scheduling,
// pairing tasks/agents, K nig's theorem for
// minimum vertex cover in bipartite graphs, minimum
// path cover in DAGs (via reduction).
// Brief usage: set `n` = left size, `k` = right size;
// fill `g[0..n-1]` with right indices (0..k-1).
// Call: `mt.assign(k, -1); for (int v=0; v<n; ++v) {
// used.assign(n,false); try_kuhn(v); }`
// Result: `mt[r] = l` if right r matched with left l,
// else -1. Complexity:  $O(n*m)$ .
int n, k;
vector<vector<int>> g;
vector<int> mt;
vector<bool> used;
bool try_kuhn(int v) {
    if (used[v])
        return false;
    used[v] = true;
    for (int to : g[v]) {
        if (mt[to] == -1 || try_kuhn(mt[to])) {
            mt[to] = v;
            return true;
        }
    }
    return false;
}
```

```
int main() {
    //... reading the graph ...

    mt.assign(k, -1);
    for (int v = 0; v < n; ++v) {
        used.assign(n, false);
        try_kuhn(v);
    }
    for (int i = 0; i < k; ++i)
        if (mt[i] != -1)
            printf("%d %d\n", mt[i] + 1, i + 1);
}
```

4 Game Theory

4.1 Inclusion Exclusion with Nim [33 lines] - 1a428d17

```
#define CheckBit(x, k) ((x >> k) & 1ll)
bool NimGame(vector<ll> v){
    ll nimsum = 0;
    for(auto x : v) nimsum ^= x;
    return nimsum != 0; // Alice win, If last pick win
}

void solve()
{
    ll n, m;
    cin >> n >> m;
    vector<ll> v(m), h(n), jinish(n);
    for(int i = 0; i < n; i++) cin >> h[i];
    for(int i = 0; i < m; i++) cin >> v[i];
    reverse(v.begin(), v.end());
    for(int j = 0; j < n; j++) {
        ll marked = 0;
        for(ll mask = 1; mask < 1ll << m; mask++){
            vector<ll> taken;
            for(int i = 0; i < 32; i++){
                if(CheckBit(mask, i))
                    taken.push_back(v[i]);
            }
            ll lcm = taken[0], ok = 1;
            for(int i = 1; i < taken.size(); i++){
                lcm = (lcm * taken[i]) / __gcd(lcm, taken[i]);
            }
            if(taken.size() & 1) marked += (h[j] / lcm);
            else marked -= (h[j] / lcm);
        }
        jinish[j] = marked + 1;
    }
    if(NimGame(jinish)) cout << "Alice\n";
    else cout << "Bob\n";
}
```

4.2 Points to be noted [14 lines] - 69c18f5f

>[First Write a Brute Force solution]
 >Nim = all xor
 >Misere Nim = Nim + corner case: if all piles are 1, reverse(nim)
 >Bogus Nim = Nim
 >Staircase Nim = Odd indexed pile Nim (Even indexed pile doesn't matter, as one player can give bogus moves to drop all even piles to ground)
 >Sprague Grundy: [Every impartial game under the normal play convention is equivalent to a one-heap game of nim]

Every tree = one nim pile = tree root value; tree leaf value = 0; tree node value = mex of all child nodes.

[Careful: one tree node can become multiple new tree roots(multiple elements in one node), then the value of that node = xor of all those root values]
 >Hackenbush(Given a rooted tree; cut an edge in one move; subtree under that edge gets removed; last player to cut wins):
 Colon: $//G(u) = (G(v_1) + 1) \oplus (G(v_2) + 1) \oplus \dots [v_1, v_2, \dots \text{ are childs of } u]$
 For multiple trees ans is their xor
 >Hackenbush on graph (instead of tree given an rooted graph):
 fusion: All edges in a cycle can be fused to get a tree structure; build a super node, connect some single nodes with that super node, number of single nodes is the number of edges in the cycle.
 Sol: [Bridge component tree] mark all bridges, a group of edges that are not bridges, becomes one component and contributes number of edges to the hackenbush. (even number of edges contributes 0, odd number of edges contributes 1)

5 Geometry

5.1 Basic Geometry [113 lines] - 00878049

```
typedef long long ll;
typedef long double ld;
#define PI acos(-1.0)
#define eps 1e-7
#define point pair<double,double>
#define x first
#define y second

point operator + (point a, point b) { return {a.x + b.x, a.y + b.y}; }
point operator - (point a, point b) { return {a.x - b.x, a.y - b.y}; }
double operator | (point a, point b) { return a.x * b.x + a.y * b.y; }
double operator * (point a, point b) { return a.x * b.y - a.y * b.x; }

point operator * (point a, double m) { return {a.x * m, a.y * m}; }
point operator / (point a, double m) { return {a.x / m, a.y / m}; }
double val(point a) { return sqrt(a | a); }
tuple<double, double, double> pointToLine(point a, point b){
    return {(b.y - a.y), (a.x - b.x), (a.y * (b.x - a.x) - a.y * (b.y - a.y))};
}

pair<point, point> lineToPoint(double a, double b, double c){
    if(a == 0) return {{1, -1 * c/b}, {0, -1 * c/b}};
    else if(b == 0) return {{-1 * c/a, 1}, {-1 * c/a, 0}};
    else return {{-1 * c/a, 0}, {0, -1 * c/b}};
}

double pointLineDistance(point p, double a, double b, double c){
    return fabs(a * (p.x) + b * (p.y) + c) / (sqrt(a*a + b*b));
}

double pointLineDistance(point p, point a, point b){
```

```
    return fabs((p-a) * (b-a)) / val(b-a);
}

double pointRayDistance(point p, point a, point b){
    if(((p-a)|(b-a)) < 0) return val(p-a);
    else return fabs((p-a) * (b-a)) / val(b-a);
}

double pointSegmentDistance(point p, point a, point b){
    if(((p-a)|(b-a)) < 0 && ((p-b)|(a-b)) > 0) return val(p-a);
    else if(((p-a)|(b-a)) > 0 && ((p-b)|(a-b)) < 0) return val(p-b);
    else return fabs((p-a) * (b-a)) / val(b-a);
}

double segmentSegmentDistance(point a, point b, point c, point d){
    bool dif1 = ((b-a)*(c-a) >= 0 && (b-a)*(d-a) <= 0) || ((b-a)*(c-a) <= 0 && (b-a)*(d-a) >= 0);
    bool dif2 = ((d-c)*(a-c) >= 0 && (d-c)*(b-c) <= 0) || ((d-c)*(a-c) <= 0 && (d-c)*(b-c) >= 0);
    if(dif1 == true && dif2 == true) return 0;
    else return min({
        pointSegmentDistance(a,c,d),
        pointSegmentDistance(b,c,d),
        pointSegmentDistance(c,a,b),
        pointSegmentDistance(d,a,b)
    });
}

point intersection(double a1, double b1, double c1, double a2, double b2, double c2){
    double x = (b1 * c2 - b2 * c1) / (a1 * b2 - a2 * b1);
    double y = (c1 * a2 - c2 * a1) / (a1 * b2 - a2 * b1);
    return {x, y};
}

point intersection(point a, point b, point c, point d){
    auto [a1, b1, c1] = pointToLine(a, b);
    auto [a2, b2, c2] = pointToLine(c, d);
    return intersection(a1,b1,c1,a2,b2,c2);
}

bool isOnLine(point p, double a, double b, double c){
    return fabs(a*p.x + b*p.y + c) <= eps; }
bool isOnRay(point p, point a, point b){ return fabs((p-a)*(b-a)) <= eps && ((p-a)|(b-a)) >= 0; }
bool isOnSegment(point p, point a, point b){ return fabs(val(p-a) + val(b-p) - val(b-a)) <= eps; }
bool isParallel(point a, point b, point c, point d) { return fabs((b-a)*(d-a)) <= eps; }
bool isSameSide(point p, point q, point p1, point p2){
    if(((p-p1) * (p2-p1)) * ((q-p1) * (p2-p1))) >= 0) return true;
    else return false;
}

bool isSameSide(point p, point q, double a, double b, double c){
    return (a*p.x + b*p.y + c) * (a*q.x + b*q.y + c) >= 0;
}

double rayRayDistance(point a, point b, point c, point d){
    double ans = min(pointRayDistance(a,c,d), pointRayDistance(c,a,b));
    if(isParallel(a,b,c,d)) return ans;
```

```

else if(isOnRay(intersection(a,b,c,d), a, b) &&
isOnRay(intersection(a,b,c,d), c, d)) return 0;
else return ans;
}
double area_of_triangle(point a, point b, point c){
return fabs((a - c) * (b - c)) / 2.0;
}
double area_of_polygon(vector<point> &p){
double area = 0.0;
int n = p.size();
for(int i = 0; i < n; i++){
area += (p[i] * p[(i+1)%n]) / 2.0; //
anticlockwise = +ve area, clockwise = -ve
area
}
return fabs(area);
}
// Angle Bisector
point p = ((y - x) * val(z - x)) / val(y-x); // vector
towards (y-x) with length |z-x|
p = p + (z - x); // resultant vector
p = p + x; // translating start point at x from (0,0)
auto [a, b, c] = pointToLine(x, p);

// Formula for Basic Geometry Operations
circumradius = (a * b * c) / (4 * area); //pori
inradius = area / s; //onto
isosceles_side = (b / 4) * sqrt(4 * a * a - b * b); // a
same
equilateral_area = (sqrt(3) / 4) * a * a;
regular_polygon_area = (n * a * a / 4) * (1 / tan(M_PI /
n));
point_line_distance = abs(a*x + b*y + c) / sqrt(a*a +
b*b);
two_point_distance = sqrt((x2 - x1)*(x2 - x1) + (y2 -
y1)*(y2 - y1));
area_triangle_sine = 0.5 * a * b * sin(C);
line_intercept = y1 - (perpendicular_slope * x1);
perpendicular_slope = -1 / line_slope;
sine_rule = a / sin(A) == b / sin(B) == c / sin(C) == 2
* circumradius;
cosine_rule = c * c = a * a + b * b - 2 * a * b *
cos(C);
herons_area = sqrt(s * (s - a) * (s - b) * (s - c)); //
s = (a+b+c)/2
centroid = ( (x1 + x2 + x3) / 3 , (y1 + y2 + y3) / 3 )
orthocenter = (tanA*x1 + tanB*x2 + tanC*x3) / (tanA +
tanB + tanC) , (tanA*y1 + tanB*y2 + tanC*y3) / (tanA
+ tanB + tanC) )
incenter = ( (a*x1 + b*x2 + c*x3) / (a + b + c) , (a*y1
+ b*y2 + c*y3) / (a + b + c) )
circumcenter = intersection of perpendicular bisectors
of any two sides
median = ( (x1 + x2) / 2 , (y1 + y2) / 2 )

```

5.2 Geometry [536 lines] - 349abbca

```

int sign(T x) { return (x > eps) - (x < -eps); }
struct PT {
T x, y;
PT() { x = 0, y = 0; }
PT(T x, T y) : x(x), y(y) {}
PT(const PT &p) : x(p.x), y(p.y) {}
PT operator + (const PT &a) const { return PT(x +
a.x, y + a.y); }

```

```

PT operator - (const PT &a) const { return PT(x -
a.x, y - a.y); }
PT operator * (const T a) const { return PT(x * a, y
* a); }
friend PT operator * (const T &a, const PT &b) {
return PT(a * b.x, a * b.y); }
PT operator / (const T a) const { return PT(x / a, y /
a); }
bool operator == (PT a) const { return sign(a.x - x)
== 0 && sign(a.y - y) == 0; }
bool operator != (PT a) const { return !(*this == a);
}
bool operator < (PT a) const { return sign(a.x - x)
== 0 ? y < a.y : x < a.x; }
bool operator > (PT a) const { return sign(a.x - x)
== 0 ? y > a.y : x > a.x; }
T norm() { return sqrt(x * x + y * y); }
T norm2() { return x * x + y * y; }
PT perp() { return PT(-y, x); }
T arg() { return atan2(y, x); }
PT truncate(T r) { // returns a vector with norm r and
having same direction
T k = norm();
if (!sign(k)) return *this;
r /= k;
return PT(x * r, y * r);
}
};
istream &operator >> (istream &in, PT &p) { return in
>> p.x >> p.y; }
ostream &operator << (ostream &out, PT &p) { return out
<< "(" << p.x << "," << p.y << ")"; }
inline T dot(PT a, PT b) { return a.x * b.x + a.y *
b.y; }
inline T dist2(PT a, PT b) { return dot(a - b, a - b); }
inline T dist(PT a, PT b) { return sqrt(dot(a - b, a -
b)); }
inline T cross(PT a, PT b) { return a.x * b.y - a.y *
b.x; }
inline T cross2(PT a, PT b, PT c) { return cross(b - a,
c - a); }
inline int orientation(PT a, PT b, PT c) { return
sign(cross(b - a, c - a)); }
PT perp(PT a) { return PT(-a.y, a.x); }
PT rotateccw90(PT a) { return PT(-a.y, a.x); }
PT rotatecw90(PT a) { return PT(a.y, -a.x); }
PT rotateccw(PT a, T t) { return PT(a.x * cos(t) - a.y
* sin(t), a.x * sin(t) + a.y * cos(t)); }
PT rotatecw(PT a, T t) { return PT(a.x * cos(t) + a.y *
sin(t), -a.x * sin(t) + a.y * cos(t)); }
T rad_to_deg(T r) { return (r * 180.0 / PI); }
T deg_to_rad(T d) { return (d * PI / 180.0); }
T get_angle(PT a, PT b) {
T costheta = dot(a, b) / a.norm() / b.norm();
return acos(max((T)-1.0, min((T)1.0, costheta)));
}
bool is_point_in_angle(PT b, PT a, PT c, PT p) { // does
point p lie in angle <bac
assert(orientation(a, b, c) != 0);
if (orientation(a, c, b) < 0) swap(b, c);
return orientation(a, c, p) >= 0 && orientation(a, b,
p) <= 0;
}
bool half(PT p) {

```

```

return p.y > 0.0 || (p.y == 0.0 && p.x < 0.0);
}
void polar_sort(vector<PT> &v) { // sort points in
counterclockwise
sort(v.begin(), v.end(), [](PT a, PT b) {
return make_tuple(half(a), 0.0, a.norm2()) <
make_tuple(half(b), cross(a, b), b.norm2());
});
}
void polar_sort(vector<PT> &v, PT o) { // sort points in
counterclockwise with respect to point o
sort(v.begin(), v.end(), [&](PT a, PT b) {
return make_tuple(half(a - o), 0.0, (a - o).norm2())
< make_tuple(half(b - o), cross(a - o, b - o),
(b - o).norm2());
});
}
struct line {
PT a, b; // goes through points a and b
PT v; T c; //line form: direction vec [cross] (x, y)
= c
line() {}
//direction vector v and offset c
line(PT v, T c) : v(v), c(c) {
auto p = get_points();
a = p.first; b = p.second;
}
// equation ax + by + c = 0
line(T _a, T _b, T _c) : v({_b, -_a}), c(-_c) {
auto p = get_points();
a = p.first; b = p.second;
}
// goes through points p and q
line(PT p, PT q) : v(q - p), c(cross(v, p)), a(p),
b(q) {}
pair<PT, PT> get_points() { //extract any two points
from this line
PT p, q; T a = -v.x, b = v.x; // ax + by = c
if (sign(a) == 0) {
p = PT(0, c / b);
q = PT(1, c / b);
}
else if (sign(b) == 0) {
p = PT(c / a, 0);
q = PT(c / a, 1);
}
else {
p = PT(0, c / b);
q = PT(1, (c - a) / b);
}
return {p, q};
}
// ax + by + c = 0
array<T, 3> get_abc() {
T a = -v.y, b = v.x;
return {a, b, -c};
}
// 1 if on the left, -1 if on the right, 0 if on the
line
int side(PT p) { return sign(cross(v, p) - c); }
// line that is perpendicular to this and goes through
point p

```

```

line_perpendicular_through(Pt p) { return {p, p +
    perp(v)}; }
// translate the line by vector t i.e. shifting it by
// vector t
line_translate(Pt t) { return {v, c + cross(v, t)}; }
// compare two points by their orthogonal projection
// on this line
// a projection point comes before another if it comes
// first according to vector v
bool cmp_by_projection(Pt p, Pt q) { return dot(v, p)
    < dot(v, q); }
line_shift_left(T d) {
    Pt z = v.perp().truncate(d);
    return line(a + z, b + z);
}
};
// find a point from a through b with distance d
Pt point_along_line(Pt a, Pt b, T d) {
    assert(a != b);
    return a + ((b - a) / (b - a).norm()) * d;
}
// projection point c onto line through a and b
// assuming a != b
Pt project_from_point_to_line(Pt a, Pt b, Pt c) {
    return a + (b - a) * dot(c - a, b - a) / (b -
        a).norm2();
}
// reflection point c onto line through a and b
// assuming a != b
Pt reflection_from_point_to_line(Pt a, Pt b, Pt c) {
    Pt p = project_from_point_to_line(a, b, c);
    return p + p - c;
}
// minimum distance from point c to line through a and
// b
T dist_from_point_to_line(Pt a, Pt b, Pt c) {
    return fabs(cross(b - a, c - a) / (b - a).norm());
}
// returns true if point p is on line segment ab
bool is_point_on_seg(Pt a, Pt b, Pt p) {
    if (fabs(cross(p - b, a - b)) < eps) {
        if (p.x < min(a.x, b.x) - eps || p.x > max(a.x, b.x)
            + eps) return false;
        if (p.y < min(a.y, b.y) - eps || p.y > max(a.y, b.y)
            + eps) return false;
        return true;
    }
    return false;
}
// minimum distance point from point c to segment ab
// that lies on segment ab
Pt project_from_point_to_seg(Pt a, Pt b, Pt c) {
    T r = dist2(a, b);
    if (sign(r) == 0) return a;
    r = dot(c - a, b - a) / r;
    if (r < 0) return a;
    if (r > 1) return b;
    return a + (b - a) * r;
}
// minimum distance from point c to segment ab
T dist_from_point_to_seg(Pt a, Pt b, Pt c) {
    return dist(c, project_from_point_to_seg(a, b, c));
}
// 0 if not parallel, 1 if parallel, 2 if collinear

```

```

int is_parallel(Pt a, Pt b, Pt c, Pt d) {
    T k = fabs(cross(b - a, d - c));
    if (k < eps) {
        if (fabs(cross(a - b, a - c)) < eps && fabs(cross(c
            - d, c - a)) < eps) return 2;
        else return 1;
    }
    else return 0;
}
// check if two lines are same
bool are_lines_same(Pt a, Pt b, Pt c, Pt d) {
    if (fabs(cross(a - c, c - d)) < eps && fabs(cross(b -
        c, c - d)) < eps) return true;
    return false;
}
// bisector vector of <abc
Pt angle_bisector(Pt &a, Pt &b, Pt &c) {
    Pt p = a - b, q = c - b;
    return p + q * sqrt(dot(p, p) / dot(q, q));
}
// 1 if point is ccw to the line, 2 if point is cw to
// the line, 3 if point is on the line
int point_line_relation(Pt a, Pt b, Pt p) {
    int c = sign(cross(p - a, b - a));
    if (c < 0) return 1;
    if (c > 0) return 2;
    return 3;
}
// intersection point between ab and cd assuming unique
// intersection exists
bool line_line_intersection(Pt a, Pt b, Pt c, Pt d, Pt
    &ans) {
    T a1 = a.y - b.y, b1 = b.x - a.x, c1 = cross(a, b);
    T a2 = c.y - d.y, b2 = d.x - c.x, c2 = cross(c, d);
    T det = a1 * b2 - a2 * b1;
    if (det == 0) return 0;
    ans = PT((b1 * c2 - b2 * c1) / det, (c1 * a2 - a1 *
        c2) / det);
    return 1;
}
// intersection point between segment ab and segment cd
// assuming unique intersection exists
bool seg_seg_intersection(Pt a, Pt b, Pt c, Pt d, Pt
    &ans) {
    T oa = cross2(c, d, a), ob = cross2(c, d, b);
    T oc = cross2(a, b, c), od = cross2(a, b, d);
    if (oa * ob < 0 && oc * od < 0) {
        ans = (a * ob - b * oa) / (ob - oa);
        return 1;
    }
    else return 0;
}
// intersection point between segment ab and segment cd
// assuming unique intersection may not exists
// se.size()==0 means no intersection
// se.size()==1 means one intersection
// se.size()==2 means range intersection
set<Pt> seg_seg_intersection_inside(Pt a, Pt b, Pt c,
    Pt d) {
    Pt ans;
    if (seg_seg_intersection(a, b, c, d, ans)) return
        {ans};
    set<Pt> se;
    if (is_point_on_seg(c, d, a)) se.insert(a);
}

```

```

    if (is_point_on_seg(c, d, b)) se.insert(b);
    if (is_point_on_seg(a, b, c)) se.insert(c);
    if (is_point_on_seg(a, b, d)) se.insert(d);
    return se;
}
// intersection between segment ab and line cd
// 0 if do not intersect, 1 if proper intersect, 2 if
// segment intersect
int seg_line_relation(Pt a, Pt b, Pt c, Pt d) {
    T p = cross2(c, d, a);
    T q = cross2(c, d, b);
    if (sign(p) == 0 && sign(q) == 0) return 2;
    else if (p * q < 0) return 1;
    else return 0;
}
// intersection between segment ab and line cd assuming
// unique intersection exists
bool seg_line_intersection(Pt a, Pt b, Pt c, Pt d, Pt
    &ans) {
    bool k = seg_line_relation(a, b, c, d);
    assert(k != 2);
    if (k) line_line_intersection(a, b, c, d, ans);
    return k;
}
// minimum distance from segment ab to segment cd
T dist_from_seg_to_seg(Pt a, Pt b, Pt c, Pt d) {
    Pt dummy;
    if (seg_seg_intersection(a, b, c, d, dummy)) return
        0.0;
    else return min({dist_from_point_to_seg(a, b, c),
        dist_from_point_to_seg(a, b, d),
        dist_from_point_to_seg(c, d, a),
        dist_from_point_to_seg(c, d, b)});
}
// minimum distance from point c to ray (starting point
// a and direction vector b)
T dist_from_point_to_ray(Pt a, Pt b, Pt c) {
    b = a + b;
    T r = dot(c - a, b - a);
    if (r < 0.0) return dist(c, a);
    return dist_from_point_to_line(a, b, c);
}
// starting point as and direction vector ad
bool ray_ray_intersection(Pt as, Pt ad, Pt bs, Pt bd) {
    T dx = bs.x - as.x, dy = bs.y - as.y;
    T det = bd.x * ad.y - bd.y * ad.x;
    if (fabs(det) < eps) return 0;
    T u = (dy * bd.x - dx * bd.y) / det;
    T v = (dy * ad.x - dx * ad.y) / det;
    if (sign(u) >= 0 && sign(v) >= 0) return 1;
    else return 0;
}
T ray_ray_distance(Pt as, Pt ad, Pt bs, Pt bd) {
    if (ray_ray_intersection(as, ad, bs, bd)) return 0.0;
    T ans = dist_from_point_to_ray(as, ad, bs);
    ans = min(ans, dist_from_point_to_ray(bs, bd, as));
    return ans;
}
// CONVEX HULL
vector<Pt> convex_hull(vector<Pt> &p) {
    if (p.size() <= 1) return p;
    vector<Pt> v = p;
    sort(v.begin(), v.end());
}

```



```

vector<PT> up, dn;
for (auto& p : v) {
    while (up.size() > 1 && orientation(up[up.size() - 2], up.back(), p) >= 0) {
        up.pop_back();
    }
    while (dn.size() > 1 && orientation(dn[dn.size() - 2], dn.back(), p) <= 0) {
        dn.pop_back();
    }
    up.push_back(p);
    dn.push_back(p);
}
v = dn;
if (v.size() > 1) v.pop_back();
reverse(up.begin(), up.end());
up.pop_back();
for (auto& p : up) {
    v.push_back(p);
}
if (v.size() == 2 && v[0] == v[1]) v.pop_back();
return v;
}

//checks if convex or not
bool is_convex(vector<PT> &p) {
    bool s[3]; s[0] = s[1] = s[2] = 0;
    int n = p.size();
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n;
        int k = (j + 1) % n;
        s[sign(cross(p[j] - p[i], p[k] - p[i])) + 1] = 1;
        if (s[0] && s[2]) return 0;
    }
    return 1;
}

// -1 if strictly inside, 0 if on the polygon, 1 if strictly outside
// it must be strictly convex, otherwise make it strictly convex first
int is_point_in_convex(vector<PT> &p, const PT& x) { // O(log n)
    int n = p.size(); assert(n >= 3);
    int a = orientation(p[0], p[1], x), b = orientation(p[0], p[n - 1], x);
    if (a < 0 || b > 0) return 1;
    int l = 1, r = n - 1;
    while (l + 1 < r) {
        int mid = l + r >> 1;
        if (orientation(p[0], p[mid], x) >= 0) l = mid;
        else r = mid;
    }
    int k = orientation(p[l], p[r], x);
    if (k <= 0) return -k;
    if (l == 1 && a == 0) return 0;
    if (r == n - 1 && b == 0) return 0;
    return -1;
}

struct circle {
    PT p; T r;
    circle() {}
    circle(PT _p, T _r): p(_p), r(_r) {};
    // center (x, y) and radius r
    circle(T x, T y, T _r): p(PT(x, y)), r(_r) {};

```

```

// circumcircle of a triangle
// the three points must be unique
circle(PT a, PT b, PT c) {
    b = (a + b) * 0.5;
    c = (a + c) * 0.5;
    line_line_intersection(b, b + rotatecw90(a - b), c, c + rotatecw90(a - c), p);
    r = dist(a, p);
}

// inscribed circle of a triangle
// pass a bool just to differentiate from circumcircle
circle(PT a, PT b, PT c, bool t) {
    line u, v;
    T m = atan2(b.y - a.y, b.x - a.x), n = atan2(c.y - a.y, c.x - a.x);
    u.a = a;
    u.b = u.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0)));
    v.a = b;
    m = atan2(a.y - b.y, a.x - b.x), n = atan2(c.y - b.y, c.x - b.x);
    v.b = v.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0)));
    line_line_intersection(u.a, u.b, v.a, v.b, p);
    r = dist_from_point_to_seg(a, b, p);
}

bool operator == (circle v) { return p == v.p && sign(r - v.r) == 0; }
T area() { return PI * r * r; }
T circumference() { return 2.0 * PI * r; }
};

// 0 if outside, 1 if on circumference, 2 if inside circle
int circle_point_relation(PT p, T r, PT b) {
    T d = dist(p, b);
    if (sign(d - r) < 0) return 2;
    if (sign(d - r) == 0) return 1;
    return 0;
}

// 0 if outside, 1 if on circumference, 2 if inside circle
int circle_line_relation(PT p, T r, PT a, PT b) {
    T d = dist_from_point_to_line(a, b, p);
    if (sign(d - r) < 0) return 2;
    if (sign(d - r) == 0) return 1;
    return 0;
}

//compute intersection of line through points a and b with
//circle centered at c with radius r > 0
vector<PT> circle_line_intersection(PT c, T r, PT a, PT b) {
    vector<PT> ret;
    b = b - a; a = a - c;
    T A = dot(b, b), B = dot(a, b);
    T C = dot(a, a) - r * r, D = B * B - A * C;
    if (D < -eps) return ret;
    ret.push_back(c + a + b * (-B + sqrt(D + eps)) / A);
    if (D > eps) ret.push_back(c + a + b * (-B - sqrt(D)) / A);
    return ret;
}

```

```

//5 - outside and do not intersect
//4 - intersect outside in one point
//3 - intersect in 2 points
//2 - intersect inside in one point
//1 - inside and do not intersect
int circle_circle_relation(PT a, T r, PT b, T R) {
    T d = dist(a, b);
    if (sign(d - r - R) > 0) return 5;
    if (sign(d - r - R) == 0) return 4;
    T l = fabs(r - R);
    if (sign(d - r - R) < 0 && sign(d - l) > 0) return 3;
    if (sign(d - l) == 0) return 2;
    if (sign(d - l) < 0) return 1;
    assert(0); return -1;
}

vector<PT> circle_circle_intersection(PT a, T r, PT b, T R) {
    if (a == b && sign(r - R) == 0) return {PT(1e18, 1e18)};
    vector<PT> ret;
    T d = sqrt(dist2(a, b));
    if (d > r + R || d + min(r, R) < max(r, R)) return ret;
    T x = (d * d - R * R + r * r) / (2 * d);
    T y = sqrt(r * r - x * x);
    PT v = (b - a) / d;
    ret.push_back(a + v * x + rotateccw90(v) * y);
    if (y > 0) ret.push_back(a + v * x - rotateccw90(v) * y);
    return ret;
}

// -1 if strictly inside, 0 if on the polygon, 1 if strictly outside
int is_point_in_triangle(PT a, PT b, PT c, PT p) {
    if (sign(cross(b - a, c - a)) < 0) swap(b, c);
    int c1 = sign(cross(b - a, p - a));
    int c2 = sign(cross(c - b, p - b));
    int c3 = sign(cross(a - c, p - c));
    if (c1 < 0 || c2 < 0 || c3 < 0) return 1;
    if (c1 + c2 + c3 != 3) return 0;
    return -1;
}

T perimeter(vector<PT> &p) {
    T ans=0; int n = p.size();
    for (int i = 0; i < n; i++) ans += dist(p[i], p[(i + 1) % n]);
    return ans;
}

T area(vector<PT> &p) {
    T ans = 0; int n = p.size();
    for (int i = 0; i < n; i++) ans += cross(p[i], p[(i + 1) % n]);
    return fabs(ans) * 0.5;
}

// centroid of a (possibly non-convex) polygon,
// assuming that the coordinates are listed in a clockwise or
// counterclockwise fashion. Note that the centroid is often known as
// the "center of gravity" or "center of mass".
PT centroid(vector<PT> &p) {
    int n = p.size(); PT c(0, 0);
    T sum = 0;

```

```

for (int i = 0; i < n; i++) sum += cross(p[i], p[(i + 1) % n]);
T scale = 3.0 * sum;
for (int i = 0; i < n; i++) {
    int j = (i + 1) % n;
    c = c + (p[i] + p[j]) * cross(p[i], p[j]);
}
return c / scale;
}
// 0 if cw, 1 if ccw
bool get_direction(vector<PT> &p) {
    T ans = 0; int n = p.size();
    for (int i = 0; i < n; i++) ans += cross(p[i], p[(i + 1) % n]);
    if (sign(ans) > 0) return 1;
    return 0;
}
// it returns a point such that the sum of distances
// from that point to all points in p is minimum
// O(n log^2 MX)
PT geometric_median(vector<PT> p) {
    auto tot_dist = [&](PT z) {
        T res = 0;
        for (int i = 0; i < p.size(); i++) res +=
            dist(p[i], z);
        return res;
    };
    auto findY = [&](T x) {
        T yl = -1e5, yr = 1e5;
        for (int i = 0; i < 60; i++) {
            T ym1 = yl + (yr - yl) / 3;
            T ym2 = yr - (yr - yl) / 3;
            T d1 = tot_dist(PT(x, ym1));
            T d2 = tot_dist(PT(x, ym2));
            if (d1 < d2) yr = ym2;
            else yl = ym1;
        }
        return pair<T, T> (yl, tot_dist(PT(x, yl)));
    };
    T xl = -1e5, xr = 1e5;
    for (int i = 0; i < 60; i++) {
        T xm1 = xl + (xr - xl) / 3;
        T xm2 = xr - (xr - xl) / 3;
        T y1, d1, y2, d2;
        auto z = findY(xm1); y1 = z.first; d1 = z.second;
        z = findY(xm2); y2 = z.first; d2 = z.second;
        if (d1 < d2) xr = xm2;
        else xl = xm1;
    }
    return {xl, findY(xl).first};
}

bool is_point_on_polygon(vector<PT> &p, const PT& z) {
    int n = p.size();
    for (int i = 0; i < n; i++) {
        if (is_point_on_seg(p[i], p[(i + 1) % n], z)) return
            1;
    }
    return 0;
}

// -1 if strictly inside, 0 if on the polygon, 1 if
// strictly outside

```

```

int is_point_in_polygon(vector<PT> &p, const PT& z) { //
    O(n)
    int k = winding_number(p, z);
    return k == 1e9 ? 0 : k == 0 ? 1 : -1;
}
// id of the vertex having maximum dot product with z
// polygon must need to be convex
// top - upper right vertex
// for minimum dot product negate z and return -dot(z,
// p[id])
int extreme_vertex(vector<PT> &p, const PT &z, const int
top) { // O(log n)
    int n = p.size();
    if (n == 1) return 0;
    T ans = dot(p[0], z); int id = 0;
    if (dot(p[top], z) > ans) ans = dot(p[top], z), id =
        top;
    int l = 1, r = top - 1;
    while (l < r) {
        int mid = l + r >> 1;
        if (dot(p[mid + 1], z) >= dot(p[mid], z)) l = mid +
            1;
        else r = mid;
    }
    if (dot(p[l], z) > ans) ans = dot(p[l], z), id = l;
    l = top + 1, r = n - 1;
    while (l < r) {
        int mid = l + r >> 1;
        if (dot(p[(mid + 1) % n], z) >= dot(p[mid], z)) l =
            mid + 1;
        else r = mid;
    }
    l %= n;
    if (dot(p[l], z) > ans) ans = dot(p[l], z), id = l;
    return id;
}

// maximum distance from any point on the perimeter to
// another point on the perimeter
T diameter(vector<PT> &p) {
    int n = (int)p.size();
    if (n == 1) return 0;
    if (n == 2) return dist(p[0], p[1]);
    T ans = 0;
    int i = 0, j = 1;
    while (i < n) {
        while (cross(p[(i + 1) % n] - p[i], p[(j + 1) % n]
            - p[j]) >= 0) {
            ans = max(ans, dist2(p[i], p[j]));
            j = (j + 1) % n;
        }
        ans = max(ans, dist2(p[i], p[j]));
        i++;
    }
    return sqrt(ans);
}

5.3 Rotation Matrix [39 lines] - d41f8b6c
struct { double x; double y; double z; } Point;
double rMat[4][4];
double inMat[4][1] = {0.0, 0.0, 0.0, 0.0};
double outMat[4][1] = {0.0, 0.0, 0.0, 0.0};
void mulMat() {
    for (int i = 0; i < 4; i++) {
        for (int j = 0; j < 1; j++) {

```

```

            outMat[i][j] = 0;
            for (int k = 0; k < 4; k++)
                outMat[i][j] += rMat[i][k] * inMat[k][j];
        }
    }
}

void setMat(double ang, double u, double v, double w) {
    double L = (u * u + v * v + w * w);
    ang = ang * PI / 180.0; /*converting to radian
        value*/
    double u2 = u*u; double v2 = v*v; double w2 = w*w;
    rMat[0][0] = (u2 + (v2 + w2) * cos(ang)) / L;
    rMat[0][1] = (u*v*(1 - cos(ang)) - w*sqrt(L)*sin(ang)) / L;
    rMat[0][2] = (u*w*(1 - cos(ang)) + v*sqrt(L)*sin(ang)) / L;
    rMat[0][3] = 0.0;
    rMat[1][0] = (u*v*(1 - cos(ang)) + w*sqrt(L)*sin(ang)) / L;
    rMat[1][1] = (v2 + (u2 + w2) * cos(ang)) / L;
    rMat[1][2] = (v*w*(1 - cos(ang)) - u*sqrt(L)*sin(ang)) / L;
    rMat[1][3] = 0.0;
    rMat[2][0] = (u*w*(1 - cos(ang)) - v*sqrt(L)*sin(ang)) / L;
    rMat[2][1] = (v*w*(1 - cos(ang)) + u*sqrt(L)*sin(ang)) / L;
    rMat[2][2] = (w2 + (u2 + v2) * cos(ang)) / L;
    rMat[2][3] = 0.0; rMat[3][0] = 0.0; rMat[3][1] = 0.0;
    rMat[3][2] = 0.0; rMat[3][3] = 1.0;
}

/*double ang;
double u, v, w; //points = the point to be rotated
Point point, rotated; //u,v,w=unit vector of line
inMat[0][0] = points.x; inMat[1][0] = points.y;
inMat[2][0] = points.z; inMat[3][0] = 1.0;
setMat(ang, u, v, w); mulMat();
rotated.x = outMat[0][0]; rotated.y = outMat[1][0];
rotated.z = outMat[2][0];*/
}

6 Graph

6.1 Articulation Bridge [24 lines] - ce2d2a56

int timer = 0;
vector <int> G[N];
bool visited[N];
int disc[N], low[N];
vector <pair <int, int>> bridges;

void DFS(int v, int par = -1) {
    visited[v] = true;
    disc[v] = low[v] = timer;
    timer++;
    for (auto child : G[v]) {
        if (!visited[child]) {
            DFS(child, v);
            low[v] = min(low[child], low[v]);
            if (disc[v] < low[child]) {
                bridges.push_back({min(v, child), max(v,
                    child)});
            }
        }
        else {
            if (child == par) continue;
            low[v] = min(low[child], low[v]);
        }
    }
}
}

```

6.2 Articulation Point [25 lines] - ce1ae03f

```
vector<int> G[N];
bool visited[N];
int disc[N], low[N];
bool mark[N]; // articulation point marker
int timer;

void DFS(int v, int par = -1){
    visited[v] = true;
    disc[v] = low[v] = timer;
    timer++;
    int children = 0;
    for(auto child : G[v]){
        if(child == par) continue;
        if(!visited[child]){
            DFS(child, v);
            low[v] = min(low[child], low[v]);
            if(par != -1 && low[child] >= disc[v]){
                mark[v] = true;
                children++;
            }
        }
        else{
            low[v] = min(low[v], disc[child]);
        }
    }
    if(par == -1 && children > 1) mark[v] = true;
}
```

6.3 Basic [137 lines] - 5a88e77e

```
struct info{
    ll v, w;
    bool const operator < (const info node) const{
        return w > node.w;
    }
};

void dijkstra(int start){
    fill(dist, dist + N, 1e17);
    dist[start] = 0;
    priority_queue<info> q;
    q.push({start, 0});
    while(!q.empty()){
        info cur = q.top();
        q.pop();
        if(cur.w > dist[cur.v]) continue;
        for(auto x : G[cur.v]){
            ll v = x.first;
            ll w = x.second;
            if(dist[v] > cur.w + w){
                dist[v] = cur.w + w;
                q.push({v, dist[v]});
            }
        }
    }

    // Bipartite Check
    bool dfs(int u, int c, int& ct0, int& ct1){
        color[u] = c;
        if(c) ct1++;
        else ct0++;

        bool bipartite = true;
        for(auto v : G[u]){
            if(color[v] == -1){
                if(!dfs(v, !c, ct0, ct1)) bipartite = false;
            }
        }
    }
}
```

```
        else if(color[v] == color[u]) bipartite = false;
    }
    return bipartite;
}

// Cycle Check
bool dfs(int u, int par = -1){
    visited[u] = true;
    for(auto v : G[u]){
        if(visited[v] == true && v != par) return true;
        if(!visited[v] && dfs(v, u)) return true; // cycle check
    }
    return false;
}

// BFS
while(!q.empty()){
    auto [r,c,face,time] = q.front(); q.pop();
    if(r == n-1 && c == n-1 && face == 0){
        cout << time << "\n";
        break;
    }
    int nr = r + dr[face], nc = c + dc[face];
    if(!visited[r][c][(face+1)%4]){
        q.push({r, c, (face+1)%4, time+1});
        visited[r][c][(face+1)%4] = true;
    }
    if(nr < 0 || nr >= n || nc < 0 || nc >= n ||
        s[nr][nc] == '#' || visited[nr][nc][face])
        continue;
    q.push({nr, nc, face, time+1});
    visited[nr][nc][face] = true;
}

// DP on Trees
void dfs(int u, int par = -1){
    for(auto v : G[u]){
        if(v == par) continue;
        dfs(v, u); // FIRST solve child's dp
        // THEN use child's dp to update parent u's dp
        // accumulate into dp[u][0] (when a_u = L[u]):
        dp[u][0] += max(
            dp[v][0] + abs(L[u] - L[v]), // child
            dp[v][1] + abs(L[u] - R[v]) // child
        );
        // accumulate into dp[u][1] (when a_u = R[u]):
        dp[u][1] += max(
            dp[v][0] + abs(R[u] - L[v]), // child
            dp[v][1] + abs(R[u] - R[v]) // child
        );
        // Update dp[u] using best from children
        // assuming a_u is L[u] or R[u]
    }
}

// Floyd Warshall
for(int k = 0; k < n; k++){
    for(int i = 0; i < n; i++){
        for(int j = 0; j < n; j++){
            dis[i][j] = min(dis[i][j], dis[i][k] +
                dis[k][j]);
        }
    }
}
```

```
}

// MST - Kruskal
int Find(int x) {
    if(parent[x] != x) parent[x] = Find(parent[x]);
    return parent[x];
}

void Union(int x, int y) {
    int root_x = Find(x);
    int root_y = Find(y);
    if(root_x != root_y){
        parent[root_x] = root_y;
    }
}

ll Kruskal(vector<tuple<ll,ll,ll>> edges) {
    vector<tuple<ll,ll,ll>> MST;
    sort(edges.begin(), edges.end());
    ll sum = 0;
    for(auto [w, u, v] : edges){
        if(Find(u) != Find(v)){
            MST.push_back({w, u, v});
            Union(u, v);
            sum += w;
        }
        if(MST.size() == n - 1) break;
    }
    if(MST.size() == n - 1) return sum;
    else return -1;
}

// Topological Sort - Kahn's Algorithm
void kahn_topological_sort(){
    queue<int> q;
    for(int i = 0; i < n; i++){
        if(indegree[i] == 0) q.push(i);
    }
    while(!q.empty()){
        int u = q.front();
        q.pop();
        topo_order.push_back(u);
        for(auto v : G[u]){
            indegree[v]--;
            if(indegree[v] == 0) q.push(v);
        }
    }
}
```

6.4 Centroid Decomposition [39 lines] - f24b6f45

```
ll n,subsize[mx];
vector<int>adj[mx];
bool b[mx];
int cpar[mx];
vector<int>ctree[mx];

void calculatesize(ll u,ll par){
    subsize[u]=1;
    for(ll i=0;i<(ll)adj[u].size();i++){
        ll v=adj[u][i];
        if(v==par or b[v]==true)continue;
        calculatesize(v,u);
        subsize[u]+=subsize[v];
    }
}

ll getcentroid(ll u,ll par,ll n){
```

```

11 ret=u;
for(11 i=0;i<(11)adj[u].size();i++){
    11 v=adj[u][i];
    if(v==par or b[v]==true)continue;
    if(subsize[v]>(n/2)){
        ret=getcentroid(v,u,n);
        break;
    }
}
return ret;
}
void decompose(11 u, int p){
    calculatesize(u,-1);
    11 c=getcentroid(u,-1,subsize[u]);
    b[c]=true;
    cpar[c] = p;
    //if(p != -1)ctree[p].push_back(c);
    for(11 i=0;i<(11)adj[c].size();i++){
        11 v=adj[c][i];
        if(b[v]==true)continue;
        decompose(v, c);
    }
}

```

6.5 DSU on Tree [56 lines] - b5007715

```

int n;
//extra data you need
vector<int> adj[mxn];
vector<int> *dsu[mxn];
void call(int u, int p=-1){
    sz[u] = 1;
    for(auto v: adj[u]){
        if(v != p){
            dep[v] = dep[u]+1;
            call(v, u);
            sz[u] += sz[v];
        }
    }
}
void dfs(int u, int p = -1, int isb = 1){
    int mx=-1, big=-1;
    for(auto v: adj[u]){
        if(v != p && sz[v]>mx){
            mx = sz[v];
            big = v;
        }
    }
    for(auto v: adj[u]){
        if(v != p && v != big){
            dfs(v, u, 0);
        }
    }
    if(big != -1){
        dfs(big, u, 1);
        dsu[u] = dsu[big];
    }
    else{
        dsu[u] = new vector<int>();
    }
    dsu[u]->push_back(u);
    //calculation
    for(auto v: adj[u]){
        if(v == p || v == big) continue;
        for(auto x: *dsu[v]){
            dsu[u]->push_back(x);

```

```

        //calculation
    }
}
//calculate ans for node u
if(isb == 0){
    for(auto x: *dsu[u]){
        //reverse calculation
    }
}
}
int main() {
    //input graph
    dep[1] = 1;
    call(1);
    dfs(1);
}
6.6 Heavy Light Decomposition [73 lines] - 74d2c2ea
/*Heavy Light Decomposition
Build Complexity O(n)
Query Complexity O(lg^2 n)
Call init()with number of nodes
It's probably for the best to not do"using namespace
hld"*/
namespace hld {
    //N is the maximum number of nodes
    /*par,lev,size corresponds to
    parent,depth,subtree-size*/
    //head[u]is the starting node of the chain u is in
    //in[u]to out[u]keeps the subtree indices
    const int N=100000+7;
    vector<int>g[N];
    int par[N],lev[N],head[N],size[N],in[N],out[N];
    int cur_pos,n;
    //returns the size of subtree rooted at u
    /*maintains the child with the largest subtree at the
    front of g[u]*/
    //WARNING: Don't change anything here specially with
    size[]if Jon Snow
    int dfs(int u,int p){
        size[u]=1,par[u]=p;
        lev[u]=lev[p]+1;
        for(auto &v : g[u]){
            if(v==p)continue;
            size[u]+=dfs(v,u);
            if(size[v]>size[g[u].front()]){
                swap(v,g[u].front());
            }
        }
        return size[u];
    }
    //decomposed the tree in an array
    //note that there is no physical array here
    void decompose(int u,int p){
        in[u]=++cur_pos;
        for(auto &v : g[u]){
            if(v==p)continue;
            head[v]=(v==g[u].front()? head[u]: v);
            decompose(v,u);
        }
        out[u]=cur_pos;
    }
    //initializes the structure with _n nodes
    void init(int _n,int root=1){
        n=_n;

```

```

        cur_pos=0;
        dfs(root,0);
        head[root]=root;
        decompose(root,0);
    }
    //checks whether p is an ancestor of u
    bool isances(int p,int u){
        return in[p]<=in[u]and out[u]<=out[p];
    }
    //Returns the maximum node value in the path u-v
    11 query(int u,int v){
        11 ret=-INF;
        while(!isances(head[u],v)){
            ret=max(ret,seg.query(1,1,n,in[head[u]],in[u]));
            u=par[head[u]];
        }
        swap(u,v);
        while(!isances(head[u],v)){
            ret=max(ret,seg.query(1,1,n,in[head[u]],in[u]));
            u=par[head[u]];
        }
        if(in[v]<in[u])swap(u,v);
        ret=max(ret,seg.query(1,1,n,in[u],in[v]));
        return ret;
    }
    //Adds val to subtree of u
    void update(int u,11 val){
        seg.update(1,1,n,in[u],out[u],val);
    }
}

```

6.7 K'th Shortest path [40 lines] - 1294302c

```

int m,n,deg[MM],source,sink,K,val[MM][12];
struct edge{
    int v,w;
}adj[MM][500];
struct info{
    int v,w,k;
    bool operator<(const info &b)const{
        return w>b.w;
    }
};
priority_queue<info,vector<info>>Q;
void kthBestShortestPath(){
    int i,j;
    info u,v;
    for(i=0;i<n;i++){
        for(j=0;j<K;j++)val[i][j]=inf;
        u.v=source,u.k=0,u.w=0;
        Q.push(u);
        while(!Q.empty()){
            u=Q.top();
            Q.pop();
            for(i=0;i<deg[u.v];i++){
                v.v=adj[u.v][i].v;
                int cost=adj[u.v][i].w+u.w;
                for(v.k=u.k;v.k<K;v.k++){
                    if(cost==inf)break;
                    if(val[v.v][v.k]>cost){
                        swap(cost,val[v.v][v.k]);
                        v.w=val[v.v][v.k];
                        Q.push(v);
                        break;

```



```

    }
    }
    for(v.k++;v.k<K;v.k++){
        if(cost==inf)break;
        if(val[v.v][v.k]>cost)swap(cost, val[v.v][v.k]);
    }
}
}
}
}

```

6.8 LCA [121 lines] - 3f335059

```
#include <bits/stdc++.h>
```

```
using namespace std;
```

```
class LCA_BinaryLifting
```

```
{
public:
    int n, max_log;
    vector<vector<int>> adj;
    vector<vector<int>> ancestor;
    vector<int> depth;
```

```
LCA_BinaryLifting(int n) : n(n)
```

```
{
    adj.resize(n + 1);
    max_log = log2(n) + 1;
    ancestor.assign(n + 1, vector<int>(max_log,
        -1));
    depth.resize(n + 1);
}
```

```
void add_edge(int u, int v)
```

```
{
    adj[u].push_back(v);
    adj[v].push_back(u);
}
```

```
void dfs(int node, int parent)
```

```
{
    ancestor[node][0] = parent;
    for (int i = 1; i < max_log; i++)
    {
        if (ancestor[node][i - 1] != -1)
        {
            ancestor[node][i] =
                ancestor[ancestor[node][i - 1]][i - 1];
        }
    }
    for (int neighbor : adj[node])
    {
        if (neighbor != parent)
        {
            depth[neighbor] = depth[node] + 1;
            dfs(neighbor, node);
        }
    }
}
```

```
void preprocess(int root)
```

```
{
    depth[root] = 0;
    dfs(root, -1);
}
```

```
int get_lca(int u, int v)
```

```
{
    if (depth[u] < depth[v])
    {
```

```
        swap(u, v);
    }
    for (int i = max_log - 1; i >= 0; i--)
    {
        if (ancestor[u][i] != -1 &&
            depth[ancestor[u][i]] >= depth[v])
        {
            u = ancestor[u][i];
        }
    }
    if (u == v)
    {
        return u;
    }
    for (int i = max_log - 1; i >= 0; i--)
    {
        if (ancestor[u][i] != ancestor[v][i])
        {
            u = ancestor[u][i];
            v = ancestor[v][i];
        }
    }
    return ancestor[u][0];
}

int get_kth_ancestor(int u, int k)
{
    for (int i = 0; i < max_log; i++)
    {
        if (k & (1 << i))
        {
            u = ancestor[u][i];
            if (u == -1)
                break;
        }
    }
    return u;
}

int query_distance(int u, int v)
{
    int lca = get_lca(u, v);
    return depth[u] + depth[v] - 2 * depth[lca];
}

int get_kth_node_in_path(int u, int v, int k)
{
    int lca = get_lca(u, v);
    int dist_u_lca = depth[u] - depth[lca];
    int dist_lca_v = depth[v] - depth[lca];
    int total_distance = dist_u_lca + dist_lca_v;
    if (k > total_distance)
    {
        return -1;
    }
    if (k <= dist_u_lca)
    {
        return get_kth_ancestor(u, k);
    }
    else
    {
        return get_kth_ancestor(v, dist_u_lca +
            dist_lca_v - k);
    }
}

int get_ancestor_depth(int u, int target_depth)
{

```

```

        if (depth[u] < target_depth)
        {
            return -1;
        }
        int diff = depth[u] - target_depth;
        return get_kth_ancestor(u, diff);
    }
};

```

6.9 Multisource BFS [75 lines] - d8742599

```

int dr[4] = {1, -1, 0, 0};
int dc[4] = {0, 0, 1, -1};
int n, m, ans = 0;
vector<pair<int,int>> fire;
vector<vector<int>> firetime;
vector<vector<bool>> visited;
vector<vector<char>> s;
bool isvalid(int x, int y, int timer){
    if(x < 0 || y < 0 || x >= n || y >= m) return false;
    if(firetime[x][y] <= timer) return false;
    return true;
}
bool isfree(int x, int y, int timer){
    if(!isvalid(x, y, timer)) return false;
    if(x == 0 || y == 0 || x == n - 1 || y == m - 1)
        return true;
    return false;
}
void firebfs(){
    queue <tuple<int,int,int>> q;
    for(auto [x,y] : fire){
        q.push({x, y, 0});
    }
    while(!q.empty()){
        auto[r, c, timer] = q.front();
        timer++; q.pop();
        for(int i = 0; i < 4; i++){
            int rr = r + dr[i];
            int cc = c + dc[i];
            if(isvalid(rr, cc, timer)){
                firetime[rr][cc] = timer;
                q.push({rr, cc, timer});
            }
        }
    }
}

bool escapebfs(int sr, int sc){
    queue <tuple<int,int,int>> q;
    q.push({sr, sc, 0});
    visited[sr][sc] = true;
    while(!q.empty()){
        auto[r, c, timer] = q.front();
        timer++; q.pop();
        for(int i = 0; i < 4; i++){
            int rr = r + dr[i];
            int cc = c + dc[i];
            if(isfree(rr, cc, timer)){
                ans = timer;
                return true;
            }
        }
        if(isvalid(rr, cc, timer) &&
            !visited[rr][cc]){
            visited[rr][cc] = true;

```

```

        q.push({rr, cc, timer});
    }
}
return false;
}
// Minimum number of elements product is exactly equal
// to i
sort(v.begin(), v.end());
v.erase(unique(v.begin(), v.end(), v.end()), v.end());
for(auto x : v){
    if(x <= n) dist[x] = 1, q.push(x);
}
while(!q.empty()){
    ll cur = q.front();
    q.pop();
    for(auto x : v){
        if(cur * x > n) break;
        ll xx = cur * x;
        if(dist[xx] == -1){
            dist[xx] = dist[cur] + 1;
            q.push(xx);
        }
    }
}

```

6.10 SCC [31 lines] - 9982799c

```

const int mxn = 100003;
vector<int> adj[mxn], stak;
int tin[mxn], low[mxn], n, color[mxn]; // component no 1
// based;
bool onstack[mxn];
int timer = 0, sccCount = 0;
void dfs(int at) {
    stak.push_back(at);
    onstack[at] = true;
    tin[at] = low[at] = ++timer;

    for (int to : adj[at]) {
        if (!tin[to]) {
            dfs(to);
            low[at] = min(low[at], low[to]);
        } else if (onstack[to])
            low[at] = min(low[at], tin[to]);
    }

    if (tin[at] == low[at]) {
        ++sccCount;
        while (1) {
            int node = stak.back();
            stak.pop_back();
            onstack[node] = false;
            color[node] = sccCount;
            if (node == at) break;
        }
    }
}
for (int i = 1; i <= n; i++)
    if (!tin[i]) dfs(i);

```

6.11 Tree [48 lines] - 8fa963f9

```

// Tree DFS Basic Structure
void dfs(int u, int par = -1){
    // process u's information
    for(auto v : G[u]){

```

```

        if(v == par) continue;
        // process edge u-v's information
        // process v's information
        dfs(v, u);
        // process child v's information to update u's
        // information
    }
    // process u's information after processing all
    // children
}
// Common Tricks for tree dfs/dp on trees
// 1. To find the parent of each node, pass the parent
// as a parameter in the dfs function.
// 2. To find the depth of each node, pass the depth as
// a parameter in the dfs function.
// 3. To find the size of each subtree, maintain a size
// array and update it during the dfs.
// 4. To find the maximum depth of each subtree,
// maintain a max_depth array and update it during the
// dfs.
// 5. To find the sum of values in each subtree,
// maintain a sum array and update it during the dfs.
// 6. To find the answer for each node based on its
// children, maintain a dp array and update it during
// the dfs.
// 7. To find the answer for each node based on its
// parent, maintain a dp array and update it during the
// dfs.
vector<ll> depth, a, sub, dp1, dp2, max_depth;
void dfs1(int u, int par = -1){
    sub[u] += a[u];
    max_depth[u] = depth[u];
    for(auto v : G[u]){
        if(v == par) continue;
        depth[v] = depth[u] + 1;
        dfs1(v, u);
        sub[u] += sub[v];
        max_depth[u] = max(max_depth[u], max_depth[v]);
        dp1[u] += (dp1[v] + sub[v]);
    }
}
void dfs2(int u, int par = -1){
    ll f = 0, s = 0;
    for(auto v : G[u]){
        if(v == par) continue;
        if(f < max_depth[v]) s = f, f = max_depth[v];
        else if(s < max_depth[v]) s = max_depth[v];
    }
    for(auto v : G[u]){
        if(v == par) continue;
        dfs2(v, u);
        // take best among: previous answer, best inside
        // child, or cutting this child
        if(max_depth[v] != f) dp2[u] = max({dp2[u],
            dp2[v], sub[v] * (f+1-depth[v])});
        else dp2[u] = max({dp2[u], dp2[v], sub[v] *
            (s+1-depth[v])});
    }
}

```

7 Math

7.1 Basic [132 lines] - 7c2ca56e

```

// a + ar + ar^2 + ar^3 + ... + ar^n-1 = a(r^n - 1) /
// (r - 1)
// 1 + a + a^2 + a^3 + a^4 + .... + a^(n-1) = (a^n - 1)
// (a - 1)

// 1 + a + a^2 + a^3 + a^4 + a^5 = 1 + a^2 + (a^2)^2 +
// a(1 + a^2 + (a^2)^2)
// bigsum(a, 6) = bigsum(a^2, 3) + a * bigsum(a^2, 3)
// 1 + a + a^2 + a^3 + a^4 = 1 + a(1 + a + a^2 + a^3)
// bigsum(a, 5) = 1 + a * bigsum(a, 4)

ll bigsum(ll a, ll n) {
    if(n == 0 || n == 1) return n % mod;
    if(n & 1) return ((a % mod) * bigsum(a % mod, n - 1)
        + 1) % mod;
    ll x = bigsum((a * a) % mod, n / 2);
    return (x + (a * x) % mod) % mod;
}

ll power(ll a, ll b) {
    ll result = 1;
    a = a % mod;
    while (b > 0){
        if (b & 1) result = (result * a) % mod;
        a = (a * a) % mod;
        b >>= 1ll;
    }
    return result;
}

inline ll modInverse(ll a) { return power(a, mod - 2); }

ll formula(ll a, ll n){
    if(a == 1) return n;
    return ((power(a, n) - 1) * (modInverse(a - 1))) %
        mod; // if mod is prime
}

int NotPrime[N], phi[N];
// coprime = No common factors between two numbers
// except 1
// phi(n) = number of numbers less than n that are
// coprime with n
// phi(n) = n * (1 - 1/p1) * (1 - 1/p2) * ... * (1 -
// 1/pk)
// phi(n) = n * ((p1 - 1)/p1) * ((p2 - 1)/p2) * ... *
// ((pk - 1)/pk)
// Here p1, p2, ... , pk - everyone divides n because
// they are prime divisors
// In this sieve, phi[j] is always divisible by i (The
// Prime Factor)
void sievePhi(){
    for(int i = 1; i < N; i++) phi[i] = i;
    NotPrime[1] = 1;
    for(int i = 2; i < N; i++){
        if(!NotPrime[i]){
            for(int j = i; j < N; j += i){
                NotPrime[j] = 1;
                phi[j] = (phi[j] / i) * (i - 1);
            }
        }
    }
}

```

```

}
// Properties of Phi :
// 1. if p is a prime number, phi[p] = p - 1;
// 2. if p is a prime number and n is a positive
//    integer, phi[p^n] = p^n - p^(n-1);
// 3. if a and m are coprime, a^phi[m] = 1 mod m
//    (Euler's Theorem)
// 4. if a and m are coprime and m is prime, a^(m-1)
//    = 1 mod m (Fermat's little theorem)

int phi(int n){
    int ans = n;
    for(int i = 2; 1ll * i * i <= n; i++){
        if(n % i == 0){ // i is prime
            while(n % i == 0){
                n /= i;
            }
            ans -= (ans / i); // n * (1 - 1/p1) -> (n - n/p1)
        }
    }
    if(n > 1){
        ans -= (ans / n); // there can be only one prime
        factor > sqrt(n)
    }
    return ans;
}

int spf[N];
vector<int> primes;

void sieve() {
    for(int i = 1; i < N; i++) spf[i] = i;
    for(int i = 2; 1ll * i * i < N; i++) {
        if(spf[i] == i) { // i is prime
            for(int j = i * i; j < N; j += i) {
                if(spf[j] == j) spf[j] = i;
            }
        }
    }
    for(int i = 2; i < N; i++){
        if(spf[i] == i) primes.push_back(i);
    }
}

vector<pair<ll,ll>> factor(ll n) {
    vector<pair<ll,ll>> fact;
    for(auto p : primes){
        if(1ll * p * p > n) break;
        if(n % p == 0){
            ll power = 0;
            while(n % p == 0){
                n /= p;
                power++;
            }
            fact.push_back({p, power});
        }
    }
    if(n > 1) fact.push_back({n, 1});
    return fact;
}

// Modular Arithmetic Functions
static inline ll mulmod(ll a, ll b, ll m) {
    a %= m; b %= m;

```

```

        return (1ll)((__int128)a * b % m);
    }
    ll powmod(ll a, long long b, ll m) {
        a %= m;
        if (a < 0) a += m;
        ll res = 1 % m;
        while (b > 0) {
            if (b & 1) res = mulmod(res, a, m);
            a = mulmod(a, a, m);
            b >>= 1;
        }
        return res;
    }

    ll modMul(ll a, ll b) { return mulmod(a, b, mod); }
    ll modAdd(ll a, ll b) { return ( (a%mod) + (b%mod) ) % mod; }
    ll modSub(ll a, ll b) { return ( (a%mod) - (b%mod) + mod ) % mod; }
    ll modInverse(ll a) { return powmod((a%mod+mod)%mod, mod-2, mod); }
    ll modDiv(ll a, ll b) { return modMul(a, modInverse(b)); }

    // Exponents reduced modulo (mod-1)
    ll p = (powmod(2, n, mod-1) - 1 + (mod-1)) % (mod-1);
}

7.2 CRT [52 lines] - ff3bd658
ll ext_gcd(ll A, ll B, ll* X, ll* Y) {
    ll x2, y2, x1, y1, x, y, r2, r1, q, r;
    x2 = 1; y2 = 0;
    x1 = 0; y1 = 1;
    for (r2 = A, r1 = B; r1 != 0; r2 = r1, r1 = r, x2 = x1, y2 = y1, x1 = x, y1 = y) {
        q = r2 / r1;
        r = r2 % r1;
        x = x2 - (q * x1);
        y = y2 - (q * y1);
    }
    *X = x2; *Y = y2;
    return r2;
}

/*-----BlackBox-----*/
class ChineseRemainderTheorem {
    typedef long long vlong;
    typedef pair<vlong, vlong> pll;
    /** CRT Equations stored as pairs of vector. See addEquation() */
    vector<pll> equations;
public:
    void clear() { equations.clear(); }
    /** Add equation of the form x = r (mod m) */
    void addEquation(vlong r, vlong m) { equations.push_back({ r, m }); }
}

pll solve() {
    if (equations.size() == 0) return { -1, -1 }; /// No equations to solve
    vlong a1 = equations[0].first;
    vlong m1 = equations[0].second;
    a1 %= m1;
    /** Initially x = a_0 (mod m_0) */
    /** Merge the solution with remaining equations */

```

```

    for (int i = 1; i < equations.size(); i++) {
        vlong a2 = equations[i].first;
        vlong m2 = equations[i].second;
        vlong g = __gcd(m1, m2);
        if (a1 % g != a2 % g) return { -1, -1 }; /// Conflict in equations
        /** Merge the two equations */
        vlong p, q;
        ext_gcd(m1 / g, m2 / g, &p, &q);
        vlong mod = m1 / g * m2;
        vlong x = ((__int128)a1 * (m2 / g) % mod * q % mod + (__int128)a2 * (m1 / g) % mod * p % mod) % mod;
        /** Merged equation */
        a1 = x;
        if (a1 < 0) a1 += mod;
        m1 = mod;
    }
    return { a1, m1 };
}

};

7.3 Coprime Subsequence Mobius [31 lines] - dc967df5
const int N = 1e5 + 7, mod = 1e9 + 7;
ll cnt[N]; // cnt[x] = frequency of x in the input
ll d[N]; // d[i] = # of input elements divisible by i

ll f[N]; // f[i] = # of non-empty subseq's all divisible by i
ll mob[N]; // Mobius function mu(i)
ll power(ll a, ll b) { }
void coprime_subsequence_mobius(){
    int n; cin >> n;
    for(int i = 0; i < n; i++){
        int x; cin >> x;
        cnt[x]++;
    }
    mob[1] = 1;
    for(int i = 1; i < N; i++){
        for(int j = i + i; j < N; j += i){
            mob[j] -= mob[i];
        }
    }
    for(int i = 1; i < N; i++){
        for(int j = i; j < N; j += i){
            d[i] += cnt[j];
        }
    }
    ll ans = 0;
    for(int i = 1; i < N; i++){
        if(d[i] == 0 || mob[i] == 0) continue; // nothing to add/subtract
        f[i] = (power(2, d[i]) - 1 + mod) % mod; // number of non-empty subsequences from d[i]
        ans = ((ans + mob[i] * f[i]) % mod + mod) % mod; // inclusion-exclusion using mobius
    }
    cout << ans << "\n";
}

7.4 Extended GCD [19 lines] - 45160ec3
// Extended GCD: finds gcd(a,b) and x,y such that a*x + b*y = gcd(a,b)
int gcdExt(int a, int b, int &x, int &y) {

```

```

if (b == 0) {
    x = 1; y = 0; // base: a*1 + 0*0 = a
    return a;
}
int x1, y1;
int g = gcdExt(b, a % b, x1, y1); // recurse
x = y1; // transform back
y = x1 - (a / b) * y1;
return g;
}

// Modular inverse: returns x where (a*x) % m = 1,
// exists only if gcd(a,m) = 1
int modInv(int a, int m) {
    int x, y;
    int g = gcdExt(a, m, x, y); // a*x + m*y = gcd(a,m),
    // if g==1 then x is inverse
    return (x % m + m) % m; // normalize to positive
}

```

7.5 FFT [85 lines] - 5ed04be4

```

template<typename float_t>
struct mycomplex {
    float_t x, y;
    mycomplex<float_t>(float_t _x = 0, float_t _y = 0) :
        x(_x), y(_y) {}
    float_t real() const { return x; }
    float_t imag() const { return y; }
    void real(float_t _x) { x = _x; }
    void imag(float_t _y) { y = _y; }
    mycomplex<float_t>& operator+=(const
        mycomplex<float_t> &other) { x += other.x; y +=
        other.y; return *this; }
    mycomplex<float_t>& operator-=(const
        mycomplex<float_t> &other) { x -= other.x; y -=
        other.y; return *this; }
    mycomplex<float_t> operator+(const mycomplex<float_t>
        &other) const { return mycomplex<float_t>(*this)
        += other; }
    mycomplex<float_t> operator-(const mycomplex<float_t>
        &other) const { return mycomplex<float_t>(*this)
        -= other; }
    mycomplex<float_t> operator*(const mycomplex<float_t>
        &other) const {
        return {x * other.x - y * other.y, x * other.y +
        other.x * y};
    }
    mycomplex<float_t> operator*(float_t mult) const {
        return {x * mult, y * mult};
    }
    friend mycomplex<float_t> conj(const
        mycomplex<float_t> &c) {
        return {c.x, -c.y};
    }
    friend ostream& operator<<(ostream &stream, const
        mycomplex<float_t> &c) {
        return stream << '(' << c.x << ", " << c.y << ')';
    }
};

using cd = mycomplex<double>;
void fft(vector<cd> &a, bool invert) {
    int n = a.size();
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j < bit; bit >>= 1)

```

```

            j ^= bit;
            j ^= bit;
            if (i < j)
                swap(a[i], a[j]);
        }
        for (int len = 2; len <= n; len <= 1) {
            double ang = 2 * PI / len * (invert ? -1 : 1);
            cd wlen(cos(ang), sin(ang));
            for (int i = 0; i < n; i += len) {
                cd w(1);
                for (int j = 0; j < len / 2; j++) {
                    cd u = a[i+j], v = a[i+j+len/2] * w;
                    a[i+j] = u + v;
                    a[i+j+len/2] = u - v;
                    w = w*wlen;
                }
            }
            if (invert) {
                for (cd &x : a) {
                    double z = n;
                    z=1/z;
                    x = x*z;
                }
                // x /= n;
            }
        }
    }

void multiply (const vector<bool> &a, const
    vector<bool> &b, vector<bool> &res) { //change all
    the bool to your type needed
    vector<cd> fa (a.begin(), a.end()), fb (b.begin(),
        b.end());
    size_t n = 1;
    while (n < max (a.size(), b.size())) n <= 1;
    fa.resize (n), fb.resize (n);
    fft (fa, false), fft (fb, false);
    for (size_t i=0; i<n; ++i)
        fa[i] =fa[i] * fb[i];
    fft (fa, true);
    res.resize (n);
    for (size_t i=0; i<n; ++i)
        res[i] = round(fa[i].real());
    while(res.back()==0) res.pop_back();
}

void pow(const vector<bool> &a, vector<bool> &res, long
    long int k){
    vector<bool> po=a;
    res.resize(1);
    res[0] = 1;
    while(k){
        if(k&1){
            multiply(po, res, res);
        }
        multiply(po, po, po);
        k/=2;
    }
}

```

7.6 GaussElimination [39 lines] - 1203a4bb

```

template<typename ld>
int gauss(vector<vector<ld>>& a, vector<ld>& ans) {
    const ld EPS = 1e-9;
    int n = a.size(); //number of equations
    int m = a[0].size() - 1; //number of variables

```

```

    vector<int> where(m, -1); //indicates which row
    contains the solution
    int row, col;
    for (col = 0, row = 0; col < m && row < n; ++col) {
        int sel = row; //which row contains the maximum
        value/
        for (int i = row + 1; i < n; i++)
            if (abs(a[i][col]) > abs(a[sel][col]))
                sel = i;
        if (abs(a[sel][col]) < EPS) continue; //it's
        basically 0.
        a[sel].swap(a[row]); //taking the max row up
        where[col] = row;
        ld t = a[row][col];
        for (int i = col; i <= m; i++) a[row][i] /= t;
        for (int i = 0; i < n; i++) {
            if (i != row) {
                ld c = a[i][col];
                for (int j = col; j <= m; j++)
                    a[i][j] -= a[row][j] * c;
            }
        }
        row++;
    }
    ans.assign(m, 0);
    for (int i = 0; i < m; i++)
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];
    for (int i = 0; i < n; i++) {
        ld sum = 0;
        for (int j = 0; j < m; j++)
            sum += ans[j] * a[i][j];
        if (abs(sum - a[i][m]) > EPS) //L.H.S!=R.H.S
            ans.clear(); //No solution
    }
    return row;
}

```

7.7 GaussMod2 [44 lines] - 1d49c381

```

template<typename T>
struct Gauss {
    int bits = 60;
    vector<T> table;
    Gauss() {
        table = vector<T>(bits, 0);
    }
    //call with constructor to define bit size.
    Gauss(int _bits) {
        bits = _bits;
        table = vector<T>(bits, 0);
    }
    int basis() //return rank/size of basis
    {
        int ans = 0;
        for (int i = 0; i < bits; i++)
            if (table[i])
                ans++;
        return ans;
    }
    bool can(T x) //can x be obtained from the basis
    {
        for (int i = bits - 1; i >= 0; i--) x = min(x, x ^
            table[i]);
    }
}

```



```

    return x == 0;
}
void add(T x) {
    for (int i = bits - 1; i >= 0 && x; i--) {
        if (table[i] == 0) {
            table[i] = x;
            x = 0;
        }
        else x = min(x, x ^ table[i]);
    }
}
T getBest() {
    T x = 0;
    for (int i = bits - 1; i >= 0; i--)
        x = max(x, x ^ table[i]);
    return x;
}
void Merge(Gauss& other) {
    for (int i = bits - 1; i >= 0; i--)
        add(other.table[i]);
}
};

```

7.8 Karatsuba Idea [5 lines] - 6686aa78

Three subproblems:

$a = x_H y_H$
 $d = x_L y_L$
 $e = (x_H + x_L)(y_H + y_L) - a - d$
 Then $xy = a r_n + e r_n/2 + d$

7.9 Linear Diophantine [19 lines] - ebfad56a

```

int extended_gcd(ll a, ll b, ll& x, ll& y) {
    if (b == 0) {x = 1; y = 0; return a;}
    ll x1, y1;
    ll d = extended_gcd(b, a % b, x1, y1);
    x = y1; y = x1 - y1 * (a / b);
    return d;
}
/*x'=x+(k*B/g), y'=y-(k*A/g); infinite soln
if A=B=0, C must equal 0 and any x,y is solution;
if A/B=0, (x,y)=(C/A,k)|(k,C/B)*
bool LDE(ll A, ll B, ll C, ll &x, ll &y) {
    int g=gcd(A,B);
    if (C%g!=0) return false;
    int a=A/g, b=B/g, c=C/g;
    extended_gcd(a,b,x,y); //ax+by=1
    if (g<0) {a*=-1; b*=-1; c*=-1;} //Ensure gcd(a,b)=1
    x*=c; y*=c; //ax+by=c
    return true; //Solution Exists
}

```

7.10 Matrix [100 lines] - 60a4fb89

```

template<typename T>
struct Matrix {
    T MOD = 1e9 + 7; //change if necessary
    T add(T a, T b) const {
        T res = a + b;
        if (res >= MOD) return res - MOD;
        return res;
    }
    T sub(T a, T b) const {
        T res = a - b;
        if (res < 0) return res + MOD;
        return res;
    }
};

```

```

T mul(T a, T b) const {
    T res = a * b;
    if (res >= MOD) return res % MOD;
    return res;
}
int R, C;
vector<vector<T>> mat;
Matrix(int _R = 0, int _C = 0) {
    R = _R, C = _C;
    mat.resize(R);
    for (auto& v : mat) v.assign(C, 0);
}
void print() {
    for (int i = 0; i < R; i++)
        for (int j = 0; j < C; j++)
            cout << mat[i][j] << " \n"[j == C - 1];
}
void createIdentity() {
    for (int i = 0; i < R; i++)
        for (int j = 0; j < C; j++)
            mat[i][j] = (i == j);
}
Matrix operator+(const Matrix& o) const {
    Matrix res(R, C);
    for (int i = 0; i < R; i++)
        for (int j = 0; j < C; j++)
            res[i][j] = add(mat[i][j] + o.mat[i][j]);
}
Matrix operator-(const Matrix& o) const {
    Matrix res(R, C);
    for (int i = 0; i < R; i++)
        for (int j = 0; j < C; j++)
            res[i][j] = sub(mat[i][j] + o.mat[i][j]);
}
Matrix operator*(const Matrix& o) const {
    Matrix res(R, o.C);
    for (int i = 0; i < R; i++)
        for (int j = 0; j < o.C; j++)
            for (int k = 0; k < C; k++)
                res.mat[i][j] = add(res.mat[i][j],
                    mul(mat[i][k], o.mat[k][j]));
    return res;
}
Matrix pow(long long x) {
    Matrix res(R, C);
    res.createIdentity();
    Matrix<T> o = *this;
    while (x) {
        if (x & 1) res = res * o;
        o = o * o;
        x >>= 1;
    }
    return res;
}
Matrix inverse() //Only square matrix && non-zero determinant
{
    Matrix res(R, R + R);
    for (int i = 0; i < R; i++) {
        for (int j = 0; j < R; j++)
            res.mat[i][j] = mat[i][j];
        res.mat[i][R + i] = 1;
    }
    for (int i = 0; i < R; i++) {

```

```

        //find row 'r' with highest value at [r][i]
        int tr = i;
        for (int j = i + 1; j < R; j++)
            if (abs(res.mat[j][i]) > abs(res.mat[tr][i]))
                tr = j;
        //swap the row
        res.mat[tr].swap(res.mat[i]);
        //make 1 at [i][i]
        T val = res.mat[i][i];
        for (int j = 0; j < R + R; j++) res.mat[i][j] /= val;
        //eliminate [r][i] from every row except i.
        for (int j = 0; j < R; j++) {
            if (j == i) continue;
            for (int k = R + R - 1; k >= i; k--) {
                res.mat[j][k] -= res.mat[i][k] * res.mat[j][i]
                    / res.mat[i][i];
            }
        }
    }
    Matrix ans(R, R);
    for (int i = 0; i < R; i++)
        for (int j = 0; j < R; j++)
            ans.mat[i][j] = res.mat[i][R + j];
    return ans;
}
};

```

7.11 Miller-Rabin-Pollard-Rho [46 lines] - d12e2f09

```

namespace rho {
    ll mul(ll a, ll b, ll mod) {
        ll ret = __int128(a) * b - mod * (ll)(1.L / mod * a
            * b);
        return ret + mod * (ret < 0) - mod * (ret >=
            (ll)mod);
    }
    ll bigMod(ll a, ll e, ll mod) {
        ll ret = 1;
        while (e) {
            if (e & 1) ret = mul(ret, a, mod);
            a = mul(a, a, mod);
            e >>= 1;
        }
        return ret;
    }
    bool isPrime(ll n) {
        if (n < 2 or n % 6 % 4 != 1) return (n | 1) == 3;
        ll a[] = {2, 325, 9375, 28178, 450775, 9780504,
            1795265022};
        ll s = __builtin_ctzll(n - 1), d = n >> s;
        for (ll x : a) {
            ll p = bigMod(x % n, d, n), i = s;
            while (p != 1 and p != n - 1 and x % n and i--) p
                = mul(p, p, n);
            if ((p != n - 1) and i != s) return 0;
        }
        return 1;
    }
    ll pollard(ll n) {
        auto f = [&](ll x) { return mul(x, x, n) + 1; };
        ll x = 0, y = 0, t = 0, prod = 2, i = 1, q;
        while (t++ % 40 or gcd(prod, n) == 1) {
            if (x == y) x = ++i, y = f(x);

```

```

    if ((q = mul(prod, max(x, y) - min(x, y), n)))
        prod = q;
    x = f(x), y = f(f(y));
}
return gcd(prod, n);
}
vector<ll> factors(ll n) { // return unsorted
    factors
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ll x = pollard(n);
    auto l = factors(x), r = factors(n / x);
    l.insert(l.end(), r.begin(), r.end());
    return l;
}
};

```

7.12 NTT [96 lines] - b8108f51

```

ll power(ll a, ll p, ll mod) {
    if (p==0) return 1;
    ll ans = power(a, p/2, mod);
    ans = (ans * ans)%mod;
    if(p%2) ans = (ans * a)%mod;
    return ans;
}
int primitive_root(int p) {
    vector<int> factor;
    int phi = p-1, n = phi;
    for (int i=2; i*i<=n; i++) {
        if (n%i) continue;
        factor.push_back(i);
        while (n%i==0) n/=i;
    }
    if (n>1) factor.push_back(n);
    for (int res=2; res<=p; res++) {
        bool ok = true;
        for (int i=0; i<factor.size() && ok; i++)
            ok &= power(res, phi/factor[i], p) != 1;
        if (ok) return res;
    }
    return -1;
}
int nttdata(int mod, int &root, int &inv, int &pw) {
    int c = 0, n = mod-1;
    while (n%2==0) c++, n/=2;
    pw = (mod-1)/n;
    int g = primitive_root(mod);
    root = power(g, n, mod);
    inv = power(root, mod-2, mod);
    return c;
}
const int M = 786433;
struct NTT {
    int N;
    vector<int> perm;
    int mod, root, inv, pw;
    NTT(){}
    NTT(int mod, int root, int inv, int pw) : mod(mod),
        root(root), inv(inv), pw(pw) {}
    void precalculate() {
        perm.resize(N);
        perm[0] = 0;
        for (int k=1; k<N; k<=1) {
            for (int i=0; i<k; i++) {

```

```

                perm[i] <= 1;
                perm[i+k] = 1 + perm[i];
            }
        }
    }
    void fft(vector<ll> &v, bool invert = false) {
        if (v.size() != perm.size()) {
            N = v.size();
            assert(N && (N&(N-1)) == 0);
            precalculate();
        }
        for (int i=0; i<N; i++)
            if (i < perm[i])
                swap(v[i], v[perm[i]]);
        for (int len = 2; len <= N; len <= 1) {
            ll factor = invert ? inv : root;
            for (int i=len; i<pw; i<=1)
                factor = (factor * factor) % mod;
            for (int i=0; i<N; i+=len) {
                ll w = 1;
                for (int j=0; j<len/2; j++) {
                    ll x = v[i+j], y = (w*v[i+j+len/2])%mod;
                    v[i+j] = (x+y)%mod;
                    v[i+j+len/2] = (x-y+mod)%mod;
                    w = (w*factor)%mod;
                }
            }
        }
        if (invert) {
            ll n1 = power(N, mod-2, mod);
            for (ll &x: v) x = (x*n1)%mod;
        }
    }
    vector<ll> multiply(vector<ll> a, vector<ll> &b) {
        while (a.size() && a.back() == 0) a.pop_back();
        while (b.size() && b.back() == 0) b.pop_back();
        int n = 1;
        while (n < a.size() + b.size()) n<=1;
        a.resize(n);
        b.resize(n);
        fft(a);
        fft(b);
        for (int i=0; i<n; i++) a[i] = (a[i] * b[i])%M;
        fft(a, true);
        while (a.size() && a.back() == 0) a.pop_back();
        return a;
    }
    // int mod=786433, root, inv, pw;
    // nttdata(mod, root, inv, pw);
    // NTT nn = NTT(mod, root, inv, pw);
};

```

7.13 No of Digits in n! in base B [7 lines] - 21d4aeb2

```

ll NoOfDigitInNFactInBaseB(ll N, ll B) {
    ll i;
    double ans=0;
    for(i=1; i<=N; i++) ans+=log(i);
    ans=ans/log(B), ans=ans+1;
    return (ll)ans;
}

```

7.14 SOD Upto N [42 lines] - 10b7fcd5

```

int gp[1000000];
ll SOD[N];

```

```

void sieve() { // O(N log log N)
    gp[1] = 1;
    for (int i = 2; i < N; i++) {
        if (gp[i] == 0) {
            for (int j = i; j <= N; j += i) {
                gp[j] = i; // greatest prime factor
            }
        }
    }
}

void FindSOD() { // sum of divisors up to N in O(N log log N)
    sieve();
    for (int i = 2; i < N; i++) {
        ll x = i;
        ll sod = 1;
        while (x > 1) {
            ll p = gp[x];
            ll mul = p;
            while (x % p == 0) {
                x /= p;
                mul *= p; // mul = p^ni (at the end of loop)
            }
            mul -= 1;
            mul /= (p-1); // geometric series:
            // (p^(n+1)-1)/(p-1)
            sod *= mul;
        }
        SOD[i] = sod;
    }
}

ll NOD(ll n) {
    vector<pair<ll, ll>> fact = factor(n);
    ll divisors = 1;
    for (auto x : fact) {
        divisors *= (x.second + 1);
    }
    return divisors;
}

```

7.15 Sieve Phi Mobius [26 lines] - 966c3571

```

const int N = 1e7;
vector<int> pr;
int mu[N + 1], phi[N + 1], lp[N + 1];
void sieve() {
    phi[1] = 1, mu[1] = 1;
    for (int i = 2; i <= N; i++) {
        if (lp[i] == 0) {
            lp[i] = i;
            phi[i] = i - 1;
            pr.push_back(i);
        }
        for (int j = 0; j < pr.size() && i * pr[j] <= N; j++) {
            lp[i * pr[j]] = pr[j];
            if (i % pr[j] == 0) {
                phi[i * pr[j]] = phi[i] * pr[j];
                break;
            }
            else

```

```

    phi[i * pr[j]] = phi[i] * phi[pr[j]];
}
for (int i = 2; i <= N; i++) {
    if (lp[i / lp[i]] == lp[i]) mu[i] = 0;
    else mu[i] = -1 * mu[i / lp[i]];
}
}

```

7.16 nCr [46 lines] - 79b48d4a

```

ll power(ll a, ll b) {
    ll result = 1;
    a = a % mod;
    while (b > 0) {
        if (b & 1) result = (result * a) % mod;
        a = (a * a) % mod;
        b >>= 1ll;
    }
    return result;
}

int f[N], invf[N];

void pre() {
    f[0] = 1;
    for (int i = 1; i < N; i++) {
        f[i] = 1LL * i * f[i - 1] % mod;
    }
    invf[N - 1] = power(f[N - 1], mod - 2);
    for (int i = N - 2; i >= 0; i--) {
        invf[i] = 1LL * invf[i + 1] * (i + 1) % mod;
    }
}

int nCr(int n, int r) {
    if (n < r or n < 0) return 0;
    return 1LL * f[n] * invf[r] % mod * invf[n - r] %
        mod;
}

```

```

// Catalan Number: 1, 1, 2, 5, 14, 42, 132, 429, 1430,
// 4862, ...
// C(n) = (1 / (n + 1)) * (2n choose n) = (2n choose n)
// - (2n choose n + 1)
ll catalan = (nCr(2*n, n) % mod - nCr(2*n, n+1) % mod +
    mod) % mod;
// Hockey Stick Identity:
// sum_{k=r}^{n} (k choose r) = (n+1 choose r+1)
ll hockey_stick = nCr(n + 1, r + 1);
ll vandermonde = nCr(m + n, r);
ll C[N + 2][N + 2];
void pre(){
    C[0][0] = 1;
    for(int n = 1; n <= N; n++){
        C[n][0] = C[n][n] = 1;
        for(int k = 1; k < n; k++){
            C[n][k] = C[n - 1][k - 1] + C[n - 1][k];
        }
    }
}

```

8 Misc

8.1 BigSum [35 lines] - 2a3cf6fd

```

string findSum(string str1, string str2)
{

```

```

    if(str1.length() > str2.length()) swap(str1, str2);
    string str = "";
    int n1 = str1.length(), n2 = str2.length();
    reverse(str1.begin(), str1.end());
    reverse(str2.begin(), str2.end());
    int carry = 0;
    for(int i = 0; i < n1; i++)
    {
        int sum = ((str1[i] - '0') + (str2[i] - '0') + carry);
        str.push_back(sum % 10 + '0');
        carry = sum / 10;
    }
    for(int i = n1; i < n2; i++)
    {
        int sum = ((str2[i] - '0') + carry);
        str.push_back(sum % 10 + '0');
        carry = sum / 10;
    }
    if(carry) str.push_back(carry + '0');
    reverse(str.begin(), str.end());
    return str;
}

int compare(string str1, string str2)
{
    int n1 = str1.length(), n2 = str2.length();
    if (n1 < n2) return -1;
    if (n2 < n1) return 1;
    for (int i = 0; i < n1; i++) {
        if (str1[i] < str2[i]) return -1;
        else if (str1[i] > str2[i]) return 1;
    }
    return 0;
} // 0 equal, 1 str1>str2, -1 str1<str2

```

8.2 Bit Hacks [51 lines] - 15b43442

```

#define ckbbit(n, k) ((n) & (1LL << (k)))
#define toggle(n, k) ((n) ^ (1LL << (k)))
#define setbit(n, k) ((n) |= (1LL << (k)))
#define unsetbit(n, k) ((n) &= ~(1LL << (k)))
#define lowbit(n) ((n) & -(n))
#define highbit(n) (63 - __builtin_clzll(n))
// ----- Iterate Submasks (non-zero) -----
#define ForSubmask(s, m) for (ll s = (m); s; s = (s -
    1) & (m))
// ----- Iterate Supersets of m inside [0, 1<n) -----
#define ForSuperset(s, m, n) for (ll s = (m); s < (1LL
    << (n)); s = (s + 1) | (m))
// ----- Gosper's Hack | next mask with same popcount
// -----
inline ll NextCombination(ll x){
    ll u = x & -x;
    ll v = x + u;
    return v + (((v ^ x) / u) >> 2);
}

// XOR Properties
a | b = a ^ b + a & b
a ^ (a & b) = (a | b) ^ b
b ^ (a & b) = (a | b) ^ a
(a & b) ^ (a | b) = a ^ b
// Addition
a + b = a | b + a & b
a + b = a ^ b + 2(a & b)
// Subtraction
a - b = (a ^ (a & b)) - ((a | b) ^ a)
a - b = ((a | b) ^ b) - ((a | b) ^ a)

```

```

a - b = (a ^ (a & b)) - (b ^ (a & b))
a - b = ((a | b) ^ b) - (b ^ (a & b))
// Precompute XOR from 1 to n
ll prexor(ll n){
    if(n % 4 == 0) return n;
    else if(n % 4 == 1) return 1;
    else if(n % 4 == 2) return n + 1;
    else return 0;
}

// Bit Hacks
# x & -x is the least bit in x.
# iterate over all the subsets of the mask
for (int s=m; ; s=(s-1)&m) {
    ... you can use s ...
    if (s==0) break;
}
# c = x&-x, r = x+c; (((r^x) >> 2)/c) | r is the
next number after x with the same number of bits set.
# __builtin_popcount(x) // number of ones in binary
# __builtin_popcountll(x) // for long long
# __builtin_clz(x) // number of leading zeros
# __builtin_ctz(x) // number of trailing zeros, they
also have long long version

```

// __int128 for 128 bit integer operations

8.3 Bitset C++ [33 lines] - 62a433dd

```

// Declaration & Initialization
bitset<100> bs, bs1(42); // empty, from decimal
bitset<8> bs2("11001010"); // from binary string

// Set/Reset/Flip
bs.set(), bs.set(5), bs[5] = 1; // set all, set bit 5,
direct assignment
bs.reset(), bs.reset(5); // reset all, reset bit 5
bs.flip(), bs.flip(5); // flip all, flip bit 5

// Query
bs.test(5), bs.all(), bs.any(), bs.none(); // test bit,
all set, any set, none set
bs.count(), bs.size(); // count set bits, total size

// Bitwise Operations
bitset<8> a("10101010"), b("11001100"), c;
c = a & b, c = a | b, c = a ^ b, c = ~a; // AND, OR,
XOR, NOT
c = a << 2, c = a >> 2; // left shift, right shift

// Conversion
bs.to_ulong(), bs.to_ullong(), bs.to_string(); // to
unsigned long, unsigned long long, string

// Find Set Bits
bitset<17> BS; BS[1] = BS[7] = 1;
BS.Find_first(); // first set bit (or size() if none)
BS.Find_next(idx); // next set bit after idx (or size()
if none)
for(int i = BS.Find_first(); i < BS.size(); i =
    BS.Find_next(i))
    cout << i << endl; // iterate all set bits

// Applications

```

```
for(int m = 0; m < (1 << n); m++) bitset<32> bs(m); //
    subset generation
bool isPow2 = (bs.count() == 1); // check power of 2
```

8.4 Custom Hash [19 lines] - 496c4203

```
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    size_t operator()(const pair<int,int>& p) const
    noexcept {
        static const uint64_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().count();

        uint64_t key = (uint64_t(uint32_t(p.first)) <<
            32)
            | uint32_t(p.second);
        return splitmix64(key + FIXED_RANDOM);
    }
    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().count();

        return splitmix64(x + FIXED_RANDOM);
    }
};
```

8.5 Important [94 lines] - a982d219

```
// Ternary Search Template
double left = 0, right = 1e8;
// unimodal function: exactly one minima or maxima
while(fabs(right - left) > eps){
    double m1 = left + (right - left) / 3;
    double m2 = right - (right - left) / 3;
    double f1 = 0, f2 = 0;
    for(int i = 0; i < n; i++){
        f1 = max(f1, t[i] + fabs(x[i] - m1));
        f2 = max(f2, t[i] + fabs(x[i] - m2));
    } // .....min.....
    if(f1 > f2) left = m1;
    else if(f1 < f2) right = m2;
    else left = m1, right = m2;
}
template <const int32_t MOD>
struct modint {
    int32_t value;
    modint() = default;
    modint(int32_t value_) : value(value_) {}
    inline modint<MOD> operator + (modint<MOD> other)
        const { int32_t c = this->value + other.value;
        return modint<MOD>(c >= MOD ? c - MOD : c); }
    inline modint<MOD> operator - (modint<MOD> other)
        const { int32_t c = this->value - other.value;
        return modint<MOD>(c < 0 ? c + MOD : c); }
    inline modint<MOD> operator * (modint<MOD> other)
        const { int32_t c = (int64_t)this->value *
        other.value % MOD; return modint<MOD>(c < 0 ? c +
        MOD : c); }
```

```
inline modint<MOD> & operator += (modint<MOD> other) {
    this->value += other.value; if (this->value >=
    MOD) this->value -= MOD; return *this; }
inline modint<MOD> & operator -= (modint<MOD> other) {
    this->value -= other.value; if (this->value <
    0) this->value += MOD; return *this; }
inline modint<MOD> & operator *= (modint<MOD> other) {
    this->value = (int64_t)this->value * other.value %
    MOD; if (this->value < 0) this->value += MOD;
    return *this; }
inline modint<MOD> operator - () const { return
    modint<MOD>(this->value ? MOD - this->value : 0);
    }
modint<MOD> pow(uint64_t k) const { modint<MOD> x =
    *this, y = 1; for (; k >= 1) { if (k & 1) y
    *= x; x *= x; } return y; }
modint<MOD> inv() const { return pow(MOD - 2); } //
    MOD must be a prime
inline modint<MOD> operator / (modint<MOD> other)
    const { return *this * other.inv(); }
inline modint<MOD> operator /= (modint<MOD> other)
    { return *this *= other.inv(); }
inline bool operator == (modint<MOD> other) const {
    return value == other.value; }
inline bool operator != (modint<MOD> other) const {
    return value != other.value; }
inline bool operator < (modint<MOD> other) const {
    return value < other.value; }
inline bool operator > (modint<MOD> other) const {
    return value > other.value; }
};
template <int32_t MOD> modint<MOD> operator * (int64_t
    value, modint<MOD> n) { return modint<MOD>(value) *
    n; }
template <int32_t MOD> modint<MOD> operator * (int32_t
    value, modint<MOD> n) { return modint<MOD>(value %
    MOD) * n; }
template <int32_t MOD> istream & operator >> (istream &
    in, modint<MOD> &n) { return in >> n.value; }
template <int32_t MOD> ostream & operator << (ostream &
    out, modint<MOD> n) { return out << n.value; }

using mint = modint<mod>;
struct combi{
    int n; vector<mint> facts, finvs, invs;
    combi(int _n): n(_n), facts(_n), finvs(_n), invs(_n){
        facts[0] = finvs[0] = 1;
        invs[1] = 1;
        for (int i = 2; i < n; i++) invs[i] = invs[mod % i]
            * (-mod / i);
        for(int i = 1; i < n; i++){
            facts[i] = facts[i - 1] * i;
            finvs[i] = finvs[i - 1] * invs[i];
        }
    }
    inline mint fact(int n) { return facts[n]; }
    inline mint finv(int n) { return finvs[n]; }
    inline mint inv(int n) { return invs[n]; }
    inline mint ncr(int n, int k) { return n < k or k < 0
        ? 0 : facts[n] * finvs[k] * finvs[n-k]; }
};
combi C(N);
ll power(ll a, ll b) {
    ll ans = 1;
```

```
bool flag = (a >= mod);
while(b) {
    if(b & 1) {
        ans *= a;
        if(ans >= mod) {
            ans %= mod;
            flag = true;
        }
    }
    a *= a;
    if(a >= mod) {
        a %= mod;
        flag = true;
    }
    b >>= 1;
    return (ans + (flag * mod)) % mod;
}
set <string> getPerm(string s) {
    int n = s.size();
    vector<int> v(n);
    for(int i = 0; i < n; i++) v[i] = i;
    set <string> st;
    do{
        string ss = s;
        // cout << ss << " ";
        for(int i = 0; i < n; i++){
            ss[i] = s[v[i]];
        }
        st.insert(ss);
    } while (next_permutation(v.begin(), v.end()));
    return st;
}
```

8.6 N-Queen [15 lines] - c51ac310

```
bool place(vector <int> &x, int row, int col) {
    for(int j = 0; j < row; j++){
        if(x[j] == col || abs(x[j] - col) == abs(row -
            j)) return false;
    }
    return true;
}
void NQueens(vector <int> &x, int row, int n) {
    for(int col = 0; col < n; col++){
        if(place(x, row, col)){
            x[row] = col;
            if(row == n - 1) ans.push_back(x);
            else NQueens(x, row + 1, n);
        }
    }
}
```

8.7 Template [33 lines] - 52af6a79

```
// #pragma GCC optimize("O3,unroll-loops")
// #pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace std;
using namespace __gnu_pbds;

template <typename A, typename B> ostream&
operator<<(ostream& os, const pair<A, B>& p) {
    return os << '(' << p.first << ", " << p.second <<
    ')'; }
```



```
template <typename T_container, typename T = typename
enable_if<!is_same<T_container, string>::value,
typename T_container::value_type>::type> ostream&
operator<<(ostream& os, const T_container& v) { os
<< '{'; string sep; for (const T& x : v) os << sep
<< x, sep = ", "; return os << '}'; }
void dbg_out() { cerr << endl; }
template <typename Head, typename... Tail> void
dbg_out(Head H, Tail... T) { cerr << " " << H;
dbg_out(T...); }
```

```
#ifdef SMIE
#define debug(args...) cerr << "(" << #args << "):",
    dbg_out(args)
#else
#define debug(args...)
#endif
```

```
template <typename T> inline T gcd(T a, T b) { T c; while
(b) { c = b; b = a % b; a = c; } return a; } // better
than __gcd
ll powmod(ll a, ll b, ll MOD) { ll res = 1; a %=
MOD; assert(b >= 0); for (; b >= 1) { if (b &
1) res = res * a % MOD; a = a * a % MOD; } return res;
}
template <typename T> using orderedSet = tree<T,
null_type, less_equal<T>, rb_tree_tag,
tree_order_statistics_node_update>;
//order_of_key(k) - number of element strictly less than
k
//find_by_order(k) - k'th element in set.(0
indexed)(iterator)
```

```
mt19937
rng(chrono::steady_clock::now().time_since_epoch()
.count());
//uniform_int_distribution<int>(0, i)(rng)
int main(int argc, char* argv[]) {
ios_base::sync_with_stdio(false); //DON'T CC++
cin.tie(NULL); //DON'T use for interactive
int seed = atoi(argv[1]);
}
```

8.8 debug scripts [49 lines] - 72496740

```
#!/bin/bash
# compact debug helper: build/test/debug/stress
# Install: mkdir -p ~/bin && chmod +x ~/bin/* && add to
PATH
```

```
build(){ # build <name> [flags]
g++ -std=gnu++17 -Wall -O2 -g
-fsanitize=undefined,address $2 "$1.cpp" -o "$1"
}
```

```
test_all(){ # test <name>
build "$1" || return 1
for IN in "$1".in*; do
echo "=== $IN ==="; cat "$IN"
echo "--- OUTPUT ---"; ./ $1 < "$IN"
done
}
```

```
debug(){ # debug <name>
build "$1" -DSMIE || return 1
./ $1
```

```
}
stress(){ # stress <name>
build "$1" || return 1
build "${1}_gen" || return 1
build "${1}_brute" || return 1
i=0
while true; do ((i++)); echo "Test $i"
./ ${1}_gen "$i" > inp
./ $1 < inp > out1
./ ${1}_brute < inp > out2
if ! diff -w out1 out2 >/dev/null; then
echo "FAILED on test $i"; cat inp; echo "Your:";
cat out1; echo "Exp:"; cat out2
break
fi
done
}
```

```
# Quick: build name | test name | debug name | stress
name
```

```
if [[ "${BASH_SOURCE[0]}" == "${0}" ]]; then
cmd="$1"; shift || true
case "$cmd" in
build) build "$@" ;;
test) test_all "$@" ;;
debug) debug "$@" ;;
stress) stress "$@" ;;
*) echo "Usage: $0 {build|test|debug|stress} name"
;;
esac
fi
```

8.9 pbds inversions [21 lines] - 9cb3c2cf

```
#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace std;
using namespace __gnu_pbds;
template <class T>
using pbds = tree<T, null_type, less<T>, rb_tree_tag,
tree_order_statistics_node_update>;
// greater for descending, less_equal for multiset
typedef long long ll;
// Count inversions in array using PBDS - O(n log n)
// Returns number of pairs (i, j) where i < j and arr[i]
> arr[j]
template <class T>
ll countInversions(vector<T> &arr) {
ll inv = 0;
pbds<T> pset;
for(int i = arr.size() - 1; i >= 0; i--) { //
traverse from right to left
inv += pset.order_of_key(arr[i]); // count
elements < arr[i] in right side
pset.insert(arr[i]);
}
return inv;
}
```

8.10 sublime-build [12 lines] - ea28f58d

```
// Windows:
{
```

```
"cmd": "g++.exe -std=c++17 $file -o
$file_base_name.exe && $file_base_name.exe <
inputf.in > outputf.in",
"shell": true,
"working_dir": "$file_path"
}
// Linux/MacOS:
{
"cmd": "g++ -std=c++17 $file -o $file_base_name &&
./ $file_base_name < inputf.in > outputf.in",
"shell": true,
"working_dir": "$file_path"
}
```

9 String

9.1 Double Hasing [50 lines] - f434a7a8

```
struct SimpleHash {
int len;
long long base, mod;
vector<int> P, H, R;
SimpleHash() {}
SimpleHash(string str, long long b, long long m) {
base = b, mod = m, len = str.size();
P.resize(len + 4, 1), H.resize(len + 3, 0),
R.resize(len + 3, 0);
for (int i = 1; i <= len + 3; i++)
P[i] = (P[i - 1] * base) % mod;
for (int i = 1; i <= len; i++)
H[i] = (H[i - 1] * base + str[i - 1] + 1007)
% mod;
for (int i = len; i >= 1; i--)
R[i] = (R[i + 1] * base + str[i - 1] + 1007)
% mod;
}
inline int range_hash(int l, int r) {
int hashval = H[r + 1] - ((long long)P[r - 1 +
1] * H[1] % mod);
return (hashval < 0 ? hashval + mod : hashval);
}
inline int reverse_hash(int l, int r) {
int hashval = R[l + 1] - ((long long)P[r - 1 +
1] * R[r + 2] % mod);
return (hashval < 0 ? hashval + mod : hashval);
}
};
struct DoubleHash {
SimpleHash sh1, sh2;
DoubleHash() {}
DoubleHash(string str) {
sh1 = SimpleHash(str, 1949313259, 2091573227);
sh2 = SimpleHash(str, 1997293877, 2117566807);
}
long long concate(DoubleHash& B, int l1, int r1,
int l2, int r2) {
int len1 = r1 - l1 + 1, len2 = r2 - l2 + 1;
long long x1 = sh1.range_hash(l1, r1),
x2 = B.sh1.range_hash(l2, r2);
x1 = (x1 * B.sh1.P[len2]) % 2091573227;
long long newx1 = (x1 + x2) % 2091573227;
x1 = sh2.range_hash(l1, r1);
x2 = B.sh2.range_hash(l2, r2);
x1 = (x1 * B.sh2.P[len2]) % 2117566807;
long long newx2 = (x1 + x2) % 2117566807;
```

```

    return (newx1 << 32) ^ newx2;
}
inline long long range_hash(int l, int r) {
    return ((long long)sh1.range_hash(l, r) << 32) ^
           sh2.range_hash(l, r);
}
inline long long reverse_hash(int l, int r) {
    return ((long long)sh1.reverse_hash(l, r) << 32) ^
           sh2.reverse_hash(l, r);
}
};

```

9.2 KMP [33 lines] - c11dbb44

```

vector<int> build_lps(string p) {
    vector<int> lps(p.size());
    int j = 0;
    for(int i = 1; i < p.size(); ) {
        if(p[i] == p[j]){
            lps[i] = j + 1;
            ++i, j++;
        }
        else{
            if(j != 0) j = lps[j - 1];
            else lps[i] = 0, ++i;
        }
    }
    return lps;
}
int kmp(string s, string p) {
    vector<int> lps = build_lps(p);
    int psz = p.size(), sz = s.size(), ans = 0;
    int i = 0, j = 0; // i -> s, j -> p;
    while(i < s.size()) {
        if(s[i] == p[j]){
            ++i, j++;
        }
        else{
            if(j != 0) j = lps[j - 1];
            else ++i;
        }
        if(j == p.size()){
            ans++;
        }
    }
    return ans;
}

```

9.3 Manacher [41 lines] - c534b74d

```

struct Manacher {
    vector<int> p[2]; // p[0]: even-length, p[1]:
                      // odd-length palindromes
    // p[1][i] = (maximum half-length of odd-length
    //            palindrome centered at i)
    // p[0][i] = (maximum half-length of even-length
    //            palindrome centered at i)
    // For s = "abbabba",
    // p[1][3] = 3, "abbabba" centered at index 3 has a
    //            length of 7, and 7/2 = 3.
    // p[0][2] = 2, "abba" centered between index 1 and
    //            2 has a length of 4, and 4/2 = 2.
    Manacher(string s) {
        int n = s.size();
        p[0].resize(n + 1);
        p[1].resize(n);
        for (int z = 0; z < 2; z++) {

```

```

            for (int i = 0, l = 0, r = 0; i < n; i++) {
                int t = r - i + !z; // calculate how
                // much we can reuse
                if (i < r) p[z][i] = min(t, p[z][l +
                t]); // reuse previous results if
                // possible
                // Expand around center i for the
                // current z (even/odd)
                int L = i - p[z][i], R = i + p[z][i] -
                !z;
                while (L >= 1 && R + 1 < n && s[L - 1]
                == s[R + 1]) {
                    p[z][i]++; L--; R++;
                }
                if (R > r) l = L, r = R;
            }
        }
    }
    bool is_palindrome(int l, int r) { // O(1)
        int mid = (l + r + 1) / 2;
        int len = r - l + 1;
        // Check if the palindrome from mid can cover
        // the substring of length 'len'
        return 2 * p[len % 2][mid] + len % 2 >= len;
    }
    // Returns the total number of palindromic
    // substrings in the string
    ll total_palindromic_substrings() { // O(n)
        ll total = 0;
        for (int z = 0; z < 2; z++) {
            for (int v : p[z]) {
                total += v;
            }
        }
        return total;
    }
};

```

9.4 Palindromic Tree [30 lines] - b398a8f0

```

struct PalindromicTree {
    int n, idx, t;
    vector<vector<int>> tree;
    vector<int> len, link;
    string s; // 1-indexed
    PalindromicTree(string str) {
        s = "$" + str;
        n = s.size();
        len.assign(n + 5, 0);
        link.assign(n + 5, 0);
        tree.assign(n + 5, vector<int>(26, 0));
    }
    void extend(int p) {
        while(s[p - len[t] - 1] != s[p]) t = link[t];
        int x = link[t], c = s[p] - 'a';
        while(s[p - len[x] - 1] != s[p]) x = link[x];
        if(!tree[t][c]){
            tree[t][c] = ++idx;
            len[idx] = len[t] + 2;
            link[idx] = len[idx] == 1 ? 2 : tree[x][c];
        }
        t = tree[t][c];
    }
    void build() {
        len[1] = -1, link[1] = 1;
        len[2] = 0, link[2] = 1;
    }
};

```

```

        idx = t = 2;
        for(int i = 1; i < n; i++) extend(i);
    }
};

```

9.5 Prefix Function Automaton [21 lines] - 5a2cc30b

/* create prefix function array in 26n.*/

```

int aut[mxn][26];
int lps[mxn];

void automaton(string &s) {
    int n = s.size();
    aut[0][s[0] - 'a'] = 1;
    for(int i = 1; i < n; i++) {
        for(int j = 0; j < 26; j++) {
            if(j == s[i] - 'a') {
                aut[i][j] = i + 1;
                lps[i + 1] = aut[lps[i]][j];
            }
            else {
                aut[i][j] = aut[lps[i]][j];
            }
        }
        cout << lps[i + 1] << endl;
    }
}

```

9.6 Suffix Array [78 lines] - 582667ab

```

struct SuffixArray {
    vector<int> p, c, rank, lcp;
    vector<vector<int>> st;
    SuffixArray(string const& s) {
        build_suffix(s + char(1));
        build_rank(p.size());
        build_lcp(s + char(1));
        build_sparse_table(lcp.size());
    }
    void build_suffix(string const& s) {
        int n = s.size();
        const int MX_ASCII = 256;
        vector<int> cnt(max(MX_ASCII, n), 0);
        p.resize(n); c.resize(n);
        for (int i = 0; i < n; i++) cnt[s[i]]++;
        for (int i = 1; i < MX_ASCII; i++) cnt[i] += cnt[i - 1];
        for (int i = 0; i < n; i++) p[--cnt[s[i]]] = i;
        c[p[0]] = 0;
        int classes = 1;
        for (int i = 1; i < n; i++) {
            if (s[p[i]] != s[p[i - 1]]) classes++;
            c[p[i]] = classes - 1;
        }
        vector<int> pn(n), cn(n);
        for (int h = 0; (1 << h) < n; ++h) {
            for (int i = 0; i < n; i++) {
                pn[i] = p[i] - (1 << h);
                if (pn[i] < 0) pn[i] += n;
            }
            fill(cnt.begin(), cnt.begin() + classes, 0);
            for (int i = 0; i < n; i++) cnt[c[pn[i]]]++;
            for (int i = 1; i < classes; i++) cnt[i] += cnt[i - 1];
            for (int i = n - 1; i >= 0; i--) p[--cnt[c[pn[i]]]] = pn[i];
            cn[p[0]] = 0; classes = 1;
        }
    }
};

```

```

for (int i = 1; i < n; i++) {
    pair<int, int> cur = {c[p[i]], c[(p[i] + (1 <<
        h)) % n]};
    pair<int, int> prev = {c[p[i-1]], c[(p[i-1] + (1
        << h)) % n]};
    if (cur != prev) ++classes;
    cn[p[i]] = classes - 1;
}
c.swap(cn);
}
}
void build_rank(int n) {
    rank.resize(n, 0);
    for (int i = 0; i < n; i++) rank[p[i]] = i;
}
void build_lcp(string const& s) {
    int n = s.size(), k = 0;
    lcp.resize(n - 1, 0);
    for (int i = 0; i < n; i++) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = p[rank[i] + 1];
        while (i + k < n && j + k < n && s[i+k] == s[j+k])
            k++;
        lcp[rank[i]] = k;
        if (k) k--;
    }
}
void build_sparse_table(int n) {
    int lim = __lg(n);
    st.resize(lim + 1, vector<int>(n)); st[0] = lcp;
    for (int k = 1; k <= lim; k++)
        for (int i = 0; i + (1 << k) <= n; i++)
            st[k][i] = min(st[k - 1][i], st[k - 1][i + (1 <<
                (k - 1))]);
}
int get_lcp(int i) { return lcp[i]; }
int get_lcp(int i, int j) {
    if (j < i) swap(i, j);
    j--; /*for lcp from i to j we don't need last lcp*/
    int K = __lg(j - i + 1);
    return min(st[K][i], st[K][j - (1 << K) + 1]);
}
};

```

9.7 Trie [28 lines] - 6b8f900b

const int maxn=100005;

```

struct Trie{
    int next[27][maxn];
    int endmark[maxn],sz;
    bool created[maxn];
    void insertTrie(string& s){
        int v=0;
        for(int i=0;i<(int)s.size();i++){
            int c=s[i]-'a';
            if(!created[next[c][v]]){
                next[c][v]=++sz;
                created[sz]=true;
            }
            v=next[c][v];
        }
        endmark[v]++;
    }
};

```

```

}
bool searchTrie(string& s){
    int v=0;
    for(int i=0;i<(int)s.size();i++){
        int c=s[i]-'a';
        if(!created[next[c][v]])
            return false;
        v=next[c][v];
    }
    return(endmark[v]>0);
}
};

```

9.8 Z-Algorithm [11 lines] - 3923b6ef

```

vector<int> z_function(string s) {
    int n = s.size();
    vector<int> z(n);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
        if (i < r) z[i] = min(r - i, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            z[i]++;
        if (i + z[i] > r) l = i, r = i + z[i];
    }
    return z;
}

```

10 Random

10.1 Combinatorics

$$\bullet \sum_{k=0}^n \binom{n-k}{k} = Fib_{n+1}$$

$$\bullet \binom{n}{k} + \binom{n}{k+1} = \binom{n+1}{k+1}$$

$$\bullet k \binom{n}{k} = n \binom{n-1}{k-1}$$

• Number of binary sequences of length n such that no two 0's are adjacent = Fib_{n+1}

• Number of non-negative solution of $x_1 + x_2 + x_3 + \dots + x_k = n$ is $\binom{n+k-1}{n}$

10.1.1 Catalan Number

$$\bullet C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$\bullet C_0 = 1, C_1 = 1, C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

• 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786

• Number of correct bracket sequences consisting of n opening brackets.

• Number of ways to completely parenthesize n+1 factors.

• The number of triangulations of a convex polygon with +2 sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).

• The number of ways to connect the 2n points on a circle to form n disjoint i.e. non-intersecting chords.

• The number of monotonic lattice paths from point (0,0) to point (n,n) in a square lattice of size $n \times n$, which do not pass above the main diagonal

• Number of permutation of length n that can be stack sorted.

• The number of non-crossing partitions of a set of n elements.

• The number of rooted full binary tree with n+1 leaves.

• The number of Dyck words of length 2n. A string consisting of n X's and n Y's such that no string prefix has more Y's than X's.

• Number of permutation of length n with no three-term increasing subsequence.

• Number of ways to tile a staircase shape of height n with n rectangle.

• $C_n^k = \frac{k+1}{n+1} \binom{2n-k}{n-k}$ denote the number of bracket sequences of size 2n with the first k elements being (.

$$\bullet N(n, k) = \frac{1}{n} \binom{n}{k} \binom{n}{k-1}$$

• The number of expressions containing n pairs of correct parentheses, which contain k distinct nestings. $N(4, 2) = 6$
 $(((()))$, $((())())$, $((()()))$, $((()()))$, $((())())$, $((()()))$

• The number of paths from (0,0) to (2n, 0) with steps only northeast and southeast, not staying below the x-axis with k peaks. And sum of all number of peaks is Catalan number.

10.1.2 Stirling Number of the First Kind

• Count permutation according to their number of cycles.

• $S(n, k)$ count the number of permutation of n elements with k disjoint cycles.

$$\bullet S(n, k) = (n-1) \times S(n-1, k) + S(n-1, k-1), S(0, 0) = 1, S(n, 0) = S(0, n) = 0$$

$$\bullet S(n, 1) = (n-1)!$$

$$\bullet S(n, n-1) = \binom{n}{2}$$

$$\bullet \sum_{k=0}^n S(n, k) = n!$$

10.1.3 Stirling Numbers of the Second Kind

- Number of ways to partition a set of n objects into k non-empty subsets.
- $S(n, k) = k * S(n-1, k) + S(n-1, k-1), S(0, 0) = 1, S(n, 0) = S(0, n) = 0$
- $S(n, 2) = 2^{n-1} - 1$
- $S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$
- $S(n, k) * k! =$ number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

10.1.4 Bell Number

- Counts the number of partitions of a set.
- $B_{n+1} = \sum_{k=0}^n \binom{n}{k} * B_k$
- $B_n = \sum_{k=0}^n S(n, k)$, where S is Stirling number of second kind.
- The number of multiplicative partitions of a square free number with i prime factors is the i -th Bell number.
- $B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$
- If a deck is shuffled by removing and reinserting the top card n times, there are n^n possible shuffles. The number of shuffles that return the deck to its original order is B_n , so the probability of returning to the original order is B_n/n^n .

10.1.5 Lucas Theorem

- If p is prime then $\binom{p^a}{k} \equiv 0 \pmod{p}$
- For non-negative integers m and n and a prime p :
 $\binom{m}{n} = \prod_{i=0}^k \binom{m_i}{n_i} \pmod{p}$ where
 $m = m_k p^k + m_{k-1} p^{k-1} + \dots + m_1 p + m_0$ $n = n_k p^k + n_{k-1} p^{k-1} + \dots + n_1 p + n_0$ are the base p expansion.

10.1.6 Derangement

- A permutation such that no element appears in its original position.
- $d(n) = (n-1) * (d(n-1) + d(n-2)), d(0) = 1, d(1) = 0$
- $d(n) = nd(n-1) + (-1)^n = \lfloor \frac{n!}{e} \rfloor, n \geq 1$

10.1.7 Burnside Lemma

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|$$

where X^g are the elements fixed by $g(g.x = x)$ If $f(n)$ counts "configurations" of some sort of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k)$$

10.1.8 Eulerian Number

- $E(n, k)$ is the number of permutations of the numbers 1 to n in which exactly k elements are greater than the previous element.
- $E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k), E(n, 0) = E(n, n-1) = 1$
- $E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$
- $E(n, k) = E(n, n-1-k)$
- $E(0, k) = [k=0]$
- $E(n, 1) = 2^n - n - 1$

10.2 Number Theory

10.2.1 Mobius Function and Inversion

- define $\mu(n)$ as the sum of the primitive n th roots of unity depending on the factorization of n into prime factors:

$$\mu(x) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

- Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

- $\sum_{d|n} \mu(d) = [n=1]$
- $\phi(n) = \sum_{d|n} \mu(d) \cdot \frac{n}{d} = n \sum_{d|n} \frac{\mu(d)}{d} = \sum_{d|n} d \cdot \mu(\frac{n}{d})$
- $a|b \rightarrow \phi(a)|\phi(b)$

- $\phi(mn) = \phi(m) \cdot \phi(n) \cdot \frac{d}{\phi(d)}$ where $d = gcd(m, n)$
- $\phi(n^m) = n^{m-1} \phi(n)$
- $\sum_{i=1}^n [gcd(i, n) = k] = \phi(\frac{n}{k})$
- $\sum_{i=1}^n gcd(i, n) = \sum_{d|n} d \cdot \phi(\frac{n}{d})$
- $\sum_{i=1}^n \frac{1}{gcd(i, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi(\frac{n}{d}) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$
- $\sum_{i=1}^n \frac{i}{gcd(i, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi(\frac{n}{d}) = \frac{n}{2} \cdot \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$
- $\sum_{i=1}^n \frac{n}{gcd(i, n)} = 2 \cdot \sum_{i=1}^n \frac{i}{gcd(i, n)} - 1$

10.2.2 GCD and LCM

- $gcd(a, b) = gcd(b, a \bmod b)$
- If $a|b.c$, and $gcd(a, b) = d$, then $(a/d)|c$.
- GCD is a multiplicative function.
- $gcd(a, lcm(b, c)) = lcm(gcd(a, b), gcd(a, c))$
- $gcd(n^a - 1, n^b - 1) = n^{gcd(a, b)} - 1$

10.2.3 Gauss Circle Theorem

- Determine the number of lattice points in a circle centered at the origin with radius r .
- number of pairs (m, n) such that $m^2 + n^2 \leq r^2$
- $N(r) = 1 + 4 \sum_{i=0}^{\infty} (\lfloor \frac{r^2}{4i+1} \rfloor - \lfloor \frac{r^2}{4i+3} \rfloor)$

10.2.4 Pick's Theorem

According to Pick's Theorem We can calculate the area of any polygon by just counting the number of Interior and Boundary lattice points of that polygon. If number of interior points are I and number of boundary lattice points are B then Area (A) of polygon will be:

$$Area = I + B/2 - 1$$

where I is the number of points in the interior shape, B stands for the number of points on the boundary of the shape.

10.2.5 Formula Cheatsheet

- $\sum_{i=1}^n = \frac{1}{m+1}[(n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m)]$
- $\sum_{i=0}^n c^i = \frac{c^{n+1}-1}{c-1}, c \neq 1$
- $\sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \sum_{i=1}^{\infty} c^i = \frac{c}{1-c}, |c| < 1$
- $\sum_{i=0}^{n-1} ar^i = a \frac{1-r^n}{1-r}, r \neq 1$
- $\sum_{i=1}^n ir^{i-1} = \frac{1-(n+1)r^n + nr^{n+1}}{(1-r)^2}, r \neq 1$
- $\sum_{i=1}^n ir^i = \frac{r(1-(n+1)r^n + nr^{n+1})}{(1-r)^2}, r \neq 1$
- $1 + x + x^2 + x^3 + \dots = \frac{1}{1-x}, |x| < 1$
- $(1+x)^\alpha = \sum_{i=0}^{\infty} \binom{\alpha}{i} x^i, |x| < 1$
- $\frac{1}{1+x^2} = \sum_{i=0}^{\infty} (-1)^i x^{2i}, |x| < 1$
- $\arctan x = \sum_{i=0}^{\infty} (-1)^i \frac{x^{2i+1}}{2i+1}, |x| \leq 1, x \neq \pm 1$
- $\frac{1}{1-x^2} = \sum_{i=0}^{\infty} x^{2i}, |x| < 1$
- $\frac{1}{(1-x)^2} = \sum_{i=1}^{\infty} ix^{i-1}, |x| < 1$
- $\frac{x}{(1-x)^2} = \sum_{i=1}^{\infty} ix^i, |x| < 1$
- $\ln(1+x) = \sum_{i=1}^{\infty} (-1)^{i+1} \frac{x^i}{i}, |x| < 1$
- $\ln\left(\frac{1+x}{1-x}\right) = 2 \sum_{i=0}^{\infty} \frac{x^{2i+1}}{2i+1}, |x| < 1$
- $H_n = \sum_{i=1}^n \frac{1}{i}, \sum_{i=1}^n iH_i = \frac{n(n+1)}{2}H_n - \frac{n(n-1)}{4}$
- $\sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n}$
- $\sum_{i=r}^n \binom{i}{r} = \binom{n+1}{r+1}$

- $\sum_{i=0}^n i \binom{n}{i} = n2^{n-1}$
- $\sum_{i=0}^n i^2 \binom{n}{i} = n(n+1)2^{n-2}$
- $\sum_{i=0}^n k^i \binom{n}{i} = (k+1)^n$
- $\sum_{i=1}^n F_i = F_{n+2} - 1$
- $\sum_{i=1}^n F_{2i} = F_n F_{n+1}$
- $\sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}$
- $\sum_{i=1}^n i^3 = \left(\frac{n(n+1)}{2}\right)^2$

10.2.6 3D Geometry

- Distance between points $A(x_1, y_1, z_1)$ and $B(x_2, y_2, z_2)$:
 $|AB| = \sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2 + (z_2 - z_1)^2}$
- Area of triangle with edge vectors $\vec{u}, \vec{v}$: $\frac{1}{2} \|\vec{u} \times \vec{v}\|$
- Volume of parallelepiped with generators $\vec{u}, \vec{v}, \vec{w}$: $V = |\vec{u} \cdot (\vec{v} \times \vec{w})|$
- Distance from point $P(x_0, y_0, z_0)$ to plane $ax + by + cz + d = 0$: $\frac{|ax_0 + by_0 + cz_0 + d|}{\sqrt{a^2 + b^2 + c^2}}$
- Plane through three points A, B, C : $\vec{n} = \overrightarrow{AB} \times \overrightarrow{AC}$, equation $\vec{n} \cdot (\vec{r} - \vec{r}_A) = 0$
- Plane from point $P_0(x_0, y_0, z_0)$ and normal $\vec{n} = (a, b, c)$:
 $a(x - x_0) + b(y - y_0) + c(z - z_0) = 0$
- Distance between parallel planes $ax + by + cz + d_1 = 0$ and $ax + by + cz + d_2 = 0$: $\frac{|d_1 - d_2|}{\sqrt{a^2 + b^2 + c^2}}$
- Distance from point P to line through A with direction $\vec{d}$: $\frac{\|\overrightarrow{AP} \times \vec{d}\|}{\|\vec{d}\|}$
- Shortest distance between skew lines $L_1 : \vec{r} = \vec{a}_1 + s\vec{d}_1$ and $L_2 : \vec{r} = \vec{a}_2 + t\vec{d}_2$: $\frac{|(\vec{a}_2 - \vec{a}_1) \cdot (\vec{d}_1 \times \vec{d}_2)|}{\|\vec{d}_1 \times \vec{d}_2\|}$
- Line through two points $A(x_1, y_1, z_1)$ and $B(x_2, y_2, z_2)$:
 $\frac{x-x_1}{x_2-x_1} = \frac{y-y_1}{y_2-y_1} = \frac{z-z_1}{z_2-z_1}$

- Plane through $A(x_1, y_1, z_1), B(x_2, y_2, z_2), C(x_3, y_3, z_3)$:

$$\begin{vmatrix} x-x_1 & y-y_1 & z-z_1 \\ x_2-x_1 & y_2-y_1 & z_2-z_1 \\ x_3-x_1 & y_3-y_1 & z_3-z_1 \end{vmatrix} = 0$$
- Coplanarity of A, B, C, D :

$$\begin{vmatrix} x_A & y_A & z_A & 1 \\ x_B & y_B & z_B & 1 \\ x_C & y_C & z_C & 1 \\ x_D & y_D & z_D & 1 \end{vmatrix} = 0$$
- Plane intercept form cutting axes at a, b, c : $\frac{x}{a} + \frac{y}{b} + \frac{z}{c} = 1$
- Angle between two planes with normals $\vec{n}_1, \vec{n}_2$: $\cos \theta = \frac{|\vec{n}_1 \cdot \vec{n}_2|}{\|\vec{n}_1\| \|\vec{n}_2\|}$
- Line-plane intersection for line $\vec{p} = \vec{p}_0 + t\vec{d}$ and plane $ax + by + cz + d = 0$: $t = -\frac{a x_0 + b y_0 + c z_0 + d}{a d_x + b d_y + c d_z}$ when denominator non-zero
- Parametric line from point $P_0(x_0, y_0, z_0)$ with direction (a, b, c) : $x = x_0 + at, y = y_0 + bt, z = z_0 + ct$
- Line with direction ratios (l, m, n) through P_0 : symmetric form $\frac{x-x_0}{l} = \frac{y-y_0}{m} = \frac{z-z_0}{n}$; direction cosines $(\cos \alpha, \cos \beta, \cos \gamma)$ satisfy $\cos^2 \alpha + \cos^2 \beta + \cos^2 \gamma = 1$
- Angle between line with direction ratios (l, m, n) and plane $ax + by + cz + d = 0$: $\sin \theta = \frac{|al + bm + cn|}{\sqrt{l^2 + m^2 + n^2} \sqrt{a^2 + b^2 + c^2}}$
- Midpoint of segment joining $A(x_1, y_1, z_1)$ and $B(x_2, y_2, z_2)$: $M\left(\frac{x_1+x_2}{2}, \frac{y_1+y_2}{2}, \frac{z_1+z_2}{2}\right)$
- Centroid of triangle with vertices A, B, C :
 $G\left(\frac{x_A+x_B+x_C}{3}, \frac{y_A+y_B+y_C}{3}, \frac{z_A+z_B+z_C}{3}\right)$
- Centroid of tetrahedron with vertices A, B, C, D :
 $\left(\frac{x_A+x_B+x_C+x_D}{4}, \frac{y_A+y_B+y_C+y_D}{4}, \frac{z_A+z_B+z_C+z_D}{4}\right)$
- Sphere of radius r : surface $S = 4\pi r^2$, volume $V = \frac{4}{3}\pi r^3$
- Right circular cone (radius r , height h): $V = \frac{1}{3}\pi r^2 h$, lateral area $\pi r \sqrt{r^2 + h^2}$