



Developing a Learning Switch and a Controller






A Mechanism of a General Purpose Switch

Forwarding DB

00:00:00:00:00:01 → 1

00:00:00:00:00:02 → 4




Forwarding DB

00:00:00:00:00:01 → 1

00:00:00:00:00:02 → 4


Dst = host2




Forwarding DB


00:00:00:00:00:01 → 1


00:00:00:00:00:02 → 4




A Mechanism of a Switch based on OpenFlow









Controller


Forwarding DB

00:00:00:00:00:00:0 | → |

Packet Out
(FLOOD)



Flow Table



host1

00:00:...:01
192.168.0.1



host2


00:00:...:02
192.168.0.2

Controller


Forwarding DB

00:00:00:00:00:00:0 | → |

Packet Out
(FLOOD)



Flow Table



host1

00:00:...:01
192.168.0.1



host2

00:00:...:02
192.168.0.2




Controller

Forwarding DB

00:00:00:00:00:00:0 | → |



Flow Table



host1

00:00:...:01
192.168.0.1




host2

00:00:...:02
192.168.0.2

Controller

Forwarding DB

00:00:00:00:00:00:0 | → |



Flow Table



host1

00:00:...:01
192.168.0.1



host2


00:00:...:02
192.168.0.2

Controller


Forwarding DB	
00:00:00:00:00:01	→ 1
00:00:00:00:00:02	→ 4



Packet In



Flow Table	
Arrival of an unknown packet	




host1

00:00:..:01
192.168.0.1




host2

00:00:..:02
192.168.0.2




Controller

Forwarding DB	
00:00:00:00:00:01	→ 1
00:00:00:00:00:02	→ 4



Flow Table	




host1

00:00:..:01
192.168.0.1



host2


00:00:..:02
192.168.0.2





Controller

Forwarding DB	
00:00:00:00:00:01	→ 1
00:00:00:00:00:02	→ 4

Packet Out
(port = 1)



Flow Table	
	→ 1



host1

00:00:00:00:00:01
192.168.0.1




host2


00:00:00:00:00:02
192.168.0.2

Controller

Forwarding DB	
00:00:00:00:00:01	→ 1
00:00:00:00:00:02	→ 4



Flow Table	
<div><div></div><div></div></div>	→ 1




host1

00:00:..:01
192.168.0.1



host2

00:00:..:02
192.168.0.2



Controller


Forwarding DB

00:00:00:00:00:01	→	1
00:00:00:00:00:02	→	4

Switch does not
send a Packet In
message

Flow Table

<div><div></div><div></div></div>	→	1
-----------------------------------	---	---




host1

host2

00:00:...:01
192.168.0.1

00:00:...:02
192.168.0.2




Controller

Forwarding DB	
00:00:00:00:00:01	→ 1
00:00:00:00:00:02	→ 4

Flow Mod
Packet Out



Flow Table	
	→ 1



host1

00:00:..:01
192.168.0.1




host2

00:00:..:02
192.168.0.2


Controller

Forwarding DB	
00:00:00:00:00:01	→ 1
00:00:00:00:00:02	→ 4

Flow Mod
Packet Out



Flow Table	
	→ 1
	→ 4



host1


00:00:..:01
192.168.0.1



host2


00:00:..:02
192.168.0.2





Assignment

Generate Packet In events




```
$ trema send_packets \  
    --source host1 --dest host2
```

- Send a test packet
from host1 to host2

```
$ trema show_stats host2
```

- Show statistics of RX on host2
- You can check whether packets properly arrive at host2.

How to send packets to only
destination nodes


Hash table

Forwarding DB

00:00:00:00:00:01 → 1

00:00:00:00:00:02 → 4

Dst = host2




```
# Learn a map from MAC addresses to  
ports
```

```
@fdb[message.macsa] = message.in_port
```

```
# Look up a destination port with a  
MAC address in the hash table
```

```
port_no = @fdb[message.macda]
```

- Learning: `hash[key] = value`
- Lookup: `hash[key]`

Pseudo Code

```
def packet_in(dpid, message)
    Learn a map from a MAC address to a port ID
    Look up a port ID with message.macda in the FDB
    if the port ID is in the FDB
        Send message out the port
    else
        Flood message
    end
end
end
```



```
$ trema dump_flows 0xabc
```

- Dump flows on switch 0xabc

Conclusion

- A mechanisms of an OpenFlow switch
Packet In/Packet Out/Flow Mod
- How to send test packets
- How to dump a flow table