

Confidence intervals


PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON



Conor Dewey


Data Scientist, Squarespace

Intro to sampling



¹ Wikimedia

What is a confidence interval?



¹ Wikimedia

Calculating confidence intervals

Means

$$\bar{X} \pm Z_{\frac{\alpha}{2}} \frac{\sigma}{\sqrt{n}}$$

Calculating confidence intervals

Proportions

$$\hat{p} \pm Z_{\frac{\alpha}{2}} \sqrt{\frac{\hat{p}(1 - \hat{p})}{n}}$$

Example: means

```
import scipy.stats as st
a = range(10,14)
st.t.interval(0.95, len(a) - 1, loc = np.mean(a),
              scale = st.sem(a))
```

```
(9.446, 13.554)
```

Example: proportions

```
from sm.stats.proportion import proportion_confint  
proportion_confint(4, 10, .05)
```

```
(0.0964, 0.7036)
```

Summary

- Sampling
- Confidence intervals
- Example

Let's prepare for the interview!

PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON

Hypothesis testing

PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON



Conor Dewey

Data Scientist, Squarespace

Quick review



¹ xkcd


Assumptions

- Random sampling
- Independent observations
- Normally distributed
- Constant variance


Generating hypotheses

Two-tailed test	One tailed test
H_0 : Estimate = value	H_0 : Estimate \geq value (Estimate \leq value)
H_1 : Estimate \neq value	H_1 : Estimate < value (Estimate > value)

Which test to use



Evaluating results



¹ Wikimedia

Types of errors

		Reality	
		True	False
Measured or Perceived	True	Correct 😊	Type 1 error False Positive
	False	Type 2 error False Negative	Correct 😊

¹ AB Tasty

Summary


- Quick review
- Assumptions
- Testing process
- Types of errors

Let's prepare for the interview!

PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON

Power and sample size

PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON




Conor Dewey


Data Scientist, Squarespace

Power analysis

Many



Few



¹ Public domain vectors

Moving parts

- Effect size
- Significance level
- Power
- Sample size

Calculating sample size

- `zt_ind_solve_power()`
- `tt_ind_solve_power()`
- `proportion_effectsize()`

Example: conversion rates

```
from statsmodels.stats.power import zt_ind_solve_power
import statsmodels.stats.proportion as prop

std_effect = prop.proportion_effectsize(.20, .25)
zt_ind_solve_power(effect_size=std_effect, nobs1=None,
                    alpha=.05, power=.80)
```

1091.8962

Example: conversion rates

```
from statsmodels.stats.power import zt_ind_solve_power
import statsmodels.stats.proportion as prop

std_effect = prop.proportion_effectsize(.20, .25)
zt_ind_solve_power(effect_size=std_effect, nobs1=None,
                    alpha=.05, power=.95)
```

1807.76215

Summary

- Power analysis
- Moving parts
- Example

Let's prepare for the interview!

PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON

Multiple testing


PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON



Conor Dewey


Data Scientist, Squarespace

Multiple comparisons problem



¹ xkcd

Correcting for multiple comparisons



¹ GraphPad

Common approaches

- Bonferroni correction
- Sidak correction
- Step-based procedures
- Tukey's procedure
- Dunnet's correction

Bonferroni correction

The original p value 

$$\text{Bonferroni-corrected } p \text{ value} = \frac{\alpha}{n}$$

The number of tests performed 

¹ Wikimedia

Example

```
from statsmodels.sandbox.stats.multicomp import multipletests
p_adjusted = multipletests(pvals, alpha=.05, method='bonferroni')
print(p_adjusted[0])
print(p_adjusted[1])
```

```
[ True False False False False]
[0.05 0.25 0.5  1.   1.   ]
```


Side effects



¹ What's wrong with Bonferroni adjustments

Summary

- Multiple comparisons problem
- Common correction approaches
- Bonferroni correction

Let's prepare for the interview!

PRACTICING STATISTICS INTERVIEW QUESTIONS IN PYTHON