Codemagic setup sheet — fill in the blanks

Copy this page, fill in each blank, and Phase 4 (iOS) + Phase 3 (Android) become paste-only. Generated for the operator · June 2026

This sheet matches the workflows in `codemagic.yaml`. Names in `code` must match *exactly* — they are the references the build file looks for. App ID is already set: `app.fabricflo.tracker`.

> *How to read this: anything in **[BRACKETS]** is something you paste/create. "Where to get it" tells you the website + clicks. You never edit `codemagic.yaml` itself unless a name below says so.*

---

0. One-time connections in Codemagic

1. Go to https://codemagic.io → **Sign up with GitHub** → authorize the `fabric-flo` repository.
2. Open the app → it auto-detects `codemagic.yaml`. You'll run workflows `ios-release` and `android-release` from here.

---

1. Apple / iOS

1a. App Store Connect API key (lets Codemagic sign + upload for you)

Create at: **App Store Connect → Users and Access → Integrations (or Keys) → App Store Connect API → +**

What	Your value	Where to get it
Key file (`.p8`)	**[DOWNLOAD AuthKey_XXXX.p8]**	The "Download API Key" button (one time only — save it!)
Key ID	**[_____]**	Shown next to the key (e.g. `2X9ABC3DEF`)
Issuer ID	**[_____]**	Top of the Keys page (a long UUID)

Access role	**App Manager** (or Admin)	Set when creating the key

In Codemagic: Teams ▸ **Integrations** ▸ Apple Developer Portal / App Store Connect ▸ add the key. Give the integration this exact name so the build finds it:

```
Integration name:  FabricFloAppStoreKey
```

> *This name matches `integrations: app_store_connect: FabricFloAppStoreKey` in `codemagic.yaml`. If you name it differently, change that one line to match.*

1b. Create the app record in App Store Connect

App Store Connect → **Apps → + → New App**

Field	Value
Platform	iOS
Name	Fabric Flo
Bundle ID	**app.fabricflo.tracker** (register under Certificates ▸ Identifiers if not listed)
SKU	**[anything unique, e.g. `fabricflo-001`]**

After it's created, copy the **numeric Apple ID** (App Store Connect → your app → App Information → "Apple ID", a number like `6502345678`):

Variable	Your value	Used in
`APP_STORE_APPLE_ID`	**[_____]**	`codemagic.yaml` → `ios-release` → `vars` (replace the `0000000000` placeholder)

> *Signing certificates/profiles: you do **nothing manual** — `distribution_type: app_store` + the API key let Codemagic create and manage them automatically.*

---

2. Android

2a. Upload keystore (signs the app; **back this up forever**)

If you don't have one yet, you can create it locally (Windows, in the project's `android` folder):

```
keytool -genkey -v -keystore fabricflo-upload.jks -keyalg RSA
-keysize 2048 -validity 10000 -alias upload
```

Save the file and the passwords in a password manager. **If you lose this, you can never update the app on Google Play.**

In Codemagic: App settings ▸ **Code signing identities** ▸ **Android keystores** ▸ upload it, with:

What	Your value	Notes
Keystore file	**[fabricflo-upload.jks]**	the file you generated
Keystore password	**[_____]**	from `keytool`
Key alias	`upload`	(or whatever you chose)
Key password	**[_____]**	from `keytool`
Reference name	`fabricflo_upload_keystore`	**must match `codemagic.yaml`**

2b. Google Play service account (lets Codemagic upload the `.aab`)

1. Google Play Console → **Setup ▸ API access** → link a Google Cloud project.
2. Create a **service account**, grant it **Release manager** permission in Play Console.
3. Download its **JSON key**.

In Codemagic: Teams ▸ Integrations ▸ Google Play ▸ upload the JSON. Then add it as a variable:

Variable	Your value	Notes

`GCLOUD_SERVICE_ACCOUNT_CREDENTIALS`	**[paste JSON contents]**	mark **Secure**; used by `codemagic.yaml` Android publishing

> *First uploads sometimes must be done **by hand** in Play Console (Google requires the very first `.aab` manually). After that, Codemagic can publish to the **internal** track automatically.*

---

3. Web/app environment (baked into both builds)

These are the same `VITE_*` values from your `.env` / Netlify. The build reads them at `npm run build`.

In Codemagic: App settings ▸ **Environment variables** ▸ create a group named exactly:

```
Group name:  fabricflo_web
```

Variable	Your value	Secure?
`VITE_SUPABASE_URL`	**[https://xxxx.supabase.co]**	no
`VITE_SUPABASE_ANON_KEY`	**[__________]**	yes
`VITE_FABRIC_FLO_BACKEND`	`normalized`	no
`VITE_PUBLIC_APP_URL`	**[https://your-site.netlify.app]** (no trailing slash)	no
`VITE_SUPPORT_EMAIL`	**[]**	no
`VITE_PRIVACY_EMAIL`	**[]**	no

> *This group name matches `groups: - fabricflo_web` in `codemagic.yaml`. For Android, also create an (empty is fine) group named `fabricflo_android` to match the file.*

---

4. Run it

Goal	In Codemagic
iOS to TestFlight	Run workflow **`ios-release`** → check email/TestFlight
Android to Play (internal)	Run workflow **`android-release`**
Submit iOS to App Store	After listing is complete, set `submit_to_app_store: true` in `codemagic.yaml` and re-run

---

Quick "did I set everything?" checklist

- ☐ GitHub connected; `codemagic.yaml` detected
- ☐ App Store Connect API key uploaded as **`FabricFloAppStoreKey`**
- ☐ App created in App Store Connect; `APP_STORE_APPLE_ID` filled into `codemagic.yaml`
- ☐ Android keystore uploaded as **`fabricflo_upload_keystore`** (and backed up!)
- ☐ Google Play service account JSON added (`GCLOUD_SERVICE_ACCOUNT_CREDENTIALS`)
- ☐ `fabricflo_web` variable group filled (all `VITE_*`)
- ☐ `fabricflo_android` group exists (can be empty)
- ☐ First Android `.aab` uploaded manually in Play Console (Google's one-time requirement)

When these are checked, `ios-release` and `android-release` run end-to-end.

Fabric Flo — Film fabric & bag tracker for productions. Repo: https://github.com/KeatingMichael/fabric-flo