

```

...mationServerWithRegFile\AutomationServerWithRegFile.reg 1
1 Windows Registry Editor Version 5.00
2
3 ; create HKCR\Wow6432Node\CLSID\{actual clsid} key and set to any informative ➤
   string value
4 [HKEY_CLASSES_ROOT\Wow6432Node\CLSID\{71169462-E879-4B9B-ACFF-FB718082D292}]
5 @="MyComAutomationDll"
6
7 ; create HKCR\Wow6432Node\CLSID\{actual clsid}\InprocServer32 subkey and set ➤
   to path of server dll
8 [HKEY_CLASSES_ROOT\Wow6432Node\CLSID\{71169462-E879-4B9B-ACFF-FB718082D292} ➤
   \InprocServer32]
9 @="C:\\Windows\\SysWOW64\\AutomationServerWithRegFile.dll"
10
11 ; All following Keys Are Created Either By LoadRegTypeLib() Alone Or By a) ➤
   LoadTypeLib() And b) RegisterTypeLib() In Pair
12 ; ➤
   ***** ➤
   *****
13 ; create HKCR\Wow6432Node\CLSID\{actual clsid}\TypeLib subkey and set to ➤
   LIBID of server's Type Library
14 [HKEY_CLASSES_ROOT\Wow6432Node\CLSID\{71169462-E879-4B9B-ACFF-FB718082D292} ➤
   \TypeLib]
15 @="{1F879C17-26BE-420C-A3F6-2995E0970AF3}"
16
17 ; create HKCR\TypeLib\{actual libid} and set to any informative string value
18 [HKEY_CLASSES_ROOT\TypeLib\{1F879C17-26BE-420C-A3F6-2995E0970AF3}]
19 @="MyComAutomationTypeLib"
20
21 ; create HKCR\TypeLib\{actual libid}\<major.minor version number> subkey and ➤
   set to any informative string value
22 [HKEY_CLASSES_ROOT\TypeLib\{1F879C17-26BE-420C-A3F6-2995E0970AF3}\1.0]
23 @="MyComAutomationTypeLib v1.0"
24
25 ; create HKCR\TypeLib\{actual libid}\<major.minor version number>\0\win32 ➤
   subkey and set to path of type library
26 [HKEY_CLASSES_ROOT\TypeLib\{1F879C17-26BE-420C-A3F6-2995E0970AF3}\1.0\0 ➤
   \win32]
27 @="C:\\Windows\\SysWOW64\\AutomationServerTypeLib.tlb"
28
29 ; create HKCR\Interface\{actual iid} and set to the name of interface
30 [HKEY_CLASSES_ROOT\Interface\{2778214B-DE94-4BD8-B40B-DCF950D2FACC}]
31 @="IMyMath"
32
33 ; create HKCR\Interface\{actual iid}\TypeLib subkey and set to LIBID of ➤
   server's type library
34 [HKEY_CLASSES_ROOT\Interface\{2778214B-DE94-4BD8-B40B-DCF950D2FACC}\TypeLib]
35 @="{1F879C17-26BE-420C-A3F6-2995E0970AF3}"
36
37 ; create HKCR\Interface\{actual iid}\ProxyStubClsid32 subkey and set to ➤
   "hard-coded PSOAInterface IID"
38 [HKEY_CLASSES_ROOT\Interface\{2778214B-DE94-4BD8-B40B-DCF950D2FACC} ➤
   \ProxyStubClsid32]
39 @="{00020424-0000-0000-C000-000000000046}"

```

40

41 ; create HKCR\Interface\{actual iid}\ProxyStubClsid subkey and set to "hard - [↗](#)
coded" PSOAInterface IID

42 [HKEY_CLASSES_ROOT\Interface\{2778214B-DE94-4BD8-B40B-DCF950D2FACC}
 \ProxyStubClsid] [↗](#)

43 @="{00020424-0000-0000-C000-000000000046}"

44