

1) RHEL Family

* made from Red Hat Linux

* uses RPM packages

* uses dnf (or older yum) to install software

* mostly used in companies and enterprise services

Ex:- RHEL, Rocky, Linux, AlmaLinux

Debian Family

* made from Debian Linux

* uses DEB packages

* uses apt to install software

* mostly used by students, beginner desktop and servers

Ex:- Debian, Ubuntu, Linux Mint

2) what is a protocol.

A protocol is set of rules that tells computers how to communicate with each other over a network

Simple example:

Imagine two people talking on the phone. They must speak the same language to understand each other. Similarly, computers use protocols to exchange data correctly

Ex:-

- HTTPS - used to open website

- HTTPS - secure version of HTTP

- FTP - used to transfer files

- SMTP - used to send emails

- SSH - used to securely connect to another computer

What is a port?

A port is a number that identifies a specific service (or) application on a computer.

Simple examples:

Think of a computer as a house.

- The IP address is the house address
- The port number is the room number
- Data goes to the correct room (application) using the port number

protocol	port number	purpose
HTTP	80	open website
HTTPS	443	secure website
FTP	21	File transfer
SSH	22	secure remote login
SMTP	25	sending emails
DNS	53	convert domain names to IP addresses

Protocol = Rules for communication

Port = Door number where a specific service listens.