

WEEK:05

**NESTED LOOPS – WHILE AND FOR, JUMPS IN
LOOPS**

WEEK: 05-01

ROLL NO: 240801161

NAME: KEERTHANA S

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Thursday, 19 December 2024, 9:31 AM
Duration	4 days 8 hours

QUESTION:1

SIMPLE CHESSBOARD

Problem Statement:

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.

The lines after that contain a different value for size of the chessboard

Output format:

Print a chessboard of dimensions size * size.

Print W for white spaces and B for black spaces.

Sample Input:

2

3

5

Sample Output:

WBW

BWB

WBW

WBWBW

BWBWB

WBWBW

BWBWB

WBWBW

PROGRAM:

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main ()
3 {
4     int t,d,i=0,i1,i2,x;
5     char c;
6     scanf ("%d",&t);
7     while (i<t)
8     {
9         scanf ("%d",&d);
10        i1=0;
11        while (i1<d)
12        {
13
14            x=1;
15            i2=0;
16            if (i1%2==0)
17            {
18                x=0;
19            }
20            while (i2<d)
21            {
22                c = 'B';
23                if (i2%2==x)
24                {
25                    c='W';
26                }
27                printf("%c",c);
28                i2++;
29
30            }
31            i1+=1;
32            printf ("\n");
33
34        }
35        i=i+1;
36    }
37    return 0;
38
39 }
```

OUTPUT:

	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	

Passed all tests! ✓

QUESTION:2

PRINT OUR OWN CHESSBOARD

Problem Statement:

Let's print a chessboard!

Write a program that takes

Input

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input:

2

2 W

3 B

Sample Output:

WB

BW

BWB

WBW

BWB

PROGRAM:

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main ()
3 {
4     int t, d , i , i1, i2, o, z;
5     char c,s;
6     scanf("%d",&t);
7     for (i=0;i<t;i++)
8     {
9         scanf("%d %c",&d,&s);
10        for(i1=0;i1<d;i1++)
11        {
12            z=(s=='W')?0:1;
13            o=(i1%2==z)?0:1;
14            for(i2=0;i2<d;i2++)
15            {
16                c= (i2%2 ==o)?'W':'B';
17                printf("%c",c);
18            }
19            printf("\n");
20        }
21    }
22 }
23
24 return 0;
25 }
```

OUTPUT:

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! ✓

QUESTION:3

PATTERN PRINTING

Problem Statement:

Decode the logic and print the Pattern that corresponds to given input.

If N= 3 then pattern will be:

10203010011012

**4050809

***607

If N= 4, then pattern will be:

1020304017018019020

**50607014015016

***809012013

*****10011

Constraints: $2 \leq N \leq 100$

Input Format

First line contains T, the number of test cases, each test case contains a single integer N

Output Format

First line print Case #i where i is the test case number, In the subsequent line, print the pattern

Sample Input

3

3

4

5

Sample Output

Case #1

10203010011012

**4050809

****607

Case #2

1020304017018019020

**50607014015016

****809012013

*****10011

Case #3

102030405026027028029030

**6070809022023024025

****10011012019020021

*****13014017018

*****15016

PROGRAM:

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,v,p3,c,in,i,i1,i2,t,ti;
5     scanf("%d",&t);
6     for(ti=0;ti<t;ti++)
7     {
8         v = 0;
9         scanf("%d",&n);
10        printf("Case #%d\n",ti+1);
11        for (i=0;i<n;i++){
12            c=0;
13            if(i>0){
14                for(i1=0;i1<i;i1++){
15                    printf("***");
16                }
17                for(i1=i;i1<n;i1++){
18                    if (i>0)
19                        c++;
20                    printf("%d0",++v);
21                }
22                if (i ==0)
23                {
24                    p3=v+(v*(v-1))+1;
25                    in = p3;
26                }
27
28                in = in -c;
29                p3= in;
30                for(i2=i;i2<n;i2++){
31                    printf("%d",p3++);
32                    if(i2!=n-1)
33                        printf("0");
34                }
35                printf("\n");
36            }
37        }
38    }
```

OUTPUT:

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	
		Case #2	Case #2	
		1020304017018019020	1020304017018019020	
		**50607014015016	**50607014015016	
		****809012013	****809012013	
		*****10011	*****10011	
		Case #3	Case #3	
		102030405026027028029030	102030405026027028029030	
		**6070809022023024025	**6070809022023024025	
		****10011012019020021	****10011012019020021	
		*****13014017018	*****13014017018	
		*****15016	*****15016	

Passed all tests! ✓

