Java Deque Interface

Java Deque Interface is a linear collection that supports element insertion and removal at both ends. Deque is an acronym for **"double ended queue".**

Deque Interface declaration

public interface Deque<E> extends Queue<E>

Methods of Java Deque Interface


Method	Description
boolean add(object)	It is used to insert the specified element into this deque and return true upon success.
boolean offer(object)	It is used to insert the specified element into this deque.
Object remove()	It is used to retrieves and removes the head of this deque.
Object poll()	It is used to retrieves and removes the head of this deque, or returns null if this deque is empty.
Object element()	It is used to retrieves, but does not remove, the head of this deque.
Object peek()	It is used to retrieves, but does not remove, the head of this deque, or returns null if this deque is empty.

ArrayDeque class

The ArrayDeque class provides the facility of using deque and resizable-array. It inherits AbstractCollection class and implements the Deque interface.

The important points about ArrayDeque class are:

- Unlike Queue, we can add or remove elements from both sides.
- Null elements are not allowed in the ArrayDeque.
- ArrayDeque is not thread safe, in the absence of external synchronization.
- ArrayDeque has no capacity restrictions.



Java ArrayDeque Example

```
import java.util.*;
public class ArrayDequeExample {
   public static void main(String[] args) {
    //Creating Deque and adding elements
   Deque<String> deque = new ArrayDeque<String>();
   deque.add("Ravi");
   deque.add("Vijay");
   deque.add("Ajay");
   //Traversing elements
   for (String str : deque) {
    System.out.println(str);
   }
   }
}
```

Output:

```
Ravi
Vijay
Ajay
```

Java ArrayDeque Example: offerFirst() and pollLast()

```
import java.util.*;
public class DequeExample {
public static void main(String[] args) {
   Deque<String> deque=new ArrayDeque<String>();
   deque.offer("arvind");
   deque.offer("vimal");
   deque.add("mukul");
   deque.offerFirst("jai");
   System.out.println("After offerFirst Traversal...");
   for(String s:deque){
      System.out.println(s);
   }
  //deque.poll();
  //deque.pollFirst();//it is same as poll()
   deque.pollLast();
   System.out.println("After pollLast() Traversal...");
   for(String s:deque){
      System.out.println(s);
   }
}
}
```

Output:

```
After offerFirst Traversal...

jai
arvind
vimal
mukul
After pollLast() Traversal...

jai
arvind
vimal
```

Java ArrayDeque Example: Book

```
import java.util.*;
class Book {
int id;
String name, author, publisher;
int quantity;
public Book(int id, String name, String author, String publisher, int quantity) {
  this.id = id;
  this.name = name;
  this.author = author;
  this.publisher = publisher;
  this.quantity = quantity;
}
}
public class ArrayDequeExample {
public static void main(String[] args) {
  Deque<Book> set=new ArrayDeque<Book>();
  //Creating Books
  Book b1=new Book(101,"Let us C","Yashwant Kanetkar","BPB",8);
  Book b2=new Book(102,"Data Communications & Networking","Forouzan","Mc Graw Hill",4);
  Book b3=new Book(103,"Operating System","Galvin","Wiley",6);
  //Adding Books to Deque
  set.add(b1);
  set.add(b2);
  set.add(b3);
  //Traversing ArrayDeque
  for(Book b:set){
  System.out.println(b.id+" "+b.name+" "+b.author+" "+b.publisher+" "+b.quantity);
  }
}
}
```

Output:

```
101 Let us C Yashwant Kanetkar BPB 8
102 Data Communications & Networking Forouzan Mc Graw Hill 4
103 Operating System Galvin Wiley 6
```



 $next \rightarrow$

Share this page



Latest 4 Tutorials



CouchDB



Docker



Rails



RichFaces