

Rajalakshmi Engineering College

Name: KEERTHIKA .K

Email: 241901046@rajalakshmi.edu.in

Roll no: 241901046

Phone: 9363527003

Branch: REC

Department: I CSE (CS) FA

Batch: 2028

Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_MCQ

Attempt : 1

Total Mark : 15

Marks Obtained : 14

Section 1 : MCQ

1. How many distinct binary search trees can be created out of 4 distinct keys?

Answer

14

Status : Correct

Marks : 1/1

2. Which of the following is the correct pre-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

Answer

50, 30, 20, 32, 55, 52, 57

Status : Correct

Marks : 1/1

3. While inserting the elements 71, 65, 84, 69, 67, 83 in an empty binary search tree (BST) in the sequence shown, the element in the lowest level is _____.

Answer

67

Status : Correct

Marks : 1/1

4. Find the preorder traversal of the given binary search tree.

Answer

9, 2, 1, 6, 4, 7, 10, 14

Status : Correct

Marks : 1/1

5. In a binary search tree with nodes 18, 28, 12, 11, 16, 14, 17, what is the value of the left child of the node 16?

Answer

14

Status : Correct

Marks : 1/1

6. Find the postorder traversal of the given binary search tree.

Answer

1, 4, 2, 18, 14, 13

Status : Correct

Marks : 1/1

7. The preorder traversal of a binary search tree is 15, 10, 12, 11, 20, 18, 16, 19. Which one of the following is the postorder traversal of the tree?

Answer

11, 12, 10, 16, 19, 18, 20, 15

Status : Correct

Marks : 1/1

8. Which of the following is a valid preorder traversal of the binary search tree with nodes: 18, 28, 12, 11, 16, 14, 17?

Answer

18, 12, 11, 16, 14, 17, 28

Status : Correct

Marks : 1/1

9. While inserting the elements 5, 4, 2, 8, 7, 10, 12 in a binary search tree, the element at the lowest level is _____.

Answer

7

Status : Wrong

Marks : 0/1

10. Which of the following is the correct post-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

Answer

20, 32, 30, 52, 57, 55, 50

Status : Correct

Marks : 1/1

11. Find the pre-order traversal of the given binary search tree.

Answer

13, 2, 1, 4, 14, 18

Status : Correct

Marks : 1/1

12. Which of the following operations can be used to traverse a Binary Search Tree (BST) in ascending order?

Answer

Inorder traversal

Status : Correct

Marks : 1/1

13. Find the in-order traversal of the given binary search tree.

Answer

1, 2, 4, 13, 14, 18

Status : Correct

Marks : 1/1

14. Find the post-order traversal of the given binary search tree.

Answer

10, 17, 20, 18, 15, 32, 21

Status : Correct

Marks : 1/1

15. Which of the following is the correct in-order traversal of a binary search tree with nodes: 9, 3, 5, 11, 8, 4, 2?

Answer

2, 3, 4, 5, 8, 9, 11

Status : Correct

Marks : 1/1

Rajalakshmi Engineering College

Name: KEERTHIKA .K
Email: 241901046@rajalakshmi.edu.in
Roll no: 241901046
Phone: 9363527003
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

John is learning about Binary Search Trees (BST) in his computer science class. He wants to create a program that allows users to delete a node with a given value from a BST and print the remaining nodes using an in-order traversal.

Implement a function to help him delete a node with a given value from a BST.

Input Format

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the BST nodes.

The third line consists of an integer V, which is the value to delete from the BST.

Output Format

The output prints the space-separated values in the BST in an in-order traversal, after the deletion of the specified value.

If the specified value is not available in the tree, print the given input values in-order traversal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 5 15 2 7
15

Output: 2 5 7 10

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};
```

```
struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
// You are using GCC
```

```
struct TreeNode* insert(struct TreeNode* root, int key) {
    if(root==NULL)return createNode(key);
```

```
    if(key<root->data)
    root->left=insert(root->left,key);
    else if(key>root->data)
    root->right=insert(root->right,key);
    return root;
}
```

```
struct TreeNode* findMin(struct TreeNode* root) {
    while(root->left!=NULL)
    root=root->left;
    return root;
}
```

```
struct TreeNode* deleteNode(struct TreeNode* root, int key) {
    if(root==NULL)return root;
    if(key<root->data)
    root->left=deleteNode(root->left,key);
    else if(key>root->data)
    root->right=deleteNode(root->right,key);
    else{
        if(root->left==NULL){
            struct TreeNode* temp=root->right;
            free(root);
            return temp;
        }else if(root->right==NULL){
            struct TreeNode* temp=root->left;
            free(root);
            return temp;
        }
        struct TreeNode* temp=findMin(root->right);
        root->data=temp->data;
        root->right=deleteNode(root->right,temp->data);
    }
    return root;
}
```

```
void inorderTraversal(struct TreeNode* root) {
    if(root!=NULL){
        inorderTraversal(root->left);
        printf("%d ",root->data);
        inorderTraversal(root->right);
    }
}
```

```
}
```

```
int main()
```

```
{
```

```
    int N, rootValue, V;
```

```
    scanf("%d", &N);
```

```
    struct TreeNode* root = NULL;
```

```
    for (int i = 0; i < N; i++) {
```

```
        int key;
```

```
        scanf("%d", &key);
```

```
        if (i == 0) rootValue = key;
```

```
        root = insert(root, key);
```

```
    }
```

```
    scanf("%d", &V);
```

```
    root = deleteNode(root, V);
```

```
    inorderTraversal(root);
```

```
    return 0;
```

```
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: KEERTHIKA .K
Email: 241901046@rajalakshmi.edu.in
Roll no: 241901046
Phone: 9363527003
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Mike is learning about Binary Search Trees (BSTs) and wants to implement various operations on them. He wants to write a basic program for creating a BST, inserting nodes, and printing the tree in the pre-order traversal.

Write a program to help him solve this program.

Input Format

The first line of input consists of an integer N, representing the number of values to insert into the BST.

The second line consists of N space-separated integers, representing the values to insert into the BST.

Output Format

The output prints the space-separated values of the BST in the pre-order traversal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

3 1 5 2 4

Output: 3 1 2 5 4

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* left;
    struct Node* right;
};
```

```
struct Node* createNode(int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = value;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

// You are using GCC

```
struct Node* insert(struct Node* root, int value) {
    if(root==NULL){
        return createNode(value);
    }
    if(value<root->data){
        root->left=insert(root->left,value);
    }else if(value>root->data){
        root->right=insert(root->right,value);
    }
}
```

```

    return root;
}

void printPreorder(struct Node* node) {
    if(node!=NULL){
        printf("%d ",node->data);
        printPreorder(node->left);
        printPreorder(node->right);
    }
}

int main() {
    struct Node* root = NULL;

    int n;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        int value;
        scanf("%d", &value);
        root = insert(root, value);
    }

    printPreorder(root);
    return 0;
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: KEERTHIKA .K
Email: 241901046@rajalakshmi.edu.in
Roll no: 241901046
Phone: 9363527003
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are required to implement basic operations on a Binary Search Tree (BST), like insertion and searching.

Insertion: Given a list of integers, construct a Binary Search Tree by repeatedly inserting each integer into the tree according to the rules of a BST.

Searching: Given an integer, search for its presence in the constructed Binary Search Tree. Print whether the integer is found or not.

Write a program to calculate this efficiently.

Input Format

The first line of input consists of an integer n, representing the number of nodes

in the binary search tree.

The second line consists of the values of the nodes, separated by space as integers.

The third line consists of an integer representing, the value that is to be searched.

Output Format

The output prints, "Value <value> is found in the tree." if the given value is present, otherwise it prints: "Value <value> is not found in the tree."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7

8 3 10 1 6 14 23

6

Output: Value 6 is found in the tree.

Answer

// You are using GCC

```
struct Node* insertNode(struct Node* root, int value) {
    if(root==NULL){
        return createNode(value);
    }
    if(value<root->data){
        root->left=insertNode(root->left,value);
    }else if(value>root->data){
        root->right=insertNode(root->right,value);
    }
    return root;
}
struct Node* searchNode(struct Node* root, int value) {
    if(root==NULL || root->data==value){
        return root;
    }
    if(value<root->data){
        return searchNode(root->left,value);
    }
}
```

```
}  
return searchNode(root->right,value);  
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: KEERTHIKA .K
Email: 241901046@rajalakshmi.edu.in
Roll no: 241901046
Phone: 9363527003
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 4

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

John, a computer science student, is learning about binary search trees (BST) and their properties. He decides to write a program to create a BST, display it in post-order traversal, and find the minimum value present in the tree.

Help him by implementing the program.

Input Format

The first line of input consists of an integer N, representing the number of elements to insert into the BST.

The second line consists of N space-separated integers data, which is the data to be inserted into the BST.

Output Format

The first line of output prints the space-separated elements of the BST in post-order traversal.

The second line prints the minimum value found in the BST.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

5 10 15

Output: 15 10 5

The minimum value in the BST is: 5

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* left;  
    struct Node* right;  
};
```

```
struct Node* createNode(int data) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = data;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
// You are using GCC
```

```
struct Node* insert(struct Node* root, int data) {  
    if(root==NULL)  
        return createNode(data);  
    if(data<root->data)  
        root->left=insert(root->left,data);  
    else if(data>root->data)  
        root->right=insert(root->right,data);
```



```

    return root;
}

void displayTreePostOrder(struct Node* root) {
    if(root==NULL)
        return;
    displayTreePostOrder(root->left);
    displayTreePostOrder(root->right);
    printf("%d ",root->data);
}

int findMinValue(struct Node* root) {
    struct Node* current=root;
    while(current && current->left!=NULL)
        current=current->left;
    return current->data;
}

int main() {
    struct Node* root = NULL;
    int n, data;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        root = insert(root, data);
    }

    displayTreePostOrder(root);
    printf("\n");

    int minValue = findMinValue(root);
    printf("The minimum value in the BST is: %d", minValue);

    return 0;
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: KEERTHIKA .K
Email: 241901046@rajalakshmi.edu.in
Roll no: 241901046
Phone: 9363527003
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 5

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

In his computer science class, John is learning about Binary Search Trees (BST). He wants to build a BST and find the maximum value in the tree.

Help him by writing a program to insert nodes into a BST and find the maximum value in the tree.

Input Format

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the nodes to insert into the BST.

Output Format

The output prints the maximum value in the BST.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 5 15 2 7

Output: 15

Answer

```
#include <stdio.h>
#include <stdlib.h>

struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};

struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}

// You are using GCC
struct TreeNode* insert(struct TreeNode* root, int key) {
    if(root==NULL)
        return createNode(key);
    if(key<root->data)
        root->left=insert(root->left,key);
    else if(key>root->data)
        root->right=insert(root->right,key);
    return root;
}

int findMax(struct TreeNode* root) {
    if(root==NULL)
```

```
        return -1;
    while(root->right!=NULL)
        root=root->right;
    return root->data;
}

int main() {
    int N, rootValue;
    scanf("%d", &N);

    struct TreeNode* root = NULL;

    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }

    int maxVal = findMax(root);
    if (maxVal != -1) {
        printf("%d", maxVal);
    }

    return 0;
}
```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: KEERTHIKA .K
Email: 241901046@rajalakshmi.edu.in
Roll no: 241901046
Phone: 9363527003
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_CY_Updated

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

Jake is learning about binary search trees(BST) and their operations. He wants to implement a program that can delete a node from a BST based on the given key value and print the remaining nodes in an in-order traversal.

Assist Jake in the program.

Input Format

The first line of input consists of an integer n, representing the number of elements in BST.

The second line consists of n space-separated integers, representing the elements of the tree.

The third line consists of an integer x, representing the key value of the node to be deleted.

Output Format

The first line of output prints "Before deletion: " followed by the in-order traversal of the initial BST.

The second line prints "After deletion: " followed by the in-order traversal after the deletion of the key value.

If the key value is not present in the BST, print the original tree as it is.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

8 6 4 3 1

4

Output: Before deletion: 1 3 4 6 8

After deletion: 1 3 6 8

Answer

```
// You are using GCC
```

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
struct Node{
```

```
    int data;
```

```
    struct Node* left;
```

```
    struct Node* right;
```

```
};
```

```
struct Node* createnode(int data){
```

```
    struct Node* newnode=(struct Node*)malloc(sizeof(struct Node));
```

```
    newnode->data=data;
```

```
    newnode->left=newnode->right=NULL;
```

```
    return newnode;
```

```
}
```

```
struct Node* insert(struct Node* node,int data){
```

```
    if(node==NULL){
```

```
        return createnode(data);
```

```

    }
    if(data<node->data){
        node->left=insert(node->left,data);
    }else if(data>node->data){
        node->right=insert(node->right,data);
    }
    return node;
}
struct Node* findmin(struct Node* node){
    while(node->left!=NULL){
        node=node->left;
    }
    return node;
}
struct Node* deletenode(struct Node* node,int data){
    if(node==NULL){
        return node;
    }
    if(data<node->data){
        node->left=deletenode(node->left,data);
    }else if(data>node->data){
        node->right=deletenode(node->right,data);
    }else{
        if(node->left==NULL){
            struct Node* temp=node->right;
            free(node);
            return temp;
        }
        else if(node->right==NULL){
            struct Node* temp=node->left;
            free(node);
            return temp;
        }
        struct Node* temp=findmin(node->right);
        node->data=temp->data;
        node->right=deletenode(node->right,temp->data);
    }
    return node;
}
void inordertraversal(struct Node* node){
    if(node!=NULL){
        inordertraversal(node->left);

```

```

        printf("%d ",node->data);
        inordertraversal(node->right);
    }
}

int main(){
    int n,data,x;
    struct Node* root=NULL;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%d",&data);
        root=insert(root,data);
    }
    scanf("%d",&x);
    printf("Before deletion: ");
    inordertraversal(root);
    printf("\n");
    root=deletenode(root,x);
    printf("After deletion: ");
    inordertraversal(root);
    printf("\n");
    return 0;
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

John is building a system to store and manage integers using a binary search tree (BST). He needs to add a feature that allows users to search for a specific integer key in the BST using recursion.

Implement functions to create the BST and perform a recursive search for an integer.

Input Format

The first line of input consists of an integer representing, the number of nodes.

The second line consists of integers representing, the values of nodes, separated by space.

The third line consists of an integer representing, the key to be searched.

Output Format

The output prints whether the given key is present in the binary search tree or not.

Refer to the sample output for the exact format.

Sample Test Case

Input: 7
10 5 15 3 7 12 20
12

Output: The key 12 is found in the binary search tree

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
struct Node{
    int data;
    struct Node *left,*right;
};
struct Node* createnode(int data){
    struct Node* newnode=(struct Node*)malloc(sizeof(struct Node));
    newnode->data=data;
    newnode->left=newnode->right=NULL;
    return newnode;
}
struct Node* insert(struct Node* root,int data){
    if(root==NULL)
        return createnode(data);
    if(data<root->data)
        root->left=insert(root->left,data);
    else
        root->right=insert(root->right,data);
    return root;
}
int search(struct Node* root, int key){
    if(root==NULL)
```

```

        return 0;
    if(root->data==key)
        return 1;
    if(key<root->data)
        return search(root->left,key);
    else
        return search(root->right,key);
}
int main(){
    int n,key,val;
    struct Node* root=NULL;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        scanf("%d",&val);
        root=insert(root,val);
    }
    scanf("%d",&key);
    if(search(root,key))
        printf("The key %d is found in the binary search tree\n",key);
    else
        printf("The key %d is not found in the binary search tree\n",key);
    return 0;
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Kishore is studying data structures, and he is currently working on implementing a binary search tree (BST) and exploring its basic operations. He wants to practice creating a BST, inserting elements into it, and performing a specific operation, which is deleting the minimum element from the tree.

Write a program to help him perform the delete operation.

Input Format

The first line of input consists of an integer N, representing the number of elements Kishore wants to insert into the BST.

The second line consists of N space-separated integers, where each integer represents an element to be inserted into the BST.

Output Format

The output prints the remaining elements of the BST in ascending order (in-order traversal) after deleting the minimum element.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6

5 3 8 2 4 6

Output: 3 4 5 6 8

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
typedef struct Node{
    int data;
    struct Node* left;
    struct Node* right;
}Node;
Node* createnode(int data){
    Node* newnode=(Node*)malloc(sizeof(Node));
    newnode->data=data;
    newnode->left=newnode->right=NULL;
    return newnode;
}
Node* insert(Node* root,int data){
    if(root==NULL){
        return createnode(data);
    }
    if(data<root->data){
        root->left=insert(root->left,data);
    }else if(data>root->data){
        root->right=insert(root->right,data);
    }
}
```

```

    return root;
}
Node* findmin(Node* root){
    while(root->left!=NULL){
        root=root->left;
    }
    return root;
}
Node* deletemin(Node* root){
    if(root==NULL){
        return NULL;
    }
    if(root->left==NULL){
        return root->right;
    }
    root->left=deletemin(root->left);
    return root;
}
void inordertraversal(Node* root){
    if(root!=NULL){
        inordertraversal(root->left);
        printf("%d ",root->data);
        inordertraversal(root->right);
    }
}
int main(){
    int N,data;
    Node* root=NULL;
    scanf("%d",&N);
    for(int i=0;i<N;i++){
        scanf("%d",&data);
        root=insert(root,data);
    }
    if(root!=NULL){
        Node* minnode=findmin(root);
        root=deletemin(root);
    }
    inordertraversal(root);
    printf("\n");
    return 0;
}

```

Status : Correct

Marks : 10/10

Rajalakshmi Engineering College

Name: KEERTHIKA .K
Email: 241901046@rajalakshmi.edu.in
Roll no: 241901046
Phone: 9363527003
Branch: REC
Department: I CSE (CS) FA
Batch: 2028
Degree: B.E - CSE (CS)

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_PAH_Updated

Attempt : 1
Total Mark : 50
Marks Obtained : 47.5

Section 1 : Coding

1. Problem Statement

Aishu is participating in a coding challenge where she needs to reconstruct a Binary Search Tree (BST) from given preorder traversal data and then print the in-order traversal of the reconstructed BST.

Since Aishu is just learning about tree data structures, she needs your help to write a program that does this efficiently.

Input Format

The first line consists of an integer n , representing the number of nodes in the BST.

The second line of input contains n integers separated by spaces, which represent the preorder traversal of the BST.

Output Format

The output displays n space-separated integers, representing the in-order traversal of the reconstructed BST.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 6

10 5 1 7 40 50

Output: 1 5 7 10 40 50

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
#include<limits.h>
struct Treenode{
    int data;
    struct Treenode* left;
    struct Treenode* right;
};
struct Treenode* createnode(int key){
    struct Treenode* newnode=(struct Treenode*)malloc(sizeof(struct Treenode));
    newnode->data=key;
    newnode->left=newnode->right=NULL;
    return newnode;
}
struct Treenode* buildBST(int preorder[],int* index,int min,int max,int n){
    if(*index>=n)
        return NULL;
    int key=preorder[*index];
    if(key<min|| key>max)
        return NULL;
    struct Treenode* root=createnode(key);
    (*index)++;
    root->left=buildBST(preorder,index,min,key-1,n);
    root->right=buildBST(preorder,index,key+1,max,n);
    return root;
}
```

```

}
void inordertraversal(struct Treenode* root){
    if(root==NULL)
        return;
    inordertraversal(root->left);
    printf("%d ",root->data);
    inordertraversal(root->right);
}
int main(){
    int n;
    scanf("%d",&n);
    int preorder[n];
    for(int i=0;i<n;i++)
        scanf("%d",&preorder[i]);
    int index=0;
    struct Treenode* root=buildBST(preorder,&index,INT_MIN,INT_MAX,n);
    inordertraversal(root);
    return 0;
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Yogi is working on a program to manage a binary search tree (BST) containing integer values. He wants to implement a function that removes nodes from the tree that fall outside a specified range defined by a minimum and maximum value.

Help Yogi by writing a function that achieves this.

Input Format

The first line of input consists of an integer N, representing the number of elements to be inserted into the BST.

The second line consists of N space-separated integers, representing the elements to be inserted into the BST.

The third line consists of two space-separated integers min and max, representing the minimum value and the maximum value of the range.

Output Format

The output prints the remaining elements of the BST in an in-order traversal, after removing nodes that fall outside the specified range.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 5 15 20 12

5 15

Output: 5 10 12 15

Answer

```
// You are using GCC
```

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
struct Treenode{
```

```
    int data;
```

```
    struct Treenode* left;
```

```
    struct Treenode* right;
```

```
};
```

```
struct Treenode* createnode(int key){
```

```
    struct Treenode* newnode=(struct Treenode*)malloc(sizeof(struct Treenode));
```

```
    newnode->data=key;
```

```
    newnode->left=newnode->right=NULL;
```

```
    return newnode;
```

```
}
```

```
struct Treenode* insert(struct Treenode* root,int key){
```

```
    if(root==NULL)
```

```
        return createnode(key);
```

```
    if(key<root->data)
```

```
        root->left=insert(root->left,key);
```

```
    else if(key>root->data)
```

```
        root->right=insert(root->right,key);
```

```
    return root;
```

```
}
```

```
void inordertraversal(struct Treenode* root){
```

```
    if(root==NULL)
```

```

    return;
    inordertraversal(root->left);
    printf("%d ",root->data);
    inordertraversal(root->right);
}
struct Treenode* trimBST(struct Treenode* root, int min,int max){
    if(root==NULL)
        return NULL;
    root->left=trimBST(root->left,min,max);
    root->right=trimBST(root->right,min,max);
    if(root->data<min){
        struct Treenode* rightchild=root->right;
        free(root);
        return rightchild;
    }
    if(root->data>max){
        struct Treenode* leftchild=root->left;
        free(root);
        return leftchild;
    }
    return root;
}
int main(){
    int N,min,max;
    scanf("%d",&N);
    struct Treenode* root=NULL;
    for(int i=0;i<N;i++){
        int key;
        scanf("%d",&key);
        root=insert(root,key);
    }
    scanf("%d %d",&min,&max);
    root=trimBST(root,min,max);
    inordertraversal(root);
    return 0;
}

```

Status : Partially correct

Marks : 7.5/10

3. Problem Statement

Viha, a software developer, is working on a project to automate searching for a target value in a Binary Search Tree (BST). She needs to create a program that takes an integer target value as input and determines if that value is present in the BST or not.

Write a program to assist Viha.

Input Format

The first line of input consists of integers separated by spaces, which represent the elements to be inserted into the BST. The input is terminated by entering -1.

The second line consists of an integer target, which represents the target value to be searched in the BST.

Output Format

If the target value is found in the BST, print "[target] is found in the BST".

Else, print "[target] is not found in the BST"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 3 7 1 4 6 8 -1
4

Output: 4 is found in the BST

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
struct Node{
    int data;
    struct Node* left;
    struct Node* right;
};
struct Node* createnode(int data){
    struct Node* newnode=(struct Node*)malloc(sizeof(struct Node));
```

```

    newnode->data=data;
    newnode->left=newnode->right=NULL;
    return newnode;
}
struct Node* insert(struct Node* root,int data){
    if(root==NULL)return createnode(data);
    if(data<root->data)
        root->left=insert(root->left,data);
    else if(data>root->data)
        root->right=insert(root->right,data);
    return root;
}
int search(struct Node* root, int target){
    if(root==NULL)return 0;
    if(target==root->data)return 1;
    if(target<root->data)
        return search(root->left,target);
    else
        return search(root->right,target);
}
int main(){
    struct Node* root=NULL;
    int value;
    while(1){
        scanf("%d",&value);
        if(value==-1)break;
        root=insert(root,value);
    }
    int target;
    scanf("%d",&target);
    if(search(root,target))
        printf("%d is found in the BST\n",target);
    else
        printf("%d is not found in the BST\n",target);
    return 0;
}

```

Status : Correct

Marks : 10/10

4. Problem Statement

Joseph, a computer science student, is interested in understanding binary search trees (BST) and their node arrangements. He wants to create a program to explore BSTs by inserting elements into a tree and displaying the nodes using post-order traversal of the tree.

Write a program to help Joseph implement the program.

Input Format

The first line of input consists of an integer N, representing the number of elements to insert into the BST.

The second line consists of N space-separated integers data, which is the data to be inserted into the BST.

Output Format

The output prints N space-separated integer values after the post-order traversal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
10 15 5 3

Output: 3 5 15 10

Answer

```
// You are using GCC
#include<stdio.h>
#include<stdlib.h>
struct Node{
    int data;
    struct Node* left;
    struct Node* right;
};
struct Node* createnode(int data){
    struct Node* newnode=(struct Node*)malloc(sizeof(struct Node));
    newnode->data=data;
```

```

        newnode->left=newnode->right=NULL;
        return newnode;
    }
    struct Node* insert(struct Node* root,int data){
        if(root==NULL)return createnode(data);
        if(data<root->data)
            root->left=insert(root->left,data);
        else if(data>root->data)
            root->right=insert(root->right,data);
        return root;
    }
    void postorder(struct Node* root){
        if(root==NULL)return;
        postorder(root->left);
        postorder(root->right);
        printf("%d ",root->data);
    }
    int main(){
        int n,data;
        struct Node* root=NULL;
        scanf("%d",&n);
        for(int i=0;i<n;i++){
            scanf("%d",&data);
            root=insert(root,data);
        }
        postorder(root);
        return 0;
    }

```

Status : Correct

Marks : 10/10

5. Problem Statement

Arun is exploring operations on binary search trees (BST). He wants to write a program with an unsorted distinct integer array that represents the BST keys and construct a height-balanced BST from it.

After constructing, he wants to perform the following operations that can alter the structure of the tree and traverse them using a level-order traversal:

InsertionDeletion

Your task is to assist Arun in completing the program without any errors.

Input Format

The first line of input consists of an integer N, representing the number of initial keys in the BST.

The second line consists of N space-separated integers, representing the initial keys.

The third line consists of an integer X, representing the new key to be inserted into the BST.

The fourth line consists of an integer Y, representing the key to be deleted from the BST.

Output Format

The first line of output prints "Initial BST: " followed by a space-separated list of keys in the initial BST after constructing it in level order traversal.

The second line prints "BST after inserting a new node X: " followed by a space-separated list of keys in the BST after inserting X n level order traversal.

The third line prints "BST after deleting node Y: " followed by a space-separated list of keys in the BST after deleting Y n level order traversal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
25 14 56 28 12
34
12

Output: Initial BST: 25 14 56 12 28
BST after inserting a new node 34: 25 14 56 12 28 34
BST after deleting node 12: 25 14 56 28 34

Answer

```

// You are using GCC
#include<stdio.h>
#include<stdlib.h>
struct Treenode{
    int data;
    struct Treenode* left;
    struct Treenode* right;
};
struct Queue{
    struct Treenode* data[100];
    int front; int rear;
};
void enqueue(struct Queue* q,struct Treenode* node){
    q->data[q->rear++]=node;
}
struct Treenode* dequeue(struct Queue* q){
    return q->data[q->front++];
}
int isempty(struct Queue* q){
    return q->front==q->rear;
}
struct Treenode* createnode(int key){
    struct Treenode* newnode=(struct Treenode*)malloc(sizeof(struct Treenode));
    newnode->data=key;
    newnode->left=newnode->right=NULL;
    return newnode;
}
struct Treenode* insert(struct Treenode* root,int key){
    if(root==NULL)return createnode(key);
    if(key<root->data)
        root->left=insert(root->left,key);
    else if(key>root->data)
        root->right=insert(root->right,key);
    return root;
}
struct Treenode* findmin(struct Treenode* node){
    while(node->left!=NULL)
        node=node->left;
    return node;
}
struct Treenode* deletenode(struct Treenode* root,int key){
    if(root==NULL)return NULL;

```



```

if(key<root->data)
    root->left=deletenode(root->left,key);
else if(key>root->data)
    root->right=deletenode(root->right,key);
else{
    if(root->left==NULL){
        struct Treenode* temp=root->right;
        free(root);
        return temp;
    }
    else if(root->right==NULL){
        struct Treenode* temp=root->left;
        free(root);
        return temp;
    }
    struct Treenode* temp=findmin(root->right);
    root->data=temp->data;
    root->right=deletenode(root->right,temp->data);
}
return root;
}

void levelorder(struct Treenode* root){
    if(root==NULL)return;
    struct Queue q;
    q.front=q.rear=0;
    enqueue(&q,root);
    while(!isempty(&q)){
        struct Treenode* node=dequeue(&q);
        printf("%d ",node->data);
        if(node->left)enqueue(&q,node->left);
        if(node->right)enqueue(&q,node->right);
    }
    printf("\n");
}

int main(){
    int N,X,Y;
    scanf("%d",&N);
    int val;
    struct Treenode* root=NULL;
    for(int i=0;i<N;i++){
        scanf("%d",&val);
        root=insert(root,val);
    }
}

```

```
}
scanf("%d",&X);
scanf("%d",&Y);
printf("Initial BST: ");
levelorder(root);
root=insert(root,X);
printf("BST after inserting a new node %d: ",X);
levelorder(root);
root=deletenode(root,Y);
printf("BST after deleting node %d: ",Y);
levelorder(root);
return 0;
}
```

Status : Correct

Marks : 10/10