Adjusted stats of	Index with cover		Index without cover		Index and factory dongle		Index and dongle with heatsink mod		Index and dongle with added fan mod		Only factory dongle		Only dongle with heatsink mod		Safe area
start room temp	01,3°C	22,0°C	00,4°C	22,0°C	00,2°C	22,0°C	-00,1°C	22,0°C	01,0°C	22,0°C	00,4°C	22,0°C	01,0°C	22,0°C	
start temp		28,7°C		31,0°C		52,5°C		50,7°C		40,4°C			35,9°C		35,0°C	
end temp		52,5°C		42,4°C		67,7°C		66,1°C		54,8°C			37,5°C		37,1°C	
idle / off temp	28,7°C		31,0°C		52,5°C		50,7°C		40,4°C		35,9°C		35,0°C		
room humidity	52%	52%	48%	48%	51%	51%	48%	48%	51%	51%	51%	51%	53%	53%	

Frunk temperature after / **Dongle temperature after**

	Index with cover		Index without cover		Index and factory dongle		Index and dongle with heatsink mod		Index and dongle with added fan mod		Only factory dongle		Only dongle with heatsink mod		Safe area
0 min		28,7°C		31,0°C		52,5°C		50,7°C		40,4°C			35,9°C		35,0°C	60,0°C
5 min		39,5°C		36,9°C		58,9°C		56,7°C		44,7°C			35,7°C		35,6°C	60,0°C
10 min		44,6°C		40,1°C		63,0°C		59,6°C		49,7°C			36,0°C		35,8°C	60,0°C
15 min		47,9°C		41,0°C		65,9°C		61,5°C		51,9°C			36,8°C		36,2°C	60,0°C
20 min		50,1°C		41,6°C		67,7°C		62,7°C		53,7°C			37,3°C		36,6°C	60,0°C
25 min		51,5°C		41,9°C		68,4°C		63,7°C		53,8°C			37,3°C		37,2°C	60,0°C
30 min		52,5°C		42,4°C		67,7°C		64,1°C		54,6°C			37,5°C		37,1°C	60,0°C

Room temperature after

	Index with cover		Index without cover		Index and factory dongle		Index and dongle with heatsink mod		Index and dongle with added fan mod		Only factory dongle		Only dongle with heatsink mod	
0 min	-	22,0°C	-	22,0°C	-	22,0°C	-	22,0°C	-	22,0°C	-	22,0°C	-	22,0°C
5 min	-00,5°C	22,5°C	-00,2°C	22,2°C	00,1°C	21,9°C	00,1°C	21,9°C	-00,1°C	22,1°C	00,0°C	22,0°C	-00,4°C	22,4°C
10 min	-00,7°C	22,7°C	-00,4°C	22,4°C	00,1°C	21,9°C	00,1°C	21,9°C	00,0°C	22,0°C	-00,1°C	22,1°C	-00,7°C	22,7°C
15 min	-01,1°C	23,1°C	-00,5°C	22,5°C	-00,1°C	22,1°C	00,1°C	21,9°C	00,1°C	21,9°C	-00,1°C	22,1°C	-00,8°C	22,8°C
20 min	-01,3°C	23,3°C	-00,6°C	22,6°C	00,0°C	22,0°C	00,1°C	21,9°C	00,2°C	21,8°C	-00,1°C	22,1°C	-00,9°C	22,9°C
25 min	-01,4°C	23,4°C	-00,6°C	22,6°C	00,0°C	22,0°C	00,1°C	21,9°C	-00,2°C	22,2°C	-00,1°C	22,1°C	-01,0°C	23,0°C
30 min	-01,6°C	23,6°C	-00,6°C	22,6°C	00,0°C	22,0°C	00,1°C	21,9°C	-00,2°C	22,2°C	-00,1°C	22,1°C	-01,1°C	23,1°C

Room humidity after (can be neglected if humidity is equal or greater than 48%, or equal or less than 85%)

	Index with cover	Index without cover	Index and factory dongle	Index and dongle with heatsink mod	Index and dongle with added fan mod	Only dongle with heatsink mod
0 min	52%	48%	51%	48%	51%	53%
5 min	52%	49%	51%	51%	52%	53%
10 min	52%	50%	52%	51%	52%	52%
15 min	52%	50%	52%	51%	52%	52%
20 min	52%	50%	52%	51%	52%	52%
25 min	52%	50%	52%	51%	54%	52%
30 min	52%	50%	52%	51%	53%	52%

Flir hotspot temperature of

	Index and factory dongle	Index and dongle with heatsink mod			Only factory dongle	Only dongle with heatsink mod	Safe area
dongle idle	55,0°C	50,1°C	hmd front idle	32,4°C	dongle idle 47,4°C	42,4°C	
dongle in use	65,9°C	57,6°C	hmd front in use	40,1°C	dongle in use 48,9°C	42,9°C	
frunk	58,9°C (Index with cover)	50,6°C (Index without cover)					70,0°C

Average temperature of

	Index with cover	Index without cover	Index and factory dongle	Index and dongle with heatsink mod	Index and dongle with added fan mod	Only factory dongle	Only dongle with heatsink mod	Safe area
room	22,9°C	22,4°C	22,0°C	21,9°C	22,0°C	22,1°C	22,7°C	
frunk	45,0°C	39,3°C	63,4°C	59,9°C	49,8°C	dongle 36,6°C	36,2°C	65,0°C

Average humidity of

	Index with cover	Index without cover	Index and factory dongle	Index and dongle with heatsink mod	Index and dongle with added fan mod	Only dongle with heatsink mod
room	52%	50%	52%	51%	52%	52%

Frunk temperature after

	Index and dongle with heatsink mod	Index and dongle with added fan mod	Safe area
35 min	64,5°C	55,0°C	60,0°C
40 min	64,9°C	54,6°C	60,0°C
45 min	65,1°C	54,4°C	60,0°C
50 min	65,5°C	54,4°C	60,0°C
55 min	65,7°C	54,5°C	60,0°C
60 min	65,8°C	54,6°C	60,0°C
65 min	66,1°C	54,8°C	60,0°C

Room temperature after

	Index and dongle with heatsink mod		Index and dongle with added fan mod	
35 min	-	22,0°C	-	22,1°C
40 min	-00,1°C	22,1°C	-00,4°C	22,4°C
45 min	-00,1°C	22,1°C	-00,6°C	22,6°C
50 min	00,0°C	22,0°C	-00,8°C	22,8°C
55 min	00,0°C	22,0°C	-01,0°C	23,0°C
60 min	00,1°C	21,9°C	-01,1°C	23,1°C
65 min	00,1°C	21,9°C	-01,4°C	23,4°C

Room humidity after

	Index and dongle with heatsink mod	Index and dongle with added fan mod
35 min	52%	52%
40 min	52%	52%
45 min	52%	52%
50 min	52%	52%
55 min	52%	52%
60 min	52%	52%
65 min	52%	52%

Flir hotspot temperature of

	Index and dongle with heatsink mod			Safe area
dongle after 65 min	59,4°C	hmd after 65 min	40,3°C	70,0°C

Average temperature of

	Index and dongle with heatsink mod	Index and dongle with added fan mod	Safe area
room	22,0°C	22,4°C	
frunk	62,6°C	52,2°C	65,0°C

Average humidity of

	Index and dongle with heatsink mod	Index and dongle with added fan mod
room	51%	52%

Created dd/mm/yyyy: 26/01/2022

Temperature curves over the measurement time of 0 to 30 minutes

Legend: Index with cover — Index without cover — Index and factory dongle — Index and dongle with heatsink mod — Index and dongle with added fan mod — Only factory dongle — Only dongle with heatsink mod — Safe usage area

	0 min	5 min	10 min	15 min	20 min	25 min	30 min
Index with cover	28,7°C	39,5°C	44,6°C	47,9°C	50,1°C	51,5°C	52,5°C
Index without cover	31,0°C	36,9°C	40,1°C	41,0°C	41,6°C	41,9°C	42,4°C
Index and factory dongle	52,5°C	58,9°C	63,0°C	65,9°C	67,7°C	68,4°C	67,7°C
Index and dongle with heatsink mod	50,7°C	56,7°C	59,6°C	61,5°C	62,7°C	63,7°C	64,1°C
Index and dongle with added fan mod	40,4°C	44,7°C	49,7°C	51,9°C	53,7°C	53,8°C	54,6°C
Only factory dongle	35,9°C	35,7°C	36,0°C	36,8°C	37,3°C	37,3°C	37,5°C
Only dongle with heatsink mod	35,0°C	35,6°C	35,8°C	36,2°C	36,6°C	37,2°C	37,1°C
Safe usage area	60,0°C	60,0°C	60,0°C	60,0°C	60,0°C	60,0°C	60,0°C

Temperature curves over the measurement time of 30 to 65 minutes

Legend: Index and dongle with heatsink mod — Index and dongle with added fan mod — Safe usage area

	35 min	40 min	45 min	50 min	55 min	60 min	65 min
Index and dongle with heatsink mod	64,5°C	64,9°C	65,1°C	65,5°C	65,7°C	65,8°C	66,1°C
Index and dongle with added fan mod	55,0°C	54,6°C	54,4°C	54,4°C	54,5°C	54,6°C	54,8°C
Safe usage area	60,0°C	60,0°C	60,0°C	60,0°C	60,0°C	60,0°C	60,0°C