

Powervault P5 Data Sheet



Model shown is 15 kWh

Powervault P5: the fully integrated hybrid, all in one, solar and storage unit	
Hybrid Inverter (kW)	3.6 kW or 6 kW
Battery capacity (kWh)	5 kWh, 10 kWh, 15 kWh, 20 kWh
Colour	Grey or white with customisable LED display
Emergency Power	Optional critical circuit / whole house backup with the Powervault Gateway

E&OE. Edition 12/2024
PV0DLF02139D04

P5 Datasheet

Choice of Hybrid Inverter		G98	G99
Hybrid Inverter	Nominal AC Power	3.68 kW	6 kW
	Max. DC power input from PV	5.4 kW	9 kW
	Rated grid voltage (range)	230 (176 to 270) Volts	
	Max. DC Voltage from PV	540V	
	PV Start input voltage	100V	
	Nominal PV DC operating voltage	360V	
	No. of MPP trackers / strings per MPPT	2 / 1	
	PV DC operating voltage range	120V-540V	
	PV DC operating voltage range per MPPT	120V-540V	
	Max. DC short circuit current per MPPT	24A	
	AC maximum current	16A	27.3A
Conformance	Grid standards	G98, G100	G99, G100 G98 (16A AC limit)
	Conformity	UKCA, CE, EMC, ETSI EN 303 345	
	Protections	DC reverse polarity protection, Insulation resistance monitoring, Ground fault monitoring, Over current / voltage, Battery soft start, Temperature derating and protection.	

Choice of Battery Capacity		5 kWh	10 kWh	15 kWh	20 kWh
Battery storage	Nominal DC capacity	5.12 kWh	10.24 kWh	15.36 kWh	20.48 kWh
	Usable AC capacity ¹	4 kWh	8 kWh	12 kWh	16 kWh
	Max input power (3.6kW inverter) ²	2.8 kW	3.6 kW		
	Max output power(3.6kW inverter) ²	2.3 kW	3.4 kW		
	Max input power (6kW inverter) ²	2.8 kW	5.6 kW		
	Max output power (6kW inverter) ²	2.3 kW	4.8 kW		
	Warranty cycles	Unlimited cycles: please refer to the Powervault warranty			
	State of health at end of warranty	70%			
	Depth of discharge	95%			
Physical parameters	Dimensions (mm: w x h x d)	640x955x210	640x1,330x210	640x1,755x210	640x2,180x210
	Mounting	Floor standing on a flat load bearing surface with wall support required			
	Total weight: battery + inverter	90kg	140kg	190kg	235kg
Installation requirements	Optimal ambient temperature	0°-35° ambient			
	Relative Humidity	40%-60% relative humidity			
	Rating	IP65 supports indoor or outdoor installation			
	Location constraints	In accordance with PAS63100			
	Protections	VOC sniffer device (indoor install), fire suppression pack per battery module. Over / under temperature, over current			

Notes

Values accurate to +/- 5%. ¹ Values provided for 25°C. Capacity at new. Capacity declines over life and with usage to state of health at end of warranty. Capacity and power output may vary dependant on local installation conditions. ² Subject to confirmation post-launch. Power output and input also varies dependent on state of charge, temperature and grid voltage. Charging power reduced below 15°C. Charging and discharging power reduced (de-rated) at high temperature. All values are subject to Powervault's Warranty Terms and General Terms & Conditions of Sale being met. Errors and Omissions Excepted.