MPEG-4 Video Compression

A newer standard than MPEG-2. Besides compression, great attention is paid to issues about **user interactivity**.

We look at key ideas here.

- Object based coding: offers higher compression ratio, also beneficial for digital video composition, manipulation, indexing and retrieval.
- Synthetic object coding: supports 2D mesh object coding, face object coding and animation, body object coding and animation.
- MPEG-4 Part 10/H.264: new techniques for improved compression efficiency.



Multimedia CM0340


509





Object based coding (1)

Composition and manipulation of MPEG-4 videos.





Multimedia CM0340

510







Back

Object based coding (2)

Compared with MPEG-2, MPEG-4 is an entirely new standard for

- Composing media objects to create desirable audiovisual scenes.
- Multiplexing and synchronising the bitstreams for these media data entities so that they can be transmitted with guaranteed Quality of Service (QoS).
- Interacting with the audiovisual scene at the receiving end.

MPEG-4 provides a set of advanced coding modules and algorithms for audio and video compressions.

We have discussed MPEG-4 Structured Audio and we will focus on video here.



Multimedia CM0340










Object based coding (3)

The hierarchical structure of MPEG-4 visual bitstreams is very different from that of MPEG-2: it is very much video object-oriented:





Multimedia CM0340

512







Object based coding (4)

- Video-object Sequence (VS): delivers the complete MPEG4 visual scene; may contain 2D/3D natural or synthetic objects.
- Video Object (VO): a particular object in the scene, which can be of arbitrary (non-rectangular) shape corresponding to an object or background of the scene.
- Video Object Layer (VOL): facilitates a way to support (multi-layered) scalable coding. A VO can have multiple VOLs under scalable (multi-bitrate) coding, or have a single VOL under non-scalable coding.
- Group of Video Object Planes (GOV): groups of video object planes together (optional level).
- Video Object Plane (VOP): a snapshot of a VO at a particular moment.



Multimedia CM0340



VOP-based vs. Frame-based Coding

- MPEG-1 and MPEG-2 do not support the VOP concert; their coding method is frame-based (also known as block-based).
- For block-based coding, it is possible that multiple potential matches yield small prediction errors. Some may not coincide with the real motion.
- For VOP-based coding, each VOP is of arbitrary shape and ideally will obtain a unique motion vector consistent with the actual object motion.

See the example in the next page:




Multimedia CM0340

514





VOP-based vs. Frame-based Coding





Multimedia CM0340

515









VOP-based Coding

- MPEG-4 VOP-based coding also employs Motion Compensation technique:
 - I-VOPs: Intra-frame coded VOPs.
 - P-VOPs: Inter-frame coded VOPs if only forward prediction is employed.
 - B-VOPs: Inter-frame coded VOPs if bi-directional predictions are employed.
- The new difficulty for VOPs: may have arbitrary shapes. Shape information must be coded in addition to the texture (luminance or chroma) of the VOP.



Multimedia CM0340

516







VOP-based Motion Compensation (MC)

- MC-based VOP coding in MPEG-4 again involves three steps:
 - 1. Motion Estimation
 - 2. MC-based Prediction
 - 3. Coding of the Prediction Error
- ullet Only pixels within the VOP of the current (target) VOP are considered for matching in MC. To facilitate MC, each VOP is divided into macroblocks with 16×16 luminance and 8×8 chrominance images.



Multimedia CM0340

517





Back

VOP-based Motion Compensation (MC)

- Let C(x+k,y+l) be pixels of the MB in target in target VOP, and R(x+i+k,y+j+l) be pixels of the MB in Reference VOP.
- A Sum of Absolute Difference (SAD) for measuring the difference between the two MBs can be defined as:

 $N-1 \ N-1$

$$SAD(i,j) = \sum_{k=0}^{\infty} \sum_{l=0}^{\infty} |C(x+k,y+l) - R(x+i+k,y+j+l)| \cdot Map(x+k,y+l).$$

N — the size of the MB Map(p,q)=1 when C(p,q) is a pixel within the target VOP otherwise Map(p,q)=0.

• The vector (i, j) that yields the minimum SAD is adopted as the motion vector (u, v).



Multimedia CM0340

518





Coding of Texture and Shape

- Texture Coding (luminance and chrominance):
 - I-VOP: the gray values of the pixels in each MB of the VOP are directly coded using DCT followed by VLC (Variable Length Coding), such as Huffman or Arithmetic Coding.
 - P-VOP/B-VOP: MC-based coding is employed the prediction error is coded similar to I-VOP.
 - Boundary MBs need appropriate treatment. May also use improved Shape Adaptive DCT.



Multimedia CM0340

519





Coding of Texture and Shape (cont.)

- Shape Coding (shape of the VOPs)
 - Binary shape information: in the form of a binary map. A value '1' (opaque) or '0' (transparent) in the bitmap indicates whether the pixel is inside or outside the VOP.
 - Greyscale shape information: value refers to the transparency of the shape ranging from 0 (completely transparent) and 255 (opaque).
 - Specific encoding algorithms are designed to code in both cases.



Multimedia CM0340

520








Synthetic Object Coding: 2D Mesh

- 2D Mesh Object: a tessellation (or partition) of a 2D planar region using polygonal patches.
- Mesh based texture mapping can be used for 2D object animation.















Synthetic Object Coding: 3D Model

- MPEG-4 has defined special 3D models for face objects and body objects because of the frequent appearances of human faces and bodies in videos.
- Some of the potential applications: teleconferecing, human-computer interfaces, games and e-commerce.
- MPEG-4 goes beyond wireframes so that the surfaces of the face or body objects can be shaded or texture-mapped.



Multimedia CM0340

522






Synthetic Object Coding: Face Object

Face Object Coding and Animation

- MPEG-4 adopted a generic default face model, developed by VRML Consortium.
- Face Animation Parameters (FAPs) can be specified to achieve desirable animation.
- Face Definition Parameters (FDPs): feature points better describe individual faces.













Back



MPEG-4 Part 10/H.264

- Improved video coding techniques, identical standards: ISO MPEG-4 Part 10 (Advanced Video Coding / AVC) and ITU-T H.264.
- Preliminary studies using software based on this new standard suggests that H.264 offers up to 30-50% better compression than MPEG-2 and up to 30% over H.263+ and MPEG-4 advanced simple profile.
- H.264 is currently one of the leading candidates to carry High Definition TV (HDTV) video content on many applications, e.g. Blu-ray.
- Involves various technical improvements. We mainly look at improved inter-frame encoding.



Multimedia CM0340


524



Back

MPEG-4 AVC: Flexible Block Partition

Macroblock in MPEG-2 uses 16×16 luminance values. MPEG-4 AVC uses a tree-structured motion segmentation down to 4×4 block sizes (16×16 , 16×8 , 8×16 , 8×8 , 8×4 , 4×8 , 4×4). This allows much more accurate motion compensation of moving objects.





Multimedia CM0340










MPEG-4 AVC: Up to Quarter-Pixel Resolution Motion Compensation

Motion vectors can be up to half-pixel or quarter-pixel accuracy. Pixels at quarter-pixel position are obtained by bilinear interpolation.

• Improves the possibility of finding a block in the reference frame that better matches the target block.






Multimedia CM0340

526

MPEG-4 AVC: Multiple References

- Multiple references to motion estimation. Allows finding the best reference in 2 possible buffers (past pictures and future pictures) each contains up to 16 frames.
- Block prediction is done by a weighted sum of blocks from the reference picture. It allows enhanced picture quality in scenes where there are changes of plane, zoom, or when new objects are revealed.





Multimedia CM0340

527







Further Reading

- Overview of the MPEG-4 Standard
- The H.264/MPEG4 AVC Standard and its Applications



Multimedia CM0340











